Blender Index

Release 2.56.3 - UNSTABLE API

Blender Foundation

March 14, 2011

CONTENTS

1 Application Modules **3**
- 1.1 Context Access (bpy.context) . . . 3
- 1.2 Data Access (bpy.data) . . . 7
- 1.3 Operators (bpy.ops) . . . 8
- 1.4 Types (bpy.types) . . . 142
- 1.5 Utilities (bpy.utils) . . . 1029
- 1.6 Path Utilities (bpy.path) . . . 1030
- 1.7 Application Data (bpy.app) . . . 1031
- 1.8 Property Definitions (bpy.props) . . . 1032

2 Standalone Modules **1039**
- 2.1 Math Types & Utilities (mathutils) . . . 1039
- 2.2 Geometry Utilities (mathutils.geometry) . . . 1068
- 2.3 Font Drawing (blf) . . . 1071
- 2.4 Audio System (aud) . . . 1073

3 Game Engine Modules **1083**
- 3.1 Game Engine bge.types Module . . . 1083
- 3.2 Game Engine bge.logic Module . . . 1155
- 3.3 Game Engine bge.render Module . . . 1169
- 3.4 Game Engine bge.events module . . . 1172

Python Module Index **1177**

Index **1179**

This document is an API reference for Blender 2.56.3. built Unknown.

An introduction to Blender and Python can be found at Quickstart Intro,
For a more general explanation of blender/python see the API Overview

A PDF version of this document is also available

Warning: The Python API in Blender is **UNSTABLE**, It should only be used for testing, any script written now may break in future releases.
The following areas are subject to change.

- operator names and arguments
- render api
- function calls with the data api (any function calls with values accessed from bpy.data), including functions for importing and exporting meshes
- class registration (Operator, Panels, Menus, Headers)
- modules: bpy.props, blf)
- members in the bpy.context have to be reviewed
- python defined modal operators, especially drawing callbacks are highly experemental

These parts of the API are relatively stable and are unlikely to change significantly

- data API, access to attributes of blender data such as mesh verts, material color, timeline frames and scene objects
- user interface functions for defining buttons, creation of menus, headers, panels
- modules: bgl and mathutils
- game engine modules

CHAPTER

ONE

APPLICATION MODULES

1.1 Context Access (bpy.context)

The context members available depend on the area of blender which is currently being accessed.

Note that all context values are readonly, but may be modified through the data api or by running operators

1.1.1 Screen Context

bpy.context.**scene**

Type bpy.types.Scene

bpy.context.**visible_objects**

Type sequence of bpy.types.Object

bpy.context.**visible_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**selectable_objects**

Type sequence of bpy.types.Object

bpy.context.**selectable_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**selected_objects**

Type sequence of bpy.types.Object

bpy.context.**selected_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**selected_editable_objects**

Type sequence of bpy.types.Object

bpy.context.**selected_editable_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**visible_bones**

Type sequence of bpy.types.Object

bpy.context.**editable_bones**

Type sequence of bpy.types.EditBone

bpy.context.**selected_bones**

Type sequence of bpy.types.Bone

bpy.context.**selected_editable_bones**

Type sequence of bpy.types.Bone

bpy.context.**visible_pose_bones**

Type sequence of bpy.types.PoseBone

bpy.context.**selected_pose_bones**

Type sequence of bpy.types.PoseBone

bpy.context.**active_bone**

Type bpy.types.Bone

bpy.context.**active_pose_bone**

Type bpy.types.PoseBone

bpy.context.**active_base**

Type bpy.types.ObjectBase

bpy.context.**active_object**

Type bpy.types.Object

bpy.context.**object**

Type bpy.types.Object

bpy.context.**edit_object**

Type bpy.types.Object

bpy.context.**sculpt_object**

Type bpy.types.Object

bpy.context.**vertex_paint_object**

Type bpy.types.Object

bpy.context.**weight_paint_object**

Type bpy.types.Object

bpy.context.**texture_paint_object**

Type bpy.types.Object

bpy.context.**particle_edit_object**

Type bpy.types.Object

bpy.context.**sequences**

Type sequence of bpy.types.Sequence

bpy.context.**selected_sequences**

Type sequence of bpy.types.Sequence

bpy.context.**selected_editable_sequences**

Type sequence of bpy.types.Sequence

1.1.2 View3D Context

bpy.context.**selected_objects**

Type sequence of bpy.types.Object

bpy.context.**selected_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**selected_editable_objects**

Type sequence of bpy.types.Object

bpy.context.**selected_editable_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**visible_objects**

Type sequence of bpy.types.Object

bpy.context.**visible_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**selectable_objects**

Type sequence of bpy.types.Object

bpy.context.**selectable_bases**

Type sequence of bpy.types.ObjectBase

bpy.context.**active_base**

Type bpy.types.ObjectBase

bpy.context.**active_object**

Type bpy.types.Object

1.1.3 Buttons Context

bpy.context.**world**

Type bpy.types.World

bpy.context.**object**

Type bpy.types.Object

bpy.context.**mesh**

Type bpy.types.Mesh

bpy.context.**armature**

Type bpy.types.Armature

bpy.context.**lattice**

Type bpy.types.Lattice

bpy.context.**curve**

Type bpy.types.Curve

bpy.context.**meta_ball**

Type bpy.types.MetaBall

bpy.context.**lamp**

Type bpy.types.Lamp

bpy.context.**camera**

Type bpy.types.Camera

bpy.context.**material**

Type bpy.types.Material

bpy.context.**material_slot**

Type bpy.types.MaterialSlot

bpy.context.**texture**

Type bpy.types.Texture

bpy.context.**texture_slot**

Type bpy.types.MaterialTextureSlot

bpy.context.**bone**

Type bpy.types.Bone

bpy.context.**edit_bone**

Type bpy.types.EditBone

bpy.context.**pose_bone**

Type bpy.types.PoseBone

bpy.context.**particle_system**

Type bpy.types.ParticleSystem

bpy.context.**particle_system_editable**

Type bpy.types.ParticleSystem

bpy.context.**cloth**

Type bpy.types.ClothModifier

bpy.context.**soft_body**

Type bpy.types.SoftBodyModifier

bpy.context.**fluid**

Type bpy.types.FluidSimulationModifier

bpy.context.**smoke**

Type bpy.types.SmokeModifier

bpy.context.**collision**

Type bpy.types.CollisionModifier

bpy.context.**brush**

Type bpy.types.Brush

1.1.4 Image Context

bpy.context.**edit_image**

Type bpy.types.Image

1.1.5 Node Context

bpy.context.**selected_nodes**

Type sequence of bpy.types.Node

1.1.6 Text Context

bpy.context.**edit_text**

Type bpy.types.Text

1.2 Data Access (bpy.data)

This module is used for all blender/python access.

bpy.**data**

Access to blenders internal data

Type bpy.types.BlendData

```
import bpy


# print all objects
for obj in bpy.data.objects:
    print(obj.name)


# print all scene names in a list
print(bpy.data.scenes.keys())


# remove mesh Cube
if "Cube" in bpy.data.meshes:
    mesh = bpy.data.meshes["Cube"]
    print("removing mesh", mesh)
    bpy.data.meshes.unlink(mesh)


# write images into a file next to the blend
import os
file = open(os.path.splitext(bpy.data.filepath)[0] + ".txt", 'w')

for image in bpy.data.images:
    file.write("%s %dx%d\n" % (image.filepath, image.size[0], image.size[1]))
```

```
file.close()
```

1.3 Operators (bpy.ops)

1.3.1 Calling Operators

Provides python access to calling operators, this includes operators written in C, Python or Macros.

Only keyword arguments can be used to pass operator properties.

Operators don't have return values as you might expect, instead they return a set() which is made up of: {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}. Common return values are {'FINISHED'} and {'CANCELLED'}.

Calling an operator in the wrong context will raise a RuntimeError, there is a poll() method to avoid this problem.

Note that the operator ID (bl_idname) in this example is 'mesh.subdivide', 'bpy.ops' is just the access path for python.

```
import bpy

# calling an operator
bpy.ops.mesh.subdivide(number_cuts=3, smoothness=0.5)


# check poll() to avoid exception.
if bpy.ops.object.mode_set.poll():
    bpy.ops.object.mode_set(mode='EDIT')
```

1.3.2 Execution Context

When calling an operator you may want to pass the execution context.

This determines the context thats given to the operator to run in, and weather invoke() is called or execute().

'EXEC_DEFAULT' is used by default but you may want the operator to take user interaction with 'INVOKE_DEFAULT'.

The execution context is as a non keyword, string argument in: ('INVOKE_DEFAULT', 'INVOKE_REGION_WIN', 'INVOKE_REGION_CHANNELS', 'INVOKE_REGION_PREVIEW', 'INVOKE_AREA', 'INVOKE_SCREEN', 'EXEC_DEFAULT', 'EXEC_REGION_WIN', 'EXEC_REGION_CHANNELS', 'EXEC_REGION_PREVIEW', 'EXEC_AREA', 'EXEC_SCREEN')

```
# group add popup
import bpy
bpy.ops.object.group_instance_add('INVOKE_DEFAULT')
```

Action Operators

`bpy.ops.action.`**`clean`**(*threshold=0.001*)

Simplify F-Curves by removing closely spaced keyframes

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold

`bpy.ops.action.`**`clickselect`**(*extend=False*, *column=False*)

Select keyframes by clicking on them

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **column** (*boolean, (optional)*) – Column Select

`bpy.ops.action.copy()`
Copy selected keyframes to the copy/paste buffer

`bpy.ops.action.delete()`
Remove all selected keyframes

`bpy.ops.action.duplicate(mode=17)`
Make a copy of all selected keyframes

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.action.duplicate_move(ACTION_OT_duplicate=None, TRANSFORM_OT_transform=None)`
Undocumented (contribute)

Parameters

- **ACTION_OT_duplicate** (`ACTION_OT_duplicate`, (optional)) – Duplicate Keyframes, Make a copy of all selected keyframes
- **TRANSFORM_OT_transform** (`TRANSFORM_OT_transform`, (optional)) – Transform, Transform selected items by mode type

`bpy.ops.action.extrapolation_type(type='CONSTANT')`
Set extrapolation mode for selected F-Curves

Parameters **type** (*enum in ['CONSTANT', 'LINEAR'], (optional)*) – Type

`bpy.ops.action.frame_jump()`
Set the current frame to the average frame of the selected keyframes

`bpy.ops.action.handle_type(type='FREE')`
Set type of handle for selected keyframes

Parameters **type** (*enum in ['FREE', 'VECTOR', 'ALIGNED', 'AUTO', 'ANIM_CLAMPED'], (optional)*) – Type

`bpy.ops.action.interpolation_type(type='CONSTANT')`
Set interpolation mode for the F-Curve segments starting from the selected keyframes

Parameters **type** (*enum in ['CONSTANT', 'LINEAR', 'BEZIER'], (optional)*) – Type

`bpy.ops.action.keyframe_insert(type='ALL')`
Insert keyframes for the specified channels

Parameters **type** (*enum in ['ALL', 'SEL', 'GROUP'], (optional)*) – Type

`bpy.ops.action.keyframe_type(type='KEYFRAME')`
Set type of keyframe for the seleced keyframes

Parameters **type** (*enum in ['KEYFRAME', 'BREAKDOWN', 'EXTREME', 'JITTER'], (optional)*) – Type

`bpy.ops.action.markers_make_local()`
Move selected scene markers to the active Action as local 'pose' markers

`bpy.ops.action.mirror(type='CFRA')`
Flip selected keyframes over the selected mirror line

Parameters **type** (*enum in ['CFRA', 'XAXIS', 'MARKER'], (optional)*) – Type

`bpy.ops.action.new()`
Create new action

`bpy.ops.action.paste(offset='START', merge='MIX')`
Paste keyframes from copy/paste buffer for the selected channels, starting on the current frame

Parameters

- **offset** (*enum in ['START', 'END', 'RELATIVE', 'NONE'], (optional)*) – Offset, Paste time offset of keys
- **merge** (*enum in ['MIX', 'OVER_ALL', 'OVER_RANGE', 'OVER_RANGE_ALL'], (optional)*) – Type, Method of merking pasted keys and existing

`bpy.ops.action.previewrange_set()`
Set Preview Range based on extents of selected Keyframes

`bpy.ops.action.sample()`
Add keyframes on every frame between the selected keyframes

`bpy.ops.action.select_all_toggle(invert=False)`
Toggle selection of all keyframes

Parameters **invert** (*boolean, (optional)*) – Invert

`bpy.ops.action.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, axis_range=False)`
Select all keyframes within the specified region

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **axis_range** (*boolean, (optional)*) – Axis Range

`bpy.ops.action.select_column(mode='KEYS')`
Select all keyframes on the specified frame(s)

Parameters **mode** (*enum in ['KEYS', 'CFRA', 'MARKERS_COLUMN', 'MARKERS_BETWEEN'], (optional)*) – Mode

`bpy.ops.action.select_leftright(mode='CHECK', extend=False)`
Select keyframes to the left or the right of the current frame

Parameters

- **mode** (*enum in ['CHECK', 'LEFT', 'RIGHT'], (optional)*) – Mode
- **extend** (*boolean, (optional)*) – Extend Select

`bpy.ops.action.select_less()`
Deselect keyframes on ends of selection islands

`bpy.ops.action.select_linked()`
Select keyframes occurring the same F-Curves as selected ones

`bpy.ops.action.select_more()`
Select keyframes beside already selected ones

`bpy.ops.action.snap(type='CFRA')`
Snap selected keyframes to the times specified

Parameters **type** (*enum in ['CFRA', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER'], (optional)*) – Type

`bpy.ops.action.view_all()`
Reset viewable area to show full keyframe range

Anim Operators

`bpy.ops.anim.change_frame(frame=0)`
Interactively change the current frame number

Parameters **frame** (*int in [-300000, 300000], (optional)*) – Frame

`bpy.ops.anim.channels_click(extend=False, children_only=False)`
Handle mouse-clicks over animation channels

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **children_only** (*boolean, (optional)*) – Select Children Only

`bpy.ops.anim.channels_collapse(all=True)`
Collapse (i.e. close) all selected expandable animation channels

Parameters **all** (*boolean, (optional)*) – All, Collapse all channels (not just selected ones)

`bpy.ops.anim.channels_delete()`
Delete all selected animation channels

`bpy.ops.anim.channels_editable_toggle(mode='TOGGLE', type='PROTECT')`
Toggle editability of selected channels

Parameters

- **mode** (*enum in ['TOGGLE', 'DISABLE', 'ENABLE', 'INVERT'], (optional)*) – Mode
- **type** (*enum in ['PROTECT', 'MUTE'], (optional)*) – Type

`bpy.ops.anim.channels_expand(all=True)`
Expand (i.e. open) all selected expandable animation channels

Parameters **all** (*boolean, (optional)*) – All, Expand all channels (not just selected ones)

`bpy.ops.anim.channels_fcurves_enable()`
Clears 'disabled' tag from all F-Curves to get broken F-Curves working again

`bpy.ops.anim.channels_move(direction='DOWN')`
Rearrange selected animation channels

Parameters **direction** (*enum in ['TOP', 'UP', 'DOWN', 'BOTTOM'], (optional)*) – Direction

`bpy.ops.anim.channels_select_all_toggle(invert=False)`
Toggle selection of all animation channels

Parameters **invert** (*boolean, (optional)*) – Invert

`bpy.ops.anim.channels_select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Select all animation channels within the specified region

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.anim.channels_setting_disable`(*mode='DISABLE'*, *type='PROTECT'*)
Disable specified setting on all selected animation channels

Parameters

- **mode** (*enum in ['TOGGLE', 'DISABLE', 'ENABLE', 'INVERT'], (optional)*) – Mode
- **type** (*enum in ['PROTECT', 'MUTE'], (optional)*) – Type

`bpy.ops.anim.channels_setting_enable`(*mode='ENABLE'*, *type='PROTECT'*)
Enable specified setting on all selected animation channels

Parameters

- **mode** (*enum in ['TOGGLE', 'DISABLE', 'ENABLE', 'INVERT'], (optional)*) – Mode
- **type** (*enum in ['PROTECT', 'MUTE'], (optional)*) – Type

`bpy.ops.anim.channels_setting_toggle`(*mode='INVERT'*, *type='PROTECT'*)
Invert specified setting on all selected animation channels

Parameters

- **mode** (*enum in ['TOGGLE', 'DISABLE', 'ENABLE', 'INVERT'], (optional)*) – Mode
- **type** (*enum in ['PROTECT', 'MUTE'], (optional)*) – Type

`bpy.ops.anim.channels_visibility_set`()
Make only the selected animation channels visible in the Graph Editor

`bpy.ops.anim.channels_visibility_toggle`()
Toggle visibility in Graph Editor of all selected animation channels

`bpy.ops.anim.copy_driver_button`()
Copy the driver for the highlighted button

`bpy.ops.anim.driver_button_add`(*all=True*)
Add driver(s) for the property(s) connected represented by the highlighted button

Parameters **all** (*boolean, (optional)*) – All, Create drivers for all elements of the array.

`bpy.ops.anim.driver_button_remove`(*all=True*)
Remove the driver(s) for the property(s) connected represented by the highlighted button

Parameters **all** (*boolean, (optional)*) – All, Delete drivers for all elements of the array.

`bpy.ops.anim.keyframe_delete`(*type='DEFAULT'*, *confirm_success=True*)
Delete keyframes on the current frame for all properties in the specified Keying Set

Parameters

- **type** (*enum in ['DEFAULT'], (optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean, (optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added

`bpy.ops.anim.keyframe_delete_button`(*all=True*)
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Delete keyfames from all elements of the array.

`bpy.ops.anim.keyframe_delete_v3d()`
Undocumented (contribute)

`bpy.ops.anim.keyframe_insert(type='DEFAULT', confirm_success=True)`
Insert keyframes on the current frame for all properties in the specified Keying Set

Parameters

- **type** (*enum in ['DEFAULT'], (optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean, (optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added

`bpy.ops.anim.keyframe_insert_button(all=True)`
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Insert a keyframe for all element of the array.

`bpy.ops.anim.keyframe_insert_menu(type='DEFAULT', confirm_success=False, always_prompt=False)`
Insert Keyframes for specified Keying Set, with menu of available Keying Sets if undefined

Parameters

- **type** (*enum in ['DEFAULT'], (optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean, (optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added
- **always_prompt** (*boolean, (optional)*) – Always Show Menu

`bpy.ops.anim.keying_set_active_set(type=0)`
Undocumented (contribute)

Parameters **type** (*int in [-inf, inf], (optional)*) – Keying Set Number, Index (determined internally) of the Keying Set to use

`bpy.ops.anim.keying_set_add()`
Add a new (empty) Keying Set to the active Scene

`bpy.ops.anim.keying_set_export(filepath="", filter_folder=True, filter_text=True, filter_python=True)`
Export Keying Set to a python script.

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath to write file to.
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_text** (*boolean, (optional)*) – Filter text
- **filter_python** (*boolean, (optional)*) – Filter python

File ui/properties_scene.py:211

`bpy.ops.anim.keying_set_path_add()`
Add empty path to active Keying Set

`bpy.ops.anim.keying_set_path_remove()`
Remove active Path from active Keying Set

`bpy.ops.anim.keying_set_remove()`
Remove the active Keying Set

`bpy.ops.anim.keyingset_button_add(all=True)`
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Add all elements of the array to a Keying Set.

`bpy.ops.anim.keyingset_button_remove()`
Undocumented (contribute)

`bpy.ops.anim.paste_driver_button()`
Paste the driver in the copy/paste buffer for the highlighted button

`bpy.ops.anim.previewrange_clear()`
Clear Preview Range

`bpy.ops.anim.previewrange_set(xmin=0, xmax=0, ymin=0, ymax=0)`
Interactively define frame range used for playback

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.anim.time_toggle()`
Toggle whether timing is displayed in frames or seconds for active timeline view

`bpy.ops.anim.update_data_paths()`
Update data paths from 2.53 to edited data paths of drivers and fcurves

File op/animsys_update.py:693

Armature Operators

`bpy.ops.armature.align()`
Align selected bones to the active bone (or to their parent)

`bpy.ops.armature.armature_layers(layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)`
Change the visible armature layers

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers to make visible

`bpy.ops.armature.autoside_names(type='XAXIS')`
Automatically renames the selected bones according to which side of the target axis they fall on

Parameters **type** (*enum in ['XAXIS', 'YAXIS', 'ZAXIS'], (optional)*) – Axis, Axis tag names with.

`bpy.ops.armature.bone_layers(layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)`
Change the layers that the selected bones belong to

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers that bone belongs to

`bpy.ops.armature.bone_primitive_add(name="Bone")`
Add a new bone located at the 3D-Cursor

Parameters **name** (*string, (optional)*) – Name, Name of the newly created bone

`bpy.ops.armature.calculate_roll`(*type='X', axis_flip=False, axis_only=False*)
Automatically fix alignment of select bones' axes

Parameters

- **type** (*enum in ['X', 'Y', 'Z', 'ACTIVE', 'VIEW', 'CURSOR'], (optional)*) – Type
- **axis_flip** (*boolean, (optional)*) – Flip Axis, Negate the alignment axis.
- **axis_only** (*boolean, (optional)*) – Shortest Rotation, Ignore the axis direction, use the shortest rotation to align.

`bpy.ops.armature.click_extrude`()
Create a new bone going from the last selected joint to the mouse position

`bpy.ops.armature.delete`()
Remove selected bones from the armature

`bpy.ops.armature.duplicate`()
Make copies of the selected bones within the same armature

`bpy.ops.armature.duplicate_move`(*ARMATURE_OT_duplicate=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **ARMATURE_OT_duplicate** (`ARMATURE_OT_duplicate`, (optional)) – Duplicate Selected Bone(s), Make copies of the selected bones within the same armature
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.armature.extrude`(*forked=False*)
Create new bones from the selected joints

Parameters **forked** (*boolean, (optional)*) – Forked

`bpy.ops.armature.extrude_forked`(*ARMATURE_OT_extrude=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **ARMATURE_OT_extrude** (`ARMATURE_OT_extrude`, (optional)) – Extrude, Create new bones from the selected joints
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.armature.extrude_move`(*ARMATURE_OT_extrude=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **ARMATURE_OT_extrude** (`ARMATURE_OT_extrude`, (optional)) – Extrude, Create new bones from the selected joints
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.armature.fill`()
Add bone between selected joint(s) and/or 3D-Cursor

`bpy.ops.armature.flags_set`(*type='DRAWWIRE'*, *mode='CLEAR'*)
Set flags for armature bones

Parameters

- **type** (*enum in ['DRAWWIRE', 'DEFORM', 'MULT_VG', 'HINGE', 'NO_SCALE', 'LOCKED'], (optional)*) – Type
- **mode** (*enum in ['CLEAR', 'ENABLE', 'TOGGLE'], (optional)*) – Mode

`bpy.ops.armature.flip_names`()
Flips (and corrects) the axis suffixes of the names of selected bones

`bpy.ops.armature.hide`(*unselected=False*)
Tag selected bones to not be visible in Edit Mode

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

`bpy.ops.armature.layers_show_all`(*all=True*)
Make all armature layers visible

Parameters **all** (*boolean, (optional)*) – All Layers, Enable all layers or just the first 16 (top row)

`bpy.ops.armature.merge`(*type='WITHIN_CHAIN'*)
Merge continuous chains of selected bones

Parameters **type** (*enum in ['WITHIN_CHAIN'], (optional)*) – Type

`bpy.ops.armature.parent_clear`(*type='CLEAR'*)
Remove the parent-child relationship between selected bones and their parents

Parameters **type** (*enum in ['CLEAR', 'DISCONNECT'], (optional)*) – ClearType, What way to clear parenting

`bpy.ops.armature.parent_set`(*type='CONNECTED'*)
Set the active bone as the parent of the selected bones

Parameters **type** (*enum in ['CONNECTED', 'OFFSET'], (optional)*) – ParentType, Type of parenting

`bpy.ops.armature.reveal`()
Unhide all bones that have been tagged to be hidden in Edit Mode

`bpy.ops.armature.select_all`(*action='TOGGLE'*)
Toggle selection status of all bones

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.armature.select_hierarchy`(*direction='PARENT'*, *extend=False*)
Select immediate parent/children of selected bones

Parameters

- **direction** (*enum in ['PARENT', 'CHILD'], (optional)*) – Direction
- **extend** (*boolean, (optional)*) – Add to Selection

`bpy.ops.armature.select_inverse`()
Flip the selection status of bones (selected -> unselected, unselected -> selected)

`bpy.ops.armature.select_linked`(*extend=False*)
Select bones related to selected ones by parent/child relationships

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.armature.**separate**()
Isolate selected bones into a separate armature

bpy.ops.armature.**subdivide**(*number_cuts=1*)
Break selected bones into chains of smaller bones

Parameters **number_cuts** (*int in [1, inf], (optional)*) – Number of Cuts

bpy.ops.armature.**switch_direction**()
Change the direction that a chain of bones points in (head <-> tail swap)

Boid Operators

bpy.ops.boid.**rule_add**(*type='GOAL'*)
Add a boid rule to the current boid state

Parameters **type** (*enum in ['GOAL', 'AVOID', 'AVOID_COLLISION', 'SEPARATE', 'FLOCK', 'FOLLOW_LEADER', 'AVERAGE_SPEED', 'FIGHT'], (optional)*) – Type

bpy.ops.boid.**rule_del**()
Undocumented (contribute)

bpy.ops.boid.**rule_move_down**()
Move boid rule down in the list

bpy.ops.boid.**rule_move_up**()
Move boid rule up in the list

bpy.ops.boid.**state_add**()
Add a boid state to the particle system

bpy.ops.boid.**state_del**()
Undocumented (contribute)

bpy.ops.boid.**state_move_down**()
Move boid state down in the list

bpy.ops.boid.**state_move_up**()
Move boid state up in the list

Brush Operators

bpy.ops.brush.**add**()
Add brush by mode type

bpy.ops.brush.**curve_preset**(*shape='SMOOTH'*)
Set brush shape

Parameters **shape** (*enum in ['SHARP', 'SMOOTH', 'MAX', 'LINE', 'ROUND', 'ROOT'], (optional)*) – Mode

bpy.ops.brush.**reset**()
Return brush to defaults based on current tool

bpy.ops.brush.**scale_size**(*scalar=1.0*)
Change brush size by a scalar

Parameters **scalar** (*float in [0, 2], (optional)*) – Scalar, Factor to scale brush size by

bpy.ops.brush.**set_active_number**(*mode=""*, *number=0*)
Set active sculpt/paint brush from it's number

Parameters

- **mode** (*string, (optional)*) – mode, Paint mode to set brush for
- **number** (*int in [-inf, inf], (optional)*) – number, Brush number

File op/wm.py:92

Buttons Operators

`bpy.ops.buttons.`**`file_browse`**(*filepath=""*, *filter_blender=False*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=False*, *filemode=9*, *relative_path=False*)

Open a file browser, Hold Shift to open the file, Alt to browse containing directory

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

`bpy.ops.buttons.`**`toolbox`**()

Display button panel toolbox

Cloth Operators

`bpy.ops.cloth.`**`preset_add`**(*name=""*, *remove_active=False*)

Add a Cloth Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

Console Operators

`bpy.ops.console.autocomplete()`
Evaluate the namespace up until the cursor and give a list of options or complete the name if there is only one

File ui/space_console.py:108

`bpy.ops.console.banner()`
Print a message whem the terminal initializes

File ui/space_console.py:125

`bpy.ops.console.clear(scrollback=True, history=False)`
Clear text by type

Parameters

- **scrollback** (*boolean, (optional)*) – Scrollback, Clear the scrollback history
- **history** (*boolean, (optional)*) – History, Clear the command history

`bpy.ops.console.copy()`
Copy selected text to clipboard

`bpy.ops.console.delete(type='NEXT_CHARACTER')`
Delete text by cursor position

Parameters **type** (*enum in ['NEXT_CHARACTER', 'PREVIOUS_CHARACTER'], (optional)*) – Type, Which part of the text to delete.

`bpy.ops.console.execute()`
Execute the current console line as a python expression

File ui/space_console.py:90

`bpy.ops.console.history_append(text="", current_character=0, remove_duplicates=False)`
Append history at cursor position

Parameters

- **text** (*string, (optional)*) – Text, Text to insert at the cursor position.
- **current_character** (*int in [0, inf], (optional)*) – Cursor, The index of the cursor.
- **remove_duplicates** (*boolean, (optional)*) – Remove Duplicates, Remove duplicate items in the history

`bpy.ops.console.history_cycle(reverse=False)`
Cycle through history

Parameters **reverse** (*boolean, (optional)*) – Reverse, reverse cycle history

`bpy.ops.console.insert(text="")`
Insert text at cursor position

Parameters **text** (*string, (optional)*) – Text, Text to insert at the cursor position.

`bpy.ops.console.language(language="")`
Set the current language for this console

Parameters **language** (*string, (optional)*) – Language

File ui/space_console.py:148

`bpy.ops.console.move(type='LINE_BEGIN')`
Move cursor position

Parameters type (*enum in ['LINE_BEGIN', 'LINE_END', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD'], (optional)*) – Type, Where to move cursor to.

`bpy.ops.console.paste()`
Paste text from clipboard

`bpy.ops.console.scrollback_append(text="", type='OUTPUT')`
Append scrollback text by type

Parameters

- **text** (*string, (optional)*) – Text, Text to insert at the cursor position.
- **type** (*enum in ['OUTPUT', 'INPUT', 'INFO', 'ERROR'], (optional)*) – Type, Console output type.

`bpy.ops.console.select_set()`
Set the console selection

Constraint Operators

`bpy.ops.constraint.childof_clear_inverse(constraint="", owner='OBJECT')`
Clear inverse correction for ChildOf constraint

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

`bpy.ops.constraint.childof_set_inverse(constraint="", owner='OBJECT')`
Set inverse correction for ChildOf constraint

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

`bpy.ops.constraint.delete()`
Remove constraint from constraint stack

`bpy.ops.constraint.limitdistance_reset(constraint="", owner='OBJECT')`
Reset limiting distance for Limit Distance Constraint

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

`bpy.ops.constraint.move_down(constraint="", owner='OBJECT')`
Move constraint down in constraint stack

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

`bpy.ops.constraint.move_up(constraint="", owner='OBJECT')`
Move constraint up in constraint stack

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

`bpy.ops.constraint.stretchto_reset(constraint="", owner='OBJECT')`
Reset original length of bone for Stretch To Constraint

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

Curve Operators

`bpy.ops.curve.cyclic_toggle(direction='CYCLIC_U')`
Undocumented (contribute)

Parameters **direction** (*enum in ['CYCLIC_U', 'CYCLIC_V'], (optional)*) – Direction, Direction to make surface cyclic in.

`bpy.ops.curve.de_select_first()`
Undocumented (contribute)

`bpy.ops.curve.de_select_last()`
Undocumented (contribute)

`bpy.ops.curve.delete(type='SELECTED')`
Undocumented (contribute)

Parameters **type** (*enum in ['SELECTED', 'SEGMENT', 'ALL'], (optional)*) – Type, Which elements to delete.

`bpy.ops.curve.duplicate(mode=1)`
Undocumented (contribute)

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.curve.extrude(mode=1)`
Undocumented (contribute)

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.curve.handle_type_set(type='AUTOMATIC')`
Undocumented (contribute)

Parameters **type** (*enum in ['AUTOMATIC', 'VECTOR', 'ALIGNED', 'FREE_ALIGN', 'TOGGLE_FREE_ALIGN'], (optional)*) – Type, Spline type

`bpy.ops.curve.hide(unselected=False)`
Undocumented (contribute)

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

`bpy.ops.curve.make_segment()`
Undocumented (contribute)

`bpy.ops.curve.primitive_bezier_circle_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Construct a Bezier Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.curve.`**`primitive_bezier_curve_add`**(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Bezier Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.curve.`**`primitive_nurbs_circle_add`**(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.curve.`**`primitive_nurbs_curve_add`**(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.curve.primitive_nurbs_path_add`(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Path

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.curve.radius_set`(*radius=1.0*)

Set per-point radius which is used for bevel tapering

Parameters **radius** (*float in [0, inf], (optional)*) – Radius

`bpy.ops.curve.reveal`()

Undocumented (contribute)

`bpy.ops.curve.select_all`(*action='TOGGLE'*)

Undocumented (contribute)

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.curve.select_inverse`()

Undocumented (contribute)

`bpy.ops.curve.select_less`()

Undocumented (contribute)

`bpy.ops.curve.select_linked`()

Undocumented (contribute)

`bpy.ops.curve.select_linked_pick`(*deselect=False*)

Undocumented (contribute)

Parameters **deselect** (*boolean, (optional)*) – Deselect, Deselect linked control points rather than selecting them.

`bpy.ops.curve.select_more()`
Undocumented (contribute)

`bpy.ops.curve.select_next()`
Undocumented (contribute)

`bpy.ops.curve.select_nth(nth=2)`
Undocumented (contribute)

Parameters **nth** (*int in [2, 100], (optional)*) – Nth Selection

`bpy.ops.curve.select_previous()`
Undocumented (contribute)

`bpy.ops.curve.select_random(percent=50.0, extend=False)`
Undocumented (contribute)

Parameters

- **percent** (*float in [0, 100], (optional)*) – Percent, Percentage of elements to select randomly.
- **extend** (*boolean, (optional)*) – Extend Selection, Extend selection instead of deselecting everything first.

`bpy.ops.curve.select_row()`
Undocumented (contribute)

`bpy.ops.curve.separate()`
Undocumented (contribute)

`bpy.ops.curve.shade_flat()`
Undocumented (contribute)

`bpy.ops.curve.shade_smooth()`
Undocumented (contribute)

`bpy.ops.curve.smooth()`
Flatten angles of selected points

`bpy.ops.curve.smooth_radius()`
Flatten radiuses of selected points

`bpy.ops.curve.spin(center=(0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0))`
Undocumented (contribute)

Parameters

- **center** (*float array of 3 items in [-inf, inf], (optional)*) – Center, Center in global view space
- **axis** (*float array of 3 items in [-1, 1], (optional)*) – Axis, Axis in global view space

`bpy.ops.curve.spline_type_set(type='POLY')`
Undocumented (contribute)

Parameters **type** (*enum in ['POLY', 'BEZIER', 'NURBS'], (optional)*) – Type, Spline type

`bpy.ops.curve.spline_weight_set(weight=1.0)`
Set softbody goal weight for selected points

Parameters **weight** (*float in [0, 1], (optional)*) – Weight

`bpy.ops.curve.subdivide(number_cuts=1)`
Subdivide selected segments

Parameters **number_cuts** (*int in [1, inf], (optional)*) – Number of cuts

`bpy.ops.curve.switch_direction()`
Switch direction of selected splines

`bpy.ops.curve.tilt_clear()`
Undocumented (contribute)

`bpy.ops.curve.vertex_add(location=(0.0, 0.0, 0.0))`
Undocumented (contribute)

Parameters **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location to add new vertex at.

Ed Operators

`bpy.ops.ed.redo()`
Redo previous action

`bpy.ops.ed.undo()`
Undo previous action

`bpy.ops.ed.undo_push(message="Add an undo step *function may be moved*")`
Add an undo state (internal use only)

Parameters **message** (*string, (optional)*) – Undo Message

Export Anim Operators

`bpy.ops.export_anim.bvh(filepath="", check_existing=True, filter_glob="*.bvh", global_scale=1.0, frame_start=0, frame_end=0)`
Save a BVH motion capture file from an armature

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **global_scale** (*float in [0.0001, 1e+06], (optional)*) – Scale, Scale the BVH by this value
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Starting frame to export
- **frame_end** (*int in [-inf, inf], (optional)*) – End Frame, End frame to export

File addons/io_anim_bvh/__init__.py:107

Export Mesh Operators

`bpy.ops.export_mesh.ply(filepath="", check_existing=True, filter_glob="*.ply", use_modifiers=True, use_normals=True, use_uv_coords=True, use_colors=True)`
Export a single object as a stanford PLY with normals, colours and texture coordinates.

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files

- **use_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply Modifiers to the exported mesh
- **use_normals** (*boolean, (optional)*) – Normals, Export Normals for smooth and hard shaded faces
- **use_uv_coords** (*boolean, (optional)*) – UVs, Exort the active UV layer
- **use_colors** (*boolean, (optional)*) – Vertex Colors, Exort the active vertex color layer

File addons/io_mesh_ply/__init__.py:93

`bpy.ops.export_mesh.stl`(*filepath=""*, *check_existing=True*, *ascii=False*, *apply_modifiers=True*)

Save STL triangle mesh data from the active object

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **ascii** (*boolean, (optional)*) – Ascii, Save the file in ASCII file format
- **apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply the modifiers before saving

File addons/io_mesh_stl/__init__.py:117

Export Scene Operators

`bpy.ops.export_scene.autodesk_3ds`(*filepath=""*, *check_existing=True*, *filter_glob="*.3ds"*, *use_selection=False*)

Export to 3DS file format (.3ds)

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only

File addons/io_scene_3ds/__init__.py:74

`bpy.ops.export_scene.fbx`(*filepath=""*, *check_existing=True*, *filter_glob="*.fbx"*, *use_selection=True*, *TX_SCALE=1.0*, *TX_XROT90=True*, *TX_YROT90=False*, *TX_ZROT90=False*, *EXP_EMPTY=True*, *EXP_CAMERA=True*, *EXP_LAMP=True*, *EXP_ARMATURE=True*, *EXP_MESH=True*, *EXP_MESH_APPLY_MOD=True*, *EXP_IMAGE_COPY=False*, *ANIM_ENABLE=True*, *ANIM_OPTIMIZE=True*, *ANIM_OPTIMIZE_PRECISSION=6.0*, *ANIM_ACTION_ALL=False*, *batch_mode='OFF'*, *BATCH_OWN_DIR=True*, *use_metadata=True*)

Selection to an ASCII Autodesk FBX

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files

- **use_selection** (*boolean, (optional)*) – Selected Objects, Export selected objects on visible layers
- **TX_SCALE** (*float in [0.01, 1000], (optional)*) – Scale, Scale all data, (Note! some imports dont support scaled armatures)
- **TX_XROT90** (*boolean, (optional)*) – Rot X90, Rotate all objects 90 degrees about the X axis
- **TX_YROT90** (*boolean, (optional)*) – Rot Y90, Rotate all objects 90 degrees about the Y axis
- **TX_ZROT90** (*boolean, (optional)*) – Rot Z90, Rotate all objects 90 degrees about the Z axis
- **EXP_EMPTY** (*boolean, (optional)*) – Empties, Export empty objects
- **EXP_CAMERA** (*boolean, (optional)*) – Cameras, Export camera objects
- **EXP_LAMP** (*boolean, (optional)*) – Lamps, Export lamp objects
- **EXP_ARMATURE** (*boolean, (optional)*) – Armatures, Export armature objects
- **EXP_MESH** (*boolean, (optional)*) – Meshes, Export mesh objects
- **EXP_MESH_APPLY_MOD** (*boolean, (optional)*) – Modifiers, Apply modifiers to mesh objects
- **EXP_IMAGE_COPY** (*boolean, (optional)*) – Copy Image Files, Copy image files to the destination path
- **ANIM_ENABLE** (*boolean, (optional)*) – Enable Animation, Export keyframe animation
- **ANIM_OPTIMIZE** (*boolean, (optional)*) – Optimize Keyframes, Remove double keyframes
- **ANIM_OPTIMIZE_PRECISSION** (*float in [1, 16], (optional)*) – Precision, Tolerence for comparing double keyframes (higher for greater accuracy)
- **ANIM_ACTION_ALL** (*boolean, (optional)*) – All Actions, Use all actions for armatures, if false, use current action
- **batch_mode** (*enum in ['OFF', 'SCENE', 'GROUP'], (optional)*) – Batch Mode
- **BATCH_OWN_DIR** (*boolean, (optional)*) – Own Dir, Create a dir for each exported file
- **use_metadata** (*boolean, (optional)*) – Use Metadata

File addons/io_scene_fbx/__init__.py:94

`bpy.ops.export_scene.obj`(*filepath=""*, *check_existing=True*, *filter_glob="*.obj;*.mtl"*, *use_selection=False*, *use_all_scenes=False*, *use_animation=False*, *use_apply_modifiers=True*, *use_rotate_x90=True*, *use_edges=True*, *use_normals=False*, *use_hq_normals=True*, *use_uvs=True*, *use_materials=True*, *copy_images=False*, *use_triangles=False*, *use_vertex_groups=False*, *use_nurbs=False*, *use_blen_objects=True*, *group_by_object=False*, *group_by_material=False*, *keep_vertex_order=False*)

Save a Wavefront OBJ File

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files

- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only
- **use_all_scenes** (*boolean, (optional)*) – All Scenes
- **use_animation** (*boolean, (optional)*) – Animation
- **use_apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply modifiers (preview resolution)
- **use_rotate_x90** (*boolean, (optional)*) – Rotate X90
- **use_edges** (*boolean, (optional)*) – Edges
- **use_normals** (*boolean, (optional)*) – Normals
- **use_hq_normals** (*boolean, (optional)*) – High Quality Normals
- **use_uvs** (*boolean, (optional)*) – UVs
- **use_materials** (*boolean, (optional)*) – Materials
- **copy_images** (*boolean, (optional)*) – Copy Images
- **use_triangles** (*boolean, (optional)*) – Triangulate
- **use_vertex_groups** (*boolean, (optional)*) – Polygroups
- **use_nurbs** (*boolean, (optional)*) – Nurbs
- **use_blen_objects** (*boolean, (optional)*) – Objects as OBJ Objects
- **group_by_object** (*boolean, (optional)*) – Objects as OBJ Groups
- **group_by_material** (*boolean, (optional)*) – Material Groups
- **keep_vertex_order** (*boolean, (optional)*) – Keep Vertex Order

File addons/io_scene_obj/__init__.py:114

`bpy.ops.export_scene.x3d`(*filepath=""*, *check_existing=True*, *filter_glob="*.x3d"*, *use_selection=False*, *use_apply_modifiers=True*, *use_triangulate=False*, *use_compress=False*)

Export selection to Extensible 3D file (.x3d)

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only
- **use_apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Use transformed mesh data from each object
- **use_triangulate** (*boolean, (optional)*) – Triangulate, Triangulate quads.
- **use_compress** (*boolean, (optional)*) – Compress, GZip the resulting file, requires a full python install

File addons/io_scene_x3d/__init__.py:73

File Operators

`bpy.ops.file.bookmark_add()`
Add a bookmark for the selected/active directory

`bpy.ops.file.bookmark_toggle()`
Toggle bookmarks display

`bpy.ops.file.cancel()`
Cancel loading of selected file

`bpy.ops.file.delete()`
Delete selected file

`bpy.ops.file.delete_bookmark(index=-1)`
Delete selected bookmark

Parameters **index** (*int in [-1, 20000], (optional)*) – Index

`bpy.ops.file.directory()`
Enter a directory name

`bpy.ops.file.directory_new(directory="")`
Create a new directory

Parameters **directory** (*string, (optional)*) – Directory, Name of new directory

`bpy.ops.file.execute(need_active=False)`
Execute selected file

Parameters **need_active** (*boolean, (optional)*) – Need Active, Only execute if there's an active selected file in the file list.

`bpy.ops.file.filenum(increment=1)`
Increment number in filename

Parameters **increment** (*int in [0, 100], (optional)*) – Increment

`bpy.ops.file.find_missing_files(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=9)`
Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders

- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

`bpy.ops.file.hidedot()`
Toggle hide hidden dot files

`bpy.ops.file.highlight()`
Highlight selected file(s)

`bpy.ops.file.make_paths_absolute()`
Undocumented (contribute)

`bpy.ops.file.make_paths_relative()`
Undocumented (contribute)

`bpy.ops.file.next()`
Move to next folder

`bpy.ops.file.pack_all()`
Undocumented (contribute)

`bpy.ops.file.parent()`
Move to parent directory

`bpy.ops.file.previous()`
Move to previous folder

`bpy.ops.file.refresh()`
Refresh the file list

`bpy.ops.file.rename()`
Rename file or file directory

`bpy.ops.file.report_missing_files()`
Undocumented (contribute)

`bpy.ops.file.select(extend=False, fill=False)`
Activate/select file

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **fill** (*boolean, (optional)*) – Fill, Select everything beginning with the last selection.

`bpy.ops.file.select_all_toggle()`
Select/deselect all files

`bpy.ops.file.select_bookmark(dir="")`
Select a bookmarked directory

Parameters **dir** (*string, (optional)*) – Dir

`bpy.ops.file.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Activate/select the file(s) contained in the border

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min

- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.file.smoothscroll()`
Smooth scroll to make editable file visible.

`bpy.ops.file.unpack_all(method='USE_LOCAL')`
Undocumented (contribute)

Parameters method (*enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL', 'KEEP', 'ASK'], (optional)*) – Method, How to unpack.

Fluid Operators

`bpy.ops.fluid.bake()`
Bake fluid simulation

Font Operators

`bpy.ops.font.buffer_paste()`
Paste text from OS buffer

`bpy.ops.font.case_set(case='LOWER')`
Set font case

Parameters case (*enum in ['LOWER', 'UPPER'], (optional)*) – Case, Lower or upper case.

`bpy.ops.font.case_toggle()`
Toggle font case

`bpy.ops.font.change_character(delta=1)`
Change font character code

Parameters delta (*int in [-255, 255], (optional)*) – Delta, Number to increase or decrease character code with.

`bpy.ops.font.change_spacing(delta=1)`
Change font spacing

Parameters delta (*int in [-20, 20], (optional)*) – Delta, Amount to decrease or increasing character spacing with.

`bpy.ops.font.delete(type='ALL')`
Delete text by cursor position

Parameters type (*enum in ['ALL', 'NEXT_CHARACTER', 'PREVIOUS_CHARACTER', 'SELECTION', 'NEXT_OR_SELECTION', 'PREVIOUS_OR_SELECTION'], (optional)*) – Type, Which part of the text to delete.

`bpy.ops.font.file_paste(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9)`
Paste contents from file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files

- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

`bpy.ops.font.insert_lorem()`

Insert placeholder text

`bpy.ops.font.line_break(ctrl=False)`

Insert line break at cursor position

Parameters **ctrl** (*boolean, (optional)*) – Ctrl

`bpy.ops.font.move(type='LINE_BEGIN')`

Move cursor to position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], (optional)*) – Type, Where to move cursor to.

`bpy.ops.font.move_select(type='LINE_BEGIN')`

Make selection from current cursor position to new cursor position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], (optional)*) – Type, Where to move cursor to, to make a selection.

`bpy.ops.font.open(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=True, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)`

Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files

- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

`bpy.ops.font.style_set`(*style='BOLD'*, *clear=False*)
Set font style

Parameters

- **style** (*enum in ['BOLD', 'ITALIC', 'UNDERLINE', 'SMALL_CAPS'], (optional)*) – Style, Style to set selection to.
- **clear** (*boolean, (optional)*) – Clear, Clear style rather than setting it.

`bpy.ops.font.style_toggle`(*style='BOLD'*)
Toggle font style

Parameters **style** (*enum in ['BOLD', 'ITALIC', 'UNDERLINE', 'SMALL_CAPS'], (optional)*) – Style, Style to set selection to.

`bpy.ops.font.text_copy`()
Copy selected text to clipboard

`bpy.ops.font.text_cut`()
Cut selected text to clipboard

`bpy.ops.font.text_insert`(*text=""*, *accent=False*)
Insert text at cursor position

Parameters

- **text** (*string, (optional)*) – Text, Text to insert at the cursor position.
- **accent** (*boolean, (optional)*) – Accent mode, Next typed character will strike through previous, for special character input.

`bpy.ops.font.text_paste`()
Paste text from clipboard

`bpy.ops.font.textbox_add`()
Add a new text box

`bpy.ops.font.textbox_remove`(*index=0*)
Remove the textbox

Parameters **index** (*int in [0, inf], (optional)*) – Index, The current text box.

`bpy.ops.font.unlink`()
Unlink active font data block

Gpencil Operators

`bpy.ops.gpencil.active_frame_delete`()
Delete the active frame for the active Grease Pencil datablock

`bpy.ops.gpencil.convert`(*type='PATH'*)
Convert the active Grease Pencil layer to a new Object

Parameters **type** (*enum in ['PATH', 'CURVE'], (optional)*) – Type

`bpy.ops.gpencil.data_add()`
Add new Grease Pencil datablock

`bpy.ops.gpencil.data_unlink()`
Unlink active Grease Pencil datablock

`bpy.ops.gpencil.draw(mode='DRAW', stroke=None)`
Make annotations on the active data

Parameters

- **mode** (*enum in ['DRAW', 'DRAW_STRAIGHT', 'ERASER'], (optional)*) – Mode, Way to intepret mouse movements.
- **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke

`bpy.ops.gpencil.layer_add()`
Add new Grease Pencil layer for the active Grease Pencil datablock

Graph Operators

`bpy.ops.graph.bake()`
Bake selected F-Curves to a set of sampled points defining a similar curve

`bpy.ops.graph.clean(threshold=0.001)`
Simplify F-Curves by removing closely spaced keyframes

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold

`bpy.ops.graph.click_insert(frame=1.0, value=1.0)`
Insert new keyframe at the cursor position for the active F-Curve

Parameters

- **frame** (*float in [-inf, inf], (optional)*) – Frame Number, Frame to insert keyframe on
- **value** (*float in [-inf, inf], (optional)*) – Value, Value for keyframe on

`bpy.ops.graph.clickselect(extend=False, column=False, curves=False)`
Select keyframes by clicking on them

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **column** (*boolean, (optional)*) – Column Select, Select all keyframes that occur on the same frame as the one under the mouse
- **curves** (*boolean, (optional)*) – Only Curves, Select all the keyframes in the curve

`bpy.ops.graph.copy()`
Copy selected keyframes to the copy/paste buffer

`bpy.ops.graph.cursor_set(frame=0, value=0.0)`
Interactively set the current frame number and value cursor

Parameters

- **frame** (*int in [-300000, 300000], (optional)*) – Frame
- **value** (*float in [1.17549e-38, inf], (optional)*) – Value

`bpy.ops.graph.delete()`
Remove all selected keyframes

`bpy.ops.graph.duplicate(mode=1)`
Make a copy of all selected keyframes

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.graph.duplicate_move(GRAPH_OT_duplicate=None, TRANSFORM_OT_transform=None)`
Undocumented (contribute)

Parameters

- **GRAPH_OT_duplicate** (`GRAPH_OT_duplicate`, (optional)) – Duplicate Keyframes, Make a copy of all selected keyframes
- **TRANSFORM_OT_transform** (`TRANSFORM_OT_transform`, (optional)) – Transform, Transform selected items by mode type

`bpy.ops.graph.euler_filter()`
Fixes the most common causes of gimbal lock in the fcurves of the active bone

File op/fcurve_euler_filter.py:76

`bpy.ops.graph.extrapolation_type(type='CONSTANT')`
Set extrapolation mode for selected F-Curves

Parameters **type** (*enum in ['CONSTANT', 'LINEAR'], (optional)*) – Type

`bpy.ops.graph.fmodifier_add(type='NULL', only_active=True)`
Add F-Modifiers to the selected F-Curves

Parameters

- **type** (*enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED'], (optional)*) – Type
- **only_active** (*boolean, (optional)*) – Only Active, Only add F-Modifier to active F-Curve.

`bpy.ops.graph.fmodifier_copy()`
Copy the F-Modifier(s) of the active F-Curve.

`bpy.ops.graph.fmodifier_paste()`
Add copied F-Modifiers to the selected F-Curves

`bpy.ops.graph.frame_jump()`
Set the current frame to the average frame of the selected keyframes

`bpy.ops.graph.ghost_curves_clear()`
Clear F-Curve snapshots (Ghosts) for active Graph Editor

`bpy.ops.graph.ghost_curves_create()`
Create snapshot (Ghosts) of selected F-Curves as background aid for active Graph Editor

`bpy.ops.graph.handle_type(type='FREE_ALIGN')`
Set type of handle for selected keyframes

Parameters **type** (*enum in ['AUTO', 'VECTOR', 'ALIGNED', 'FREE_ALIGN', 'ANIM_CLAMPED'], (optional)*) – Type

`bpy.ops.graph.handles_view_toggle()`
Toggle whether handles are drawn on all keyframes that need them

`bpy.ops.graph.interpolation_type(type='CONSTANT')`
Set interpolation mode for the F-Curve segments starting from the selected keyframes

Parameters **type** (*enum in ['CONSTANT', 'LINEAR', 'BEZIER'], (optional)*) – Type

`bpy.ops.graph.`**`keyframe_insert`**(*type='ALL'*)
Insert keyframes for the specified channels

Parameters **type** (*enum in ['ALL', 'SEL'], (optional)*) – Type

`bpy.ops.graph.`**`mirror`**(*type='CFRA'*)
Flip selected keyframes over the selected mirror line

Parameters **type** (*enum in ['CFRA', 'VALUE', 'YAXIS', 'XAXIS', 'MARKER'], (optional)*) – Type

`bpy.ops.graph.`**`paste`**(*offset='START'*, *merge='MIX'*)
Paste keyframes from copy/paste buffer for the selected channels, starting on the current frame

Parameters

- **offset** (*enum in ['START', 'END', 'RELATIVE', 'NONE'], (optional)*) – Offset, Paste time offset of keys
- **merge** (*enum in ['MIX', 'OVER_ALL', 'OVER_RANGE', 'OVER_RANGE_ALL'], (optional)*) – Type, Method of merking pasted keys and existing

`bpy.ops.graph.`**`previewrange_set`**()
Automatically set Preview Range based on range of keyframes

`bpy.ops.graph.`**`properties`**()
Toggle display properties panel

`bpy.ops.graph.`**`sample`**()
Add keyframes on every frame between the selected keyframes

`bpy.ops.graph.`**`select_all_toggle`**(*invert=False*)
Toggle selection of all keyframes

Parameters **invert** (*boolean, (optional)*) – Invert

`bpy.ops.graph.`**`select_border`**(*gesture_mode=0*, *xmin=0*, *xmax=0*, *ymin=0*, *ymax=0*, *axis_range=False*, *include_handles=False*)
Select all keyframes within the specified region

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **axis_range** (*boolean, (optional)*) – Axis Range
- **include_handles** (*boolean, (optional)*) – Include Handles, Are handles tested individually against the selection criteria

`bpy.ops.graph.`**`select_column`**(*mode='KEYS'*)
Select all keyframes on the specified frame(s)

Parameters **mode** (*enum in ['KEYS', 'CFRA', 'MARKERS_COLUMN', 'MARKERS_BETWEEN'], (optional)*) – Mode

`bpy.ops.graph.`**`select_leftright`**(*mode='CHECK'*, *extend=False*)
Select keyframes to the left or the right of the current frame

Parameters

- **mode** (*enum in ['CHECK', 'LEFT', 'RIGHT'], (optional)*) – Mode
- **extend** (*boolean, (optional)*) – Extend Select

`bpy.ops.graph.select_less()`
Deselect keyframes on ends of selection islands

`bpy.ops.graph.select_linked()`
Select keyframes occurring the same F-Curves as selected ones

`bpy.ops.graph.select_more()`
Select keyframes beside already selected ones

`bpy.ops.graph.smooth()`
Apply weighted moving means to make selected F-Curves less bumpy

`bpy.ops.graph.snap(type='CFRA')`
Snap selected keyframes to the chosen times/values

Parameters **type** (*enum in ['CFRA', 'VALUE', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER', 'HORIZONTAL'], (optional)*) – Type

`bpy.ops.graph.sound_bake(filepath="", filter_blender=False, filter_image=False, filter_movie=True, filter_python=False, filter_font=False, filter_sound=True, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, low=0.0, high=100000.0, attack=0.005, release=0.2, threshold=0.0, accumulate=False, use_additive=False, square=False, sthreshold=0.1)`
Bakes a sound wave to selected F-Curves

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **low** (*float in [0, 100000], (optional)*) – Lowest frequency
- **high** (*float in [0, 100000], (optional)*) – Highest frequency
- **attack** (*float in [0, 2], (optional)*) – Attack time
- **release** (*float in [0, 5], (optional)*) – Release time
- **threshold** (*float in [0, 1], (optional)*) – Threshold

- **accumulate** (*boolean, (optional)*) – Accumulate
- **use_additive** (*boolean, (optional)*) – Additive
- **square** (*boolean, (optional)*) – Square
- **sthreshold** (*float in [0, 1], (optional)*) – Square Threshold

`bpy.ops.graph.view_all()`
Reset viewable area to show full keyframe range

Group Operators

`bpy.ops.group.create(name="Group")`
Create an object group from selected objects

Parameters **name** (*string, (optional)*) – Name, Name of the new group

`bpy.ops.group.objects_add_active()`
Add the object to an object group that contains the active object

`bpy.ops.group.objects_remove()`
Remove selected objects from all groups

`bpy.ops.group.objects_remove_active()`
Remove the object from an object group that contains the active object

Help Operators

`bpy.ops.help.operator_cheat_sheet()`
Undocumented (contribute)

File ui/space_info.py:382

Image Operators

`bpy.ops.image.curves_point_set(point='BLACK_POINT')`
Undocumented (contribute)

Parameters **point** (*enum in ['BLACK_POINT', 'WHITE_POINT'], (optional)*) – Point, Set black point or white point for curves.

`bpy.ops.image.cycle_render_slot(reverse=False)`
Undocumented (contribute)

Parameters **reverse** (*boolean, (optional)*) – Cycle in Reverse

`bpy.ops.image.external_edit(filepath="")`
Edit image in an external application

Parameters **filepath** (*string, (optional)*) – File Path, Path to an image file

File op/image.py:57

`bpy.ops.image.invert(invert_r=False, invert_g=False, invert_b=False, invert_a=False)`
Undocumented (contribute)

Parameters

- **invert_r** (*boolean, (optional)*) – Red, Invert Red Channel

- **invert_g** (*boolean, (optional)*) – Green, Invert Green Channel
- **invert_b** (*boolean, (optional)*) – Blue, Invert Blue Channel
- **invert_a** (*boolean, (optional)*) – Alpha, Invert Alpha Channel

`bpy.ops.image.new`(*name="untitled", width=1024, height=1024, color=(0.0, 0.0, 0.0, 1.0), alpha=True, uv_test_grid=False, float=False*)

Undocumented (contribute)

Parameters

- **name** (*string, (optional)*) – Name, Image datablock name.
- **width** (*int in [1, inf], (optional)*) – Width, Image width.
- **height** (*int in [1, inf], (optional)*) – Height, Image height.
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Default fill color.
- **alpha** (*boolean, (optional)*) – Alpha, Create an image with an alpha channel.
- **uv_test_grid** (*boolean, (optional)*) – UV Test Grid, Fill the image with a grid for UV map testing.
- **float** (*boolean, (optional)*) – 32 bit Float, Create image with 32 bit floating point bit depth.

`bpy.ops.image.open`(*filepath="", filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False*)

Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

`bpy.ops.image.pack`(*as_png=False*)

Pack an image as embedded data into the .blend file

Parameters **as_png** (*boolean, (optional)*) – Pack As PNG, Pack image as lossless PNG.

`bpy.ops.image.project_apply`()

Project edited image back onto the object

File op/image.py:177

`bpy.ops.image.project_edit()`
Edit a snapshot if the viewport in an external image editor

File op/image.py:114

`bpy.ops.image.properties()`
Toggle display properties panel

`bpy.ops.image.record_composite()`
Undocumented (contribute)

`bpy.ops.image.reload()`
Undocumented (contribute)

`bpy.ops.image.replace(filepath="", filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)`
Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

`bpy.ops.image.sample()`
Undocumented (contribute)

`bpy.ops.image.sample_line(xstart=0, xend=0, ystart=0, yend=0, cursor=1002)`
Undocumented (contribute)

Parameters

- **xstart** (*int in [-inf, inf], (optional)*) – X Start
- **xend** (*int in [-inf, inf], (optional)*) – X End
- **ystart** (*int in [-inf, inf], (optional)*) – Y Start
- **yend** (*int in [-inf, inf], (optional)*) – Y End

- **cursor** (*int in [0, inf], (optional)*) – Cursor, Mouse cursor style to use during the modal operator

`bpy.ops.image.save()`
Undocumented (contribute)

`bpy.ops.image.save_as(file_type='PNG', filepath="", check_existing=True, filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, copy=False)`
Undocumented (contribute)

Parameters

- **file_type** (*enum in ['TARGA', 'TARGA RAW', 'PNG', 'BMP', 'JPEG', 'IRIS', 'OPENEXR', 'MULTILAYER'], (optional)*) – File Type, File type to save image as.
- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **copy** (*boolean, (optional)*) – Copy, Create a new image file without modifying the current image in blender

`bpy.ops.image.save_dirty()`
Save all modified textures

File op/image.py:91

`bpy.ops.image.save_sequence()`
Undocumented (contribute)

`bpy.ops.image.scopes()`
Toggle display scopes panel

`bpy.ops.image.toolbox()`
Undocumented (contribute)

`bpy.ops.image.unpack(method='USE_LOCAL', id="")`
Save an image packed in the .blend file to disk

Parameters

- **method** (*enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL'], (optional)*) – Method, How to unpack.
- **id** (*string, (optional)*) – Image Name, Image datablock name to unpack.

`bpy.ops.image.view_all()`
Undocumented (contribute)

`bpy.ops.image.view_pan(offset=(0.0, 0.0))`
Undocumented (contribute)

Parameters **offset** (*float array of 2 items in [-inf, inf], (optional)*) – Offset, Offset in floating point units, 1.0 is the width and height of the image.

`bpy.ops.image.view_selected()`
Undocumented (contribute)

`bpy.ops.image.view_zoom(factor=0.0)`
Undocumented (contribute)

Parameters **factor** (*float in [0, inf], (optional)*) – Factor, Zoom factor, values higher than 1.0 zoom in, lower values zoom out.

`bpy.ops.image.view_zoom_in()`
Undocumented (contribute)

`bpy.ops.image.view_zoom_out()`
Undocumented (contribute)

`bpy.ops.image.view_zoom_ratio(ratio=0.0)`
Undocumented (contribute)

Parameters **ratio** (*float in [0, inf], (optional)*) – Ratio, Zoom ratio, 1.0 is 1:1, higher is zoomed in, lower is zoomed out.

Import Anim Operators

`bpy.ops.import_anim.bvh(filepath="", filter_glob="*.bvh", target='ARMATURE', global_scale=1.0, frame_start=1, use_cyclic=False, rotate_mode='NATIVE')`
Load a BVH motion capture file

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **target** (*enum in ['ARMATURE', 'OBJECT'], (optional)*) – Target, Import target type.
- **global_scale** (*float in [0.0001, 1e+06], (optional)*) – Scale, Scale the BVH by this value
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Starting frame for the animation
- **use_cyclic** (*boolean, (optional)*) – Loop, Loop the animation playback
- **rotate_mode** (*enum in ['QUATERNION', 'NATIVE', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'], (optional)*) – Rotation, Rotation conversion.

File addons/io_anim_bvh/__init__.py:79

Import Mesh Operators

`bpy.ops.import_mesh.ply` (*filepath=""*, *files=None*, *directory=""*, *filter_glob="*.ply"*)

Load a PLY geometry file

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **files** (Collection of `OperatorFileListElement`, (optional)) – File Path, File path used for importing the PLY file

File addons/io_mesh_ply/__init__.py:63

`bpy.ops.import_mesh.stl` (*filepath=""*, *filter_glob="*.stl"*, *files=None*, *directory=""*)

Load STL triangle mesh data

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **files** (Collection of `OperatorFileListElement`, (optional)) – File Path, File path used for importing the STL file

File addons/io_mesh_stl/__init__.py:82

Import Scene Operators

`bpy.ops.import_scene.autodesk_3ds` (*filepath=""*, *filter_glob="*.3ds"*, *constrain_size=10.0*, *use_image_search=True*, *use_apply_transform=True*)

Import from 3DS file format (.3ds)

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **constrain_size** (*float in [0, 1000], (optional)*) – Size Constraint, Scale the model by 10 until it reacehs the size constraint. Zero Disables.
- **use_image_search** (*boolean, (optional)*) – Image Search, Search subdirectories for any assosiated images (Warning, may be slow)
- **use_apply_transform** (*boolean, (optional)*) – Apply Transform, Workaround for object transformations importing incorrectly

File addons/io_scene_3ds/__init__.py:59

`bpy.ops.import_scene.obj` (*filepath=""*, *filter_glob="*.obj;*.mtl"*, *CREATE_SMOOTH_GROUPS=True*, *CREATE_FGONS=True*, *CREATE_EDGES=True*, *SPLIT_OBJECTS=True*, *SPLIT_GROUPS=True*, *ROTATE_X90=True*, *CLAMP_SIZE=0.0*, *POLYGROUPS=True*, *IMAGE_SEARCH=True*)

Load a Wavefront OBJ File

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **CREATE_SMOOTH_GROUPS** (*boolean, (optional)*) – Smooth Groups, Surround smooth groups by sharp edges
- **CREATE_FGONS** (*boolean, (optional)*) – NGons as FGons, Import faces with more then 4 verts as fgons

- **CREATE_EDGES** (*boolean, (optional)*) – Lines as Edges, Import lines and faces with 2 verts as edge
- **SPLIT_OBJECTS** (*boolean, (optional)*) – Object, Import OBJ Objects into Blender Objects
- **SPLIT_GROUPS** (*boolean, (optional)*) – Group, Import OBJ Groups into Blender Objects
- **ROTATE_X90** (*boolean, (optional)*) – -X90, Rotate X 90.
- **CLAMP_SIZE** (*float in [0, 1000], (optional)*) – Clamp Scale, Clamp the size to this maximum (Zero to Disable)
- **POLYGROUPS** (*boolean, (optional)*) – Poly Groups, Import OBJ groups as vertex groups.
- **IMAGE_SEARCH** (*boolean, (optional)*) – Image Search, Search subdirs for any assosiated images (Warning, may be slow)

File addons/io_scene_obj/__init__.py:69

`bpy.ops.import_scene.x3d`(*filepath=""*, *filter_glob="*.x3d;*.wrl"*)
Load a BVH motion capture file

Parameters **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file

File addons/io_scene_x3d/__init__.py:55

Info Operators

`bpy.ops.info.report_copy`()
Copy selected reports to Clipboard

`bpy.ops.info.report_delete`()
Delete selected reports

`bpy.ops.info.report_replay`()
Replay selected reports

`bpy.ops.info.reports_display_update`()
Undocumented (contribute)

`bpy.ops.info.select_all_toggle`()
(de)select all reports

`bpy.ops.info.select_border`(*gesture_mode=0*, *xmin=0*, *xmax=0*, *ymin=0*, *ymax=0*)
Toggle border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.info.select_pick`(*report_index=0*)
Select reports by index

Parameters **report_index** (*int in [0, inf], (optional)*) – Report, The index of the report.

Lamp Operators

`bpy.ops.lamp.sunsky_preset_add`(*name=""*, *remove_active=False*)
Add a Sky & Atmosphere Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

Lattice Operators

`bpy.ops.lattice.make_regular`()
Set UVW control points a uniform distance apart

`bpy.ops.lattice.select_all`(*action='TOGGLE'*)
Change selection of all UVW control points

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

Logic Operators

`bpy.ops.logic.actuator_add`(*type=''*, *name=""*, *object=""*)
Add a actuator to the active object

Parameters

- **type** (*enum in [], (optional)*) – Type, Type of actuator to add
- **name** (*string, (optional)*) – Name, Name of the Actuator to add
- **object** (*string, (optional)*) – Object, Name of the Object to add the Actuator to

`bpy.ops.logic.actuator_move`(*actuator=""*, *object=""*, *direction='UP'*)
Move Actuator

Parameters

- **actuator** (*string, (optional)*) – Actuator, Name of the actuator to edit
- **object** (*string, (optional)*) – Object, Name of the object the actuator belongs to
- **direction** (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Move Up or Down

`bpy.ops.logic.actuator_remove`(*actuator=""*, *object=""*)
Remove a actuator from the active object

Parameters

- **actuator** (*string, (optional)*) – Actuator, Name of the actuator to edit
- **object** (*string, (optional)*) – Object, Name of the object the actuator belongs to

`bpy.ops.logic.controller_add`(*type='LOGIC_AND'*, *name=""*, *object=""*)
Add a controller to the active object

Parameters

- **type** (*enum in ['LOGIC_AND', 'LOGIC_OR', 'LOGIC_NAND', 'LOGIC_NOR', 'LOGIC_XOR', 'LOGIC_XNOR', 'EXPRESSION', 'PYTHON'], (optional)*) – Type, Type of controller to add
- **name** (*string, (optional)*) – Name, Name of the Controller to add

- **object** (*string, (optional)*) – Object, Name of the Object to add the Controller to

`bpy.ops.logic.controller_move`(*controller=""*, *object=""*, *direction='UP'*)
Move Controller

Parameters

- **controller** (*string, (optional)*) – Controller, Name of the controller to edit
- **object** (*string, (optional)*) – Object, Name of the object the controller belongs to
- **direction** (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Move Up or Down

`bpy.ops.logic.controller_remove`(*controller=""*, *object=""*)
Remove a controller from the active object

Parameters

- **controller** (*string, (optional)*) – Controller, Name of the controller to edit
- **object** (*string, (optional)*) – Object, Name of the object the controller belongs to

`bpy.ops.logic.links_cut`(*path=None*, *cursor=9*)
Remove logic brick connections

Parameters

- **path** (Collection of `OperatorMousePath`, (optional)) – path
- **cursor** (*int in [0, inf], (optional)*) – Cursor

`bpy.ops.logic.properties`()
Toggle display properties panel

`bpy.ops.logic.sensor_add`(*type=''*, *name=""*, *object=""*)
Add a sensor to the active object

Parameters

- **type** (*enum in [], (optional)*) – Type, Type of sensor to add
- **name** (*string, (optional)*) – Name, Name of the Sensor to add
- **object** (*string, (optional)*) – Object, Name of the Object to add the Sensor to

`bpy.ops.logic.sensor_move`(*sensor=""*, *object=""*, *direction='UP'*)
Move Densor

Parameters

- **sensor** (*string, (optional)*) – Sensor, Name of the sensor to edit
- **object** (*string, (optional)*) – Object, Name of the object the sensor belongs to
- **direction** (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Move Up or Down

`bpy.ops.logic.sensor_remove`(*sensor=""*, *object=""*)
Remove a sensor from the active object

Parameters

- **sensor** (*string, (optional)*) – Sensor, Name of the sensor to edit
- **object** (*string, (optional)*) – Object, Name of the object the sensor belongs to

Marker Operators

`bpy.ops.marker.add()`
Add a new time marker

`bpy.ops.marker.camera_bind()`
Bind the active camera to selected markers(s)

`bpy.ops.marker.delete()`
Delete selected time marker(s)

`bpy.ops.marker.duplicate(frames=0)`
Duplicate selected time marker(s)

Parameters **frames** (*int in [-inf, inf], (optional)*) – Frames

`bpy.ops.marker.make_links_scene(scene='')`
Copy selected markers to another scene

Parameters **scene** (*enum in [], (optional)*) – Scene

`bpy.ops.marker.move(frames=0)`
Move selected time marker(s)

Parameters **frames** (*int in [-inf, inf], (optional)*) – Frames

`bpy.ops.marker.rename(name="RenamedMarker")`
Rename first selected time marker

Parameters **name** (*string, (optional)*) – Name, New name for marker

`bpy.ops.marker.select(extend=False, camera=False)`
Select time marker(s)

Parameters

- **extend** (*boolean, (optional)*) – Extend, extend the selection
- **camera** (*boolean, (optional)*) – Camera, Select the camera

`bpy.ops.marker.select_all(action='TOGGLE')`
Change selection of all time markers

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.marker.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Select all time markers using border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

Material Operators

`bpy.ops.material.copy()`
Copy the material settings and nodes

`bpy.ops.material.new()`
Add a new material

`bpy.ops.material.paste()`
Paste the material settings and nodes

`bpy.ops.material.sss_preset_add(name="", remove_active=False)`
Add a Subsurface Scattering Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

Mball Operators

`bpy.ops.mball.delete_metaelems()`
Delete selected metaelement(s)

`bpy.ops.mball.duplicate_metaelems(mode=1)`
Delete selected metaelement(s)

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.mball.hide_metaelems(unselected=False)`
Hide (un)selected metaelement(s)

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

`bpy.ops.mball.reveal_metaelems()`
Reveal all hidden metaelements

`bpy.ops.mball.select_all(action='TOGGLE')`
Change selection of all meta elements

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.mball.select_inverse_metaelems()`
Select inverse of (un)selected metaelements

`bpy.ops.mball.select_random_metaelems(percent=0.5)`
Randomly select metaelements

Parameters **percent** (*float in [0, 1], (optional)*) – Percent, Percentage of metaelems to select randomly.

Mesh Operators

`bpy.ops.mesh.beautify_fill()`
Rearrange geometry on a selected surface to avoid skinny faces

`bpy.ops.mesh.blend_from_shape(shape='', blend=1.0, add=False)`
Blend in shape from a shape key

Parameters

- **shape** (*enum in [], (optional)*) – Shape, Shape key to use for blending.
- **blend** (*float in [-inf, inf], (optional)*) – Blend, Blending factor.
- **add** (*boolean, (optional)*) – Add, Add rather then blend between shapes.

`bpy.ops.mesh.colors_mirror(axis='X')`
Mirror UV/image color layer

Parameters **axis** (*enum in ['X', 'Y'], (optional)*) – Axis, Axis to mirror colors around.

`bpy.ops.mesh.colors_rotate(direction='CW')`
Rotate UV/image color layer

Parameters **direction** (*enum in ['CW', 'CCW'], (optional)*) – Direction, Direction to rotate edge around.

`bpy.ops.mesh.delete(type='VERT')`
Delete selected vertices, edges or faces

Parameters **type** (*enum in ['VERT', 'EDGE', 'FACE', 'ALL', 'EDGE_FACE', 'ONLY_FACE', 'EDGE_LOOP'], (optional)*) – Type, Method used for deleting mesh data

`bpy.ops.mesh.delete_edgeloop()`
Delete an edge loop by merging the faces on each side to a single face loop

File op/wm.py:31

`bpy.ops.mesh.drop_named_image(name="Image", filepath="Path")`
Assigns Image to active UV layer, or creates a UV layer

Parameters

- **name** (*string, (optional)*) – Name, Image name to assign.
- **filepath** (*string, (optional)*) – Filepath, Path to image file

`bpy.ops.mesh.dupli_extrude_cursor(rotate_source=True)`
Duplicate and extrude selected vertices, edges or faces towards 3D Cursor

Parameters **rotate_source** (*boolean, (optional)*) – Rotate Source, Rotate initial selection giving better shape

`bpy.ops.mesh.duplicate(mode=1)`
Duplicate selected vertices, edges or faces

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.mesh.duplicate_move(MESH_OT_duplicate=None, TRANSFORM_OT_translate=None)`
Undocumented (contribute)

Parameters

- **MESH_OT_duplicate** (`MESH_OT_duplicate`, (optional)) – Duplicate, Duplicate selected vertices, edges or faces
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.mesh.edge_face_add()`
Add an edge or face to selected

`bpy.ops.mesh.edge_flip()`
Flip selected edge or adjoining faces

`bpy.ops.mesh.edge_rotate(direction='CW')`
Rotate selected edge or adjoining faces

Parameters **direction** (*enum in ['CW', 'CCW'], (optional)*) – Direction, Direction to rotate the edge around.

`bpy.ops.mesh.edgering_select`(*extend=False*)
Select an edge ring

Parameters **extend** (*boolean, (optional)*) – Extend, Extend the selection

`bpy.ops.mesh.edges_select_sharp`(*sharpness=0.01*)
Marked selected edges as sharp

Parameters **sharpness** (*float in [0, inf], (optional)*) – sharpness

`bpy.ops.mesh.extrude`(*type='REGION'*)
Extrude selected vertices, edges or faces

Parameters **type** (*enum in ['REGION', 'FACES', 'EDGES', 'VERTS'], (optional)*) – Type

`bpy.ops.mesh.extrude_edges_move`(*MESH_OT_extrude=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (`MESH_OT_extrude`, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.mesh.extrude_faces_move`(*MESH_OT_extrude=None, TRANSFORM_OT_shrink_fatten=None*)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (`MESH_OT_extrude`, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_shrink_fatten** (`TRANSFORM_OT_shrink_fatten`, (optional)) – Shrink/Fatten, Shrink/fatten selected vertices along normals

`bpy.ops.mesh.extrude_region_move`(*MESH_OT_extrude=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (`MESH_OT_extrude`, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.mesh.extrude_repeat`(*offset=2.0, steps=10*)
Extrude selected vertices, edges or faces repeatedly

Parameters

- **offset** (*float in [0, 100], (optional)*) – Offset
- **steps** (*int in [0, 180], (optional)*) – Steps

`bpy.ops.mesh.extrude_vertices_move`(*MESH_OT_extrude=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (`MESH_OT_extrude`, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.mesh.`**`faces_miror_uv`**`()`
Copy mirror UV coordinates on the X axis based on a mirrored mesh

File op/mesh.py:78

`bpy.ops.mesh.`**`faces_select_interior`**`()`
Select faces where all edges have more then 2 face users.

File op/mesh.py:36

`bpy.ops.mesh.`**`faces_select_linked_flat`**`(`*sharpness=135.0*`)`
Select linked faces by angle

Parameters **sharpness** (*float in [0, inf], (optional)*) – sharpness

`bpy.ops.mesh.`**`faces_shade_flat`**`()`
Display faces 'flat'

`bpy.ops.mesh.`**`faces_shade_smooth`**`()`
Display faces 'smooth' (using vertex normals)

`bpy.ops.mesh.`**`fgon_clear`**`()`
Clear fgon from selected face

`bpy.ops.mesh.`**`fgon_make`**`()`
Make fgon from selected faces

`bpy.ops.mesh.`**`fill`**`()`
Create a segment, edge or face

`bpy.ops.mesh.`**`flip_normals`**`()`
Toggle the direction of selected face's vertex and face normals

`bpy.ops.mesh.`**`hide`**`(`*unselected=False*`)`
Hide (un)selected vertices, edges or faces

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

`bpy.ops.mesh.`**`knife_cut`**`(`*type='EXACT', path=None, num_cuts=1, cursor=9*`)`
Cut selected edges and faces into parts

Parameters

- **type** (*enum in ['EXACT', 'MIDPOINTS', 'MULTICUT'], (optional)*) – Type
- **path** (Collection of `OperatorMousePath`, (optional)) – path
- **num_cuts** (*int in [1, 256], (optional)*) – Number of Cuts, Only for Multi-Cut
- **cursor** (*int in [0, inf], (optional)*) – Cursor

`bpy.ops.mesh.`**`loop_multi_select`**`(`*ring=False*`)`
Select a loop of connected edges by connection type

Parameters **ring** (*boolean, (optional)*) – Ring

`bpy.ops.mesh.`**`loop_select`**`(`*extend=False, ring=False*`)`
Select a loop of connected edges

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **ring** (*boolean, (optional)*) – Select Ring

`bpy.ops.mesh.loop_to_region()`
Select a loop of connected edges as a region

`bpy.ops.mesh.loopcut(number_cuts=1)`
Add a new loop between existing loops

Parameters **number_cuts** (*int in [1, inf], (optional)*) – Number of Cuts

`bpy.ops.mesh.loopcut_slide(MESH_OT_loopcut=None, TRANSFORM_OT_edge_slide=None)`
Undocumented (contribute)

Parameters

- **MESH_OT_loopcut** (`MESH_OT_loopcut`, (optional)) – Loop Cut, Add a new loop between existing loops
- **TRANSFORM_OT_edge_slide** (`TRANSFORM_OT_edge_slide`, (optional)) – Edge Slide, Slide an edge loop along a mesh

`bpy.ops.mesh.mark_seam(clear=False)`
(un)mark selected edges as a seam

Parameters **clear** (*boolean, (optional)*) – Clear

`bpy.ops.mesh.mark_sharp(clear=False)`
(un)mark selected edges as sharp

Parameters **clear** (*boolean, (optional)*) – Clear

`bpy.ops.mesh.merge(type='CENTER', uvs=False)`
Merge selected vertices

Parameters

- **type** (*enum in ['FIRST', 'LAST', 'CENTER', 'CURSOR', 'COLLAPSE'], (optional)*) – Type, Merge method to use.
- **uvs** (*boolean, (optional)*) – UVs, Move UVs according to merge.

`bpy.ops.mesh.noise(factor=0.1)`
Use vertex coordinate as texture coordinate

Parameters **factor** (*float in [-inf, inf], (optional)*) – Factor

`bpy.ops.mesh.normals_make_consistent(inside=False)`
Flip all selected vertex and face normals in a consistent direction

Parameters **inside** (*boolean, (optional)*) – Inside

`bpy.ops.mesh.primitive_circle_add(vertices=32, radius=1.0, fill=False, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)`
Construct a circle mesh

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **fill** (*boolean, (optional)*) – Fill

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.primitive_cone_add`(*vertices=32, radius=1.0, depth=2.0, cap_end=True, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a conic mesh (ends filled)

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **depth** (*float in [0, inf], (optional)*) – Depth
- **cap_end** (*boolean, (optional)*) – Cap End
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.primitive_cube_add`(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a cube mesh

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.mesh.**primitive_cylinder_add**(*vertices=32, radius=1.0, depth=2.0, cap_ends=True, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a cylinder mesh

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **depth** (*float in [0, inf], (optional)*) – Depth
- **cap_ends** (*boolean, (optional)*) – Cap Ends
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.mesh.**primitive_grid_add**(*x_subdivisions=10, y_subdivisions=10, size=1.0, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a grid mesh

Parameters

- **x_subdivisions** (*int in [-inf, inf], (optional)*) – X Subdivisions
- **y_subdivisions** (*int in [-inf, inf], (optional)*) – Y Subdivisions
- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.mesh.**primitive_ico_sphere_add**(*subdivisions=2, size=1.0, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct an Icosphere mesh

Parameters

- **subdivisions** (*int in [0, inf], (optional)*) – Subdivisions
- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.primitive_monkey_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Suzanne mesh

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.primitive_plane_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a filled planar mesh with 4 vertices

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.primitive_torus_add`(*major_radius=1.0*, *minor_radius=0.25*, *major_segments=48*, *minor_segments=12*, *use_abso=False*, *abso_major_rad=1.0*, *abso_minor_rad=0.5*, *view_align=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*)

Add a torus mesh

Parameters

- **major_radius** (*float in [0.01, 100], (optional)*) – Major Radius, Radius from the origin to the center of the cross sections
- **minor_radius** (*float in [0.01, 100], (optional)*) – Minor Radius, Radius of the torus' cross section
- **major_segments** (*int in [3, 256], (optional)*) – Major Segments, Number of segments for the main ring of the torus
- **minor_segments** (*int in [3, 256], (optional)*) – Minor Segments, Number of segments for the minor ring of the torus
- **use_abso** (*boolean, (optional)*) – Use Int+Ext Controls, Use the Int / Ext controls for torus dimensions
- **abso_major_rad** (*float in [0.01, 100], (optional)*) – Exterior Radius, Total Exterior Radius of the torus
- **abso_minor_rad** (*float in [0.01, 100], (optional)*) – Inside Radius, Total Interior Radius of the torus
- **view_align** (*boolean, (optional)*) – Align to View
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation

File op/add_mesh_torus.py:114

`bpy.ops.mesh.primitive_uv_sphere_add`(*segments=32*, *ring_count=16*, *size=1.0*, *view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a UV sphere mesh

Parameters

- **segments** (*int in [-inf, inf], (optional)*) – Segments
- **ring_count** (*int in [-inf, inf], (optional)*) – Rings
- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.mesh.quads_convert_to_tris()`
Convert selected quads to triangles

`bpy.ops.mesh.region_to_loop()`
Select a region as a loop of connected edges

`bpy.ops.mesh.remove_doubles(limit=0.0001)`
Remove duplicate vertices

Parameters **limit** (*float in [1e-06, 50], (optional)*) – Merge Threshold, Minimum distance between merged verts

`bpy.ops.mesh.reveal()`
Reveal all hidden vertices, edges and faces

`bpy.ops.mesh.rip(constraint_axis=(False, False, False), constraint_orientation='', mirror=False, release_confirm=False)`
Rip selection from mesh (quads only)

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.mesh.rip_move(MESH_OT_rip=None, TRANSFORM_OT_translate=None)`
Undocumented (contribute)

Parameters

- **MESH_OT_rip** (`MESH_OT_rip`, (optional)) – Rip, Rip selection from mesh (quads only)
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.mesh.screw(steps=9, turns=1, center=(0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0))`
Extrude selected vertices in screw-shaped rotation around the cursor in indicated viewport

Parameters

- **steps** (*int in [0, inf], (optional)*) – Steps, Steps
- **turns** (*int in [0, inf], (optional)*) – Turns, Turns
- **center** (*float array of 3 items in [-inf, inf], (optional)*) – Center, Center in global view space
- **axis** (*float array of 3 items in [-1, 1], (optional)*) – Axis, Axis in global view space

`bpy.ops.mesh.select_all(action='TOGGLE')`
Change selection of all vertices, edges or faces

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.mesh.select_axis(mode='POSITIVE', axis='X_AXIS')`
Select all data in the mesh on a single axis

Parameters

- **mode** (*enum in ['POSITIVE', 'NEGATIVE', 'ALIGNED'], (optional)*) – Axis Mode, Axis side to use when selecting

- **axis** (*enum in ['X_AXIS', 'Y_AXIS', 'Z_AXIS'], (optional)*) – Axis, Select the axis to compare each vertex on

bpy.ops.mesh.**select_by_number_vertices**(*type='TRIANGLES'*)
Select vertices or faces by vertex count

Parameters **type** (*enum in ['TRIANGLES', 'QUADS', 'OTHER'], (optional)*) – Type, Type of elements to select.

bpy.ops.mesh.**select_inverse**()
Select inverse of (un)selected vertices, edges or faces

bpy.ops.mesh.**select_less**()
Select less vertices, edges or faces connected to initial selection

bpy.ops.mesh.**select_linked**(*limit=False*)
Select all vertices linked to the active mesh

Parameters **limit** (*boolean, (optional)*) – Limit by Seams, Limit selection by seam boundries (faces only)

bpy.ops.mesh.**select_linked_pick**(*deselect=False*, *limit=False*)
(un)select all vertices linked to the active mesh

Parameters

- **deselect** (*boolean, (optional)*) – Deselect
- **limit** (*boolean, (optional)*) – Limit by Seams, Limit selection by seam boundries (faces only)

bpy.ops.mesh.**select_mirror**(*extend=False*)
Select mesh items at mirrored locations

Parameters **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

bpy.ops.mesh.**select_more**()
Select more vertices, edges or faces connected to initial selection

bpy.ops.mesh.**select_non_manifold**()
Select all non-manifold vertices or edges

bpy.ops.mesh.**select_nth**(*nth=2*)
Undocumented (contribute)

Parameters **nth** (*int in [2, 100], (optional)*) – Nth Selection

bpy.ops.mesh.**select_random**(*percent=50.0*, *extend=False*)
Randomly select vertices

Parameters

- **percent** (*float in [0, 100], (optional)*) – Percent, Percentage of elements to select randomly.
- **extend** (*boolean, (optional)*) – Extend Selection, Extend selection instead of deselecting everything first.

bpy.ops.mesh.**select_shortest_path**(*extend=False*)
Select shortest path between two selections

Parameters **extend** (*boolean, (optional)*) – Extend Select

bpy.ops.mesh.**select_similar**(*type='NORMAL'*, *threshold=0.01*)
Select similar vertices, edges or faces by property types

Parameters

- **type** (*enum in ['NORMAL', 'FACE', 'VGROUP', 'LENGTH', 'DIR', 'FACE', 'FACE_ANGLE', 'CREASE', 'SEAM', 'SHARP', 'MATERIAL', 'IMAGE', 'AREA', 'PERIMETER', 'NORMAL', 'COPLANAR'], (optional)*) – Type
- **threshold** (*float in [0, inf], (optional)*) – Threshold

`bpy.ops.mesh.select_vertex_path(type='EDGE_LENGTH')`
Select shortest path between two vertices by distance type

Parameters **type** (*enum in ['EDGE_LENGTH', 'TOPOLOGICAL'], (optional)*) – Type, Method to compute distance.

`bpy.ops.mesh.separate(type='SELECTED')`
Separate selected geometry into a new mesh

Parameters **type** (*enum in ['SELECTED', 'MATERIAL', 'LOOSE'], (optional)*) – Type

`bpy.ops.mesh.shape_propagate_to_all()`
Apply selected vertex locations to all other shape keys

`bpy.ops.mesh.solidify(thickness=0.01)`
Create a solid skin by extruding, compensating for sharp angles

Parameters **thickness** (*float in [-inf, inf], (optional)*) – Thickness

`bpy.ops.mesh.sort_faces(type='VIEW_AXIS')`
The faces of the active Mesh Object are sorted, based on the current view.

Parameters **type** (*enum in ['VIEW_AXIS', 'CURSOR_DISTANCE', 'MATERIAL', 'SELECTION', 'RANDOMIZE'], (optional)*) – Type

`bpy.ops.mesh.spin(steps=9, dupli=False, degrees=90.0, center=(0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0))`
Extrude selected vertices in a circle around the cursor in indicated viewport

Parameters

- **steps** (*int in [0, inf], (optional)*) – Steps, Steps
- **dupli** (*boolean, (optional)*) – Dupli, Make Duplicates
- **degrees** (*float in [-inf, inf], (optional)*) – Degrees, Degrees
- **center** (*float array of 3 items in [-inf, inf], (optional)*) – Center, Center in global view space
- **axis** (*float array of 3 items in [-1, 1], (optional)*) – Axis, Axis in global view space

`bpy.ops.mesh.split()`
Split selected geometry into separate disconnected mesh

`bpy.ops.mesh.sticky_add()`
Add sticky UV texture layer

`bpy.ops.mesh.sticky_remove()`
Remove sticky UV texture layer

`bpy.ops.mesh.subdivide(number_cuts=1, smoothness=0.0, fractal=0.0, corner_cut_pattern='INNER_VERTEX')`
Subdivide selected edges

Parameters

- **number_cuts** (*int in [1, inf], (optional)*) – Number of Cuts
- **smoothness** (*float in [0, inf], (optional)*) – Smoothness, Smoothness factor.
- **fractal** (*float in [0, inf], (optional)*) – Fractal, Fractal randomness factor.

- **corner_cut_pattern** (*enum in ['PATH', 'INNER_VERTEX', 'FAN'], (optional)*) – Corner Cut Pattern, Topology pattern to use to fill a face after cutting across its corner

`bpy.ops.mesh.tris_convert_to_quads()`
Convert selected triangles to quads

`bpy.ops.mesh.uv_texture_add()`
Add UV texture layer

`bpy.ops.mesh.uv_texture_remove()`
Remove UV texture layer

`bpy.ops.mesh.uvs_mirror(axis='X')`
Mirror selected UVs

Parameters **axis** (*enum in ['X', 'Y'], (optional)*) – Axis, Axis to mirror UVs around.

`bpy.ops.mesh.uvs_rotate(direction='CW')`
Rotate selected UVs

Parameters **direction** (*enum in ['CW', 'CCW'], (optional)*) – Direction, Direction to rotate UVs around.

`bpy.ops.mesh.vertex_color_add()`
Add vertex color layer

`bpy.ops.mesh.vertex_color_remove()`
Remove vertex color layer

`bpy.ops.mesh.vertices_randomize()`
Randomize vertex order

`bpy.ops.mesh.vertices_smooth(repeat=1, xaxis=True, yaxis=True, zaxis=True)`
Flatten angles of selected vertices

Parameters

- **repeat** (*int in [1, 100], (optional)*) – Smooth Iterations
- **xaxis** (*boolean, (optional)*) – X-Axis, Smooth along the X axis.
- **yaxis** (*boolean, (optional)*) – Y-Axis, Smooth along the Y axis.
- **zaxis** (*boolean, (optional)*) – Z-Axis, Smooth along the Z axis.

`bpy.ops.mesh.vertices_sort()`
Sort vertex order

Nla Operators

`bpy.ops.nla.action_sync_length(active=True)`
Sychronise the length of the referenced Action with the lengths used in the strip

Parameters **active** (*boolean, (optional)*) – Active Strip Only, Only sync the active length for the active strip.

`bpy.ops.nla.actionclip_add(action='')`
Add an Action-Clip strip (i.e. an NLA Strip referencing an Action) to the active track

Parameters **action** (*enum in [], (optional)*) – Action

`bpy.ops.nla.apply_scale()`
Apply scaling of selected strips to their referenced Actions

`bpy.ops.nla.bake`(*frame_start=1*, *frame_end=250*, *step=1*, *only_selected=True*)
Bake animation to an Action

Parameters

- **frame_start** (*int in [1, 300000], (optional)*) – Start Frame, Start frame for baking
- **frame_end** (*int in [1, 300000], (optional)*) – End Frame, End frame for baking
- **step** (*int in [1, 120], (optional)*) – Frame Step, Frame Step
- **only_selected** (*boolean, (optional)*) – Only Selected

File op/nla.py:148

`bpy.ops.nla.channels_click`(*extend=False*)
Handle clicks to select NLA channels

Parameters **extend** (*boolean, (optional)*) – Extend Select

`bpy.ops.nla.clear_scale`()
Reset scaling of selected strips

`bpy.ops.nla.click_select`(*extend=False*)
Handle clicks to select NLA Strips

Parameters **extend** (*boolean, (optional)*) – Extend Select

`bpy.ops.nla.delete`()
Delete selected strips

`bpy.ops.nla.delete_tracks`()
Delete selected NLA-Tracks and the strips they contain

`bpy.ops.nla.duplicate`(*mode=1*)
Duplicate selected NLA-Strips, adding the new strips in new tracks above the originals

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.nla.fmodifier_add`(*type='NULL'*, *only_active=False*)
Add F-Modifier of the secified type to the selected NLA-Strips

Parameters

- **type** (*enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED'], (optional)*) – Type
- **only_active** (*boolean, (optional)*) – Only Active, Only add F-Modifier of the specified type to the active strip.

`bpy.ops.nla.fmodifier_copy`()
Copy the F-Modifier(s) of the active NLA-Strip

`bpy.ops.nla.fmodifier_paste`()
Add copied F-Modifiers to the selected NLA-Strips

`bpy.ops.nla.meta_add`()
Add new meta-strips incorporating the selected strips

`bpy.ops.nla.meta_remove`()
Separate out the strips held by the selected meta-strips

`bpy.ops.nla.move_down`()
Move selected strips down a track if there's room

`bpy.ops.nla.move_up()`
Move selected strips up a track if there's room

`bpy.ops.nla.mute_toggle()`
Mute or un-muted selected strips

`bpy.ops.nla.properties()`
Toggle display properties panel

`bpy.ops.nla.select_all_toggle(invert=False)`
(De)Select all NLA-Strips

Parameters **invert** (*boolean, (optional)*) – Invert

`bpy.ops.nla.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, axis_range=False)`
Use box selection to grab NLA-Strips

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **axis_range** (*boolean, (optional)*) – Axis Range

`bpy.ops.nla.select_leftright(mode='CHECK', extend=False)`
Select strips to the left or the right of the current frame

Parameters

- **mode** (*enum in ['CHECK', 'LEFT', 'RIGHT'], (optional)*) – Mode
- **extend** (*boolean, (optional)*) – Extend Select

`bpy.ops.nla.snap(type='CFRA')`
Move start of strips to specified time

Parameters **type** (*enum in ['CFRA', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER'], (optional)*) – Type

`bpy.ops.nla.split()`
Split selected strips at their midpoints

`bpy.ops.nla.swap()`
Swap order of selected strips within tracks

`bpy.ops.nla.tracks_add(above_selected=False)`
Add NLA-Tracks above/after the selected tracks

Parameters **above_selected** (*boolean, (optional)*) – Above Selected, Add a new NLA Track above every existing selected one.

`bpy.ops.nla.transition_add()`
Add a transition strip between two adjacent selected strips

`bpy.ops.nla.tweakmode_enter()`
Enter tweaking mode for the action referenced by the active strip

`bpy.ops.nla.tweakmode_exit()`
Exit tweaking mode for the action referenced by the active strip

Node Operators

`bpy.ops.node.add_file`(*filepath=""*, *filter_blender=False*, *filter_image=True*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=9*, *name="Image"*)

Add a file node to the current node editor

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **name** (*string, (optional)*) – Name, Datablock name to assign.

`bpy.ops.node.backimage_move`()

Move Node backdrop

`bpy.ops.node.backimage_sample`()

Undocumented (contribute)

`bpy.ops.node.backimage_zoom`(*factor=1.2*)

Undocumented (contribute)

Parameters **factor** (*float in [0, 10], (optional)*) – Factor

`bpy.ops.node.delete`()

Delete selected nodes

`bpy.ops.node.duplicate`()

Duplicate the nodes

`bpy.ops.node.duplicate_move`(*NODE_OT_duplicate=None*, *TRANSFORM_OT_translate=None*)

Undocumented (contribute)

Parameters

- **NODE_OT_duplicate** (`NODE_OT_duplicate`, (optional)) – Duplicate Nodes, Duplicate the nodes
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.node.group_edit`()

Edit node group

`bpy.ops.node.group_make()`
Make group from selected nodes

`bpy.ops.node.group_socket_add(in_out='IN', name="", type='VALUE')`
Add node group socket

Parameters

- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output
- **name** (*string, (optional)*) – Name, Group socket name
- **type** (*enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)*) – Type, Type of the group socket

`bpy.ops.node.group_socket_move_down(index=0, in_out='IN')`
Move down node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

`bpy.ops.node.group_socket_move_up(index=0, in_out='IN')`
Move up node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

`bpy.ops.node.group_socket_remove(index=0, in_out='IN')`
Removed node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

`bpy.ops.node.group_ungroup()`
Ungroup selected nodes

`bpy.ops.node.hide_socket_toggle()`
Toggle unused node socket display

`bpy.ops.node.hide_toggle()`
Toggle hiding of selected nodes

`bpy.ops.node.link()`
Undocumented (contribute)

`bpy.ops.node.link_make(replace=False)`
Makes a link between selected output in input sockets

Parameters **replace** (*boolean, (optional)*) – Replace, Replace socket connections with the new links

`bpy.ops.node.link_viewer()`
Link to Viewer Node

`bpy.ops.node.links_cut(path=None, cursor=9)`
Undocumented (contribute)

Parameters

- **path** (Collection of `OperatorMousePath`, (optional)) – path

- **cursor** (*int in [0, inf], (optional)*) – Cursor

`bpy.ops.node.mute_toggle()`
Toggle muting of the nodes

`bpy.ops.node.preview_toggle()`
Toggle preview display for selected nodes

`bpy.ops.node.properties()`
Toggles the properties panel display

`bpy.ops.node.read_fullsamplelayers()`
Undocumented (contribute)

`bpy.ops.node.read_renderlayers()`
Undocumented (contribute)

`bpy.ops.node.render_changed()`
Undocumented (contribute)

`bpy.ops.node.resize()`
Undocumented (contribute)

`bpy.ops.node.select(mouse_x=0, mouse_y=0, extend=False)`
Select node under cursor

Parameters

- **mouse_x** (*int in [-inf, inf], (optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf], (optional)*) – Mouse Y
- **extend** (*boolean, (optional)*) – Extend

`bpy.ops.node.select_all()`
(De)select all nodes

`bpy.ops.node.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, tweak=False)`
Use box selection to select nodes

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **tweak** (*boolean, (optional)*) – Tweak, Only activate when mouse is not over a node - useful for tweak gesture

`bpy.ops.node.select_link_viewer(NODE_OT_select=None, NODE_OT_link_viewer=None)`
Undocumented (contribute)

Parameters

- **NODE_OT_select** (`NODE_OT_select`, (optional)) – Select, Select node under cursor
- **NODE_OT_link_viewer** (`NODE_OT_link_viewer`, (optional)) – Link to Viewer Node, Link to Viewer Node

`bpy.ops.node.select_linked_from()`
Select nodes linked from the selected ones

`bpy.ops.node.select_linked_to()`
Select nodes linked to the selected ones

`bpy.ops.node.select_same_type()`
Select all the same type

`bpy.ops.node.select_same_type_next()`
Select the next node of the same type.

`bpy.ops.node.select_same_type_prev()`
Select the prev node of the same type.

`bpy.ops.node.show_cyclic_dependencies()`
Sort the nodes and show the cyclic dependencies between the nodes

`bpy.ops.node.view_all()`
Resize view so you can see all nodes

`bpy.ops.node.visibility_toggle(mouse_x=0, mouse_y=0)`
Handle clicks on node header buttons

Parameters

- **mouse_x** (*int in [-inf, inf], (optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf], (optional)*) – Mouse Y

Object Operators

`bpy.ops.object.add(type='EMPTY', view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Add an object to the scene

Parameters

- **type** (*enum in ['MESH', 'CURVE', 'SURFACE', 'META', 'FONT', 'ARMATURE', 'LATTICE', 'EMPTY', 'CAMERA', 'LAMP'], (optional)*) – Type
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.add_named(linked=False, name="Cube")`
Add named object

Parameters

- **linked** (*boolean, (optional)*) – Linked, Duplicate object but not object data, linking to the original data.
- **name** (*string, (optional)*) – Name, Object name to add.

`bpy.ops.object.add_named_cursor`(*name="Cube"*, *VIEW3D_OT_cursor3d=None*, *OBJECT_OT_add_named=None*)

Undocumented (contribute)

Parameters

- **name** (*string, (optional)*) – Name, Object name to add.
- **VIEW3D_OT_cursor3d** (`VIEW3D_OT_cursor3d`, (optional)) – Set 3D Cursor, Set the location of the 3D cursor
- **OBJECT_OT_add_named** (`OBJECT_OT_add_named`, (optional)) – Add Named Object, Add named object

`bpy.ops.object.align`(*align_mode='OPT_2'*, *relative_to='OPT_4'*, *align_axis=set()*)

Align Objects

Parameters

- **align_mode** (*enum in ['OPT_1', 'OPT_2', 'OPT_3'], (optional)*) – Align Mode:
- **relative_to** (*enum in ['OPT_1', 'OPT_2', 'OPT_3', 'OPT_4'], (optional)*) – Relative To:
- **align_axis** (*enum set in {'X', 'Y', 'Z'}, (optional)*) – Align, Align to axis

File op/object_align.py:272

`bpy.ops.object.armature_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Add an armature object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.bake_image`()

Bake image textures of selected objects

`bpy.ops.object.camera_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Add a camera object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.

- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.constraint_add(type='')`

Add a constraint to the active object

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

`bpy.ops.object.constraint_add_with_targets(type='')`

Add a constraint to the active object, with target (where applicable) set to the selected Objects/Bones

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

`bpy.ops.object.constraints_clear()`

Clear all the constraints for the active Object only

`bpy.ops.object.constraints_copy()`

Copy constraints to other selected objects.

`bpy.ops.object.convert(target='MESH', keep_original=False)`

Convert selected objects to another type

Parameters

- **target** (*enum in ['CURVE', 'MESH'], (optional)*) – Target, Type of object to convert to.
- **keep_original** (*boolean, (optional)*) – Keep Original, Keep original objects instead of replacing them.

`bpy.ops.object.delete()`

Delete selected objects

`bpy.ops.object.drop_named_material(name="Material")`

Undocumented (contribute)

Parameters name (*string, (optional)*) – Name, Material name to assign.

`bpy.ops.object.duplicate(linked=False, mode=1)`

Duplicate selected objects

Parameters

- **linked** (*boolean, (optional)*) – Linked, Duplicate object but not object data, linking to the original data.
- **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.object.duplicate_move(OBJECT_OT_duplicate=None, TRANSFORM_OT_translate=None)`

Undocumented (contribute)

Parameters

- **OBJECT_OT_duplicate** (`OBJECT_OT_duplicate`, (optional)) – Duplicate, Duplicate selected objects
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.object.`**`duplicate_move_linked`**(*OBJECT_OT_duplicate=None*, *TRANSFORM_OT_translate=None*)

Undocumented (contribute)

Parameters

- **OBJECT_OT_duplicate** (`OBJECT_OT_duplicate`, (optional)) – Duplicate, Duplicate selected objects
- **TRANSFORM_OT_translate** (`TRANSFORM_OT_translate`, (optional)) – Translate, Translate selected items

`bpy.ops.object.`**`duplicates_make_real`**()

Make dupli objects attached to this object real

`bpy.ops.object.`**`editmode_toggle`**()

Toggle object's editmode

`bpy.ops.object.`**`effector_add`**(*type='FORCE'*, *view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Add an empty object with a physics effector to the scene

Parameters

- **type** (*enum in ['FORCE', 'WIND', 'VORTEX', 'MAGNET', 'HARMONIC', 'CHARGE', 'LENNARDJ', 'TEXTURE', 'GUIDE', 'BOID', 'TURBULENCE', 'DRAG'], (optional)*) – Type
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.`**`explode_refresh`**(*modifier=""*)

Refresh data in the Explode modifier

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.`**`forcefield_toggle`**()

Toggle object's force field

`bpy.ops.object.`**`game_property_clear`**()

Undocumented (contribute)

`bpy.ops.object.`**`game_property_copy`**(*operation='COPY'*, *property=''*)

Undocumented (contribute)

Parameters

- **operation** (*enum in ['REPLACE', 'MERGE', 'COPY'], (optional)*) – Operation
- **property** (*enum in [], (optional)*) – Property, Properties to copy

`bpy.ops.object.game_property_new()`
Undocumented (contribute)

`bpy.ops.object.game_property_remove(index=0)`
Undocumented (contribute)

Parameters **index** (*int in [0, inf], (optional)*) – Index, Property index to remove

`bpy.ops.object.group_add()`
Add an object to a new group

`bpy.ops.object.group_instance_add(group='', view_align=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Add a dupligroup instance

Parameters

- **group** (*enum in [], (optional)*) – Group
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.group_link(group='')`
Add an object to an existing group

Parameters **group** (*enum in [], (optional)*) – Group

`bpy.ops.object.group_remove()`
Undocumented (contribute)

`bpy.ops.object.hide_render_clear()`
Reveal the render object by setting the hide render flag

`bpy.ops.object.hide_render_clear_all()`
Reveal all render objects by setting the hide render flag

File op/object.py:560

`bpy.ops.object.hide_render_set(unselected=False)`
Hide the render object by setting the hide render flag

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

`bpy.ops.object.hide_view_clear()`
Reveal the object by setting the hide flag

`bpy.ops.object.hide_view_set(unselected=False)`
Hide the object by setting the hide flag

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

bpy.ops.object.**hook_add_newob**()
Hook selected vertices to the first selected Object

bpy.ops.object.**hook_add_selob**()
Hook selected vertices to the first selected Object

bpy.ops.object.**hook_assign**(*modifier=''*)
Assign the selected vertices to a hook

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

bpy.ops.object.**hook_recenter**(*modifier=''*)
Set hook center to cursor position

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

bpy.ops.object.**hook_remove**(*modifier=''*)
Remove a hook from the active object

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to remove.

bpy.ops.object.**hook_reset**(*modifier=''*)
Recalculate and clear offset transformation

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

bpy.ops.object.**hook_select**(*modifier=''*)
Selects effected vertices on mesh

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to remove.

bpy.ops.object.**isolate_type_render**()
Hide unselected render objects of same type as active by setting the hide render flag

File op/object.py:540

bpy.ops.object.**join**()
Join selected objects into active object

bpy.ops.object.**join_shapes**()
Merge selected objects to shapes of active object

bpy.ops.object.**join_uvs**()
Copy UV Layout to objects with matching geometry

File op/object.py:462

bpy.ops.object.**lamp_add**(*type='POINT', view_align=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)
Add a lamp object to the scene

Parameters

- **type** (*enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA'], (optional)*) – Type
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.location_apply()`
Apply the object's location to its data

`bpy.ops.object.location_clear()`
Clear the object's location

`bpy.ops.object.logic_bricks_copy()`
Copy logic bricks to other selected objects.

`bpy.ops.object.make_dupli_face()`
Make linked objects into dupli-faces

File op/object.py:529

`bpy.ops.object.make_links_data(type='OBDATA')`
Make links from the active object to other selected objects

Parameters **type** (*enum in ['OBDATA', 'MATERIAL', 'ANIMATION', 'DUPLIGROUP', 'MODIFIERS'], (optional)*) – Type

`bpy.ops.object.make_links_scene(scene='')`
Make linked data local to each object

Parameters **scene** (*enum in [], (optional)*) – Scene

`bpy.ops.object.make_local(type='SELECTED_OBJECTS')`
Make library linked datablocks local to this file

Parameters **type** (*enum in ['SELECTED_OBJECTS', 'SELECTED_OBJECTS_DATA', 'ALL'], (optional)*) – Type

`bpy.ops.object.make_single_user(type='SELECTED_OBJECTS', object=False, obdata=False, material=False, texture=False, animation=False)`
Make linked data local to each object

Parameters

- **type** (*enum in ['SELECTED_OBJECTS', 'ALL'], (optional)*) – Type
- **object** (*boolean, (optional)*) – Object, Make single user objects
- **obdata** (*boolean, (optional)*) – Object Data, Make single user object data
- **material** (*boolean, (optional)*) – Materials, Make materials local to each datablock
- **texture** (*boolean, (optional)*) – Textures, Make textures local to each material
- **animation** (*boolean, (optional)*) – Object Animation, Make animation data local to each object

`bpy.ops.object.material_slot_add()`
Add a new material slot or duplicate the selected one

`bpy.ops.object.material_slot_assign()`
Assign the material in the selected material slot to the selected vertices

`bpy.ops.object.material_slot_copy()`
Copies materials to other selected objects

`bpy.ops.object.material_slot_deselect()`
Deselect vertices assigned to the selected material slot

`bpy.ops.object.material_slot_remove()`
Remove the selected material slot

`bpy.ops.object.material_slot_select()`
Select vertices assigned to the selected material slot

`bpy.ops.object.meshdeform_bind(modifier="")`
Bind mesh to cage in mesh deform modifier

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.metaball_add(type='BALL', view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Add an metaball object to the scene

Parameters

- **type** (*enum in ['BALL', 'CAPSULE', 'PLANE', 'ELLIPSOID', 'CUBE'], (optional)*) – Primitive
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.mode_set(mode='OBJECT', toggle=False)`
Sets the object interaction mode

Parameters

- **mode** (*enum in ['OBJECT', 'EDIT', 'SCULPT', 'VERTEX_PAINT', 'WEIGHT_PAINT', 'TEXTURE_PAINT', 'PARTICLE_EDIT', 'POSE'], (optional)*) – Mode
- **toggle** (*boolean, (optional)*) – Toggle

`bpy.ops.object.modifier_add(type='SUBSURF')`
Add a modifier to the active object

Parameters **type** (*enum in ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE'], (optional)*) – Type

`bpy.ops.object.modifier_apply(apply_as='DATA', modifier="")`
Apply modifier and remove from the stack

Parameters

- **apply_as** (*enum in ['DATA', 'SHAPE'], (optional)*) – Apply as, How to apply the modifier to the geometry
- **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.modifier_convert(modifier="")`
Convert particles to a mesh object

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.modifier_copy(modifier="")`
Duplicate modifier at the same position in the stack

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.modifier_move_down(modifier="")`
Move modifier down in the stack

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.modifier_move_up(modifier="")`
Move modifier up in the stack

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.modifier_remove(modifier="")`
Remove a modifier from the active object

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.move_to_layer(layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Move the object to different layers

Parameters **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.multires_base_apply(modifier="")`
Modify the base mesh to conform to the displaced mesh

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.multires_external_pack()`
Pack displacements from an external file

`bpy.ops.object.multires_external_save(filepath="", check_existing=True, filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=True, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, modifier="")`
Save displacements to an external file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files

- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.multires_higher_levels_delete`(*modifier=""*)
Undocumented (contribute)

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.multires_reshape`(*modifier=""*)
Copy vertex coordinates from other object

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.multires_subdivide`(*modifier=""*)
Add a new level of subdivision

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

`bpy.ops.object.origin_clear`()
Clear the object's origin

`bpy.ops.object.origin_set`(*type='GEOMETRY_ORIGIN', center='MEDIAN'*)
Set the object's origin, by either moving the data, or set to center of data, or use 3d cursor

Parameters

- **type** (*enum in ['GEOMETRY_ORIGIN', 'ORIGIN_GEOMETRY', 'ORIGIN_CURSOR'], (optional)*) – Type
- **center** (*enum in ['MEDIAN', 'BOUNDS'], (optional)*) – Center

`bpy.ops.object.parent_clear`(*type='CLEAR'*)
Clear the object's parenting

Parameters **type** (*enum in ['CLEAR', 'CLEAR_KEEP_TRANSFORM', 'CLEAR_INVERSE'], (optional)*) – Type

`bpy.ops.object.parent_no_inverse_set`()
Set the object's parenting without setting the inverse parent correction

`bpy.ops.object.parent_set`(*type='OBJECT'*)
Set the object's parenting

Parameters **type** (*enum in ['OBJECT', 'ARMATURE', 'ARMATURE_NAME', 'ARMATURE_AUTO', 'ARMATURE_ENVELOPE', 'BONE', 'CURVE', 'FOLLOW', 'PATH_CONST', 'LATTICE', 'VERTEX', 'TRIA'], (optional)*) – Type

`bpy.ops.object.particle_system_add`()
Add a particle system

`bpy.ops.object.particle_system_remove`()
Remove the selected particle system

`bpy.ops.object.paths_calculate`()
Calculate paths for the selected bones

`bpy.ops.object.paths_clear()`
Clear path caches for selected bones

`bpy.ops.object.posemode_toggle()`
Enables or disables posing/selecting bones

`bpy.ops.object.proxy_make(object="", type='DEFAULT')`
Add empty object to become local replacement data of a library-linked object

Parameters

- **object** (*string, (optional)*) – Proxy Object, Name of lib-linked/grouped object to make a proxy for.
- **type** (*enum in ['DEFAULT'], (optional)*) – Type, Group object

`bpy.ops.object.randomize_transform(random_seed=0, use_delta=False, use_loc=True, loc=(0.0, 0.0, 0.0), use_rot=True, rot=(0.0, 0.0, 0.0), use_scale=True, scale_even=False, scale=(0.0, 0.0, 0.0))`
Randomize objects loc/rot/scale

Parameters

- **random_seed** (*int in [0, 1000], (optional)*) – Random Seed, Seed value for the random generator
- **use_delta** (*boolean, (optional)*) – Transform Delta, Randomize delta transform values instead of regular transform
- **use_loc** (*boolean, (optional)*) – Randomize Location, Randomize the location values
- **loc** (*float array of 3 items in [-100, 100], (optional)*) – Location, Maximun distance the objects can spread over each axis
- **use_rot** (*boolean, (optional)*) – Randomize Rotation, Randomize the rotation values
- **rot** (*float array of 3 items in [-180, 180], (optional)*) – Rotation, Maximun rotation over each axis
- **use_scale** (*boolean, (optional)*) – Randomize Scale, Randomize the scale values
- **scale_even** (*boolean, (optional)*) – Scale Even, Use the same scale value for all axis
- **scale** (*float array of 3 items in [-100, 100], (optional)*) – Scale, Maximum scale randomization over each axis

File op/object_randomize_transform.py:131

`bpy.ops.object.rotation_apply()`
Apply the object's rotation to its data

`bpy.ops.object.rotation_clear()`
Clear the object's rotation

`bpy.ops.object.scale_apply()`
Apply the object's scale to its data

`bpy.ops.object.scale_clear()`
Clear the object's scale

`bpy.ops.object.select_all(action='TOGGLE')`
Change selection of all visible objects in scene

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.object.select_by_layer(extend=False, layers=1)`
Select all visible objects on a layer

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **layers** (*int in [1, 20], (optional)*) – Layer

`bpy.ops.object.select_by_type(extend=False, type='MESH')`
Select all visible objects that are of a type

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['MESH', 'CURVE', 'SURFACE', 'META', 'FONT', 'ARMATURE', 'LATTICE', 'EMPTY', 'CAMERA', 'LAMP'], (optional)*) – Type

`bpy.ops.object.select_camera()`
Select object matching a naming pattern

File op/object.py:84

`bpy.ops.object.select_grouped(extend=False, type='CHILDREN_RECURSIVE')`
Select all visible objects grouped by various properties

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['CHILDREN_RECURSIVE', 'CHILDREN', 'PARENT', 'SIBLINGS', 'TYPE', 'LAYER', 'GROUP', 'HOOK', 'PASS', 'COLOR', 'PROPERTIES'], (optional)*) – Type

`bpy.ops.object.select_hierarchy(direction='PARENT', extend=False)`
Select object relative to the active objects position in the hierarchy

Parameters

- **direction** (*enum in ['PARENT', 'CHILD'], (optional)*) – Direction, Direction to select in the hierarchy
- **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

File op/object.py:114

`bpy.ops.object.select_inverse()`
Invert selection of all visible objects

`bpy.ops.object.select_linked(extend=False, type='OBDATA')`
Select all visible objects that are linked

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['OBDATA', 'MATERIAL', 'TEXTURE', 'DUPGROUP', 'PARTICLE', 'LIBRARY', 'LIBRARY_OBDATA'], (optional)*) – Type

`bpy.ops.object.select_mirror(extend=False)`
Select the Mirror objects of the selected object eg. L.sword -> R.sword

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

`bpy.ops.object.select_name`(*name=""*, *extend=False*)
Select an object with this name

Parameters

- **name** (*string, (optional)*) – Name, Object name to select.
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

`bpy.ops.object.select_pattern`(*pattern="*"*, *case_sensitive=False*, *extend=True*)
Select object matching a naming pattern

Parameters

- **pattern** (*string, (optional)*) – Pattern, Name filter using '*' and '?' wildcard chars
- **case_sensitive** (*boolean, (optional)*) – Case Sensitive, Do a case sensitive compare
- **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

File op/object.py:35

`bpy.ops.object.select_random`(*percent=50.0*, *extend=False*)
Set select on random visible objects

Parameters

- **percent** (*float in [0, 100], (optional)*) – Percent, Percentage of objects to select randomly
- **extend** (*boolean, (optional)*) – Extend Selection, Extend selection instead of deselecting everything first.

`bpy.ops.object.select_same_group`(*group=""*)
Select object in the same group

Parameters **group** (*string, (optional)*) – Group, Name of the group to select.

`bpy.ops.object.shade_flat`()
Undocumented (contribute)

`bpy.ops.object.shade_smooth`()
Undocumented (contribute)

`bpy.ops.object.shape_key_add`(*from_mix=True*)
Add shape key to the object

Parameters **from_mix** (*boolean, (optional)*) – From Mix, Create the new shape key from the existing mix of keys.

`bpy.ops.object.shape_key_clear`()
Clear weights for all shape keys

`bpy.ops.object.shape_key_mirror`()
Undocumented (contribute)

`bpy.ops.object.shape_key_move`(*type='UP'*)
Undocumented (contribute)

Parameters **type** (*enum in ['UP', 'DOWN'], (optional)*) – Type

`bpy.ops.object.shape_key_remove`()
Remove shape key from the object

`bpy.ops.object.shape_key_transfer`(*mode='OFFSET'*, *use_clamp=False*)
Copy another selected objects active shape to this one by applying the relative offsets

Parameters

- **mode** (*enum in ['OFFSET', 'RELATIVE_FACE', 'RELATIVE_EDGE'], (optional)*) – Transformation Mode, Method to apply relative shape positions to the new shape
- **use_clamp** (*boolean, (optional)*) – Clamp Offset, Clamp the transformation to the distance each vertex moves in the original shape.

File op/object.py:388

`bpy.ops.object.slow_parent_clear`()
Clear the object's slow parent

`bpy.ops.object.slow_parent_set`()
Set the object's slow parent

`bpy.ops.object.subdivision_set`(*level=1*, *relative=False*)
Sets a Subdivision Surface Level (1-5)

Parameters

- **level** (*int in [-100, 100], (optional)*) – Level
- **relative** (*boolean, (optional)*) – Relative, Apply the subsurf level as an offset relative to the current level

File op/object.py:173

`bpy.ops.object.text_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)
Add a text object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.object.track_clear`(*type='CLEAR'*)
Clear tracking constraint or flag from object

Parameters **type** (*enum in ['CLEAR', 'CLEAR_KEEP_TRANSFORM'], (optional)*) – Type

`bpy.ops.object.track_set`(*type='DAMPTRACK'*)
Make the object track another object, either by constraint or old way or locked track

Parameters **type** (*enum in ['DAMPTRACK', 'TRACKTO', 'LOCKTRACK'], (optional)*) – Type

`bpy.ops.object.vertex_group_add`()
Undocumented (contribute)

`bpy.ops.object.vertex_group_assign(new=False)`
Undocumented (contribute)

Parameters **new** (*boolean, (optional)*) – New, Assign vertex to new vertex group.

`bpy.ops.object.vertex_group_blend()`
Undocumented (contribute)

`bpy.ops.object.vertex_group_clean(limit=0.01, all_groups=False, keep_single=False)`
Remove Vertex Group assignments which aren't required

Parameters

- **limit** (*float in [0, 1], (optional)*) – Limit, Remove weights under this limit.
- **all_groups** (*boolean, (optional)*) – All Groups, Clean all vertex groups.
- **keep_single** (*boolean, (optional)*) – Keep Single, Keep verts assigned to at least one group when cleaning.

`bpy.ops.object.vertex_group_copy()`
Undocumented (contribute)

`bpy.ops.object.vertex_group_copy_to_linked()`
Copy Vertex Groups to all users of the same Geometry data

`bpy.ops.object.vertex_group_copy_to_selected()`
Copy Vertex Groups to other selected objects with matching indices

`bpy.ops.object.vertex_group_deselect()`
Undocumented (contribute)

`bpy.ops.object.vertex_group_invert(auto_assign=True, auto_remove=True)`
Undocumented (contribute)

Parameters

- **auto_assign** (*boolean, (optional)*) – Add Weights, Add verts from groups that have zero weight before inverting.
- **auto_remove** (*boolean, (optional)*) – Remove Weights, Remove verts from groups that have zero weight after inverting.

`bpy.ops.object.vertex_group_levels(offset=0.0, gain=1.0)`
Undocumented (contribute)

Parameters

- **offset** (*float in [-1, 1], (optional)*) – Offset, Value to add to weights.
- **gain** (*float in [0, inf], (optional)*) – Gain, Value to multiply weights by.

`bpy.ops.object.vertex_group_mirror(mirror_weights=True, flip_group_names=True)`
Mirror all vertex groups, flip weights and/or names, editing only selected vertices, flipping when both sides are selected otherwise copy from unselected

Parameters

- **mirror_weights** (*boolean, (optional)*) – Mirror Weights, Mirror weights.
- **flip_group_names** (*boolean, (optional)*) – Flip Groups, Flip vertex group names.

`bpy.ops.object.vertex_group_move(direction='UP')`
Undocumented (contribute)

Parameters **direction** (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Direction to move, UP or DOWN

`bpy.ops.object.vertex_group_normalize()`
Undocumented (contribute)

`bpy.ops.object.vertex_group_normalize_all(lock_active=True)`
Undocumented (contribute)

Parameters **lock_active** (*boolean, (optional)*) – Lock Active, Keep the values of the active group while normalizing others.

`bpy.ops.object.vertex_group_remove(all=False)`
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Remove from all vertex groups.

`bpy.ops.object.vertex_group_remove_from(all=False)`
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Remove from all vertex groups.

`bpy.ops.object.vertex_group_select()`
Undocumented (contribute)

`bpy.ops.object.vertex_group_set_active(group='')`
Set the active vertex group

Parameters **group** (*enum in [], (optional)*) – Group, Vertex group to set as active.

`bpy.ops.object.vertex_group_sort()`
Sorts vertex groups alphabetically

`bpy.ops.object.vertex_parent_set()`
Parent selected objects to the selected vertices

`bpy.ops.object.visual_transform_apply()`
Apply the object's visual transformation to its data

Outliner Operators

`bpy.ops.outliner.data_operation(type='SELECT')`
Undocumented (contribute)

Parameters **type** (*enum in ['SELECT', 'DESELECT', 'HIDE', 'UNHIDE'], (optional)*) – Data Operation

`bpy.ops.outliner.drivers_add_selected()`
Add drivers to selected items

`bpy.ops.outliner.drivers_delete_selected()`
Delete drivers assigned to selected items

`bpy.ops.outliner.expanded_toggle()`
Expand/Collapse all items

`bpy.ops.outliner.group_operation(type='UNLINK')`
Undocumented (contribute)

Parameters **type** (*enum in ['UNLINK', 'LOCAL', 'LINK', 'TOGVIS', 'TOGSEL', 'TOGREN'], (optional)*) – Group Operation

`bpy.ops.outliner.id_operation(type='UNLINK')`
Undocumented (contribute)

Parameters **type** (*enum in ['UNLINK', 'LOCAL'], (optional)*) – ID data Operation

`bpy.ops.outliner.item_activate(extend=True)`
Handle mouse clicks to activate/select items

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection for activation.

`bpy.ops.outliner.item_openclose(all=True)`
Toggle whether item under cursor is enabled or closed

Parameters **all** (*boolean, (optional)*) – All, Close or open all items.

`bpy.ops.outliner.item_rename()`
Rename item under cursor

`bpy.ops.outliner.keyingset_add_selected()`
Add selected items (blue-grey rows) to active Keying Set

`bpy.ops.outliner.keyingset_remove_selected()`
Remove selected items (blue-grey rows) from active Keying Set

`bpy.ops.outliner.object_operation(type='SELECT')`
Undocumented (contribute)

Parameters **type** (*enum in ['SELECT', 'DESELECT', 'DELETE', 'TOGVIS', 'TOGSEL', 'TOGREN'], (optional)*) – Object Operation

`bpy.ops.outliner.operation()`
Context menu for item operations

`bpy.ops.outliner.renderability_toggle()`
Toggle the renderbility of selected items

`bpy.ops.outliner.scroll_page(up=False)`
Scroll page up or down

Parameters **up** (*boolean, (optional)*) – Up, Scroll up one page.

`bpy.ops.outliner.selectability_toggle()`
Toggle the selectability

`bpy.ops.outliner.selected_toggle()`
Toggle the Outliner selection of items

`bpy.ops.outliner.show_active()`
Adjust the view so that the active Object is shown centered

`bpy.ops.outliner.show_hierarchy()`
Open all object entries and close all others

`bpy.ops.outliner.show_one_level(open=True)`
Expand/collapse all entries by one level

Parameters **open** (*boolean, (optional)*) – Open, Expand all entries one level deep.

`bpy.ops.outliner.visibility_toggle()`
Toggle the visibility of selected items

Paint Operators

`bpy.ops.paint.clone_cursor_set`(*location=(0.0, 0.0, 0.0)*)
Undocumented (contribute)

Parameters **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Cursor location in world space coordinates.

`bpy.ops.paint.face_select_all`(*action='TOGGLE'*)
Change selection for all faces

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.paint.face_select_hide`(*unselected=False*)
Hide selected faces

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

`bpy.ops.paint.face_select_inverse`()
Invert selection of faces

`bpy.ops.paint.face_select_linked`()
Select linked faces

`bpy.ops.paint.face_select_linked_pick`(*extend=False*)
Select linked faces

Parameters **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

`bpy.ops.paint.face_select_reveal`(*unselected=False*)
Reveal hidden faces

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

`bpy.ops.paint.grab_clone`(*delta=(0.0, 0.0)*)
Undocumented (contribute)

Parameters **delta** (*float array of 2 items in [-inf, inf], (optional)*) – Delta, Delta offset of clone image in 0.0..1.0 coordinates.

`bpy.ops.paint.image_from_view`(*filepath=""*)
Make an image from the current 3D view for re-projection

Parameters **filepath** (*string, (optional)*) – File Path, Name of the file

`bpy.ops.paint.image_paint`(*stroke=None*)
Undocumented (contribute)

Parameters **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke

`bpy.ops.paint.image_paint_radial_control`(*initial_value=0.0, new_value=0.0, mode='SIZE', initial_mouse=(0, 0), color=(1.0, 1.0, 1.0, 0.5), texture_color=(1.0, 1.0, 1.0, 1.0)*)
Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode

- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

`bpy.ops.paint.project_image(image='')`

Project an edited render from the active camera back onto the object

Parameters **image** (*enum in [], (optional)*) – Image

`bpy.ops.paint.sample_color(location=(0, 0))`

Undocumented (contribute)

Parameters **location** (*int array of 2 items in [0, inf], (optional)*) – Location, Cursor location in region coordinates.

`bpy.ops.paint.texture_paint_radial_control(initial_value=0.0, new_value=0.0, mode='SIZE', initial_mouse=(0, 0), color=(1.0, 1.0, 1.0, 0.5), texture_color=(1.0, 1.0, 1.0, 1.0))`

Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode
- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

`bpy.ops.paint.texture_paint_toggle()`

Undocumented (contribute)

`bpy.ops.paint.vertex_color_dirt(blur_strength=1.0, blur_iterations=1, clean_angle=180.0, dirt_angle=0.0, dirt_only=False)`

Undocumented (contribute)

Parameters

- **blur_strength** (*float in [0.01, 1], (optional)*) – Blur Strength, Blur strength per iteration
- **blur_iterations** (*int in [0, 40], (optional)*) – Blur Iterations, Number times to blur the colors. (higher blurs more)
- **clean_angle** (*float in [0, 180], (optional)*) – Highlight Angle, Less then 90 limits the angle used in the tonal range
- **dirt_angle** (*float in [0, 180], (optional)*) – Dirt Angle, Less then 90 limits the angle used in the tonal range
- **dirt_only** (*boolean, (optional)*) – Dirt Only, Dont calculate cleans for convex areas

File op/vertexpaint_dirt.py:159

`bpy.ops.paint.vertex_color_set()`

Undocumented (contribute)

bpy.ops.paint.**vertex_paint**(*stroke=None*)
Undocumented (contribute)

Parameters **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke

bpy.ops.paint.**vertex_paint_radial_control**(*initial_value=0.0, new_value=0.0, mode='SIZE', initial_mouse=(0, 0), color=(1.0, 1.0, 1.0, 0.5), texture_color=(1.0, 1.0, 1.0, 1.0)*)
Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode
- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

bpy.ops.paint.**vertex_paint_toggle**()
Undocumented (contribute)

bpy.ops.paint.**weight_from_bones**(*type='AUTOMATIC'*)
Undocumented (contribute)

Parameters **type** (*enum in ['AUTOMATIC', 'ENVELOPES'], (optional)*) – Type, Method to use for assigning weights.

bpy.ops.paint.**weight_paint**(*stroke=None*)
Undocumented (contribute)

Parameters **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke

bpy.ops.paint.**weight_paint_radial_control**(*initial_value=0.0, new_value=0.0, mode='SIZE', initial_mouse=(0, 0), color=(1.0, 1.0, 1.0, 0.5), texture_color=(1.0, 1.0, 1.0, 1.0)*)
Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode
- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

bpy.ops.paint.**weight_paint_toggle**()
Undocumented (contribute)

bpy.ops.paint.**weight_set**()
Undocumented (contribute)

Particle Operators

bpy.ops.particle.**brush_edit**(*stroke=None*)
Undocumented (contribute)

Parameters **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke

bpy.ops.particle.**brush_radial_control**(*initial_value=0.0*, *new_value=0.0*, *mode='SIZE'*, *initial_mouse=(0, 0)*, *color=(1.0, 1.0, 1.0, 0.5)*, *texture_color=(1.0, 1.0, 1.0, 1.0)*)
Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode
- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

bpy.ops.particle.**connect_hair**(*all=False*)
Connect hair to the emitter mesh

Parameters **all** (*boolean, (optional)*) – All hair, Connect all hair systems to the emitter mesh

bpy.ops.particle.**delete**(*type='PARTICLE'*)
Undocumented (contribute)

Parameters **type** (*enum in ['PARTICLE', 'KEY'], (optional)*) – Type, Delete a full particle or only keys.

bpy.ops.particle.**disconnect_hair**(*all=False*)
Disconnect hair from the emitter mesh

Parameters **all** (*boolean, (optional)*) – All hair, Disconnect all hair systems from the emitter mesh

bpy.ops.particle.**dupliob_copy**()
Duplicate the current dupliobject

bpy.ops.particle.**dupliob_move_down**()
Move dupli object down in the list

bpy.ops.particle.**dupliob_move_up**()
Move dupli object up in the list

bpy.ops.particle.**dupliob_remove**()
Remove the selected dupliobject

bpy.ops.particle.**edited_clear**()
Undocumented (contribute)

bpy.ops.particle.**hide**(*unselected=False*)
Undocumented (contribute)

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

bpy.ops.particle.**mirror**()
Undocumented (contribute)

`bpy.ops.particle.new()`
Add new particle settings

`bpy.ops.particle.new_target()`
Add a new particle target

`bpy.ops.particle.particle_edit_toggle()`
Undocumented (contribute)

`bpy.ops.particle.rekey(keys=2)`
Undocumented (contribute)

Parameters **keys** (*int in [2, inf], (optional)*) – Number of Keys

`bpy.ops.particle.remove_doubles(threshold=0.0002)`
Undocumented (contribute)

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold, Threshold distance withing which particles are removed

`bpy.ops.particle.reveal()`
Undocumented (contribute)

`bpy.ops.particle.select_all(action='TOGGLE')`
Undocumented (contribute)

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.particle.select_inverse()`
Undocumented (contribute)

`bpy.ops.particle.select_less()`
Undocumented (contribute)

`bpy.ops.particle.select_linked(deselect=False, location=(0, 0))`
Undocumented (contribute)

Parameters

- **deselect** (*boolean, (optional)*) – Deselect, Deselect linked keys rather than selecting them.
- **location** (*int array of 2 items in [0, inf], (optional)*) – Location

`bpy.ops.particle.select_more()`
Undocumented (contribute)

`bpy.ops.particle.select_roots()`
Undocumented (contribute)

`bpy.ops.particle.select_tips()`
Undocumented (contribute)

`bpy.ops.particle.subdivide()`
Undocumented (contribute)

`bpy.ops.particle.target_move_down()`
Move particle target down in the list

`bpy.ops.particle.target_move_up()`
Move particle target up in the list

`bpy.ops.particle.target_remove()`
Remove the selected particle target

bpy.ops.particle.**weight_set**(*factor=1.0*)
Undocumented (contribute)

Parameters **factor** (*float in [0, 1], (optional)*) – Factor

Pose Operators

bpy.ops.pose.**armature_apply**()
Apply the current pose as the new rest pose

bpy.ops.pose.**armature_layers**(*layers=(False, False)*)
Change the visible armature layers

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers to make visible

bpy.ops.pose.**autoside_names**(*axis='XAXIS'*)
Automatically renames the selected bones according to which side of the target axis they fall on

Parameters **axis** (*enum in ['XAXIS', 'YAXIS', 'ZAXIS'], (optional)*) – Axis, Axis tag names with.

bpy.ops.pose.**bone_layers**(*layers=(False, False)*)
Change the layers that the selected bones belong to

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers that bone belongs to

bpy.ops.pose.**breakdown**(*prev_frame=0, next_frame=0, percentage=0.5*)
Create a suitable breakdown pose on the current frame

Parameters

- **prev_frame** (*int in [-300000, 300000], (optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000], (optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.
- **percentage** (*float in [0, 1], (optional)*) – Percentage, Weighting factor for the sliding operation

bpy.ops.pose.**constraint_add**(*type=''*)
Add a constraint to the active bone

Parameters **type** (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

bpy.ops.pose.**constraint_add_with_targets**(*type=''*)
Add a constraint to the active bone, with target (where applicable) set to the selected Objects/Bones

Parameters **type** (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO',*

'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)) – Type

`bpy.ops.pose.constraints_clear()`
Clear all the constraints for the selected bones

`bpy.ops.pose.constraints_copy()`
Copy constraints to other selected bones.

`bpy.ops.pose.copy()`
Copies the current pose of the selected bones to copy/paste buffer

`bpy.ops.pose.flags_set(type='DRAWWIRE', mode='CLEAR')`
Set flags for armature bones

Parameters

- **type** (*enum in ['DRAWWIRE', 'DEFORM', 'MULT_VG', 'HINGE', 'NO_SCALE', 'LOCKED'], (optional)*) – Type
- **mode** (*enum in ['CLEAR', 'ENABLE', 'TOGGLE'], (optional)*) – Mode

`bpy.ops.pose.flip_names()`
Flips (and corrects) the axis suffixes of the the names of selected bones

`bpy.ops.pose.group_add()`
Add a new bone group

`bpy.ops.pose.group_assign(type=0)`
Add selected bones to the chosen bone group

Parameters **type** (*int in [0, 10], (optional)*) – Bone Group Index

`bpy.ops.pose.group_deselect()`
Deselect bones of active Bone Group

`bpy.ops.pose.group_remove()`
Removes the active bone group

`bpy.ops.pose.group_select()`
Select bones in active Bone Group

`bpy.ops.pose.group_unassign()`
Remove selected bones from all bone groups

`bpy.ops.pose.hide(unselected=False)`
Tag selected bones to not be visible in Pose Mode

Parameters **unselected** (*boolean, (optional)*) – Unselected

`bpy.ops.pose.ik_add(with_targets=True)`
Add IK Constraint to the active Bone

Parameters **with_targets** (*boolean, (optional)*) – With Targets, Assign IK Constraint with targets derived from the select bones/objects

`bpy.ops.pose.ik_clear()`
Remove all IK Constraints from selected bones

`bpy.ops.pose.loc_clear()`
Reset locations of selected bones to their default values

`bpy.ops.pose.paste(flipped=False, selected_mask=False)`
Pastes the stored pose on to the current pose

Parameters

- **flipped** (*boolean, (optional)*) – Flipped on X-Axis, Paste the stored pose flipped on to current pose
- **selected_mask** (*boolean, (optional)*) – On Selected Only, Only paste the stored post on to selected bones in the current pose

`bpy.ops.pose.paths_calculate()`
Calculate paths for the selected bones

`bpy.ops.pose.paths_clear()`
Clear path caches for selected bones

`bpy.ops.pose.push(prev_frame=0, next_frame=0, percentage=0.5)`
Exaggerate the current pose

Parameters

- **prev_frame** (*int in [-300000, 300000], (optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000], (optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.
- **percentage** (*float in [0, 1], (optional)*) – Percentage, Weighting factor for the sliding operation

`bpy.ops.pose.quaternions_flip()`
Flip quaternion values to achieve desired rotations, while maintaining the same orientations

`bpy.ops.pose.relax(prev_frame=0, next_frame=0, percentage=0.5)`
Make the current pose more similar to its surrounding ones

Parameters

- **prev_frame** (*int in [-300000, 300000], (optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000], (optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.
- **percentage** (*float in [0, 1], (optional)*) – Percentage, Weighting factor for the sliding operation

`bpy.ops.pose.reveal()`
Unhide all bones that have been tagged to be hidden in Pose Mode

`bpy.ops.pose.rot_clear()`
Reset rotations of selected bones to their default values

`bpy.ops.pose.scale_clear()`
Reset scaling of selected bones to their default values

`bpy.ops.pose.select_all(action='TOGGLE')`
Toggle selection status of all bones

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.pose.select_constraint_target()`
Select bones used as targets for the currently selected bones

`bpy.ops.pose.select_flip_active()`
Activate the bone with a flipped name.

`bpy.ops.pose.select_grouped`(*extend=False*, *type='LAYER'*)
Select all visible bones grouped by similar properties

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['LAYER', 'GROUP'], (optional)*) – Type

`bpy.ops.pose.select_hierarchy`(*direction='PARENT'*, *extend=False*)
Select immediate parent/children of selected bones

Parameters

- **direction** (*enum in ['PARENT', 'CHILD'], (optional)*) – Direction
- **extend** (*boolean, (optional)*) – Add to Selection

`bpy.ops.pose.select_inverse`()
Flip the selection status of bones (selected -> unselected, unselected -> selected)

`bpy.ops.pose.select_linked`(*extend=False*)
Select bones related to selected ones by parent/child relationships

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

`bpy.ops.pose.select_parent`()
Select bones that are parents of the currently selected bones

`bpy.ops.pose.transforms_clear`()
Reset location, rotation, and scaling of selected bones to their default values

`bpy.ops.pose.visual_transform_apply`()
Apply final constrained position of pose bones to their transform.

Poselib Operators

`bpy.ops.poselib.action_sanitise`()
Make action suitable for use as a Pose Library

`bpy.ops.poselib.apply_pose`(*pose_index=-1*)
Apply specified Pose Library pose to the rig

Parameters **pose_index** (*int in [-2, inf], (optional)*) – Pose, Index of the pose to apply (-2 for no change to pose, -1 for poselib active pose)

`bpy.ops.poselib.browse_interactive`(*pose_index=-1*)
Interactively browse poses in 3D-View

Parameters **pose_index** (*int in [-2, inf], (optional)*) – Pose, Index of the pose to apply (-2 for no change to pose, -1 for poselib active pose)

`bpy.ops.poselib.new`()
Add New Pose Library to active Object

`bpy.ops.poselib.pose_add`(*frame=1*, *name="Pose"*)
Add the current Pose to the active Pose Library

Parameters

- **frame** (*int in [0, inf], (optional)*) – Frame, Frame to store pose on

- **name** (*string, (optional)*) – Pose Name, Name of newly added Pose

`bpy.ops.poselib.pose_remove`(*pose='DEFAULT'*)
Remove nth pose from the active Pose Library

Parameters **pose** (*enum in ['DEFAULT'], (optional)*) – Pose, The pose to remove

`bpy.ops.poselib.pose_rename`(*name="RenamedPose", pose=''*)
Rename specified pose from the active Pose Library

Parameters

- **name** (*string, (optional)*) – New Pose Name, New name for pose
- **pose** (*enum in [], (optional)*) – Pose, The pose to rename

`bpy.ops.poselib.unlink`()
Remove Pose Library from active Object

Ptcache Operators

`bpy.ops.ptcache.add`()
Undocumented (contribute)

`bpy.ops.ptcache.bake`(*bake=False*)
Undocumented (contribute)

Parameters **bake** (*boolean, (optional)*) – Bake

`bpy.ops.ptcache.bake_all`(*bake=True*)
Undocumented (contribute)

Parameters **bake** (*boolean, (optional)*) – Bake

`bpy.ops.ptcache.bake_from_cache`()
Undocumented (contribute)

`bpy.ops.ptcache.free_bake`()
Undocumented (contribute)

`bpy.ops.ptcache.free_bake_all`()
Undocumented (contribute)

`bpy.ops.ptcache.remove`()
Undocumented (contribute)

Render Operators

`bpy.ops.render.netclientanim`()
Start rendering an animation on network

File io/netrender/operators.py:95

`bpy.ops.render.netclientblacklistslave`()
Operator documentation text, will be used for the operator tooltip and python docs.

File io/netrender/operators.py:240

`bpy.ops.render.netclientcancel`()
Cancel the selected network rendering job.

File io/netrender/operators.py:348

`bpy.ops.render.netclientcancelall()`
Cancel all running network rendering jobs.

File io/netrender/operators.py:377

`bpy.ops.render.netclientdownload()`
Download render results from the network

File io/netrender/operators.py:406

`bpy.ops.render.netclientscan()`
Listen on network for master server broadcasting its address and port.

File io/netrender/operators.py:493

`bpy.ops.render.netclientsend()`
Send Render Job to the Network

File io/netrender/operators.py:139

`bpy.ops.render.netclientsendframe()`
Send Render Job with current frame to the Network

File io/netrender/operators.py:169

`bpy.ops.render.netclientslaves()`
Refresh status about available Render slaves

File io/netrender/operators.py:301

`bpy.ops.render.netclientstart()`
Start network rendering service

File io/netrender/operators.py:122

`bpy.ops.render.netclientstatus()`
Refresh the status of the current jobs

File io/netrender/operators.py:199

`bpy.ops.render.netclientvcsguess()`
Guess VCS setting for the current file

File io/netrender/operators.py:516

`bpy.ops.render.netclientweb()`
Open new window with information about running rendering jobs

File io/netrender/operators.py:549

`bpy.ops.render.netclientwhitelistslave()`
Operator documentation text, will be used for the operator tooltip and python docs.

File io/netrender/operators.py:270

`bpy.ops.render.netslavebake()`
NEED DESCRIPTION

File io/netrender/operators.py:40

`bpy.ops.render.opengl(animation=False, write_still=False, view_context=True)`
OpenGL render active viewport

Parameters

- **animation** (*boolean, (optional)*) – Animation, Render files from the animation range of this scene

- **write_still** (*boolean, (optional)*) – Write Image, Save rendered the image to the output path (used only when animation is disabled)
- **view_context** (*boolean, (optional)*) – View Context, Use the current 3D view for rendering, else use scene settings.

`bpy.ops.render.play_rendered_anim()`
Plays back rendered frames/movies using an external player.

File op/screen_play_rendered_anim.py:72

`bpy.ops.render.preset_add(name="", remove_active=False)`
Add a Render Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

`bpy.ops.render.render(animation=False, write_still=False, layer="", scene="")`
Render active scene

Parameters

- **animation** (*boolean, (optional)*) – Animation, Render files from the animation range of this scene
- **write_still** (*boolean, (optional)*) – Write Image, Save rendered the image to the output path (used only when animation is disabled)
- **layer** (*string, (optional)*) – Render Layer, Single render layer to re-render
- **scene** (*string, (optional)*) – Scene, Re-render single layer in this scene

`bpy.ops.render.view_cancel()`
Cancel show render view

`bpy.ops.render.view_show()`
Toggle show render view

Scene Operators

`bpy.ops.scene.delete()`
Delete active scene

`bpy.ops.scene.new(type='EMPTY')`
Add new scene by type

Parameters **type** (*enum in ['EMPTY', 'LINK_OBJECTS', 'LINK_OBJECT_DATA', 'FULL_COPY'], (optional)*) – Type

`bpy.ops.scene.render_layer_add()`
Add a render layer

`bpy.ops.scene.render_layer_remove()`
Remove the selected render layer

Screen Operators

`bpy.ops.screen.actionzone(modifier=0)`
Handle area action zones for mouse actions/gestures

Parameters **modifier** (*int in [0, 2], (optional)*) – modifier, modifier state

bpy.ops.screen.**animation_cancel**()
Cancel animation, returning to the original frame

bpy.ops.screen.**animation_play**(*reverse=False*, *sync=False*)
Play animation

Parameters

- **reverse** (*boolean, (optional)*) – Play in Reverse, Animation is played backwards
- **sync** (*boolean, (optional)*) – Sync, Drop frames to maintain framerate

bpy.ops.screen.**animation_step**()
Step through animation by position

bpy.ops.screen.**area_dupli**()
Duplicate selected area into new window

bpy.ops.screen.**area_join**(*min_x=-100*, *min_y=-100*, *max_x=-100*, *max_y=-100*)
Join selected areas into new window

Parameters

- **min_x** (*int in [-inf, inf], (optional)*) – X 1
- **min_y** (*int in [-inf, inf], (optional)*) – Y 1
- **max_x** (*int in [-inf, inf], (optional)*) – X 2
- **max_y** (*int in [-inf, inf], (optional)*) – Y 2

bpy.ops.screen.**area_move**(*x=0*, *y=0*, *delta=0*)
Move selected area edges

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y
- **delta** (*int in [-inf, inf], (optional)*) – Delta

bpy.ops.screen.**area_options**()
Operations for splitting and merging

bpy.ops.screen.**area_split**(*direction='HORIZONTAL'*, *factor=0.5*, *mouse_x=-100*, *mouse_y=-100*)
Split selected area into new windows

Parameters

- **direction** (*enum in ['HORIZONTAL', 'VERTICAL'], (optional)*) – Direction
- **factor** (*float in [0, 1], (optional)*) – Factor
- **mouse_x** (*int in [-inf, inf], (optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf], (optional)*) – Mouse Y

bpy.ops.screen.**area_swap**()
Swap selected areas screen positions

bpy.ops.screen.**back_to_previous**()
Revert back to the original screen layout, before fullscreen area overlay

bpy.ops.screen.**delete**()
Delete active screen

bpy.ops.screen.**frame_jump**(*end=False*)
Jump to first/last frame in frame range

Parameters **end** (*boolean, (optional)*) – Last Frame, Jump to the last frame of the frame range.

bpy.ops.screen.**frame_offset**(*delta=0*)
Undocumented (contribute)

Parameters **delta** (*int in [-inf, inf], (optional)*) – Delta

bpy.ops.screen.**header_flip**()
Undocumented (contribute)

bpy.ops.screen.**header_toolbox**()
Display header region toolbox

bpy.ops.screen.**keyframe_jump**(*next=True*)
Jump to previous/next keyframe

Parameters **next** (*boolean, (optional)*) – Next Keyframe

bpy.ops.screen.**new**()
Add a new screen

bpy.ops.screen.**redo_last**()
Display menu for last action performed

bpy.ops.screen.**region_flip**()
Undocumented (contribute)

bpy.ops.screen.**region_quadview**()
Split selected area into camera, front, right & top views

bpy.ops.screen.**region_scale**()
Scale selected area

bpy.ops.screen.**repeat_history**(*index=0*)
Display menu for previous actions performed

Parameters **index** (*int in [0, inf], (optional)*) – Index

bpy.ops.screen.**repeat_last**()
Repeat last action

bpy.ops.screen.**screen_full_area**()
Toggle display selected area as fullscreen

bpy.ops.screen.**screen_set**(*delta=0*)
Cycle through available screens

Parameters **delta** (*int in [-inf, inf], (optional)*) – Delta

bpy.ops.screen.**screencast**(*filepath=""*, *full=True*)
Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – filepath
- **full** (*boolean, (optional)*) – Full Screen

bpy.ops.screen.**screenshot**(*filepath=""*, *check_existing=True*, *filter_blender=False*, *filter_image=True*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=9*, *full=True*)
Undocumented (contribute)

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **full** (*boolean, (optional)*) – Full Screen

`bpy.ops.screen.spacedata_cleanup()`
Remove unused settings for invisible editors

`bpy.ops.screen.userpref_show()`
Show/hide user preferences

Script Operators

`bpy.ops.script.execute_preset(filepath="", menu_idname="")`
Executes a preset

Parameters

- **filepath** (*string, (optional)*) – Path, Path of the Python file to execute
- **menu_idname** (*string, (optional)*) – Menu ID Name, ID name of the menu this was called from

File op/presets.py:140

`bpy.ops.script.python_file_run(filepath="")`
Run Python file

Parameters **filepath** (*string, (optional)*) – Path

`bpy.ops.script.reload()`
Reload Scripts

Sculpt Operators

`bpy.ops.sculpt.brush_stroke`(*stroke=None*, *mode='NORMAL'*, *ignore_background_click=False*)
Undocumented (contribute)

Parameters

- **stroke** (Collection of `OperatorStrokeElement`, (optional)) – Stroke
- **mode** (*enum in ['NORMAL', 'INVERT', 'SMOOTH'], (optional)*) – Sculpt Stroke Mode, Action taken when a sculpt stroke is made
- **ignore_background_click** (*boolean, (optional)*) – Ignore Background Click, Clicks on the background do not start the stroke

`bpy.ops.sculpt.radial_control`(*initial_value=0.0*, *new_value=0.0*, *mode='SIZE'*, *initial_mouse=(0, 0)*, *color=(1.0, 1.0, 1.0, 0.5)*, *texture_color=(1.0, 1.0, 1.0, 1.0)*)
Undocumented (contribute)

Parameters

- **initial_value** (*float in [0, inf], (optional)*) – Initial Value
- **new_value** (*float in [0, inf], (optional)*) – New Value
- **mode** (*enum in ['SIZE', 'STRENGTH', 'ANGLE'], (optional)*) – Mode
- **initial_mouse** (*int array of 2 items in [-inf, inf], (optional)*) – Initial Mouse
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Radial control color
- **texture_color** (*float array of 4 items in [0, inf], (optional)*) – Texture Color, Radial control texture color

`bpy.ops.sculpt.sculptmode_toggle`()
Undocumented (contribute)

`bpy.ops.sculpt.set_persistent_base`()
Undocumented (contribute)

Sequencer Operators

`bpy.ops.sequencer.copy`()
Undocumented (contribute)

`bpy.ops.sequencer.crossfade_sounds`()
Do crossfading volume animation of two selected sound strips.

File op/sequencer.py:40

`bpy.ops.sequencer.cut`(*frame=0*, *type='SOFT'*, *side='BOTH'*)
Cut the selected strips

Parameters

- **frame** (*int in [-inf, inf], (optional)*) – Frame, Frame where selected strips will be cut
- **type** (*enum in ['SOFT', 'HARD'], (optional)*) – Type, The type of cut operation to perform on strips
- **side** (*enum in ['LEFT', 'RIGHT', 'BOTH'], (optional)*) – Side, The side that remains selected after cutting

`bpy.ops.sequencer.cut_multicam(camera=1)`
Cut multicam strip and select camera.

Parameters **camera** (*int in [1, 32], (optional)*) – Camera

File op/sequencer.py:94

`bpy.ops.sequencer.deinterlace_selected_movies()`
Deinterlace all selected movie sources.

File op/sequencer.py:129

`bpy.ops.sequencer.delete()`
Erase selected strips from the sequencer

`bpy.ops.sequencer.duplicate(mode=1)`
Duplicate the selected strips

Parameters **mode** (*int in [0, inf], (optional)*) – Mode

`bpy.ops.sequencer.effect_strip_add(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=9, relative_path=False, frame_start=0, frame_end=0, channel=1, replace_sel=True, type='CROSS', color=(0.0, 0.0, 0.0))`
Add an effect to the sequencer, most are applied on top of existing strips

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **frame_end** (*int in [-inf, inf], (optional)*) – End Frame, End frame for the color strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection

- **type** (*enum in ['CROSS', 'ADD', 'SUBTRACT', 'ALPHA_OVER', 'ALPHA_UNDER', 'GAMMA_CROSS', 'MULTIPLY', 'OVER_DROP', 'PLUGIN', 'WIPE', 'GLOW', 'TRANSFORM', 'COLOR', 'SPEED', 'MULTICAM'], (optional)*) – Type, Sequencer effect type
- **color** (*float array of 3 items in [0, 1], (optional)*) – Color, Initialize the strip with this color (only used when type='COLOR')

`bpy.ops.sequencer.image_strip_add`(*directory=""*, *filter_blender=False*, *filter_image=True*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=9*, *relative_path=False*, *frame_start=0*, *frame_end=0*, *channel=1*, *replace_sel=True*, *files=None*)

Add an image or image sequence to the sequencer

Parameters

- **directory** (*string, (optional)*) – Directory, Directory of the file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **frame_end** (*int in [-inf, inf], (optional)*) – End Frame, End frame for the color strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (Collection of `OperatorFileListElement`, (optional)) – Files

`bpy.ops.sequencer.images_separate`(*length=1*)

On image sequences strips, it return a strip for each image

Parameters **length** (*int in [1, 1000], (optional)*) – Length, Length of each frame

`bpy.ops.sequencer.lock`()

Lock the active strip so that it can't be transformed

`bpy.ops.sequencer.meta_make`()

Group selected strips into a metastrip

`bpy.ops.sequencer.meta_separate`()

Put the contents of a metastrip back in the sequencer

`bpy.ops.sequencer.meta_toggle()`
Toggle a metastrip (to edit enclosed strips)

`bpy.ops.sequencer.movie_strip_add(filepath="", filter_blender=False, filter_image=False, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, frame_start=0, channel=1, replace_sel=True, files=None, sound=True)`
Add a movie strip to the sequencer

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (Collection of `OperatorFileListElement`, (optional)) – Files
- **sound** (*boolean, (optional)*) – Sound, Load sound with the movie

`bpy.ops.sequencer.mute(unselected=False)`
Mute selected strips

Parameters **unselected** (*boolean, (optional)*) – Unselected, Mute unselected rather than selected strips.

`bpy.ops.sequencer.next_edit()`
Move frame to next edit point

`bpy.ops.sequencer.paste()`
Undocumented (contribute)

`bpy.ops.sequencer.previous_edit()`
Move frame to previous edit point

`bpy.ops.sequencer.properties()`
Open sequencer properties panel

`bpy.ops.sequencer.reassign_inputs()`
Reassign the inputs for the effects strip

`bpy.ops.sequencer.refresh_all()`
Refresh the sequencer editor

`bpy.ops.sequencer.reload()`
Reload strips in the sequencer

`bpy.ops.sequencer.rendersize()`
Set render size and aspect from active sequence

`bpy.ops.sequencer.scene_strip_add(frame_start=0, channel=1, replace_sel=True, scene='')`
Add a strip to the sequencer using a blender scene as a source

Parameters

- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **scene** (*enum in [], (optional)*) – Scene

`bpy.ops.sequencer.select(extend=False, linked_handle=False, left_right=False, linked_time=False)`
Select a strip (last selected becomes the "active strip")

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend the selection.
- **linked_handle** (*boolean, (optional)*) – Linked Handle, Select handles next to the active strip.
- **left_right** (*boolean, (optional)*) – Left/Right, select based on the frame side the cursor is on.
- **linked_time** (*boolean, (optional)*) – Linked Time, Select other strips at the same time.

`bpy.ops.sequencer.select_active_side(side='BOTH')`
Select strips on the nominated side of the active strip

Parameters **side** (*enum in ['LEFT', 'RIGHT', 'BOTH'], (optional)*) – Side, The side of the handle that is selected

`bpy.ops.sequencer.select_all_toggle()`
Select or deselect all strips

`bpy.ops.sequencer.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Enable border select mode

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.sequencer.select_handles(side='BOTH')`
Select manipulator handles on the sides of the selected strip

Parameters side (*enum in ['LEFT', 'RIGHT', 'BOTH'], (optional)*) – Side, The side of the handle that is selected

`bpy.ops.sequencer.select_inverse()`
Select unselected strips

`bpy.ops.sequencer.select_less()`
Shrink the current selection of adjacent selected strips

`bpy.ops.sequencer.select_linked()`
Select all strips adjacent to the current selection

`bpy.ops.sequencer.select_linked_pick(extend=False)`
Select a chain of linked strips nearest to the mouse pointer

Parameters extend (*boolean, (optional)*) – Extend, extend the selection

`bpy.ops.sequencer.select_more()`
Select more strips adjacent to the current selection

`bpy.ops.sequencer.snap(frame=0)`
Frame where selected strips will be snapped

Parameters frame (*int in [-inf, inf], (optional)*) – Frame, Frame where selected strips will be snapped

`bpy.ops.sequencer.sound_strip_add(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=True, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, frame_start=0, channel=1, replace_sel=True, files=None, cache=False)`
Add a sound strip to the sequencer

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into

- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (Collection of `OperatorFileListElement`, (optional)) – Files
- **cache** (*boolean, (optional)*) – Cache, Cache the sound in memory.

`bpy.ops.sequencer.swap(side='RIGHT')`
Swap active strip with strip to the left

Parameters **side** (*enum in ['LEFT', 'RIGHT'], (optional)*) – Side, Side of the strip to swap

`bpy.ops.sequencer.swap_data()`
Swap 2 sequencer strips

`bpy.ops.sequencer.swap_inputs()`
Swap the first two inputs for the effects strip

`bpy.ops.sequencer.unlock()`
Unlock the active strip so that it can't be transformed

`bpy.ops.sequencer.unmute(unselected=False)`
Un-Mute unselected rather than selected strips

Parameters **unselected** (*boolean, (optional)*) – Unselected, UnMute unselected rather than selected strips.

`bpy.ops.sequencer.view_all()`
View all the strips in the sequencer

`bpy.ops.sequencer.view_all_preview()`
Zoom preview to fit in the area

`bpy.ops.sequencer.view_ghost_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Enable border select mode

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.sequencer.view_selected()`
Zoom the sequencer on the selected strips

`bpy.ops.sequencer.view_toggle()`
Toggle between sequencer views (sequence, preview, both)

`bpy.ops.sequencer.view_zoom_ratio(ratio=1.0)`
Change zoom ratio of sequencer preview

Parameters **ratio** (*float in [0, inf], (optional)*) – Ratio, Zoom ratio, 1.0 is 1:1, higher is zoomed in, lower is zoomed out.

Sketch Operators

`bpy.ops.sketch.cancel_stroke()`
Undocumented (contribute)

`bpy.ops.sketch.convert()`
Undocumented (contribute)

`bpy.ops.sketch.delete()`
Undocumented (contribute)

`bpy.ops.sketch.draw_preview(snap=False)`
Undocumented (contribute)

Parameters **snap** (*boolean, (optional)*) – Snap

`bpy.ops.sketch.draw_stroke(snap=False)`
Undocumented (contribute)

Parameters **snap** (*boolean, (optional)*) – Snap

`bpy.ops.sketch.finish_stroke()`
Undocumented (contribute)

`bpy.ops.sketch.gesture(snap=False)`
Undocumented (contribute)

Parameters **snap** (*boolean, (optional)*) – Snap

`bpy.ops.sketch.select()`
Undocumented (contribute)

Sound Operators

`bpy.ops.sound.open(filepath="", filter_blender=False, filter_image=False, filter_movie=True, filter_python=False, filter_font=False, filter_sound=True, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, cache=False)`
Load a sound file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **cache** (*boolean, (optional)*) – Cache, Cache the sound in memory.

`bpy.ops.sound.pack()`
Pack the sound into the current blend file

`bpy.ops.sound.unpack(method='USE_LOCAL', id="")`
Unpack the sound to the samples filename

Parameters

- **method** (*enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL'], (optional)*) – Method, How to unpack.
- **id** (*string, (optional)*) – Sound Name, Sound datablock name to unpack.

Surface Operators

`bpy.ops.surface.primitive_nurbs_surface_circle_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Construct a Nurbs surface Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.surface.primitive_nurbs_surface_curve_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False))`
Construct a Nurbs surface Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object

- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.surface.primitive_nurbs_surface_cylinder_add`(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs surface Cylinder

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.surface.primitive_nurbs_surface_sphere_add`(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs surface Sphere

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.surface.primitive_nurbs_surface_surface_add`(*view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs surface Patch

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

`bpy.ops.surface.primitive_nurbs_surface_torus_add`(*view_align=False*, *enter_editmode=False*, *location=(0.0, 0.0, 0.0)*, *rotation=(0.0, 0.0, 0.0)*, *layers=(False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)*)

Construct a Nurbs surface Torus

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view.
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object.
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object.
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

Text Operators

`bpy.ops.text.comment`()

Convert selected text to comment

`bpy.ops.text.convert_whitespace`(*type='SPACES'*)

Convert whitespaces by type

Parameters **type** (*enum in ['SPACES', 'TABS'], (optional)*) – type, Type of whitespace to convert to.

`bpy.ops.text.copy`()

Copy selected text to clipboard

`bpy.ops.text.cursor_set`(*x=False*, *y=False*)

Set cursor position

Parameters

- **x** (*boolean, (optional)*) – X, X-coordinate to set cursor to.

- **y** (*boolean, (optional)*) – Y, X-coordinate to set cursor to.

`bpy.ops.text.cut()`
Cut selected text to clipboard

`bpy.ops.text.delete(type='NEXT_CHARACTER')`
Delete text by cursor position

Parameters **type** (*enum in ['NEXT_CHARACTER', 'PREVIOUS_CHARACTER', 'NEXT_WORD', 'PREVIOUS_WORD'], (optional)*) – Type, Which part of the text to delete.

`bpy.ops.text.find()`
Find specified text

`bpy.ops.text.find_set_selected()`
Find specified text and set as selected

`bpy.ops.text.indent()`
Indent selected text

`bpy.ops.text.insert(text="")`
Insert text at cursor position

Parameters **text** (*string, (optional)*) – Text, Text to insert at the cursor position.

`bpy.ops.text.jump(line=1)`
Jump cursor to line

Parameters **line** (*int in [1, inf], (optional)*) – Line, Line number to jump to.

`bpy.ops.text.line_break()`
Insert line break at cursor position

`bpy.ops.text.line_number()`
The current line number

`bpy.ops.text.make_internal()`
Make active text file internal

`bpy.ops.text.mark_all()`
Mark all specified text

`bpy.ops.text.markers_clear()`
Clear all markers

`bpy.ops.text.move(type='LINE_BEGIN')`
Move cursor to position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'FILE_TOP', 'FILE_BOTTOM', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], (optional)*) – Type, Where to move cursor to.

`bpy.ops.text.move_select(type='LINE_BEGIN')`
Make selection from current cursor position to new cursor position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'FILE_TOP', 'FILE_BOTTOM', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], (optional)*) – Type, Where to move cursor to, to make a selection.

`bpy.ops.text.new()`
Create a new text data block

`bpy.ops.text.next_marker()`
Move to next marker

`bpy.ops.text.open(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=True, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, internal=False)`
Open a new text data block

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **internal** (*boolean, (optional)*) – Make internal, Make text file internal after loading

`bpy.ops.text.overwrite_toggle()`
Toggle overwrite while typing

`bpy.ops.text.paste(selection=False)`
Paste text from clipboard

Parameters **selection** (*boolean, (optional)*) – Selection, Paste text selected elsewhere rather than copied, X11 only.

`bpy.ops.text.previous_marker()`
Move to previous marker

`bpy.ops.text.properties()`
Toggle text properties panel

`bpy.ops.text.refresh_pyconstraints()`
Refresh all pyconstraints

`bpy.ops.text.reload()`
Reload active text data block from its file

`bpy.ops.text.replace()`
Replace text with the specified text

`bpy.ops.text.replace_set_selected()`
Replace text with specified text and set as selected

`bpy.ops.text.resolve_conflict(resolution='IGNORE')`
When external text is out of sync, resolve the conflict

Parameters resolution (*enum in ['IGNORE', 'RELOAD', 'SAVE', 'MAKE_INTERNAL'], (optional)*) – Resolution, How to solve conflict due to different in internal and external text.

`bpy.ops.text.run_script()`
Run active script

`bpy.ops.text.save()`
Save active text data block

`bpy.ops.text.save_as(filepath="", check_existing=True, filter_blender=False, filter_image=False, filter_movie=False, filter_python=True, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9)`
Save active text file with options

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

`bpy.ops.text.scroll(lines=1)`
Scroll text screen

Parameters lines (*int in [-inf, inf], (optional)*) – Lines, Number of lines to scroll.

`bpy.ops.text.scroll_bar(lines=1)`
Scroll text screen

Parameters lines (*int in [-inf, inf], (optional)*) – Lines, Number of lines to scroll.

`bpy.ops.text.select_all()`
Select all text

`bpy.ops.text.select_line()`
Select text by line

`bpy.ops.text.select_word()`
Select word under cursor

`bpy.ops.text.selection_set(select=False)`
Set cursor selection

Parameters **select** (*boolean, (optional)*) – Select, Set selection end rather than cursor.

`bpy.ops.text.to_3d_object(split_lines=False)`
Create 3d text object from active text data block

Parameters **split_lines** (*boolean, (optional)*) – Split Lines, Create one object per line in the text.

`bpy.ops.text.uncomment()`
Convert selected comment to text

`bpy.ops.text.unindent()`
Unindent selected text

`bpy.ops.text.unlink()`
Unlink active text data block

Texture Operators

`bpy.ops.texture.envmap_clear()`
Discard the environment map and free it from memory

`bpy.ops.texture.envmap_clear_all()`
Discard all environment maps in the .blend file and free them from memory

`bpy.ops.texture.envmap_save(filepath="", check_existing=True, filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)`
Save the current generated Environment map to an image file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

`bpy.ops.texture.new()`
Add a new texture

`bpy.ops.texture.slot_copy()`
Copy the material texture settings and nodes

`bpy.ops.texture.slot_move(type='UP')`
Move texture slots up and down

Parameters **type** (*enum in ['UP', 'DOWN'], (optional)*) – Type

`bpy.ops.texture.slot_paste()`
Copy the texture settings and nodes

Time Operators

`bpy.ops.time.end_frame_set()`
Set the end frame

`bpy.ops.time.start_frame_set()`
Set the start frame

`bpy.ops.time.view_all()`
Show the entire playable frame range

Transform Operators

`bpy.ops.transform.create_orientation(name="", use=False, overwrite=False)`
Create transformation orientation from selection

Parameters

- **name** (*string, (optional)*) – Name, Text to insert at the cursor position.
- **use** (*boolean, (optional)*) – Use after creation, Select orientation after its creation
- **overwrite** (*boolean, (optional)*) – Overwrite previous, Overwrite previously created orientation with same name

`bpy.ops.transform.delete_orientation()`
Delete transformation orientation

`bpy.ops.transform.edge_crease(value=0.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)`
Change the crease of edges

Parameters

- **value** (*float in [-1, 1], (optional)*) – Factor
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**edge_slide**(*value=0.0*, *mirror=False*, *snap=False*, *snap_target='CLOSEST'*, *snap_point=(0.0, 0.0, 0.0)*, *snap_align=False*, *snap_normal=(0.0, 0.0, 0.0)*, *release_confirm=False*)

Slide an edge loop along a mesh

Parameters

- **value** (*float in [-1, 1], (optional)*) – Factor
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**mirror**(*constraint_axis=(False, False, False)*, *constraint_orientation=''*, *proportional='DISABLED'*, *proportional_edit_falloff='SMOOTH'*, *proportional_size=1.0*, *release_confirm=False*)

Mirror selected vertices around one or more axes

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**push_pull**(*value=0.0*, *mirror=False*, *proportional='DISABLED'*, *proportional_edit_falloff='SMOOTH'*, *proportional_size=1.0*, *snap=False*, *snap_target='CLOSEST'*, *snap_point=(0.0, 0.0, 0.0)*, *snap_align=False*, *snap_normal=(0.0, 0.0, 0.0)*, *release_confirm=False*)

Push/Pull selected items

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Distance
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing

- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.`**`resize`**(*value=(1.0, 1.0, 1.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), texture_space=False, release_confirm=False*)

Resize selected items

Parameters

- **value** (*float array of 3 items in [-inf, inf], (optional)*) – Vector
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **texture_space** (*boolean, (optional)*) – Edit Object data texture space
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**rotate**(*value=(0.0), axis=(0.0, 0.0, 0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Rotate selected items

Parameters

- **value** (*float array of 1 items in [-inf, inf], (optional)*) – Angle
- **axis** (*float array of 3 items in [-inf, inf], (optional)*) – Axis, The axis around which the transformation occurs
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**select_orientation**(*orientation=''*)

Select transformation orientation

Parameters **orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation

bpy.ops.transform.**seq_slide**(*value=(1.0, 1.0), snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Slide a sequence strip in time

Parameters

- **value** (*float array of 2 items in [-inf, inf], (optional)*) – angle
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal

- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.shear`(*value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Shear selected items along the horizontal screen axis

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Offset
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.shrink_fatten`(*value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Shrink/fatten selected vertices along normals

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Offset
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point

- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.snap_type`(*type='INCREMENT'*)

Set the snap element type

Parameters **type** (*enum in ['INCREMENT', 'VERTEX', 'EDGE', 'FACE', 'VOLUME'], (optional)*) – Type, Set the snap element type

`bpy.ops.transform.tilt`(*value=(0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Tilt selected control vertices of 3d curve

Parameters

- **value** (*float array of 1 items in [-inf, inf], (optional)*) – Angle
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.tosphere`(*value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Move selected vertices outward in a spherical shape around mesh center

Parameters

- **value** (*float in [0, 1], (optional)*) – Factor
- **mirror** (*boolean, (optional)*) – Mirror Editing

- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.`**`trackball`**(*value=(1.0, 1.0), mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Trackball style rotation of selected items

Parameters

- **value** (*float array of 2 items in [-inf, inf], (optional)*) – angle
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**transform**(*mode='DUMMY', value=(0.0, 0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Transform selected items by mode type

Parameters

- **mode** (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TOSPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode
- **value** (*float array of 4 items in [-inf, inf], (optional)*) – Values
- **axis** (*float array of 3 items in [-inf, inf], (optional)*) – Axis, The axis around which the transformation occurs
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.**translate**(*value=(0.0, 0.0, 0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), texture_space=False, release_confirm=False*)

Translate selected items

Parameters

- **value** (*float array of 3 items in [-inf, inf], (optional)*) – Vector

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **texture_space** (*boolean, (optional)*) – Edit Object data texture space
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.transform.`**`warp`**(*value=(0.0), mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False*)

Warp selected items around the cursor

Parameters

- **value** (*float array of 1 items in [-inf, inf], (optional)*) – Angle
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

Ui Operators

`bpy.ops.ui.copy_data_path_button()`
Copy the RNA data path for this property to the clipboard

`bpy.ops.ui.copy_to_selected_button(all=True)`
Copy property from this object to selected objects or bones

Parameters **all** (*boolean, (optional)*) – All, Reset to default values all elements of the array.

`bpy.ops.ui.eyedropper()`
Sample a color from the Blender Window to store in a property

`bpy.ops.ui.reports_to_textblock()`
Write the reports

`bpy.ops.ui.reset_default_button(all=True)`
Reset this property's value to its default value

Parameters **all** (*boolean, (optional)*) – All, Reset to default values all elements of the array.

`bpy.ops.ui.reset_default_theme()`
Reset to the default theme colors

Uv Operators

`bpy.ops.uv.align(axis='ALIGN_AUTO')`
Align selected UV vertices to an axis

Parameters **axis** (*enum in ['ALIGN_AUTO', 'ALIGN_X', 'ALIGN_Y'], (optional)*) – Axis, Axis to align UV locations on.

`bpy.ops.uv.average_islands_scale()`
Undocumented (contribute)

`bpy.ops.uv.circle_select(x=0, y=0, radius=0, gesture_mode=0)`
Select UV vertices using circle selection

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y
- **radius** (*int in [-inf, inf], (optional)*) – Radius
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode

`bpy.ops.uv.cube_project(cube_size=1.0, correct_aspect=True, clip_to_bounds=False, scale_to_bounds=False)`
Undocumented (contribute)

Parameters

- **cube_size** (*float in [0, inf], (optional)*) – Cube Size, Size of the cube to project on.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

`bpy.ops.uv.cursor_set` (*location=(0.0, 0.0)*)
Set 2D cursor location

Parameters **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Cursor location in 0.0-1.0 coordinates.

`bpy.ops.uv.cylinder_project` (*direction='VIEW_ON_EQUATOR', align='POLAR_ZX', radius=1.0, correct_aspect=True, clip_to_bounds=False, scale_to_bounds=False*)
Undocumented (contribute)

Parameters

- **direction** (*enum in ['VIEW_ON_EQUATOR', 'VIEW_ON_POLES', 'ALIGN_TO_OBJECT'], (optional)*) – Direction, Direction of the sphere or cylinder.
- **align** (*enum in ['POLAR_ZX', 'POLAR_ZY'], (optional)*) – Align, How to determine rotation around the pole.
- **radius** (*float in [0, inf], (optional)*) – Radius, Radius of the sphere or cylinder.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

`bpy.ops.uv.export_layout` (*filepath="", check_existing=True, export_all=False, mode='PNG', size=(1024, 1024), opacity=0.25*)
Export UV layout to file

Parameters

- **filepath** (*string, (optional)*) – File Path, File path used for exporting the SVG file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **export_all** (*boolean, (optional)*) – All UV's, Export all UVs in this mesh (not just the visible ones)
- **mode** (*enum in ['SVG', 'EPS', 'PNG'], (optional)*) – Format, File format to export the UV layout to
- **size** (*int array of 2 items in [8, 32768], (optional)*) – Dimensions of the exported file
- **opacity** (*float in [0, 1], (optional)*) – Fill Opacity

File addons/io_mesh_uv_layout/__init__.py:132

`bpy.ops.uv.follow_active_quads` (*mode='LENGTH'*)
Follow UVs from active quads along continuous face loops

Parameters **mode** (*enum in ['EVEN', 'LENGTH'], (optional)*) – Edge Length Mode, Method to space UV edge loops

File op/uvcalc_follow_active.py:244

`bpy.ops.uv.hide` (*unselected=False*)
Hide (un)selected UV vertices

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

`bpy.ops.uv.lightmap_pack`(*PREF_CONTEXT='SEL_FACES'*, *PREF_PACK_IN_ONE=True*, *PREF_NEW_UVLAYER=False*, *PREF_APPLY_IMAGE=False*, *PREF_IMG_PX_SIZE=512*, *PREF_BOX_DIV=12*, *PREF_MARGIN_DIV=0.1*)

Follow UVs from active quads along continuous face loops

Parameters

- **PREF_CONTEXT** (*enum in ['SEL_FACES', 'ALL_FACES', 'ALL_OBJECTS'], (optional)*) – Selection
- **PREF_PACK_IN_ONE** (*boolean, (optional)*) – Share Tex Space, Objects Share texture space, map all objects into 1 uvmap
- **PREF_NEW_UVLAYER** (*boolean, (optional)*) – New UV Layer, Create a new UV layer for every mesh packed
- **PREF_APPLY_IMAGE** (*boolean, (optional)*) – New Image, Assign new images for every mesh (only one if shared tex space enabled)
- **PREF_IMG_PX_SIZE** (*int in [64, 5000], (optional)*) – Image Size, Width and Height for the new image
- **PREF_BOX_DIV** (*int in [1, 48], (optional)*) – Pack Quality, Pre Packing before the complex boxpack
- **PREF_MARGIN_DIV** (*float in [0.001, 1], (optional)*) – Margin, Size of the margin as a division of the UV

File op/uvcalc_lightmap.py:560

`bpy.ops.uv.minimize_stretch`(*fill_holes=True*, *blend=0.0*, *iterations=0*)

Reduce UV stretching by relaxing angles

Parameters

- **fill_holes** (*boolean, (optional)*) – Fill Holes, Virtual fill holes in mesh before unwrapping, to better avoid overlaps and preserve symmetry.
- **blend** (*float in [0, 1], (optional)*) – Blend, Blend factor between stretch minimized and original.
- **iterations** (*int in [0, inf], (optional)*) – Iterations, Number of iterations to run, 0 is unlimited when run interactively.

`bpy.ops.uv.pack_islands`()

Undocumented (contribute)

`bpy.ops.uv.pin`(*clear=False*)

Set/clear selected UV vertices as anchored between multiple unwrap operations

Parameters **clear** (*boolean, (optional)*) – Clear, Clear pinning for the selection instead of setting it.

`bpy.ops.uv.project_from_view`(*orthographic=False*, *correct_aspect=True*, *clip_to_bounds=False*, *scale_to_bounds=False*)

Undocumented (contribute)

Parameters

- **orthographic** (*boolean, (optional)*) – Orthographic, Use orthographic projection.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.

- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

`bpy.ops.uv.reset()`
Undocumented (contribute)

`bpy.ops.uv.reveal()`
Reveal all hidden UV vertices

`bpy.ops.uv.select(extend=False, location=(0.0, 0.0))`
Select UV vertice

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

`bpy.ops.uv.select_all(action='TOGGLE')`
Change selection of all UV vertices

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

`bpy.ops.uv.select_border(pinned=False, gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`
Select UV vertices using border selection

Parameters

- **pinned** (*boolean, (optional)*) – Pinned, Border select pinned UVs only.
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.uv.select_inverse()`
Select inverse of (un)selected UV vertices

`bpy.ops.uv.select_linked(extend=False)`
Select all UV vertices linked to the active UV map

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.

`bpy.ops.uv.select_linked_pick(extend=False, location=(0.0, 0.0))`
Select all UV vertices linked under the mouse

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

`bpy.ops.uv.select_loop`(*extend=False*, *location=(0.0, 0.0)*)
Select a loop of connected UV vertices

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

`bpy.ops.uv.select_pinned`()
Select all pinned UV vertices

`bpy.ops.uv.smart_project`(*angle_limit=66.0*, *island_margin=0.0*)
This script projection unwraps the selected faces of a mesh. it operates on all selected mesh objects, and can be used unwrap selected faces, or all faces.

Parameters

- **angle_limit** (*float in [1, 89], (optional)*) – Angle Limit, lower for more projection groups, higher for less distortion.
- **island_margin** (*float in [0, 1], (optional)*) – Island Margin, Margin to reduce bleed from adjacent islands.

File op/uvcalc_smart_project.py:1135

`bpy.ops.uv.snap_cursor`(*target='PIXELS'*)
Snap cursor to target type

Parameters **target** (*enum in ['PIXELS', 'SELECTION'], (optional)*) – Target, Target to snap the selected UV's to.

`bpy.ops.uv.snap_selection`(*target='PIXELS'*)
Snap selected UV vertices to target type

Parameters **target** (*enum in ['PIXELS', 'CURSOR', 'ADJACENT_UNSELECTED'], (optional)*) – Target, Target to snap the selected UV's to.

`bpy.ops.uv.sphere_project`(*direction='VIEW_ON_EQUATOR'*, *align='POLAR_ZX'*, *correct_aspect=True*, *clip_to_bounds=False*, *scale_to_bounds=False*)
Undocumented (contribute)

Parameters

- **direction** (*enum in ['VIEW_ON_EQUATOR', 'VIEW_ON_POLES', 'ALIGN_TO_OBJECT'], (optional)*) – Direction, Direction of the sphere or cylinder.
- **align** (*enum in ['POLAR_ZX', 'POLAR_ZY'], (optional)*) – Align, How to determine rotation around the pole.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

`bpy.ops.uv.stitch`(*use_limit=True*, *limit=0.01*)
Stitch selected UV vertices by proximity

Parameters

- **use_limit** (*boolean, (optional)*) – Use Limit, Stitch UVs within a specified limit distance.
- **limit** (*float in [0, inf], (optional)*) – Limit, Limit distance in normalized coordinates.

`bpy.ops.uv.tile_set` (*tile=(0, 0)*)
Set UV image tile coordinates

Parameters **tile** (*int array of 2 items in [0, inf], (optional)*) – Tile, Tile coordinate.

`bpy.ops.uv.unlink_selection` ()
Unlink selected UV vertices from active UV map

`bpy.ops.uv.unwrap` (*method='ANGLE_BASED', fill_holes=True, correct_aspect=True*)
Undocumented (contribute)

Parameters

- **method** (*enum in ['ANGLE_BASED', 'CONFORMAL'], (optional)*) – Method, Unwrapping method. Angle Based usually gives better results than Conformal, while being somewhat slower.
- **fill_holes** (*boolean, (optional)*) – Fill Holes, Virtual fill holes in mesh before unwrapping, to better avoid overlaps and preserve symmetry.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.

`bpy.ops.uv.weld` ()
Weld selected UV vertices together

View2D Operators

`bpy.ops.view2d.pan` (*deltax=0, deltay=0*)
Pan the view

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

`bpy.ops.view2d.reset` ()
Reset the view

`bpy.ops.view2d.scroll_down` (*deltax=0, deltay=0, page=False*)
Scroll the view down

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y
- **page** (*boolean, (optional)*) – Page, Scroll down one page.

`bpy.ops.view2d.scroll_left` (*deltax=0, deltay=0*)
Scroll the view left

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

`bpy.ops.view2d.scroll_right`(*deltax=0*, *deltay=0*)
Scroll the view right

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

`bpy.ops.view2d.scroll_up`(*deltax=0*, *deltay=0*, *page=False*)
Scroll the view up

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y
- **page** (*boolean, (optional)*) – Page, Scroll up one page.

`bpy.ops.view2d.scroller_activate`()
Scroll view by mouse click and drag

`bpy.ops.view2d.zoom`(*deltax=0.0*, *deltay=0.0*)
Zoom in/out the view

Parameters

- **deltax** (*float in [-inf, inf], (optional)*) – Delta X
- **deltay** (*float in [-inf, inf], (optional)*) – Delta Y

`bpy.ops.view2d.zoom_border`(*gesture_mode=0*, *xmin=0*, *xmax=0*, *ymin=0*, *ymax=0*)
Zoom in the view to the nearest item contained in the border

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.view2d.zoom_in`(*zoomfacx=0.0*, *zoomfacy=0.0*)
Zoom in the view

Parameters

- **zoomfacx** (*float in [-inf, inf], (optional)*) – Zoom Factor X
- **zoomfacy** (*float in [-inf, inf], (optional)*) – Zoom Factor Y

`bpy.ops.view2d.zoom_out`(*zoomfacx=0.0*, *zoomfacy=0.0*)
Zoom out the view

Parameters

- **zoomfacx** (*float in [-inf, inf], (optional)*) – Zoom Factor X
- **zoomfacy** (*float in [-inf, inf], (optional)*) – Zoom Factor Y

View3D Operators

`bpy.ops.view3d.background_image_add`(*name="Image", filepath="Path"*)
Add a new background image

Parameters

- **name** (*string, (optional)*) – Name, Image name to assign.
- **filepath** (*string, (optional)*) – Filepath, Path to image file

`bpy.ops.view3d.background_image_remove`(*index=0*)
Remove a background image from the 3D view

Parameters **index** (*int in [0, inf], (optional)*) – Index, Background image index to remove

`bpy.ops.view3d.camera_to_view`()
Set camera view to active view

`bpy.ops.view3d.clip_border`(*xmin=0, xmax=0, ymin=0, ymax=0*)
Set the view clipping border

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.view3d.cursor3d`()
Set the location of the 3D cursor

`bpy.ops.view3d.edit_mesh_extrude_individual_move`()
Extrude individual elements and move

File ui/space_view3d.py:1445

`bpy.ops.view3d.edit_mesh_extrude_move_normal`()
Extrude and move along normals

File ui/space_view3d.py:1474

`bpy.ops.view3d.enable_manipulator`(*translate=False, rotate=False, scale=False*)
Enable the transform manipulator for use

Parameters

- **translate** (*boolean, (optional)*) – Translate, Enable the translate manipulator
- **rotate** (*boolean, (optional)*) – Rotate, Enable the rotate manipulator
- **scale** (*boolean, (optional)*) – Scale, Enable the scale manipulator

`bpy.ops.view3d.fly`()
Interactively fly around the scene

`bpy.ops.view3d.game_start`()
Start game engine

`bpy.ops.view3d.layers`(*nr=1, extend=False, toggle=True*)
Toggle layer(s) visibility

Parameters

- **nr** (*int in [0, 20], (optional)*) – Number, The layer number to set, zero for all layers
- **extend** (*boolean, (optional)*) – Extend, Add this layer to the current view layers
- **toggle** (*boolean, (optional)*) – Toggle, Toggle the layer

`bpy.ops.view3d.localview()`
Toggle display of selected object(s) separately and centered in view

`bpy.ops.view3d.manipulator(constraint_axis=(False, False, False), constraint_orientation='', release_confirm=False)`
Manipulate selected item by axis

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

`bpy.ops.view3d.move()`
Move the view

`bpy.ops.view3d.object_as_camera()`
Set the active object as the active camera for this view or scene

`bpy.ops.view3d.properties()`
Toggles the properties panel display

`bpy.ops.view3d.render_border(xmin=0, xmax=0, ymin=0, ymax=0)`
Set the boundries of the border render and enables border render

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.view3d.rotate()`
Rotate the view

`bpy.ops.view3d.select(extend=False, center=False, enumerate=False)`
Activate/select item(s)

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **center** (*boolean, (optional)*) – Center, Use the object center when selecting (object mode only).
- **enumerate** (*boolean, (optional)*) – Enumerate, List objects under the mouse (object mode only).

`bpy.ops.view3d.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, extend=True)`
Select items using border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first

`bpy.ops.view3d.select_circle`(*x=0*, *y=0*, *radius=0*, *gesture_mode=0*)
Select items using circle selection

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y
- **radius** (*int in [-inf, inf], (optional)*) – Radius
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Event Type

`bpy.ops.view3d.select_lasso`(*path=None*, *deselect=False*, *extend=True*)
Select items using lasso selection

Parameters

- **path** (Collection of `OperatorMousePath`, (optional)) – Path
- **deselect** (*boolean, (optional)*) – Deselect, Deselect rather than select items.
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

`bpy.ops.view3d.smoothview`()
The time to animate the change of view (in milliseconds)

`bpy.ops.view3d.snap_cursor_to_active`()
Snap cursor to active item

`bpy.ops.view3d.snap_cursor_to_center`()
Snap cursor to the Center

`bpy.ops.view3d.snap_cursor_to_grid`()
Snap cursor to nearest grid node

`bpy.ops.view3d.snap_cursor_to_selected`()
Snap cursor to center of selected item(s)

`bpy.ops.view3d.snap_selected_to_cursor`()
Snap selected item(s) to cursor

`bpy.ops.view3d.snap_selected_to_grid`()
Snap selected item(s) to nearest grid node

`bpy.ops.view3d.toolshelf`()
Toggles tool shelf display

`bpy.ops.view3d.view_all`(*center=False*)
View all objects in scene

Parameters **center** (*boolean, (optional)*) – Center

`bpy.ops.view3d.view_center_camera()`
Center the camera view

`bpy.ops.view3d.view_center_cursor()`
Centers the view so that the cursor is in the middle of the view

`bpy.ops.view3d.view_orbit(type='ORBITLEFT')`
Orbit the view

Parameters **type** (*enum in ['ORBITLEFT', 'ORBITRIGHT', 'ORBITUP', 'ORBITDOWN'], (optional)*) – Orbit, Direction of View Orbit

`bpy.ops.view3d.view_pan(type='PANLEFT')`
Pan the view

Parameters **type** (*enum in ['PANLEFT', 'PANRIGHT', 'PANUP', 'PANDOWN'], (optional)*) – Pan, Direction of View Pan

`bpy.ops.view3d.view_persportho()`
Switch the current view from perspective/orthographic

`bpy.ops.view3d.view_selected()`
Move the view to the selection center

`bpy.ops.view3d.viewnumpad(type='FRONT', align_active=False)`
Set the view

Parameters

- **type** (*enum in ['FRONT', 'BACK', 'LEFT', 'RIGHT', 'TOP', 'BOTTOM', 'CAMERA'], (optional)*) – View, The Type of view
- **align_active** (*boolean, (optional)*) – Align Active, Align to the active objects axis

`bpy.ops.view3d.zoom(delta=0, mx=0, my=0)`
Zoom in/out in the view

Parameters

- **delta** (*int in [-inf, inf], (optional)*) – Delta
- **mx** (*int in [0, inf], (optional)*) – Zoom Position X
- **my** (*int in [0, inf], (optional)*) – Zoom Position Y

`bpy.ops.view3d.zoom_border(xmin=0, xmax=0, ymin=0, ymax=0)`
Zoom in the view to the nearest object contained in the border

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.view3d.zoom_camera_1_to_1()`
Match the camera to 1:1 to the render output

Wm Operators

`bpy.ops.wm.addon_disable(module="")`
Disable an addon

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to disable

File ui/space_userpref.py:1042

`bpy.ops.wm.addon_enable(module="")`
Enable an addon

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to enable

File ui/space_userpref.py:1021

`bpy.ops.wm.addon_expand(module="")`
Display more information on this add-on

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to expand

File ui/space_userpref.py:1176

`bpy.ops.wm.addon_install(overwrite=True, filepath="", filter_folder=True, filter_python=True, filter_glob="*.py;*.zip")`
Install an addon

Parameters

- **overwrite** (*boolean, (optional)*) – Overwrite, Remove existing addons with the same ID
- **filepath** (*string, (optional)*) – File Path, File path to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_python** (*boolean, (optional)*) – Filter python

File ui/space_userpref.py:1072

`bpy.ops.wm.call_menu(name="")`
Undocumented (contribute)

Parameters **name** (*string, (optional)*) – Name, Name of the menu

`bpy.ops.wm.context_cycle_array(data_path="", reverse=False)`

Set a context array value. Useful for cycling the active mesh edit mode.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **reverse** (*boolean, (optional)*) – Reverse, Cycle backwards

File op/wm.py:368

`bpy.ops.wm.context_cycle_enum(data_path="", reverse=False)`
Toggle a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **reverse** (*boolean, (optional)*) – Reverse, Cycle backwards

File op/wm.py:315

`bpy.ops.wm.context_cycle_int(data_path="", reverse=False)`
Set a context value. Useful for cycling active material,

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string

- **reverse** (*boolean, (optional)*) – Reverse, Cycle backwards

File op/wm.py:281

`bpy.ops.wm.context_menu_enum`(*data_path=""*)

Undocumented (contribute)

Parameters **data_path** (*string, (optional)*) – Context Attributes, rna context string

File op/wm.py:412

`bpy.ops.wm.context_modal_mouse`(*data_path_iter=""*, *data_path_item=""*, *input_scale=0.01*, *invert=False*, *initial_x=0*)

Adjust arbitrary values with mouse input

Parameters

- **data_path_iter** (*string, (optional)*) – The data path relative to the context, must point to an iterable.
- **data_path_item** (*string, (optional)*) – The data path from each iterable to the value (int or float)
- **input_scale** (*float in [-inf, inf], (optional)*) – Scale the mouse movement by this value before applying the delta
- **invert** (*boolean, (optional)*) – Invert the mouse input

File op/wm.py:531

`bpy.ops.wm.context_scale_int`(*data_path=""*, *value=1.0*, *always_step=True*)

Scale an int context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*float in [-inf, inf], (optional)*) – Value, Assign value
- **always_step** (*boolean, (optional)*) – Always Step, Always adjust the value by a minimum of 1 when 'value' is not 1.0.

File op/wm.py:143

`bpy.ops.wm.context_set_boolean`(*data_path=""*, *value=True*)

Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*boolean, (optional)*) – Value, Assignment value

File op/wm.py:65

`bpy.ops.wm.context_set_enum`(*data_path=""*, *value=""*)

Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assignment value (as a string)

File op/wm.py:65

`bpy.ops.wm.context_set_float`(*data_path=""*, *value=0.0*, *relative=False*)

Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*float in [-inf, inf], (optional)*) – Value, Assignment value
- **relative** (*boolean, (optional)*) – Relative, Apply relative to the current value (delta)

File op/wm.py:65

`bpy.ops.wm.context_set_id`(*data_path=""*, *value=""*)
Toggle a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assign value

File op/wm.py:429

`bpy.ops.wm.context_set_int`(*data_path=""*, *value=0*, *relative=False*)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*int in [-inf, inf], (optional)*) – Value, Assign value
- **relative** (*boolean, (optional)*) – Relative, Apply relative to the current value (delta)

File op/wm.py:65

`bpy.ops.wm.context_set_string`(*data_path=""*, *value=""*)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assign value

File op/wm.py:65

`bpy.ops.wm.context_set_value`(*data_path=""*, *value=""*)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assignment value (as a string)

File op/wm.py:219

`bpy.ops.wm.context_toggle`(*data_path=""*)
Toggle a context value.

Parameters **data_path** (*string, (optional)*) – Context Attributes, rna context string

File op/wm.py:234

`bpy.ops.wm.context_toggle_enum`(*data_path=""*, *value_1=""*, *value_2=""*)
Toggle a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string

- **value_1** (*string, (optional)*) – Value, Toggle enum
- **value_2** (*string, (optional)*) – Value, Toggle enum

File op/wm.py:258

`bpy.ops.wm.debug_menu`(*debug_value=0*)
Open a popup to set the debug level

Parameters **debug_value** (*int in [-10000, 10000], (optional)*) – Debug Value

`bpy.ops.wm.doc_edit`(*doc_id=""*, *doc_new=""*)
Load online reference docs

Parameters

- **doc_id** (*string, (optional)*) – Doc ID
- **doc_new** (*string, (optional)*) – Edit Description

File op/wm.py:653

`bpy.ops.wm.doc_view`(*doc_id=""*)
Load online reference docs

Parameters **doc_id** (*string, (optional)*) – Doc ID

File op/wm.py:608

`bpy.ops.wm.interaction_preset_add`(*name=""*, *remove_active=False*)
Add an Application Interaction Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

`bpy.ops.wm.keyconfig_activate`(*filepath=""*)
Undocumented (contribute)

Parameters **filepath** (*string, (optional)*) – File Path

File op/wm.py:831

`bpy.ops.wm.keyconfig_export`(*filepath="keymap.py"*, *filter_folder=True*, *filter_text=True*, *filter_python=True*)
Export key configuration to a python script

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_text** (*boolean, (optional)*) – Filter text
- **filter_python** (*boolean, (optional)*) – Filter python

File ui/space_userpref_keymap.py:595

`bpy.ops.wm.keyconfig_import`(*filepath="keymap.py"*, *filter_folder=True*, *filter_text=True*, *filter_python=True*, *keep_original=True*)
Import key configuration from a python script

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders

- **filter_text** (*boolean, (optional)*) – Filter text
- **filter_python** (*boolean, (optional)*) – Filter python
- **keep_original** (*boolean, (optional)*) – Keep original, Keep original file after copying to configuration folder

File ui/space_userpref_keymap.py:546

`bpy.ops.wm.keyconfig_preset_add`(*name=""*, *remove_active=False*)
Add a Keyconfig Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File op/presets.py:43

`bpy.ops.wm.keyconfig_remove`()
Remove key config

File ui/space_userpref_keymap.py:777

`bpy.ops.wm.keyconfig_test`()
Test keyconfig for conflicts

File ui/space_userpref_keymap.py:513

`bpy.ops.wm.keyitem_add`()
Add key map item

File ui/space_userpref_keymap.py:730

`bpy.ops.wm.keyitem_remove`(*item_id=0*)
Remove key map item

Parameters **item_id** (*int in [-inf, inf], (optional)*) – Item Identifier, Identifier of the item to remove

File ui/space_userpref_keymap.py:760

`bpy.ops.wm.keyitem_restore`(*item_id=0*)
Restore key map item

Parameters **item_id** (*int in [-inf, inf], (optional)*) – Item Identifier, Identifier of the item to remove

File ui/space_userpref_keymap.py:715

`bpy.ops.wm.keymap_edit`()
Edit stored key map

File ui/space_userpref_keymap.py:678

`bpy.ops.wm.keymap_restore`(*all=False*)
Restore key map(s)

Parameters **all** (*boolean, (optional)*) – All Keymaps, Restore all keymaps to default

File ui/space_userpref_keymap.py:691

`bpy.ops.wm.link_append`(*filepath=""*, *directory=""*, *filename=""*, *filter_blender=True*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=1*, *relative_path=False*, *link=True*, *autoselect=True*, *active_layer=True*, *instance_groups=True*, *files=None*)
Link or Append from a Library .blend file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **directory** (*string, (optional)*) – Directory, Directory of the file
- **filename** (*string, (optional)*) – File Name, Name of the file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **link** (*boolean, (optional)*) – Link, Link the objects or datablocks rather than appending
- **autoselect** (*boolean, (optional)*) – Select, Select the linked objects
- **active_layer** (*boolean, (optional)*) – Active Layer, Put the linked objects on the active layer
- **instance_groups** (*boolean, (optional)*) – Instance Groups, Create instances for each group as a DupliGroup
- **files** (Collection of `OperatorFileListElement`, (optional)) – Files

`bpy.ops.wm.memory_statistics()`

Print memory statistics to the console

`bpy.ops.wm.open_mainfile(filepath="", filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=8, load_ui=True, use_scripts=True)`

Open a Blender file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files

- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **load_ui** (*boolean, (optional)*) – Load UI, Load user interface setup in the .blend file
- **use_scripts** (*boolean, (optional)*) – Trusted Source, Allow blend file execute scripts automatically, default available from system preferences

`bpy.ops.wm.operator_preset_add`(*name=""*, *remove_active=False*, *operator=""*)

Add an Application Interaction Preset

Parameters

- **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name
- **operator** (*string, (optional)*) – Operator

File op/presets.py:43

`bpy.ops.wm.path_open`(*filepath=""*)

Open a path in a file browser

Parameters **filepath** (*string, (optional)*) – File Path

File op/wm.py:566

`bpy.ops.wm.properties_add`(*data_path=""*)

Internal use (edit a property data_path)

Parameters **data_path** (*string, (optional)*) – Property Edit, Property data_path edit

File op/wm.py:792

`bpy.ops.wm.properties_edit`(*data_path=""*, *property=""*, *value=""*, *min=0.0*, *max=1.0*, *description=""*)

Internal use (edit a property data_path)

Parameters

- **data_path** (*string, (optional)*) – Property Edit, Property data_path edit
- **property** (*string, (optional)*) – Property Name, Property name edit
- **value** (*string, (optional)*) – Property Value, Property value edit
- **min** (*float in [-inf, inf], (optional)*) – Min
- **max** (*float in [-inf, inf], (optional)*) – Max
- **description** (*string, (optional)*) – Tip

File op/wm.py:730

`bpy.ops.wm.properties_remove`(*data_path=""*, *property=""*)

Internal use (edit a property data_path)

Parameters

- **data_path** (*string, (optional)*) – Property Edit, Property data_path edit
- **property** (*string, (optional)*) – Property Name, Property name edit

File op/wm.py:819

`bpy.ops.wm.quit_blender()`
Quit Blender

`bpy.ops.wm.read_factory_settings()`
Load default file and user preferences

`bpy.ops.wm.read_homefile()`
Open the default file (doesn't save the current file)

`bpy.ops.wm.recover_auto_save(filepath="", filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=8)`
Open an automatically saved file to recover it

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

`bpy.ops.wm.recover_last_session()`
Open the last closed file ("quit.blend")

`bpy.ops.wm.redraw_timer(type='DRAW', iterations=10)`
Simple redraw timer to test the speed of updating the interface

Parameters

- **type** (*enum in ['DRAW', 'DRAW_SWAP', 'DRAW_WIN', 'DRAW_WIN_SWAP', 'ANIM_STEP', 'ANIM_PLAY', 'UNDO'], (optional)*) – Type
- **iterations** (*int in [1, inf], (optional)*) – Iterations, Number of times to redraw

`bpy.ops.wm.save_as_mainfile(filepath="", check_existing=True, filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=8, compress=False, relative_remap=True, copy=False)`
Save the current file in the desired location

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file

- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **compress** (*boolean, (optional)*) – Compress, Write compressed .blend file
- **relative_remap** (*boolean, (optional)*) – Remap Relative, Remap relative paths when saving in a different directory
- **copy** (*boolean, (optional)*) – Save Copy, Save a copy of the actual working state but does not make saved file active.

`bpy.ops.wm.save_homefile()`

Make the current file the default .blend file

`bpy.ops.wm.save_mainfile(filepath="", check_existing=True, filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=8, compress=False, relative_remap=False)`

Save the current Blender file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files

- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **compress** (*boolean, (optional)*) – Compress, Write compressed .blend file
- **relative_remap** (*boolean, (optional)*) – Remap Relative, Remap relative paths when saving in a different directory

`bpy.ops.wm.search_menu()`
Undocumented (contribute)

`bpy.ops.wm.splash()`
Opens a blocking popup region with release info

`bpy.ops.wm.sysinfo()`
Generate System Info

File op/wm.py:841

`bpy.ops.wm.url_open(url="")`
Open a website in the Webbrowser

Parameters **url** (*string, (optional)*) – URL, URL to open

File op/wm.py:553

`bpy.ops.wm.window_duplicate()`
Duplicate the current Blender window

`bpy.ops.wm.window_fullscreen_toggle()`
Toggle the current window fullscreen

World Operators

`bpy.ops.world.new()`
Add a new world

1.4 Types (bpy.types)

1.4.1 Action(ID)

base classes — `bpy_struct`, `ID`

class `bpy.types.Action(ID)`
A collection of F-Curves for animation

fcurves
The individual F-Curves that make up the Action

Type `ActionFCurves` collection of `FCurve`, (readonly)

frame_range
The final frame range of all fcurves within this action

Type float array of 2 items in [-inf, inf], default (0.0, 0.0), (readonly)

groups
Convenient groupings of F-Curves

Type ActionGroups collection of ActionGroup, (readonly)

pose_markers

Markers specific to this Action, for labeling poses

Type ActionPoseMarkers collection of TimelineMarker, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- ActionActuator.action
- ActionConstraint.action
- AnimData.action
- BlendData.actions
- BlendDataActions.new
- BlendDataActions.remove
- NlaStrip.action
- NlaStrips.new
- Object.pose_library
- ShapeActionActuator.action

- SpaceDopeSheetEditor.action

1.4.2 ActionActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ActionActuator** (*Actuator*)

Actuator to control the object movement

action

Type Action

frame_blend_in

Number of frames of motion blending

Type int in [0, 32767], default 0

frame_end

Type float in [-inf, inf], default 0.0

frame_property

Assign the action's current frame number to this property

Type string, default ""

frame_start

Type float in [-inf, inf], default 0.0

play_mode

Action playback type

Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'LOOPSTOP', 'LOOPEND', 'PROPERTY'], default 'PLAY'

priority

Execution priority - lower numbers will override actions with higher numbers. With 2 or more actions at once, the overriding channels must be lower in the stack

Type int in [0, 100], default 0

property

Use this property to define the Action position

Type string, default ""

use_continue_last_frame

Restore last frame when switching on/off, otherwise play from the start each time

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.3 ActionConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**ActionConstraint**(*Constraint*)

Map an action to the transform axes of a bone

action

Type Action

frame_end

Last frame of the Action to use

Type int in [-300000, 300000], default 0

frame_start

First frame of the Action to use

Type int in [-300000, 300000], default 0

max

Maximum value for target channel range

Type float in [-1000, 1000], default 0.0

min

Minimum value for target channel range

Type float in [-1000, 1000], default 0.0

subtarget

Type string, default “”

target

Target Object

Type Object

transform_channel
Transformation channel from the target that is used to key the Action

Type enum in ['LOCATION_X', 'LOCATION_Y', 'LOCATION_Z', 'ROTATION_X', 'ROTATION_Y', 'ROTATION_Z', 'SCALE_X', 'SCALE_Y', 'SCALE_Z'], default 'ROTATION_X'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.4 ActionFCurves(bpy_struct)

base class — bpy_struct

class bpy.types.**ActionFCurves** (*bpy_struct*)
Collection of action fcurves

new (*data_path*, *index=0*, *action_group=""*)
Add a keyframe to the curve.

Parameters

- **data_path** (*string*) – Data Path, FCurve data path to use.
- **index** (*int in [0, inf], (optional)*) – Index, Array index.
- **action_group** (*string, (optional)*) – Action Group, Acton group to add this fcurve into.

Returns Newly created fcurve

Return type FCurve

remove (*fcurve*)

Remove action group.

Parameters **fcurve** (FCurve, (never None)) – FCurve to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.fcurves

1.4.5 ActionGroup(bpy_struct)

base class — bpy_struct

class bpy.types.**ActionGroup** (*bpy_struct*)

Groups of F-Curves

channels

F-Curves in this group

Type Collection of FCurve, (readonly)

custom_color
Index of custom color set

Type int in [-inf, inf], default 0

lock
Action Group is locked

Type boolean, default False

name

Type string, default “”

select
Action Group is selected

Type boolean, default False

show_expanded
Action Group is expanded

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.groups
- ActionGroups.new
- ActionGroups.remove
- FCurve.group

1.4.6 ActionGroups(bpy_struct)

base class — bpy_struct

class bpy.types.**ActionGroups**(*bpy_struct*)
Collection of action groups

new(*name*)
Add a keyframe to the curve.

Parameters **name** (*string*) – New name for the action group.

Returns Newly created action group

Return type ActionGroup

remove(*action_group*)
Remove action group.

Parameters **action_group** (ActionGroup, (never None)) – Action group to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.groups

1.4.7 ActionPoseMarkers(bpy_struct)

base class — bpy_struct

class bpy.types.**ActionPoseMarkers**(*bpy_struct*)
Collection of timeline markers

active
Active pose marker for this Action

Type TimelineMarker

active_index
Index of active pose marker

Type int in [-inf, inf], default 0

new(*name*)
Add a pose marker to the action.

Parameters **name** (*string*) – New name for the marker (not unique).

Returns Newly created marker

Return type TimelineMarker

remove(*marker*)
Remove a timeline marker.

Parameters **marker** (TimelineMarker, (never None)) – Timeline marker to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.pose_markers

1.4.8 Actuator(bpy_struct)

base class — bpy_struct

subclasses — ShapeActionActuator, VisibilityActuator, MessageActuator, RandomActuator, Filter2DActuator, GameActuator, CameraActuator, ArmatureActuator, SoundActuator, ParentActuator, SceneActuator, StateActuator, ActionActuator, ConstraintActuator, PropertyActuator, FCurveActuator, ObjectActuator, EditObjectActuator

class bpy.types.**Actuator**(*bpy_struct*)

Actuator to apply actions in the game engine

name

Type string, default ""

pin

Display when not linked to a visible states controller

Type boolean, default False

show_expanded

Set actuator expanded in the user interface

Type boolean, default False

type

Type enum in ['ACTION', 'ARMATURE', 'CAMERA', 'CONSTRAINT', 'EDIT_OBJECT', 'FCURVE', 'FILTER_2D', 'GAME', 'MESSAGE', 'OBJECT', 'PARENT', 'PROPERTY', 'RANDOM', 'SCENE', 'SHAPE_ACTION', 'SOUND', 'STATE', 'VISIBILITY'], default 'OBJECT'

link(*controller*)

Link the actuator to a controller.

Parameters **controller** (Controller) – Controller to link to.

unlink(*controller*)

Unlink the actuator from a controller.

Parameters **controller** (Controller) – Controller to unlink from.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- Controller.link
- Controller.unlink
- GameObjectSettings.actuators

1.4.9 ActuatorSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**ActuatorSensor** (*Sensor*)

Sensor to detect state modifications of actuators

actuator

Actuator name, actuator active state modifications will be detected

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.10 Addon(bpy_struct)

base class — bpy_struct

class bpy.types.**Addon** (*bpy_struct*)

Python addons to be loaded automatically

module

Module name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Addons.new
- Addons.remove
- UserPreferences.addons

1.4.11 Addons(bpy_struct)

base class — bpy_struct

class bpy.types.**Addons** (*bpy_struct*)

Collection of add-ons

classmethod new()
Add a new addon

Returns Addon datablock.

Return type Addon

classmethod remove(*addon*)
Remove addon.

Parameters **addon** (Addon, (never None)) – Addon to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.addons

1.4.12 AlwaysSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**AlwaysSensor**(*Sensor*)
Sensor to generate continuous pulses

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency

- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.13 AndController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**AndController**(*Controller*)

Controller passing on events based on a logical AND operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.14 AnimData(bpy_struct)

base class — bpy_struct

class bpy.types.**AnimData** (*bpy_struct*)

Animation data for datablock

action

Active Action for this datablock

Type Action

action_blend_type

Method used for combining Active Action's result with result of NLA stack

Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULITPLY'], default 'REPLACE'

action_extrapolation

Action to take for gaps past the Active Action's range (when evaluating with NLA)

Type enum in ['NOTHING', 'HOLD', 'HOLD_FORWARD'], default 'HOLD'

action_influence

Amount the Active Action contributes to the result of the NLA stack

Type float in [0, 1], default 1.0

drivers

The Drivers/Expressions for this datablock

Type Collection of FCurve, (readonly)

nla_tracks

NLA Tracks (i.e. Animation Layers)

Type NlaTracks collection of NlaTrack, (readonly)

use_nla

NLA stack is evaluated when evaluating this block

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.animation_data
- Camera.animation_data
- Curve.animation_data
- ID.animation_data_create
- Key.animation_data
- Lamp.animation_data
- Lattice.animation_data
- Material.animation_data
- Mesh.animation_data
- MetaBall.animation_data
- NodeTree.animation_data
- Object.animation_data
- ParticleSettings.animation_data
- Scene.animation_data
- Texture.animation_data
- World.animation_data

1.4.15 AnimViz(bpy_struct)

base class — bpy_struct

class bpy.types.**AnimViz** (*bpy_struct*)

Settings for the visualisation of motion

motion_path

Motion Path settings for visualisation

Type AnimVizMotionPaths, (readonly, never None)

onion_skin_frames

Onion Skinning (ghosting) settings for visualisation

Type AnimVizOnionSkinning, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.animation_visualisation
- Pose.animation_visualisation

1.4.16 AnimVizMotionPaths(bpy_struct)

base class — bpy_struct

class bpy.types.**AnimVizMotionPaths**(*bpy_struct*)

Motion Path settings for animation visualisation

bake_location

When calculating Bone Paths, use Head or Tips

Type enum in ['HEADS', 'TAILS'], default 'TAILS'

frame_after

Number of frames to show after the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [1, 150000], default 0

frame_before

Number of frames to show before the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [1, 150000], default 0

frame_end

End frame of range of paths to display/calculate (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_start
Starting frame of range of paths to display/calculate (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_step
Number of frames between paths shown (not for 'On Keyframes' Onion-skinning method)

Type int in [1, 100], default 0

show_frame_numbers
Show frame numbers on Motion Paths

Type boolean, default False

show_keyframe_action_all
For bone motion paths, search whole Action for keyframes instead of in group with matching name only (is slower)

Type boolean, default False

show_keyframe_highlight
Emphasize position of keyframes on Motion Paths

Type boolean, default False

show_keyframe_numbers
Show frame numbers of Keyframes on Motion Paths

Type boolean, default False

type
Type of range to show for Motion Paths

Type enum in ['CURRENT_FRAME', 'RANGE'], default 'RANGE'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- AnimViz.motion_path

1.4.17 AnimVizOnionSkinning(bpy_struct)

base class — bpy_struct

class bpy.types.**AnimVizOnionSkinning**(*bpy_struct*)

Onion Skinning settings for animation visualisation

frame_after

Number of frames to show after the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [0, 30], default 0

frame_before

Number of frames to show before the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [0, 30], default 0

frame_end

End frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_start

Starting frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_step

Number of frames between ghosts shown (not for 'On Keyframes' Onion-skinning method)

Type int in [1, 20], default 0

show_only_selected

For Pose-Mode drawing, only draw ghosts for selected bones

Type boolean, default False

type

Method used for determining what ghosts get drawn

Type enum in ['NONE', 'CURRENT_FRAME', 'RANGE', 'KEYS'], default 'NONE'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- AnimViz.onion_skin_frames

1.4.18 AnyType(bpy_struct)

base class — bpy_struct

class bpy.types.**AnyType** (*bpy_struct*)

RNA type used for pointers to any possible data

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

References

- KeyingSetInfo.generate
- UILayout.context_pointer_set
- UILayout.prop
- UILayout.prop_enum
- UILayout.prop_menu_enum
- UILayout.prop_search
- UILayout.prop_search
- UILayout.props_enum
- UILayout.template_ID
- UILayout.template_ID_preview
- UILayout.template_any_ID
- UILayout.template_color_ramp
- UILayout.template_color_wheel
- UILayout.template_curve_mapping
- UILayout.template_histogram
- UILayout.template_image
- UILayout.template_layers
- UILayout.template_layers
- UILayout.template_list
- UILayout.template_list
- UILayout.template_path_builder
- UILayout.template_vectorscope
- UILayout.template_waveform

1.4.19 Area(bpy_struct)

base class — bpy_struct

class bpy.types.**Area**(*bpy_struct*)

Area in a subdivided screen, containing an editor

active_space

Space currently being displayed in this area

Type Space, (readonly)

regions

Regions this area is subdivided in

Type Collection of Region, (readonly)

show_menus

Show menus in the header

Type boolean, default False

spaces

Spaces contained in this area, the first being the active space. NOTE: Useful for example to restore a previously used 3d view space in a certain area to get the old view orientation.

Type Collection of Space, (readonly)

type
Space type

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY'

tag_redraw()
tag_redraw

header_text_set(*text=""*)
Set the header text

Parameters **text** (*string, (optional)*) – Text, New string for the header, no argument clears the text.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.area
- Screen.areas

1.4.20 AreaLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.**AreaLamp**(*Lamp*)
Directional area lamp

gamma
Light gamma correction value

Type float in [-inf, inf], default 0.0

shadow_adaptive_threshold
Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_color
Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method
Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method
Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC', 'CONSTANT_JITTERED'], default 'CONSTANT_JITTERED'

shadow_ray_samples_x
Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_ray_samples_y
Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size
Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

shape
Shape of the area lamp

Type enum in ['SQUARE', 'RECTANGLE'], default 'SQUARE'

size
Size of the area of the area Lamp, X direction size for Rectangle shapes

Type float in [-inf, inf], default 0.0

size_y
Size of the area of the area Lamp in the Y direction for Rectangle shapes

Type float in [-inf, inf], default 0.0

use_dither
Use 2x2 dithering for sampling (Constant Jittered sampling)

Type boolean, default False

use_jitter
Use noise for sampling (Constant Jittered sampling)

Type boolean, default False

use_only_shadow
Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer
Causes only objects on the same layer to cast shadows

Type boolean, default False

use_umbra
Emphasize parts that are fully shadowed (Constant Jittered sampling)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy

- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.21 Armature(ID)

base classes — bpy_struct, ID

class bpy.types.**Armature**(*ID*)

Armature datablock containing a hierarchy of bones, usually used for rigging characters

animation_data

Animation data for this datablock

Type AnimData, (readonly)

bones

Type ArmatureBones collection of Bone, (readonly)

draw_type

Type enum in ['OCTAHEDRAL', 'STICK', 'BBONE', 'ENVELOPE'], default 'OCTAHEDRAL'

edit_bones

Type ArmatureEditBones collection of EditBone, (readonly)

ghost_frame_end

End frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

ghost_frame_start

Starting frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

ghost_size

Frame step for Ghosts (not for 'On Keyframes' Onion-skinning method)

Type int in [1, 20], default 0

ghost_step

Number of frame steps on either side of current frame to show as ghosts (only for 'Around Current Frame' Onion-skinning method)

Type int in [0, 30], default 0

ghost_type

Method of Onion-skinning for active Action

Type enum in ['CURRENT_FRAME', 'RANGE', 'KEYS'], default 'CURRENT_FRAME'

layers

Armature layer visibility

Type boolean array of 32 items, default (False, False)

layers_protected
Protected layers in Proxy Instances are restored to Proxy settings on file reload and undo

Type boolean array of 32 items, default (False, False)

pose_position
Show armature in binding pose or final posed state

Type enum in ['POSE', 'REST'], default 'POSE'

show_axes
Draw bone axes

Type boolean, default False

show_bone_custom_shapes
Draw bones with their custom shapes

Type boolean, default False

show_group_colors
Draw bone group colors

Type boolean, default False

show_names
Draw bone names

Type boolean, default False

show_only_ghost_selected

Type boolean, default False

use_auto_ik
Add temporaral IK constraints while grabbing bones in Pose Mode

Type boolean, default False

use_deform_delay
Don't deform children when manipulating bones in Pose Mode

Type boolean, default False

use_deform_envelopes
Enable Bone Envelopes when defining deform

Type boolean, default False

use_deform_preserve_volume
Enable deform rotation with Quaternions

Type boolean, default False

use_deform_vertex_groups
Enable Vertex Groups when defining deform

Type boolean, default False

use_mirror_x
Apply changes to matching bone on opposite side of X-Axis

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.armatures
- BlendDataArmatures.new
- BlendDataArmatures.remove

1.4.22 ArmatureActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ArmatureActuator**(*Actuator*)

Actuator to ..

bone

Bone on which the constraint is defined

Type string, default “”

constraint

Name of the constraint you want to control

Type string, default “”

mode

Type enum in [’RUN’, ‘ENABLE’, ‘DISABLE’, ‘SETTARGET’, ‘SETWEIGHT’], default ‘RUN’

secondary_target

Set this object as the secondary target of the constraint (only IK polar target at the moment)

Type Object

target

Set this object as the target of the constraint

Type Object

weight

Set weight of this constraint

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.23 ArmatureBones(bpy_struct)

base class — bpy_struct

class bpy.types.**ArmatureBones**(*bpy_struct*)
Collection of armature bones

active
Armatures active bone

Type Bone

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.bones

1.4.24 ArmatureEditBones(bpy_struct)

base class — bpy_struct

class bpy.types.**ArmatureEditBones**(*bpy_struct*)
Collection of armature edit bones

active
Armatures active edit bone

Type EditBone

new(*name*)
Add a new bone.

Parameters **name** (*string*) – New name for the bone

Returns Newly created edit bone

Return type EditBone

remove (*bone*)
Remove an existing bone from the armature

Parameters **bone** (EditBone, (never None)) – EditBone to remove

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.edit_bones

1.4.25 ArmatureModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ArmatureModifier** (*Modifier*)
Armature deformation modifier

invert_vertex_group
Invert vertex group influence

Type boolean, default False

object
Armature object to deform with

Type Object

use_bone_envelopes

Type boolean, default False

use_deform_preserve_volume
Deform rotation interpolation with quaternions

Type boolean, default False

use_multi_modifier
Use same input as previous modifier, and mix results using overall vgroup

Type boolean, default False

use_vertex_groups

Type boolean, default False

vertex_group
Name of Vertex Group which determines influence of modifier per point

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.26 ArmatureSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**ArmatureSensor** (*Sensor*)
Sensor to detect values and changes in values of IK solver

bone
Identify the bone to check value from

Type string, default “”

constraint
Identify the bone constraint to check value from

Type string, default “”

test_type
Type of value and test

Type enum in [’STATECHG’, ‘LINERRORBELOW’, ‘LINERRORABOVE’, ‘ROTERRORBELOW’, ‘ROTERRORABOVE’], default ‘STATECHG’

value
Specify value to be used in comparison

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.27 ArrayModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ArrayModifier**(*Modifier*)

Array duplication modifier

constant_offset_displace

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

count

Number of duplicates to make

Type int in [1, inf], default 0

curve

Curve object to fit array length to

Type Object

end_cap

Mesh object to use as an end cap

Type Object

fit_length

Length to fit array within

Type float in [0, inf], default 0.0

fit_type

Array length calculation method

Type enum in ['FIXED_COUNT', 'FIT_LENGTH', 'FIT_CURVE'], default 'FIXED_COUNT'

merge_threshold

Limit below which to merge vertices

Type float in [0, inf], default 0.0

offset_object

Type Object

relative_offset_displace

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

start_cap

Mesh object to use as a start cap

Type Object

use_constant_offset

Add a constant offset

Type boolean, default False

use_merge_vertices

Merge vertices in adjacent duplicates

Type boolean, default False

use_merge_vertices_cap

Merge vertices in first and last duplicates

Type boolean, default False

use_object_offset
Add another object's transformation to the total offset

Type boolean, default False

use_relative_offset
Add an offset relative to the object's bounding box

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.28 BackgroundImage(bpy_struct)

base class — bpy_struct

class bpy.types.**BackgroundImage**(*bpy_struct*)
Image and settings for display in the 3d View background

image
Image displayed and edited in this space

Type Image

image_user
Parameters defining which layer, pass and frame of the image is displayed

Type ImageUser, (readonly, never None)

offset_x
Offsets image horizontally from the world origin

Type float in [-inf, inf], default 0.0

offset_y
Offsets image vertically from the world origin

Type float in [-inf, inf], default 0.0

opacity
Image opacity to blend the image against the background color

Type float in [0, 1], default 0.0

show_expanded
Show the expanded in the user interface

Type boolean, default False

size
Scaling factor for the background image

Type float in [0, inf], default 0.0

view_axis
The axis to display the image on

Type enum in ['LEFT', 'RIGHT', 'BACK', 'FRONT', 'BOTTOM', 'TOP', 'ALL', 'CAMERA'], default 'ALL'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceView3D.background_images

1.4.29 BevelModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**BevelModifier** (*Modifier*)

Bevel modifier to make edges and vertices more rounded

angle_limit

Angle above which to bevel edges

Type float in [0, 180], default 0.0

edge_weight_method

What edge weight to use for weighting a vertex

Type enum in ['AVERAGE', 'SHARPEST', 'LARGEST'], default 'AVERAGE'

limit_method

Type enum in ['NONE', 'ANGLE', 'WEIGHT'], default 'NONE'

use_only_vertices

Bevel verts/corners, not edges

Type boolean, default False

width

Bevel value/amount

Type float in [0, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.30 BezierSplinePoint(bpy_struct)

base class — bpy_struct

class bpy.types.**BezierSplinePoint**(*bpy_struct*)

Bezier curve point with two handles

co

Coordinates of the control point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_left

Coordinates of the first handle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_left_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

handle_right

Coordinates of the second handle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_right_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

hide

Visibility status

Type boolean, default False

radius

Radius for bevelling

Type float in [0, inf], default 0.0

select_control_point

Control point selection status

Type boolean, default False

select_left_handle

Handle 1 selection status

Type boolean, default False

select_right_handle
Handle 2 selection status

Type boolean, default False

tilt
Tilt in 3D View

Type float in [-inf, inf], default 0.0

weight
Softbody goal weight

Type float in [0.01, 100], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.bezier_points

1.4.31 BlendData(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendData**(*bpy_struct*)
Main data structure representing a .blend file and all its datablocks

actions
Action datablocks.

Type BlendDataActions collection of Action, (readonly)

armatures
Armature datablocks.

Type BlendDataArmatures collection of Armature, (readonly)

brushes
Brush datablocks.

Type BlendDataBrushes collection of Brush, (readonly)

cameras
Camera datablocks.

Type BlendDataCameras collection of Camera, (readonly)

curves
Curve datablocks.

Type BlendDataCurves collection of Curve, (readonly)

filepath
Path to the .blend file

Type string, default "", (readonly)

fonts
Vector font datablocks.

Type BlendDataFonts collection of VectorFont, (readonly)

grease_pencil
Grease Pencil datablocks.

Type BlendDataGreasePencils collection of GreasePencil, (readonly)

groups
Group datablocks.

Type BlendDataGroups collection of Group, (readonly)

images
Image datablocks.

Type BlendDataImages collection of Image, (readonly)

is_dirty
Has the current session been saved to disk as a .blend file

Type boolean, default False, (readonly)

lamps
Lamp datablocks.

Type BlendDataLamps collection of Lamp, (readonly)

lattices
Lattice datablocks.

Type BlendDataLattices collection of Lattice, (readonly)

libraries
Library datablocks.

Type BlendDataLibraries collection of Library, (readonly)

materials
Material datablocks.

Type BlendDataMaterials collection of Material, (readonly)

meshes
Mesh datablocks.

Type BlendDataMeshes collection of Mesh, (readonly)

metaballs
Metaball datablocks.

Type BlendDataMetaBalls collection of MetaBall, (readonly)

node_groups
Node group datablocks.

Type BlendDataNodeTrees collection of NodeTree, (readonly)

objects
Object datablocks.

Type BlendDataObjects collection of Object, (readonly)

particles
Particle datablocks.

Type BlendDataParticles collection of ParticleSettings, (readonly)

scenes
Scene datablocks.

Type BlendDataScenes collection of Scene, (readonly)

screens
Screen datablocks.

Type BlendDataScreens collection of Screen, (readonly)

scripts
Script datablocks (DEPRECATED).

Type Collection of ID, (readonly)

shape_keys
Shape Key datablocks.

Type Collection of Key, (readonly)

sounds
Sound datablocks.

Type BlendDataSounds collection of Sound, (readonly)

texts
Text datablocks.

Type BlendDataTexts collection of Text, (readonly)

textures
Texture datablocks.

Type BlendDataTextures collection of Texture, (readonly)

window_managers
Window manager datablocks.

Type BlendDataWindowManagers collection of WindowManager, (readonly)

worlds
World datablocks.

Type BlendDataWorlds collection of World, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.blend_data

1.4.32 BlendDataActions(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataActions**(*bpy_struct*)
Collection of actions

new(*name*)
Add a new action to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New action datablock.

Return type Action

remove(*action*)
Remove a action from the current blendfile.

Parameters **action** (Action, (never None)) – Action to remove.

tag(*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.actions

1.4.33 BlendDataArmatures(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataArmatures**(*bpy_struct*)

Collection of armatures

new(*name*)

Add a new armature to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New armature datablock.

Return type Armature

remove(*armature*)

Remove a armature from the current blendfile.

Parameters **armature** (Armature, (never None)) – Armature to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.armatures

1.4.34 BlendDataBrushes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataBrushes**(*bpy_struct*)

Collection of brushes

new(*name*)

Add a new brush to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New brush datablock.

Return type Brush

remove(*brush*)

Remove a brush from the current blendfile.

Parameters **brush** (Brush, (never None)) – Brush to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.brushes

1.4.35 BlendDataCameras(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataCameras**(*bpy_struct*)

Collection of cameras

new(*name*)

Add a new camera to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New camera datablock.

Return type Camera

remove(*camera*)

Remove a camera from the current blendfile.

Parameters **camera** (Camera, (never None)) – Camera to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.cameras

1.4.36 BlendDataCurves(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataCurves**(*bpy_struct*)

Collection of curves

new(*name*, *type*)

Add a new curve to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in ['CURVE', 'SURFACE', 'FONT']*) – Type, The type of curve to add

Returns New curve datablock.

Return type Curve

remove(*curve*)

Remove a curve from the current blendfile.

Parameters **curve** (Curve, (never None)) – Curve to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.curves

1.4.37 BlendDataFonts(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataFonts**(*bpy_struct*)

Collection of fonts

load(*filepath*)

Load a new font into the main database

Parameters **filepath** (*string*) – path of the font to load.

Returns New font datablock.

Return type VectorFont

remove(*vfont*)

Remove a font from the current blendfile.

Parameters **vfont** (VectorFont, (never None)) – Font to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.fonts

1.4.38 BlendDataGreasePencils(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataGreasePencils**(*bpy_struct*)

Collection of grease pencils

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.grease_pencil

1.4.39 BlendDataGroups(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataGroups**(*bpy_struct*)

Collection of groups

new(*name*)

Add a new group to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New group datablock.

Return type Group

remove(*group*)

Remove a group from the current blendfile.

Parameters **group** (Group, (never None)) – Group to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.groups

1.4.40 BlendDataImages(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataImages**(*bpy_struct*)

Collection of images

new(*name*, *width*, *height*, *alpha=False*, *float_buffer=False*)

Add a new image to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **width** (*int in [1, inf]*) – Width of the image.
- **height** (*int in [1, inf]*) – Height of the image.
- **alpha** (*boolean, (optional)*) – Alpha, Use alpha channel
- **float_buffer** (*boolean, (optional)*) – Float Buffer, Create an image with floating point color

Returns New image datablock.

Return type Image

load(*filepath*)

Load a new image into the main database

Parameters **filepath** (*string*) – path of the file to load.

Returns New image datablock.

Return type Image

remove(*image*)

Remove an image from the current blendfile.

Parameters **image** (Image, (never None)) – Image to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.images

1.4.41 BlendDataLamps(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataLamps**(*bpy_struct*)

Collection of lamps

new(*name*, *type*)

Add a new lamp to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA']*) – Type, The type of texture to add

Returns New lamp datablock.

Return type Lamp

remove(*lamp*)

Remove a lamp from the current blendfile.

Parameters **lamp** (Lamp, (never None)) – Lamp to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.lamps

1.4.42 BlendDataLattices(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataLattices**(*bpy_struct*)

Collection of lattices

new(*name*)

Add a new lattice to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New lattices datablock.

Return type Lattice

remove(*lattice*)

Remove a lattice from the current blendfile.

Parameters **lattice** (Lattice, (never None)) – Lattice to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.lattices

1.4.43 BlendDataLibraries(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataLibraries**(*bpy_struct*)

Collection of libraries

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

load(*filepath*, *link=False*, *relative=False*)

Returns a context manager which exposes 2 library objects on entering. Each object has attributes matching bpy.data which are lists of strings to be linked.

Parameters

- **filepath** (*string*) – The path to a blend file.
- **link** (*bool*) – When False reference to the original file is lost.
- **relative** (*bool*) – When True the path is stored relative to the open blend file.

```
import bpy

filepath = "//link_library.blend"
```

```
# load a single scene we know the name of.
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.scenes = ["Scene"]


# load all meshes
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.meshes = data_from.meshes


# link all objects starting with 'A'
with bpy.data.libraries.load(filepath, link=True) as (data_from, data_to):
    data_to.objects = [name for name in data_from.objects if name.startswith("A")]


# append everything
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    for attr in dir(data_to):
        setattr(data_to, attr, getattr(data_from, attr))
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.libraries

1.4.44 BlendDataMaterials(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataMaterials**(*bpy_struct*)
Collection of materials

new(*name*)
Add a new material to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New material datablock.

Return type Material

remove(*material*)
Remove a material from the current blendfile.

Parameters **material** (Material, (never None)) – Material to remove.

tag(*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.materials

1.4.45 BlendDataMeshes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataMeshes**(*bpy_struct*)
Collection of meshes

new (*name*)
Add a new mesh to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New mesh datablock.

Return type Mesh

remove (*mesh*)
Remove a mesh from the current blendfile.

Parameters **mesh** (Mesh, (never None)) – Mesh to remove.

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.meshes

1.4.46 BlendDataMetaBalls(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataMetaBalls** (*bpy_struct*)
Collection of metaballs

new (*name*)
Add a new metaball to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New metaball datablock.

Return type `MetaBall`

remove (*metaball*)
Remove a metaball from the current blendfile.

Parameters **metaball** (`MetaBall`, (never None)) – MetaBall to remove.

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.metaballs`

1.4.47 BlendDataNodeTrees(bpy_struct)

base class — `bpy_struct`

class `bpy.types.`**`BlendDataNodeTrees`** (*bpy_struct*)
Collection of node trees

new (*name*, *type*)
Add a new node tree to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in ['SHADER', 'COMPOSITE', 'TEXTURE']*) – Type, The type of node_group to add

Returns New node tree datablock.

Return type NodeTree

remove (*tree*)
Remove a node tree from the current blendfile.

Parameters **tree** (NodeTree, (never None)) – Node tree to remove.

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.node_groups

1.4.48 BlendDataObjects(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataObjects** (*bpy_struct*)
Collection of objects

new (*name*, *object_data*)
Add a new object to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **object_data** (ID) – Object data or None for an empty object.

Returns New object datablock.

Return type Object

remove (*object*)

Remove a object from the current blendfile.

Parameters **object** (Object, (never None)) – Object to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.objects

1.4.49 BlendDataParticles(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataParticles** (*bpy_struct*)

Collection of particle settings

new (*name*)
Add a new particle settings instance to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New particle settings datablock.

Return type ParticleSettings

remove (*particle*)
Remove a particle settings instance from the current blendfile.

Parameters **particle** (ParticleSettings, (never None)) – Particle Settings to remove.

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.particles

1.4.50 BlendDataScenes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataScenes** (*bpy_struct*)
Collection of scenes

new (*name*)
Add a new scene to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New scene datablock.

Return type `Scene`

remove (*scene*)
Remove a scene from the current blendfile.

Parameters **scene** (`Scene`, (never None)) – Scene to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.scenes`

1.4.51 BlendDataScreens(bpy_struct)

base class — `bpy_struct`

class `bpy.types.`**`BlendDataScreens`** (*bpy_struct*)
Collection of screens

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.screens

1.4.52 BlendDataSounds(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataSounds** (*bpy_struct*)

Collection of sounds

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.sounds

1.4.53 BlendDataTexts(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataTexts**(*bpy_struct*)

Collection of texts

new(*name*)

Add a new text to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New text datablock.

Return type Text

remove(*text*)

Remove a text from the current blendfile.

Parameters **text** (Text, (never None)) – Text to remove.

load(*filepath*)

Add a new text to the main database from a file

Parameters **filepath** (*string*) – path for the datablock.

Returns New text datablock.

Return type Text

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.texts

1.4.54 BlendDataTextures(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataTextures**(*bpy_struct*)

Collection of groups

new(*name*, *type*)

Add a new texture to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in ['NONE', 'BLEND', 'CLOUDS', 'DISTORTED_NOISE', 'ENVIRONMENT_MAP', 'IMAGE', 'MAGIC', 'MARBLE', 'MUSGRAVE', 'NOISE', 'POINT_DENSITY', 'STUCCI', 'VORONOI', 'VOXEL_DATA', 'WOOD']*) – Type, The type of texture to add

Returns New texture datablock.

Return type Texture

remove(*texture*)

Remove a texture from the current blendfile.

Parameters **texture** (Texture, (never None)) – Texture to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.textures

1.4.55 BlendDataWindowManagers(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataWindowManagers**(*bpy_struct*)

Collection of window managers

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

References

- BlendData.window_managers

1.4.56 BlendDataWorlds(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataWorlds**(*bpy_struct*)

Collection of worlds

new(*name*)

Add a new world to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New world datablock.

Return type World

remove(*world*)

Remove a world from the current blendfile.

Parameters **world** (World, (never None)) – World to remove.

tag(*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.worlds

1.4.57 BlendTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**BlendTexture**(*Texture*)

Procedural color blending texture

progression

Sets the style of the color blending

Type enum in ['LINEAR', 'QUADRATIC', 'EASING', 'DIAGONAL', 'SPHERICAL', 'QUADRATIC_SPHERE', 'RADIAL'], default 'LINEAR'

use_flip_axis

Flips the texture's X and Y axis

Type enum in ['HORIZONTAL', 'VERTICAL'], default 'HORIZONTAL'

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.58 BlenderRNA(bpy_struct)

base class — bpy_struct

class bpy.types.**BlenderRNA**(*bpy_struct*)

Blender RNA structure definitions

structs

Type Collection of Struct, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.59 BoidRule(bpy_struct)

base class — bpy_struct

subclasses — BoidRuleAvoidCollision, BoidRuleAverageSpeed, BoidRuleAvoid, BoidRuleFight, BoidRuleFollowLeader, BoidRuleGoal

class bpy.types.**BoidRule**(*bpy_struct*)

name
Boid rule name

Type string, default ""

type

Type enum in ['GOAL', 'AVOID', 'AVOID_COLLISION', 'SEPARATE', 'FLOCK', 'FOLLOW_LEADER', 'AVERAGE_SPEED', 'FIGHT'], default 'GOAL', (readonly)

use_in_air
Use rule when boid is flying

Type boolean, default False

use_on_land
Use rule when boid is on land

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- BoidSettings.active_boid_state
- BoidState.active_boid_rule
- BoidState.rules

1.4.60 BoidRuleAverageSpeed(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleAverageSpeed**(*BoidRule*)

level
How much velocity's z-component is kept constant

Type float in [0, 1], default 0.0

speed
Percentage of maximum speed

Type float in [0, 1], default 0.0

wander
How fast velocity's direction is randomized

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.61 BoidRuleAvoid(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleAvoid**(*BoidRule*)

fear_factor
Avoid object if danger from it is above this threshold

Type float in [0, 100], default 0.0

object
Object to avoid

Type Object

use_predict
Predict target movement

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.62 BoidRuleAvoidCollision(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleAvoidCollision**(*BoidRule*)

look_ahead
Time to look ahead in seconds

Type float in [0, 100], default 0.0

use_avoid
Avoid collision with other boids

Type boolean, default False

use_avoid_collision
Avoid collision with deflector objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.63 BoidRuleFight(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleFight**(*BoidRule*)

distance
Attack boids at max this distance

Type float in [0, 100], default 0.0

flee_distance
Flee to this distance

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.64 BoidRuleFollowLeader(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleFollowLeader**(*BoidRule*)

distance
Distance behind leader to follow

Type float in [0, 100], default 0.0

object
Follow this object instead of a boid

Type Object

queue_count
How many boids in a line

Type int in [0, 100], default 0

use_line
Follow leader in a line

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.65 BoidRuleGoal(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.**BoidRuleGoal**(*BoidRule*)

object
Goal object

Type Object

use_predict
Predict target movement

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.66 BoidSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**BoidSettings**(*bpy_struct*)

Settings for boid physics

accuracy

Accuracy of attack

Type float in [0, 1], default 0.0

active_boid_state

Type BoidRule, (readonly)

active_boid_state_index

Type int in [0, inf], default 0

aggression

Boid will fight this times stronger enemy

Type float in [0, 100], default 0.0

air_acc_max

Maximum acceleration in air (relative to maximum speed)

Type float in [0, 1], default 0.0

air_ave_max

Maximum angular velocity in air (relative to 180 degrees)

Type float in [0, 1], default 0.0

air_personal_space
Radius of boids personal space in air (% of particle size)

Type float in [0, 10], default 0.0

air_speed_max
Maximum speed in air

Type float in [0, 100], default 0.0

air_speed_min
Minimum speed in air (relative to maximum speed)

Type float in [0, 1], default 0.0

bank
Amount of rotation around velocity vector on turns

Type float in [0, 2], default 0.0

health
Initial boid health when born

Type float in [0, 100], default 0.0

height
Boid height relative to particle size

Type float in [0, 2], default 0.0

land_acc_max
Maximum acceleration on land (relative to maximum speed)

Type float in [0, 1], default 0.0

land_ave_max
Maximum angular velocity on land (relative to 180 degrees)

Type float in [0, 1], default 0.0

land_jump_speed
Maximum speed for jumping

Type float in [0, 100], default 0.0

land_personal_space
Radius of boids personal space on land (% of particle size)

Type float in [0, 10], default 0.0

land_smooth
How smoothly the boids land

Type float in [0, 10], default 0.0

land_speed_max
Maximum speed on land

Type float in [0, 100], default 0.0

land_stick_force
How strong a force must be to start effecting a boid on land

Type float in [0, 1000], default 0.0

pitch
Amount of rotation around side vector

Type float in [0, 2], default 0.0

range
The maximum distance from which a boid can attack

Type float in [0, 100], default 0.0

states

Type Collection of BoidState, (readonly)

strength
Maximum caused damage on attack per second

Type float in [0, 100], default 0.0

use_climb
Allow boids to climb goal objects

Type boolean, default False

use_flight
Allow boids to move in air

Type boolean, default False

use_land
Allow boids to move on land

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSettings.boids

1.4.67 BoidState(bpy_struct)

base class — bpy_struct

class bpy.types.**BoidState**(*bpy_struct*)

Boid state for boid physics

active_boid_rule

Type BoidRule, (readonly)

active_boid_rule_index

Type int in [0, inf], default 0

falloff

Type float in [0, 10], default 0.0

name

Boid state name

Type string, default ""

rule_fuzzy

Type float in [0, 1], default 0.0

rules

Type Collection of BoidRule, (readonly)

ruleset_type

How the rules in the list are evaluated

Type enum in ['FUZZY', 'RANDOM', 'AVERAGE'], default 'FUZZY'

volume

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- BoidSettings.states

1.4.68 Bone(bpy_struct)

base class — bpy_struct

class bpy.types.**Bone**(*bpy_struct*)

Bone in an Armature datablock

bbone_in

Length of first Bezier Handle (for B-Bones only)

Type float in [0, 2], default 0.0

bbone_out

Length of second Bezier Handle (for B-Bones only)

Type float in [0, 2], default 0.0

bbone_segments

Number of subdivisions of bone (for B-Bones only)

Type int in [1, 32], default 0

bbone_x

B-Bone X size

Type float in [0, 1000], default 0.0

bbone_z

B-Bone Z size

Type float in [0, 1000], default 0.0

children

Bones which are children of this bone

Type Collection of Bone, (readonly)

envelope_distance

Bone deformation distance (for Envelope deform only)

Type float in [0, 1000], default 0.0

envelope_weight

Bone deformation weight (for Envelope deform only)

Type float in [0, 1000], default 0.0

head

Location of head end of the bone relative to its parent

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_local

Location of head end of the bone relative to armature

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_radius
Radius of head of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

hide
Bone is not visible when it is not in Edit Mode (i.e. in Object or Pose Modes)

Type boolean, default False

hide_select
Bone is able to be selected

Type boolean, default False

layers
Layers bone exists in

Type boolean array of 32 items, default (False, False)

matrix
3x3 bone matrix

Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_local
4x4 bone matrix relative to armature

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

name

Type string, default “”

parent
Parent bone (in same Armature)

Type `Bone`, (readonly)

select

Type boolean, default False

select_head

Type boolean, default False

select_tail

Type boolean, default False

show_wire
Bone is always drawn as Wireframe regardless of viewport draw mode. Useful for non-obstructive custom bone shapes

Type boolean, default False

tail
Location of tail end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_local
Location of tail end of the bone relative to armature

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_radius
Radius of tail of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

use_connect
When bone has a parent, bone's head is struck to the parent's tail

Type boolean, default False, (readonly)

use_cyclic_offset
When bone doesn't have a parent, it receives cyclic offset effects

Type boolean, default False

use_deform
Bone does not deform any geometry

Type boolean, default False

use_envelope_multiply
When deforming bone, multiply effects of Vertex Group weights with Envelope influence

Type boolean, default False

use_inherit_rotation
Bone inherits rotation or scale from parent bone

Type boolean, default False

use_inherit_scale
Bone inherits scaling from parent bone

Type boolean, default False

use_local_location
Bone location is set in local space

Type boolean, default False

basename
The name of this bone before any '.' character (readonly)

center
The midpoint between the head and the tail. (readonly)

children
A list of all the bones children. (readonly)

children_recursive
a list of all children from this bone. (readonly)

children_recursive_basename
Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned.

(readonly)

length
The distance from head to tail, when set the head is moved to fit the length.

parent_recursive
A list of parents, starting with the immediate parent (readonly)

vector
The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis
Vector pointing down the x-axis of the bone.

(readonly)

y_axis
Vector pointing down the x-axis of the bone.

(readonly)

z_axis
Vector pointing down the x-axis of the bone.

(readonly)

evaluate_envelope(*point*)
Calculate bone envelope at given point.

Parameters **point** (*float array of 3 items in [-inf, inf]*) – Point, Position in 3d space to evaluate

Returns Factor, Envelope factor

Return type float in [-inf, inf]

parent_index(*parent_test*)
The same as 'bone in other_bone.parent_recursive' but saved generating a list.

translate(*vec*)
Utility function to add *vec* to the head and tail of this bone.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.bones
- ArmatureBones.active
- Bone.children
- Bone.parent
- PoseBone.bone

1.4.69 BoneGroup(bpy_struct)

base class — bpy_struct

class bpy.types.**BoneGroup**(*bpy_struct*)

Groups of Pose Channels (Bones)

color_set

Custom color set to use

Type enum in ['DEFAULT', 'THEME01', 'THEME02', 'THEME03', 'THEME04', 'THEME05', 'THEME06', 'THEME07', 'THEME08', 'THEME09', 'THEME10', 'THEME11', 'THEME12', 'THEME13', 'THEME14', 'THEME15', 'THEME16', 'THEME17', 'THEME18', 'THEME19', 'THEME20', 'CUSTOM'], default 'DEFAULT'

colors

Copy of the colors associated with the group's color set

Type ThemeBoneColorSet, (readonly, never None)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BoneGroups.active
- Pose.bone_groups
- PoseBone.bone_group

1.4.70 BoneGroups(bpy_struct)

base class — bpy_struct

class bpy.types.**BoneGroups**(*bpy_struct*)

Collection of bone groups

active

Active bone group for this pose

Type BoneGroup

active_index

Active index in bone groups array

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Pose.bone_groups

1.4.71 BooleanModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**BooleanModifier**(*Modifier*)

Boolean operations modifier

object

Mesh object to use for Boolean operation

Type Object

operation

Type enum in ['INTERSECT', 'UNION', 'DIFFERENCE'], default 'INTERSECT'

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.72 BooleanProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**BooleanProperty**(*Property*)

RNA boolean property definition

array_length
Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default
Default value for this number

Type boolean, default False, (readonly)

default_array
Default value for this array

Type boolean array of 3 items, default (False, False, False), (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.73 Brush(ID)

base classes — bpy_struct, ID

class bpy.types.**Brush**(*ID*)

Brush datablock for storing brush settings for painting and sculpting

auto_smooth_factor

Amount of smoothing to automatically apply to each stroke

Type float in [0, 1], default 0.0

blend

Brush blending mode

Type enum in ['MIX', 'ADD', 'SUB', 'MUL', 'LIGHTEN', 'DARKEN', 'ERASE_ALPHA', 'ADD_ALPHA'], default 'MIX'

clone_alpha

Opacity of clone image display

Type float in [0, 1], default 0.0

clone_image

Image for clone tool

Type Image

clone_offset

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

color

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

crease_pinch_factor

How much the crease brush pinches

Type float in [0, 1], default 0.666667

cursor_color_add

Color of cursor when adding

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor_color_subtract

Color of cursor when subtracting

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

curve

Editable falloff curve

Type CurveMapping, (readonly, never None)

direction

Type enum in ['ADD', 'SUBTRACT'], default 'ADD'

height

Affectable height of brush (layer height for layer tool, i.e.)

Type float in [0, 1], default 0.5

icon_filepath

File path to brush icon

Type string, default “”

imagepaint_tool

Type enum in [’DRAW’, ‘SOFTEN’, ‘SMEAR’, ‘CLONE’], default ‘DRAW’

jitter

Jitter the position of the brush while painting

Type float in [0, 1], default 0.0

normal_weight

How much grab will pull vertexes out of surface during a grab

Type float in [0, 1], default 0.0

plane_offset

Adjusts plane on which the brush acts towards or away from the object surface

Type float in [-2, 2], default 0.0

plane_trim

If a vertex is further from offset plane than this then it is not affected

Type float in [0, 1], default 0.5

rate

Interval between paints for Airbrush

Type float in [0.0001, 10000], default 0.0

sculpt_plane

Type enum in [’AREA’, ‘VIEW’, ‘X’, ‘Y’, ‘Z’], default ‘AREA’

sculpt_tool

Type enum in [’BLOB’, ‘CLAY’, ‘CREASE’, ‘DRAW’, ‘FILL’, ‘FLATTEN’, ‘GRAB’, ‘INFLATE’, ‘LAYER’, ‘NUDGE’, ‘PINCH’, ‘ROTATE’, ‘SCRAPE’, ‘SMOOTH’, ‘SNAKE_HOOK’, ‘THUMB’], default ‘BLOB’

size

Radius of the brush in pixels

Type int in [1, 2000], default 0

smooth_stroke_factor

Higher values give a smoother stroke

Type float in [0.5, 0.99], default 0.0

smooth_stroke_radius

Minimum distance from last point before stroke continues

Type int in [10, 200], default 0

spacing

Spacing between brush daubs as a percentage of brush diameter

Type int in [1, 1000], default 0

strength

How powerful the effect of the brush is when applied

Type float in [0, 10], default 0.5

stroke_method

Type enum in ['DOTS', 'DRAG_DOT', 'SPACE', 'ANCHORED', 'AIRBRUSH'], default 'DOTS'

texture

Type Texture

texture_angle_source_no_random

Type enum in ['USER', 'RAKE'], default 'USER'

texture_angle_source_random

Type enum in ['USER', 'RAKE', 'RANDOM'], default 'USER'

texture_overlay_alpha

Type int in [1, 100], default 0

texture_sample_bias

Value added to texture samples

Type float in [-1, 1], default 0.0

texture_slot

Type BrushTextureSlot, (readonly)

unprojected_radius

Radius of brush in Blender units

Type float in [0.001, inf], default 0.0

use_accumulate

Accumulate stroke dabs on top of each other

Type boolean, default False

use_adaptive_space

Space daubs according to surface orientation instead of screen space

Type boolean, default False

use_airbrush

Keep applying paint effect while holding mouse (spray)

Type boolean, default False

use_alpha

When this is disabled, lock alpha while painting

Type boolean, default False

use_anchor

Keep the brush anchored to the initial location

Type boolean, default False

use_custom_icon

Set the brush icon from an image file

Type boolean, default False

use_edge_to_edge

Drag anchor brush from edge-to-edge

Type boolean, default False

use_fixed_texture
Keep texture origin in fixed position

Type boolean, default False

use_frontface
Brush only affects vertexes that face the viewer

Type boolean, default False

use_inverse_smooth_pressure
Lighter pressure causes more smoothing to be applied

Type boolean, default False

use_locked_size
When locked brush stays same size relative to object; when unlocked brush size is given in pixels

Type boolean, default False

use_offset_pressure
Enable tablet pressure sensitivity for offset

Type boolean, default False

use_original_normal
When locked keep using normal of surface where stroke was initiated

Type boolean, default False

use_paint_sculpt
Use this brush in sculpt mode

Type boolean, default False

use_paint_texture
Use this brush in texture paint mode

Type boolean, default False

use_paint_vertex
Use this brush in vertex paint mode

Type boolean, default False

use_paint_weight
Use this brush in weight paint mode

Type boolean, default False

use_persistent
Sculpts on a persistent layer of the mesh

Type boolean, default False

use_plane_trim
Enable Plane Trim

Type boolean, default False

use_pressure_jitter
Enable tablet pressure sensitivity for jitter

Type boolean, default False

use_pressure_size
Enable tablet pressure sensitivity for size

Type boolean, default False

use_pressure_spacing
Enable tablet pressure sensitivity for spacing

Type boolean, default False

use_pressure_strength
Enable tablet pressure sensitivity for strength

Type boolean, default False

use_rake
Rotate the brush texture to match the stroke direction

Type boolean, default False

use_random_rotation
Rotate the brush texture at random

Type boolean, default False

use_restore_mesh
Allows a single dot to be carefully positioned

Type boolean, default False

use_smooth_stroke
Brush lags behind mouse and follows a smoother path

Type boolean, default False

use_space
Limit brush application to the distance specified by spacing

Type boolean, default False

use_space_atten
Automatically adjusts strength to give consistent results for different spacings

Type boolean, default False

use_texture_overlay
Show texture in viewport

Type boolean, default False

use_wrap
Enable torus wrapping while painting

Type boolean, default False

vertexpaint_tool

Type enum in ['MIX', 'ADD', 'SUB', 'MUL', 'BLUR', 'LIGHTEN', 'DARKEN'], default 'MIX'

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag

- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.brushes
- BlendDataBrushes.new
- BlendDataBrushes.remove
- Paint.brush

1.4.74 BrushTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.**BrushTextureSlot**(*TextureSlot*)

Texture slot for textures in a Brush datablock

angle

Defines brush texture rotation

Type float in [0, 6.28319], default 0.0

map_mode

Type enum in ['FIXED', 'TILED', '3D'], default 'FIXED'

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name

- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Brush.texture_slot

1.4.75 BuildModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**BuildModifier**(*Modifier*)

Build effect modifier

frame_duration

Specify the total time the build effect requires

Type float in [1, 300000], default 0.0

frame_start

Specify the start frame of the effect

Type float in [-300000, 300000], default 0.0

seed

Specify the seed for random if used

Type int in [1, 300000], default 0

use_random_order
Randomize the faces or edges during build

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.76 Camera(ID)

base classes — bpy_struct, ID

class bpy.types.**Camera**(*ID*)
Camera datablock for storing camera settings

angle
Perspective Camera lens field of view in degrees

Type float in [0.00640536, 3.01675], default 0.0

animation_data
Animation data for this datablock

Type AnimData, (readonly)

clip_end
Camera far clipping distance

Type float in [1, inf], default 0.0

clip_start
Camera near clipping distance

Type float in [0, inf], default 0.0

dof_distance
Distance to the focus point for depth of field

Type float in [0, 5000], default 0.0

dof_object
Use this object to define the depth of field focal point

Type `Object`

draw_size
Apparent size of the Camera object in the 3D View

Type float in [0.01, 1000], default 0.0

lens
Perspective Camera lens value in millimeters

Type float in [1, 5000], default 0.0

lens_unit
Unit to edit lens in for the user interface

Type enum in ['MILLIMETERS', 'DEGREES'], default 'MILLIMETERS'

ortho_scale
Orthographic Camera scale (similar to zoom)

Type float in [0.01, 1000], default 0.0

passepartout_alpha
Opacity (alpha) of the darkened overlay in Camera view

Type float in [0, 1], default 0.0

shift_x
Perspective Camera horizontal shift

Type float in [-10, 10], default 0.0

shift_y
Perspective Camera vertical shift

Type float in [-10, 10], default 0.0

show_limits
Draw the clipping range and focus point on the camera

Type boolean, default False

show_mist
Draw a line from the Camera to indicate the mist area

Type boolean, default False

show_name
Show the active Camera's name in Camera view

Type boolean, default False

show_passepartout
Show a darkened overlay outside the image area in Camera view

Type boolean, default False

show_title_safe
Show indicators for the title safe zone in Camera view

Type boolean, default False

type
Camera types

Type enum in ['PERSP', 'ORTHO'], default 'PERSP'

use_panorama
Render the scene with a cylindrical camera for pseudo-fisheye lens effects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.cameras
- BlendDataCameras.new
- BlendDataCameras.remove

1.4.77 CameraActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**CameraActuator** (*Actuator*)

Actuator to ..

axis

Specify the axis the Camera will try to get behind

Type enum in ['X', 'Y'], default 'X'

height

Type float in [-inf, inf], default 0.0

max

Type float in [-inf, inf], default 0.0

min

Type float in [-inf, inf], default 0.0

object

Look at this Object

Type Object

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.78 CastModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**CastModifier**(*Modifier*)

Cast modifier to cast to other shapes

cast_type

Type enum in ['SPHERE', 'CYLINDER', 'CUBOID'], default 'SPHERE'

factor

Type float in [-inf, inf], default 0.0

object

Control object: if available, its location determines the center of the effect

Type Object

radius

Only deform vertices within this distance from the center of the effect (leave as 0 for infinite.)

Type float in [0, inf], default 0.0

size

Size of projection shape (leave as 0 for auto.)

Type float in [0, inf], default 0.0

use_radius_as_size

Use radius as size of projection shape (0 = auto)

Type boolean, default False

use_transform

Use object transform to control projection shape

Type boolean, default False

use_x

Type boolean, default False

use_y

Type boolean, default False

use_z

Type boolean, default False

vertex_group

Vertex group name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.79 ChannelDriverVariables(bpy_struct)

base class — bpy_struct

class bpy.types.**ChannelDriverVariables**(*bpy_struct*)

Collection of channel driver Variables

new()

Add a new variable for the driver.

Returns Newly created Driver Variable.

Return type DriverVariable

remove(*variable*)

Remove an existing variable from the driver.

Parameters **variable** (DriverVariable, (never None)) – Variable to remove from the driver.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Driver.variables

1.4.80 ChildOfConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**ChildOfConstraint**(*Constraint*)

Creates constraint-based parent-child relationship

subtarget

Type string, default “”

target

Target Object

Type Object

use_location_x

Use X Location of Parent

Type boolean, default False

use_location_y

Use Y Location of Parent

Type boolean, default False

use_location_z

Use Z Location of Parent

Type boolean, default False

use_rotation_x

Use X Rotation of Parent

Type boolean, default False

use_rotation_y
Use Y Rotation of Parent

Type boolean, default False

use_rotation_z
Use Z Rotation of Parent

Type boolean, default False

use_scale_x
Use X Scale of Parent

Type boolean, default False

use_scale_y
Use Y Scale of Parent

Type boolean, default False

use_scale_z
Use Z Scale of Parent

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

1.4.81 ChildParticle(bpy_struct)

base class — bpy_struct

class bpy.types.**ChildParticle**(*bpy_struct*)

Child particle interpolated from simulated or edited particles

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.child_particles

1.4.82 ClampToConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**ClampToConstraint**(*Constraint*)

Constrains an object's location to the nearest point along the target path

main_axis

Main axis of movement

Type enum in ['CLAMPTO_AUTO', 'CLAMPTO_X', 'CLAMPTO_Y', 'CLAMPTO_Z'], default 'CLAMPTO_AUTO'

target

Target Object

Type Object

use_cyclic

Treat curve as cyclic curve (no clamping to curve bounding box

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.83 ClothCollisionSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**ClothCollisionSettings**(*bpy_struct*)

Cloth simulation settings for self collision and collision with other objects

collision_quality

How many collision iterations should be done. (higher is better quality but slower)

Type int in [1, 20], default 0

distance_min
Minimum distance between collision objects before collision response takes in

Type float in [0.001, 1], default 0.0

friction
Friction force if a collision happened. (higher = less movement)

Type float in [0, 80], default 0.0

group
Limit colliders to this Group

Type Group

self_collision_quality
How many self collision iterations should be done. (higher is better quality but slower)

Type int in [1, 10], default 0

self_distance_min
0.5 means no distance at all, 1.0 is maximum distance

Type float in [0.5, 1], default 0.0

self_friction
Friction/damping with self contact

Type float in [0, 80], default 0.0

use_collision
Enable collisions with other objects

Type boolean, default False

use_self_collision
Enable self collisions

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- ClothModifier.collision_settings

1.4.84 ClothModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ClothModifier**(*Modifier*)

Cloth simulation modifier

collision_settings

Type ClothCollisionSettings, (readonly, never None)

point_cache

Type PointCache, (readonly, never None)

settings

Type ClothSettings, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.cloth

1.4.85 ClothSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**ClothSettings** (*bpy_struct*)

Cloth simulation settings for an object

air_damping

Air has normally some thickness which slows falling things down

Type float in [0, 10], default 0.0

bending_stiffness

Wrinkle coefficient. (higher = less smaller but more big wrinkles)

Type float in [0, 10000], default 0.0

bending_stiffness_max

Maximum bending stiffness value

Type float in [0, 10000], default 0.0

collider_friction

Type float in [0, 1], default 0.0

effector_weights

Type EffectorWeights, (readonly)

goal_default

Default Goal (vertex target position) value, when no Vertex Group used

Type float in [0, 1], default 0.0

goal_friction

Goal (vertex target position) friction

Type float in [0, 50], default 0.0

goal_max

Goal maximum, vertex group weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_min

Goal minimum, vertex group weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_spring

Goal (vertex target position) spring stiffness

Type float in [0, 0.999], default 0.0

gravity
Gravity or external force vector

Type float array of 3 items in [-100, 100], default (0.0, 0.0, 0.0)

internal_friction

Type float in [0, 1], default 0.0

mass
Mass of cloth material

Type float in [0, 10], default 0.0

pin_stiffness
Pin (vertex target position) spring stiffness

Type float in [0, 50], default 0.0

pre_roll
Simulation starts on this frame

Type int in [0, 200], default 0

quality
Quality of the simulation in steps per frame. (higher is better quality but slower)

Type int in [4, 80], default 0

rest_shape_key
Shape key to use the rest spring lengths from

Type `ShapeKey`

spring_damping
Damping of cloth velocity. (higher = more smooth, less jiggling)

Type float in [0, 50], default 0.0

structural_stiffness
Overall stiffness of structure

Type float in [0, 10000], default 0.0

structural_stiffness_max
Maximum structural stiffness value

Type float in [0, 10000], default 0.0

use_pin_cloth
Enable pinning of cloth vertices to other objects/positions

Type boolean, default False

use_stiffness_scale
If enabled, stiffness can be scaled along a weight painted vertex group

Type boolean, default False

vertex_group_bending
Vertex group for fine control over bending stiffness

Type string, default “”

vertex_group_mass
Vertex Group for pinning of vertices

Type string, default “”

vertex_group_structural_stiffness
Vertex group for fine control over structural stiffness

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothModifier.settings

1.4.86 CloudsTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**CloudsTexture** (*Texture*)
Procedural noise texture

cloud_type

Type enum in [’GREYSCALE’, ‘COLOR’], default ‘GREYSCALE’

nabla
Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis
Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_depth
Sets the depth of the cloud calculation

Type int in [0, 30], default 0

noise_scale
Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.87 CollectionProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**CollectionProperty**(*Property*)

RNA collection property to define lists, arrays and mappings

fixed_type

Fixed pointer type, empty if variable type

Type Struct, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.88 CollisionModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**CollisionModifier**(*Modifier*)

Collision modifier defining modifier stack position used for collision

settings

Type CollisionSettings, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.89 CollisionSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**CollisionSensor**(*Sensor*)

Sensor to detect objects colliding with the current object, with more settings than the Touch sensor

material

Only look for Objects with this material (blank = all objects)

Type string, default ""

property

Only look for Objects with this property (blank = all objects)

Type string, default ""

use_material

Toggle collision on material or property

Type boolean, default False

use_pulse

Changes to the set of colliding objects generates pulse

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.90 CollisionSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**CollisionSettings**(*bpy_struct*)

Collision settings for object in physics simulation

absorption

How much of effector force gets lost during collision with this object (in percent)

Type float in [0, 1], default 0.0

damping

Amount of damping during collision

Type float in [0, 1], default 0.0

damping_factor

Amount of damping during particle collision

Type float in [0, 1], default 0.0

damping_random

Random variation of damping

Type float in [0, 1], default 0.0

friction_factor

Amount of friction during particle collision

Type float in [0, 1], default 0.0

friction_random

Random variation of friction

Type float in [0, 1], default 0.0

permeability

Chance that the particle will pass through the mesh

Type float in [0, 1], default 0.0

stickness

Amount of stickness to surface collision

Type float in [0, 10], default 0.0

thickness_inner
Inner face thickness

Type float in [0.001, 1], default 0.0

thickness_outer
Outer face thickness

Type float in [0.001, 1], default 0.0

use
Enable this objects as a collider for physics systems

Type boolean, default False

use_particle_kill
Kill collided particles

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CollisionModifier.settings
- Object.collision

1.4.91 ColorRamp(bpy_struct)

base class — bpy_struct

class bpy.types.**ColorRamp**(*bpy_struct*)
Color ramp mapping a scalar value to a color

elements

Type ColorRampElements collection of ColorRampElement, (readonly)

interpolation

Type enum in ['EASE', 'CARDINAL', 'LINEAR', 'B_SPLINE', 'CONSTANT'], default 'LINEAR'

evaluate(*position*)

Evaluate ColorRamp

Parameters **position** (*float in [0, 1]*) – Position, Evaluate ColorRamp at position

Returns Color, Color at given position

Return type float array of 4 items in [-inf, inf]

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CompositorNodeValToRGB.color_ramp
- Material.diffuse_ramp
- Material.specular_ramp
- PointDensity.color_ramp
- ShaderNodeValToRGB.color_ramp
- Texture.color_ramp
- TextureNodeValToRGB.color_ramp
- UserPreferencesSystem.weight_color_range

1.4.92 ColorRampElement(bpy_struct)

base class — bpy_struct

class bpy.types.**ColorRampElement**(*bpy_struct*)

Element defining a color at a position in the color ramp

color

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

position

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ColorRamp.elements
- ColorRampElements.new
- ColorRampElements.remove

1.4.93 ColorRampElements(bpy_struct)

base class — bpy_struct

class bpy.types.**ColorRampElements**(*bpy_struct*)

Collection of Color Ramp Elements

new(*position*)

Add element to ColorRamp

Parameters **position** (*float in [0, 1]*) – Position, Position to add element

Returns New element.

Return type ColorRampElement

remove(*element*)

Delete element from ColorRamp

Parameters **element** (ColorRampElement, (never None)) – Element to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ColorRamp.elements

1.4.94 ColorSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.**ColorSequence**(*EffectSequence*)

Sequence strip creating an image filled with a single g

color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data
- Sequence.name

- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.95 CompositorNode(Node)

base classes — bpy_struct, Node

subclasses — CompositorNodeSepHSVA, CompositorNodeValToRGB, CompositorNodeSepYCCA, CompositorNodeSetAlpha, CompositorNodeCrop, CompositorNodeMath, CompositorNodeCurveRGB, CompositorNodeDilateErode, CompositorNodeGamma, CompositorNodeRotate, CompositorNodeLensdist, CompositorNodeLumaMatte, CompositorNodeTranslate, CompositorNodeCombYCCA, CompositorNodeBilateralblur, CompositorNodeZcombine, CompositorNodeFilter, CompositorNodePremulKey, CompositorNodeMixRGB, CompositorNodeTime, CompositorNodeValue, CompositorNodeHueCorrect, CompositorNodeNormal, CompositorNodeIDMask, CompositorNodeVecBlur, CompositorNodeRLayers, CompositorNodeComposite, CompositorNodeCombRGBA, CompositorNodeViewer, CompositorNodeCombHSVA, CompositorNodeOutputFile, CompositorNodeInvert, CompositorNodeFlip, CompositorNodeDistanceMatte, CompositorNodeRGBToBW, CompositorNodeCombYUVA, CompositorNodeBlur, CompositorNodeDefocus, CompositorNodeGlare, CompositorNodeDiffMatte, CompositorNodeImage, CompositorNodeDBlur, CompositorNodeMapValue, CompositorNodeBrightContrast, CompositorNodeTexture, CompositorNodeLevels, CompositorNodeNormalize, CompositorNodeChannelMatte, CompositorNodeRGB, CompositorNodeColorSpill, CompositorNodeSepRGBA, CompositorNodeScale, CompositorNodeMapUV, CompositorNodeChromaMatte, CompositorNodeDisplace, CompositorNodeColorBalance, CompositorNodeTonemap, CompositorNodeAlphaOver, CompositorNodeColorMatte, CompositorNodeHueSat, CompositorNodeSepYUVA, CompositorNodeCurveVec, CompositorNodeSplitViewer

class bpy.types.**CompositorNode**(*Node*)

type

Type enum in ['VIEWER', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RGBTOBW', 'NORMAL', 'CURVE_VEC', 'CURVE_RGB', 'ALPHAOVER', 'BLUR', 'FILTER', 'MAP_VALUE', 'TIME', 'VECBLUR', 'SEPRGBA', 'SEPHSVA', 'SETALPHA', 'HUE_SAT', 'IMAGE', 'R_LAYERS', 'COMPOSITE', 'OUTPUT_FILE', 'TEXTURE', 'TRANSLATE', 'ZCOMBINE', 'COMBRGBA', 'DILATEERODE', 'ROTATE', 'SCALE', 'SEPYCCA', 'COMBYCCA', 'SEPYUVA', 'COMBYUVA', 'DIFF_MATTE', 'COLOR_SPILL', 'CHROMA_MATTE', 'CHANNEL_MATTE', 'FLIP', 'SPLITVIEWER', 'MAP_UV', 'ID_MASK', 'DEFOCUS', 'DISPLACE', 'COMBHSVA', 'MATH', 'LUMA_MATTE', 'BRIGHTCONTRAST', 'GAMMA', 'INVERT', 'NORMALIZE', 'CROP', 'DBLUR', 'BILATERALBLUR', 'PREMULKEY', 'DISTANCE_MATTE',

'LEVELS', 'COLOR_MATTE', 'COLORBALANCE', 'HUECORRECT', 'GLARE', 'TONEMAP', 'LENSDIST', 'SCRIPT', 'GROUP'], default 'VIEWER', (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.96 CompositorNodeAlphaOver(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeAlphaOver**(*CompositorNode*)

premul
Mix Factor

Type float in [0, 1], default 0.0

use_premultiply

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs

- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.97 CompositorNodeBilateralblur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeBilateralblur**(*CompositorNode*)

iterations

Type int in [1, 128], default 0

sigma_color

Type float in [0.01, 3], default 0.0

sigma_space

Type float in [0.01, 30], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.98 CompositorNodeBlur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeBlur**(*CompositorNode*)

aspect_correction
Type of aspect correction to use

Type enum in ['NONE', 'Y', 'X'], default 'NONE'

factor

Type float in [0, 2], default 0.0

factor_x

Type float in [0, 100], default 0.0

factor_y

Type float in [0, 100], default 0.0

filter_type

Type enum in ['FLAT', 'TENT', 'QUAD', 'CUBIC', 'GAUSS', 'FAST_GAUSS', 'CATROM', 'MITCH'], default 'FLAT'

size_x

Type int in [0, 2048], default 0

size_y

Type int in [0, 2048], default 0

use_bokeh
Uses circular filter (slower)

Type boolean, default False

use_gamma_correction
Applies filter on gamma corrected values

Type boolean, default False

use_relative
Use relative (percent) values to define blur radius

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.99 CompositorNodeBrightContrast(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeBrightContrast**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.100 CompositorNodeChannelMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeChannelMatte**(*CompositorNode*)

color_space

Type enum in ['RGB', 'HSV', 'YUV', 'YCC'], default 'RGB'

limit_channel

Limit by this channels value

Type enum in ['R', 'G', 'B'], default 'R'

limit_max

Values higher than this setting are 100% opaque

Type float in [0, 1], default 0.0

limit_method

Algorithm to use to limit channel

Type enum in ['SINGLE', 'MAX'], default 'SINGLE'

limit_min

Values lower than this setting are 100% keyed

Type float in [0, 1], default 0.0

matte_channel

Channel used to determine matte

Type enum in ['R', 'G', 'B'], default 'R'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.101 CompositorNodeChromaMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeChromaMatte**(*CompositorNode*)

gain
Alpha gain

Type float in [0, 1], default 0.0

lift
Alpha lift

Type float in [0, 1], default 0.0

shadow_adjust
Adjusts the brightness of any shadows captured

Type float in [0, 1], default 0.0

threshold
Tolerance below which colors will be considered as exact matches

Type float in [0, 30], default 0.0

tolerance
Tolerance for a color to be considered a keying color

Type float in [1, 80], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location

- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.102 CompositorNodeColorBalance(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeColorBalance**(*CompositorNode*)

correction_method

Type enum in ['LIFT_GAMMA_GAIN', 'OFFSET_POWER_SLOPE'], default 'LIFT_GAMMA_GAIN'

gain

Correction for Highlights

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

gamma

Correction for Midtones

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

lift

Correction for Shadows

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

offset

Correction for Shadows

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

power

Correction for Midtones

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

slope
Correction for Highlights

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.103 CompositorNodeColorMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeColorMatte**(*CompositorNode*)

color_hue
Hue tolerance for colors to be considered a keying color

Type float in [0, 1], default 0.0

color_saturation
Saturation Tolerance for the color

Type float in [0, 1], default 0.0

color_value
Value Tolerance for the color

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.104 CompositorNodeColorSpill(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeColorSpill**(*CompositorNode*)

channel

Type enum in ['R', 'G', 'B'], default 'R'

limit_channel

Type enum in ['R', 'G', 'B'], default 'R'

limit_method

Type enum in ['SIMPLE', 'AVERAGE'], default 'SIMPLE'

ratio

Scale limit by value

Type float in [0.5, 1.5], default 0.0

unspill_blue

Blue spillmap scale

Type float in [0, 1.5], default 0.0

unspill_green
Green spillmap scale

Type float in [0, 1.5], default 0.0

unspill_red
Red spillmap scale

Type float in [0, 1.5], default 0.0

use_unspill
Compensate all channels (diffenrently) by hand

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.105 CompositorNodeCombHSVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCombHSVA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.106 CompositorNodeCombRGBA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCombRGBA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.107 CompositorNodeCombYCCA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCombYCCA**(*CompositorNode*)

mode

Type enum in ['ITUBT601', 'ITUBT709', 'JFIF'], default 'ITUBT601'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.108 CompositorNodeCombYUVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCombYUVA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.109 CompositorNodeComposite(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeComposite**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.110 CompositorNodeCrop(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCrop**(*CompositorNode*)

max_x

Type int in [0, 10000], default 0

max_y

Type int in [0, 10000], default 0

min_x

Type int in [0, 10000], default 0

min_y

Type int in [0, 10000], default 0

rel_max_x

Type float in [0, 1], default 0.0

rel_max_y

Type float in [0, 1], default 0.0

rel_min_x

Type float in [0, 1], default 0.0

rel_min_y

Type float in [0, 1], default 0.0

relative

Use relative values to crop image

Type boolean, default False

use_crop_size

Whether to crop the size of the input image

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.111 CompositorNodeCurveRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCurveRGB**(*CompositorNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.112 CompositorNodeCurveVec(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeCurveVec**(*CompositorNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.113 CompositorNodeDBlur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDBlur**(*CompositorNode*)

angle

Type float in [0, 360], default 0.0

center_x

Type float in [0, 1], default 0.0

center_y

Type float in [0, 1], default 0.0

distance

Type float in [-1, 1], default 0.0

iterations

Type int in [1, 32], default 0

spin

Type float in [-360, 360], default 0.0

use_wrap

Type boolean, default False

zoom

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.114 CompositorNodeDefocus(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDefocus**(*CompositorNode*)

angle
Bokeh shape rotation offset in degrees

Type int in [0, 90], default 0

blur_max
blur limit, maximum CoC radius, 0=no limit

Type float in [0, 10000], default 0.0

bokeh

Type enum in ['OCTAGON', 'HEPTAGON', 'HEXAGON', 'PENTAGON', 'SQUARE', 'TRIANGLE', 'CIRCLE'], default 'CIRCLE'

f_stop
Amount of focal blur, 128=infinity=perfect focus, half the value doubles the blur radius

Type float in [0, 128], default 0.0

samples
Number of samples (16=grainy, higher=less noise)

Type int in [16, 256], default 0

threshold
CoC radius threshold, prevents background bleed on in-focus midground, 0=off

Type float in [0, 100], default 0.0

use_gamma_correction
Enable gamma correction before and after main process

Type boolean, default False

use_preview
Enable sampling mode, useful for preview when using low samplecounts

Type boolean, default False

use_zbuffer
Disable when using an image as input instead of actual zbuffer (auto enabled if node not image based, eg. time node)

Type boolean, default False

z_scale
Scales the Z input when not using a zbuffer, controls maximum blur designated by the color white or input value 1

Type float in [0, 1000], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.115 CompositorNodeDiffMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDiffMatte**(*CompositorNode*)

falloff
Color distances below this additional threshold are partially keyed

Type float in [0, 1], default 0.0

tolerance
Color distances below this threshold are keyed

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.116 CompositorNodeDilateErode(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDilateErode**(*CompositorNode*)

distance
Distance to grow/shrink (number of iterations)

Type int in [-100, 100], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.117 CompositorNodeDisplace(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDisplace**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.118 CompositorNodeDistanceMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeDistanceMatte**(*CompositorNode*)

falloff

Color distances below this additional threshold are partially keyed

Type float in [0, 1], default 0.0

tolerance
Color distances below this threshold are keyed

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.119 CompositorNodeFilter(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeFilter**(*CompositorNode*)

filter_type

Type enum in ['SOFTEN', 'SHARPEN', 'LAPLACE', 'SOBEL', 'PREWITT', 'KIRSCH', 'SHADOW'], default 'SOFTEN'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs

- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.120 CompositorNodeFlip(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeFlip**(*CompositorNode*)

axis

Type enum in ['X', 'Y', 'XY'], default 'X'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.121 CompositorNodeGamma(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeGamma**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.122 CompositorNodeGlare(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeGlare**(*CompositorNode*)

angle_offset
Streak angle offset in degrees

Type int in [0, 180], default 0

color_modulation
Amount of Color Modulation, modulates colors of streaks and ghosts for a spectral dispersion effect

Type float in [0, 1], default 0.0

fade
Streak fade-out factor

Type float in [0.75, 1], default 0.0

glare_type

Type enum in ['GHOSTS', 'STREAKS', 'FOG_GLOW', 'SIMPLE_STAR'], default 'SIMPLE_STAR'

iterations

Type int in [2, 5], default 0

mix
-1 is original image only, 0 is exact 50/50 mix, 1 is processed image only

Type float in [-1, 1], default 0.0

quality
If not set to high quality, the effect will be applied to a low-res copy of the source image

Type enum in ['HIGH', 'MEDIUM', 'LOW'], default 'HIGH'

size
Glow/glare size (not actual size; relative to initial size of bright area of pixels)

Type int in [6, 9], default 0

streaks
Total number of streaks

Type int in [2, 16], default 0

threshold
The glare filter will only be applied to pixels brighter than this value

Type float in [0, 1000], default 0.0

use_rotate_45
Simple star filter: add 45 degree rotation offset

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.123 CompositorNodeHueCorrect(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeHueCorrect**(*CompositorNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.124 CompositorNodeHueSat(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeHueSat**(*CompositorNode*)

color_hue

Type float in [0, 1], default 0.0

color_saturation

Type float in [0, 2], default 0.0

color_value

Type float in [0, 2], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.125 CompositorNodeIDMask(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeIDMask**(*CompositorNode*)

index
Pass index number to convert to alpha

Type int in [0, 10000], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.126 CompositorNodeImage(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeImage**(*CompositorNode*)

frame_duration
Number of images used in animation

Type int in [0, 300000], default 0

frame_offset
Offsets the number of the frame to use in the animation

Type int in [-300000, 300000], default 0

frame_start

Type int in [-300000, 300000], default 0

image

Type Image

layer

Type enum in ['PLACEHOLDER'], default 'PLACEHOLDER'

use_auto_refresh

Type boolean, default False

use_cyclic

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.127 CompositorNodeInvert(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeInvert**(*CompositorNode*)

invert_alpha

Type boolean, default False

invert_rgb

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.128 CompositorNodeLensdist(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeLensdist**(*CompositorNode*)

use_fit

For positive distortion factor only: scale image such that black areas are not visible

Type boolean, default False

use_jitter

Enable/disable jittering; faster, but also noisier

Type boolean, default False

use_projector

Enable/disable projector mode. Effect is applied in horizontal direction only

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.129 CompositorNodeLevels(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeLevels**(*CompositorNode*)

channel

Type enum in ['COMBINED_RGB', 'RED', 'GREEN', 'BLUE', 'LUMINANCE'], default 'COMBINED_RGB'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.130 CompositorNodeLumaMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeLumaMatte**(*CompositorNode*)

limit_max
Values higher than this setting are 100% opaque

Type float in [0, 1], default 0.0

limit_min
Values lower than this setting are 100% keyed

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.131 CompositorNodeMapUV(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeMapUV**(*CompositorNode*)

alpha

Type int in [0, 100], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.132 CompositorNodeMapValue(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeMapValue**(*CompositorNode*)

max

Type float array of 1 items in [-1000, 1000], default (0.0)

min

Type float array of 1 items in [-1000, 1000], default (0.0)

offset

Type float array of 1 items in [-1000, 1000], default (0.0)

size

Type float array of 1 items in [-1000, 1000], default (0.0)

use_max

Type boolean, default False

use_min

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.133 CompositorNodeMath(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeMath**(*CompositorNode*)

operation

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.134 CompositorNodeMixRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeMixRGB**(*CompositorNode*)

blend_type

Type enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'SCREEN', 'OVERLAY', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'DODGE', 'BURN', 'COLOR', 'VALUE', 'SATURATION', 'HUE', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

use_alpha
Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.135 CompositorNodeNormal(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeNormal**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.136 CompositorNodeNormalize(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeNormalize**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.137 CompositorNodeOutputFile(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeOutputFile**(*CompositorNode*)

exr_codec

Type enum in ['NONE', 'PXR24', 'ZIP', 'PIZ', 'RLE'], default 'NONE'

filepath

Output path for the image, same functionality as render output.

Type string, default ""

frame_end

Type int in [0, 300000], default 0

frame_start

Type int in [0, 300000], default 0

image_type

Type enum in ['TARGA', 'RAW_TARGA', 'PNG', 'BMP', 'JPEG', 'IRIS', 'RADIANCE_HDR', 'CINEON', 'DPX', 'OPENEXR'], default 'TARGA'

quality

Type int in [1, 100], default 0

use_exr_half

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.138 CompositorNodePremulKey(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodePremulKey**(*CompositorNode*)

mapping
Conversion between premultiplied alpha and key alpha

Type enum in ['KEY_TO_PREMUL', 'PREMUL_TO_KEY'], default 'KEY_TO_PREMUL'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.139 CompositorNodeRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeRGB**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.140 CompositorNodeRGBToBW(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeRGBToBW**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.141 CompositorNodeRLayers(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeRLayers**(*CompositorNode*)

layer

Type enum in ['PLACEHOLDER'], default 'PLACEHOLDER'

scene

Type Scene

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.142 CompositorNodeRotate(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeRotate**(*CompositorNode*)

filter_type
Method to use to filter rotation

Type enum in ['NEAREST', 'BILINEAR', 'BICUBIC'], default 'NEAREST'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.143 CompositorNodeScale(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeScale**(*CompositorNode*)

space
Coordinate space to scale relative to

Type enum in ['RELATIVE', 'ABSOLUTE', 'SCENE_SIZE', 'RENDER_SIZE'], default 'RELATIVE'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.144 CompositorNodeSepHSVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSepHSVA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.145 CompositorNodeSepRGBA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSepRGBA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.146 CompositorNodeSepYCCA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSepYCCA**(*CompositorNode*)

mode

Type enum in ['ITUBT601', 'ITUBT709', 'JFIF'], default 'ITUBT601'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.147 CompositorNodeSepYUVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSepYUVA**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.148 CompositorNodeSetAlpha(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSetAlpha**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.149 CompositorNodeSplitViewer(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeSplitViewer**(*CompositorNode*)

axis

Type enum in ['X', 'Y'], default 'X'

factor

Type int in [0, 100], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.150 CompositorNodeTexture(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeTexture**(*CompositorNode*)

node_output

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

texture

Type Texture

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.151 CompositorNodeTime(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeTime**(*CompositorNode*)

curve

Type CurveMapping, (readonly)

frame_end

Type int in [-32768, 32767], default 0

frame_start

Type int in [-32768, 32767], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs

- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.152 CompositorNodeTonemap(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeTonemap**(*CompositorNode*)

adaptation
If 0, global; if 1, based on pixel intensity

Type float in [0, 1], default 0.0

contrast
Set to 0 to use estimate from input image

Type float in [0, 1], default 0.0

correction
If 0, same for all channels; if 1, each independent

Type float in [0, 1], default 0.0

gamma
If not used, set to 1

Type float in [0.001, 3], default 0.0

intensity
If less than zero, darkens image; otherwise, makes it brighter

Type float in [-8, 8], default 0.0

key
The value the average luminance is mapped to

Type float in [0, 1], default 0.0

offset
Normally always 1, but can be used as an extra control to alter the brightness curve

Type float in [0.001, 10], default 0.0

tonemap_type

Type enum in ['RD_PHOTORECEPTOR', 'RH_SIMPLE'], default 'RH_SIMPLE'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.153 CompositorNodeTranslate(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeTranslate**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.154 CompositorNodeTree(NodeTree)

base classes — bpy_struct, ID, NodeTree

class bpy.types.**CompositorNodeTree**(*NodeTree*)

Node tree consisting of linked nodes used for compositing

nodes

Type CompositorNodes collection of Node, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- NodeTree.animation_data
- NodeTree.grease_pencil
- NodeTree.inputs
- NodeTree.links
- NodeTree.outputs
- NodeTree.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.155 CompositorNodeValToRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeValToRGB**(*CompositorNode*)

color_ramp

Type ColorRamp, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

1.4.156 CompositorNodeValue(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeValue**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.157 CompositorNodeVecBlur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeVecBlur**(*CompositorNode*)

factor

Scaling factor for motion vectors; actually 'shutter speed' in frames

Type float in [0, 2], default 0.0

samples

Type int in [1, 256], default 0

speed_max
Maximum speed, or zero for none

Type int in [0, 1024], default 0

speed_min
Minimum speed for a pixel to be blurred; used to separate background from foreground

Type int in [0, 1024], default 0

use_curved
Interpolate between frames in a bezier curve, rather than linearly

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.158 CompositorNodeViewer(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeViewer**(*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.159 CompositorNodeZcombine(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.**CompositorNodeZcombine**(*CompositorNode*)

use_alpha
Takes Alpha channel into account when doing the Z operation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.160 CompositorNodes(bpy_struct)

base class — bpy_struct

class bpy.types.**CompositorNodes**(*bpy_struct*)

Collection of Compositor Nodes

new(*type*, *group=None*)

Add a node to this node tree.

Parameters

- **type** (*enum in ['VIEWER', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RGBTOBW', 'NORMAL', 'CURVE_VEC', 'CURVE_RGB', 'ALPHAOVER', 'BLUR', 'FILTER', 'MAP_VALUE', 'TIME', 'VECBLUR', 'SEPRGBA', 'SEPHSVA', 'SETALPHA', 'HUE_SAT', 'IMAGE', 'R_LAYERS', 'COMPOSITE', 'OUTPUT_FILE', 'TEXTURE', 'TRANSLATE', 'ZCOMBINE', 'COMBRGBA', 'DILATEERODE', 'ROTATE', 'SCALE', 'SEPYCCA', 'COMBYCCA', 'SEPYUVA', 'COMBYUVA', 'DIFF_MATTE', 'COLOR_SPILL', 'CHROMA_MATTE', 'CHANNEL_MATTE', 'FLIP', 'SPLITVIEWER', 'MAP_UV', 'ID_MASK', 'DEFOCUS', 'DISPLACE', 'COMBHSVA', 'MATH', 'LUMA_MATTE', 'BRIGHTCONTRAST', 'GAMMA', 'INVERT', 'NORMALIZE', 'CROP', 'DBLUR', 'BILATERALBLUR', 'PREMULKEY', 'DISTANCE_MATTE', 'LEVELS', 'COLOR_MATTE', 'COLORBALANCE', 'HUECORRECT', 'GLARE', 'TONEMAP', 'LENSDIST', 'SCRIPT', 'GROUP']*) – Type, Type of node to add
- **group** (NodeTree, (optional)) – The group tree

Returns New node.

Return type Node

remove(*node*)

remove a node from this node tree.

Parameters **node** (Node) – The node to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CompositorNodeTree.nodes

1.4.161 ConsoleLine(bpy_struct)

base class — bpy_struct

class bpy.types.**ConsoleLine**(*bpy_struct*)

Input line for the interactive console

body

Text in the line

Type string, default ""

current_character

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceConsole.history
- SpaceConsole.scrollback

1.4.162 Constraint(bpy_struct)

base class — bpy_struct

subclasses — KinematicConstraint, CopyScaleConstraint, ShrinkwrapConstraint, FollowPathConstraint, LockedTrackConstraint, CopyTransformsConstraint, PythonConstraint, LimitDistanceConstraint, TransformConstraint, PivotConstraint, ClampToConstraint, StretchToConstraint, LimitRotationConstraint, LimitLocationConstraint, ChildOfConstraint, CopyRotationConstraint, DampedTrackConstraint, TrackToConstraint, SplineIKConstraint, MaintainVolumeConstraint, LimitScaleConstraint, RigidBodyJointConstraint, FloorConstraint, ActionConstraint, CopyLocationConstraint

class bpy.types.**Constraint**(*bpy_struct*)

Constraint modifying the transformation of objects and bones

active

Constraint is the one being edited

Type boolean, default False

error_location

Amount of residual error in Blender space unit for constraints that work on position

Type float in [-inf, inf], default 0.0, (readonly)

error_rotation

Amount of residual error in radiant for constraints that work on orientation

Type float in [-inf, inf], default 0.0, (readonly)

influence

Amount of influence constraint will have on the final solution

Type float in [0, 1], default 0.0

is_proxy_local

Constraint was added in this proxy instance (i.e. did not belong to source Armature)

Type boolean, default False

is_valid

Constraint has invalid settings and will not be evaluated

Type boolean, default False, (readonly)

mute

Enable/Disable Constraint

Type boolean, default False

name
Constraint name

Type string, default “”

owner_space
Space that owner is evaluated in

Type enum in [’WORLD’, ‘POSE’, ‘LOCAL_WITH_PARENT’, ‘LOCAL’], default ‘WORLD’

show_expanded
Constraint’s panel is expanded in UI

Type boolean, default False

target_space
Space that target is evaluated in

Type enum in [’WORLD’, ‘POSE’, ‘LOCAL_WITH_PARENT’, ‘LOCAL’], default ‘WORLD’

type

Type enum in [’COPY_LOCATION’, ‘COPY_ROTATION’, ‘COPY_SCALE’, ‘COPY_TRANSFORMS’, ‘LIMIT_DISTANCE’, ‘LIMIT_LOCATION’, ‘LIMIT_ROTATION’, ‘LIMIT_SCALE’, ‘MAINTAIN_VOLUME’, ‘TRANSFORM’, ‘CLAMP_TO’, ‘DAMPED_TRACK’, ‘IK’, ‘LOCKED_TRACK’, ‘SPLINE_IK’, ‘STRETCH_TO’, ‘TRACK_TO’, ‘ACTION’, ‘CHILD_OF’, ‘FLOOR’, ‘FOLLOW_PATH’, ‘PIVOT’, ‘RIGID_BODY_JOINT’, ‘SCRIPT’, ‘SHRINKWRAP’], default ‘COPY_LOCATION’, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.constraints
- ObjectConstraints.active
- ObjectConstraints.new
- ObjectConstraints.remove
- PoseBone.constraints
- PoseBoneConstraints.active
- PoseBoneConstraints.new
- PoseBoneConstraints.remove
- UILayout.template_constraint

1.4.163 ConstraintActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ConstraintActuator** (*Actuator*)

Actuator to handle Constraints

angle_max

Maximum angle (in degree) allowed with target direction. No correction is done if angle with target direction is between min and max

Type float in [0, 180], default 0.0

angle_min

Minimum angle (in degree) to maintain with target direction. No correction is done if angle with target direction is between min and max

Type float in [0, 180], default 0.0

damping

Damping factor: time constant (in frame) of low pass filter

Type int in [-32768, 32767], default 0

damping_rotation

Use a different damping for orientation

Type int in [-32768, 32767], default 0

direction

Set the direction of the ray

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ', 'DIRNX', 'DIRNY', 'DIRNZ'], default 'NONE'

direction_axis

Select the axis to be aligned along the reference direction

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ', 'DIRNX', 'DIRNY', 'DIRNZ'], default 'NONE'

direction_axis_pos

Select the axis to be aligned along the reference direction

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ'], default 'NONE'

distance

Set the maximum length of ray

Type float in [-inf, inf], default 0.0

fh_damping
Damping factor of the force field spring

Type float in [-inf, inf], default 0.0

fh_force
Spring force within the force field area

Type float in [-inf, inf], default 0.0

fh_height
Height of the force field area

Type float in [-inf, inf], default 0.0

limit

Type enum in ['NONE', 'LOCX', 'LOCY', 'LOCZ'], default 'NONE'

limit_max

Type float in [-inf, inf], default 0.0

limit_min

Type float in [-inf, inf], default 0.0

material
Ray detects only Objects with this material

Type string, default ""

mode
The type of the constraint

Type enum in ['LOC', 'DIST', 'ORI', 'FH'], default 'LOC'

property
Ray detect only Objects with this property

Type string, default ""

range
Set the maximum length of ray

Type float in [-inf, inf], default 0.0

rotation_max
Reference Direction

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

time
Maximum activation time in frame, 0 for unlimited

Type int in [-32768, 32767], default 0

use_fh_normal
Add a horizontal spring force on slopes

Type boolean, default False

use_fh_paralel_axis
Keep object axis parallel to normal

Type boolean, default False

use_force_distance
Force distance of object to point of impact of ray

Type boolean, default False

use_local
Set ray along object's axis or global axis

Type boolean, default False

use_material_detect
Detect material instead of property

Type boolean, default False

use_normal
Set object axis along (local axis) or parallel (global axis) to the normal at hit position

Type boolean, default False

use_persistent
Persistent actuator: stays active even if ray does not reach target

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.164 ConstraintTarget(bpy_struct)

base class — bpy_struct

class bpy.types.**ConstraintTarget**(*bpy_struct*)

Target object for multi-target constraints

subtarget

Type string, default ""

target

Target Object

Type Object

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PythonConstraint.targets

1.4.165 Context(bpy_struct)

base class — bpy_struct

class bpy.types.**Context**(*bpy_struct*)

Current windowmanager and data context

area

Type Area, (readonly)

blend_data

Type BlendData, (readonly)

mode

Type enum in ['EDIT_MESH', 'EDIT_CURVE', 'EDIT_SURFACE', 'EDIT_TEXT', 'EDIT_ARMATURE', 'EDIT_METABALL', 'EDIT_LATTICE', 'POSE', 'SCULPT', 'PAINT_WEIGHT', 'PAINT_VERTEX', 'PAINT_TEXTURE', 'PARTICLE', 'OBJECT'], default 'EDIT_MESH', (readonly)

region

Type Region, (readonly)

region_data

Type RegionView3D, (readonly)

scene

Type Scene, (readonly)

screen

Type Screen, (readonly)

space_data

Type Space, (readonly)

tool_settings

Type ToolSettings, (readonly)

user_preferences

Type UserPreferences, (readonly)

window

Type Window, (readonly)

window_manager

Type WindowManager, (readonly)

static **copy**(*self*)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Header.draw
- KeyingSetInfo.generate
- KeyingSetInfo.iterator
- KeyingSetInfo.poll
- Macro.draw
- Macro.poll
- Menu.draw
- Menu.poll
- Operator.check
- Operator.draw
- Operator.execute
- Operator.invoke
- Operator.modal
- Operator.poll
- Panel.draw
- Panel.draw_header
- Panel.poll

1.4.166 ControlFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**ControlFluidSettings**(*FluidSettings*)

Fluid simulation settings for objects controlling the motion of fluid in the simulation

attraction_radius

Specifies the force field radius around the control object

Type float in [0, 10], default 0.0

attraction_strength

Force strength for directional attraction towards the control object

Type float in [-10, 10], default 0.0

end_time

Specifies time when the control particles are deactivated

Type float in [0, 100], default 0.0

quality

Specifies the quality which is used for object sampling. (higher = better but slower)

Type float in [5, 100], default 0.0

start_time

Specifies time when the control particles are activated

Type float in [0, 100], default 0.0

use
Object contributes to the fluid simulation

Type boolean, default False

use_reverse_frames
Reverse control object movement

Type boolean, default False

velocity_radius
Specifies the force field radius around the control object

Type float in [0, 10], default 0.0

velocity_strength
Force strength of how much of the control object's velocity is influencing the fluid velocity

Type float in [0, 10], default 0.0

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.167 Controller(bpy_struct)

base class — bpy_struct

subclasses — ExpressionController, XnorController, PythonController, AndController, NorController, OrController, XorController, NandController

class bpy.types.**Controller**(*bpy_struct*)
Game engine logic brick to process events, connecting sensors to actuators

name

Type string, default ""

show_expanded
Set controller expanded in the user interface

Type boolean, default False

states
Set Controller state index (1 to 30)

Type int in [1, 30], default 0

type

Type enum in ['LOGIC_AND', 'LOGIC_OR', 'LOGIC_NAND', 'LOGIC_NOR', 'LOGIC_XOR', 'LOGIC_XNOR', 'EXPRESSION', 'PYTHON'], default 'LOGIC_AND'

use_priority
Mark controller for execution before all non-marked controllers (good for startup scripts)

Type boolean, default False

link (*sensor=None*, *actuator=None*)
Link the controller with a sensor/actuator.

Parameters

- **sensor** (Sensor, (optional)) – Sensor to link the controller to.
- **actuator** (Actuator, (optional)) – Actuator to link the controller to.

unlink (*sensor=None*, *actuator=None*)
Unlink the controller from a sensor/actuator.

Parameters

- **sensor** (Sensor, (optional)) – Sensor to unlink the controller from.
- **actuator** (Actuator, (optional)) – Actuator to unlink the controller from.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Actuator.link
- Actuator.unlink
- GameObjectSettings.controllers
- Sensor.link
- Sensor.unlink

1.4.168 CopyLocationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**CopyLocationConstraint**(*Constraint*)

Copies the location of the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

invert_x

Invert the X location

Type boolean, default False

invert_y

Invert the Y location

Type boolean, default False

invert_z

Invert the Z location

Type boolean, default False

subtarget

Type string, default “”

target

Target Object

Type Object

use_offset

Add original location into copied location

Type boolean, default False

use_x

Copy the target’s X location

Type boolean, default False

use_y

Copy the target’s Y location

Type boolean, default False

use_z

Copy the target’s Z location

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.169 CopyRotationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**CopyRotationConstraint**(*Constraint*)

Copies the rotation of the target

invert_x

Invert the X rotation

Type boolean, default False

invert_y

Invert the Y rotation

Type boolean, default False

invert_z

Invert the Z rotation

Type boolean, default False

subtarget

Type string, default “”

target
Target Object

Type Object

use_offset
Add original rotation into copied rotation

Type boolean, default False

use_x
Copy the target’s X rotation

Type boolean, default False

use_y
Copy the target’s Y rotation

Type boolean, default False

use_z
Copy the target’s Z rotation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.170 CopyScaleConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**CopyScaleConstraint**(*Constraint*)

Copies the scale of the target

subtarget

Type string, default “”

target

Target Object

Type Object

use_offset

Add original scale into copied scale

Type boolean, default False

use_x

Copy the target’s X scale

Type boolean, default False

use_y

Copy the target’s Y scale

Type boolean, default False

use_z

Copy the target’s Z scale

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.171 CopyTransformsConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**CopyTransformsConstraint**(*Constraint*)

Copies all the transforms of the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

subtarget

Type string, default ""

target

Target Object

Type Object

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.172 Curve(ID)

base classes — bpy_struct, ID

subclasses — SurfaceCurve, TextCurve

class bpy.types.**Curve**(*ID*)

Curve datablock storing curves, splines and NURBS

animation_data

Animation data for this datablock

Type AnimData, (readonly)

bevel_depth

Bevel depth when not using a bevel object

Type float in [-inf, inf], default 0.0

bevel_object

Curve object name that defines the bevel shape

Type Object

bevel_resolution

Bevel resolution when depth is non-zero and no specific bevel object has been defined

Type int in [0, 32], default 0

dimensions

Select 2D or 3D curve type

Type enum in ['2D', '3D'], default '2D'

eval_time

Parametric position along the length of the curve that Objects 'following' it should be at. Position is evaluated by dividing by the 'Path Length' value

Type float in [-inf, inf], default 0.0

extrude
Amount of curve extrusion when not using a bevel object

Type float in [0, inf], default 0.0

materials

Type IDMaterials collection of Material, (readonly)

offset
Offset the curve to adjust the width of a text

Type float in [-inf, inf], default 0.0

path_duration
The number of frames that are needed to traverse the path, defining the maximum value for the 'Evaluation Time' setting

Type int in [1, 300000], default 0

render_resolution_u
Surface resolution in U direction used while rendering. Zero skips this property

Type int in [0, 32767], default 0

render_resolution_v
Surface resolution in V direction used while rendering. Zero skips this property

Type int in [0, 32767], default 0

resolution_u
Surface resolution in U direction

Type int in [1, 32767], default 0

resolution_v
Surface resolution in V direction

Type int in [1, 32767], default 0

shape_keys

Type Key, (readonly)

show_handles
Display bezier handles in editmode

Type boolean, default False

show_normal_face
Display 3D curve normals in editmode

Type boolean, default False

splines
Collection of splines in this curve data object

Type CurveSplines collection of Spline, (readonly)

taper_object
Curve object name that defines the taper (width)

Type Object

texspace_location
Texture space location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size
Texture space size

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

twist_mode
The type of tilt calculation for 3D Curves

Type enum in ['Z_UP', 'MINIMUM', 'TANGENT'], default 'Z_UP'

twist_smooth
Smoothing iteration for tangents

Type float in [-inf, inf], default 0.0

use_auto_texspace
Adjusts active object's texture space automatically when transforming object

Type boolean, default False

use_deform_bounds
Use the mesh bounds to clamp the deformation

Type boolean, default False

use_fill_back
Draw filled back for extruded/beveled curves

Type boolean, default False

use_fill_deform
Fill curve after applying shape keys and all modifiers

Type boolean, default False

use_fill_front
Draw filled front for extruded/beveled curves

Type boolean, default False

use_path
Enable the curve to become a translation path

Type boolean, default False

use_path_follow
Make curve path children to rotate along the path

Type boolean, default False

use_radius
Option for paths: apply the curve radius with path following it and deforming

Type boolean, default False

use_stretch
Option for curve-deform: makes deformed child to stretch along entire path

Type boolean, default False

use_time_offset
Children will use TimeOffs value as path distance offset

Type boolean, default False

use_uv_as_generated
Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.curves
- BlendDataCurves.new
- BlendDataCurves.remove

1.4.173 CurveMap(bpy_struct)

base class — bpy_struct

class bpy.types.**CurveMap**(*bpy_struct*)
Curve in a curve mapping

extend
Extrapolate the curve or extend it horizontally

Type enum in ['HORIZONTAL', 'EXTRAPOLATED'], default 'HORIZONTAL', (readonly)

points

Type Collection of CurveMapPoint, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CurveMapping.curves

1.4.174 CurveMapPoint(bpy_struct)

base class — bpy_struct

class bpy.types.**CurveMapPoint**(*bpy_struct*)
Point of a curve used for a curve mapping

handle_type
Curve interpolation at this point: bezier or vector

Type enum in ['AUTO', 'VECTOR'], default 'AUTO', (readonly)

location
X/Y coordinates of the curve point

Type float array of 2 items in [-inf, inf], default (0.0, 0.0), (readonly)

select
Selection state of the curve point

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CurveMap.points

1.4.175 CurveMapping(bpy_struct)

base class — bpy_struct

class bpy.types.**CurveMapping**(*bpy_struct*)

Curve mapping to map color, vector and scalar values to other values using a user defined curve

black_level

For RGB curves, the color that black is mapped to

Type float array of 3 items in [-1000, 1000], default (0.0, 0.0, 0.0)

clip_max_x

Type float in [-100, 100], default 0.0

clip_max_y

Type float in [-100, 100], default 0.0

clip_min_x

Type float in [-100, 100], default 0.0

clip_min_y

Type float in [-100, 100], default 0.0

curves

Type Collection of CurveMap, (readonly)

use_clip

Force the curve view to fit a defined boundary

Type boolean, default False

white_level

For RGB curves, the color that white is mapped to

Type float array of 3 items in [-1000, 1000], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Brush.curve
- CompositorNodeCurveRGB.mapping
- CompositorNodeCurveVec.mapping
- CompositorNodeHueCorrect.mapping
- CompositorNodeTime.curve
- ParticleBrush.curve
- PointLamp.falloff_curve
- ShaderNodeRGBCurve.mapping
- ShaderNodeVectorCurve.mapping
- SpaceImageEditor.curves
- SpotLamp.falloff_curve
- TextureNodeCurveRGB.mapping
- TextureNodeCurveTime.curve

1.4.176 CurveModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**CurveModifier**(*Modifier*)

Curve deformation modifier

deform_axis

The axis that the curve deforms along

Type enum in ['POS_X', 'POS_Y', 'POS_Z', 'NEG_X', 'NEG_Y', 'NEG_Z'], default 'POS_X'

object

Curve object to deform with

Type Object

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.177 CurveSplines(bpy_struct)

base class — bpy_struct

class bpy.types.**CurveSplines**(*bpy_struct*)

Collection of curve splines

active

Active curve spline

Type Object

new(*type*)

Add a new spline to the curve.

Parameters **type** (*enum in ['POLY', 'BEZIER', 'BSPLINE', 'CARDINAL', 'NURBS']*) – type for the new spline.

Returns The newly created spline.

Return type Spline

remove(*spline*)

Remove a spline from a curve.

Parameters **spline** (Spline, (never None)) – The spline to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Curve.splines

1.4.178 DampedTrackConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**DampedTrackConstraint**(*Constraint*)

Points toward target by taking the shortest rotation path

subtarget

Type string, default ""

target

Target Object

Type Object

track_axis

Axis that points to the target object

Type enum in ['TRACK_X', 'TRACK_Y', 'TRACK_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'TRACK_X'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.179 DecimateModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**DecimateModifier**(*Modifier*)

Decimation modifier

face_count

The current number of faces in the decimated mesh

Type int in [-inf, inf], default 0, (readonly)

ratio

Defines the ratio of triangles to reduce to

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.180 DelaySensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**DelaySensor**(*Sensor*)

Sensor to send delayed events

delay
Delay in number of logic tics before the positive trigger (default 60 per second)

Type int in [0, 5000], default 0

duration
If >0, delay in number of logic tics before the negative trigger following the positive trigger

Type int in [0, 5000], default 0

use_repeat
Toggle repeat option. If selected, the sensor restarts after Delay+Dur logic tics

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.181 DisplaceModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**DisplaceModifier**(*Modifier*)

Displacement modifier

direction

Type enum in ['X', 'Y', 'Z', 'NORMAL', 'RGB_TO_XYZ'], default 'X'

mid_level

Material value that gives no displacement

Type float in [0, 1], default 0.0

strength

Type float in [-inf, inf], default 0.0

texture

Type Texture

texture_coordinate_object

Type Object

texture_coords

Type enum in ['LOCAL', 'GLOBAL', 'OBJECT', 'UV'], default 'LOCAL'

uv_layer

UV layer name

Type string, default ""

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.182 DistortedNoiseTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**DistortedNoiseTexture**(*Texture*)

Procedural distorted noise texture

distortion

Type float in [0, 10], default 0.0

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_distortion

Sets the noise basis for the distortion

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag

- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.183 DomainFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**DomainFluidSettings** (*FluidSettings*)

Fluid simulation settings for the domain of a fluid simulation

compressibility

Allowed compressibility due to gravitational force for standing fluid. (directly affects simulation step size)

Type float in [0.001, 0.1], default 0.0

end_time
Simulation time of the last blender frame (in seconds)

Type float in [0, 100], default 0.0

filepath
Directory (and/or filename prefix) to store baked fluid simulation files in

Type string, default “”

generate_particles
Amount of particles to generate (0=off, 1=normal, >1=more)

Type float in [0, 10], default 0.0

gravity
Gravity in X, Y and Z direction

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

grid_levels
Number of coarsened grids to use (-1 for automatic)

Type int in [-1, 4], default 0

memory_estimate
Estimated amount of memory needed for baking the domain

Type string, default “”, (readonly)

partial_slip_factor
Amount of mixing between no- and free-slip, 0 is no slip and 1 is free slip

Type float in [0, 1], default 0.0

preview_resolution
Preview resolution in X,Y and Z direction

Type int in [1, 100], default 0

render_display_mode
How to display the mesh for rendering

Type enum in [’GEOMETRY’, ‘PREVIEW’, ‘FINAL’], default ‘GEOMETRY’

resolution
Domain resolution in X,Y and Z direction

Type int in [1, 1024], default 0

simulation_scale
Size of the simulation domain in metres

Type float in [0.001, 10], default 0.0

slip_type

Type enum in [’NOSLIP’, ‘PARTIALSLIP’, ‘FREESLIP’], default ‘NOSLIP’

start_time
Simulation time of the first blender frame (in seconds)

Type float in [0, 100], default 0.0

surface_smooth
Amount of surface smoothing. A value of 0 is off, 1 is normal smoothing and more than 1 is extra smoothing

Type float in [0, 5], default 0.0

surface_subdivisions
Number of isosurface subdivisions. This is necessary for the inclusion of particles into the surface generation. Warning - can lead to longer computation times!

Type int in [0, 5], default 0

tracer_particles
Number of tracer particles to generate

Type int in [0, 10000], default 0

use_reverse_frames
Reverse fluid frames

Type boolean, default False

use_speed_vectors
Generate speed vectors for vector blur

Type boolean, default False

use_time_override
Use a custom start and end time (in seconds) instead of the scene's timeline

Type boolean, default False

viewport_display_mode
How to display the mesh in the viewport

Type enum in ['GEOMETRY', 'PREVIEW', 'FINAL'], default 'GEOMETRY'

viscosity_base
Viscosity setting: value that is multiplied by 10 to the power of (exponent*-1)

Type float in [0, 10], default 0.0

viscosity_exponent
Negative exponent for the viscosity value (to simplify entering small values e.g. 5*10^-6.)

Type int in [0, 10], default 0

viscosity_preset
Set viscosity of the fluid to a preset value, or use manual input

Type enum in ['MANUAL', 'WATER', 'OIL', 'HONEY'], default 'MANUAL'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.184 DopeSheet(bpy_struct)

base class — bpy_struct

class bpy.types.**DopeSheet**(*bpy_struct*)

Settings for filtering the channels shown in Animation Editors

filter_group

Group that included Object should be a member of

Type Group

show_armatures

Include visualization of Armature related Animation data

Type boolean, default False

show_cameras

Include visualization of Camera related Animation data

Type boolean, default False

show_curves

Include visualization of Curve related Animation data

Type boolean, default False

show_expanded_summary

Collapse summary when shown, so all other channels get hidden. (DopeSheet Editors Only)

Type boolean, default False

show_hidden

Include channels from objects/bone that aren't visible

Type boolean, default False

show_lamps

Include visualization of Lamp related Animation data

Type boolean, default False

show_lattices

Include visualization of Lattice related Animation data

Type boolean, default False

show_materials

Include visualization of Material related Animation data

Type boolean, default False

show_meshes
Include visualization of Mesh related Animation data

Type boolean, default False

show_metaballs
Include visualization of Metaball related Animation data

Type boolean, default False

show_missing_nla
Include Animation Data blocks with no NLA data. (NLA Editor only)

Type boolean, default False

show_nodes
Include visualization of Node related Animation data

Type boolean, default False

show_only_group_objects
Only include channels from Objects in the specified Group

Type boolean, default False

show_only_selected
Only include channels relating to selected objects and data

Type boolean, default False

show_particles
Include visualization of Particle related Animation data

Type boolean, default False

show_scenes
Include visualization of Scene related Animation data

Type boolean, default False

show_shapekeys
Include visualization of ShapeKey related Animation data

Type boolean, default False

show_summary
Display an additional 'summary' line. (DopeSheet Editors only)

Type boolean, default False

show_textures
Include visualization of Texture related Animation data

Type boolean, default False

show_transforms
Include visualization of Object-level Animation data (mostly Transforms)

Type boolean, default False

show_worlds
Include visualization of World related Animation data

Type boolean, default False

source
ID-Block representing source data, currently ID_SCE (for Dopesheet), and ID_SC (for Grease Pencil)

Type ID, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceDopeSheetEditor.dopesheet
- SpaceGraphEditor.dopesheet
- SpaceNLA.dopesheet

1.4.185 Driver(bpy_struct)

base class — bpy_struct

class bpy.types.**Driver**(*bpy_struct*)

Driver for the value of a setting based on an external value

expression

Expression to use for Scripted Expression

Type string, default “”

is_valid

Driver could not be evaluated in past, so should be skipped

Type boolean, default False

show_debug_info

Show intermediate values for the driver calculations to allow debugging of drivers

Type boolean, default False

type
Driver type

Type enum in ['AVERAGE', 'SUM', 'SCRIPTED', 'MIN', 'MAX'], default 'AVERAGE'

variables
Properties acting as inputs for this driver

Type ChannelDriverVariables collection of DriverVariable, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.driver

1.4.186 DriverTarget(bpy_struct)

base class — bpy_struct

class bpy.types.**DriverTarget**(*bpy_struct*)
Source of input values for driver variables

bone_target
Name of PoseBone to use as target

Type string, default ""

data_path
RNA Path (from ID-block) to property used

Type string, default ""

id
ID-block that the specific property used can be found from (id_type property must be set first)

Type ID

id_type
Type of ID-block that can be used

Type enum in ['ACTION', 'ARMATURE', 'BRUSH', 'CAMERA', 'CURVE', 'FONT', 'GREASEPENCIL', 'GROUP', 'IMAGE', 'KEY', 'LAMP', 'LIBRARY', 'LATTICE', 'MATERIAL', 'META', 'MESH', 'NODETREE', 'OBJECT', 'PARTICLE', 'SCENE', 'SCREEN', 'SOUND', 'TEXT', 'TEXTURE', 'WORLD', 'WINDOWMANAGER'], default 'OBJECT'

transform_type
Driver variable type

Type enum in ['LOC_X', 'LOC_Y', 'LOC_Z', 'ROT_X', 'ROT_Y', 'ROT_Z', 'SCALE_X', 'SCALE_Y', 'SCALE_Z'], default 'LOC_X'

use_local_space_transform
Use transforms in Local Space (as opposed to the worldspace default)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- DriverVariable.targets

1.4.187 DriverVariable(bpy_struct)

base class — bpy_struct

class bpy.types.**DriverVariable** (*bpy_struct*)

Variable from some source/target for driver relationship

name

Name to use in scripted expressions/functions. (No spaces or dots are allowed. Also, must not start with a symbol or digit)

Type string, default ""

targets

Sources of input data for evaluating this variable

Type Collection of DriverTarget, (readonly)

type

Driver variable type

Type enum in ['SINGLE_PROP', 'TRANSFORMS', 'ROTATION_DIFF', 'LOC_DIFF'], default 'SINGLE_PROP'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ChannelDriverVariables.new
- ChannelDriverVariables.remove
- Driver.variables

1.4.188 DupliObject(bpy_struct)

base class — bpy_struct

class bpy.types.**DupliObject**(*bpy_struct*)

An object duplicate

matrix

Object duplicate transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_original

The original matrix of this object before it was duplicated

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

object

Object being duplicated

Type Object, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.dupli_list

1.4.189 EdgeSplitModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**EdgeSplitModifier**(*Modifier*)
Edge splitting modifier to create sharp edges

split_angle
Angle above which to split edges

Type float in [0, 180], default 0.0

use_edge_angle
Split edges with high angle between faces

Type boolean, default False

use_edge_sharp
Split edges that are marked as sharp

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.190 EditBone(bpy_struct)

base class — bpy_struct

class bpy.types.**EditBone**(*bpy_struct*)
Editmode bone in an Armature datablock

bbone_in
Length of first Bezier Handle (for B-Bones only)

Type float in [0, 2], default 0.0

bbone_out
Length of second Bezier Handle (for B-Bones only)

Type float in [0, 2], default 0.0

bbone_segments
Number of subdivisions of bone (for B-Bones only)

Type int in [1, 32], default 0

bbone_x
B-Bone X size

Type float in [0, 1000], default 0.0

bbone_z
B-Bone Z size

Type float in [0, 1000], default 0.0

envelope_distance
Bone deformation distance (for Envelope deform only)

Type float in [0, 1000], default 0.0

envelope_weight
Bone deformation weight (for Envelope deform only)

Type float in [0, 1000], default 0.0

head
Location of head end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_radius
Radius of head of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

hide
Bone is not visible when in Edit Mode

Type boolean, default False

hide_select
Bone is able to be selected

Type boolean, default False

layers
Layers bone exists in

Type boolean array of 32 items, default (False, False)

lock
Bone is not able to be transformed when in Edit Mode

Type boolean, default False

matrix
Read-only matrix calculated from the roll (armature space)

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

name

Type string, default ""

parent
Parent edit bone (in same Armature)

Type EditBone

roll
Bone rotation around head-tail axis

Type float in [-inf, inf], default 0.0

select

Type boolean, default False

select_head

Type boolean, default False

select_tail

Type boolean, default False

show_wire
Bone is always drawn as Wireframe regardless of viewport draw mode. Useful for non-obstructive custom bone shapes

Type boolean, default False

tail
Location of tail end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_radius
Radius of tail of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

use_connect
When bone has a parent, bone's head is struck to the parent's tail

Type boolean, default False

use_cyclic_offset
When bone doesn't have a parent, it receives cyclic offset effects

Type boolean, default False

use_deform
Bone does not deform any geometry

Type boolean, default False

use_envelope_multiply
When deforming bone, multiply effects of Vertex Group weights with Envelope influence

Type boolean, default False

use_inherit_rotation
Bone inherits rotation or scale from parent bone

Type boolean, default False

use_inherit_scale
Bone inherits scaling from parent bone

Type boolean, default False

use_local_location
Bone location is set in local space

Type boolean, default False

basename
The name of this bone before any '.' character (readonly)

center
The midpoint between the head and the tail. (readonly)

children
A list of all the bones children. (readonly)

children_recursive
a list of all children from this bone. (readonly)

children_recursive_basename
Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned.

(readonly)

length
The distance from head to tail, when set the head is moved to fit the length.

parent_recursive
A list of parents, starting with the immediate parent (readonly)

vector
The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis
Vector pointing down the x-axis of the bone.

(readonly)

y_axis
Vector pointing down the x-axis of the bone.

(readonly)

z_axis
Vector pointing down the x-axis of the bone.

(readonly)

align_roll(*vector*)
Align the bone to a localspace roll so the Z axis points in the direction of the vector given.

Parameters **vector** (*float array of 3 items in [-inf, inf]*) – Vector

align_orientation(*other*)
Align this bone to another by moving its tail and settings its roll the length of the other bone is not used.

parent_index (*parent_test*)
The same as 'bone in other_bone.parent_recursive' but saved generating a list.

transform (*matrix*, *scale=True*, *roll=True*)
Transform the the bones head, tail, roll and envalope (when the matrix has a scale component).

Parameters

- **matrix** (`Matrix`) – 3x3 or 4x4 transformation matrix.
- **scale** (*bool*) – Scale the bone envalope by the matrix.
- **roll** (*bool*) – Correct the roll to point in the same relative direction to the head and tail.

translate (*vec*)
Utility function to add *vec* to the head and tail of this bone.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Armature.edit_bones`
- `ArmatureEditBones.active`
- `ArmatureEditBones.new`
- `ArmatureEditBones.remove`
- `EditBone.parent`

1.4.191 EditObjectActuator(Actuator)

base classes — `bpy_struct`, `Actuator`

class `bpy.types.`**EditObjectActuator** (*Actuator*)
Actuator used to edit objects

angular_velocity
Angular velocity upon creation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dynamic_operation

Type enum in ['RESTOREDYN', 'SUSPENDDYN', 'ENABLERIGIDBODY', 'DISABLERIGIDBODY', 'SETMASS'], default 'RESTOREDYN'

linear_velocity
Velocity upon creation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mass
The mass of the object

Type float in [-inf, inf], default 0.0

mesh
Replace the existing, when left blank 'Phys' will remake the existing physics mesh

Type `Mesh`

mode
The mode of the actuator

Type enum in ['ADDOBJECT', 'ENDOBJECT', 'REPLACEMESH', 'TRACKTO', 'DYNAMICS'], default 'ADDOBJECT'

object
Add this Object and all its children (cant be on an visible layer)

Type `Object`

time
Duration the new Object lives or the track takes

Type int in [-inf, inf], default 0

track_object
Track to this Object

Type `Object`

use_3d_tracking
Enable 3D tracking

Type boolean, default False

use_local_angular_velocity
Apply the rotation locally

Type boolean, default False

use_local_linear_velocity
Apply the transformation locally

Type boolean, default False

use_replace_display_mesh
Replace the display mesh

Type boolean, default False

use_replace_physics_mesh
Replace the physics mesh (triangle bounds only - compound shapes not supported)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.192 EffectSequence(Sequence)

base classes — bpy_struct, Sequence

subclasses — GlowSequence, PluginSequence, ColorSequence, TransformSequence, WipeSequence, SpeedControlSequence

class bpy.types.**EffectSequence**(*Sequence*)
Sequence strip applying an effect on the images created by other strips

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

proxy

Type SequenceProxy, (readonly)

strobe
Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance
(3-Way color correction) on input

Type boolean, default False

use_crop
Crop image before processing

Type boolean, default False

use_deinterlace
For video movies to remove fields

Type boolean, default False

use_flip_x
Flip on the X axis

Type boolean, default False

use_flip_y
Flip on the Y axis

Type boolean, default False

use_float
Convert input to float data

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy
Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.193 EffectorWeights(bpy_struct)

base class — bpy_struct

class bpy.types.**EffectorWeights**(*bpy_struct*)

Effector weights for physics simulation

all

All effector's weight

Type float in [-200, 200], default 0.0

apply_to_hair_growing

Use force fields when growing hair

Type boolean, default False

boid

Boid effector weight

Type float in [-200, 200], default 0.0

charge

Charge effector weight

Type float in [-200, 200], default 0.0

curve_guide

Curve guide effector weight

Type float in [-200, 200], default 0.0

drag

Drag effector weight

Type float in [-200, 200], default 0.0

force

Force effector weight

Type float in [-200, 200], default 0.0

gravity

Global gravity weight

Type float in [-200, 200], default 0.0

group

Limit effectors to this Group

Type Group

harmonic

Harmonic effector weight

Type float in [-200, 200], default 0.0

lennardjones
Lennard-Jones effector weight

Type float in [-200, 200], default 0.0

magnetic
Magnetic effector weight

Type float in [-200, 200], default 0.0

texture
Texture effector weight

Type float in [-200, 200], default 0.0

turbulence
Turbulence effector weight

Type float in [-200, 200], default 0.0

vortex
Vortex effector weight

Type float in [-200, 200], default 0.0

wind
Wind effector weight

Type float in [-200, 200], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothSettings.effector_weights
- ParticleSettings.effector_weights

- SmokeDomainSettings.effector_weights
- SoftBodySettings.effector_weights

1.4.194 EnumProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**EnumProperty**(*Property*)

RNA enumeration property definition, to choose from a number of predefined options

default

Default value for this enum

Type enum in ['DUMMY'], default 'DUMMY', (readonly)

default_flag

Default value for this enum

Type enum set in {'DUMMY'}, default set(), (readonly)

items

Possible values for the property

Type Collection of EnumPropertyItem, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.195 EnumPropertyItem(bpy_struct)

base class — bpy_struct

class bpy.types.**EnumPropertyItem**(*bpy_struct*)

Definition of a choice in an RNA enum property

description

Description of the item's purpose

Type string, default "", (readonly)

identifier

Unique name used in the code and scripting

Type string, default "", (readonly)

name

Human readable name

Type string, default "", (readonly)

value

Value of the item

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- EnumProperty.items

1.4.196 EnvironmentMap(bpy_struct)

base class — bpy_struct

class bpy.types.**EnvironmentMap** (*bpy_struct*)

Environment map created by the renderer and cached for subsequent renders

clip_end

Objects further than this are not visible to map

Type float in [0.01, inf], default 0.0

clip_start

Objects nearer than this are not visible to map

Type float in [0.01, inf], default 0.0

depth

Number of times a map will be rendered recursively (mirror effects.)

Type int in [0, 5], default 0

layers_ignore

Hide objects on these layers when generating the Environment Map

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

mapping

Type enum in ['CUBE', 'PLANE'], default 'CUBE'

resolution

Pixel resolution of the rendered environment map

Type int in [50, 4096], default 0

source

Type enum in ['STATIC', 'ANIMATED', 'IMAGE_FILE'], default 'STATIC'

viewpoint_object

Object to use as the environment map's viewpoint location

Type Object

zoom

Type float in [0.1, 5], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EnvironmentMapTexture.environment_map

1.4.197 EnvironmentMapTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**EnvironmentMapTexture**(*Texture*)

Environment map texture

environment_map

Gets the environment map associated with this texture

Type EnvironmentMap, (readonly)

filter_eccentricity

Maximum eccentricity. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_probes

Maximum number of samples. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_size

Multiplies the filter size used by MIP Map and Interpolation

Type float in [0.1, 50], default 0.0

filter_type

Texture filter to use for sampling image

Type enum in ['BOX', 'EWA', 'FELINE', 'AREA'], default 'BOX'

image

Source image file to read the environment map from

Type Image

image_user
Parameters defining which layer, pass and frame of the image is displayed

Type ImageUser, (readonly)

use_filter_size_min
Use Filter Size as a minimal filter value in pixels

Type boolean, default False

use_mipmap
Uses auto-generated MIP maps for the image

Type boolean, default False

use_mipmap_gauss
Uses Gauss filter to sample down MIP maps

Type boolean, default False

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.198 Event(bpy_struct)

base class — bpy_struct

class bpy.types.**Event** (*bpy_struct*)

Window Manager Event

alt

True when the Alt/Option key is held

Type boolean, default False, (readonly)

ascii

Single ASCII character for this event

Type string, default "", (readonly)

ctrl

True when the Ctrl key is held

Type boolean, default False, (readonly)

mouse_prev_x

The window relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_prev_y

The window relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_region_x

The region relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_region_y

The region relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_x
The window relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_y
The window relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

oskey
True when the Cmd key is held

Type boolean, default False, (readonly)

shift
True when the Shift key is held

Type boolean, default False, (readonly)

type

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE', (readonly)

value
The type of event, only applies to some

Type enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK'], default 'NOTHING', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Operator.invoke
- Operator.modal
- WindowManager.invoke_confirm
- WindowManager.invoke_props_popup

1.4.199 ExplodeModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ExplodeModifier**(*Modifier*)

Explosion effect modifier based on a particle system

particle_uv

UV Layer to change with particle age

Type string, default “”

protect

Clean vertex group edges

Type float in [0, 1], default 0.0

show_alive

Show mesh when particles are alive

Type boolean, default False

show_dead

Show mesh when particles are dead

Type boolean, default False

show_unborn

Show mesh when particles are unborn

Type boolean, default False

use_edge_cut
Cut face edges for nicer shrapnel

Type boolean, default False

use_size
Use particle size for the shrapnel

Type boolean, default False

vertex_group

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.200 ExpressionController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**ExpressionController**(*Controller*)
Controller passing on events based on the evaluation of an expression

expression

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.201 FCurve(bpy_struct)

base class — bpy_struct

class bpy.types.**FCurve** (*bpy_struct*)

F-Curve defining values of a period of time

array_index

Index to the specific property affected by F-Curve if applicable

Type int in [-inf, inf], default 0

color

Color of the F-Curve in the Graph Editor

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color_mode

Method used to determine color of F-Curve in Graph Editor

Type enum in ['AUTO_RAINBOW', 'AUTO_RGB', 'CUSTOM'], default 'AUTO_RAINBOW'

data_path

RNA Path to property affected by F-Curve

Type string, default ""

driver
Channel Driver (only set for Driver F-Curves)

Type Driver, (readonly)

extrapolation

Type enum in ['CONSTANT', 'LINEAR'], default 'CONSTANT'

group
Action Group that this F-Curve belongs to

Type ActionGroup

hide
F-Curve and its keyframes are hidden in the Graph Editor graphs

Type boolean, default False

is_valid
False when F-Curve could not be evaluated in past, so should be skipped when evaluating

Type boolean, default False

keyframe_points
User-editable keyframes

Type FCurveKeyframePoints collection of Keyframe, (readonly)

lock
F-Curve's settings cannot be edited

Type boolean, default False

modifiers
Modifiers affecting the shape of the F-Curve

Type FCurveModifiers collection of FModifier, (readonly)

mute
F-Curve is not evaluated

Type boolean, default False

sampled_points
Sampled animation data

Type Collection of FCurveSample, (readonly)

select
F-Curve is selected for editing

Type boolean, default False

use_auto_handle_clamp
All auto-handles for F-Curve are clamped

Type boolean, default False

evaluate (*frame*)
Evaluate fcurve.

Parameters **frame** (*float in [-inf, inf]*) – Frame, Evaluate fcurve at given frame

Returns Position, FCurve position

Return type float in [-inf, inf]

range()

Get the time extents for F-Curve.

Returns Range, Min/Max values

Return type float array of 2 items in [-inf, inf]

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.fcurves
- ActionFCurves.new
- ActionFCurves.remove
- ActionGroup.channels
- AnimData.drivers
- NlaStrip.fcurves

1.4.202 FCurveActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**FCurveActuator**(*Actuator*)

Actuator to animate the object

apply_to_children

Update F-Curve on all children Objects as well

Type boolean, default False

frame_end

Type float in [-inf, inf], default 0.0

frame_property
Assign the action's current frame number to this property

Type string, default ""

frame_start

Type float in [-inf, inf], default 0.0

play_type
Specify the way you want to play the animation

Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'STOP', 'END', 'PROP'], default 'PLAY'

property
Use this property to define the F-Curve position

Type string, default ""

use_additive
F-Curve is added to the current loc/rot/scale in global or local coordinate according to Local flag

Type boolean, default False

use_force
Apply F-Curve as a global or local force depending on the local option (dynamic objects only)

Type boolean, default False

use_local
Let the F-Curve act in local coordinates, used in Force and Add mode

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.203 FCurveKeyframePoints(bpy_struct)

base class — bpy_struct

class bpy.types.**FCurveKeyframePoints**(*bpy_struct*)

Collection of keyframe points

insert(*frame*, *value*, *options=set()*)

Add a keyframe point to a F-Curve.

Parameters

- **frame** (*float in [-inf, inf]*) – X Value of this keyframe point
- **value** (*float in [-inf, inf]*) – Y Value of this keyframe point
- **options** (*enum set in {'REPLACE', 'NEEDED', 'FAST'}, (optional)*) – Keyframe options.

Returns Newly created keyframe

Return type Keyframe

add(*count=1*)

Add a keyframe point to a F-Curve.

Parameters **count** (*int in [1, inf], (optional)*) – Number, Number of points to add to the spline

remove(*keyframe*, *fast=False*)

Remove keyframe from an fcurve.

Parameters

- **keyframe** (Keyframe, (never None)) – Keyframe to remove.
- **fast** (*boolean, (optional)*) – Fast, Fast keyframe removal to avoid recalculating the curve each time

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.keyframe_points

1.4.204 FCurveModifiers(bpy_struct)

base class — bpy_struct

class bpy.types.**FCurveModifiers**(*bpy_struct*)

Collection of F-Curve Modifiers

active

Active F-Curve Modifier

Type FModifier

new(*type*)

Add a constraint to this object

Parameters **type** (*enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED']*) – Constraint type to add.

Returns New fmodifier.

Return type FModifier

remove(*modifier*)

Remove a modifier from this fcurve.

Parameters **modifier** (FModifier, (never None)) – Removed modifier.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.modifiers

1.4.205 FCurveSample(bpy_struct)

base class — bpy_struct

class bpy.types.**FCurveSample**(*bpy_struct*)

Sample point for F-Curve

co

Point coordinates

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

select

Selection status

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.sampled_points

1.4.206 FModifier(bpy_struct)

base class — bpy_struct

subclasses — FModifierCycles, FModifierPython, FModifierFunctionGenerator, FModifierLimits, FModifierEnvelope, FModifierNoise, FModifierStepped, FModifierGenerator

class bpy.types.**FModifier**(*bpy_struct*)

Modifier for values of F-Curve

active

F-Curve Modifier is the one being edited

Type boolean, default False

is_valid

F-Curve Modifier has invalid settings and will not be evaluated

Type boolean, default False, (readonly)

mute

F-Curve Modifier will not be evaluated

Type boolean, default False

show_expanded

F-Curve Modifier's panel is expanded in UI

Type boolean, default False

type

F-Curve Modifier Type

Type enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED'], default 'NULL', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.modifiers
- FCurveModifiers.active
- FCurveModifiers.new
- FCurveModifiers.remove
- NlaStrip.modifiers

1.4.207 FModifierCycles(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierCycles**(*FModifier*)

Repeats the values of the modified F-Curve

cycles_after

Maximum number of cycles to allow after last keyframe. (0 = infinite)

Type int in [-32768, 32767], default 0

cycles_before

Maximum number of cycles to allow before first keyframe. (0 = infinite)

Type int in [-32768, 32767], default 0

mode_after

Cycling mode to use after last keyframe

Type enum in ['NONE', 'REPEAT', 'REPEAT_OFFSET', 'MIRROR'], default 'NONE'

mode_before

Cycling mode to use before first keyframe

Type enum in ['NONE', 'REPEAT', 'REPEAT_OFFSET', 'MIRROR'], default 'NONE'

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.208 FModifierEnvelope(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierEnvelope**(*FModifier*)

Scales the values of the modified F-Curve

control_points

Control points defining the shape of the envelope

Type Collection of FModifierEnvelopeControlPoint, (readonly)

default_max

Upper distance from Reference Value for 1:1 default influence

Type float in [-inf, inf], default 0.0

default_min

Lower distance from Reference Value for 1:1 default influence

Type float in [-inf, inf], default 0.0

reference_value

Value that envelope's influence is centered around / based on

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.209 FModifierEnvelopeControlPoint(bpy_struct)

base class — bpy_struct

class bpy.types.**FModifierEnvelopeControlPoint**(*bpy_struct*)

Control point for envelope F-Modifier

frame

Frame this control-point occurs on

Type float in [-inf, inf], default 0.0

max

Upper bound of envelope at this control-point

Type float in [-inf, inf], default 0.0

min

Lower bound of envelope at this control-point

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FModifierEnvelope.control_points

1.4.210 FModifierFunctionGenerator(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierFunctionGenerator**(*FModifier*)

Generates values using a Built-In Function

amplitude

Scale factor determining the maximum/minimum values

Type float in [-inf, inf], default 0.0

function_type

Type of built-in function to use

Type enum in ['SIN', 'COS', 'TAN', 'SQRT', 'LN', 'SINC'], default 'SIN'

phase_multiplier

Scale factor determining the 'speed' of the function

Type float in [-inf, inf], default 0.0

phase_offset

Constant factor to offset time by for function

Type float in [-inf, inf], default 0.0

use_additive

Values generated by this modifier are applied on top of the existing values instead of overwriting them

Type boolean, default False

value_offset

Constant factor to offset values by

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.211 FModifierGenerator(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierGenerator**(*FModifier*)

Deterministically generates values for the modified F-Curve

coefficients

Coefficients for 'x' (starting from lowest power of x^0)

Type float array of 32 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

mode

Type of generator to use

Type enum in ['POLYNOMIAL', 'POLYNOMIAL_FACTORISED'], default 'POLYNOMIAL'

poly_order

The highest power of 'x' for this polynomial. (number of coefficients - 1)

Type int in [-inf, inf], default 0

use_additive

Values generated by this modifier are applied on top of the existing values instead of overwriting them

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute

- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.212 FModifierLimits(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierLimits**(*FModifier*)

Limits the time/value ranges of the modified F-Curve

max_x

Highest X value to allow

Type float in [-inf, inf], default 0.0

max_y

Highest Y value to allow

Type float in [-inf, inf], default 0.0

min_x

Lowest X value to allow

Type float in [-inf, inf], default 0.0

min_y

Lowest Y value to allow

Type float in [-inf, inf], default 0.0

use_max_x

Use the maximum X value

Type boolean, default False

use_max_y

Use the maximum Y value

Type boolean, default False

use_min_x
Use the minimum X value

Type boolean, default False

use_min_y
Use the minimum Y value

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.213 FModifierNoise(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierNoise**(*FModifier*)
Gives randomness to the modified F-Curve

blend_type
Method of modifying the existing F-Curve

Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULTIPLY'], default 'REPLACE'

depth
Amount of fine level detail present in the noise

Type int in [0, 32767], default 0

phase
A random seed for the noise effect

Type float in [-inf, inf], default 0.0

scale
Scaling (in time) of the noise

Type float in [-inf, inf], default 0.0

strength
Amplitude of the noise - the amount that it modifies the underlying curve

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.214 FModifierPython(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierPython**(*FModifier*)
Performs user-defined operation on the modified F-Curve

Inherited Properties

- bpy_struct.id_data

- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.215 FModifierStepped(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.**FModifierStepped**(*FModifier*)

Holds each interpolated value from the F-Curve for several frames without changing the timing

frame_end

Frame that modifier's influence ends (if applicable)

Type float in [-inf, inf], default 0.0

frame_offset

Reference number of frames before frames get held. Use to get hold for '1-3' vs '5-7' holding patterns

Type float in [-inf, inf], default 0.0

frame_start

Frame that modifier's influence starts (if applicable)

Type float in [-inf, inf], default 0.0

frame_step

Number of frames to hold each value

Type float in [-inf, inf], default 0.0

use_frame_end

Restrict modifier to only act before its 'end' frame

Type boolean, default False

use_frame_start
Restrict modifier to only act after its 'start' frame

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.216 FieldSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**FieldSettings** (*bpy_struct*)
Field settings for an object in physics simulation

apply_to_location
Effect particles' location

Type boolean, default False

apply_to_rotation
Effect particles' dynamic rotation

Type boolean, default False

distance_max
Maximum distance for the field to work

Type float in [0, 1000], default 0.0

distance_min
Minimum distance for the field's fall-off

Type float in [0, 1000], default 0.0

falloff_power
Falloff power (real gravitational falloff = 2)

Type float in [0, 10], default 0.0

falloff_type
Fall-off shape

Type enum in ['SPHERE', 'TUBE', 'CONE'], default 'SPHERE'

flow
Convert effector force into air flow velocity

Type float in [0, 10], default 0.0

guide_clump_amount
Amount of clumping

Type float in [-1, 1], default 0.0

guide_clump_shape
Shape of clumping

Type float in [-0.999, 0.999], default 0.0

guide_free
Guide-free time from particle life's end

Type float in [0, 0.99], default 0.0

guide_kink_amplitude
The amplitude of the offset

Type float in [0, 10], default 0.0

guide_kink_axis
Which axis to use for offset

Type enum in ['X', 'Y', 'Z'], default 'X'

guide_kink_frequency
The frequency of the offset (1/total length)

Type float in [0, 10], default 0.0

guide_kink_shape
Adjust the offset to the beginning/end

Type float in [-0.999, 0.999], default 0.0

guide_kink_type
Type of periodic offset on the curve

Type enum in ['NONE', 'CURL', 'RADIAL', 'WAVE', 'BRAID', 'ROTATION', 'ROLL'], default 'NONE'

guide_minimum
The distance from which particles are affected fully

Type float in [0, 1000], default 0.0

harmonic_damping
Damping of the harmonic force

Type float in [0, 10], default 0.0

inflow
Inwards component of the vortex force

Type float in [-10, 10], default 0.0

linear_drag
Drag component proportional to velocity

Type float in [-2, 2], default 0.0

noise
Amount of noise for the force strength

Type float in [0, 10], default 0.0

quadratic_drag
Drag component proportional to the square of velocity

Type float in [-2, 2], default 0.0

radial_falloff
Radial falloff power (real gravitational falloff = 2)

Type float in [0, 10], default 0.0

radial_max
Maximum radial distance for the field to work

Type float in [0, 1000], default 0.0

radial_min
Minimum radial distance for the field's fall-off

Type float in [0, 1000], default 0.0

rest_length
Rest length of the harmonic force

Type float in [0, 1000], default 0.0

seed
Seed of the noise

Type int in [1, 128], default 0

shape
Which direction is used to calculate the effector force

Type enum in ['POINT', 'PLANE', 'SURFACE', 'POINTS'], default 'POINT'

size
Size of the turbulence

Type float in [0, 10], default 0.0

strength
Strength of force field

Type float in [-1000, 1000], default 0.0

texture
Texture to use as force

Type Texture

texture_mode
How the texture effect is calculated (RGB & Curl need a RGB texture else Gradient will be used instead)

Type enum in ['RGB', 'GRADIENT', 'CURL'], default 'RGB'

texture_nabla
Defines size of derivative offset used for calculating gradient and curl

Type float in [0.0001, 1], default 0.0

type
Type of field

Type enum in ['NONE', 'FORCE', 'WIND', 'VORTEX', 'MAGNET', 'HARMONIC', 'CHARGE', 'LENNARDJ', 'TEXTURE', 'GUIDE', 'BOID', 'TURBULENCE', 'DRAG'], default 'NONE'

use_2d_force
Apply force only in 2d

Type boolean, default False

use_absorption
Force gets absorbed by collision objects

Type boolean, default False

use_global_coords
Use effector/global coordinates for turbulence

Type boolean, default False

use_guide_path_add
Based on distance/falloff it adds a portion of the entire path

Type boolean, default False

use_guide_path_weight
Use curve weights to influence the particle influence along the curve

Type boolean, default False

use_max_distance
Use a maximum distance for the field to work

Type boolean, default False

use_min_distance
Use a minimum distance for the field's fall-off

Type boolean, default False

use_multiple_springs
Every point is effected by multiple springs

Type boolean, default False

use_object_coords
Use object/global coordinates for texture

Type boolean, default False

use_radial_max
Use a maximum radial distance for the field to work

Type boolean, default False

use_radial_min
Use a minimum radial distance for the field's fall-off

Type boolean, default False

use_root_coords
Texture coordinates from root particle locations

Type boolean, default False

z_direction
Effect in full or only positive/negative Z direction

Type enum in ['BOTH', 'POSITIVE', 'NEGATIVE'], default 'BOTH'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.field
- ParticleSettings.force_field_1
- ParticleSettings.force_field_2

1.4.217 FileSelectParams(bpy_struct)

base class — bpy_struct

class bpy.types.**FileSelectParams**(*bpy_struct*)
File Select Parameters

directory
Directory displayed in the file browser

Type string, default “”

display_type
Display mode for the file list

Type enum in [’FILE_SHORTDISPLAY’, ‘FILE_LONGDISPLAY’, ‘FILE_IMGDISPLAY’], default ‘FILE_SHORTDISPLAY’

filename
Active file in the file browser

Type string, default “”

filter_glob

Type string, default “”

show_hidden
Show hidden dot files

Type boolean, default False

sort_method

Type enum in [’FILE_SORT_ALPHA’, ‘FILE_SORT_EXTENSION’, ‘FILE_SORT_TIME’, ‘FILE_SORT_SIZE’], default ‘FILE_SORT_ALPHA’

title
Title for the file browser

Type string, default “”, (readonly)

use_filter
Enable filtering of files

Type boolean, default False

use_filter_blender
Show .blend files

Type boolean, default False

use_filter_folder
Show folders

Type boolean, default False

use_filter_font
Show font files

Type boolean, default False

use_filter_image
Show image files

Type boolean, default False

use_filter_movie
Show movie files

Type boolean, default False

use_filter_script
Show script files

Type boolean, default False

use_filter_sound
Show sound files

Type boolean, default False

use_filter_text
Show text files

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceFileBrowser.params

1.4.218 Filter2DActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**Filter2DActuator**(*Actuator*)
Actuator to apply screen graphic effects

filter_pass
Set filter order

Type int in [0, 99], default 0

glsl_shader

Type Text

mode

Type enum in ['ENABLE', 'DISABLE', 'REMOVE', 'MOTIONBLUR', 'BLUR', 'SHARPEN', 'DILATION', 'EROSION', 'LAPLACIAN', 'SOBEL', 'PREWITT', 'GRAYSCALE', 'SEPIA', 'INVERT', 'CUSTOMFILTER'], default 'REMOVE'

motion_blur_factor
Set motion blur factor

Type float in [0, 1], default 0.0

use_motion_blur
Enable/Disable Motion Blur

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.219 FloatProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**FloatProperty**(*Property*)
RNA floating pointer number property definition

array_length
Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default
Default value for this number

Type float in [-inf, inf], default 0.0, (readonly)

default_array
Default value for this array

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

hard_max
Maximum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

hard_min
Minimum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

precision
Number of digits after the dot used by buttons

Type int in [0, inf], default 0, (readonly)

soft_max
Maximum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

soft_min
Minimum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

step
Step size used by number buttons, for floats 1/100th of the step size

Type float in [0, inf], default 0.0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.220 FloorConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**FloorConstraint**(*Constraint*)

Uses the target object for location limitation

floor_location

Location of target that object will not pass through

Type enum in ['FLOOR_X', 'FLOOR_Y', 'FLOOR_Z', 'FLOOR_NEGATIVE_X', 'FLOOR_NEGATIVE_Y', 'FLOOR_NEGATIVE_Z'], default 'FLOOR_X'

offset

Offset of floor from object origin

Type float in [0, 100], default 0.0

subtarget

Type string, default ""

target

Target Object

Type Object

use_rotation

Use the target's rotation to determine floor

Type boolean, default False

use_sticky

Immobilize object while constrained

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.221 FluidFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**FluidFluidSettings**(*FluidSettings*)

Fluid simulation settings for the fluid in the simulation

initial_velocity

Initial velocity of fluid

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_initialization
Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.222 FluidSettings(bpy_struct)

base class — bpy_struct

subclasses — FluidFluidSettings, DomainFluidSettings, ControlFluidSettings, InflowFluidSettings, ObstacleFluidSettings, ParticleFluidSettings, OutflowFluidSettings

class bpy.types.**FluidSettings**(*bpy_struct*)
Fluid simulation settings for an object taking part in the simulation

type
Type of participation in the fluid simulation

Type enum in ['NONE', 'DOMAIN', 'FLUID', 'OBSTACLE', 'INFLOW', 'OUTFLOW', 'PARTICLE', 'CONTROL'], default 'NONE'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FluidSimulationModifier.settings

1.4.223 FluidSimulationModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**FluidSimulationModifier**(*Modifier*)

Fluid simulation modifier

settings

Settings for how this object is used in the fluid simulation

Type FluidSettings, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.224 FollowPathConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**FollowPathConstraint**(*Constraint*)

Locks motion to the target path

forward_axis

Axis that points forward along the path

Type enum in ['FORWARD_X', 'FORWARD_Y', 'FORWARD_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'FORWARD_X'

offset

Offset from the position corresponding to the time frame

Type float in [-300000, 300000], default 0.0

offset_factor

Percentage value defining target position along length of bone

Type float in [0, 1], default 0.0

target

Target Object

Type Object

up_axis

Axis that points upward

Type enum in ['UP_X', 'UP_Y', 'UP_Z'], default 'UP_X'

use_curve_follow

Object will follow the heading and banking of the curve

Type boolean, default False

use_curve_radius

Objects scale by the curve radius

Type boolean, default False

use_fixed_location

Object will stay locked to a single point somewhere along the length of the curve regardless of time

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.225 Function(bpy_struct)

base class — bpy_struct

class bpy.types.**Function**(*bpy_struct*)

RNA function definition

description

Description of the Function's purpose

Type string, default "", (readonly)

identifier

Unique name used in the code and scripting

Type string, default "", (readonly)

is_registered

Function is registered as callback as part of type registration

Type boolean, default False, (readonly)

is_registered_optional
Function is optionally registered as callback part of type registration

Type boolean, default False, (readonly)

parameters
Parameters for the function

Type Collection of `Property`, (readonly)

use_self
Function does not pass its self as an argument (becomes a class method in python)

Type boolean, default False, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Struct.functions`

1.4.226 GPencilFrame(bpy_struct)

base class — `bpy_struct`

class `bpy.types.GPencilFrame`(*bpy_struct*)
Collection of related sketches on a particular frame

frame_number
The frame on which this sketch appears

Type int in [0, 300000], default 0

is_edited
Frame is being edited (painted on)

Type boolean, default False

select
Frame is selected for editing in the DopeSheet

Type boolean, default False

strokes
Freehand curves defining the sketch on this frame

Type Collection of GPencilStroke, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GPencilLayer.active_frame
- GPencilLayer.frames

1.4.227 GPencilLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**GPencilLayer**(*bpy_struct*)
Collection of related sketches

active
Set active layer for editing

Type boolean, default False

active_frame
Frame currently being displayed for this layer

Type GPencilFrame, (readonly)

alpha
Layer Opacity

Type float in [0.3, 1], default 0.0

color
Color for all strokes in this layer

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

frames
Sketches for this layer on different frames

Type Collection of GPencilFrame, (readonly)

ghost_range_max
Maximum number of frames on either side of the active frame to show (0 = show the 'first' available sketch on either side)

Type int in [0, 120], default 0

hide
Set layer Visibility

Type boolean, default False

info
Layer name

Type string, default ""

line_width
Thickness of strokes (in pixels)

Type int in [1, 10], default 0

lock
Protect layer from further editing and/or frame changes

Type boolean, default False

lock_frame
Lock current frame displayed by layer

Type boolean, default False

select
Layer is selected for editing in the DopeSheet

Type boolean, default False

show_points
Draw the points which make up the strokes (for debugging purposes)

Type boolean, default False

use_onion_skinning
Ghost frames on either side of frame

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GreasePencil.layers

1.4.228 GPencilStroke(bpy_struct)

base class — bpy_struct

class bpy.types.**GPencilStroke** (*bpy_struct*)

Freehand curve defining part of a sketch

points

Stroke data points

Type Collection of GPencilStrokePoint, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GPencilFrame.strokes

1.4.229 GPencilStrokePoint(bpy_struct)

base class — bpy_struct

class bpy.types.**GPencilStrokePoint**(*bpy_struct*)

Data point for freehand stroke curve

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

pressure

Pressure of tablet at point when drawing it

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GPencilStroke.points

1.4.230 GameActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**GameActuator** (*Actuator*)

filename
Load this blend file, use the "//" prefix for a path relative to the current blend file

Type string, default ""

mode

Type enum in ['START', 'RESTART', 'QUIT', 'SAVECFG', 'LOADCFG'], default 'START'

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.231 GameBooleanProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.**GameBooleanProperty**(*GameProperty*)
Game engine user defined Boolean property

value
Property value

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.232 GameFloatProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.**GameFloatProperty**(*GameProperty*)
Game engine user defined floating pointer number property

value
Property value

Type float in [-10000, 10000], default 0.0

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.233 GameIntProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.**GameIntProperty**(*GameProperty*)

Game engine user defined integer number property

value

Property value

Type int in [-10000, 10000], default 0

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.234 GameObjectSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**GameObjectSettings**(*bpy_struct*)

Game engine related settings for the object

actuators

Game engine actuators to act on events

Type Collection of Actuator, (readonly)

collision_bounds_type

Selects the collision type

Type enum in ['BOX', 'SPHERE', 'CYLINDER', 'CONE', 'CONVEX_HULL', 'TRIANGLE_MESH', 'CAPSULE'], default 'BOX'

collision_margin

Extra margin around object for collision detection, small amount required for stability

Type float in [0, 1], default 0.0

controllers

Game engine controllers to process events, connecting sensor to actuators

Type Collection of Controller, (readonly)

damping

General movement damping

Type float in [0, 1], default 0.0

form_factor

Form factor scales the inertia tensor

Type float in [0, 1], default 0.0

friction_coefficients

Relative friction coefficient in the in the X, Y and Z directions, when anisotropic friction is enabled

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

lock_location_x

Disable simulation of linear motion along the X axis

Type boolean, default False

lock_location_y

Disable simulation of linear motion along the Y axis

Type boolean, default False

lock_location_z

Disable simulation of linear motion along the Z axis

Type boolean, default False

lock_rotation_x
Disable simulation of angular motion along the X axis

Type boolean, default False

lock_rotation_y
Disable simulation of angular motion along the Y axis

Type boolean, default False

lock_rotation_z
Disable simulation of angular motion along the Z axis

Type boolean, default False

mass
Mass of the object

Type float in [0.01, 10000], default 0.0

physics_type
Selects the type of physical representation

Type enum in ['NO_COLLISION', 'STATIC', 'DYNAMIC', 'RIGID_BODY', 'SOFT_BODY', 'OCCLUDE', 'SENSOR'], default 'NO_COLLISION'

properties
Game engine properties

Type Collection of `GameProperty`, (readonly)

radius
Radius of bounding sphere and material physics

Type float in [0.01, 10], default 0.0

rotation_damping
General rotation damping

Type float in [0, 1], default 0.0

sensors
Game engine sensor to detect events

Type Collection of `Sensor`, (readonly)

show_actuators
Shows actuators for this object in the user interface

Type boolean, default False

show_controllers
Shows controllers for this object in the user interface

Type boolean, default False

show_debug_state
Print state debug info in the game engine

Type boolean, default False

show_sensors
Shows sensors for this object in the user interface

Type boolean, default False

show_state_panel
Show state panel

Type boolean, default False

soft_body
Settings for Bullet soft body simulation

Type GameSoftBodySettings, (readonly)

states_initial
Initial state when the game starts

Type boolean array of 30 items, default (False, False)

states_visible
State determining which controllers are displayed

Type boolean array of 30 items, default (False, False)

use_activity_culling
Disable simulation of angular motion along the Z axis

Type boolean, default False

use_actor
Object is detected by the Near and Radar sensor

Type boolean, default False

use_all_states
Set all state bits

Type boolean, default False

use_anisotropic_friction
Enable anisotropic friction

Type boolean, default False

use_collision_bounds
Specify a collision bounds type other than the default

Type boolean, default False

use_collision_compound
Add children to form a compound collision object

Type boolean, default False

use_ghost
Object does not restitute collisions, like a ghost

Type boolean, default False

use_material_physics_fh
React to force field physics settings in materials

Type boolean, default False

use_rotate_from_normal
Use face normal to rotate object, so that it points away from the surface

Type boolean, default False

use_sleep
Disable auto (de)activation in physics simulation

Type boolean, default False

used_states
States which are being used by controllers

Type boolean array of 30 items, default (False, False), (readonly)

velocity_max
Clamp velocity to this maximum speed

Type float in [0, 1000], default 0.0

velocity_min
Clamp velocity to this minimum speed (except when totally still)

Type float in [0, 1000], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.game

1.4.235 GameProperty(bpy_struct)

base class — bpy_struct

subclasses — GameStringProperty, GameIntProperty, GameBooleanProperty, GameFloatProperty, GameTimerProperty

class bpy.types.**GameProperty**(*bpy_struct*)

Game engine user defined object property

name

Available as GameObject attributes in the game engine's python API

Type string, default ""

show_debug

Print debug information for this property

Type boolean, default False

type

Type enum in ['BOOL', 'INT', 'FLOAT', 'STRING', 'TIMER'], default 'BOOL'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GameObjectSettings.properties

1.4.236 GameSoftBodySettings(bpy_struct)

base class — bpy_struct

class bpy.types.**GameSoftBodySettings**(*bpy_struct*)

Soft body simulation settings for an object in the game engine

cluster_iterations
Specify the number of cluster iterations

Type int in [1, 128], default 0

collision_margin
Collision margin for soft body. Small value makes the algorithm unstable

Type float in [0.01, 1], default 0.0

dynamic_friction
Dynamic Friction

Type float in [0, 1], default 0.0

linear_stiffness
Linear stiffness of the soft body links

Type float in [0, 1], default 0.0

location_iterations
Position solver iterations

Type int in [0, 10], default 0

shape_threshold
Shape matching threshold

Type float in [0, 1], default 0.0

use_bending_constraints
Enable bending constraints

Type boolean, default False

use_cluster_rigid_to_softbody
Enable cluster collision between soft and rigid body

Type boolean, default False

use_cluster_soft_to_softbody
Enable cluster collision between soft and soft body

Type boolean, default False

use_shape_match
Enable soft body shape matching goal

Type boolean, default False

weld_threshold
Welding threshold: distance between nearby vertices to be considered equal => set to 0.0 to disable welding test and speed up scene loading (ok if the mesh has no duplicates)

Type float in [0, 0.01], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GameObjectSettings.soft_body

1.4.237 GameStringProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.**GameStringProperty**(*GameProperty*)

Game engine user defined text string property

value

Property value

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.238 GameTimerProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.**GameTimerProperty**(*GameProperty*)

Game engine user defined timer property

value

Property value

Type float in [-10000, 10000], default 0.0

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.239 GlowSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class `bpy.types.GlowSequence`(*EffectSequence*)

Sequence strip creating a glow effect

blur_radius

Radius of glow effect

Type float in [0.5, 20], default 0.0

boost_factor

Brightness multiplier

Type float in [0, 10], default 0.0

clamp

rightness limit of intensity

Type float in [0, 1], default 0.0

quality

Accuracy of the blur effect

Type int in [1, 5], default 0

threshold

Minimum intensity to trigger a glow

Type float in [0, 1], default 0.0

use_only_boost

Show the glow buffer only

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start

- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.240 GreasePencil(ID)

base classes — bpy_struct, ID

class bpy.types.**GreasePencil**(*ID*)

Freehand annotation sketchbook

draw_mode

Type enum in ['CURSOR', 'VIEW', 'SURFACE', 'STROKE'], default 'VIEW'

layers

Type Collection of GPencilLayer, (readonly)

use_stroke_endpoints

Only use the first and last parts of the stroke for snapping

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.grease_pencil
- NodeTree.grease_pencil
- Object.grease_pencil
- Scene.grease_pencil
- SpaceImageEditor.grease_pencil

1.4.241 Group(ID)

base classes — bpy_struct, ID

class bpy.types.**Group**(*ID*)

Group of Object datablocks

dupli_offset

Offset from the origin to use when instancing as DupliGroup

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

layers

Layers visible when this groups is instanced as a dupli

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

objects

A collection of this groups objects

Type GroupObjects collection of Object, (readonly)

users_dupli_group

The dupli group this group is used in (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create

- ID.animation_data_clear
- ID.update_tag

References

- BlendData.groups
- BlendDataGroups.new
- BlendDataGroups.remove
- ClothCollisionSettings.group
- DopeSheet.filter_group
- EffectorWeights.group
- Material.light_group
- Object.dupli_group
- ParticleSettings.dupli_group
- RenderLayer.light_override
- SceneRenderLayer.light_override
- SmokeDomainSettings.collision_group
- SmokeDomainSettings.effector_group
- SmokeDomainSettings.fluid_group

1.4.242 GroupInputs(bpy_struct)

base class — bpy_struct

class bpy.types.**GroupInputs**(*bpy_struct*)

Collection of group sockets

new(*name="Socket"*, *type='VALUE'*)

Add a socket to the group tree.

Parameters

- **name** (*string, (optional)*) – Name, Name of the socket
- **type** (*enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)*) – Type, Type of socket

Returns New socket.

Return type NodeSocket

expose(*sock=None*, *add_link=True*)

Expose an internal socket in the group tree.

Parameters

- **sock** (NodeSocket, (optional)) – Socket, Internal node socket to expose
- **add_link** (*boolean, (optional)*) – Add Link, If TRUE, adds a link to the internal socket

Returns New socket.

Return type NodeSocket

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NodeTree.inputs

1.4.243 GroupObjects(bpy_struct)

base class — bpy_struct

class bpy.types.**GroupObjects**(*bpy_struct*)

Collection of group objects

link(*object*)

Add this object to a group

Parameters **object** (Object) – Object to add.

unlink(*object*)

Remove this object to a group

Parameters **object** (Object) – Object to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Group.objects

1.4.244 GroupOutputs(bpy_struct)

base class — bpy_struct

class bpy.types.**GroupOutputs**(*bpy_struct*)

Collection of group sockets

new(*name="Socket"*, *type='VALUE'*)

Add a socket to the group tree.

Parameters

- **name** (*string, (optional)*) – Name, Name of the socket
- **type** (*enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)*) – Type, Type of socket

Returns New socket.

Return type NodeSocket

expose(*sock=None*, *add_link=True*)

Expose an internal socket in the group tree.

Parameters

- **sock** (NodeSocket, (optional)) – Socket, Internal node socket to expose
- **add_link** (*boolean, (optional)*) – Add Link, If TRUE, adds a link to the internal socket

Returns New socket.

Return type NodeSocket

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NodeTree.outputs

1.4.245 Header(bpy_struct)

base class — bpy_struct

class bpy.types.**Header**(*bpy_struct*)

Editor header containing UI elements.

bl_idname

If this is set, the header gets a custom ID, otherwise it takes the name of the class used to define the panel. For example, if the class name is "OBJECT_HT_hello", and bl_idname is not set by the script, then bl_idname = "OBJECT_HT_hello"

Type string, default ""

bl_space_type

The space where the header is going to be used in.

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY'

layout

Defines the structure of the header in the UI.

Type UILayout, (readonly)

draw(*context*)

Draw UI elements into the header UI layout.

classmethod append(*draw_func*)

Append a draw function to this menu, takes the same arguments as the menus draw function.

classmethod prepend(*draw_func*)

Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove (*draw_func*)
Remove a draw function that has been added to this menu

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.246 HemiLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.**HemiLamp** (*Lamp*)
180 degree constant lamp

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular

- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.247 Histogram(bpy_struct)

base class — bpy_struct

class bpy.types.**Histogram**(*bpy_struct*)

Statistical view of the levels of color in an image

mode

Channels to display when drawing the histogram

Type enum in ['LUMA', 'RGB', 'R', 'G', 'B'], default 'LUMA'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scopes.histogram
- SpaceImageEditor.sample_histogram

1.4.248 HookModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**HookModifier**(*Modifier*)

Hook modifier to modify the location of vertices

falloff

If not zero, the distance from the hook where influence ends

Type float in [0, inf], default 0.0

force

Relative force of the hook

Type float in [0, 1], default 0.0

object

Parent Object for hook, also recalculates and clears offset

Type Object

subtarget

Name of Parent Bone for hook (if applicable), also recalculates and clears offset

Type string, default ""

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render

- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.249 ID(bpy_struct)

base class — bpy_struct

subclasses — Lattice, Library, Key, NodeTree, MetaBall, Text, Lamp, World, Brush, Object, Armature, Mesh, VectorFont, GreasePencil, Sound, ParticleSettings, Scene, WindowManager, Texture, Curve, Action, Group, Screen, Material, Image, Camera

class bpy.types.**ID**(*bpy_struct*)

Base type for datablocks, defining a unique name, linking from other libraries and garbage collection

library

Library file the datablock is linked from

Type Library, (readonly)

name

Unique datablock ID name

Type string, default “”

tag

Tools can use this to tag data, (initial state is undefined)

Type boolean, default False

use_fake_user

Saves this datablock even if it has no users

Type boolean, default False

users

Number of times this datablock is referenced

Type int in [0, 32767], default 0, (readonly)

copy()

Create a copy of this datablock (not supported for all datablocks).

Returns New copy of the ID.

Return type ID

user_clear()
Clears the user count of a datablock so its not saved, on reload the data will be removed.

animation_data_create()
Create animation data to this ID, note that not all ID types support this.

Returns New animation data or NULL.

Return type AnimData

animation_data_clear()
Clear animation on this this ID.

update_tag(*refresh=set()*)
Tag the id to update its display data.

Parameters **refresh** (*enum set in {'OBJECT', 'DATA', 'TIME'}, (optional)*) – Type of updates to perform.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.scripts
- BlendDataObjects.new
- DopeSheet.source
- DriverTarget.id
- ID.copy
- Key.user
- KeyingSetPath.id

- KeyingSetPaths.add
- Object.data
- SpaceNodeEditor.id
- SpaceNodeEditor.id_from
- SpaceProperties.pin_id
- UILayout.template_path_builder
- UILayout.template_preview
- UILayout.template_preview

1.4.250 IDMaterials(bpy_struct)

base class — bpy_struct

class bpy.types.**IDMaterials**(*bpy_struct*)

Collection of materials

append(*material*)

Add a new material to Mesh.

Parameters **material** (Material) – Material to add.

pop(*index*)

Add a new material to Mesh.

Parameters **index** (*int in [0, inf]*) – Frame number to set.

Returns Material to add.

Return type Material

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Curve.materials
- Mesh.materials
- MetaBall.materials

1.4.251 IKParam(bpy_struct)

base class — bpy_struct

subclasses — Itasc

class bpy.types.**IKParam**(*bpy_struct*)

Base type for IK solver parameters

ik_solver

IK solver for which these parameters are defined, 0 for Legacy, 1 for iTaSC

Type enum in ['LEGACY', 'ITASC'], default 'LEGACY', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Pose.ik_param

1.4.252 Image(ID)

base classes — bpy_struct, ID

class `bpy.types.Image`(*ID*)

Image datablock referencing an external or packed image

bindcode

OpenGL bindcode

Type int in [0, inf], default 0, (readonly)

depth

Image bit depth

Type int in [0, inf], default 0, (readonly)

display_aspect

Display Aspect for this image, does not affect rendering

Type float array of 2 items in [0.1, 5000], default (0.0, 0.0)

field_order

Order of video fields. Select which lines are displayed first

Type enum in ['EVEN', 'ODD'], default 'EVEN'

file_format

Format used for re-saving this file

Type enum in ['BMP', 'IRIS', 'PNG', 'JPEG', 'TARGA', 'TARGA_RAW', 'MULTILAYER', 'OPEN_EXR', 'AVI_JPEG', 'AVI_RAW', 'FRAMESERVER'], default 'TARGA'

filepath

Image/Movie file name

Type string, default ""

filepath_raw

Image/Movie file name (without data refreshing)

Type string, default ""

fps

Speed of the animation in frames per second

Type int in [1, 100], default 0

frame_end

End frame of an animated texture

Type int in [0, 128], default 0

frame_start

Start frame of an animated texture

Type int in [0, 128], default 0

generated_height

Generated image height

Type int in [1, 16384], default 0

generated_type

Generated image type

Type enum in ['BLANK', 'UV_GRID', 'COLOR_GRID'], default 'BLANK'

generated_width

Generated image width

Type int in [1, 16384], default 0

has_data
True if this image has data

Type boolean, default False, (readonly)

is_dirty
Image has changed and is not saved

Type boolean, default False, (readonly)

mapping
Mapping type to use for this image in the game engine

Type enum in ['UV', 'REFLECTION'], default 'UV'

packed_file

Type `PackedFile`, (readonly)

size
Width and height in pixels, zero when image data cant be loaded

Type int array of 2 items in [-inf, inf], default (0, 0), (readonly)

source
Where the image comes from

Type enum in ['FILE', 'SEQUENCE', 'MOVIE', 'GENERATED', 'VIEWER'], default 'FILE'

tiles_x
Degree of repetition in the X direction

Type int in [1, 16], default 0

tiles_y
Degree of repetition in the Y direction

Type int in [1, 16], default 0

type
How to generate the image

Type enum in ['IMAGE', 'MULTILAYER', 'UV_TEST', 'RENDER_RESULT', 'COMPOSITING'], default 'IMAGE', (readonly)

use_animation
Use as animated texture in the game engine

Type boolean, default False

use_clamp_x
Disable texture repeating horizontally

Type boolean, default False

use_clamp_y
Disable texture repeating vertically

Type boolean, default False

use_fields
Use fields of the image

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_tiles
Use of tilemode for faces (default shift-LMB to pick the tile for selected faces)

Type boolean, default False

save_render(*filepath*, *scene=None*)
Save image to a specific path using a scenes render settings

Parameters

- **filepath** (*string*) – Save path.
- **scene** (Scene, (optional)) – Scene to take image parameters from

save()
Save image to its source path

reload()
Reload the image from its source path

update()
Update the display image from the floating point buffer

gl_load(*filter=9985*, *mag=9729*)
Load the image into OpenGL graphics memory

Parameters

- **filter** (*int in [-inf, inf], (optional)*) – Filter, The texture minifying function
- **mag** (*int in [-inf, inf], (optional)*) – Magnification, The texture magnification function

Returns Error, OpenGL error value

Return type int in [-inf, inf]

gl_free()
Free the image from OpenGL graphics memory

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BackgroundImage.image
- BlendData.images
- BlendDataImages.load
- BlendDataImages.new
- BlendDataImages.remove
- Brush.clone_image
- CompositorNodeImage.image
- EnvironmentMapTexture.image
- ImageTexture.image
- MeshTextureFace.image
- SpaceImageEditor.image
- TextureNodeImage.image
- UILayout.template_image_layers
- UVProjectModifier.image
- VoxelDataTexture.image

1.4.253 ImagePaint(Paint)

base classes — bpy_struct, Paint

class bpy.types.**ImagePaint**(*Paint*)

Properties of image and texture painting mode

invert_stencil

Invert the stencil layer

Type boolean, default False

normal_angle

Paint most on faces pointing towards the view according to this angle

Type int in [0, 90], default 0

screen_grab_size

Size to capture the image for re-projecting

Type int array of 2 items in [512, 16384], default (0, 0)

seam_bleed
Extend paint beyond the faces UVs to reduce seams (in pixels, slower)

Type int in [0, 32767], default 0

use_backface_culling
Ignore faces pointing away from the view (faster)

Type boolean, default False

use_clone_layer
Use another UV layer as clone source, otherwise use 3D the cursor as the source

Type boolean, default False

use_normal_falloff
Paint most on faces pointing towards the view

Type boolean, default False

use_occlude
Only paint onto the faces directly under the brush (slower)

Type boolean, default False

use_projection
Use projection painting for improved consistency in the brush strokes

Type boolean, default False

use_stencil_layer
Set the mask layer from the UV layer buttons

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Paint.brush
- Paint.show_low_resolution
- Paint.show_brush
- Paint.show_brush_on_surface

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.image_paint

1.4.254 ImageSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**ImageSequence**(*Sequence*)

Sequence strip to load one or more images

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

directory

Type string, default “”

elements

Type Collection of SequenceElement, (readonly)

proxy

Type SequenceProxy, (readonly)

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop
Crop image before processing

Type boolean, default False

use_deinterlace
For video movies to remove fields

Type boolean, default False

use_flip_x
Flip on the X axis

Type boolean, default False

use_flip_y
Flip on the Y axis

Type boolean, default False

use_float
Convert input to float data

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy
Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader

- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.255 ImageTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**ImageTexture**(*Texture*)

checker_distance

Sets distance between checker tiles

Type float in [0, 0.99], default 0.0

crop_max_x
Sets maximum X value to crop the image

Type float in [-10, 10], default 0.0

crop_max_y
Sets maximum Y value to crop the image

Type float in [-10, 10], default 0.0

crop_min_x
Sets minimum X value to crop the image

Type float in [-10, 10], default 0.0

crop_min_y
Sets minimum Y value to crop the image

Type float in [-10, 10], default 0.0

extension
Sets how the image is extrapolated past its original bounds

Type enum in ['EXTEND', 'CLIP', 'CLIP_CUBE', 'REPEAT', 'CHECKER'], default 'EXTEND'

filter_eccentricity
Maximum eccentricity. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_probes
Maximum number of samples. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_size
Multiplies the filter size used by MIP Map and Interpolation

Type float in [0.1, 50], default 0.0

filter_type
Texture filter to use for sampling image

Type enum in ['BOX', 'EWA', 'FELINE', 'AREA'], default 'BOX'

image

Type `Image`

image_user
Parameters defining which layer, pass and frame of the image is displayed

Type `ImageUser`, (readonly)

invert_alpha
Inverts all the alpha values in the image

Type boolean, default False

repeat_x
Sets a repetition multiplier in the X direction

Type int in [1, 512], default 0

repeat_y
Sets a repetition multiplier in the Y direction

Type int in [1, 512], default 0

use_alpha
Uses the alpha channel information in the image

Type boolean, default False

use_calculate_alpha
Calculates an alpha channel based on RGB values in the image

Type boolean, default False

use_checker_even
Sets even checker tiles

Type boolean, default False

use_checker_odd
Sets odd checker tiles

Type boolean, default False

use_filter_size_min
Use Filter Size as a minimal filter value in pixels

Type boolean, default False

use_flip_axis
Flips the texture's X and Y axis

Type boolean, default False

use_interpolation
Interpolates pixels using Area filter

Type boolean, default False

use_mipmap
Uses auto-generated MIP maps for the image

Type boolean, default False

use_mipmap_gauss
Uses Gauss filter to sample down MIP maps

Type boolean, default False

use_mirror_x
Mirrors the image repetition on the X direction

Type boolean, default False

use_mirror_y
Mirrors the image repetition on the Y direction

Type boolean, default False

use_normal_map
Uses image RGB values for normal mapping

Type boolean, default False

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.256 ImageUser(bpy_struct)

base class — bpy_struct

class bpy.types.**ImageUser**(*bpy_struct*)

Parameters defining how an Image datablock is used by another datablock

fields_per_frame

The number of fields per rendered frame (2 fields is 1 image)

Type int in [1, 200], default 0

frame_duration

Sets the number of images of a movie to use

Type int in [0, 300000], default 0

frame_offset

Offsets the number of the frame to use in the animation

Type int in [-300000, 300000], default 0

frame_start

Sets the global starting frame of the movie/sequence, assuming first picture has a #1

Type int in [-300000, 300000], default 0

multilayer_layer

Layer in multilayer image

Type int in [0, 32767], default 0, (readonly)

multilayer_pass

Pass in multilayer image

Type int in [0, 32767], default 0, (readonly)

use_auto_refresh

Always refresh image on frame changes

Type boolean, default False

use_cyclic

Cycle the images in the movie

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BackgroundImage.image_user
- EnvironmentMapTexture.image_user
- ImageTexture.image_user
- SpaceImageEditor.image_user
- UILayout.template_image
- UILayout.template_image_layers
- VoxelDataTexture.image_user

1.4.257 InflowFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**InflowFluidSettings** (*FluidSettings*)

Fluid simulation settings for objects adding fluids in the simulation

inflow_velocity

Initial velocity of fluid

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

use_local_coords

Use local coordinates for inflow. (e.g. for rotating objects)

Type boolean, default False

volume_initialization

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.258 InputKeyMapPanel(Panel)

base classes — bpy_struct, Panel

class bpy.types.**InputKeyMapPanel**(*Panel*)

classmethod append(*draw_func*)
Append a draw function to this menu, takes the same arguments as the menus draw function.

draw_entry(*display_keymaps*, *entry*, *col*, *level=0*)

draw_filtered(*display_keymaps*, *filter_text*, *layout*)

draw_hierarchy(*display_keymaps*, *layout*)

draw_keymaps(*context*, *layout*)

draw_km(*display_keymaps*, *kc*, *km*, *children*, *layout*, *level*)

draw_kmi(*display_keymaps*, *kc*, *km*, *kmi*, *layout*, *level*)

static draw_kmi_properties(*box*, *properties*, *title=None*)

indented_layout(*layout*, *level*)

classmethod prepend(*draw_func*)
Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove(*draw_func*)
Remove a draw function that has been added to this menu

Inherited Properties

- bpy_struct.id_data
- Panel.bl_context
- Panel.bl_idname
- Panel.bl_label
- Panel.layout

- Panel.bl_options
- Panel.bl_region_type
- Panel.bl_space_type
- Panel.text

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Panel.poll
- Panel.draw
- Panel.draw_header
- Panel.append
- Panel.prepend
- Panel.remove

1.4.259 IntProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**IntProperty**(*Property*)

RNA integer number property definition

array_length

Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default

Default value for this number

Type int in [-inf, inf], default 0, (readonly)

default_array

Default value for this array

Type int array of 3 items in [-inf, inf], default (0, 0, 0), (readonly)

hard_max

Maximum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

hard_min
Minimum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

soft_max
Maximum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

soft_min
Minimum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

step
Step size used by number buttons, for floats 1/100th of the step size

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

1.4.260 Itasc(IKParam)

base classes — bpy_struct, IKParam

class bpy.types.**Itasc**(*IKParam*)

Parameters for the iTaSC IK solver

damping_epsilon

Singular value under which damping is progressively applied. Higher values=more stability, less reactivity. Default=0.1

Type float in [0, 1], default 0.0

damping_max

Maximum damping coefficient when singular value is nearly 0. Higher values=more stability, less reactivity. Default=0.5

Type float in [0, 1], default 0.0

feedback

Feedback coefficient for error correction. Average response time=1/feedback. Default=20

Type float in [0, 100], default 0.0

iterations

Maximum number of iterations for convergence in case of reiteration

Type int in [1, 1000], default 0

mode

Type enum in ['ANIMATION', 'SIMULATION'], default 'ANIMATION'

precision

Precision of convergence in case of reiteration

Type float in [0, 0.1], default 0.0

reiteration_method

Defines if the solver is allowed to reiterate (converges until precision is met) on none, first or all frames

Type enum in ['NEVER', 'INITIAL', 'ALWAYS'], default 'NEVER'

solver

Solving method selection: Automatic damping or manual damping

Type enum in ['SDLS', 'DLS'], default 'SDLS'

step_count

Divides the frame interval into this many steps

Type int in [1, 50], default 0

step_max

Higher bound for timestep in second in case of automatic substeps

Type float in [0, 1], default 0.0

step_min

Lower bound for timestep in second in case of automatic substeps

Type float in [0, 0.1], default 0.0

use_auto_step
Automatically determine the optimal number of steps for best performance/accuracy trade off

Type boolean, default False

velocity_max
Maximum joint velocity in rad/s. Default=50

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- IKParam.ik_solver

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.261 JoystickSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**JoystickSensor**(*Sensor*)
Sensor to detect joystick events

axis_direction
The direction of the axis

Type enum in ['RIGHTAXIS', 'UPAXIS', 'LEFTAXIS', 'DOWNAXIS'], default 'RIGHTAXIS'

axis_number
Specify which axis pair to use, 1 is usually the main direction input

Type int in [1, 2], default 0

axis_threshold
Specify the precision of the axis

Type int in [0, 32768], default 0

button_number
Specify which button to use

Type int in [0, 18], default 0

event_type
The type of event this joystick sensor is triggered on

Type enum in ['BUTTON', 'AXIS', 'HAT', 'AXIS_SINGLE'], default 'BUTTON'

hat_direction
Specify hat direction

Type enum in ['UP', 'DOWN', 'LEFT', 'RIGHT', 'UPRIGHT', 'DOWNLEFT', 'UPLEFT', 'DOWNRIGHT'], default 'UP'

hat_number
Specify which hat to use

Type int in [1, 2], default 0

joystick_index
Specify which joystick to use

Type int in [0, 7], default 0

single_axis_number
Specify a single axis (verticle/horizontal/other) to detect

Type int in [1, 16], default 0

use_all_events
Triggered by all events on this joysticks current type (axis/button/hat)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.262 Key(ID)

base classes — bpy_struct, ID

class bpy.types.**Key**(*ID*)

Shape keys datablock containing different shapes of geometric datablocks

animation_data

Animation data for this datablock

Type AnimData, (readonly)

keys

Shape keys

Type Collection of ShapeKey, (readonly)

reference_key

Type ShapeKey, (readonly, never None)

slurph

Creates a delay in amount of frames in applying keypositions, first vertex goes first

Type int in [-500, 500], default 0

use_relative

Makes shape keys relative

Type boolean, default False

user

Datablock using these shape keys

Type ID, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.shape_keys
- Curve.shape_keys
- Lattice.shape_keys
- Mesh.shape_keys

1.4.263 KeyConfig(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyConfig**(*bpy_struct*)

Input configuration, including keymaps

is_user_defined

Indicates that a keyconfig was defined by the user

Type boolean, default False, (readonly)

keymaps

Key maps configured as part of this configuration

Type KeyMaps collection of KeyMap, (readonly)

name

Name of the key configuration

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyConfigurations.active
- KeyConfigurations.default
- KeyConfigurations.new
- KeyConfigurations.remove
- WindowManager.keyconfigs

1.4.264 KeyConfigurations(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyConfigurations**(*bpy_struct*)

Collection of KeyConfigs

active

Active wm KeyConfig

Type KeyConfig

default

Type KeyConfig, (readonly)

new(*name*)

new

Parameters **name** (*string*) – Name

Returns Key Configuration, Added key configuration.

Return type KeyConfig

remove (*keyconfig*)
remove

Parameters **keyconfig** (KeyConfig) – Key Configuration, Removed key configuration.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- WindowManager.keyconfigs

1.4.265 KeyMap(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyMap** (*bpy_struct*)
Input configuration, including keymaps

is_modal
Indicates that a keymap is used for translate modal events for an operator

Type boolean, default False, (readonly)

is_user_defined
Keymap is defined by the user

Type boolean, default False

items
Items in the keymap, linking an operator to an input event

Type KeyMapItems collection of KeyMapItem, (readonly)

name
Name of the key map

Type string, default "", (readonly)

region_type
Optional region type keymap is associated with

Type enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], default 'WINDOW', (readonly)

show_expanded_children
Children expanded in the user interface

Type boolean, default False

show_expanded_items
Expanded in the user interface

Type boolean, default False

space_type
Optional space type keymap is associated with

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY', (readonly)

active()
active

Returns Key Map, Active key map.

Return type KeyMap

copy_to_user()
copy_to_user

Returns Key Map, User editable key map.

Return type KeyMap

restore_to_default()
restore_to_default

restore_item_to_default(*item*)
restore_item_to_default

Parameters **item** (KeyMapItem, (never None)) – Item

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyConfig.keymaps
- KeyMap.active
- KeyMap.copy_to_user
- KeyMaps.find
- KeyMaps.find_modal
- KeyMaps.new
- UserPreferencesInput.edited_keymaps

1.4.266 KeyMapItem(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyMapItem**(*bpy_struct*)

Item in a Key Map

active

Activate or deactivate item

Type boolean, default False

alt

Alt key pressed

Type boolean, default False

any

Any modifier keys pressed

Type boolean, default False

ctrl

Control key pressed

Type boolean, default False

id

ID of the item

Type int in [-32768, 32767], default 0, (readonly)

idname

Identifier of operator to call on input event

Type string, default “”

is_user_defined

Is this keymap item user defined (doesn’t just override a builtin item)

Type boolean, default False, (readonly)

key_modifier

Regular key pressed as a modifier

Type enum in [’NONE’, ‘LEFTMOUSE’, ‘MIDDLEMOUSE’, ‘RIGHTMOUSE’, ‘BUTTON4MOUSE’, ‘BUTTON5MOUSE’, ‘ACTIONMOUSE’, ‘SELECTMOUSE’, ‘MOUSEMOVE’, ‘INBETWEEN_MOUSEMOVE’, ‘TRACKPADPAN’, ‘TRACKPADZOOM’, ‘MOUSEROTATE’, ‘WHEELUPMOUSE’, ‘WHEELDOWNMOUSE’, ‘WHEELINMOUSE’, ‘WHEELOUTMOUSE’, ‘EVT_TWEAK_L’, ‘EVT_TWEAK_M’, ‘EVT_TWEAK_R’, ‘EVT_TWEAK_A’, ‘EVT_TWEAK_S’, ‘A’, ‘B’, ‘C’, ‘D’, ‘E’, ‘F’, ‘G’, ‘H’, ‘I’, ‘J’, ‘K’, ‘L’, ‘M’, ‘N’, ‘O’, ‘P’, ‘Q’, ‘R’, ‘S’, ‘T’, ‘U’, ‘V’, ‘W’, ‘X’, ‘Y’, ‘Z’, ‘ZERO’, ‘ONE’, ‘TWO’, ‘THREE’, ‘FOUR’, ‘FIVE’, ‘SIX’, ‘SEVEN’, ‘EIGHT’, ‘NINE’, ‘LEFT_CTRL’, ‘LEFT_ALT’, ‘LEFT_SHIFT’, ‘RIGHT_ALT’, ‘RIGHT_CTRL’, ‘RIGHT_SHIFT’, ‘OSKEY’, ‘GRLESS’, ‘ESC’, ‘TAB’, ‘RET’, ‘SPACE’, ‘LINE_FEED’, ‘BACK_SPACE’, ‘DEL’, ‘SEMI_COLON’, ‘PERIOD’, ‘COMMA’, ‘QUOTE’, ‘ACCENT_GRAVE’, ‘MINUS’, ‘SLASH’, ‘BACK_SLASH’, ‘EQUAL’, ‘LEFT_BRACKET’, ‘RIGHT_BRACKET’, ‘LEFT_ARROW’, ‘DOWN_ARROW’, ‘RIGHT_ARROW’, ‘UP_ARROW’, ‘NUMPAD_2’, ‘NUMPAD_4’, ‘NUMPAD_6’, ‘NUMPAD_8’, ‘NUMPAD_1’, ‘NUMPAD_3’, ‘NUMPAD_5’, ‘NUMPAD_7’, ‘NUMPAD_9’, ‘NUMPAD_PERIOD’, ‘NUMPAD_SLASH’, ‘NUMPAD_ASTERIX’, ‘NUMPAD_0’, ‘NUMPAD_MINUS’, ‘NUMPAD_ENTER’, ‘NUMPAD_PLUS’, ‘F1’, ‘F2’, ‘F3’, ‘F4’, ‘F5’, ‘F6’, ‘F7’, ‘F8’, ‘F9’, ‘F10’, ‘F11’, ‘F12’, ‘F13’, ‘F14’, ‘F15’, ‘F16’, ‘F17’, ‘F18’, ‘F19’, ‘PAUSE’, ‘INSERT’, ‘HOME’, ‘PAGE_UP’, ‘PAGE_DOWN’, ‘END’, ‘MEDIA_PLAY’, ‘MEDIA_STOP’, ‘MEDIA_FIRST’, ‘MEDIA_LAST’, ‘WINDOW_DEACTIVATE’, ‘TIMER’, ‘TIMER0’, ‘TIMER1’, ‘TIMER2’], default ‘NONE’

map_type

Type of event mapping

Type enum in [’KEYBOARD’, ‘TWEAK’, ‘MOUSE’, ‘TEXTINPUT’, ‘TIMER’], default ‘KEYBOARD’

name

Name of operator to call on input event

Type string, default “”, (readonly)

oskey

Operating system key pressed

Type boolean, default False

properties

Properties to set when the operator is called

Type `OperatorProperties`, (readonly)

propvalue

The value this event translates to in a modal keymap

Type enum in [’NONE’], default ‘NONE’

shift

Shift key pressed

Type boolean, default False

show_expanded
Show key map event and property details in the user interface

Type boolean, default False

type
Type of event

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

value

Type enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK'], default 'NOTHING'

compare(*item*)
compare

Parameters **item** (KeyMapItem) – Item

Returns Comparison result

Return type boolean

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyMap.items
- KeyMap.restore_item_to_default
- KeyMapItem.compare
- KeyMapItems.from_id
- KeyMapItems.new
- KeyMapItems.new_modal
- KeyMapItems.remove

1.4.267 KeyMapItems(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyMapItems**(*bpy_struct*)

Collection of keymap items

new(*idname*, *type*, *value*, *any=False*, *shift=False*, *ctrl=False*, *alt=False*, *oskey=False*, *key_modifier='NONE'*)

new

Parameters

- **idname** (*string*) – Operator Identifier
- **type** (*enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN',*

'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2']) – Type

- **value** (*enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK']*) – Value
- **any** (*boolean, (optional)*) – Any
- **shift** (*boolean, (optional)*) – Shift
- **ctrl** (*boolean, (optional)*) – Ctrl
- **alt** (*boolean, (optional)*) – Alt
- **oskey** (*boolean, (optional)*) – OS Key
- **key_modifier** (*enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], (optional)*) – Key Modifier

Returns Item, Added key map item.

Return type `KeyMapItem`

new_modal(*propvalue*, *type*, *value*, *any=False*, *shift=False*, *ctrl=False*, *alt=False*, *oskey=False*, *key_modifier='NONE'*)

new_modal

Parameters

- **propvalue** (*string*) – Property Value
- **type** (*enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE',*

'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2']) – Type

- **value** (*enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK']*) – Value
- **any** (*boolean, (optional)*) – Any
- **shift** (*boolean, (optional)*) – Shift
- **ctrl** (*boolean, (optional)*) – Ctrl
- **alt** (*boolean, (optional)*) – Alt
- **oskey** (*boolean, (optional)*) – OS Key
- **key_modifier** (*enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], (optional)*) – Key Modifier

Returns Item, Added key map item.

Return type `KeyMapItem`

remove(*item*)

remove

Parameters **item** (`KeyMapItem`) – Item

from_id(*id*)

from_id

Parameters **id** (*int in [-inf, inf]*) – id, ID of the item

Returns Item

Return type KeyMapItem

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyMap.items

1.4.268 KeyMaps(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyMaps** (*bpy_struct*)

Collection of keymaps

new (*name*, *space_type='EMPTY'*, *region_type='WINDOW'*, *modal=False*)

new

Parameters

- **name** (*string*) – Name
- **space_type** (*enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], (optional)*) – Space Type

- **region_type** (*enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], (optional)*) – Region Type
- **modal** (*boolean, (optional)*) – Modal

Returns Key Map, Added key map.

Return type KeyMap

find(*name*, *space_type='EMPTY'*, *region_type='WINDOW'*)

find

Parameters

- **name** (*string*) – Name
- **space_type** (*enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], (optional)*) – Space Type
- **region_type** (*enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], (optional)*) – Region Type

Returns Key Map, Corresponding key map.

Return type KeyMap

find_modal(*name*)

find_modal

Parameters **name** (*string*) – Operator Name

Returns Key Map, Corresponding key map.

Return type KeyMap

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- KeyConfig.keymaps

1.4.269 KeyboardSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**KeyboardSensor**(*Sensor*)

Sensor to detect keyboard events

key

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

log

Property that indicates whether to log keystrokes as a string

Type string, default ""

modifier_key_1

Modifier key code

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE',

'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

modifier_key_2

Modifier key code

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

target

Property that receive the keystrokes in case a string is logged

Type string, default ""

use_all_keys

Trigger this sensor on any keystroke

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin

- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.270 Keyframe(bpy_struct)

base class — bpy_struct

class bpy.types.**Keyframe**(*bpy_struct*)

Bezier curve point with two handles defining a Keyframe on an F-Curve

co

Coordinates of the control point

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_left

Coordinates of the first handle

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_left_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

handle_right

Coordinates of the second handle

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_right_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

interpolation
Interpolation method to use for segment of the curve from this Keyframe until the next Keyframe

Type enum in ['CONSTANT', 'LINEAR', 'BEZIER'], default 'CONSTANT'

select_control_point
Control point selection status

Type boolean, default False

select_left_handle
Handle 1 selection status

Type boolean, default False

select_right_handle
Handle 2 selection status

Type boolean, default False

type
The type of keyframe

Type enum in ['KEYFRAME', 'BREAKDOWN', 'EXTREME', 'JITTER'], default 'KEYFRAME'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.keyframe_points
- FCurveKeyframePoints.insert
- FCurveKeyframePoints.remove

1.4.271 KeyingSet(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSet**(*bpy_struct*)

Settings that should be keyframed together

bl_options

Keying set options

Type enum set in {'INSERTKEY_NEEDED', 'INSERTKEY_VISUAL', 'INSERTKEY_XYZ_TO_RGB'}, default {'INSERTKEY_NEEDED'}

is_path_absolute

Keying Set defines specific paths/settings to be keyframed (i.e. is not reliant on context info)

Type boolean, default False, (readonly)

name

Type string, default ""

paths

Keying Set Paths to define settings that get keyframed together

Type KeyingSetPaths collection of KeyingSetPath, (readonly)

type_info

Callback function defines for built-in Keying Sets

Type KeyingSetInfo, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSetInfo.generate
- KeyingSetInfo.iterator
- KeyingSets.active
- KeyingSets.new
- KeyingSetsAll.active
- Scene.keying_sets
- Scene.keying_sets_all

1.4.272 KeyingSetInfo(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSetInfo**(*bpy_struct*)

Callback function defines for builtin Keying Sets

bl_idname

Type string, default ""

bl_label

Type string, default ""

bl_options

Keying set options

Type enum set in {'INSERTKEY_NEEDED', 'INSERTKEY_VISUAL', 'INSERTKEY_XYZ_TO_RGB'}, default {'INSERTKEY_NEEDED'}

poll(*context*)

Test if Keying Set can be used or not

Return type boolean

iterator(*context*, *ks*)

Call generate() on the structs which have properties to be keyframed

generate(*context*, *ks*, *data*)

Add Paths to the Keying Set to keyframe the properties of the given data

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSet.type_info

1.4.273 KeyingSetPath(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSetPath**(*bpy_struct*)

Path to a setting for use in a Keying Set

array_index

Index to the specific setting if applicable

Type int in [-inf, inf], default 0

bl_options

Keying set options

Type enum set in {'INSERTKEY_NEEDED', 'INSERTKEY_VISUAL', 'INSERTKEY_XYZ_TO_RGB'}, default {'INSERTKEY_NEEDED'}

data_path

Path to property setting

Type string, default ""

group

Name of Action Group to assign setting(s) for this path to

Type string, default ""

group_method

Method used to define which Group-name to use

Type enum in ['NAMED', 'NONE', 'KEYINGSET'], default 'NAMED'

id

ID-Block that keyframes for Keying Set should be added to (for Absolute Keying Sets only)

Type ID

id_type

Type of ID-block that can be used

Type enum in ['ACTION', 'ARMATURE', 'BRUSH', 'CAMERA', 'CURVE', 'FONT', 'GREASEPENCIL', 'GROUP', 'IMAGE', 'KEY', 'LAMP', 'LIBRARY', 'LATTICE', 'MATERIAL', 'META', 'MESH', 'NODETREE', 'OBJECT', 'PARTICLE', 'SCENE',

'SCREEN', 'SOUND', 'TEXT', 'TEXTURE', 'WORLD', 'WINDOWMANAGER'], default 'OBJECT'

use_entire_array
When an 'array/vector' type is chosen (Location, Rotation, Color, etc.), entire array is to be used

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSet.paths
- KeyingSetPaths.active
- KeyingSetPaths.add
- KeyingSetPaths.remove

1.4.274 KeyingSetPaths(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSetPaths** (*bpy_struct*)
Collection of keying set paths

active
Active Keying Set used to insert/delete keyframes

Type KeyingSetPath

active_index
Current Keying Set index

Type int in [-inf, inf], default 0

add(*target_id*, *data_path*, *index=-1*, *group_method='KEYINGSET'*, *group_name=""*)
Add a new path for the Keying Set.

Parameters

- **target_id** (ID) – Target ID, ID-Datablock for the destination.
- **data_path** (*string*) – Data-Path, RNA-Path to destination property.
- **index** (*int in [-1, inf], (optional)*) – Index, The index of the destination property (i.e. axis of Location/Rotation/etc.), or -1 for the entire array.
- **group_method** (*enum in ['NAMED', 'NONE', 'KEYINGSET'], (optional)*) – Grouping Method, Method used to define which Group-name to use.
- **group_name** (*string, (optional)*) – Group Name, Name of Action Group to assign destination to (only if grouping mode is to use this name).

Returns New Path, Path created and added to the Keying Set

Return type KeyingSetPath

remove(*path*)
Remove the given path from the Keying Set.

Parameters **path** (KeyingSetPath, (never None)) – Path

clear()
Remove all the paths from the Keying Set.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSet.paths

1.4.275 KeyingSets(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSets**(*bpy_struct*)

Scene keying sets

active

Active Keying Set used to insert/delete keyframes

Type KeyingSet

active_index

Current Keying Set index (negative for 'builtin' and positive for 'absolute')

Type int in [-inf, inf], default 0

new(*name="KeyingSet"*)

Add a new Keying Set to Scene.

Parameters **name** (*string, (optional)*) – Name, Name of Keying Set

Returns Newly created Keying Set.

Return type KeyingSet

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.keying_sets

1.4.276 KeyingSetsAll(bpy_struct)

base class — bpy_struct

class bpy.types.**KeyingSetsAll**(*bpy_struct*)

All available keying sets

active

Active Keying Set used to insert/delete keyframes

Type KeyingSet

active_index

Current Keying Set index (negative for 'builtin' and positive for 'absolute')

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.keying_sets_all

1.4.277 KinematicConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**KinematicConstraint**(*Constraint*)

Inverse Kinematics

chain_count

How many bones are included in the IK effect - 0 uses all bones

Type int in [0, 255], default 0

distance
Radius of limiting sphere

Type float in [0, 100], default 0.0

ik_type

Type enum in ['COPY_POSE', 'DISTANCE'], default 'COPY_POSE'

iterations
Maximum number of solving iterations

Type int in [1, 10000], default 0

limit_mode
Distances in relation to sphere of influence to allow

Type enum in ['LIMITDIST_INSIDE', 'LIMITDIST_OUTSIDE', 'LIMITDIST_ONSURFACE'], default 'LIMITDIST_INSIDE'

lock_location_x
Constraint position along X axis

Type boolean, default False

lock_location_y
Constraint position along Y axis

Type boolean, default False

lock_location_z
Constraint position along Z axis

Type boolean, default False

lock_rotation_x
Constraint rotation along X axis

Type boolean, default False

lock_rotation_y
Constraint rotation along Y axis

Type boolean, default False

lock_rotation_z
Constraint rotation along Z axis

Type boolean, default False

orient_weight
For Tree-IK: Weight of orientation control for this target

Type float in [0.01, 1], default 0.0

pole_angle
Pole rotation offset

Type float in [-3.14159, 3.14159], default 0.0

pole_subtarget

Type string, default ""

pole_target
Object for pole rotation

Type Object

reference_axis
Constraint axis Lock options relative to Bone or Target reference

Type enum in ['BONE', 'TARGET'], default 'BONE'

subtarget

Type string, default ""

target
Target Object

Type Object

use_location
Chain follows position of target

Type boolean, default False

use_rotation
Chain follows rotation of target

Type boolean, default False

use_stretch
Enable IK Stretching

Type boolean, default False

use_tail
Include bone's tail as last element in chain

Type boolean, default False

use_target
Disable for targetless IK

Type boolean, default False

weight
For Tree-IK: Weight of position control for this target

Type float in [0.01, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation

- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.278 Lamp(ID)

base classes — bpy_struct, ID

subclasses — SpotLamp, AreaLamp, HemiLamp, PointLamp, SunLamp

class bpy.types.**Lamp**(*ID*)

Lamp datablock for lighting a scene

active_texture

Active texture slot being displayed

Type Texture

active_texture_index

Index of active texture slot

Type int in [0, 17], default 0

animation_data

Animation data for this datablock

Type AnimData, (readonly)

color

Light color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

distance

Falloff distance - the light is at half the original intensity at this point

Type float in [0, inf], default 0.0

energy

Amount of light that the lamp emits

Type float in [-inf, inf], default 0.0

texture_slots
Texture slots defining the mapping and influence of textures

Type LampTextureSlots collection of LampTextureSlot, (readonly)

type
Type of Lamp

Type enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA'], default 'POINT'

use_diffuse
Lamp does diffuse shading

Type boolean, default False

use_negative
Lamp casts negative light

Type boolean, default False

use_own_layer
Illuminates objects only on the same layer the lamp is on

Type boolean, default False

use_specular
Lamp creates specular highlights

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.lamps
- BlendDataLamps.new
- BlendDataLamps.remove

1.4.279 LampSkySettings(bpy_struct)

base class — bpy_struct

class bpy.types.**LampSkySettings**(*bpy_struct*)

Sky related settings for a sun lamp

atmosphere_distance_factor

Multiplier to convert blender units to physical distance

Type float in [0, 500], default 0.0

atmosphere_extinction

Extinction scattering contribution factor

Type float in [0, 1], default 0.0

atmosphere_inscattering

Scatter contribution factor

Type float in [0, 1], default 0.0

atmosphere_turbidity

Sky turbidity

Type float in [1, 30], default 0.0

backscattered_light

Backscattered light

Type float in [-1, 1], default 0.0

horizon_brightness

Horizon brightness

Type float in [0, 20], default 0.0

sky_blend

Blend factor with sky

Type float in [0, 2], default 0.0

sky_blend_type

Blend mode for combining sun sky with world sky

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR'], default 'MIX'

sky_color_space
Color space to use for internal XYZ->RGB color conversion

Type enum in ['SMPTE', 'REC709', 'CIE'], default 'SMPTE'

sky_exposure
Strength of sky shading exponential exposure correction

Type float in [0, 20], default 0.0

spread
Horizon Spread

Type float in [0, 10], default 0.0

sun_brightness
Sun brightness

Type float in [0, 10], default 0.0

sun_intensity
Sun intensity

Type float in [0, 10], default 0.0

sun_size
Sun size

Type float in [0, 10], default 0.0

use_atmosphere
Apply sun effect on atmosphere

Type boolean, default False

use_sky
Apply sun effect on sky

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- SunLamp.sky

1.4.280 LampTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.**LampTextureSlot**(*TextureSlot*)

Texture slot for textures in a Lamp datablock

color_factor

Amount texture affects color values

Type float in [-inf, inf], default 0.0

object

Object to use for mapping with Object texture coordinates

Type Object

shadow_factor

Amount texture affects shadow

Type float in [-inf, inf], default 0.0

texture_coords

Type enum in ['GLOBAL', 'VIEW', 'OBJECT'], default 'GLOBAL'

use_map_color

Lets the texture affect the basic color of the lamp

Type boolean, default False

use_map_shadow

Lets the texture affect the shadow color of the lamp

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Lamp.texture_slots
- LampTextureSlots.add
- LampTextureSlots.create

1.4.281 LampTextureSlots(bpy_struct)

base class — bpy_struct

class bpy.types.**LampTextureSlots**(*bpy_struct*)

Collection of texture slots

classmethod add()

add

Returns The newly initialized mtex.

Return type LampTextureSlot

classmethod create(*index*)

create

Parameters **index** (*int in [0, inf]*) – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type LampTextureSlot

classmethod clear(*index*)

clear

Parameters **index** (*int in [0, inf]*) – Index, Slot index to clear.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Lamp.texture_slots

1.4.282 Lattice(ID)

base classes — bpy_struct, ID

class bpy.types.**Lattice**(*ID*)

Lattice datablock defining a grid for deforming other objects

animation_data

Animation data for this datablock

Type AnimData, (readonly)

interpolation_type_u

Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default 'KEY_LINEAR'

interpolation_type_v

Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default 'KEY_LINEAR'

interpolation_type_w

Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default 'KEY_LINEAR'

points

Points of the lattice

Type Collection of LatticePoint, (readonly)

points_u

Points in U direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

points_v
Points in V direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

points_w
Points in W direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

shape_keys

Type Key, (readonly)

use_outside
Only draw, and take into account, the outer vertices

Type boolean, default False

vertex_group
Vertex group to apply the influence of the lattice

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear

- ID.update_tag

References

- BlendData.lattices
- BlendDataLattices.new
- BlendDataLattices.remove

1.4.283 LatticeModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**LatticeModifier**(*Modifier*)

Lattice deformation modifier

object

Lattice object to deform with

Type Object

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

1.4.284 LatticePoint(bpy_struct)

base class — bpy_struct

class bpy.types.**LatticePoint**(*bpy_struct*)

Point in the lattice grid

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

co_deform

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

groups

Weights for the vertex groups this point is member of

Type Collection of VertexGroupElement, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Lattice.points

1.4.285 Library(ID)

base classes — bpy_struct, ID

class bpy.types.**Library**(*ID*)

External .blend file from which data is linked

filepath

Path to the library .blend file

Type string, default ""

parent

Type Library, (readonly)

users_id

ID datablocks which use this library (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.libraries
- ID.library
- Library.parent

1.4.286 LimitDistanceConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LimitDistanceConstraint**(*Constraint*)

Limits the distance from target object

distance

Radius of limiting sphere

Type float in [0, 100], default 0.0

limit_mode

Distances in relation to sphere of influence to allow

Type enum in ['LIMITDIST_INSIDE', 'LIMITDIST_OUTSIDE', 'LIMITDIST_ONSURFACE'], default 'LIMITDIST_INSIDE'

subtarget

Type string, default ""

target

Target Object

Type Object

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.287 LimitLocationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LimitLocationConstraint**(*Constraint*)

Limits the location of the constrained object

max_x

Highest X value to allow

Type float in [-1000, 1000], default 0.0

max_y

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

max_z

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

min_x

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

min_y

Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

min_z

Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

use_max_x

Use the maximum X value

Type boolean, default False

use_max_y

Use the maximum Y value

Type boolean, default False

use_max_z

Use the maximum Z value

Type boolean, default False

use_min_x
Use the minimum X value

Type boolean, default False

use_min_y
Use the minimum Y value

Type boolean, default False

use_min_z
Use the minimum Z value

Type boolean, default False

use_transform_limit
Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.288 LimitRotationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LimitRotationConstraint**(*Constraint*)

Limits the rotation of the constrained object

max_x

Highest X value to allow

Type float in [-1000, 1000], default 0.0

max_y

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

max_z

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

min_x

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

min_y

Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

min_z

Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

use_limit_x

Use the minimum X value

Type boolean, default False

use_limit_y

Use the minimum Y value

Type boolean, default False

use_limit_z

Use the minimum Z value

Type boolean, default False

use_transform_limit

Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute

- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.289 LimitScaleConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LimitScaleConstraint**(*Constraint*)

Limits the scaling of the constrained object

max_x

Highest X value to allow

Type float in [-1000, 1000], default 0.0

max_y

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

max_z

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

min_x

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

min_y
Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

min_z
Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

use_max_x
Use the maximum X value

Type boolean, default False

use_max_y
Use the maximum Y value

Type boolean, default False

use_max_z
Use the maximum Z value

Type boolean, default False

use_min_x
Use the minimum X value

Type boolean, default False

use_min_y
Use the minimum Y value

Type boolean, default False

use_min_z
Use the minimum Z value

Type boolean, default False

use_transform_limit
Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.290 LockedTrackConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LockedTrackConstraint**(*Constraint*)

Points toward the target along the track axis, while locking the other axis

lock_axis

Axis that points upward

Type enum in ['LOCK_X', 'LOCK_Y', 'LOCK_Z'], default 'LOCK_X'

subtarget

Type string, default ""

target

Target Object

Type Object

track_axis

Axis that points to the target object

Type enum in ['TRACK_X', 'TRACK_Y', 'TRACK_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'TRACK_X'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location

- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.291 Macro(bpy_struct)

base class — bpy_struct

class bpy.types.**Macro**(*bpy_struct*)

Storage of a macro operator being executed, or registered after execution

bl_description

Type string, default “”

bl_idname

Type string, default “”

bl_label

Type string, default “”

bl_options

Options for this operator type

Type enum set in {‘REGISTER’, ‘UNDO’, ‘BLOCKING’, ‘MACRO’, ‘GRAB_POINTER’, ‘PRESET’}, default {‘REGISTER’}

name

Type string, default “”, (readonly)

properties

Type OperatorProperties, (readonly, never None)

report (*type*, *message*)
report

Parameters

- **type** (*enum set in {'DEBUG', 'INFO', 'OPERATOR', 'WARNING', 'ERROR', 'ERROR_INVALID_INPUT', 'ERROR_INVALID_CONTEXT', 'ERROR_OUT_OF_MEMORY'}*) – Type
- **message** (*string*) – Report Message

classmethod poll (*context*)
Test if the operator can be called or not.

Return type boolean

draw (*context*)
Draw function for the operator.

define (*opname*)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.292 MagicTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**MagicTexture** (*Texture*)
Procedural noise texture

noise_depth
Sets the depth of the cloud calculation

Type int in [0, 30], default 0

turbulence
Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.293 MaintainVolumeConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**MaintainVolumeConstraint**(*Constraint*)

Maintains a constant volume along a single scaling axis

free_axis

The free scaling axis of the object

Type enum in ['SAMEVOL_X', 'SAMEVOL_Y', 'SAMEVOL_Z'], default 'SAMEVOL_X'

volume

Volume of the bone at rest

Type float in [0.001, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.294 MarbleTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**MarbleTexture** (*Texture*)

Procedural noise texture

marble_type

Type enum in ['SOFT', 'SHARP', 'SHARPER'], default 'SOFT'

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_depth

Sets the depth of the cloud calculation

Type int in [0, 30], default 0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

noisebasis_2

Type enum in ['SIN', 'SAW', 'TRI'], default 'SIN'

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name

- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.295 MaskModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**MaskModifier**(*Modifier*)

Mask modifier to hide parts of the mesh

armature
Armature to use as source of bones to mask

Type Object

invert_vertex_group
Use vertices that are not part of region defined

Type boolean, default False

mode

Type enum in ['VERTEX_GROUP', 'ARMATURE'], default 'VERTEX_GROUP'

vertex_group
Vertex group name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.296 Material(ID)

base classes — bpy_struct, ID

class bpy.types.**Material**(*ID*)

Material datablock to defined the appearance of geometric objects for rendering

active_node_material

Active node material

Type Material

active_texture

Active texture slot being displayed

Type Texture

active_texture_index

Index of active texture slot

Type int in [0, 17], default 0

alpha

Alpha transparency of the material

Type float in [0, 1], default 0.0

ambient

Amount of global ambient color the material receives

Type float in [0, 1], default 0.0

animation_data

Animation data for this datablock

Type AnimData, (readonly)

darkness

Minnaert darkness

Type float in [0, 2], default 0.0

diffuse_color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

diffuse_fresnel

Power of Fresnel

Type float in [0, 5], default 0.0

diffuse_fresnel_factor

Blending factor of Fresnel

Type float in [0, 5], default 0.0

diffuse_intensity

Amount of diffuse reflection

Type float in [0, 1], default 0.0

diffuse_ramp

Color ramp used to affect diffuse shading

Type ColorRamp, (readonly)

diffuse_ramp_blend

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

diffuse_ramp_factor
Blending factor (also uses alpha in Colorband)

Type float in [0, 1], default 0.0

diffuse_ramp_input

Type enum in ['SHADER', 'ENERGY', 'NORMAL', 'RESULT'], default 'SHADER'

diffuse_shader

Type enum in ['LAMBERT', 'OREN_NAYAR', 'TOON', 'MINNAERT', 'FRESNEL'], default 'LAMBERT'

diffuse_toon_size
Size of diffuse toon area

Type float in [0, 3.14], default 0.0

diffuse_toon_smooth
Smoothness of diffuse toon area

Type float in [0, 1], default 0.0

emit
Amount of light to emit

Type float in [0, inf], default 0.0

halo
Halo settings for the material

Type `MaterialHalo`, (readonly, never None)

invert_z
Renders material's faces with an inverted Z buffer (scanline only)

Type boolean, default False

light_group
Limit lighting to lamps in this Group

Type `Group`

mirror_color
Mirror color of the material

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

node_tree
Node tree for node based materials

Type `NodeTree`, (readonly)

offset_z
Gives faces an artificial offset in the Z buffer for Z transparency

Type float in [-inf, inf], default 0.0

physics
Game physics settings

Type `MaterialPhysics`, (readonly, never None)

preview_render_type
Type of preview render

Type enum in ['FLAT', 'SPHERE', 'CUBE', 'MONKEY', 'HAIR', 'SPHERE_A'], default 'FLAT'

raytrace_mirror
Raytraced reflection settings for the material

Type MaterialRaytraceMirror, (readonly, never None)

raytrace_transparency
Raytraced transparency settings for the material

Type MaterialRaytraceTransparency, (readonly, never None)

roughness
Oren-Nayar Roughness

Type float in [0, 3.14], default 0.0

shadow_buffer_bias
Factor to multiply shadow buffer bias with (0 is ignore.)

Type float in [0, 10], default 0.0

shadow_cast_alpha
Shadow casting alpha, in use for Irregular and Deep shadow buffer

Type float in [0.001, 1], default 0.0

shadow_only_type
How to draw shadows

Type enum in ['SHADOW_ONLY_OLD', 'SHADOW_ONLY', 'SHADOW_ONLY_SHADED'], default 'SHADOW_ONLY_OLD'

shadow_ray_bias
Shadow raytracing bias to prevent terminator problems on shadow boundary

Type float in [0, 0.25], default 0.0

specular_alpha
Alpha transparency for specular areas

Type float in [0, 1], default 0.0

specular_color
Specular color of the material

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

specular_hardness

Type int in [1, 511], default 0

specular_intensity

Type float in [0, 1], default 0.0

specular_ior

Type float in [1, 10], default 0.0

specular_ramp
Color ramp used to affect specular shading

Type ColorRamp, (readonly)

specular_ramp_blend

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

specular_ramp_factor
Blending factor (also uses alpha in Colorband)

Type float in [0, 1], default 0.0

specular_ramp_input

Type enum in ['SHADER', 'ENERGY', 'NORMAL', 'RESULT'], default 'SHADER'

specular_shader

Type enum in ['COOKTORR', 'PHONG', 'BLINN', 'TOON', 'WARDISO'], default 'COOKTORR'

specular_slope
The standard deviation of surface slope

Type float in [0, 0.4], default 0.0

specular_toon_size
Size of specular toon area

Type float in [0, 1.53], default 0.0

specular_toon_smooth
Smoothness of specular toon area

Type float in [0, 1], default 0.0

strand
Strand settings for the material

Type `MaterialStrand`, (readonly, never None)

subsurface_scattering
Subsurface scattering settings for the material

Type `MaterialSubsurfaceScattering`, (readonly, never None)

texture_slots
Texture slots defining the mapping and influence of textures

Type `MaterialTextureSlots` collection of `MaterialTextureSlot`, (readonly)

translucency
Amount of diffuse shading on the back side

Type float in [0, 1], default 0.0

transparency_method
Method to use for rendering transparency

Type enum in ['MASK', 'Z_TRANSPARENCY', 'RAYTRACE'], default 'MASK'

type
Material type defining how the object is rendered

Type enum in ['SURFACE', 'WIRE', 'VOLUME', 'HALO'], default 'SURFACE'

use_cast_approximate
Allow this material to cast shadows when using approximate ambient occlusion.

Type boolean, default False

use_cast_buffer_shadows
Allow this material to cast shadows from shadow buffer lamps

Type boolean, default False

use_cast_shadows_only
Makes objects with this material appear invisible, only casting shadows (not rendered)

Type boolean, default False

use_cubic
Use cubic interpolation for diffuse values, for smoother transitions

Type boolean, default False

use_diffuse_ramp
Toggle diffuse ramp operations

Type boolean, default False

use_face_texture
Replaces the object's base color with color from face assigned image textures

Type boolean, default False

use_face_texture_alpha
Replaces the object's base alpha value with alpha from face assigned image textures

Type boolean, default False

use_full_oversampling
Force this material to render full shading/textures for all anti-aliasing samples

Type boolean, default False

use_light_group_exclusive
Material uses the light group exclusively - these lamps are excluded from other scene lighting

Type boolean, default False

use_mist
Use mist with this material (in world settings)

Type boolean, default False

use_nodes
Use shader nodes to render the material

Type boolean, default False

use_object_color
Modulate the result with a per-object color

Type boolean, default False

use_only_shadow
Renders shadows as the material's alpha value, making materials transparent except for shadowed areas

Type boolean, default False

use_ray_shadow_bias
Prevents raytraced shadow errors on surfaces with smooth shaded normals (terminator problem)

Type boolean, default False

use_raytrace
Include this material and geometry that uses it in ray tracing calculations

Type boolean, default False

use_shadeless
Makes this material insensitive to light or shadow

Type boolean, default False

use_shadows
Allows this material to receive shadows

Type boolean, default False

use_sky
Renders this material with zero alpha, with sky background in place (scanline only)

Type boolean, default False

use_specular_ramp
Toggle specular ramp operations

Type boolean, default False

use_tangent_shading
Use the material's tangent vector instead of the normal for shading - for anisotropic shading effects

Type boolean, default False

use_textures
Enable/Disable each texture

Type boolean array of 18 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

use_transparency
Render material as transparent

Type boolean, default False

use_transparent_shadows
Allow this object to receive transparent shadows casted through other objects

Type boolean, default False

use_vertex_color_light
Add vertex colors as additional lighting

Type boolean, default False

use_vertex_color_paint
Replaces object base color with vertex colors (multiplies with 'texture face' face assigned textures)

Type boolean, default False

volume
Volume settings for the material

Type `MaterialVolume`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`

- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.materials
- BlendDataMaterials.new
- BlendDataMaterials.remove
- Curve.materials
- IDMaterials.append
- IDMaterials.pop
- Material.active_node_material
- MaterialSlot.material
- Mesh.materials
- MetaBall.materials
- Object.active_material
- RenderLayer.material_override
- SceneRenderLayer.material_override
- ShaderNodeExtendedMaterial.material
- ShaderNodeMaterial.material
- TouchSensor.material

1.4.297 MaterialHalo(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialHalo**(*bpy_struct*)

Halo particle effect settings for a Material datablock

add
Sets the strength of the add effect

Type float in [0, 1], default 0.0

flare_boost
Gives the flare extra strength

Type float in [0.1, 10], default 0.0

flare_seed
Specifies an offset in the flare seed table

Type int in [0, 255], default 0

flare_size
Sets the factor by which the flare is larger than the halo

Type float in [0.1, 25], default 0.0

flare_subflare_count
Sets the number of subflares

Type int in [1, 32], default 0

flare_subflare_size
Sets the dimension of the subflares, dots and circles

Type float in [0.1, 25], default 0.0

hardness
Sets the hardness of the halo

Type int in [0, 127], default 0

line_count
Sets the number of star shaped lines rendered over the halo

Type int in [0, 250], default 0

ring_count
Sets the number of rings rendered over the halo

Type int in [0, 24], default 0

seed
Randomizes ring dimension and line location

Type int in [0, 255], default 0

size
Sets the dimension of the halo

Type float in [0, 100], default 0.0

star_tip_count
Sets the number of points on the star shaped halo

Type int in [3, 50], default 0

use_extreme_alpha
Uses extreme alpha

Type boolean, default False

use_flare_mode
Renders halo as a lensflare

Type boolean, default False

use_lines
Renders star shaped lines over halo

Type boolean, default False

use_ring
Renders rings over halo

Type boolean, default False

use_shaded
Lets halo receive light and shadows from external objects

Type boolean, default False

use_soft
Softens the edges of halos at intersections with other geometry

Type boolean, default False

use_star
Renders halo as a star

Type boolean, default False

use_texture
Gives halo a texture

Type boolean, default False

use_vertex_normal
Uses the vertex normal to specify the dimension of the halo

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.halo

1.4.298 MaterialPhysics(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialPhysics**(*bpy_struct*)

Physics settings for a Material datablock

elasticity

Elasticity of collisions

Type float in [0, 1], default 0.0

fh_damping

Damping of the spring force, when inside the physics distance area

Type float in [0, 1], default 0.0

fh_distance

Distance of the physics area

Type float in [0, 20], default 0.0

fh_force

Upward spring force, when inside the physics distance area

Type float in [0, 1], default 0.0

friction

Coulomb friction coefficient, when inside the physics distance area

Type float in [0, 100], default 0.0

use_fh_normal

Align dynamic game objects along the surface normal, when inside the physics distance area

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.physics

1.4.299 MaterialRaytraceMirror(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialRaytraceMirror**(*bpy_struct*)

Raytraced reflection settings for a Material datablock

depth

Maximum allowed number of light inter-reflections

Type int in [0, 32767], default 0

distance

Maximum distance of reflected rays. Reflections further than this range fade to sky color or material color

Type float in [0, 10000], default 0.0

fade_to

The color that rays with no intersection within the Max Distance take. Material color can be best for indoor scenes, sky color for outdoor

Type enum in ['FADE_TO_SKY', 'FADE_TO_MATERIAL'], default 'FADE_TO_SKY'

fresnel

Power of Fresnel for mirror reflection

Type float in [0, 5], default 0.0

fresnel_factor

Blending factor for Fresnel

Type float in [0, 5], default 0.0

gloss_anisotropic

The shape of the reflection, from 0.0 (circular) to 1.0 (fully stretched along the tangent

Type float in [0, 1], default 0.0

gloss_factor

The shininess of the reflection. Values < 1.0 give diffuse, blurry reflections

Type float in [0, 1], default 0.0

gloss_samples

Number of cone samples averaged for blurry reflections

Type int in [0, 1024], default 0

gloss_threshold
Threshold for adaptive sampling. If a sample contributes less than this amount (as a percentage), sampling is stopped

Type float in [0, 1], default 0.0

reflect_factor
Sets the amount mirror reflection for raytrace

Type float in [0, 1], default 0.0

use
Enable raytraced reflections

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.raytrace_mirror

1.4.300 MaterialRaytraceTransparency(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialRaytraceTransparency**(*bpy_struct*)
Raytraced refraction settings for a Material datablock

depth
Maximum allowed number of light inter-refractions

Type int in [0, 32767], default 0

depth_max
Maximum depth for light to travel through the transparent material before becoming fully filtered (0.0 is disabled)

Type float in [0, 100], default 0.0

falloff
Falloff power for transmissivity filter effect (1.0 is linear)

Type float in [0.1, 10], default 0.0

filter
Amount to blend in the material's diffuse color in raytraced transparency (simulating absorption)

Type float in [0, 1], default 0.0

fresnel
Power of Fresnel for transparency (Ray or ZTransp)

Type float in [0, 5], default 0.0

fresnel_factor
Blending factor for Fresnel

Type float in [1, 5], default 0.0

gloss_factor
The clarity of the refraction. Values < 1.0 give diffuse, blurry refractions

Type float in [0, 1], default 0.0

gloss_samples
Number of cone samples averaged for blurry refractions

Type int in [0, 1024], default 0

gloss_threshold
Threshold for adaptive sampling. If a sample contributes less than this amount (as a percentage), sampling is stopped

Type float in [0, 1], default 0.0

ior
Sets angular index of refraction for raytraced refraction

Type float in [0.25, 4], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.raytrace_transparency

1.4.301 MaterialSlot(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialSlot**(*bpy_struct*)

Material slot in an object

link

Link material to object or the object's data

Type enum in ['OBJECT', 'DATA'], default 'DATA'

material

Material datablock used by this material slot

Type Material

name

Material slot name

Type string, default "", (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.material_slots

1.4.302 MaterialStrand(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialStrand**(*bpy_struct*)

Strand settings for a Material datablock

blend_distance

Worldspace distance over which to blend in the surface normal

Type float in [0, 10], default 0.0

root_size

Start size of strands in pixels or Blender units

Type float in [0, inf], default 0.0

shape

Positive values make strands rounder, negative makes strands spiky

Type float in [-0.9, 0.9], default 0.0

size_min

Minimum size of strands in pixels

Type float in [0.001, 10], default 0.0

tip_size

End size of strands in pixels or Blender units

Type float in [0, inf], default 0.0

use_blender_units

Use Blender units for widths instead of pixels

Type boolean, default False

use_surface_diffuse

Make diffuse shading more similar to shading the surface

Type boolean, default False, (readonly)

use_tangent_shading

Uses direction of strands as normal for tangent-shading

Type boolean, default False

uv_layer

Name of UV layer to override

Type string, default “”

width_fade

Transparency along the width of the strand

Type float in [0, 2], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.strand

1.4.303 MaterialSubsurfaceScattering(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialSubsurfaceScattering**(*bpy_struct*)

Diffuse subsurface scattering settings for a Material datablock

back

Back scattering weight

Type float in [0, 10], default 0.0

color

Scattering color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

color_factor

Blend factor for SSS colors

Type float in [0, 1], default 0.0

error_threshold

Error tolerance (low values are slower and higher quality)

Type float in [-inf, inf], default 0.0

front
Front scattering weight

Type float in [0, 2], default 0.0

ior
Index of refraction (higher values are denser)

Type float in [-inf, inf], default 0.0

radius
Mean red/green/blue scattering path length

Type float array of 3 items in [0.001, inf], default (0.0, 0.0, 0.0)

scale
Object scale factor

Type float in [-inf, inf], default 0.0

texture_factor
Texture scatting blend factor

Type float in [0, 1], default 0.0

use
Enable diffuse subsurface scatting effects in a material

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.subsurface_scattering

1.4.304 MaterialTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.**MaterialTextureSlot**(*TextureSlot*)

Texture slot for textures in a Material datablock

alpha_factor

Amount texture affects alpha

Type float in [-inf, inf], default 0.0

ambient_factor

Amount texture affects ambient

Type float in [-inf, inf], default 0.0

bump_method

Method to use for bump mapping

Type enum in ['BUMP_ORIGINAL', 'BUMP_COMPATIBLE', 'BUMP_DEFAULT', 'BUMP_BEST_QUALITY'], default 'BUMP_ORIGINAL'

bump_objectspace

Space to apply bump mapping in

Type enum in ['BUMP_VIEWSPACE', 'BUMP_OBJECTSPACE', 'BUMP_TEXTURESPACE'], default 'BUMP_VIEWSPACE'

density_factor

Amount texture affects density

Type float in [-inf, inf], default 0.0

diffuse_color_factor

Amount texture affects diffuse color

Type float in [-inf, inf], default 0.0

diffuse_factor

Amount texture affects diffuse reflectivity

Type float in [-inf, inf], default 0.0

displacement_factor

Amount texture displaces the surface

Type float in [-inf, inf], default 0.0

emission_color_factor

Amount texture affects emission color

Type float in [-inf, inf], default 0.0

emission_factor

Amount texture affects emission

Type float in [-inf, inf], default 0.0

emit_factor

Amount texture affects emission

Type float in [-inf, inf], default 0.0

hardness_factor

Amount texture affects hardness

Type float in [-inf, inf], default 0.0

mapping

Type enum in ['FLAT', 'CUBE', 'TUBE', 'SPHERE'], default 'FLAT'

mapping_x

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_y

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_z

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mirror_factor

Amount texture affects mirror color

Type float in [-inf, inf], default 0.0

normal_factor

Amount texture affects normal values

Type float in [-inf, inf], default 0.0

normal_map_space

Sets space of normal map image

Type enum in ['CAMERA', 'WORLD', 'OBJECT', 'TANGENT'], default 'CAMERA'

object

Object to use for mapping with Object texture coordinates

Type `Object`

raymir_factor

Amount texture affects ray mirror

Type float in [-inf, inf], default 0.0

reflection_color_factor

Amount texture affects color of out-scattered light

Type float in [-inf, inf], default 0.0

reflection_factor

Amount texture affects brightness of out-scattered light

Type float in [-inf, inf], default 0.0

scattering_factor

Amount texture affects scattering

Type float in [-inf, inf], default 0.0

specular_color_factor

Amount texture affects specular color

Type float in [-inf, inf], default 0.0

specular_factor

Amount texture affects specular reflectivity

Type float in [-inf, inf], default 0.0

texture_coords

Type enum in ['GLOBAL', 'OBJECT', 'UV', 'ORCO', 'STRAND', 'STICKY', 'WINDOW', 'NORMAL', 'REFLECTION', 'STRESS', 'TANGENT'], default 'GLOBAL'

translucency_factor

Amount texture affects translucency

Type float in [-inf, inf], default 0.0

transmission_color_factor

Amount texture affects result color after light has been scattered/absorbed

Type float in [-inf, inf], default 0.0

use

Enable this material texture slot

Type boolean, default False

use_from_dupli

Dupli's instanced from verts, faces or particles, inherit texture coordinate from their parent

Type boolean, default False

use_from_original

Dupli's derive their object coordinates from the original objects transformation

Type boolean, default False

use_map_alpha

Causes the texture to affect the alpha value

Type boolean, default False

use_map_ambient

Causes the texture to affect the value of ambient

Type boolean, default False

use_map_color_diffuse

Causes the texture to affect basic color of the material

Type boolean, default False

use_map_color_emission

Causes the texture to affect the color of emission

Type boolean, default False

use_map_color_reflection

Causes the texture to affect the color of scattered light

Type boolean, default False

use_map_color_spec

Causes the texture to affect the specularity color

Type boolean, default False

use_map_color_transmission

Causes the texture to affect the result color after other light has been scattered/absorbed

Type boolean, default False

use_map_density

Causes the texture to affect the volume's density

Type boolean, default False

use_map_diffuse
Causes the texture to affect the value of the materials diffuse reflectivity

Type boolean, default False

use_map_displacement
Let the texture displace the surface

Type boolean, default False

use_map_emission
Causes the texture to affect the volume's emission

Type boolean, default False

use_map_emit
Causes the texture to affect the emit value

Type boolean, default False

use_map_hardness
Causes the texture to affect the hardness value

Type boolean, default False

use_map_mirror
Causes the texture to affect the mirror color

Type boolean, default False

use_map_normal
Causes the texture to affect the rendered normal

Type boolean, default False

use_map_raymir
Causes the texture to affect the ray-mirror value

Type boolean, default False

use_map_reflect
Causes the texture to affect the reflected light's brightness

Type boolean, default False

use_map_scatter
Causes the texture to affect the volume's scattering

Type boolean, default False

use_map_specular
Causes the texture to affect the value of specular reflectivity

Type boolean, default False

use_map_translucency
Causes the texture to affect the translucency value

Type boolean, default False

use_map_warp
Let the texture warp texture coordinates of next channels

Type boolean, default False

uv_layer
UV layer to use for mapping with UV texture coordinates

Type string, default “”

warp_factor
Amount texture affects texture coordinates of next channels

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.texture_slots
- MaterialTextureSlots.add
- MaterialTextureSlots.create

1.4.305 MaterialTextureSlots(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialTextureSlots**(*bpy_struct*)

Collection of texture slots

classmethod add()

add

Returns The newly initialized mtex.

Return type MaterialTextureSlot

classmethod create(*index*)

create

Parameters **index** (*int in [0, inf]*) – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type MaterialTextureSlot

classmethod clear(*index*)

clear

Parameters **index** (*int in [0, inf]*) – Index, Slot index to clear.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.texture_slots

1.4.306 MaterialVolume(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialVolume** (*bpy_struct*)

Volume rendering settings for a Material datablock

asymmetry

Back scattering (-1.0) to Forward scattering (1.0) and the range in between

Type float in [-1, 1], default 0.0

cache_resolution

Resolution of the voxel grid, low resolutions are faster, high resolutions use more memory

Type int in [1, 1024], default 0

density

The base density of the volume

Type float in [0, 1], default 0.0

density_scale

Multiplier for the material's density

Type float in [0, inf], default 0.0

depth_threshold

Stop ray marching early if transmission drops below this luminance - higher values give speedups in dense volumes at the expense of accuracy

Type float in [0, 1], default 0.0

emission

Amount of light that gets emitted by the volume

Type float in [0, inf], default 0.0

emission_color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

light_method

Method of shading, attenuating, and scattering light through the volume

Type enum in ['SHADELESS', 'SHADOWED', 'SHADED', 'MULTIPLE_SCATTERING', 'SHADED_PLUS_MULTIPLE_SCATTERING'], default 'SHADELESS'

ms_diffusion

Diffusion factor, the strength of the blurring effect

Type float in [0, inf], default 0.0

ms_intensity

Multiplier for multiple scattered light energy

Type float in [0, inf], default 0.0

ms_spread

Proportional distance over which the light is diffused

Type float in [0, inf], default 0.0

reflection

Multiplier to make out-scattered light brighter or darker (non-physically correct)

Type float in [0, inf], default 0.0

reflection_color
Color of light scattered out of the volume (does not affect transmission)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scattering
Amount of light that gets scattered out by the volume - the more out-scattering, the shallower the light will penetrate

Type float in [0, inf], default 0.0

step_method
Method of calculating the steps through the volume

Type enum in ['RANDOMIZED', 'CONSTANT'], default 'RANDOMIZED'

step_size
Distance between subsequent volume depth samples

Type float in [0, inf], default 0.0

transmission_color
Result color of the volume, after other light has been scattered/absorbed

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_external_shadows
Receive shadows from sources outside the volume (temporary)

Type boolean, default False

use_light_cache
Pre-calculate the shading information into a voxel grid, speeds up shading at slightly less accuracy

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

References

- Material.volume

1.4.307 Menu(bpy_struct)

Basic Menu Example

This script is a simple menu, menus differ from panels in that they must reference from a header, panel or another menu.

Notice the 'CATEGORY_MT_name' Menu.bl_idname, this is a naming convention for menus.

Note: Menu subclasses must be registered before referencing them from blender.

```
import bpy


class BasicMenu(bpy.types.Menu):
    bl_idname = "OBJECT_MT_select_test"
    bl_label = "Select"

    def draw(self, context):
        layout = self.layout

        layout.operator("object.select_all", text="Select/Deselect All")
        layout.operator("object.select_inverse", text="Inverse")
        layout.operator("object.select_random", text="Random")


bpy.utils.register_class(BasicMenu)

# test call to display immediately.
bpy.ops.wm.call_menu(name="OBJECT_MT_select_test")
```

Submenus

This menu demonstrates some different functions.

```
import bpy


class SubMenu(bpy.types.Menu):
    bl_idname = "OBJECT_MT_select_submenu"
    bl_label = "Select"

    def draw(self, context):
        layout = self.layout

        layout.operator("object.select_all", text="Select/Deselect All")
        layout.operator("object.select_inverse", text="Inverse")
```

```
        layout.operator("object.select_random", text="Random")

        # access this operator as a submenu
        layout.operator_menu_enum("object.select_by_type", "type", text="Select All by Type...")

        layout.separator()

        # expand each operator option into this menu
        layout.operator_enum("object.lamp_add", "type")

        layout.separator()

        # use existing memu
        layout.menu("VIEW3D_MT_transform")


bpy.utils.register_class(SubMenu)

# test call to display immediately.
bpy.ops.wm.call_menu(name="OBJECT_MT_select_submenu")
```

Extending Menus

When creating menus for addons you can't reference menus in blenders default scripts.

Instead the addon can add menu items to existing menus.

The function menu_draw acts like Menu.draw

```
import bpy


def menu_draw(self, context):
    self.layout.operator("wm.save_homefile")

bpy.types.INFO_MT_file.append(menu_draw)
```

base class — `bpy_struct`

class `bpy.types.`**`Menu`**(*bpy_struct*)

Editor menu containing buttons

`bl_idname`

If this is set, the menu gets a custom ID, otherwise it takes the name of the class used to define the panel. For example, if the class name is "OBJECT_MT_hello", and bl_idname is not set by the script, then bl_idname = "OBJECT_MT_hello"

Type string, default ""

`bl_label`

The menu label

Type string, default ""

`layout`

Defines the structure of the menu in the UI.

Type `UILayout`, (readonly)

classmethod poll (*context*)
If this method returns a non-null output, then the menu can be drawn.

Return type boolean

draw (*context*)
Draw UI elements into the menu UI layout.

classmethod append (*draw_func*)
Append a draw function to this menu, takes the same arguments as the menus draw function.

draw_preset (*context*)
Define these on the subclass - preset_operator - preset_subdir

path_menu (*searchpaths*, *operator*, *props_default={}*)

classmethod prepend (*draw_func*)
Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove (*draw_func*)
Remove a draw function that has been added to this menu

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.308 Mesh(ID)

base classes — bpy_struct, ID

class bpy.types.**Mesh** (*ID*)
Mesh datablock defining geometric surfaces

animation_data
Animation data for this datablock

Type AnimData, (readonly)

auto_smooth_angle
Defines maximum angle between face normals that 'Auto Smooth' will operate on

Type int in [1, 80], default 0

edges
Edges of the mesh

Type MeshEdges collection of MeshEdge, (readonly)

faces
Faces of the mesh

Type MeshFaces collection of MeshFace, (readonly)

layers_float

Type Collection of MeshFloatPropertyLayer, (readonly)

layers_int

Type Collection of MeshIntPropertyLayer, (readonly)

layers_string

Type Collection of MeshStringPropertyLayer, (readonly)

materials

Type IDMaterials collection of Material, (readonly)

shape_keys

Type Key, (readonly)

show_all_edges
Displays all edges for wireframe in all view modes in the 3D view

Type boolean, default False

show_double_sided
Render/display the mesh with double or single sided lighting

Type boolean, default False

show_edge_bevel_weight
Displays weights created for the Bevel modifier

Type boolean, default False

show_edge_crease
Displays creases created for subsurf weighting

Type boolean, default False

show_edge_seams
Displays UV unwrapping seams

Type boolean, default False

show_edge_sharp
Displays sharp edges, used with the EdgeSplit modifier

Type boolean, default False

show_edges
Displays selected edges using highlights in the 3D view and UV editor

Type boolean, default False

show_extra_edge_length
Displays selected edge lengths, Using global values when set in the transform panel

Type boolean, default False

show_extra_face_angle
Displays the angles in the selected edges in degrees, Using global values when set in the transform panel

Type boolean, default False

show_extra_face_area
Displays the area of selected faces, Using global values when set in the transform panel

Type boolean, default False

show_faces
Displays all faces as shades in the 3D view and UV editor

Type boolean, default False

show_normal_face
Displays face normals as lines

Type boolean, default False

show_normal_vertex
Displays vertex normals as lines

Type boolean, default False

sticky
Sticky texture coordinates

Type Collection of `MeshSticky`, (readonly)

texco_mesh
Derive texture coordinates from another mesh

Type `Mesh`

texspace_location
Texture space location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size
Texture space size

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texture_mesh
Use another mesh for texture indices (vertex indices must be aligned)

Type `Mesh`

total_edge_sel
Selected edge count in editmode

Type int in [0, inf], default 0, (readonly)

total_face_sel
Selected face count in editmode

Type int in [0, inf], default 0, (readonly)

total_vert_sel
Selected vertex count in editmode

Type int in [0, inf], default 0, (readonly)

use_auto_smooth
Treats all set-smoothed faces with angles less than the specified angle as 'smooth' during render

Type boolean, default False

use_auto_texspace
Adjusts active object's texture space automatically when transforming object

Type boolean, default False

use_mirror_topology
Use topology based mirroring

Type boolean, default False

use_mirror_x
X Axis mirror editing

Type boolean, default False

use_paint_mask
Face selection masking for painting

Type boolean, default False

uv_texture_clone
UV texture to be used as cloning source

Type MeshTextureFaceLayer

uv_texture_clone_index
Clone UV texture index

Type int in [0, inf], default 0

uv_texture_stencil
UV texture to mask the painted area

Type MeshTextureFaceLayer

uv_texture_stencil_index
Mask UV texture index

Type int in [0, inf], default 0

uv_textures

Type UVTextures collection of MeshTextureFaceLayer, (readonly)

vertex_colors

Type VertexColors collection of MeshColorLayer, (readonly)

vertices
Vertices of the mesh

Type MeshVertices collection of MeshVertex, (readonly)

edge_face_count
(readonly)

edge_face_count_dict
(readonly)

edge_keys
(readonly)

transform(*matrix*)
Transform mesh vertices by a matrix.

Parameters **matrix** (*float array of 16 items in [-inf, inf]*) – Matrix.

calc_normals()
Calculate vertex normals.

update(*calc_edges=False*)
update

Parameters **calc_edges** (*boolean, (optional)*) – Calculate Edges, Force recalculation of edges.

validate(*verbose=False*)
validate geometry, return True when the mesh has had invalid geometry corrected/removed.

Parameters **verbose** (*boolean, (optional)*) – Verbose, Output information about the errors found

Returns Result

Return type boolean

edge_loops_from_edges(*edges=None*)
Edge loops defined by edges

Takes me.edges or a list of edges and returns the edge loops

return a list of vertex indices. [[1, 6, 7, 2], ...]

closed loops have matching start and end values.

edge_loops_from_faces(*faces=None*, *seams=()*)
Edge loops defined by faces

Takes me.faces or a list of faces and returns the edge loops These edge loops are the edges that sit between quads, so they dont touch 1 quad, note: not connected will make 2 edge loops, both only containing 2 edges.

return a list of edge key lists [[(0,1), (4, 8), (3,8)], ...]

return a list of edge vertex index lists

from_pydata(*vertices*, *edges*, *faces*)
Make a mesh from a list of verts/edges/faces Until we have a nicer way to make geometry, use this.

Parameters

- **vertices** (*iterable object*) – float triplets each representing (X, Y, Z) eg: [(0.0, 1.0, 0.5), ...].
- **edges** (*iterable object*) – int pairs, each pair contains two indices to the *vertices* argument. eg: [(1, 2), ...]
- **faces** (*iterable object*) – iterator of faces, each faces contains three or four indices to the *vertices* argument. eg: [(5, 6, 8, 9), (1, 2, 3), ...]

Inherited Properties

- bpy_struct.id_data

- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.meshes
- BlendDataMeshes.new
- BlendDataMeshes.remove
- EditObjectActuator.mesh
- Mesh.texco_mesh
- Mesh.texture_mesh
- Object.to_mesh

1.4.309 MeshColor(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshColor**(*bpy_struct*)

Vertex colors for a face in a Mesh

color1

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color2

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color3

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color4

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshColorLayer.data

1.4.310 MeshColorLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshColorLayer**(*bpy_struct*)

Layer of vertex colors in a Mesh datablock

active

Sets the layer as active for display and editing

Type boolean, default False

active_render

Sets the layer as active for rendering

Type boolean, default False

data

Type Collection of MeshColor, (readonly)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertex_colors
- VertexColors.active
- VertexColors.new

1.4.311 MeshDeformModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**MeshDeformModifier**(*Modifier*)

Mesh deformation modifier to deform with other meshes

invert_vertex_group

Invert vertex group influence

Type boolean, default False

is_bound

Whether geometry has been bound to control cage

Type boolean, default False, (readonly)

object

Mesh object to deform with

Type Object

precision
The grid size for binding

Type int in [2, 10], default 0

use_dynamic_bind
Recompute binding dynamically on top of other deformers (slower and more memory consuming.)

Type boolean, default False

vertex_group
Vertex group name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.312 MeshEdge(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshEdge**(*bpy_struct*)
Edge in a Mesh datablock

bevel_weight
Weight used by the Bevel modifier

Type float in [-inf, inf], default 0.0

crease
Weight used by the Subsurf modifier for creasing

Type float in [-inf, inf], default 0.0

hide

Type boolean, default False

index
Index number of the vertex

Type int in [0, inf], default 0, (readonly)

is_fgon
Fgon edge

Type boolean, default False

is_loose
Loose edge

Type boolean, default False

select

Type boolean, default False

use_edge_sharp
Sharp edge for the EdgeSplit modifier

Type boolean, default False

use_seam
Seam edge for UV unwrapping

Type boolean, default False

vertices
Vertex indices

Type int array of 2 items in [0, inf], default (0, 0)

key
(readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.edges

1.4.313 MeshEdges(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshEdges**(*bpy_struct*)

Collection of mesh edges

add(*count=0*)

add

Parameters **count** (*int in [0, inf], (optional)*) – Count, Number of vertices to add.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.edges

1.4.314 MeshFace(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshFace**(*bpy_struct*)

Face in a Mesh datablock

area

read only area of the face

Type float in [0, inf], default 0.0, (readonly)

hide

Type boolean, default False

index

Index number of the vertex

Type int in [0, inf], default 0, (readonly)

material_index

Type int in [0, 32767], default 0

normal

local space unit length normal vector for this face

Type float array of 3 items in [-1, 1], default (0.0, 0.0, 0.0), (readonly)

select

Type boolean, default False

use_smooth

Type boolean, default False

vertices

Vertex indices

Type int array of 4 items in [0, inf], default (0, 0, 0, 0)

vertices_raw

Fixed size vertex indices array

Type int array of 4 items in [0, inf], default (0, 0, 0, 0)

center

The midpoint of the face. (readonly)

edge_keys

(readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.faces

1.4.315 MeshFaces(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshFaces**(*bpy_struct*)

Collection of mesh faces

active

The active face for this mesh

Type int in [-inf, inf], default 0

active_tface

Active Texture Face

Type MeshTextureFace, (readonly)

add(*count=0*)

add

Parameters **count** (*int in [0, inf], (optional)*) – Count, Number of vertices to add.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.faces

1.4.316 MeshFloatProperty(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshFloatProperty**(*bpy_struct*)

User defined floating point number value in a float properties layer

value

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshFloatPropertyLayer.data

1.4.317 MeshFloatPropertyLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshFloatPropertyLayer**(*bpy_struct*)

User defined layer of floating pointer number values

data

Type Collection of MeshFloatProperty, (readonly)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.layers_float

1.4.318 MeshIntProperty(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshIntProperty**(*bpy_struct*)

User defined integer number value in an integer properties layer

value

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshIntPropertyLayer.data

1.4.319 MeshIntPropertyLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshIntPropertyLayer**(*bpy_struct*)

User defined layer of integer number values

data

Type Collection of MeshIntProperty, (readonly)

name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.layers_int

1.4.320 MeshSticky(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshSticky**(*bpy_struct*)

Stricky texture coordinate

co

Sticky texture coordinate location

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.sticky

1.4.321 MeshStringProperty(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshStringProperty**(*bpy_struct*)
User defined string text value in a string properties layer

value

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshStringPropertyLayer.data

1.4.322 MeshStringPropertyLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshStringPropertyLayer**(*bpy_struct*)
User defined layer of string text values

data

Type Collection of MeshStringProperty, (readonly)

name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.layers_string

1.4.323 MeshTextureFace(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshTextureFace**(*bpy_struct*)

UV mapping, texturing and game engine data for a face

blend_type

Transparency blending mode

Type enum in [’OPAQUE’, ‘ADD’, ‘ALPHA’, ‘CLIPALPHA’], default ‘OPAQUE’

hide

Make face invisible

Type boolean, default False

image

Type Image

pin_uv

Type boolean array of 4 items, default (False, False, False, False)

select_uv

Type boolean array of 4 items, default (False, False, False, False)

use_alpha_sort
Enable sorting of faces for correct alpha drawing (slow, use Clip Alpha instead when possible)

Type boolean, default False

use_billboard
Billboard with Z-axis constraint

Type boolean, default False

use_bitmap_text
Enable bitmap text on face

Type boolean, default False

use_blend_shared
Blend vertex colors across face when vertices are shared

Type boolean, default False

use_collision
Use face for collision and ray-sensor detection

Type boolean, default False

use_halo
Screen aligned billboard

Type boolean, default False

use_image
Render face with texture

Type boolean, default False

use_light
Use light for face

Type boolean, default False

use_object_color
Use ObColor instead of vertex colors

Type boolean, default False

use_shadow_cast
Face is used for shadow

Type boolean, default False

use_twoside
Render face two-sided

Type boolean, default False

uv

Type float array of 8 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

uv1

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv2

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv3

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv4

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv_raw
Fixed size UV coordinates array

Type float array of 8 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshFaces.active_tface
- MeshTextureFaceLayer.data

1.4.324 MeshTextureFaceLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshTextureFaceLayer**(*bpy_struct*)
Layer of texture faces in a Mesh datablock

active
Sets the layer as active for display and editing

Type boolean, default False

active_clone
Sets the layer as active for cloning

Type boolean, default False

active_render
Sets the layer as active for rendering

Type boolean, default False

data

Type Collection of MeshTextureFace, (readonly)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.uv_texture_clone
- Mesh.uv_texture_stencil
- Mesh.uv_textures
- UVTextures.active
- UVTextures.new

1.4.325 MeshVertex(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshVertex**(*bpy_struct*)

Vertex in a Mesh datablock

bevel_weight

Weight used by the Bevel modifier 'Only Vertices' option

Type float in [-inf, inf], default 0.0

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

groups

Weights for the vertex groups this vertex is member of

Type Collection of VertexGroupElement, (readonly)

hide

Type boolean, default False

index

Index number of the vertex

Type int in [0, inf], default 0, (readonly)

normal

Vertex Normal

Type float array of 3 items in [-1, 1], default (0.0, 0.0, 0.0)

select

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertices

1.4.326 MeshVertices(bpy_struct)

base class — bpy_struct

class bpy.types.**MeshVertices**(*bpy_struct*)
Collection of mesh vertices

add(*count=0*)
add

Parameters **count** (*int in [0, inf], (optional)*) – Count, Number of vertices to add.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertices

1.4.327 MessageActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**MessageActuator**(*Actuator*)
Actuator to ..

body_message
Optional message body Text

Type string, default “”

body_property
The message body will be set by the Property Value

Type string, default “”

body_type
Toggle message type: either Text or a PropertyName

Type enum in [’TEXT’, ‘PROPERTY’], default ‘TEXT’

subject
Optional message subject. This is what can be filtered on

Type string, default “”

to_property
Optional send message to objects with this name only, or empty to broadcast

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.328 MessageSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**MessageSensor**(*Sensor*)
Sensor to detect incoming messages

subject
Optional subject filter: only accept messages with this subject, or empty for all

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.329 MetaBall(ID)

base classes — bpy_struct, ID

class bpy.types.**MetaBall**(*ID*)
Metaball datablock to defined blobby surfaces

animation_data
Animation data for this datablock

Type AnimData, (readonly)

elements
Meta elements

Type MetaBallElements collection of MetaElement, (readonly)

materials

Type IDMaterials collection of Material, (readonly)

render_resolution
Polygonization resolution in rendering

Type float in [0.05, 1], default 0.0

resolution
Polygonization resolution in the 3D viewport

Type float in [0.05, 1], default 0.0

texspace_location
Texture space location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size
Texture space size

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

threshold
Influence of meta elements

Type float in [0, 5], default 0.0

update_method
Metaball edit update behavior

Type enum in ['UPDATE_ALWAYS', 'HALFRES', 'FAST', 'NEVER'], default 'UPDATE_ALWAYS'

use_auto_texspace
Adjusts active object's texture space automatically when transforming object

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.metaballs
- BlendDataMetaBalls.new
- BlendDataMetaBalls.remove

1.4.330 MetaBallElements(bpy_struct)

base class — bpy_struct

class bpy.types.**MetaBallElements**(*bpy_struct*)

Collection of metaball elements

active

Last selected element

Type MetaElement, (readonly)

new(*type='BALL'*)

Add a new spline to the curve.

Parameters **type** (*enum in ['BALL', 'CAPSULE', 'PLANE', 'ELLIPSOID', 'CUBE'], (optional)*) – type for the new meta element.

Returns The newly created metaelement.

Return type MetaElement

remove(*element*)

Remove a spline from a curve.

Parameters **element** (MetaElement, (never None)) – The element to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MetaBall.elements

1.4.331 MetaElement(bpy_struct)

base class — bpy_struct

class bpy.types.**MetaElement**(*bpy_struct*)

Blobby element in a MetaBall datablock

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

hide

Hide element

Type boolean, default False

radius

Type float in [0, inf], default 0.0

rotation

Normalized quaternion rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

size_x

Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

size_y

Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

size_z
Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

stiffness
Stiffness defines how much of the element to fill

Type float in [0, 10], default 0.0

type
Metaball types

Type enum in ['BALL', 'CAPSULE', 'PLANE', 'ELLIPSOID', 'CUBE'], default 'BALL'

use_negative
Set metaball as negative one

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MetaBall.elements
- MetaBallElements.active
- MetaBallElements.new
- MetaBallElements.remove

1.4.332 MetaSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**MetaSequence**(*Sequence*)

Sequence strip to group other strips as a single sequence strip

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

proxy

Type SequenceProxy, (readonly)

sequences

Type Collection of Sequence, (readonly)

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop

Crop image before processing

Type boolean, default False

use_deinterlace

For video movies to remove fields

Type boolean, default False

use_flip_x

Flip on the X axis

Type boolean, default False

use_flip_y

Flip on the Y axis

Type boolean, default False

use_float
Convert input to float data

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy
Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start

- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.333 MirrorModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**MirrorModifier**(*Modifier*)

Mirroring modifier

merge_threshold

Distance from axis within which mirrored vertices are merged

Type float in [0, inf], default 0.0

mirror_object

Object to use as mirror

Type Object

use_clip

Prevents vertices from going through the mirror during transform

Type boolean, default False

use_mirror_merge

Merge vertices within the merge threshold

Type boolean, default False

use_mirror_u

Mirror the U texture coordinate around the 0.5 point

Type boolean, default False

use_mirror_v
Mirror the V texture coordinate around the 0.5 point

Type boolean, default False

use_mirror_vertex_groups
Mirror vertex groups (e.g. .R->.L)

Type boolean, default False

use_x
Enable X axis mirror

Type boolean, default False

use_y
Enable Y axis mirror

Type boolean, default False

use_z
Enable Z axis mirror

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.334 Modifier(bpy_struct)

base class — bpy_struct

subclasses — FluidSimulationModifier, BevelModifier, SolidifyModifier, SmokeModifier, UVProjectModifier, DecimateModifier, ExplodeModifier, SmoothModifier, HookModifier, SoftBodyModifier, BooleanModifier, ArrayModifier, LatticeModifier, BuildModifier, ClothModifier, ParticleSystemModifier, SubsurfModifier, CurveModifier, ScrewModifier, MaskModifier, ShrinkwrapModifier, CollisionModifier, CastModifier, WaveModifier, ParticleInstanceModifier, SurfaceModifier, SimpleDeformModifier, DisplaceModifier, ArmatureModifier, MeshDeformModifier, EdgeSplitModifier, MultiresModifier, MirrorModifier

class bpy.types.**Modifier**(*bpy_struct*)

Modifier affecting the geometry data of an object

name

Modifier name

Type string, default ""

show_expanded

Set modifier expanded in the user interface

Type boolean, default False

show_in_editmode

Use modifier while in the edit mode

Type boolean, default False

show_on_cage

Enable direct editing of modifier control cage

Type boolean, default False

show_render

Use modifier during rendering

Type boolean, default False

show_viewport

Realtime display of a modifier

Type boolean, default False

type

Type enum in ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE'], default 'ARRAY', (readonly)

use_apply_on_spline

Apply this and all preceding deformation modifiers on splines' points rather than on filled curve/surface

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.modifiers
- ObjectModifiers.new
- ObjectModifiers.remove
- UILayout.template_modifier

1.4.335 MotionPath(bpy_struct)

base class — bpy_struct

class bpy.types.**MotionPath**(*bpy_struct*)

Cache of the worldspace positions of an element over a frame range

frame_end

End frame of the stored range

Type int in [-inf, inf], default 0, (readonly)

frame_start

Starting frame of the stored range

Type int in [-inf, inf], default 0, (readonly)

is_modified

Path is being edited

Type boolean, default False

length

Number of frames cached

Type int in [-inf, inf], default 0, (readonly)

points
Cached positions per frame

Type Collection of `MotionPathVert`, (readonly)

use_bone_head
For PoseBone paths, use the bone head location when calculating this path

Type boolean, default False, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.motion_path`
- `PoseBone.motion_path`

1.4.336 MotionPathVert(bpy_struct)

base class — `bpy_struct`

class `bpy.types.`**`MotionPathVert`**(*bpy_struct*)
Cached location on path

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

select
Path point is selected for editing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MotionPath.points

1.4.337 MouseSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**MouseSensor**(*Sensor*)

Sensor to detect mouse events

mouse_event

Specify the type of event this mouse sensor should trigger on

Type enum in ['LEFTCLICK', 'MIDDLECLICK', 'RIGHTCLICK', 'WHEELUP', 'WHEELDOWN', 'MOVEMENT', 'MOUSEOVER', 'MOUSEOVERANY'], default 'LEFTCLICK'

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap

- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.338 MovieSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**MovieSequence**(*Sequence*)

Sequence strip to load a video

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

elements

Type Collection of SequenceElement, (readonly)

filepath

Type string, default “”

mpeg_preseek
For MPEG movies, preseek this many frames

Type int in [0, 50], default 0

proxy

Type SequenceProxy, (readonly)

strobe
Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance
(3-Way color correction) on input

Type boolean, default False

use_crop
Crop image before processing

Type boolean, default False

use_deinterlace
For video movies to remove fields

Type boolean, default False

use_flip_x
Flip on the X axis

Type boolean, default False

use_flip_y
Flip on the Y axis

Type boolean, default False

use_float
Convert input to float data

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy
Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.339 MulticamSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**MulticamSequence**(*Sequence*)

Sequence strip to perform multicam editing: select channel from below

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

multicam_source

Type int in [0, 31], default 0

proxy

Type SequenceProxy, (readonly)

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop
Crop image before processing

Type boolean, default False

use_deinterlace
For video movies to remove fields

Type boolean, default False

use_flip_x
Flip on the X axis

Type boolean, default False

use_flip_y
Flip on the Y axis

Type boolean, default False

use_float
Convert input to float data

Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy
Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader

- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.340 MultiresModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**MultiresModifier**(*Modifier*)

Multiresolution mesh modifier

filepath

Path to external displacements file

Type string, default “”

is_external
Store multires displacements outside the .blend file, to save memory

Type boolean, default False, (readonly)

levels
Number of subdivisions to use in the viewport

Type int in [0, 255], default 0

render_levels

Type int in [0, 255], default 0

sculpt_levels
Number of subdivisions to use in sculpt mode

Type int in [0, 255], default 0

show_only_control_edges
Skip drawing/rendering of interior subdivided edges

Type boolean, default False

subdivision_type
Selects type of subdivision algorithm

Type enum in ['CATMULL_CLARK', 'SIMPLE'], default 'CATMULL_CLARK'

total_levels
Number of subdivisions for which displacements are stored

Type int in [0, 255], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.341 MusgraveTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**MusgraveTexture**(*Texture*)

Procedural musgrave texture

dimension_max

Highest fractal dimension

Type float in [0.0001, 2], default 0.0

gain

The gain multiplier

Type float in [0, 6], default 0.0

lacunarity

Gap between successive frequencies

Type float in [0, 6], default 0.0

musgrave_type

Type enum in ['MULTIFRACTAL', 'RIDGED_MULTIFRACTAL', 'HYBRID_MULTIFRACTAL', 'FBM', 'HETERO_TERRAIN'], default 'MULTIFRACTAL'

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_intensity

Type float in [0, 10], default 0.0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

octaves

Number of frequencies used

Type float in [0, 8], default 0.0

offset

The fractal offset

Type float in [0, 6], default 0.0

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create

- ID.animation_data_clear
- ID.update_tag

1.4.342 NET_RENDER(RenderEngine)

base classes — bpy_struct, RenderEngine

class bpy.types.**NET_RENDER**(*RenderEngine*)

render(*scene*)

render_client(*scene*)

render_master(*scene*)

render_slave(*scene*)

Inherited Properties

- bpy_struct.id_data
- RenderEngine.bl_idname
- RenderEngine.bl_label
- RenderEngine.bl_use_postprocess
- RenderEngine.bl_use_preview

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- RenderEngine.render
- RenderEngine.begin_result
- RenderEngine.update_result
- RenderEngine.end_result
- RenderEngine.test_break
- RenderEngine.update_stats

1.4.343 NandController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**NandController**(*Controller*)

Controller passing on events based on a logical NAND operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.344 NearSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**NearSensor**(*Sensor*)

Sensor to detect nearby objects

distance

Trigger distance

Type float in [0, 10000], default 0.0

property

Only look for objects with this property (blank = all objects)

Type string, default “”

reset_distance
The distance where the sensor forgets the actor

Type float in [0, 10000], default 0.0

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.345 NetRenderJob(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**NetRenderJob**(*PropertyGroup*)

name

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NetRenderSettings.jobs

1.4.346 NetRenderSettings(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**NetRenderSettings**(*PropertyGroup*)

active_blacklisted_slave_index

Type int in [-1, 65535], default -1

active_job_index

Type int in [-1, 65535], default -1

active_slave_index

Type int in [-1, 65535], default -1

chunks

Number of frame to dispatch to each slave in one chunk

Type int in [1, 65535], default 5

job_category

Category of the job

Type string, default “”

job_id
id of the last sent render job

Type string, default “”

job_name
Name of the job

Type string, default “[default]”

job_type
Type of render job

Type enum in [’JOB_BLENDER’, ‘JOB_PROCESS’, ‘JOB_VCS’], default ‘JOB_BLENDER’

jobs

Type Collection of `NetRenderJob`, (readonly)

mode
Mode of operation of this instance

Type enum in [’RENDER_CLIENT’, ‘RENDER_MASTER’, ‘RENDER_SLAVE’], default ‘RENDER_CLIENT’

path
Path for temporary files

Type string, default “/tmp/”

priority
Priority of the job

Type int in [1, 10], default 1

server_address
IP or name of the master render server

Type string, default “[default]”

server_port
port of the master render server

Type int in [1, 65535], default 8000

slaves

Type Collection of `NetRenderSlave`, (readonly)

slaves_blacklist

Type Collection of `NetRenderSlave`, (readonly)

use_master_broadcast
broadcast master server address on local network

Type boolean, default True

use_master_clear
delete saved files on exit

Type boolean, default False

use_slave_clear
delete downloaded files on exit

Type boolean, default True

use_slave_output_log
Output render text log to console as well as sending it to the master

Type boolean, default True

use_slave_thumb
Generate thumbnails on slaves instead of master

Type boolean, default False

vcs_revision
Revision for this job

Type string, default ""

vcs_rpath
Path of the server copy (protocol specific)

Type string, default ""

vcs_system
Version Control System

Type string, default "Subversion"

vcs_wpath
Path of the local working copy

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.network_render

1.4.347 NetRenderSlave(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**NetRenderSlave**(*PropertyGroup*)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NetRenderSettings.slaves
- NetRenderSettings.slaves_blacklist

1.4.348 NlaStrip(bpy_struct)

base class — bpy_struct

class bpy.types.**NlaStrip**(*bpy_struct*)

A container referencing an existing Action

action

Action referenced by this strip

Type Action

action_frame_end

Type float in [-inf, inf], default 0.0

action_frame_start

Type float in [-inf, inf], default 0.0

active
NLA Strip is active

Type boolean, default False, (readonly)

blend_in
Number of frames at start of strip to fade in influence

Type float in [-inf, inf], default 0.0

blend_out

Type float in [-inf, inf], default 0.0

blend_type
Method used for combining strip's result with accumulated result

Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULITPLY'], default 'REPLACE'

extrapolation
Action to take for gaps past the strip extents

Type enum in ['NOTHING', 'HOLD', 'HOLD_FORWARD'], default 'HOLD'

fcurves
F-Curves for controlling the strip's influence and timing

Type Collection of `FCurve`, (readonly)

frame_end

Type float in [-inf, inf], default 0.0

frame_start

Type float in [-inf, inf], default 0.0

influence
Amount the strip contributes to the current result

Type float in [0, 1], default 0.0

modifiers
Modifiers affecting all the F-Curves in the referenced Action

Type Collection of `FModifier`, (readonly)

mute
NLA Strip is not evaluated

Type boolean, default False

name

Type string, default ""

repeat
Number of times to repeat the action range

Type float in [0.1, 1000], default 0.0

scale
Scaling factor for action

Type float in [0.0001, 1000], default 0.0

select
NLA Strip is selected

Type boolean, default False

strip_time
Frame of referenced Action to evaluate

Type float in [-inf, inf], default 0.0

strips
NLA Strips that this strip acts as a container for (if it is of type Meta)

Type Collection of `NlaStrip`, (readonly)

type
Type of NLA Strip

Type enum in ['CLIP', 'TRANSITION', 'META'], default 'CLIP', (readonly)

use_animated_influence
Influence setting is controlled by an F-Curve rather than automatically determined

Type boolean, default False

use_animated_time
Strip time is controlled by an F-Curve rather than automatically determined

Type boolean, default False

use_animated_time_cyclic
Cycle the animated time within the action start & end

Type boolean, default False

use_auto_blend
Number of frames for Blending In/Out is automatically determined from overlapping strips

Type boolean, default False

use_reverse
NLA Strip is played back in reverse order (only when timing is automatically determined)

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NlaStrip.strips
- NlaStrips.new
- NlaStrips.remove
- NlaTrack.strips

1.4.349 NlaStrips(bpy_struct)

base class — bpy_struct

class bpy.types.**NlaStrips**(*bpy_struct*)

Collection of Nla Strips

new(*name*, *start*, *action*)

Add a new Action-Clip strip to the track

Parameters

- **name** (*string*) – Name for the NLA Strips.
- **start** (*int in [-inf, inf]*) – Start Frame, Start frame for this strip.
- **action** (Action, (never None)) – Action to assign to this strip.

Returns New NLA Strip.

Return type NlaStrip

remove(*strip*)

Remove a NLA Strip.

Parameters **strip** (NlaStrip, (never None)) – NLA Strip to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NlaTrack.strips

1.4.350 NlaTrack(bpy_struct)

base class — bpy_struct

class bpy.types.**NlaTrack**(*bpy_struct*)

A animation layer containing Actions referenced as NLA strips

active

NLA Track is active

Type boolean, default False, (readonly)

is_solo

NLA Track is evaluated itself (i.e. active Action and all other NLA Tracks in the same AnimData block are disabled)

Type boolean, default False, (readonly)

lock

NLA Track is locked

Type boolean, default False

mute

NLA Track is not evaluated

Type boolean, default False

name

Type string, default “”

select

NLA Track is selected

Type boolean, default False

strips

NLA Strips on this NLA-track

Type NlaStrips collection of NlaStrip, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- AnimData.nla_tracks
- NlaTracks.active
- NlaTracks.new
- NlaTracks.new
- NlaTracks.remove

1.4.351 NlaTracks(bpy_struct)

base class — bpy_struct

class bpy.types.**NlaTracks**(*bpy_struct*)

Collection of NLA Tracks

active

Active Object constraint

Type NlaTrack

new(*prev=None*)

Add a new NLA Tracks

Parameters **prev** (NlaTrack, (optional)) – NLA Track to add the new one after.

Returns New NLA Track.

Return type NlaTrack

remove(*track*)

Remove a NLA Track.

Parameters **track** (NlaTrack, (never None)) – NLA Track to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- AnimData.nla_tracks

1.4.352 Node(bpy_struct)

base class — bpy_struct

subclasses — TextureNode, ShaderNode, CompositorNode, NodeGroup

class bpy.types.**Node**(*bpy_struct*)

Node in a node tree

inputs

Type Collection of NodeSocket, (readonly)

location

Type float array of 2 items in [-10000, 10000], default (0.0, 0.0)

name

Node name

Type string, default “”

outputs

Type Collection of NodeSocket, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CompositorNodeTree.nodes
- CompositorNodes.new
- CompositorNodes.remove
- NodeLink.from_node
- NodeLink.to_node
- ShaderNodeTree.nodes
- ShaderNodes.new
- ShaderNodes.remove
- TextureNodeTree.nodes
- TextureNodes.new
- TextureNodes.remove

1.4.353 NodeGroup(Node)

base classes — bpy_struct, Node

class bpy.types.**NodeGroup**(*Node*)

node_tree

Type NodeTree

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.354 NodeLink(bpy_struct)

base class — bpy_struct

class bpy.types.**NodeLink** (*bpy_struct*)

Link between nodes in a node tree

from_node

Type Node, (readonly)

from_socket

Type NodeSocket, (readonly)

to_node

Type Node, (readonly)

to_socket

Type NodeSocket, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NodeLinks.new
- NodeLinks.remove
- NodeTree.links

1.4.355 NodeLinks(bpy_struct)

base class — bpy_struct

class bpy.types.**NodeLinks**(*bpy_struct*)

Collection of Node Links

new(*input*, *output*)

Add a node link to this node tree.

Parameters

- **input** (NodeSocket) – The input socket.
- **output** (NodeSocket) – The output socket.

Returns New node link.

Return type NodeLink

remove(*link*)

remove a node link from the node tree.

Parameters **link** (NodeLink) – The node link to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NodeTree.links

1.4.356 NodeSocket(bpy_struct)

base class — bpy_struct

subclasses — VectorNodeSocket, RGBANodeSocket, ValueNodeSocket

class bpy.types.**NodeSocket**(*bpy_struct*)

Input or output socket of a node

name

Socket name

Type string, default ""

type

Node Socket type

Type enum in ['VALUE', 'VECTOR', 'RGBA'], default 'VALUE', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GroupInputs.expose
- GroupInputs.expose
- GroupInputs.new
- GroupOutputs.expose
- GroupOutputs.expose
- GroupOutputs.new
- Node.inputs
- Node.outputs
- NodeLink.from_socket
- NodeLink.to_socket
- NodeLinks.new
- NodeLinks.new
- NodeTree.inputs
- NodeTree.outputs

1.4.357 NodeTree(ID)

base classes — bpy_struct, ID

subclasses — CompositorNodeTree, ShaderNodeTree, TextureNodeTree

class bpy.types.**NodeTree**(*ID*)

Node tree consisting of linked nodes used for materials, textures and compositing

animation_data

Animation data for this datablock

Type AnimData, (readonly)

grease_pencil

Grease Pencil datablock

Type GreasePencil

inputs

Type GroupInputs collection of NodeSocket, (readonly)

links

Type NodeLinks collection of NodeLink, (readonly)

outputs

Type GroupOutputs collection of NodeSocket, (readonly)

type

Node Tree type

Type enum in ['SHADER', 'COMPOSITE', 'TEXTURE'], default 'SHADER', (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.node_groups
- BlendDataNodeTrees.new
- BlendDataNodeTrees.remove
- CompositorNodes.new
- Material.node_tree
- NodeGroup.node_tree
- Scene.node_tree
- ShaderNodes.new
- SpaceNodeEditor.node_tree
- Texture.node_tree
- TextureNodes.new

1.4.358 NoiseTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**NoiseTexture**(*Texture*)

Procedural noise texture

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.359 NorController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**NorController**(*Controller*)

Controller passing on events based on a logical NOR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.360 Object(ID)

base classes — bpy_struct, ID

class bpy.types.**Object**(*ID*)

Object datablock defining an object in a scene

active_material

Active material being displayed

Type Material

active_material_index
Index of active material slot

Type int in [0, inf], default 0

active_shape_key
Current shape key

Type ShapeKey, (readonly)

active_shape_key_index
Current shape key index

Type int in [-32768, 32767], default 0

animation_data
Animation data for this datablock

Type AnimData, (readonly)

animation_visualisation
Animation data for this datablock

Type AnimViz, (readonly, never None)

bound_box
Objects bound box in object-space coordinates, all values are -1.0 when not available.

Type float array of 24 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

collision
Settings for using the objects as a collider in physics simulation

Type CollisionSettings, (readonly)

color
Object color and alpha, used when faces have the ObColor mode enabled

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

constraints
Constraints affecting the transformation of the object

Type ObjectConstraints collection of Constraint, (readonly)

data
Object data

Type ID

delta_location
Extra translation added to the location of the object

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

delta_rotation_euler
Extra rotation added to the rotation of the object (when using Euler rotations)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

delta_rotation_quaternion
Extra rotation added to the rotation of the object (when using Quaternion rotations)

Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

delta_scale
Extra scaling added to the scale of the object

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dimensions
Absolute bounding box dimensions of the object

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

draw_bounds_type
Object boundary display type

Type enum in ['BOX', 'SPHERE', 'CYLINDER', 'CONE', 'POLYHEDRON', 'CAPSULE'], default 'BOX'

draw_type
Maximum draw type to display object with in viewport

Type enum in ['BOUNDS', 'WIRE', 'SOLID', 'TEXTURED'], default 'BOUNDS'

dupli_faces_scale
Scale the DupliFace objects

Type float in [0.001, 10000], default 0.0

dupli_frames_end
End frame for DupliFrames

Type int in [-300000, 300000], default 0

dupli_frames_off
Recurring frames to exclude from the Dupliframes

Type int in [0, 300000], default 0

dupli_frames_on
Number of frames to use between DupOff frames

Type int in [0, 300000], default 0

dupli_frames_start
Start frame for DupliFrames

Type int in [-300000, 300000], default 0

dupli_group
Instance an existing group

Type `Group`

dupli_list
Object duplis

Type Collection of `DupliObject`, (readonly)

dupli_type
If not None, object duplication method to use

Type enum in ['NONE', 'FRAMES', 'VERTS', 'FACES', 'GROUP'], default 'NONE'

empty_draw_size
Size of display for empties in the viewport

Type float in [0.0001, 1000], default 0.0

empty_draw_type
Viewport display style for empties

Type enum in ['PLAIN_AXES', 'ARROWS', 'SINGLE_ARROW', 'CIRCLE', 'CUBE', 'SPHERE', 'CONE'], default 'PLAIN_AXES'

field
Settings for using the objects as a field in physics simulation

Type `FieldSettings`, (readonly)

game
Game engine related settings for the object

Type `GameObjectSettings`, (readonly, never None)

grease_pencil
Grease Pencil datablock

Type `GreasePencil`

hide
Restrict visibility in the viewport

Type boolean, default False

hide_render
Restrict renderability

Type boolean, default False

hide_select
Restrict selection in the viewport

Type boolean, default False

is_duplicator

Type boolean, default False, (readonly)

layers
Layers the object is on

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

location
Location of the object

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lock_location
Lock editing of location in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation
Lock editing of rotation in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation_w
Lock editing of 'angle' component of four-component rotations in the interface

Type boolean, default False

lock_rotations_4d
Lock editing of four component rotations by components (instead of as Eulers)

Type boolean, default False

lock_scale
Lock editing of scale in the interface

Type boolean array of 3 items, default (False, False, False)

material_slots
Material slots in the object

Type Collection of `MaterialSlot`, (readonly)

matrix_basis
Matrix access to location, rotation and scale (including deltas), before constraints and parenting are applied.

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_local
Parent relative transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_world
Worldspace transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

mode
Object interaction mode

Type enum in ['OBJECT', 'EDIT', 'SCULPT', 'VERTEX_PAINT', 'WEIGHT_PAINT', 'TEXTURE_PAINT', 'PARTICLE_EDIT', 'POSE'], default 'OBJECT', (readonly)

modifiers
Modifiers affecting the geometric data of the object

Type `ObjectModifiers` collection of `Modifier`, (readonly)

motion_path
Motion Path for this element

Type `MotionPath`, (readonly)

parent
Parent Object

Type `Object`

parent_bone
Name of parent bone in case of a bone parenting relation

Type string, default ""

parent_type
Type of parent relation

Type enum in ['OBJECT', 'CURVE', 'KEY', 'ARMATURE', 'LATTICE', 'VERTEX', 'VERTEX_3', 'BONE'], default 'OBJECT'

parent_vertices
Indices of vertices in cases of a vertex parenting relation

Type int array of 3 items in [0, inf], default (0, 0, 0), (readonly)

particle_systems
Particle systems emitted from the object

Type ParticleSystems collection of ParticleSystem, (readonly)

pass_index
Index # for the IndexOB render pass

Type int in [0, 32767], default 0

pose
Current pose for armatures

Type Pose, (readonly)

pose_library
Action used as a pose library for armatures

Type Action

proxy
Library object this proxy object controls

Type Object, (readonly)

proxy_group
Library group duplicator object this proxy object controls

Type Object, (readonly)

rotation_axis_angle
Angle of Rotation for Axis-Angle rotation representation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 1.0, 0.0)

rotation_euler
Rotation in Eulers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_mode

Type enum in ['QUATERNION', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX', 'AXIS_ANGLE'], default 'QUATERNION'

rotation_quaternion
Rotation in Quaternions

Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

scale
Scaling of the object

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

select
Object selection state

Type boolean, default False

show_axis
Displays the object's origin and axis

Type boolean, default False

show_bounds
Displays the object's bounds

Type boolean, default False

show_name
Displays the object's name

Type boolean, default False

show_only_shape_key
Always show the current Shape for this Object

Type boolean, default False

show_texture_space
Displays the object's texture space

Type boolean, default False

show_transparent
Displays material transparency in the object

Type boolean, default False

show_wire
Adds the object's wireframe over solid drawing

Type boolean, default False

show_x_ray
Makes the object draw in front of others

Type boolean, default False

soft_body
Settings for soft body simulation

Type `SoftBodySettings`, (readonly)

time_offset
Animation offset in frames for F-Curve and dupligroup instances

Type float in [-300000, 300000], default 0.0

track_axis
Axis that points in 'forward' direction

Type enum in ['POS_X', 'POS_Y', 'POS_Z', 'NEG_X', 'NEG_Y', 'NEG_Z'], default 'POS_X'

type
Type of Object

Type enum in ['MESH', 'CURVE', 'SURFACE', 'META', 'FONT', 'ARMATURE', 'LATTICE', 'EMPTY', 'CAMERA', 'LAMP'], default 'EMPTY', (readonly)

up_axis
Axis that points in the upward direction

Type enum in ['X', 'Y', 'Z'], default 'X'

use_dupli_faces_scale
Scale dupli based on face size

Type boolean, default False

use_dupli_frames_speed
Set dupliframes to use the frame

Type boolean, default False

use_dupli_vertices_rotation
Rotate dupli according to vertex normal

Type boolean, default False

use_shape_key_edit_mode
Apply shape keys in edit mode (for Meshes only)

Type boolean, default False

use_slow_parent
Create a delay in the parent relationship

Type boolean, default False

use_time_offset_add_parent
Add the parents time offset value

Type boolean, default False

use_time_offset_edit
Use time offset when inserting keys and display time offset for F-Curve and action views

Type boolean, default False

use_time_offset_parent
Apply the time offset to this objects parent relationship

Type boolean, default False

use_time_offset_particle
Let the time offset work on the particle effect

Type boolean, default False

vertex_groups
Vertex groups of the object

Type `VertexGroups` collection of `VertexGroup`, (readonly)

children
All the children of this object (readonly)

users_group
The groups this object is in (readonly)

users_scene
The scenes this object is in (readonly)

to_mesh (*scene*, *apply_modifiers*, *settings*)
Create a Mesh datablock with modifiers applied.

Parameters

- **scene** (`Scene`, (never None)) – Scene within which to evaluate modifiers.
- **apply_modifiers** (*boolean*) – Apply modifiers.
- **settings** (*enum in ['PREVIEW', 'RENDER']*) – Modifier settings to apply.

Returns Mesh created from object, remove it if it is only used for export.

Return type Mesh

dupli_list_create(*scene*)

Create a list of dupli objects for this object, needs to be freed manually with free_dupli_list to restore the objects real matrix and layers.

Parameters **scene** (Scene, (never None)) – Scene within which to evaluate duplis.

dupli_list_clear()

Free the list of dupli objects.

find_armature()

Find armature influencing this object as a parent or via a modifier.

Returns Armature object influencing this object or NULL.

Return type Object

shape_key_add(*name="Key", from_mix=True*)

Add shape key to an object.

Parameters

- **name** (*string, (optional)*) – Unique name for the new keylock.
- **from_mix** (*boolean, (optional)*) – Create new shape from existing mix of shapes.

Returns New shape keyblock.

Return type ShapeKey

ray_cast(*start, end*)

Cast a ray onto in object space.

Return (location, normal, index) *location*, The hit location of this ray cast, float array of 3 items in [-inf, inf]

normal, The face normal at the ray cast hit location, float array of 3 items in [-inf, inf]

index, The face index, -1 when no intersection is found., int in [-inf, inf]

is_visible(*scene*)

Determine if object is visible in a given scene.

Returns Object visibility.

Return type boolean

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- ActionConstraint.target
- ArmatureActuator.secondary_target
- ArmatureActuator.target
- ArmatureModifier.object
- ArrayModifier.curve
- ArrayModifier.end_cap
- ArrayModifier.offset_object
- ArrayModifier.start_cap
- BlendData.objects
- BlendDataObjects.new
- BlendDataObjects.remove
- BoidRuleAvoid.object
- BoidRuleFollowLeader.object
- BoidRuleGoal.object
- BooleanModifier.object
- Camera.dof_object
- CameraActuator.object
- CastModifier.object
- ChildOfConstraint.target
- ClampToConstraint.target
- ConstraintTarget.target
- CopyLocationConstraint.target
- CopyRotationConstraint.target
- CopyScaleConstraint.target
- CopyTransformsConstraint.target
- Curve.bevel_object
- Curve.taper_object

- CurveModifier.object
- CurveSplines.active
- DampedTrackConstraint.target
- DisplaceModifier.texture_coordinate_object
- DupliObject.object
- EditObjectActuator.object
- EditObjectActuator.track_object
- EnvironmentMap.viewpoint_object
- FloorConstraint.target
- FollowPathConstraint.target
- Group.objects
- GroupObjects.link
- GroupObjects.unlink
- HookModifier.object
- KinematicConstraint.pole_target
- KinematicConstraint.target
- LampTextureSlot.object
- LatticeModifier.object
- LimitDistanceConstraint.target
- LockedTrackConstraint.target
- MaskModifier.armature
- MaterialTextureSlot.object
- MeshDeformModifier.object
- MirrorModifier.mirror_object
- Object.find_armature
- Object.parent
- Object.proxy
- Object.proxy_group
- ObjectActuator.reference_object
- ObjectBase.object
- ParentActuator.object
- ParticleEdit.object
- ParticleInstanceModifier.object
- ParticleSettings.billboard_object
- ParticleSettings.dupli_object
- ParticleSettingsTextureSlot.object
- ParticleSystem.parent
- ParticleSystem.reactor_target_object
- ParticleTarget.object
- PivotConstraint.target
- PointDensity.object
- PoseBone.custom_shape
- PropertyActuator.object
- RigidBodyJointConstraint.child
- RigidBodyJointConstraint.target
- Scene.camera
- Scene.objects
- SceneActuator.camera
- SceneObjects.active
- SceneObjects.link
- SceneObjects.unlink
- SceneSequence.scene_camera
- ScrewModifier.object
- ShrinkwrapConstraint.target

- ShrinkwrapModifier.auxiliary_target
- ShrinkwrapModifier.target
- SimpleDeformModifier.origin
- SpaceView3D.camera
- SpaceView3D.lock_object
- SplineIKConstraint.target
- StretchToConstraint.target
- TextCurve.follow_curve
- TimelineMarker.camera
- ToolSettings.etch_template
- TrackToConstraint.target
- TransformConstraint.target
- UVProjector.object
- VoxelData.domain_object
- WaveModifier.start_position_object
- WaveModifier.texture_coords_object
- WorldTextureSlot.object

1.4.361 ObjectActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ObjectActuator**(*Actuator*)

Actuator to control the object movement

angular_velocity

Sets the angular velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

damping

Number of frames to reach the target velocity

Type int in [-32768, 32767], default 0

derivate_coefficient

Not required, high values can cause instability

Type float in [-inf, inf], default 0.0

force

Sets the force

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

force_max_x

Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_max_y

Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_max_z

Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_min_x
Set the lower limit for force

Type float in [-inf, inf], default 0.0

force_min_y
Set the lower limit for force

Type float in [-inf, inf], default 0.0

force_min_z
Set the lower limit for force

Type float in [-inf, inf], default 0.0

integral_coefficient
Low value (0.01) for slow response, high value (0.5) for fast response

Type float in [-inf, inf], default 0.0

linear_velocity
Sets the linear velocity (in Servo mode it sets the target relative linear velocity, it will be achieved by automatic application of force. Null velocity is a valid target)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mode
Specify the motion system

Type enum in ['OBJECT_NORMAL', 'OBJECT_SERVO'], default 'OBJECT_NORMAL'

offset_location
Sets the location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

offset_rotation
Sets the rotation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

proportional_coefficient
Typical value is 60x integral coefficient

Type float in [-inf, inf], default 0.0

reference_object
Reference object for velocity calculation, leave empty for world reference

Type `Object`

torque
Sets the torque

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_add_linear_velocity
Toggles between ADD and SET linV

Type boolean, default False

use_local_angular_velocity
Angular velocity is defined in local coordinates

Type boolean, default False

use_local_force
Force is defined in local coordinates

Type boolean, default False

use_local_linear_velocity
Velocity is defined in local coordinates

Type boolean, default False

use_local_location
Location is defined in local coordinates

Type boolean, default False

use_local_rotation
Rotation is defined in local coordinates

Type boolean, default False

use_local_torque
Torque is defined in local coordinates

Type boolean, default False

use_servo_limit_x
Set limit to force along the X axis

Type boolean, default False

use_servo_limit_y
Set limit to force along the Y axis

Type boolean, default False

use_servo_limit_z
Set limit to force along the Z axis

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.362 ObjectBase(bpy_struct)

base class — bpy_struct

class bpy.types.**ObjectBase**(*bpy_struct*)

An object instance in a scene

layers

Layers the object base is on

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

object

Object this base links to

Type Object, (readonly)

select

Object base selection state

Type boolean, default False

layers_from_view(*view*)

Sets the object layers from a 3D View (use when adding an object in local view).

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.object_bases
- SceneBases.active
- SceneObjects.link

1.4.363 ObjectConstraints(bpy_struct)

base class — bpy_struct

class bpy.types.**ObjectConstraints**(*bpy_struct*)

Collection of object constraints

active

Active Object constraint

Type Constraint

new(*type*)

Add a new constraint to this object

Parameters **type** (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP']*) – Constraint type to add.

Returns New constraint.

Return type Constraint

remove(*constraint*)

Remove a constraint from this object.

Parameters **constraint** (Constraint, (never None)) – Removed constraint.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.constraints

1.4.364 ObjectModifiers(bpy_struct)

base class — bpy_struct

class bpy.types.**ObjectModifiers**(*bpy_struct*)

Collection of object modifiers

new(*name*, *type*)

Add a new modifier.

Parameters

- **name** (*string*) – New name for the bone.
- **type** (*enum in ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE']*) – Modifier type to add.

Returns Newly created modifier.

Return type Modifier

remove(*modifier*)

Remove an existing modifier from the object.

Parameters **modifier** (Modifier, (never None)) – Modifier to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.modifiers

1.4.365 ObstacleFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**ObstacleFluidSettings**(*FluidSettings*)

Fluid simulation settings for obstacles in the simulation

impact_factor

This is an unphysical value for moving objects - it controls the impact an obstacle has on the fluid, =0 behaves a bit like outflow (deleting fluid), =1 is default, while >1 results in high forces. Can be used to tweak total mass

Type float in [-2, 10], default 0.0

partial_slip_factor

Amount of mixing between no- and free-slip, 0 is no slip and 1 is free slip

Type float in [0, 1], default 0.0

slip_type

Type enum in ['NOSLIP', 'PARTIALSLIP', 'FREESLIP'], default 'NOSLIP'

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_initialization

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.366 Operator(bpy_struct)

Basic Operator Example

This script shows simple operator which prints a message.

Since the operator only has an Operator.execute function it takes no user input.

Note: Operator subclasses must be registered before accessing them from blender.

```
import bpy


class HelloWorldOperator(bpy.types.Operator):
    bl_idname = "wm.hello_world"
    bl_label = "Minimal Operator"

    def execute(self, context):
        print("Hello World")
        return {'FINISHED'}

bpy.utils.register_class(SimpleOperator)

# test call to the newly defined operator
bpy.ops.wm.hello_world()
```

Invoke Function

`Operator.invoke` is used to initialize the operator from the context at the moment the operator is called. invoke() is typically used to assign properties which are then used by execute(). Some operators don't have an execute() function, removing the ability to be repeated from a script or macro.

This example shows how to define an operator which gets mouse input to execute a function and that this operator can be invoked or executed from the python api.

Also notice this operator defines its own properties, these are different to typical class properties because blender registers them with the operator, to use as arguments when called, saved for operator undo/redo and automatically added into the user interface.

```
import bpy


class SimpleMouseOperator(bpy.types.Operator):
    """ This operator shows the mouse location,
        this string is used for the tooltip and API docs
    """
    bl_idname = "wm.mouse_position"
    bl_label = "Invoke Mouse Operator"

    x = bpy.props.IntProperty()
    y = bpy.props.IntProperty()

    def execute(self, context):
        # rather then printing, use the report function,
        # this way the messag appiers in the header,
        self.report({'INFO'}, "Mouse coords are %d %d" % (self.x, self.y))
        return {'FINISHED'}

    def invoke(self, context, event):
        self.x = event.mouse_x
        self.y = event.mouse_y
        return self.execute(context)

bpy.utils.register_class(SimpleMouseOperator)

# Test call to the newly defined operator.
# Here we call the operator and invoke it, meaning that the settings are taken
# from the mouse.
bpy.ops.wm.mouse_position('INVOKE_DEFAULT')

# Another test call, this time call execute() directly with pre-defined settings.
bpy.ops.wm.mouse_position('EXEC_DEFAULT', x=20, y=66)
```

Calling a File Selector

This example shows how an operator can use the file selector.

Notice the invoke function calls a window manager method and returns RUNNING_MODAL, this means the file selector stays open and the operator does not exit immediately after invoke finishes.

The file selector runs the operator, calling `Operator.execute` when the user confirms.

The `Operator.poll` function is optional, used to check if the operator can run.

```
import bpy


class ExportSomeData(bpy.types.Operator):
    """Test exporter which just writes hello world"""
    bl_idname = "export.some_data"
    bl_label = "Export Some Data"

    filepath = bpy.props.StringProperty(subtype="FILE_PATH")

    @classmethod
    def poll(cls, context):
        return context.object is not None

    def execute(self, context):
        file = open(self.filepath, 'w')
        file.write("Hello World " + context.object.name)
        return {'FINISHED'}

    def invoke(self, context, event):
        context.window_manager.fileselect_add(self)
        return {'RUNNING_MODAL'}


# Only needed if you want to add into a dynamic menu
def menu_func(self, context):
    self.layout.operator(ExportSomeData.bl_idname, text="Text Export Operator")

# Register and add to the file selector
bpy.utils.register_class(ExportSomeData)
bpy.types.INFO_MT_file_export.append(menu_func)


# test call
bpy.ops.export.some_data('INVOKE_DEFAULT')
```

Dialog Box

This operator uses its `Operator.invoke` function to call a popup.

```
import bpy


class DialogOperator(bpy.types.Operator):
    bl_idname = "object.dialog_operator"
    bl_label = "Simple Dialog Operator"

    my_float = bpy.props.FloatProperty(name="Some Floating Point")
    my_bool = bpy.props.BoolProperty(name="Toggle Option")
    my_string = bpy.props.StringProperty(name="String Value")

    def execute(self, context):
        message = "Popup Values: %f, %d, '%s'" % \
            (self.my_float, self.my_bool, self.my_string)
        self.report({'INFO'}, message)
        return {'FINISHED'}
```

```
    def invoke(self, context, event):
        wm = context.window_manager
        return wm.invoke_props_dialog(self)


bpy.utils.register_class(DialogOperator)

# test call
bpy.ops.object.dialog_operator('INVOKE_DEFAULT')
```

Custom Drawing

By default operator properties use an automatic user interface layout. If you need more control you can create your own layout with a `Operator.draw` function.

This works like the `Panel` and `Menu` draw functions, its used for dialogs and file selectors.

```
import bpy


class CustomDrawOperator(bpy.types.Operator):
    bl_idname = "object.custom_draw"
    bl_label = "Simple Modal Operator"

    filepath = bpy.props.StringProperty(subtype="FILE_PATH")

    my_float = bpy.props.FloatProperty(name="Float")
    my_bool = bpy.props.BoolProperty(name="Toggle Option")
    my_string = bpy.props.StringProperty(name="String Value")

    def execute(self, context):
        print()
        return {'FINISHED'}

    def invoke(self, context, event):
        context.window_manager.fileselect_add(self)
        return {'RUNNING_MODAL'}

    def draw(self, context):
        layout = self.layout
        col = layout.column()
        col.label(text="Custom Interface!")

        row = col.row()
        row.prop(self, "my_float")
        row.prop(self, "my_bool")

        col.prop(self, "my_string")

bpy.utils.register_class(CustomDrawOperator)

# test call
bpy.ops.object.custom_draw('INVOKE_DEFAULT')
```

Modal Execution

This operator defines a `Operator.modal` function which running, handling events until it returns {'FINISHED'} or {'CANCELLED'}.

Grab, Rotate, Scale and Fly-Mode are examples of modal operators. They are especially useful for interactive tools, your operator can have its own state where keys toggle options as the operator runs.

`Operator.invoke` is used to initialize the operator as being by returning {'RUNNING_MODAL'}, initializing the modal loop.

Notice __init__() and __del__() are declared. For other operator types they are not useful but for modal operators they will be called before the `Operator.invoke` and after the operator finishes.

```
import bpy


class ModalOperator(bpy.types.Operator):
    bl_idname = "object.modal_operator"
    bl_label = "Simple Modal Operator"

    def __init__(self):
        print("Start")

    def __del__(self):
        print("End")

    def execute(self, context):
        context.object.location.x = self.value / 100.0

    def modal(self, context, event):
        if event.type == 'MOUSEMOVE':  # Apply
            self.value = event.mouse_x
            self.execute(context)
        elif event.type == 'LEFTMOUSE':  # Confirm
            return {'FINISHED'}
        elif event.type in ('RIGHTMOUSE', 'ESC'):  # Cancel
            return {'CANCELLED'}

        return {'RUNNING_MODAL'}

    def invoke(self, context, event):
        self.value = event.mouse_x
        self.execute(context)

        print(context.window_manager.modal_handler_add(self))
        return {'RUNNING_MODAL'}


bpy.utils.register_class(ModalOperator)

# test call
bpy.ops.object.modal_operator('INVOKE_DEFAULT')
```

base class — `bpy_struct`

class `bpy.types.`**`Operator`**(*bpy_struct*)

Storage of an operator being executed, or registered after execution

`bl_description`

Type string, default “”

bl_idname

Type string, default “”

bl_label

Type string, default “”

bl_options

Options for this operator type

Type enum set in {‘REGISTER’, ‘UNDO’, ‘BLOCKING’, ‘MACRO’, ‘GRAB_POINTER’, ‘PRESET’}, default {‘REGISTER’}

has_reports

Operator has a set of reports (warnings and errors) from last execution

Type boolean, default False, (readonly)

layout

Type `UILayout`, (readonly)

name

Type string, default “”, (readonly)

properties

Type `OperatorProperties`, (readonly, never None)

report (*type*, *message*)

report

Parameters

- **type** (*enum set in {‘DEBUG’, ‘INFO’, ‘OPERATOR’, ‘WARNING’, ‘ERROR’, ‘ERROR_INVALID_INPUT’, ‘ERROR_INVALID_CONTEXT’, ‘ERROR_OUT_OF_MEMORY’}*) – Type
- **message** (*string*) – Report Message

classmethod poll (*context*)

Test if the operator can be called or not.

Return type boolean

execute (*context*)

Execute the operator.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

check (*context*)

Check the operator settings.

Returns result

Return type boolean

invoke (*context*, *event*)

Invoke the operator.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

modal(*context*, *event*)
Modal operator function.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

draw(*context*)
Draw function for the operator.

as_keywords(*ignore=()*)
Return a copy of the properties as a dictionary.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceFileBrowser.operator
- WindowManager.fileselect_add
- WindowManager.invoke_confirm
- WindowManager.invoke_popup
- WindowManager.invoke_props_dialog
- WindowManager.invoke_props_popup
- WindowManager.invoke_search_popup
- WindowManager.modal_handler_add
- WindowManager.operators

1.4.367 OperatorFileListElement(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**OperatorFileListElement**(*PropertyGroup*)

name
the name of a file or directory within a file list

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.368 OperatorMousePath(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**OperatorMousePath**(*PropertyGroup*)
Mouse path values for operators that record such paths

loc
Mouse location

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

time
Time of mouse location

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.369 OperatorProperties(bpy_struct)

base class — bpy_struct

class bpy.types.**OperatorProperties**(*bpy_struct*)

Input properties of an Operator

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- KeyMapItem.properties
- Macro.properties
- Operator.properties
- OperatorTypeMacro.properties
- UILayout.operator

1.4.370 OperatorStrokeElement(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.**OperatorStrokeElement**(*PropertyGroup*)

is_start

Type boolean, default False

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mouse

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

pen_flip

Type boolean, default False

pressure

Tablet pressure

Type float in [0, 1], default 0.0

time

Type float in [0, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.371 OperatorTypeMacro(bpy_struct)

base class — bpy_struct

class bpy.types.**OperatorTypeMacro**(*bpy_struct*)

Storage of a sub operator in a macro after it has been added

properties

Type OperatorProperties, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.372 OrController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**OrController**(*Controller*)

Controller passing on events based on a logical OR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.373 OutflowFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**OutflowFluidSettings** (*FluidSettings*)

Fluid simulation settings for objects removing fluids from the simulation

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_initialization

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.374 PackedFile(bpy_struct)

base class — bpy_struct

class bpy.types.**PackedFile**(*bpy_struct*)

External file packed into the .blend file

size

Size of packed file in bytes

Type int in [-inf, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Image.packed_file
- Sound.packed_file
- VectorFont.packed_file

1.4.375 Paint(bpy_struct)

base class — bpy_struct

subclasses — VertexPaint, Sculpt, ImagePaint

class bpy.types.**Paint**(*bpy_struct*)

brush
Active Brush

Type Brush

show_brush

Type boolean, default False

show_brush_on_surface

Type boolean, default False

show_low_resolution
For multires, show low resolution while navigating the view

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.376 Panel(bpy_struct)

Basic Panel Example

This script is a simple panel which will draw into the object properties section.

Notice the 'CATEGORY_PT_name' Panel.bl_idname, this is a naming convention for panels.

Note: Panel subclasses must be registered for blender to use them.

```
import bpy


class HelloWorldPanel(bpy.types.Panel):
    bl_idname = "OBJECT_PT_hello_world"
    bl_label = "Hello World"
    bl_space_type = 'PROPERTIES'
    bl_region_type = 'WINDOW'
    bl_context = "object"

    def draw(self, context):
        self.layout.label(text="Hello World")


bpy.utils.register_class(HelloWorldPanel)
```

Simple Object Panel

This panel has a Panel.poll and Panel.draw_header function, even though the contents is basic this closely resemples blenders panels.

```
import bpy


class ObjectSelectPanel(bpy.types.Panel):
    bl_idname = "OBJECT_PT_select"
    bl_label = "Select"
    bl_space_type = 'PROPERTIES'
    bl_region_type = 'WINDOW'
    bl_context = "object"
    bl_options = {'DEFAULT_CLOSED'}

    @classmethod
    def poll(cls, context):
        return (context.object is not None)
```

```
    def draw_header(self, context):
        layout = self.layout
        obj = context.object
        layout.prop(obj, "select", text="")

    def draw(self, context):
        layout = self.layout

        obj = context.object
        row = layout.row()
        row.prop(obj, "hide_select")
        row.prop(obj, "hide_render")

        box = layout.box()
        box.label("Selection Tools")
        box.operator("object.select_all")
        row = box.row()
        row.operator("object.select_inverse")
        row.operator("object.select_random")


bpy.utils.register_class(ObjectSelectPanel)
```

Mix-in Classes

A mix-in parent class can be used to share common properties and `Menu.poll` function.

```
import bpy


class View3DPanel():
    bl_space_type = 'VIEW_3D'
    bl_region_type = 'TOOLS'

    @classmethod
    def poll(cls, context):
        return (context.object is not None)


class PanelOne(View3DPanel, bpy.types.Panel):
    bl_idname = "VIEW3D_PT_test_1"
    bl_label = "Panel One"

    def draw(self, context):
        self.layout.label("Small Class")


class PanelTwo(View3DPanel, bpy.types.Panel):
    bl_idname = "VIEW3D_PT_test_2"
    bl_label = "Panel Two"

    def draw(self, context):
        self.layout.label("Also Small Class")


bpy.utils.register_class(PanelOne)
bpy.utils.register_class(PanelTwo)
```

base class — bpy_struct

subclasses — InputKeyMapPanel

class bpy.types.**Panel**(*bpy_struct*)

Panel containing UI elements

bl_context

The context in which the panel belongs to. (TODO: explain the possible combinations bl_context/bl_region_type/bl_space_type)

Type string, default ""

bl_idname

If this is set, the panel gets a custom ID, otherwise it takes the name of the class used to define the panel. For example, if the class name is "OBJECT_PT_hello", and bl_idname is not set by the script, then bl_idname = "OBJECT_PT_hello"

Type string, default ""

bl_label

The panel label, shows up in the panel header at the right of the triangle used to collapse the panel.

Type string, default ""

bl_options

Options for this panel type

Type enum set in {'DEFAULT_CLOSED', 'HIDE_HEADER'}, default {'DEFAULT_CLOSED'}

bl_region_type

The region where the panel is going to be used in.

Type enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], default 'WINDOW'

bl_space_type

The space where the panel is going to be used in.

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY'

layout

Defines the structure of the panel in the UI.

Type UILayout, (readonly)

text

XXX todo

Type string, default ""

classmethod poll(*context*)

If this method returns a non-null output, then the panel can be drawn.

Return type boolean

draw(*context*)

Draw UI elements into the panel UI layout.

draw_header(*context*)
Draw UI elements into the panel's header UI layout.

classmethod append(*draw_func*)
Append a draw function to this menu, takes the same arguments as the menus draw function.

classmethod prepend(*draw_func*)
Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove(*draw_func*)
Remove a draw function that has been added to this menu

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.377 ParentActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ParentActuator**(*Actuator*)

mode

Type enum in ['SETPARENT', 'REMOVEPARENT'], default 'SETPARENT'

object
Set this object as parent

Type Object

use_compound
Add this object shape to the parent shape (only if the parent shape is already compound)

Type boolean, default False

use_ghost
Make this object ghost while parented

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.378 Particle(bpy_struct)

base class — bpy_struct

class bpy.types.**Particle**(*bpy_struct*)
Particle in a particle system

alive_state

Type enum in ['DEAD', 'UNBORN', 'ALIVE', 'DYING'], default 'DEAD'

angular_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

birth_time

Type float in [-inf, inf], default 0.0

die_time

Type float in [-inf, inf], default 0.0

hair

Type Collection of ParticleHairKey, (readonly)

is_exist

Type boolean, default False, (readonly)

is_visible

Type boolean, default False, (readonly)

keys

Type Collection of ParticleKey, (readonly)

lifetime

Type float in [-inf, inf], default 0.0

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

prev_angular_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

prev_location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

prev_rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

prev_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

size

Type float in [-inf, inf], default 0.0

velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.particles

1.4.379 ParticleBrush(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleBrush**(*bpy_struct*)

Particle editing brush

count

Particle count

Type int in [1, 1000], default 0

curve

Type CurveMapping, (readonly)

length_mode

Type enum in ['GROW', 'SHRINK'], default 'GROW'

puff_mode

Type enum in ['ADD', 'SUB'], default 'ADD'

size

Brush size

Type int in [1, 32767], default 0

steps

Brush steps

Type int in [1, 32767], default 0

strength

Brush strength

Type float in [0.001, 1], default 0.0

use_puff_volume

Apply puff to unselected end-points, (helps maintain hair volume when puffing root)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleEdit.brush

1.4.380 ParticleDupliWeight(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleDupliWeight** (*bpy_struct*)

Weight of a particle dupliobject in a group

count

The number of times this object is repeated with respect to other objects

Type int in [0, 32767], default 0

name

Particle dupliobject name

Type string, default “”, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSettings.active_dupliweight
- ParticleSettings.dupli_weights

1.4.381 ParticleEdit(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleEdit**(*bpy_struct*)

Properties of particle editing mode

brush

Type ParticleBrush, (readonly)

default_key_count

How many keys to make new particles with

Type int in [2, 32767], default 0

draw_step

How many steps to draw the path with

Type int in [2, 10], default 0

emitter_distance

Distance to keep particles away from the emitter

Type float in [0, inf], default 0.0

fade_frames

How many frames to fade

Type int in [2, 100], default 0

is_editable

A valid edit mode exists

Type boolean, default False, (readonly)

is_hair

Editing hair

Type boolean, default False, (readonly)

object
The edited object

Type Object, (readonly)

select_mode
Particle select and display mode

Type enum in ['PATH', 'POINT', 'TIP'], default 'PATH'

show_particles
Draw actual particles

Type boolean, default False

tool

Type enum in ['NONE', 'COMB', 'SMOOTH', 'ADD', 'LENGTH', 'PUFF', 'CUT', 'WEIGHT'], default 'COMB'

type

Type enum in ['PARTICLES', 'SOFT_BODY', 'CLOTH'], default 'PARTICLES'

use_auto_velocity
Calculate point velocities automatically

Type boolean, default False

use_default_interpolate
Interpolate new particles from the existing ones

Type boolean, default False

use_emitter_deflect
Keep paths from intersecting the emitter

Type boolean, default False

use_fade_time
Fade paths and keys further away from current frame

Type boolean, default False

use_preserve_length
Keep path lengths constant

Type boolean, default False

use_preserve_root
Keep root keys unmodified

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.particle_edit

1.4.382 ParticleFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.**ParticleFluidSettings** (*FluidSettings*)

Fluid simulation settings for objects storing fluid particles generated by the simulation

alpha_influence

Amount of particle alpha change, inverse of size influence: 0=off (all same alpha), 1=full. (large particles get lower alphas, smaller ones higher values)

Type float in [0, 2], default 0.0

filepath

Directory (and/or filename prefix) to store and load particles from

Type string, default “”

particle_influence

Amount of particle size scaling: 0=off (all same size), 1=full (range 0.2-2.0), >1=stronger

Type float in [0, 2], default 0.0

show_tracer

Show tracer particles

Type boolean, default False

use_drops

Show drop particles

Type boolean, default False

use_floats

Show floating foam particles

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.383 ParticleHairKey(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleHairKey**(*bpy_struct*)

Particle key for hair particle system

co

Location of the hair key in object space

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

co_hair_space

Location of the hair key in its internal coordinate system, relative to the emitting face

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

time

Relative time of key over hair length

Type float in [0, inf], default 0.0

weight

Weight for cloth simulation

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Particle.hair

1.4.384 ParticleInstanceModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ParticleInstanceModifier**(*Modifier*)

Particle system instancing modifier

axis

Pole axis for rotation

Type enum in ['X', 'Y', 'Z'], default 'X'

object

Object that has the particle system

Type Object

particle_system_index

Type int in [1, 10], default 0

position

Position along path

Type float in [0, 1], default 0.0

random_position

Randomize position along path

Type float in [0, 1], default 0.0

show_alive

Show instances when particles are alive

Type boolean, default False

show_dead
Show instances when particles are dead

Type boolean, default False

show_unborn
Show instances when particles are unborn

Type boolean, default False

use_children
Create instances from child particles

Type boolean, default False

use_normal
Create instances from normal particles

Type boolean, default False

use_path
Create instances along particle paths

Type boolean, default False

use_preserve_shape
Don't stretch the object

Type boolean, default False

use_size
Use particle size to scale the instances

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.385 ParticleKey(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleKey**(*bpy_struct*)

Key location for a particle over time

angular_velocity

Key angular velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

location

Key location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation

Key rotation quaterion

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

time

Time of key over the simulation

Type float in [0, inf], default 0.0

velocity

Key velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Particle.keys

1.4.386 ParticleSettings(ID)

base classes — bpy_struct, ID

class bpy.types.**ParticleSettings**(*ID*)

Particle settings, reusable by multiple particle systems

active_dupliweight

Type ParticleDupliWeight, (readonly)

active_dupliweight_index

Type int in [0, inf], default 0

active_texture

Active texture slot being displayed

Type Texture

active_texture_index

Index of active texture slot

Type int in [0, 17], default 0

adaptive_angle

How many degrees path has to curve to make another render segment

Type int in [0, 45], default 0

adaptive_pixel

How many pixels path has to cover to make another render segment

Type int in [0, 50], default 0

angular_velocity_factor

Angular velocity amount

Type float in [-200, 200], default 0.0

angular_velocity_mode

Particle angular velocity mode

Type enum in ['NONE', 'SPIN', 'RAND'], default 'NONE'

animation_data

Animation data for this datablock

Type AnimData, (readonly)

apply_effector_to_children

Apply effectors to children

Type boolean, default False

apply_guide_to_children

Type boolean, default False

billboard_align
In respect to what the billboards are aligned

Type enum in ['X', 'Y', 'Z', 'VIEW', 'VEL'], default 'X'

billboard_animation
How to animate billboard textures

Type enum in ['NONE', 'AGE', 'FRAME', 'ANGLE'], default 'NONE'

billboard_object
Billboards face this object (default is active camera)

Type `Object`

billboard_offset

Type float array of 2 items in [-100, 100], default (0.0, 0.0)

billboard_offset_split
How to offset billboard textures

Type enum in ['NONE', 'LINEAR', 'RANDOM'], default 'NONE'

billboard_tilt
Tilt of the billboards

Type float in [-1, 1], default 0.0

billboard_tilt_random
Random tilt of the billboards

Type float in [0, 1], default 0.0

billboard_uv_split
Amount of rows/columns to split UV coordinates for billboards

Type int in [1, 100], default 0

boids

Type `BoidSettings`, (readonly)

branch_threshold
Threshold of branching

Type float in [0, 1], default 0.0

brownian_factor
Specify the amount of Brownian motion

Type float in [0, 200], default 0.0

child_length
Length of child paths

Type float in [0, 1], default 0.0

child_length_threshold
Amount of particles left untouched by child path length

Type float in [0, 1], default 0.0

child_nbr
Amount of children/parent

Type int in [0, 100000], default 0

child_parting_factor
Create parting in the children based on parent strands

Type float in [0, 1], default 0.0

child_parting_max
Maximum root to tip angle (tip distance/root distance for long hair)

Type float in [0, 180], default 0.0

child_parting_min
Minimum root to tip angle (tip distance/root distance for long hair)

Type float in [0, 180], default 0.0

child_radius
Radius of children around parent

Type float in [0, 10], default 0.0

child_roundness
Roundness of children around parent

Type float in [0, 1], default 0.0

child_size
A multiplier for the child particle size

Type float in [0.001, 100000], default 0.0

child_size_random
Random variation to the size of the child particles

Type float in [0, 1], default 0.0

child_type
Create child particles

Type enum in ['NONE', 'SIMPLE', 'INTERPOLATED'], default 'NONE'

clump_factor
Amount of clumping

Type float in [-1, 1], default 0.0

clump_shape
Shape of clumping

Type float in [-0.999, 0.999], default 0.0

color_maximum
Maximum length of the particle color vector

Type float in [0.01, 100], default 0.0

count
Total number of particles

Type int in [0, 10000000], default 0

create_long_hair_children
Calculate children that suit long hair well

Type boolean, default False

damping
Specify the amount of damping

Type float in [0, 1], default 0.0

distribution
How to distribute particles on selected element

Type enum in ['NONE', 'RENDER', 'DOT', 'CIRC', 'CROSS', 'AXIS'], default 'NONE'

drag_factor
Specify the amount of air-drag

Type float in [0, 1], default 0.0

draw_color
Draw additional particle data as a color

Type enum in ['NONE', 'MATERIAL', 'VELOCITY', 'ACCELERATION'], default 'NONE'

draw_method
How particles are drawn in viewport

Type enum in ['NONE', 'RENDER', 'DOT', 'CIRC', 'CROSS', 'AXIS'], default 'NONE'

draw_percentage
Percentage of particles to display in 3D view

Type int in [0, 100], default 0

draw_size
Size of particles on viewport in pixels (0=default)

Type int in [0, 1000], default 0

draw_step
How many steps paths are drawn with (power of 2)

Type int in [0, 7], default 0

dupli_group
Show Objects in this Group in place of particles

Type `Group`

dupli_object
Show this Object in place of particles

Type `Object`

dupli_weights
Weights for all of the objects in the dupli group

Type Collection of `ParticleDupliWeight`, (readonly)

effect_hair
Hair stiffness for effectors

Type float in [0, 1], default 0.0

effector_amount
How many particles are effectors (0 is all particles)

Type int in [0, 10000], default 0

effector_weights

Type EffectorWeights, (readonly)

emit_from
Where to emit particles from

Type enum in ['VERT', 'FACE', 'VOLUME'], default 'VERT'

factor_random
Give the starting speed a random variation

Type float in [0, 200], default 0.0

fluid

Type SPHFluidSettings, (readonly)

force_field_1

Type FieldSettings, (readonly)

force_field_2

Type FieldSettings, (readonly)

frame_end
Frame # to stop emitting particles

Type float in [-300000, 300000], default 0.0

frame_start
Frame # to start emitting particles

Type float in [-300000, 300000], default 0.0

grid_random
Add random offset to the grid locations

Type float in [0, 1], default 0.0

grid_resolution
The resolution of the particle grid

Type int in [1, 250], default 0

hair_length
Length of the hair

Type float in [0, 1000], default 0.0

hair_step
Number of hair segments

Type int in [2, 50], default 0

hexagonal_grid
Create the grid in a hexagonal pattern

Type boolean, default False

integrator
Select physics integrator type

Type enum in ['EULER', 'VERLET', 'MIDPOINT', 'RK4'], default 'EULER'

invert_grid
Invert what is considered object and what is not

Type boolean, default False

is_fluid
Particles were created by a fluid simulation

Type boolean, default False, (readonly)

jitter_factor
Amount of jitter applied to the sampling

Type float in [0, 2], default 0.0

keyed_loops
Number of times the keys are looped

Type int in [1, 10000], default 0

keys_step

Type int in [0, 32767], default 0

kink
Type of periodic offset on the path

Type enum in ['NO', 'CURL', 'RADIAL', 'WAVE', 'BRAID'], default 'NO'

kink_amplitude
The amplitude of the offset

Type float in [-100000, 100000], default 0.0

kink_amplitude_clump
How much clump effects kink amplitude

Type float in [0, 1], default 0.0

kink_axis
Which axis to use for offset

Type enum in ['X', 'Y', 'Z'], default 'X'

kink_flat
How flat the hairs are

Type float in [0, 1], default 0.0

kink_frequency
The frequency of the offset (1/total length)

Type float in [-100000, 100000], default 0.0

kink_shape
Adjust the offset to the beginning/end

Type float in [-0.999, 0.999], default 0.0

length_random
Give path length a random variation

Type float in [0, 1], default 0.0

lifetime
Specify the life span of the particles

Type float in [1, 300000], default 0.0

lifetime_random
Give the particle life a random variation

Type float in [0, 1], default 0.0

line_length_head
Length of the line's head

Type float in [0, 100000], default 0.0

line_length_tail
Length of the line's tail

Type float in [0, 100000], default 0.0

lock_billboard
Lock the billboards align axis

Type boolean, default False

lock_boids_to_surface
Constrain boids to a surface

Type boolean, default False

mass
Specify the mass of the particles

Type float in [0.001, 100000], default 0.0

material
Specify material used for the particles

Type int in [1, 16], default 0

normal_factor
Let the surface normal give the particle a starting speed

Type float in [-1000, 1000], default 0.0

object_align_factor
Let the emitter object orientation give the particle a starting speed

Type float array of 3 items in [-200, 200], default (0.0, 0.0, 0.0)

object_factor
Let the object give the particle a starting speed

Type float in [-200, 200], default 0.0

particle_factor
Let the target particle give the particle a starting speed

Type float in [-200, 200], default 0.0

particle_size
The size of the particles

Type float in [0.001, 100000], default 0.0

path_end
End time of drawn path

Type float in [-inf, inf], default 0.0

path_start
Starting time of drawn path

Type float in [-inf, inf], default 0.0

phase_factor
Initial rotation phase

Type float in [-1, 1], default 0.0

phase_factor_random
Randomize rotation phase

Type float in [0, 1], default 0.0

physics_type
Particle physics type

Type enum in ['NO', 'NEWTON', 'KEYED', 'BOIDS', 'FLUID'], default 'NO'

react_event
The event of target particles to react on

Type enum in ['DEATH', 'COLLIDE', 'NEAR'], default 'DEATH'

reactor_factor
Let the vector away from the target particles location give the particle a starting speed

Type float in [-10, 10], default 0.0

regrow_hair
Regrow hair for each frame

Type boolean, default False

render_step
How many steps paths are rendered with (power of 2)

Type int in [0, 9], default 0

render_type
How particles are rendered

Type enum in ['NONE', 'HALO', 'LINE', 'PATH', 'OBJECT', 'GROUP', 'BILLBOARD'], default 'NONE'

rendered_child_count
Amount of children/parent for rendering

Type int in [0, 100000], default 0

rotation_factor_random
Randomize rotation

Type float in [0, 1], default 0.0

rotation_mode
Particles initial rotation

Type enum in ['NONE', 'NOR', 'VEL', 'GLOB_X', 'GLOB_Y', 'GLOB_Z', 'OB_X', 'OB_Y', 'OB_Z'], default 'NONE'

roughness_1
Amount of location dependent rough

Type float in [0, 100000], default 0.0

roughness_1_size
Size of location dependent rough

Type float in [0.01, 100000], default 0.0

roughness_2
Amount of random rough

Type float in [0, 100000], default 0.0

roughness_2_size
Size of random rough

Type float in [0.01, 100000], default 0.0

roughness_2_threshold
Amount of particles left untouched by random rough

Type float in [0, 1], default 0.0

roughness_end_shape
Shape of end point rough

Type float in [0, 10], default 0.0

roughness_endpoint
Amount of end point rough

Type float in [0, 100000], default 0.0

show_health
Draw boid health

Type boolean, default False

show_number
Show particle number

Type boolean, default False

show_size
Show particle size

Type boolean, default False

show_unborn
Show particles before they are emitted

Type boolean, default False

show_velocity
Show particle velocity

Type boolean, default False

simplify_rate
Speed of simplification

Type float in [0, 1], default 0.0

simplify_refsize
Reference size in pixels, after which simplification begins

Type int in [1, 32768], default 0

simplify_transition
Transition period for fading out strands

Type float in [0, 1], default 0.0

simplify_viewport
Speed of Simplification

Type float in [0, 0.999], default 0.0

size_random
Give the particle size a random variation

Type float in [0, 1], default 0.0

subframes
Subframes to simulate for improved stability and finer granularity simulations

Type int in [0, 1000], default 0

tangent_factor
Let the surface tangent give the particle a starting speed

Type float in [-1000, 1000], default 0.0

tangent_phase
Rotate the surface tangent

Type float in [-1, 1], default 0.0

texture_slots
Texture slots defining the mapping and influence of textures

Type `ParticleSettingsTextureSlots` collection of `ParticleSettingsTextureSlot`, (readonly)

time_tweak
A multiplier for physics timestep (1.0 means one frame = 1/25 seconds)

Type float in [0, 100], default 0.0

trail_count
Number of trail particles

Type int in [1, 100000], default 0

type

Type enum in ['EMITTER', 'HAIR'], default 'EMITTER'

use_absolute_path_time
Path timing is in absolute frames

Type boolean, default False

use_advanced_hair
Use full physics calculations for growing hair

Type boolean, default False

use_dead
Show particles after they have died

Type boolean, default False

use_die_on_collision
Particles die when they collide with a deflector object

Type boolean, default False

use_dynamic_rotation
Sets rotation to dynamic/constant

Type boolean, default False

use_emit_random
Emit in random order of elements

Type boolean, default False

use_even_distribution
Use even distribution from faces based on face areas or edge lengths

Type boolean, default False

use_global_dupli
Use object's global coordinates for duplication

Type boolean, default False

use_group_count
Use object multiple times in the same group

Type boolean, default False

use_group_pick_random
Pick objects from group randomly

Type boolean, default False

use_hair_bspline
Interpolate hair using B-Splines

Type boolean, default False

use_multiply_size_mass
Multiply mass by particle size

Type boolean, default False

use_parent_particles
Render parent particles

Type boolean, default False

use_react_multiple
React multiple times

Type boolean, default False

use_react_start_end
Give birth to unreacted particles eventually

Type boolean, default False

use_render_adaptive
Draw steps of the particle path

Type boolean, default False

use_render_emitter
Render emitter Object also

Type boolean, default False

use_self_effect
Particle effectors effect themselves

Type boolean, default False

use_simplify
Remove child strands as the object becomes smaller on the screen

Type boolean, default False

use_simplify_viewport

Type boolean, default False

use_size_deflect
Use particle's size in deflection

Type boolean, default False

use_strand_primitive
Use the strand primitive for rendering

Type boolean, default False

use_velocity_length
Multiply line length by particle speed

Type boolean, default False

use_whole_group
Use whole group at once

Type boolean, default False

userjit
Emission locations / face (0 = automatic)

Type int in [0, 1000], default 0

virtual_parents
Relative amount of virtual parents

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.particles
- BlendDataParticles.new
- BlendDataParticles.remove
- ParticleSystem.settings

1.4.387 ParticleSettingsTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.**ParticleSettingsTextureSlot**(*TextureSlot*)

Texture slot for textures in a Particle Settings datablock

clump_factor

Amount texture affects child clump

Type float in [-inf, inf], default 0.0

damp_factor

Amount texture affects particle damping

Type float in [-inf, inf], default 0.0

density_factor

Amount texture affects particle density

Type float in [-inf, inf], default 0.0

field_factor

Amount texture affects particle force fields

Type float in [-inf, inf], default 0.0

gravity_factor

Amount texture affects particle gravity

Type float in [-inf, inf], default 0.0

kink_factor

Amount texture affects child kink

Type float in [-inf, inf], default 0.0

length_factor

Amount texture affects child hair length

Type float in [-inf, inf], default 0.0

life_factor
Amount texture affects particle life time

Type float in [-inf, inf], default 0.0

mapping

Type enum in ['FLAT', 'CUBE', 'TUBE', 'SPHERE'], default 'FLAT'

mapping_x

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_y

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_z

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

object
Object to use for mapping with Object texture coordinates

Type `Object`

rough_factor
Amount texture affects child roughness

Type float in [-inf, inf], default 0.0

size_factor
Amount texture affects physical particle size

Type float in [-inf, inf], default 0.0

texture_coords
Texture coordinates used to map the texture onto the background

Type enum in ['GLOBAL', 'OBJECT', 'UV', 'ORCO', 'STRAND'], default 'GLOBAL'

time_factor
Amount texture affects particle emission time

Type float in [-inf, inf], default 0.0

use_map_clump
Affect the child clumping

Type boolean, default False

use_map_damp
Affect the particle velocity damping

Type boolean, default False

use_map_density
Affect the density of the particles

Type boolean, default False

use_map_field
Affect the particle force fields

Type boolean, default False

use_map_gravity
Affect the particle gravity

Type boolean, default False

use_map_kink
Affect the child kink

Type boolean, default False

use_map_length
Affect the child hair length

Type boolean, default False

use_map_life
Affect the life time of the particles

Type boolean, default False

use_map_rough
Affect the child rough

Type boolean, default False

use_map_size
Affect the particle size

Type boolean, default False

use_map_time
Affect the emission time of the particles

Type boolean, default False

use_map_velocity
Affect the particle initial velocity

Type boolean, default False

uv_layer
UV layer to use for mapping with UV texture coordinates

Type string, default ""

velocity_factor
Amount texture affects particle initial velocity

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSettings.texture_slots
- ParticleSettingsTextureSlots.add
- ParticleSettingsTextureSlots.create

1.4.388 ParticleSettingsTextureSlots(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleSettingsTextureSlots**(*bpy_struct*)

Collection of texture slots

classmethod add()

add

Returns The newly initialized mtex.

Return type ParticleSettingsTextureSlot

classmethod create(*index*)

create

Parameters **index** (*int in [0, inf]*) – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type ParticleSettingsTextureSlot

classmethod clear(*index*)

clear

Parameters **index** (*int in [0, inf]*) – Index, Slot index to clear.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSettings.texture_slots

1.4.389 ParticleSystem(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleSystem**(*bpy_struct*)

Particle system in an object

active_particle_target

Type ParticleTarget, (readonly)

active_particle_target_index

Type int in [0, inf], default 0

billboard_normal_uv

UV Layer to control billboard normals

Type string, default ""

billboard_split_uv

UV Layer to control billboard splitting

Type string, default ""

billboard_time_index_uv

UV Layer to control billboard time index (X-Y)

Type string, default ""

child_particles

Child particles generated by the particle system

Type Collection of ChildParticle, (readonly)

child_seed
Offset in the random number table for child particles, to get a different randomized result

Type int in [0, inf], default 0

cloth
Cloth dynamics for hair

Type `ClothModifier`, (readonly, never None)

has_multiple_caches
Particle system has multiple point caches

Type boolean, default False, (readonly)

invert_vertex_group_clump
Negate the effect of the clump vertex group

Type boolean, default False

invert_vertex_group_density
Negate the effect of the density vertex group

Type boolean, default False

invert_vertex_group_field
Negate the effect of the field vertex group

Type boolean, default False

invert_vertex_group_kink
Negate the effect of the kink vertex group

Type boolean, default False

invert_vertex_group_length
Negate the effect of the length vertex group

Type boolean, default False

invert_vertex_group_rotation
Negate the effect of the rotation vertex group

Type boolean, default False

invert_vertex_group_roughness_1
Negate the effect of the roughness 1 vertex group

Type boolean, default False

invert_vertex_group_roughness_2
Negate the effect of the roughness 2 vertex group

Type boolean, default False

invert_vertex_group_roughness_end
Negate the effect of the roughness end vertex group

Type boolean, default False

invert_vertex_group_size
Negate the effect of the size vertex group

Type boolean, default False

invert_vertex_group_tangent
Negate the effect of the tangent vertex group

Type boolean, default False

invert_vertex_group_velocity
Negate the effect of the velocity vertex group

Type boolean, default False

is_editable
Particle system can be edited in particle mode

Type boolean, default False, (readonly)

is_edited
Particle system has been edited in particle mode

Type boolean, default False, (readonly)

is_global_hair
Hair keys are in global coordinate space

Type boolean, default False, (readonly)

name
Particle system name

Type string, default “”

parent
Use this object’s coordinate system instead of global coordinate system

Type `Object`

particles
Particles generated by the particle system

Type Collection of `Particle`, (readonly)

point_cache

Type `PointCache`, (readonly, never None)

reactor_target_object
For reactor systems, the object that has the target particle system (empty if same object)

Type `Object`

reactor_target_particle_system
For reactor systems, index of particle system on the target object

Type int in [1, 32767], default 0

seed
Offset in the random number table, to get a different randomized result

Type int in [0, inf], default 0

settings
Particle system settings

Type `ParticleSettings`, (never None)

targets
Target particle systems

Type Collection of `ParticleTarget`, (readonly)

use_hair_dynamics
Enable hair dynamics using cloth simulation

Type boolean, default False

use_keyed_timing
Use key times

Type boolean, default False

vertex_group_clump
Vertex group to control clump

Type string, default “”

vertex_group_density
Vertex group to control density

Type string, default “”

vertex_group_field
Vertex group to control field

Type string, default “”

vertex_group_kink
Vertex group to control kink

Type string, default “”

vertex_group_length
Vertex group to control length

Type string, default “”

vertex_group_rotation
Vertex group to control rotation

Type string, default “”

vertex_group_roughness_1
Vertex group to control roughness 1

Type string, default “”

vertex_group_roughness_2
Vertex group to control roughness 2

Type string, default “”

vertex_group_roughness_end
Vertex group to control roughness end

Type string, default “”

vertex_group_size
Vertex group to control size

Type string, default “”

vertex_group_tangent
Vertex group to control tangent

Type string, default “”

vertex_group_velocity
Vertex group to control velocity

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.particle_systems
- ParticleSystemModifier.particle_system
- ParticleSystems.active
- PointDensity.particle_system
- SmokeFlowSettings.particle_system

1.4.390 ParticleSystemModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ParticleSystemModifier**(*Modifier*)

Particle system simulation modifier

particle_system

Particle System that this modifier controls

Type ParticleSystem, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode

- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.391 ParticleSystems(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleSystems**(*bpy_struct*)

Collection of particle systems

active

Active particle system being displayed

Type ParticleSystem, (readonly)

active_index

Index of active particle system slot

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.particle_systems

1.4.392 ParticleTarget(bpy_struct)

base class — bpy_struct

class bpy.types.**ParticleTarget** (*bpy_struct*)

Target particle system

alliance

Type enum in ['FRIEND', 'NEUTRAL', 'ENEMY'], default 'NEUTRAL'

duration

Type float in [0, 30000], default 0.0

is_valid

Keyed particles target is valid

Type boolean, default False

name

Particle target name

Type string, default "", (readonly)

object

The object that has the target particle system (empty if same object)

Type Object

system

The index of particle system on the target object

Type int in [1, inf], default 0

time

Type float in [0, 30000], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.active_particle_target
- ParticleSystem.targets

1.4.393 PivotConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**PivotConstraint**(*Constraint*)

Rotate around a different point

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

offset

Offset of pivot from target (when set), or from owner's location (when Fixed Position is off), or the absolute pivot point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_range

Rotation range on which pivoting should occur

Type enum in ['ALWAYS_ACTIVE', 'NX', 'NY', 'NZ', 'X', 'Y', 'Z'], default 'NX'

subtarget

Type string, default ""

target

Target Object, defining the position of the pivot when defined

Type Object

use_relative_location

Offset will be an absolute point in space instead of relative to the target

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.394 PluginSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.**PluginSequence**(*EffectSequence*)

Sequence strip applying an effect, loaded from an external plugin

filename

Type string, default "", (readonly)

Inherited Properties

- bpy_struct.id_data
- Sequence.name

- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.395 PluginTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**PluginTexture** (*Texture*)

External plugin texture

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.396 PointCache(bpy_struct)

base class — bpy_struct

class bpy.types.**PointCache**(*bpy_struct*)

Point cache for physics simulations

compression

Compression method to be used

Type enum in ['NO', 'LIGHT', 'HEAVY'], default 'NO'

filepath

Cache file path

Type string, default ""

frame_end

Frame on which the simulation stops

Type int in [1, 300000], default 0

frame_start

Frame on which the simulation starts

Type int in [1, 300000], default 0

frame_step

Number of frames between cached frames

Type int in [1, 20], default 0

frames_skipped

Type boolean, default False, (readonly)

index
Index number of cache files

Type int in [-1, 100], default 0

info
Info on current cache status

Type string, default "", (readonly)

is_baked

Type boolean, default False, (readonly)

is_baking

Type boolean, default False, (readonly)

is_outdated

Type boolean, default False, (readonly)

name
Cache name

Type string, default ""

point_caches
Point cache list

Type PointCaches collection of PointCache, (readonly)

use_disk_cache
Save cache files to disk (.blend file must be saved first)

Type boolean, default False

use_external
Read cache from an external location

Type boolean, default False

use_library_path
Use this files path when library linked into another file.

Type boolean, default False

use_quick_cache
Update simulation with cache steps

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothModifier.point_cache
- ParticleSystem.point_cache
- PointCache.point_caches
- SmokeDomainSettings.point_cache
- SoftBodyModifier.point_cache

1.4.397 PointCaches(bpy_struct)

base class — bpy_struct

class bpy.types.**PointCaches**(*bpy_struct*)

Collection of point caches

active_index

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

References

- PointCache.point_caches

1.4.398 PointDensity(bpy_struct)

base class — bpy_struct

class bpy.types.**PointDensity**(*bpy_struct*)

Point density settings

color_ramp

Type ColorRamp, (readonly)

color_source

Data to derive color results from

Type enum in ['CONSTANT', 'PARTICLE_AGE', 'PARTICLE_SPEED', 'PARTICLE_VELOCITY'], default 'CONSTANT'

falloff

Method of attenuating density by distance from the point

Type enum in ['STANDARD', 'SMOOTH', 'SOFT', 'CONSTANT', 'ROOT'], default 'STANDARD'

falloff_soft

Softness of the 'soft' falloff option

Type float in [0.01, inf], default 0.0

noise_basis

Noise formula used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

object

Object to take point data from

Type Object

particle_cache_space

Co-ordinate system to cache particles in

Type enum in ['OBJECT_LOCATION', 'OBJECT_SPACE', 'WORLD_SPACE'], default 'OBJECT_LOCATION'

particle_system

Particle System to render as points

Type ParticleSystem

point_source

Point data to use as renderable point density

Type enum in ['PARTICLE_SYSTEM', 'OBJECT'], default 'PARTICLE_SYSTEM'

radius
Radius from the shaded sample to look for points within

Type float in [0.001, inf], default 0.0

speed_scale
Multiplier to bring particle speed within an acceptable range

Type float in [0.001, 100], default 0.0

turbulence_depth
Level of detail in the added turbulent noise

Type int in [0, 30], default 0

turbulence_influence
Method for driving added turbulent noise

Type enum in ['STATIC', 'PARTICLE_VELOCITY', 'PARTICLE_AGE', 'GLOBAL_TIME'], default 'STATIC'

turbulence_scale
Scale of the added turbulent noise

Type float in [0.01, inf], default 0.0

turbulence_strength

Type float in [0.01, inf], default 0.0

use_turbulence
Add directed noise to the density at render-time

Type boolean, default False

vertex_cache_space
Co-ordinate system to cache vertices in

Type enum in ['OBJECT_LOCATION', 'OBJECT_SPACE', 'WORLD_SPACE'], default 'OBJECT_LOCATION'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PointDensityTexture.point_density

1.4.399 PointDensityTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**PointDensityTexture**(*Texture*)

Settings for the Point Density texture

point_density

The point density settings associated with this texture

Type PointDensity, (readonly)

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.400 PointLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.**PointLamp**(*Lamp*)

Omnidirectional point lamp

falloff_curve

Custom Lamp Falloff Curve

Type CurveMapping, (readonly)

falloff_type

Intensity Decay with distance

Type enum in ['CONSTANT', 'INVERSE_LINEAR', 'INVERSE_SQUARE', 'CUSTOM_CURVE', 'LINEAR_QUADRATIC_WEIGHTED'], default 'CONSTANT'

linear_attenuation

Linear distance attenuation

Type float in [0, 1], default 0.0

quadratic_attenuation

Quadratic distance attenuation

Type float in [0, 1], default 0.0

shadow_adaptive_threshold

Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method
Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method
Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples
Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size
Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

use_only_shadow
Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer
Causes only objects on the same layer to cast shadows

Type boolean, default False

use_sphere
Sets light intensity to zero beyond lamp distance

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.401 PointerProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**PointerProperty**(*Property*)

RNA pointer property to point to another RNA struct

fixed_type

Fixed pointer type, empty if variable type

Type Struct, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype

- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.402 Pose(bpy_struct)

base class — bpy_struct

class bpy.types.**Pose**(*bpy_struct*)

A collection of pose channels, including settings for animating bones

animation_visualisation

Animation data for this datablock

Type AnimViz, (readonly, never None)

bone_groups

Groups of the bones

Type BoneGroups collection of BoneGroup, (readonly)

bones

Individual pose bones for the armature

Type Collection of PoseBone, (readonly)

ik_param

Parameters for IK solver

Type IKParam, (readonly)

ik_solver

Selection of IK solver for IK chain, current choice is 0 for Legacy, 1 for iTaSC

Type enum in ['LEGACY', 'ITASC'], default 'LEGACY'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.pose

1.4.403 PoseBone(bpy_struct)

base class — bpy_struct

class bpy.types.**PoseBone** (*bpy_struct*)

Channel defining pose data for a bone in a Pose

bone

Bone associated with this PoseBone

Type Bone, (readonly, never None)

bone_group

Bone Group this pose channel belongs to

Type BoneGroup

bone_group_index

Bone Group this pose channel belongs to (0=no group)

Type int in [-32768, 32767], default 0

child

Child of this pose bone

Type PoseBone, (readonly)

constraints

Constraints that act on this PoseChannel

Type PoseBoneConstraints collection of Constraint, (readonly)

custom_shape

Object that defines custom draw type for this bone

Type Object

custom_shape_transform
Bone that defines the display transform of this custom shape

Type PoseBone

head
Location of head of the channel's bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

ik_linear_weight
Weight of scale constraint for IK

Type float in [0, 1], default 0.0

ik_max_x
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_max_y
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_max_z
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_min_x
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_min_y
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_min_z
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_rotation_weight
Weight of rotation constraint for IK

Type float in [0, 1], default 0.0

ik_stiffness_x
IK stiffness around the X axis

Type float in [0, 0.99], default 0.0

ik_stiffness_y
IK stiffness around the Y axis

Type float in [0, 0.99], default 0.0

ik_stiffness_z
IK stiffness around the Z axis

Type float in [0, 0.99], default 0.0

ik_stretch
Allow scaling of the bone for IK

Type float in [0, 1], default 0.0

is_in_ik_chain
Is part of an IK chain

Type boolean, default False, (readonly)

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lock_ik_x
Disallow movement around the X axis

Type boolean, default False

lock_ik_y
Disallow movement around the Y axis

Type boolean, default False

lock_ik_z
Disallow movement around the Z axis

Type boolean, default False

lock_location
Lock editing of location in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation
Lock editing of rotation in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation_w
Lock editing of 'angle' component of four-component rotations in the interface

Type boolean, default False

lock_rotations_4d
Lock editing of four component rotations by components (instead of as Eulers)

Type boolean, default False

lock_scale
Lock editing of scale in the interface

Type boolean array of 3 items, default (False, False, False)

matrix
Final 4x4 matrix for this channel

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

matrix_basis
Provides an alternative access to loc/scale/rotation relative to the parent and own rest bone.

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_channel
4x4 matrix, before constraints

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

motion_path
Motion Path for this element

Type `MotionPath`, (readonly)

name

Type string, default ""

parent
Parent of this pose bone

Type `PoseBone`, (readonly)

rotation_axis_angle
Angle of Rotation for Axis-Angle rotation representation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 1.0, 0.0)

rotation_euler
Rotation in Eulers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_mode

Type enum in ['QUATERNION', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX', 'AXIS_ANGLE'], default 'QUATERNION'

rotation_quaternion
Rotation in Quaternions

Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

scale

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

tail
Location of tail of the channel's bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

use_ik_limit_x
Limit movement around the X axis

Type boolean, default False

use_ik_limit_y
Limit movement around the Y axis

Type boolean, default False

use_ik_limit_z
Limit movement around the Z axis

Type boolean, default False

use_ik_linear_control
Apply channel size as IK constraint if stretching is enabled

Type boolean, default False

use_ik_rotation_control
Apply channel rotation as IK constraint

Type boolean, default False

basename
The name of this bone before any '.' character (readonly)

center
The midpoint between the head and the tail. (readonly)

children
A list of all the bones children. (readonly)

children_recursive
a list of all children from this bone. (readonly)

children_recursive_basename
Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned.

(readonly)

length
The distance from head to tail, when set the head is moved to fit the length.

parent_recursive
A list of parents, starting with the immediate parent (readonly)

vector
The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis
Vector pointing down the x-axis of the bone.

(readonly)

y_axis
Vector pointing down the x-axis of the bone.

(readonly)

z_axis
Vector pointing down the x-axis of the bone.

(readonly)

evaluate_envelope (*point*)
Calculate bone envelope at given point.

Parameters **point** (*float array of 3 items in [-inf, inf]*) – Point, Position in 3d space to evaluate

Returns Factor, Envelope factor

Return type float in [-inf, inf]

parent_index (*parent_test*)
The same as 'bone in other_bone.parent_recursive' but saved generating a list.

translate (*vec*)
Utility function to add *vec* to the head and tail of this bone.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Pose.bones
- PoseBone.child
- PoseBone.custom_shape_transform
- PoseBone.parent

1.4.404 PoseBoneConstraints(bpy_struct)

base class — bpy_struct

class bpy.types.**PoseBoneConstraints**(*bpy_struct*)

Collection of pose bone constraints

active

Active PoseChannel constraint

Type Constraint

new(*type*)

Add a constraint to this object

Parameters **type** (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP']*) – Constraint type to add.

Returns New constraint.

Return type Constraint

remove (*constraint*)
Remove a constraint from this object.

Parameters **constraint** (Constraint, (never None)) – Removed constraint.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PoseBone.constraints

1.4.405 Property(bpy_struct)

base class — bpy_struct

subclasses — PointerProperty, EnumProperty, IntProperty, CollectionProperty, BooleanProperty, FloatProperty, StringProperty

class bpy.types.**Property** (*bpy_struct*)
RNA property definition

description
Description of the property for tooltips

Type string, default “”, (readonly)

identifier
Unique name used in the code and scripting

Type string, default “”, (readonly)

is_enum_flag
True when multiple enums

Type boolean, default False, (readonly)

is_hidden
True when the property is hidden

Type boolean, default False, (readonly)

is_never_none
True when this value can't be set to None

Type boolean, default False, (readonly)

is_output
True when this property is an output value from an RNA function

Type boolean, default False, (readonly)

is_readonly
Property is editable through RNA

Type boolean, default False, (readonly)

is_registered
Property is registered as part of type registration

Type boolean, default False, (readonly)

is_registered_optional
Property is optionally registered as part of type registration

Type boolean, default False, (readonly)

is_required
False when this property is an optional argument in an RNA function

Type boolean, default False, (readonly)

is_runtime
Property is editable through RNA

Type boolean, default False, (readonly)

name
Human readable name

Type string, default "", (readonly)

srna
Struct definition used for properties assigned to this item

Type `Struct`, (readonly)

subtype
Semantic interpretation of the property

Type enum in ['NONE', 'FILE_PATH', 'DIRECTORY_PATH', 'UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'COLOR', 'TRANSLATION', 'DIRECTION', 'MATRIX', 'EULER', 'QUATERNION', 'XYZ', 'COLOR_GAMMA', 'LAYER', 'LAYER_MEMBERSHIP'], default 'NONE', (readonly)

type
Data type of the property

Type enum in ['BOOLEAN', 'INT', 'FLOAT', 'STRING', 'ENUM', 'POINTER', 'COLLECTION'], default 'BOOLEAN', (readonly)

unit
Type of units for this property

Type enum in ['NONE', 'LENGTH', 'AREA', 'VOLUME', 'ROTATION', 'TIME', 'VELOCITY', 'ACCELERATION'], default 'NONE', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Function.parameters
- Struct.properties

1.4.406 PropertyActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**PropertyActuator**(*Actuator*)
Actuator to handle properties

mode

Type enum in ['ASSIGN', 'ADD', 'COPY', 'TOGGLE'], default 'ASSIGN'

object
Copy from this Object

Type Object

object_property
Copy this property

Type string, default “”

property
The name of the property

Type string, default “”

value
The name of the property or the value to use (use “” around strings)

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.407 PropertyGroup(bpy_struct)

Custom Properties

PropertyGroups are the base class for dynamically defined sets of properties.

They can be used to extend existing blender data with your own types which can be animated, accessed from the user interface and from python.

Note: The values assigned to blender data are saved to disk but the class definitions are not, this means whenever you load blender the class needs to be registered too.

This is best done by creating an addon which loads on startup and registers your properties.

Note: PropertyGroups must be registered before assigning them to blender data.

See Also:

Property types used in class declarations are all in `bpy.props`

```
import bpy


class MyPropertyGroup(bpy.types.PropertyGroup):
    custom_1 = bpy.props.FloatProperty(name="My Float")
    custom_2 = bpy.props.IntProperty(name="My Int")

bpy.utils.register_class(MyPropertyGroup)

bpy.types.Object.my_prop_grp = bpy.props.PointerProperty(type=MyPropertyGroup)


# test this worked
bpy.data.objects[0].my_prop_grp.custom_1 = 22.0
```

base class — `bpy_struct`

subclasses — `NetRenderSettings`, `OperatorFileListElement`, `NetRenderSlave`, `OperatorMousePath`, `NetRenderJob`, `OperatorStrokeElement`

class `bpy.types.`**`PropertyGroup`**(*bpy_struct*)

Group of ID properties

`name`

Unique name used in the code and scripting

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PropertyGroupItem.collection
- PropertyGroupItem.group
- PropertyGroupItem.idp_array

1.4.408 PropertyGroupItem(bpy_struct)

base class — bpy_struct

class bpy.types.**PropertyGroupItem**(*bpy_struct*)

Property that stores arbitrary, user defined properties

collection

Type Collection of PropertyGroup, (readonly)

double

Type float in [-inf, inf], default 0.0

double_array

Type float array of 1 items in [-inf, inf], default (0.0)

float

Type float in [-inf, inf], default 0.0

float_array

Type float array of 1 items in [-inf, inf], default (0.0)

group

Type PropertyGroup, (readonly)

idp_array

Type Collection of PropertyGroup, (readonly)

int

Type int in [-inf, inf], default 0

int_array

Type int array of 1 items in [-inf, inf], default (0,)

string

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.409 PropertySensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**PropertySensor**(*Sensor*)

Sensor to detect values and changes in values of properties

evaluation_type

Type of property evaluation

Type enum in ['PROPEQUAL', 'PROPNEQUAL', 'PROPINTERVAL', 'PROPCHANGED'], default 'PROPEQUAL'

property

Type string, default ""

value

Check for this value in types in Equal or Not Equal types

Type string, default ""

value_max

Specify maximum value in Interval type

Type string, default ""

value_min

Specify minimum value in Interval type

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.410 PythonConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**PythonConstraint**(*Constraint*)

Uses Python script for constraint evaluation

has_script_error

The linked Python script has thrown an error

Type boolean, default False, (readonly)

target_count

Usually only 1-3 are needed

Type int in [-inf, inf], default 0

targets

Target Objects

Type Collection of ConstraintTarget, (readonly)

text
The text object that contains the Python script

Type Text

use_targets
Use the targets indicated in the constraint panel

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.411 PythonController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**PythonController**(*Controller*)
Controller executing a python script

mode
Python script type (textblock or module - faster)

Type enum in ['SCRIPT', 'MODULE'], default 'SCRIPT'

module
Module name and function to run e.g. "someModule.main". Internal texts and external python files can be used

Type string, default ""

text
Text datablock with the python script

Type Text

use_debug
Continuously reload the module from disk for editing external modules without restarting

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.412 RGBANodeSocket(NodeSocket)

base classes — bpy_struct, NodeSocket

class bpy.types.**RGBANodeSocket** (*NodeSocket*)
Input or output socket of a node

default_value
Default value of the socket when no link is attached

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data
- NodeSocket.name
- NodeSocket.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.413 RadarSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**RadarSensor** (*Sensor*)
Sensor to detect objects in a cone shaped radar emanating from the current object

angle
Opening angle of the radar cone (in degrees)

Type float in [0, 179.9], default 0.0

axis
Specify along which axis the radar cone is cast

Type enum in ['XAXIS', 'YAXIS', 'ZAXIS', 'NEGXAXIS', 'NEGYAXIS', 'NEGZAXIS'], default 'XAXIS'

distance
Depth of the radar cone

Type float in [0, 10000], default 0.0

property
Only look for Objects with this property (blank = all objects)

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.414 RandomActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**RandomActuator**(*Actuator*)
Actuator to ..

chance
Pick a number between 0 and 1. Success if you stay below this value

Type float in [0, 1], default 0.0

distribution
Choose the type of distribution

Type enum in ['BOOL_CONSTANT', 'BOOL_UNIFORM', 'BOOL_BERNOUILLI', 'INT_CONSTANT', 'INT_UNIFORM', 'INT_POISSON', 'FLOAT_CONSTANT', 'FLOAT_UNIFORM', 'FLOAT_NORMAL', 'FLOAT_NEGATIVE_EXPONENTIAL'], default 'BOOL_CONSTANT'

float_max
Choose a number from a range. Upper boundary of the range

Type float in [-1000, 1000], default 0.0

float_mean
A normal distribution. Mean of the distribution

Type float in [-1000, 1000], default 0.0

float_min
Choose a number from a range. Lower boundary of the range

Type float in [-1000, 1000], default 0.0

float_value
Always return this number

Type float in [0, 1], default 0.0

half_life_time
Negative exponential dropoff

Type float in [-1000, 1000], default 0.0

int_max
Choose a number from a range. Upper boundary of the range

Type int in [-1000, 1000], default 0

int_mean
Expected mean value of the distribution

Type float in [0.01, 100], default 0.0

int_min
Choose a number from a range. Lower boundary of the range

Type int in [-1000, 1000], default 0

int_value
Always return this number

Type int in [-inf, inf], default 0

property
Assign the random value to this property

Type string, default ""

seed
Initial seed of the random generator. Use Python for more freedom (choose 0 for not random)

Type int in [0, 300000], default 0

standard_derivation
A normal distribution. Standard deviation of the distribution

Type float in [-1000, 1000], default 0.0

use_always_true
Always false or always true

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.415 RandomSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**RandomSensor** (*Sensor*)
Sensor to send random events

seed
Initial seed of the generator. (Choose 0 for not random)

Type int in [0, 1000], default 0

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency

- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.416 RaySensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**RaySensor**(*Sensor*)

Sensor to detect intersections with a ray emanating from the current object

axis

Specify along which axis the ray is cast

Type enum in ['XAXIS', 'YAXIS', 'ZAXIS', 'NEGXAXIS', 'NEGYAXIS', 'NEGZAXIS'], default 'YAXIS'

material

Only look for Objects with this material (blank = all objects)

Type string, default ""

property

Only look for Objects with this property (blank = all objects)

Type string, default ""

range

Sense objects no farther than this distance

Type float in [0.01, 10000], default 0.0

ray_type
Toggle collision on material or property

Type enum in ['PROPERTY', 'MATERIAL'], default 'PROPERTY'

use_x_ray
Toggle X-Ray option (see through objects that don't have the property)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.417 Region(bpy_struct)

base class — bpy_struct

class bpy.types.**Region**(*bpy_struct*)
Region in a subdivided screen area

height
Region height

Type int in [0, 32767], default 0, (readonly)

id
Unique ID for this region

Type int in [-32768, 32767], default 0, (readonly)

type
Type of this region

Type enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], default 'WINDOW', (readonly)

width
Region width

Type int in [0, 32767], default 0, (readonly)

tag_redraw()
tag_redraw

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Area.regions
- Context.region

1.4.418 RegionView3D(bpy_struct)

base class — bpy_struct

class bpy.types.**RegionView3D**(*bpy_struct*)

3D View region data

lock_rotation

Lock view rotation in side views

Type boolean, default False

perspective_matrix

Current perspective matrix of the 3D region

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

show_sync_view

Sync view position between side views

Type boolean, default False

use_box_clip

Clip objects based on what's visible in other side views

Type boolean, default False

view_distance

Distance to the view location

Type float in [0, inf], default 0.0

view_location

View pivot location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_matrix

Current view matrix of the 3D region

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

view_perspective

View Perspective

Type enum in ['PERSP', 'ORTHO', 'CAMERA'], default 'ORTHO'

view_rotation

Rotation in quaternions (keep normalized)

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.region_data
- SpaceView3D.region_3d
- SpaceView3D.region_quadview

1.4.419 RenderEngine(bpy_struct)

Simple Render Engine

```
import bpy


class CustomRenderEngine(bpy.types.RenderEngine):
    # These three members are used by blender to set up the
    # RenderEngine; define its internal name, visible name and capabilities.
    bl_idname = 'custom_renderer'
    bl_label = 'Flat Color Renderer'
    bl_use_preview = True

    # This is the only method called by blender, in this example
    # we use it to detect preview rendering and call the implementation
    # in another method.
    def render(self, scene):
        scale = scene.render.resolution_percentage / 100.0
        self.size_x = int(scene.render.resolution_x * scale)
        self.size_y = int(scene.render.resolution_y * scale)

        if scene.name == 'preview':
            self.render_preview(scene)
        else:
            self.render_scene(scene)

    # In this example, we fill the preview renders with a flat green color.
    def render_preview(self, scene):
        pixel_count = self.size_x * self.size_y

        # The framebuffer is defined as a list of pixels, each pixel
        # itself being a list of R,G,B,A values
        green_rect = [[0.0, 1.0, 0.0, 1.0]] * pixel_count

        # Here we write the pixel values to the RenderResult
```

```
        result = self.begin_result(0, 0, self.size_x, self.size_y)
        layer = result.layers[0]
        layer.rect = green_rect
        self.end_result(result)

    # In this example, we fill the full renders with a flat blue color.
    def render_scene(self, scene):
        pixel_count = self.size_x * self.size_y

        # The framebuffer is defined as a list of pixels, each pixel
        # itself being a list of R,G,B,A values
        blue_rect = [[0.0, 0.0, 1.0, 1.0]] * pixel_count

        # Here we write the pixel values to the RenderResult
        result = self.begin_result(0, 0, self.size_x, self.size_y)
        layer = result.layers[0]
        layer.rect = blue_rect
        self.end_result(result)

# Register the RenderEngine
bpy.utils.register_class(CustomRenderEngine)

# RenderEngines also need to tell UI Panels that they are compatible
# Otherwise most of the UI will be empty when the engine is selected.
# In this example, we need to see the main render image button and
# the material preview panel.
import properties_render
properties_render.RENDER_PT_render.COMPAT_ENGINES.add('custom_renderer')
del properties_render

import properties_material
properties_material.MATERIAL_PT_preview.COMPAT_ENGINES.add('custom_renderer')
del properties_material
```

base class — `bpy_struct`

subclasses — `NET_RENDER`

class `bpy.types.`**`RenderEngine`**(*bpy_struct*)

Render engine

`bl_idname`

Type string, default “”

`bl_label`

Type string, default “”

`bl_use_postprocess`

Type boolean, default False

`bl_use_preview`

Type boolean, default False

`render`(*scene=None*)

Render scene into an image.

begin_result (*x*, *y*, *w*, *h*)
begin_result

Parameters

- **x** (*int in [0, inf]*) – X
- **y** (*int in [0, inf]*) – Y
- **w** (*int in [0, inf]*) – Width
- **h** (*int in [0, inf]*) – Height

Returns Result

Return type RenderResult

update_result (*result*)
update_result

Parameters **result** (RenderResult) – Result

end_result (*result*)
end_result

Parameters **result** (RenderResult) – Result

test_break ()
test_break

Returns Break

Return type boolean

update_stats (*stats*, *info*)
update_stats

Parameters

- **stats** (*string*) – Stats
- **info** (*string*) – Info

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.420 RenderLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**RenderLayer**(*bpy_struct*)

exclude_ambient_occlusion
Exclude AO pass from combined

Type boolean, default False, (readonly)

exclude_emit
Exclude emission pass from combined

Type boolean, default False, (readonly)

exclude_environment
Exclude environment pass from combined

Type boolean, default False, (readonly)

exclude_indirect
Exclude indirect pass from combined

Type boolean, default False, (readonly)

exclude_reflection
Exclude raytraced reflection pass from combined

Type boolean, default False, (readonly)

exclude_refraction
Exclude raytraced refraction pass from combined

Type boolean, default False, (readonly)

exclude_shadow
Exclude shadow pass from combined

Type boolean, default False, (readonly)

exclude_specular
Exclude specular pass from combined

Type boolean, default False, (readonly)

invert_zmask
For Zmask, only render what is behind solid z values instead of in front

Type boolean, default False, (readonly)

layers
Scene layers included in this render layer

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False), (readonly)

layers_zmask
Zmask scene layers

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False), (readonly)

light_override
Group to override all other lights in this render layer

Type Group, (readonly)

material_override
Material to override all other materials in this render layer

Type Material, (readonly)

name
Render layer name

Type string, default "", (readonly)

passes

Type Collection of RenderPass, (readonly)

rect

Type float in [-inf, inf], default 0.0

use
Disable or enable the render layer

Type boolean, default False, (readonly)

use_all_z
Fill in Z values for solid faces in invisible layers, for masking

Type boolean, default False, (readonly)

use_edge_enhance
Render Edge-enhance in this Layer (only works for Solid faces)

Type boolean, default False, (readonly)

use_halo
Render Halos in this Layer (on top of Solid)

Type boolean, default False, (readonly)

use_pass_ambient_occlusion
Deliver AO pass

Type boolean, default False, (readonly)

use_pass_color
Deliver shade-less color pass

Type boolean, default False, (readonly)

use_pass_combined
Deliver full combined RGBA buffer

Type boolean, default False, (readonly)

use_pass_diffuse
Deliver diffuse pass

Type boolean, default False, (readonly)

use_pass_emit
Deliver emission pass

Type boolean, default False, (readonly)

use_pass_environment
Deliver environment lighting pass

Type boolean, default False, (readonly)

use_pass_indirect
Deliver indirect lighting pass

Type boolean, default False, (readonly)

use_pass_mist
Deliver mist factor pass (0.0-1.0)

Type boolean, default False, (readonly)

use_pass_normal
Deliver normal pass

Type boolean, default False, (readonly)

use_pass_object_index
Deliver object index pass

Type boolean, default False, (readonly)

use_pass_reflection
Deliver raytraced reflection pass

Type boolean, default False, (readonly)

use_pass_refraction
Deliver raytraced refraction pass

Type boolean, default False, (readonly)

use_pass_shadow
Deliver shadow pass

Type boolean, default False, (readonly)

use_pass_specular
Deliver specular pass

Type boolean, default False, (readonly)

use_pass_uv
Deliver texture UV pass

Type boolean, default False, (readonly)

use_pass_vector
Deliver speed vector pass

Type boolean, default False, (readonly)

use_pass_z
Deliver Z values pass

Type boolean, default False, (readonly)

use_sky
Render Sky in this Layer

Type boolean, default False, (readonly)

use_solid
Render Solid faces in this Layer

Type boolean, default False, (readonly)

use_strand
Render Strands in this Layer

Type boolean, default False, (readonly)

use_zmask
Only render what's in front of the solid z values

Type boolean, default False, (readonly)

use_ztransp
Render Z-Transparent faces in this Layer (On top of Solid and Halos)

Type boolean, default False, (readonly)

load_from_file (*filename*, *x=0*, *y=0*)
Copies the pixels of this renderlayer from an image file.

Parameters

- **filename** (*string*) – Filename, Filename to load into this render tile, must be no smaller then the renderlayer
- **x** (*int in [0, inf], (optional)*) – Offset X, Offset the position to copy from if the image is larger then the render layer
- **y** (*int in [0, inf], (optional)*) – Offset Y, Offset the position to copy from if the image is larger then the render layer

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- RenderResult.layers

1.4.421 RenderLayers(bpy_struct)

base class — bpy_struct

class bpy.types.**RenderLayers**(*bpy_struct*)

Collection of render layers

active

Active Render Layer

Type SceneRenderLayer

active_index

Active index in render layer array

Type int in [-32768, 32767], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- RenderSettings.layers

1.4.422 RenderPass(bpy_struct)

base class — bpy_struct

class bpy.types.**RenderPass**(*bpy_struct*)

channel_id

Type string, default "", (readonly)

channels

Type int in [-inf, inf], default 0, (readonly)

name

Type string, default "", (readonly)

rect

Type float in [-inf, inf], default 0.0

type

Type enum in ['COMBINED', 'Z', 'COLOR', 'DIFFUSE', 'SPECULAR', 'SHADOW', 'AO', 'REFLECTION', 'NORMAL', 'VECTOR', 'REFRACTION', 'OBJECT_INDEX', 'UV', 'MIST', 'EMIT', 'ENVIRONMENT'], default 'COMBINED', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- RenderLayer.passes

1.4.423 RenderResult(bpy_struct)

base class — bpy_struct

class bpy.types.**RenderResult** (*bpy_struct*)

Result of rendering, including all layers and passes

layers

Type Collection of RenderLayer, (readonly)

resolution_x

Type int in [-inf, inf], default 0, (readonly)

resolution_y

Type int in [-inf, inf], default 0, (readonly)

load_from_file (*filename*)

Copies the pixels of this render result from an image file.

Parameters **filename** (*string*) – File Name, Filename to load into this render tile, must be no smaller then the render result

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- RenderEngine.begin_result
- RenderEngine.end_result
- RenderEngine.update_result

1.4.424 RenderSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**RenderSettings** (*bpy_struct*)

Rendering settings for a Scene datablock

alpha_mode

Representation of alpha information in the RGBA pixels

Type enum in ['SKY', 'PREMUL', 'STRAIGHT'], default 'SKY'

antialiasing_samples

Amount of anti-aliasing samples per pixel

Type enum in ['5', '8', '11', '16'], default '5'

bake_aa_mode

Type enum in ['5', '8', '11', '16'], default '5'

bake_bias

Bias towards faces further away from the object (in blender units)

Type float in [0, 1000], default 0.0

bake_distance

Maximum distance from active object to other object (in blender units

Type float in [0, 1000], default 0.0

bake_margin

Amount of pixels to extend the baked result with, as post process filter

Type int in [0, 32], default 0

bake_normal_space

Choose normal space for baking

Type enum in ['CAMERA', 'WORLD', 'OBJECT', 'TANGENT'], default 'CAMERA'

bake_quad_split

Choose the method used to split a quad into 2 triangles for baking

Type enum in ['AUTO', 'FIXED', 'FIXED_ALT'], default 'AUTO'

bake_type

Choose shading information to bake into the image

Type enum in ['FULL', 'AO', 'SHADOW', 'NORMALS', 'TEXTURE', 'DISPLACEMENT'], default 'FULL'

border_max_x

Sets maximum X value for the render border

Type float in [0, 1], default 0.0

border_max_y

Sets maximum Y value for the render border

Type float in [0, 1], default 0.0

border_min_x

Sets minimum X value to for the render border

Type float in [0, 1], default 0.0

border_min_y
Sets minimum Y value for the render border

Type float in [0, 1], default 0.0

cineon_black
Log conversion reference blackpoint

Type int in [0, 1024], default 0

cineon_gamma
Log conversion gamma

Type float in [0, 10], default 0.0

cineon_white
Log conversion reference whitepoint

Type int in [0, 1024], default 0

color_mode
Choose BW for saving greyscale images, RGB for saving red, green and blue channels, AND RGBA for saving red, green, blue + alpha channels

Type enum in ['BW', 'RGB', 'RGBA'], default 'BW'

display_mode
Select where rendered images will be displayed

Type enum in ['SCREEN', 'AREA', 'WINDOW', 'NONE'], default 'SCREEN'

dither_intensity
Amount of dithering noise added to the rendered image to break up banding

Type float in [0, 2], default 0.0

edge_color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_threshold
Threshold for drawing outlines on geometry edges

Type int in [0, 255], default 0

engine
Engine to use for rendering

Type enum in ['BLENDER_RENDER'], default 'BLENDER_RENDER'

exr_codec
Codec settings for OpenEXR

Type enum in ['NONE', 'PXR24', 'ZIP', 'PIZ', 'RLE'], default 'NONE'

exr_preview
When rendering animations, save JPG preview images in same directory

Type boolean, default False

exr_zbuf
Save the z-depth per pixel (32 bit unsigned int zbuffer)

Type boolean, default False

field_order
Order of video fields. Select which lines get rendered first, to create smooth motion for TV output

Type enum in ['EVEN_FIRST', 'ODD_FIRST'], default 'EVEN_FIRST'

file_extension
The file extension used for saving renders

Type string, default "", (readonly)

file_format
File format to save the rendered images as

Type enum in ['BMP', 'IRIS', 'PNG', 'JPEG', 'TARGA', 'TARGA_RAW', 'MULTILAYER', 'OPEN_EXR', 'AVI_JPEG', 'AVI_RAW', 'FRAMESERVER'], default 'TARGA'

file_quality
Quality of JPEG images, AVI Jpeg and SGI movies, Compression for PNG's

Type int in [0, 100], default 0

filepath
Directory/name to save animations, # characters defines the position and length of frame numbers

Type string, default ""

filter_size
Pixel width over which the reconstruction filter combines samples

Type float in [0.5, 1.5], default 0.0

fps
Framerate, expressed in frames per second

Type int in [1, 120], default 0

fps_base
Framerate base

Type float in [0.1, 120], default 0.0

frame_map_new
Specify how many frames the Map Old will last

Type int in [1, 900], default 0

frame_map_old
Specify old mapping value in frames

Type int in [1, 900], default 0

has_multiple_engines
More than one rendering engine is available

Type boolean, default False, (readonly)

is_movie_format
When true the format is a movie

Type boolean, default False, (readonly)

layers

Type `RenderLayers` collection of `SceneRenderLayer`, (readonly)

motion_blur_samples
Number of scene samples to take with motion blur

Type int in [1, 32], default 0

motion_blur_shutter
Time taken in frames between shutter open and close

Type float in [0.01, 10], default 0.0

octree_resolution
Resolution of raytrace accelerator. Use higher resolutions for larger scenes

Type enum in ['64', '128', '256', '512'], default '64'

parts_x
Number of horizontal tiles to use while rendering

Type int in [1, 512], default 0

parts_y
Number of vertical tiles to use while rendering

Type int in [1, 512], default 0

pixel_aspect_x
Horizontal aspect ratio - for anamorphic or non-square pixel output

Type float in [1, 200], default 0.0

pixel_aspect_y
Vertical aspect ratio - for anamorphic or non-square pixel output

Type float in [1, 200], default 0.0

pixel_filter_type
Reconstruction filter used for combining anti-aliasing samples

Type enum in ['BOX', 'TENT', 'QUADRATIC', 'CUBIC', 'CATMULLROM', 'GAUSSIAN', 'MITCHELL'], default 'BOX'

raytrace_method
Type of raytrace accelerator structure

Type enum in ['AUTO', 'OCTREE', 'BLIBVH', 'VBVH', 'SIMD_SVBVH', 'SIMD_QBVH'], default 'AUTO'

resolution_percentage
Percentage scale for render resolution

Type int in [1, 32767], default 0

resolution_x
Number of horizontal pixels in the rendered image

Type int in [4, 10000], default 0

resolution_y
Number of vertical pixels in the rendered image

Type int in [4, 10000], default 0

sequencer_gl_preview
Method to draw in the sequencer view

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

sequencer_gl_render
Method to draw in the sequencer view

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

simplify_ao_sss
Global approximate AA and SSS quality factor

Type float in [0, 1], default 0.0

simplify_child_particles
Global child particles percentage

Type float in [0, 1], default 0.0

simplify_shadow_samples
Global maximum shadow samples

Type int in [0, 32767], default 0

simplify_subdivision
Global maximum subdivision level

Type int in [0, 32767], default 0

stamp_background
Color to use behind stamp text

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

stamp_font_size
Size of the font used when rendering stamp text

Type int in [8, 64], default 0

stamp_foreground
Color to use for stamp text

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

stamp_note_text
Custom text to appear in the stamp note

Type string, default ""

threads
Number of CPU threads to use simultaneously while rendering (for multi-core/CPU systems)

Type int in [1, 64], default 0

threads_mode
Determine the amount of render threads used

Type enum in ['AUTO', 'FIXED'], default 'AUTO'

use_antialiasing
Render and combine multiple samples per pixel to prevent jagged edges

Type boolean, default False

use_bake_antialiasing
Enables Anti-aliasing

Type boolean, default False

use_bake_clear
Clear Images before baking

Type boolean, default False

use_bake_normalize
With displacement normalize to the distance, with ambient occlusion normalize without using material settings

Type boolean, default False

use_bake_selected_to_active
Bake shading on the surface of selected objects to the active object

Type boolean, default False

use_border
Render a user-defined border region, within the frame size. Note, this disables save_buffers and full_sample

Type boolean, default False

use_cineon_log
Convert to logarithmic color space

Type boolean, default False

use_color_management
Use linear workflow - gamma corrected imaging pipeline

Type boolean, default False

use_compositing
Process the render result through the compositing pipeline, if compositing nodes are enabled

Type boolean, default False

use_crop_to_border
Crop the rendered frame to the defined border size

Type boolean, default False

use_edge_enhance
Create a toon outline around the edges of geometry

Type boolean, default False

use_envmaps
Calculate environment maps while rendering

Type boolean, default False

use_exr_half
Use 16 bit floats instead of 32 bit floats per channel

Type boolean, default False

use_fields
Render image to two fields per frame, for interlaced TV output

Type boolean, default False

use_fields_still
Disable the time difference between fields

Type boolean, default False

use_file_extension
Add the file format extensions to the rendered file name (eg: filename + .jpg)

Type boolean, default False

use_free_image_textures
Free all image texture from memory after render, to save memory before compositing

Type boolean, default False

use_free_unused_nodes
Free Nodes that are not used while compositing, to save memory

Type boolean, default False

use_full_sample
Save for every anti-aliasing sample the entire RenderLayer results. This solves anti-aliasing issues with compositing

Type boolean, default False

use_game_engine
Current rendering engine is a game engine

Type boolean, default False, (readonly)

use_instances
Instance support leads to effective memory reduction when using duplicates

Type boolean, default False

use_local_coords
Vertex coordinates are stored localy on each primitive. Increases memory usage, but may have impact on speed

Type boolean, default False

use_motion_blur
Use multi-sampled 3D scene motion blur

Type boolean, default False

use_overwrite
Overwrite existing files while rendering

Type boolean, default False

use_placeholder
Create empty placeholder files while rendering frames (similar to Unix 'touch')

Type boolean, default False

use_radiosity
Calculate radiosity in a pre-process before rendering

Type boolean, default False

use_raytrace
Pre-calculate the raytrace accelerator and render raytracing effects

Type boolean, default False

use_save_buffers
Save tiles for all RenderLayers and SceneNodes to files in the temp directory (saves memory, required for Full Sample)

Type boolean, default False

use_sequencer
Process the render (and composited) result through the video sequence editor pipeline, if sequencer strips exist

Type boolean, default False

use_sequencer_gl_preview

Type boolean, default False

use_sequencer_gl_render

Type boolean, default False

use_shadows
Calculate shadows while rendering

Type boolean, default False

use_simplify
Enable simplification of scene for quicker preview renders

Type boolean, default False

use_simplify_triangulate
Disables non-planer quads being triangulated

Type boolean, default False

use_single_layer
Only render the active layer

Type boolean, default False

use_sss
Calculate sub-surface scattering in materials rendering

Type boolean, default False

use_stamp
Render the stamp info text in the rendered image

Type boolean, default False

use_stamp_camera
Include the name of the active camera in image metadata

Type boolean, default False

use_stamp_date
Include the current date in image metadata

Type boolean, default False

use_stamp_filename
Include the filename of the .blend file in image metadata

Type boolean, default False

use_stamp_frame
Include the frame number in image metadata

Type boolean, default False

use_stamp_lens
Include the name of the active cameras lens in image metadata

Type boolean, default False

use_stamp_marker
Include the name of the last marker in image metadata

Type boolean, default False

use_stamp_note
Include a custom note in image metadata

Type boolean, default False

use_stamp_render_time
Include the render time in the stamp image

Type boolean, default False

use_stamp_scene
Include the name of the active scene in image metadata

Type boolean, default False

use_stamp_sequencer_strip
Include the name of the foreground sequence strip in image metadata

Type boolean, default False

use_stamp_time
Include the render frame as HH:MM:SS.FF in image metadata

Type boolean, default False

use_textures
Use textures to affect material properties

Type boolean, default False

use_tiff_16bit
Save TIFF with 16 bits per channel

Type boolean, default False

frame_path (*frame=-2147483648*)
Return the absolute path to the filename to be written for a given frame.

Parameters **frame** (*int in [-inf, inf], (optional)*) – Frame number to use, if unset the current frame will be used.

Returns File Path, the resulting filepath from the scenes render settings.

Return type string

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.render

1.4.425 RigidBodyJointConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**RigidBodyJointConstraint**(*Constraint*)

For use with the Game Engine

axis_x

Rotate pivot on X axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

axis_y

Rotate pivot on Y axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

axis_z

Rotate pivot on Z axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

child

Child object

Type Object

limit_angle_max_x

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_max_y

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_max_z

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_x

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_y

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_z

Type float in [-6.28319, 6.28319], default 0.0

limit_max_x

Type float in [-inf, inf], default 0.0

limit_max_y

Type float in [-inf, inf], default 0.0

limit_max_z

Type float in [-inf, inf], default 0.0

limit_min_x

Type float in [-inf, inf], default 0.0

limit_min_y

Type float in [-inf, inf], default 0.0

limit_min_z

Type float in [-inf, inf], default 0.0

pivot_type

Type enum in ['BALL', 'HINGE', 'CONE_TWIST', 'GENERIC_6_DOF'], default 'BALL'

pivot_x

Offset pivot on X

Type float in [-1000, 1000], default 0.0

pivot_y

Offset pivot on Y

Type float in [-1000, 1000], default 0.0

pivot_z

Offset pivot on Z

Type float in [-1000, 1000], default 0.0

show_pivot

Display the pivot point and rotation in 3D view

Type boolean, default False

target

Target Object

Type `Object`

use_angular_limit_x

Use minimum/maximum x angular limit

Type boolean, default False

use_angular_limit_y

Use minimum/maximum y angular limit

Type boolean, default False

use_angular_limit_z

Use minimum/maximum z angular limit

Type boolean, default False

use_limit_x
Use minimum/maximum x limit

Type boolean, default False

use_limit_y
Use minimum/maximum y limit

Type boolean, default False

use_limit_z
Use minimum/maximum z limit

Type boolean, default False

use_linked_collision
Disable collision between linked bodies

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.426 SPHFluidSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**SPHFluidSettings**(*bpy_struct*)

Settings for particle fluids physics

buoyancy

Artificial buoyancy force in negative gravity direction based on pressure differences inside the fluid

Type float in [0, 10], default 0.0

factor_density

Density is calculated as a factor of default density (depends on particle size)

Type boolean, default False

factor_radius

Interaction radius is a factor of 4 * particle size

Type boolean, default False

factor_repulsion

Repulsion is a factor of stiffness

Type boolean, default False

factor_rest_length

Spring rest length is a factor of 2 * particle size

Type boolean, default False

factor_stiff_viscosity

Stiff viscosity is a factor of normal viscosity

Type boolean, default False

fluid_radius

Fluid interaction radius

Type float in [0, 20], default 0.0

linear_viscosity

Linear viscosity

Type float in [0, 100], default 0.0

plasticity

How much the spring rest length can change after the elastic limit is crossed

Type float in [0, 100], default 0.0

repulsion

How strongly the fluid tries to keep from clustering (factor of stiffness)

Type float in [0, 100], default 0.0

rest_density

Fluid rest density

Type float in [0, 100], default 0.0

rest_length

Spring rest length (factor of particle radius)

Type float in [0, 2], default 0.0

spring_force
Spring force

Type float in [0, 100], default 0.0

spring_frames
Create springs for this number of frames since particles birth (0 is always)

Type int in [0, 100], default 0

stiff_viscosity
Creates viscosity for expanding fluid)

Type float in [0, 100], default 0.0

stiffness
How incompressible the fluid is

Type float in [0, 100], default 0.0

use_initial_rest_length
Use the initial length as spring rest length instead of 2 * particle size

Type boolean, default False

use_viscoelastic_springs
Use viscoelastic springs instead of Hooke's springs

Type boolean, default False

yield_ratio
How much the spring has to be stretched/compressed in order to change it's rest length

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSettings.fluid

1.4.427 Scene(ID)

base classes — bpy_struct, ID

class bpy.types.**Scene**(*ID*)

Scene consisting objects and defining time and render related settings

animation_data

Animation data for this datablock

Type AnimData, (readonly)

audio_distance_model

Distance model for distance attenuation calculation

Type enum in ['NONE', 'INVERSE', 'INVERSE_CLAMPED', 'LINEAR', 'LINEAR_CLAMPED', 'EXPONENT', 'EXPONENT_CLAMPED'], default 'NONE'

audio_doppler_factor

Pitch factor for Doppler effect calculation

Type float in [0, inf], default 0.0

audio_doppler_speed

Speed of sound for Doppler effect calculation

Type float in [0.01, inf], default 0.0

background_set

Background set scene

Type Scene

camera

Active camera used for rendering the scene

Type Object

cursor_location

3D cursor location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type int in [-300000, 300000], default 0

frame_end

Final frame of the playback/rendering range

Type int in [0, 300000], default 0

frame_preview_end

Alternative end frame for UI playback

Type int in [-inf, inf], default 0

frame_preview_start

Alternative start frame for UI playback

Type int in [-inf, inf], default 0

frame_start
First frame of the playback/rendering range

Type int in [0, 300000], default 0

frame_step
Number of frames to skip forward while rendering/playing back each frame

Type int in [0, 300000], default 0

game_settings

Type SceneGameData, (readonly, never None)

gravity
Constant acceleration in a given direction

Type float array of 3 items in [-200, 200], default (0.0, 0.0, 0.0)

grease_pencil
Grease Pencil datablock

Type GreasePencil

is_nla_tweakmode
Indicates whether there is any action referenced by NLA being edited. Strictly read-only

Type boolean, default False, (readonly)

keying_sets
Absolute Keying Sets for this Scene

Type KeyingSets collection of KeyingSet, (readonly)

keying_sets_all
All Keying Sets available for use (Builtins and Absolute Keying Sets for this Scene)

Type KeyingSetsAll collection of KeyingSet, (readonly)

layers
Layers visible when rendering the scene

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

network_render
Network Render Settings

Type NetRenderSettings, (readonly)

node_tree
Compositing node tree

Type NodeTree, (readonly)

object_bases

Type SceneBases collection of ObjectBase, (readonly)

objects

Type SceneObjects collection of Object, (readonly)

orientations

Type Collection of TransformOrientation, (readonly)

render

Type RenderSettings, (readonly, never None)

sequence_editor

Type SequenceEditor, (readonly)

sync_mode
How to sync playback

Type enum in ['NONE', 'FRAME_DROP', 'AUDIO_SYNC'], default 'NONE'

timeline_markers
Markers used in all timelines for the current scene

Type TimelineMarkers collection of TimelineMarker, (readonly)

tool_settings

Type ToolSettings, (readonly, never None)

unit_settings
Unit editing settings

Type UnitSettings, (readonly, never None)

use_audio
Play back of audio from Sequence Editor will be muted

Type boolean, default False

use_audio_scrub
Play audio from Sequence Editor while scrubbing

Type boolean, default False

use_audio_sync
Play back and sync with audio clock, dropping frames if frame display is too slow

Type boolean, default False

use_frame_drop
Play back dropping frames if frame display is too slow

Type boolean, default False

use_gravity
Use global gravity for all dynamics

Type boolean, default False

use_nodes
Enable the compositing node tree

Type boolean, default False

use_preview_range
Use an alternative start/end frame for UI playback, rather than the scene start/end frame

Type boolean, default False

use_stamp_note
User define note for the render stamping

Type string, default ""

world
World used for rendering the scene

Type World

statistics()
statistics

Returns Statistics

Return type string

frame_set(*frame*, *subframe=0.0*)
Set scene frame updating all objects immediately.

Parameters

- **frame** (*int in [-300000, 300000]*) – Frame number to set.
- **subframe** (*float in [0, 1], (optional)*) – Sub-frame time, between 0.0 and 1.0

update()
Update data tagged to be updated from previous access to data or operators.

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.scenes
- BlendDataScenes.new
- BlendDataScenes.remove
- CompositorNodeRLayers.scene
- Context.scene
- Image.save_render
- Object.dupli_list_create
- Object.is_visible
- Object.to_mesh
- RenderEngine.render
- Scene.background_set
- SceneActuator.scene
- SceneSequence.scene
- Screen.scene

1.4.428 SceneActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**SceneActuator** (*Actuator*)

Actuator to ..

camera

Set this Camera. Leave empty to refer to self object

Type Object

mode

Type enum in ['RESTART', 'SET', 'CAMERA', 'ADDFRONT', 'ADDBACK', 'REMOVE', 'SUSPEND', 'RESUME'], default 'RESTART'

scene

Set the Scene to be added/removed/paused/resumed

Type Scene

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.429 SceneBases(bpy_struct)

base class — bpy_struct

class bpy.types.**SceneBases**(*bpy_struct*)

Collection of scene bases

active

Active object base in the scene

Type ObjectBase

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.object_bases

1.4.430 SceneGameData(bpy_struct)

base class — bpy_struct

class bpy.types.**SceneGameData**(*bpy_struct*)

Game data for a Scene datablock

activity_culling_box_radius

Radius of the activity bubble, in Manhattan length. Objects outside the box are activity-culled

Type float in [0, 1000], default 0.0

depth

Displays bit depth of full screen display

Type int in [8, 32], default 0

dome_angle

Field of View of the Dome - it only works in mode Fisheye and Truncated

Type int in [-32768, 32767], default 0

dome_buffer_resolution

Buffer Resolution - decrease it to increase speed

Type float in [-inf, inf], default 0.0

dome_mode

Dome physical configurations

Type enum in ['FISHEYE', 'TRUNCATED_FRONT', 'TRUNCATED_REAR', 'ENVMAP', 'PANORAM_SPH'], default 'FISHEYE'

dome_tesselation

Tessellation level - check the generated mesh in wireframe mode

Type int in [-32768, 32767], default 0

dome_text

Custom Warp Mesh data file

Type Text

dome_tilt

Camera rotation in horizontal axis

Type int in [-32768, 32767], default 0

fps

The nominal number of game frames per second. Physics fixed timestep = 1/fps, independently of actual frame rate

Type int in [1, 250], default 0

frame_color

Set color of the bars

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

frame_type

Select the type of Framing you want

Type enum in ['LETTERBOX', 'EXTEND', 'SCALE'], default 'LETTERBOX'

frequency

Displays clock frequency of fullscreen display

Type int in [4, 2000], default 0

logic_step_max
Sets the maximum number of logic frame per game frame if graphics slows down the game, higher value allows better synchronization with physics

Type int in [1, 5], default 0

material_mode
Material mode to use for rendering

Type enum in ['TEXTURE_FACE', 'MULTITEXTURE', 'GLSL'], default 'TEXTURE_FACE'

occlusion_culling_resolution
The size of the occlusion buffer in pixel, use higher value for better precision (slower)

Type int in [128, 1024], default 0

physics_engine
Physics engine used for physics simulation in the game engine

Type enum in ['NONE', 'BULLET'], default 'NONE'

physics_gravity
Gravitational constant used for physics simulation in the game engine

Type float in [0, 25], default 0.0

physics_step_max
Sets the maximum number of physics step per game frame if graphics slows down the game, higher value allows physics to keep up with realtime

Type int in [1, 5], default 0

physics_step_sub
Sets the number of simulation substep per physic timestep, higher value give better physics precision

Type int in [1, 5], default 0

resolution_x
Number of horizontal pixels in the screen

Type int in [4, 10000], default 0

resolution_y
Number of vertical pixels in the screen

Type int in [4, 10000], default 0

show_debug_properties
Show properties marked for debugging while the game runs

Type boolean, default False

show_framerate_profile
Show framerate and profiling information while the game runs

Type boolean, default False

show_fullscreen
Starts player in a new fullscreen display

Type boolean, default False

show_mouse
Start player with a visible mouse cursor

Type boolean, default False

show_physics_visualization
Show a visualization of physics bounds and interactions

Type boolean, default False

stereo

Type enum in ['NONE', 'STEREO', 'DOME'], default 'NONE'

stereo_eye_separation
Set the distance between the eyes - the camera focal length/30 should be fine

Type float in [0.01, 5], default 0.0

stereo_mode
Stereographic techniques

Type enum in ['QUADBUFFERED', 'ABOVEBELOW', 'INTERLACED', 'ANAGLYPH', 'SIDEBYSIDE', 'VINTERLACE'], default 'QUADBUFFERED'

use_activity_culling
Activity culling is enabled

Type boolean, default False

use_animation_record
Record animation to fcurves

Type boolean, default False

use_auto_start
Automatically start game at load time

Type boolean, default False

use_deprecation_warnings
Print warnings when using deprecated features in the python API

Type boolean, default False

use_display_lists
Use display lists to speed up rendering by keeping geometry on the GPU

Type boolean, default False

use_frame_rate
Respect the frame rate rather than rendering as many frames as possible

Type boolean, default False

use_glsl_extra_textures
Use extra textures like normal or specular maps for GLSL rendering

Type boolean, default False

use_glsl_lights
Use lights for GLSL rendering

Type boolean, default False

use_glsl_nodes
Use nodes for GLSL rendering

Type boolean, default False

use_glsl_ramps
Use ramps for GLSL rendering

Type boolean, default False

use_glsl_shaders
Use shaders for GLSL rendering

Type boolean, default False

use_glsl_shadows
Use shadows for GLSL rendering

Type boolean, default False

use_occlusion_culling
Use optimized Bullet DBVT tree for view frustum and occlusion culling

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.game_settings

1.4.431 SceneObjects(bpy_struct)

base class — bpy_struct

class bpy.types.**SceneObjects**(*bpy_struct*)
Collection of scene objects

active
Active object for this scene

Type Object

link (*object*)
Link object to scene, run scene.update() after.

Parameters **object** (Object, (never None)) – Object to add to scene.

Returns The newly created base.

Return type ObjectBase

unlink (*object*)
Unlink object from scene.

Parameters **object** (Object, (never None)) – Object to remove from scene.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.objects

1.4.432 SceneRenderLayer(bpy_struct)

base class — bpy_struct

class bpy.types.**SceneRenderLayer** (*bpy_struct*)
Render layer

exclude_ambient_occlusion
Exclude AO pass from combined

Type boolean, default False

exclude_emit
Exclude emission pass from combined

Type boolean, default False

exclude_environment
Exclude environment pass from combined

Type boolean, default False

exclude_indirect
Exclude indirect pass from combined

Type boolean, default False

exclude_reflection
Exclude raytraced reflection pass from combined

Type boolean, default False

exclude_refraction
Exclude raytraced refraction pass from combined

Type boolean, default False

exclude_shadow
Exclude shadow pass from combined

Type boolean, default False

exclude_specular
Exclude specular pass from combined

Type boolean, default False

invert_zmask
For Zmask, only render what is behind solid z values instead of in front

Type boolean, default False

layers
Scene layers included in this render layer

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

layers_zmask
Zmask scene layers

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

light_override
Group to override all other lights in this render layer

Type `Group`

material_override
Material to override all other materials in this render layer

Type `Material`

name
Render layer name

Type string, default “”

use
Disable or enable the render layer

Type boolean, default False

use_all_z
Fill in Z values for solid faces in invisible layers, for masking

Type boolean, default False

use_edge_enhance
Render Edge-enhance in this Layer (only works for Solid faces)

Type boolean, default False

use_halo
Render Halos in this Layer (on top of Solid)

Type boolean, default False

use_pass_ambient_occlusion
Deliver AO pass

Type boolean, default False

use_pass_color
Deliver shade-less color pass

Type boolean, default False

use_pass_combined
Deliver full combined RGBA buffer

Type boolean, default False

use_pass_diffuse
Deliver diffuse pass

Type boolean, default False

use_pass_emit
Deliver emission pass

Type boolean, default False

use_pass_environment
Deliver environment lighting pass

Type boolean, default False

use_pass_indirect
Deliver indirect lighting pass

Type boolean, default False

use_pass_mist
Deliver mist factor pass (0.0-1.0)

Type boolean, default False

use_pass_normal
Deliver normal pass

Type boolean, default False

use_pass_object_index
Deliver object index pass

Type boolean, default False

use_pass_reflection
Deliver raytraced reflection pass

Type boolean, default False

use_pass_refraction
Deliver raytraced refraction pass

Type boolean, default False

use_pass_shadow
Deliver shadow pass

Type boolean, default False

use_pass_specular
Deliver specular pass

Type boolean, default False

use_pass_uv
Deliver texture UV pass

Type boolean, default False

use_pass_vector
Deliver speed vector pass

Type boolean, default False

use_pass_z
Deliver Z values pass

Type boolean, default False

use_sky
Render Sky in this Layer

Type boolean, default False

use_solid
Render Solid faces in this Layer

Type boolean, default False

use_strand
Render Strands in this Layer

Type boolean, default False

use_zmask
Only render what's in front of the solid z values

Type boolean, default False

use_ztransp
Render Z-Transparent faces in this Layer (On top of Solid and Halos)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- RenderLayers.active
- RenderSettings.layers

1.4.433 SceneSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**SceneSequence**(*Sequence*)

Sequence strip to used the rendered image of a scene

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

proxy

Type SequenceProxy, (readonly)

scene

Scene that this sequence uses

Type Scene

scene_camera

Override the scenes active camera

Type Object

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop

Crop image before processing

Type boolean, default False

use_deinterlace

For video movies to remove fields

Type boolean, default False

use_flip_x

Flip on the X axis

Type boolean, default False

use_flip_y

Flip on the Y axis

Type boolean, default False

use_float

Convert input to float data

Type boolean, default False

use_premultiply

Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy

Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames
Reverse frame order

Type boolean, default False

use_translation
Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.434 Scopes(bpy_struct)

base class — bpy_struct

class bpy.types.**Scopes** (*bpy_struct*)

Scopes for statistical view of an image

accuracy

Proportion of original image source pixel lines to sample

Type float in [0, 100], default 0.0

histogram

Histogram for viewing image statistics

Type Histogram, (readonly)

use_full_resolution

Sample every pixel of the image

Type boolean, default False

vectorscope_alpha

Opacity of the points

Type float in [0, 1], default 0.0

waveform_alpha

Opacity of the points

Type float in [0, 1], default 0.0

waveform_mode

Type enum in ['LUMA', 'RGB', 'YCBCR601', 'YCBCR709', 'YCBCRJPG'], default 'LUMA'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceImageEditor.scopes

1.4.435 Screen(ID)

base classes — bpy_struct, ID

class bpy.types.**Screen**(*ID*)

Screen datablock, defining the layout of areas in a window

areas

Areas the screen is subdivided into

Type Collection of Area, (readonly)

is_animation_playing

Animation playback is active

Type boolean, default False, (readonly)

scene

Active scene to be edited in the screen

Type Scene, (never None)

show_fullscreen

An area is maximised, filling this screen

Type boolean, default False, (readonly)

use_play_3d_editors

Type boolean, default False

use_play_animation_editors

Type boolean, default False

use_play_image_editors

Type boolean, default False

use_play_node_editors

Type boolean, default False

use_play_properties_editors

Type boolean, default False

use_play_sequence_editors

Type boolean, default False

use_play_top_left_3d_editor

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.screens
- Context.screen

- Window.screen

1.4.436 ScrewModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ScrewModifier** (*Modifier*)

Revolve edges

angle

Angle of revolution

Type float in [-inf, inf], default 0.0

axis

Screw axis

Type enum in ['X', 'Y', 'Z'], default 'X'

iterations

Number of times to apply the screw operation

Type int in [1, 10000], default 0

object

Object to define the screw axis

Type Object

render_steps

Number of steps in the revolution

Type int in [2, 10000], default 0

screw_offset

Offset the revolution along its axis

Type float in [-inf, inf], default 0.0

steps

Number of steps in the revolution

Type int in [2, 10000], default 0

use_normal_calculate

Calculate the order of edges (needed for meshes, but not curves)

Type boolean, default False

use_normal_flip

Flip normals of lathed faces

Type boolean, default False

use_object_screw_offset

Use the distance between the objects to make a screw

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name

- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.437 Sculpt(Paint)

base classes — bpy_struct, Paint

class bpy.types.**Sculpt**(*Paint*)

lock_x
Disallow changes to the X axis of vertices

Type boolean, default False

lock_y
Disallow changes to the Y axis of vertices

Type boolean, default False

lock_z
Disallow changes to the Z axis of vertices

Type boolean, default False

radial_symmetry
Number of times to copy strokes across the surface

Type int array of 3 items in [1, 64], default (1, 1, 1)

use_symmetry_feather
Reduce the strength of the brush where it overlaps symmetrical daubs

Type boolean, default False

use_symmetry_x
Mirror brush across the X axis

Type boolean, default False

use_symmetry_y
Mirror brush across the Y axis

Type boolean, default False

use_symmetry_z
Mirror brush across the Z axis

Type boolean, default False

use_threaded
Take advantage of multiple CPU cores to improve sculpting performance

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Paint.brush
- Paint.show_low_resolution
- Paint.show_brush
- Paint.show_brush_on_surface

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.sculpt

1.4.438 Sensor(bpy_struct)

base class — bpy_struct

subclasses — RaySensor, PropertySensor, MessageSensor, TouchSensor, KeyboardSensor, CollisionSensor, RadarSensor, DelaySensor, RandomSensor, AlwaysSensor, ActuatorSensor, JoystickSensor, MouseSensor, ArmatureSensor, NearSensor

class bpy.types.**Sensor**(*bpy_struct*)

Game engine logic brick to detect events

frequency

Delay between repeated pulses(in logic tics, 0=no delay)

Type int in [0, 10000], default 0

invert

Invert the level(output) of this sensor

Type boolean, default False

name

Sensor name

Type string, default ""

pin

Display when not linked to a visible states controller

Type boolean, default False

show_expanded

Set sensor expanded in the user interface

Type boolean, default False

type

Type enum in ['ACTUATOR', 'ALWAYS', 'ARMATURE', 'COLLISION', 'DELAY', 'JOYSTICK', 'KEYBOARD', 'MESSAGE', 'MOUSE', 'NEAR', 'PROPERTY', 'RADAR', 'RANDOM', 'RAY', 'TOUCH'], default 'ALWAYS'

use_level

Level detector, trigger controllers of new states(only applicable upon logic state transition)

Type boolean, default False

use_pulse_false_level

Activate FALSE level triggering (pulse mode)

Type boolean, default False

use_pulse_true_level

Activate TRUE level triggering (pulse mode)

Type boolean, default False

use_tap

Trigger controllers only for an instant, even while the sensor remains true

Type boolean, default False

link(*controller*)

Link the sensor to a controller.

Parameters controller (Controller) – Controller to link to.

unlink(*controller*)

Unlink the sensor from a controller.

Parameters **controller** (Controller) – Controller to unlink from.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Controller.link
- Controller.unlink
- GameObjectSettings.sensors

1.4.439 Sequence(bpy_struct)

base class — bpy_struct

subclasses — MulticamSequence, ImageSequence, SceneSequence, MetaSequence, SoundSequence, MovieSequence, EffectSequence

class bpy.types.**Sequence**(*bpy_struct*)

Sequence strip in the sequence editor

blend_alpha

Type float in [0, 1], default 0.0

blend_type

Type enum in ['REPLACE', 'CROSS', 'ADD', 'SUBTRACT', 'ALPHA_OVER', 'ALPHA_UNDER', 'GAMMA_CROSS', 'MULTIPLY', 'OVER_DROP'], default 'REPLACE'

channel

Y position of the sequence strip

Type int in [0, 31], default 0

effect_fader

Type float in [0, 1], default 0.0

frame_duration

The length of the contents of this strip before the handles are applied

Type int in [1, 300000], default 0, (readonly)

frame_final_duration

The length of the contents of this strip before the handles are applied

Type int in [1, 300000], default 0

frame_final_end

End frame displayed in the sequence editor after offsets are applied

Type int in [-inf, inf], default 0

frame_final_start

Start frame displayed in the sequence editor after offsets are applied, setting this is equivalent to moving the handle, not the actual start frame

Type int in [-inf, inf], default 0

frame_offset_end

Type int in [-inf, inf], default 0, (readonly)

frame_offset_start

Type int in [-inf, inf], default 0, (readonly)

frame_start

Type int in [-inf, inf], default 0

frame_still_end

Type int in [0, 300000], default 0, (readonly)

frame_still_start

Type int in [0, 300000], default 0, (readonly)

input_1

First input for the effect strip

Type `Sequence`, (readonly)

input_2

Second input for the effect strip

Type `Sequence`, (readonly)

input_3

Third input for the effect strip

Type `Sequence`, (readonly)

input_count

Type int in [0, inf], default 0, (readonly)

lock

Lock strip so that it can't be transformed

Type boolean, default False

mute

Type boolean, default False

name

Type string, default “”

select

Type boolean, default False

select_left_handle

Type boolean, default False

select_right_handle

Type boolean, default False

speed_factor

Multiply the current speed of the sequence with this number or remap current frame to this frame

Type float in [-inf, inf], default 0.0

type

Type enum in [’IMAGE’, ‘META’, ‘SCENE’, ‘MOVIE’, ‘SOUND’, ‘CROSS’, ‘ADD’, ‘SUBTRACT’, ‘ALPHA_OVER’, ‘ALPHA_UNDER’, ‘GAMMA_CROSS’, ‘MULTIPLY’, ‘OVER_DROP’, ‘PLUGIN’, ‘WIPE’, ‘GLOW’, ‘TRANSFORM’, ‘COLOR’, ‘SPEED’, ‘MULTICAM’], default ‘IMAGE’, (readonly)

use_default_fade

Fade effect using the built-in default (usually make transition as long as effect strip)

Type boolean, default False

getStripElem(*frame*)

Return the strip element from a given frame or None.

Parameters **frame** (*int in [-300000, 300000]*) – Frame, The frame to get the strip element from

Returns strip element of the current frame

Return type `SequenceElement`

swap(*other*)

swap

Parameters **other** (`Sequence`, (never None)) – Other

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MetaSequence.sequences
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.swap
- SequenceEditor.active_strip
- SequenceEditor.meta_stack
- SequenceEditor.sequences
- SequenceEditor.sequences_all

1.4.440 SequenceColorBalance(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceColorBalance**(*bpy_struct*)

Color balance parameters for a sequence strip

gain

Color balance gain (highlights)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

gamma

Color balance gamma (midtones)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

invert_gain

Type boolean, default False

invert_gamma

Type boolean, default False

invert_lift

Type boolean, default False

lift

Color balance lift (shadows)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EffectSequence.color_balance
- ImageSequence.color_balance
- MetaSequence.color_balance
- MovieSequence.color_balance
- MulticamSequence.color_balance
- SceneSequence.color_balance

1.4.441 SequenceCrop(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceCrop**(*bpy_struct*)

Cropping parameters for a sequence strip

max_x

Type int in [0, inf], default 0

max_y

Type int in [0, inf], default 0

min_x

Type int in [0, inf], default 0

min_y

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EffectSequence.crop
- ImageSequence.crop
- MetaSequence.crop
- MovieSequence.crop
- MulticamSequence.crop
- SceneSequence.crop

1.4.442 SequenceEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceEditor**(*bpy_struct*)

Sequence editing data for a Scene datablock

active_strip

Type Sequence

meta_stack

Meta strip stack, last is currently edited meta strip

Type Collection of Sequence, (readonly)

overlay_frame

Sequencers active strip

Type int in [-inf, inf], default 0

overlay_lock

Type boolean, default False

sequences

Type Collection of Sequence, (readonly)

sequences_all

Type Collection of Sequence, (readonly)

show_overlay
Partial overlay ontop of the sequencer

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.sequence_editor

1.4.443 SequenceElement(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceElement**(*bpy_struct*)
Sequence strip data for a single frame

filename

Type string, default “”

orig_height
Original image height

Type int in [-inf, inf], default 0, (readonly)

orig_width
Original image width

Type int in [-inf, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ImageSequence.elements
- MovieSequence.elements
- Sequence.getStripElem

1.4.444 SequenceProxy(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceProxy**(*bpy_struct*)
Proxy parameters for a sequence strip

directory
Location to store the proxy files

Type string, default “”

filepath
Location of custom proxy file

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EffectSequence.proxy
- ImageSequence.proxy
- MetaSequence.proxy
- MovieSequence.proxy
- MulticamSequence.proxy
- SceneSequence.proxy

1.4.445 SequenceTransform(bpy_struct)

base class — bpy_struct

class bpy.types.**SequenceTransform**(*bpy_struct*)

Transform parameters for a sequence strip

offset_x

Type int in [-inf, inf], default 0

offset_y

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EffectSequence.transform
- ImageSequence.transform
- MetaSequence.transform
- MovieSequence.transform
- MulticamSequence.transform
- SceneSequence.transform

1.4.446 ShaderNode(Node)

base classes — bpy_struct, Node

subclasses — ShaderNodeHueSaturation, ShaderNodeVectorMath, ShaderNodeRGB, ShaderNodeCameraData, ShaderNodeSeparateRGB, ShaderNodeMath, ShaderNodeRGBToBW, ShaderNodeRGBCurve, ShaderNodeInvert, ShaderNodeExtendedMaterial, ShaderNodeMaterial, ShaderNodeValue, ShaderNodeMixRGB, ShaderNodeVectorCurve, ShaderNodeCombineRGB, ShaderNodeOutput, ShaderNodeValToRGB, ShaderNodeGeometry, ShaderNodeTexture, ShaderNodeMapping, ShaderNodeSqueeze, ShaderNodeNormal

class bpy.types.**ShaderNode**(*Node*)

Material shader node

type

Type enum in ['OUTPUT', 'MATERIAL', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RGBTOBW', 'TEXTURE', 'NORMAL', 'GEOMETRY', 'MAPPING', 'CURVE_VEC', 'CURVE_RGB', 'CAMERA', 'MATH', 'VECT_MATH', 'SQUEEZE', 'MATERIAL_EXT', 'INVERT', 'SEPRGB', 'COMBRGB', 'HUE_SAT', 'SCRIPT', 'GROUP'], default 'OUTPUT', (readonly)

Inherited Properties

- bpy_struct.id_data

- Node.name
- Node.inputs
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.447 ShaderNodeCameraData(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeCameraData**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.448 ShaderNodeCombineRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeCombineRGB**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.449 ShaderNodeExtendedMaterial(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeExtendedMaterial**(*ShaderNode*)

invert_normal
Material Node uses inverted normal

Type boolean, default False

material

Type Material

use_diffuse
Material Node outputs Diffuse

Type boolean, default False

use_specular
Material Node outputs Specular

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.450 ShaderNodeGeometry(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeGeometry**(*ShaderNode*)

color_layer

Type string, default “”

uv_layer

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.451 ShaderNodeHueSaturation(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeHueSaturation**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.452 ShaderNodeInvert(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeInvert**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.453 ShaderNodeMapping(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeMapping**(*ShaderNode*)

location
Location offset for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

max
Maximum value to clamp coordinate to

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

min
Minimum value to clamp coordinate to

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation
Rotation offset for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scale
Scale adjustment for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_max
Clamp the output coordinate to a maximum value

Type boolean, default False

use_min
Clamp the output coordinate to a minimum value

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.454 ShaderNodeMaterial(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeMaterial**(*ShaderNode*)

invert_normal
Material Node uses inverted normal

Type boolean, default False

material

Type Material

use_diffuse
Material Node outputs Diffuse

Type boolean, default False

use_specular
Material Node outputs Specular

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

1.4.455 ShaderNodeMath(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeMath**(*ShaderNode*)

operation

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.456 ShaderNodeMixRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeMixRGB**(*ShaderNode*)

blend_type

Type enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'SCREEN', 'OVERLAY', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'DODGE', 'BURN', 'COLOR', 'VALUE', 'SATURATION', 'HUE', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

use_alpha
Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.457 ShaderNodeNormal(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeNormal**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.458 ShaderNodeOutput(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeOutput**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values

1.4.459 ShaderNodeRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeRGB**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.460 ShaderNodeRGBCurve(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeRGBCurve**(*ShaderNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.461 ShaderNodeRGBToBW(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeRGBToBW**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.462 ShaderNodeSeparateRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeSeparateRGB**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.463 ShaderNodeSqueeze(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeSqueeze**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data

- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.464 ShaderNodeTexture(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeTexture**(*ShaderNode*)

node_output

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

texture

Type Texture

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.465 ShaderNodeTree(NodeTree)

base classes — bpy_struct, ID, NodeTree

class bpy.types.**ShaderNodeTree** (*NodeTree*)

Node tree consisting of linked nodes used for materials

nodes

Type ShaderNodes collection of Node, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- NodeTree.animation_data
- NodeTree.grease_pencil
- NodeTree.inputs
- NodeTree.links
- NodeTree.outputs
- NodeTree.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.466 ShaderNodeValToRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeValToRGB**(*ShaderNode*)

color_ramp

Type ColorRamp, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.467 ShaderNodeValue(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeValue**(*ShaderNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.468 ShaderNodeVectorCurve(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeVectorCurve**(*ShaderNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs

- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.469 ShaderNodeVectorMath(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.**ShaderNodeVectorMath**(*ShaderNode*)

operation

Type enum in ['ADD', 'SUBTRACT', 'AVERAGE', 'DOT_PRODUCT', 'CROSS_PRODUCT', 'NORMALIZE'], default 'ADD'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.470 ShaderNodes(bpy_struct)

base class — bpy_struct

class bpy.types.**ShaderNodes**(*bpy_struct*)

Collection of Shader Nodes

new(*type*, *group=None*)

Add a node to this node tree.

Parameters

- **type** (*enum in ['OUTPUT', 'MATERIAL', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RGBTOBW', 'TEXTURE', 'NORMAL', 'GEOMETRY', 'MAPPING', 'CURVE_VEC', 'CURVE_RGB', 'CAMERA', 'MATH', 'VECT_MATH', 'SQUEEZE', 'MATERIAL_EXT', 'INVERT', 'SEPRGB', 'COMBRGB', 'HUE_SAT', 'SCRIPT', 'GROUP']*) – Type, Type of node to add
- **group** (NodeTree, (optional)) – The group tree

Returns New node.

Return type Node

remove(*node*)

remove a node from this node tree.

Parameters **node** (Node) – The node to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ShaderNodeTree.nodes

1.4.471 ShapeActionActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ShapeActionActuator** (*Actuator*)

Actuator to control shape key animations

action

Type Action

frame_blend_in

Number of frames of motion blending

Type int in [0, 32767], default 0

frame_end

Type float in [-inf, inf], default 0.0

frame_property

Assign the action's current frame number to this property

Type string, default ""

frame_start

Type float in [-inf, inf], default 0.0

mode

Action playback type

Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'LOOPSTOP', 'LOOPEND', 'PROPERTY'], default 'PLAY'

priority

Execution priority - lower numbers will override actions with higher numbers. With 2 or more actions at once, the overriding channels must be lower in the stack

Type int in [0, 100], default 0

property

Use this property to define the Action position

Type string, default ""

use_continue_last_frame

Restore last frame when switching on/off, otherwise play from the start each time

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.472 ShapeKey(bpy_struct)

base class — bpy_struct

class bpy.types.**ShapeKey** (*bpy_struct*)

Shape key in a shape keys datablock

data

Type Collection of UnknownType, (readonly)

frame

Frame for absolute keys

Type float in [-inf, inf], default 0.0, (readonly)

interpolation

Interpolation type

Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default 'KEY_LINEAR'

mute

Mute this shape key

Type boolean, default False

name

Type string, default “”

relative_key
Shape used as a relative key

Type ShapeKey

slider_max
Maximum for slider

Type float in [-10, 10], default 1.0

slider_min
Minimum for slider

Type float in [-10, 10], default 0.0

value
Value of shape key at the current frame

Type float in [0, 1], default 0.0

vertex_group
Vertex weight group, to blend with basis shape

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothSettings.rest_shape_key
- Key.keys
- Key.reference_key
- Object.active_shape_key

- Object.shape_key_add
- ShapeKey.relative_key

1.4.473 ShapeKeyBezierPoint(bpy_struct)

base class — bpy_struct

class bpy.types.**ShapeKeyBezierPoint**(*bpy_struct*)

Point in a shape key for bezier curves

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_left

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_right

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.474 ShapeKeyCurvePoint(bpy_struct)

base class — bpy_struct

class bpy.types.**ShapeKeyCurvePoint**(*bpy_struct*)

Point in a shape key for curves

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tilt

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.475 ShapeKeyPoint(bpy_struct)

base class — bpy_struct

class bpy.types.**ShapeKeyPoint**(*bpy_struct*)

Point in a shape key

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.476 ShrinkwrapConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**ShrinkwrapConstraint**(*Constraint*)

Creates constraint-based shrinkwrap relationship

distance

Distance to Target

Type float in [0, 100], default 0.0

shrinkwrap_type

Selects type of shrinkwrap algorithm for target position

Type enum in ['NEAREST_SURFACE', 'PROJECT', 'NEAREST_VERTEX'], default 'NEAREST_SURFACE'

target

Target Object

Type Object

use_x

Projection over X Axis

Type boolean, default False

use_y

Projection over Y Axis

Type boolean, default False

use_z

Projection over Z Axis

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space

- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.477 ShrinkwrapModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**ShrinkwrapModifier**(*Modifier*)

Shrink wrapping modifier to shrink wrap and object to a target

auxiliary_target

Additional mesh target to shrink to

Type Object

cull_face

Stop vertices from projecting to a the face on the target when facing towards/away

Type enum in ['OFF', 'FRONT', 'BACK'], default 'OFF'

offset

Distance to keep from the target

Type float in [-inf, inf], default 0.0

subsurf_levels

Number of subdivisions that must be performed before extracting vertices' positions and normals

Type int in [0, 6], default 0

target

Mesh target to shrink to

Type Object

use_keep_above_surface

Type boolean, default False

use_negative_direction
Allow vertices to move in the negative direction of axis

Type boolean, default False

use_positive_direction
Allow vertices to move in the positive direction of axis

Type boolean, default False

use_project_x

Type boolean, default False

use_project_y

Type boolean, default False

use_project_z

Type boolean, default False

vertex_group
Vertex group name

Type string, default “”

wrap_method

Type enum in [’NEAREST_SURFACEPOINT’, ‘PROJECT’, ‘NEAREST_VERTEX’], default ‘NEAREST_SURFACEPOINT’

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.478 SimpleDeformModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SimpleDeformModifier**(*Modifier*)

Simple deformation modifier to apply effects such as twisting and bending

deform_method

Type enum in ['TWIST', 'BEND', 'TAPER', 'STRETCH'], default 'TWIST'

factor

Type float in [-inf, inf], default 0.0

limits

Lower/Upper limits for deform

Type float array of 2 items in [0, 1], default (0.0, 0.0)

lock_x

Type boolean, default False

lock_y

Type boolean, default False

origin

Origin of modifier space coordinates

Type Object

use_relative

Sets the origin of deform space to be relative to the object

Type boolean, default False

vertex_group

Vertex group name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.479 SmokeCollSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**SmokeCollSettings**(*bpy_struct*)

Smoke collision settings

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SmokeModifier.coll_settings

1.4.480 SmokeDomainSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**SmokeDomainSettings** (*bpy_struct*)

Smoke domain settings

alpha

How much density effects smoke motion, higher value results in faster rising smoke

Type float in [-5, 5], default 0.0

amplify

Enhance the resolution of smoke by this factor using noise

Type int in [1, 10], default 0

beta

How much heat effects smoke motion, higher value results in faster rising smoke

Type float in [-5, 5], default 0.0

collision_extents

Selects which domain border will be treated as collision object.

Type enum in ['BORDEROPEN', 'BORDERVERTICAL', 'BORDERCLOSED'], default 'BORDEROPEN'

collision_group

Limit collisions to this group

Type Group

dissolve_speed

Dissolve Speed

Type int in [1, 10000], default 0

effector_group

Limit effectors to this group

Type Group

effector_weights

Type EffectorWeights, (readonly)

fluid_group

Limit fluid objects to this group

Type Group

noise_type

Noise method which is used for creating the high resolution

Type enum in ['NOISEWAVE'], default 'NOISEWAVE'

point_cache

Type PointCache, (readonly, never None)

point_cache_compress_type
Compression method to be used

Type enum in ['CACHELIGHT', 'CACHEHEAVY'], default 'CACHELIGHT'

resolution_max
Maximal resolution used in the fluid domain

Type int in [24, 512], default 0

show_high_resolution
Show high resolution (using amplification)

Type boolean, default False

smooth_emitter
Smoothens emitted smoke to avoid blockiness.

Type boolean, default False

strength
Strength of wavelet noise

Type float in [0, 10], default 0.0

time_scale
Adjust simulation speed.

Type float in [0.2, 1.5], default 0.0

use_dissolve_smoke
Enable smoke to disappear over time

Type boolean, default False

use_dissolve_smoke_log
Using 1/x

Type boolean, default False

use_high_resolution
Enable high resolution (using amplification)

Type boolean, default False

vorticity
Amount of turbulence/rotation in fluid.

Type float in [0.01, 4], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SmokeModifier.domain_settings

1.4.481 SmokeFlowSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**SmokeFlowSettings**(*bpy_struct*)

Smoke flow settings

density

Type float in [0.001, 1], default 0.0

initial_velocity

Smoke inherits it's velocity from the emitter particle

Type boolean, default False

particle_system

Particle systems emitted from the object

Type ParticleSystem

temperature

Temperature difference to ambient temperature

Type float in [-10, 10], default 0.0

use_absolute

Only allows given density value in emitter area.

Type boolean, default False

use_outflow

Deletes smoke from simulation

Type boolean, default False

velocity_factor

Multiplier to adjust velocity passed to smoke

Type float in [-2, 2], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SmokeModifier.flow_settings

1.4.482 SmokeModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SmokeModifier**(*Modifier*)

Smoke simulation modifier

coll_settings

Type SmokeCollSettings, (readonly)

domain_settings

Type SmokeDomainSettings, (readonly)

flow_settings

Type SmokeFlowSettings, (readonly)

smoke_type

Type enum in ['NONE', 'DOMAIN', 'FLOW', 'COLLISION'], default 'NONE'

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport

- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.483 SmoothModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SmoothModifier**(*Modifier*)

Smoothing effect modifier

factor

Type float in [-inf, inf], default 0.0

iterations

Type int in [-32768, 32767], default 0

use_x

Type boolean, default False

use_y

Type boolean, default False

use_z

Type boolean, default False

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name

- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.484 SoftBodyModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SoftBodyModifier**(*Modifier*)

Soft body simulation modifier

point_cache

Type PointCache, (readonly, never None)

settings

Type SoftBodySettings, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.485 SoftBodySettings(bpy_struct)

base class — bpy_struct

class bpy.types.**SoftBodySettings**(*bpy_struct*)

Soft body simulation settings for an object

aero

Make edges 'sail'

Type int in [0, 30000], default 0

aerodynamics_type

Method of calculating aerodynamic interaction

Type enum in ['SIMPLE', 'LIFT_FORCE'], default 'SIMPLE'

ball_damp

Blending to inelastic collision

Type float in [0.001, 1], default 0.0

ball_size

Absolute ball size or factor if not manual adjusted

Type float in [-10, 10], default 0.0

ball_stiff

Ball inflating pressure

Type float in [0.001, 100], default 0.0

bend

Bending Stiffness

Type float in [0, 10], default 0.0

choke

'Viscosity' inside collision target

Type int in [0, 100], default 0

collision_type
Choose Collision Type

Type enum in ['MANUAL', 'AVERAGE', 'MINIMAL', 'MAXIMAL', 'MINMAX'], default 'MANUAL'

damping
Edge spring friction

Type float in [0, 50], default 0.0

effector_weights

Type EffectorWeights, (readonly)

error_threshold
The Runge-Kutta ODE solver error limit, low value gives more precision, high values speed

Type float in [0.001, 10], default 0.0

friction
General media friction for point movements

Type float in [0, 50], default 0.0

fuzzy
Fuzziness while on collision, high values make collsion handling faster but less stable

Type int in [1, 100], default 0

goal_default
Default Goal (vertex target position) value, when no Vertex Group used

Type float in [0, 1], default 0.0

goal_friction
Goal (vertex target position) friction

Type float in [0, 50], default 0.0

goal_max
Goal maximum, vertex weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_min
Goal minimum, vertex weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_spring
Goal (vertex target position) spring stiffness

Type float in [0, 0.999], default 0.0

gravity
Apply gravitation to point movement

Type float in [-10, 10], default 0.0

location_mass_center
Location of Center of mass

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mass
General Mass value

Type float in [0, 50000], default 0.0

plastic
Permanent deform

Type int in [0, 100], default 0

pull
Edge spring stiffness when longer than rest length

Type float in [0, 0.999], default 0.0

push
Edge spring stiffness when shorter than rest length

Type float in [0, 0.999], default 0.0

rotation_estimate
Estimated rotation matrix

Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

scale_estimate
Estimated scale matrix

Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

shear
Shear Stiffness

Type float in [0, 1], default 0.0

speed
Tweak timing for physics to control frequency and speed

Type float in [0.01, 100], default 0.0

spring_length
Alter spring length to shrink/blow up (unit %) 0 to disable

Type int in [0, 200], default 0

step_max
Maximal # solver steps/frame

Type int in [0, 30000], default 0

step_min
Minimal # solver steps/frame

Type int in [0, 30000], default 0

use_auto_step
Use velocities for automagic step sizes

Type boolean, default False

use_diagnose
Turn on SB diagnose console prints

Type boolean, default False

use_edge_collision
Edges collide too

Type boolean, default False

use_edges
Use Edges as springs

Type boolean, default False

use_estimate_matrix
estimate matrix .. split to COM , ROT ,SCALE

Type boolean, default False

use_face_collision
Faces collide too, can be very slow

Type boolean, default False

use_goal
Define forces for vertices to stick to animated position

Type boolean, default False

use_self_collision
Enable naive vertex ball self collision

Type boolean, default False

use_stiff_quads
Adds diagonal springs on 4-gons

Type boolean, default False

vertex_group_goal
Control point weight values

Type string, default “”

vertex_group_mass
Control point mass values

Type string, default “”

vertex_group_spring
Control point spring strength values

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.soft_body
- SoftBodyModifier.settings

1.4.486 SolidifyModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SolidifyModifier**(*Modifier*)

Create a solid skin by extruding, compensating for sharp angles

edge_crease_inner

Assign a crease to inner edges

Type float in [0, 1], default 0.0

edge_crease_outer

Assign a crease to outer edges

Type float in [0, 1], default 0.0

edge_crease_rim

Assign a crease to the edges making up the rim

Type float in [0, 1], default 0.0

invert_vertex_group

Invert the vertex group influence

Type boolean, default False

material_offset

Offset material index of generated faces

Type int in [-32768, 32767], default 0

material_offset_rim

Offset material index of generated rim faces

Type int in [-32768, 32767], default 0

offset

Offset the thickness from the center

Type float in [-inf, inf], default 0.0

thickness

Thickness of the shell

Type float in [-inf, inf], default 0.0

use_even_offset

Maintain thickness by adjusting for sharp corners (slow, disable when not needed)

Type boolean, default False

use_quality_normals
Calculate normals which result in more even thickness (slow, disable when not needed)

Type boolean, default False

use_rim
Create edge loops between the inner and outer surfaces on face edges (slow, disable when not needed)

Type boolean, default False

vertex_group
Vertex group name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.487 Sound(ID)

base classes — bpy_struct, ID

class bpy.types.**Sound**(*ID*)
Sound datablock referencing an external or packed sound file

filepath
Sound sample file used by this Sound datablock

Type string, default ""

packed_file

Type PackedFile, (readonly)

use_memory_cache
The sound file is decoded and loaded into RAM

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.sounds
- SoundActuator.sound
- SoundSequence.sound

1.4.488 SoundActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**SoundActuator**(*Actuator*)

Sound file

cone_inner_angle_3d

The angle of the inner cone

Type float in [-inf, inf], default 0.0

cone_outer_angle_3d

The angle of the outer cone

Type float in [-inf, inf], default 0.0

cone_outer_gain_3d

The gain outside the outer cone. The gain in the outer cone will be interpolated between this value and the normal gain in the inner cone

Type float in [-inf, inf], default 0.0

distance_3d_max

The maximum distance at which you can hear the sound

Type float in [-inf, inf], default 0.0

distance_3d_reference

The distance where the sound has a gain of 1.0

Type float in [-inf, inf], default 0.0

gain_3d_max

The maximum gain of the sound, no matter how near it is

Type float in [-inf, inf], default 0.0

gain_3d_min

The minimum gain of the sound, no matter how far it is away

Type float in [-inf, inf], default 0.0

mode

Type enum in ['PLAYSTOP', 'PLAYEND', 'LOOPSTOP', 'LOOPEND', 'LOOPBIDIRECTIONAL', 'LOOPBIDIRECTIONALSTOP'], default 'PLAYSTOP'

pitch

Sets the pitch of the sound

Type float in [-inf, inf], default 0.0

rolloff_factor_3d

The influence factor on volume depending on distance

Type float in [-inf, inf], default 0.0

sound

Type Sound

use_sound_3d

Enable/Disable 3D Sound

Type boolean, default False

volume
Sets the initial volume of the sound

Type float in [0, 2], default 0.0

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.489 SoundSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.**SoundSequence**(*Sequence*)
Sequence strip defining a sound to be played over a period of time

animation_offset_end
Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start
Animation start offset (trim start)

Type int in [0, inf], default 0

attenuation
Attenuation in decibel

Type float in [-100, 40], default 0.0

filepath

Type string, default “”

sound

Sound datablock used by this sequence

Type Sound, (readonly)

volume

Playback volume of the sound

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.490 Space(bpy_struct)

base class — bpy_struct

subclasses — SpaceUserPreferences, SpaceOutliner, SpaceImageEditor, SpaceSequenceEditor, SpaceProperties, SpaceGraphEditor, SpaceLogicEditor, SpaceInfo, SpaceConsole, SpaceNodeEditor, SpaceView3D, SpaceDopeSheetEditor, SpaceTextEditor, SpaceFileBrowser, SpaceNLA, SpaceTimeline

class bpy.types.**Space**(*bpy_struct*)

Space data for a screen area

type

Space data type

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Area.active_space
- Area.spaces
- Context.space_data

1.4.491 SpaceConsole(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceConsole**(*Space*)

Interactive python console

font_size

Font size to use for displaying the text

Type int in [8, 32], default 0

history

Command history

Type Collection of ConsoleLine, (readonly)

language

Command line prompt language

Type string, default ""

prompt

Command line prompt

Type string, default ""

scrollback

Command output

Type Collection of ConsoleLine, (readonly)

select_end

Type int in [0, inf], default 0

select_start

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.492 SpaceDopeSheetEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceDopeSheetEditor**(*Space*)

DopeSheet space data

action

Action displayed and edited in this space

Type Action

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

dopesheet

Settings for filtering animation data

Type DopeSheet, (readonly)

mode

Editing context being displayed

Type enum in ['DOPESHEET', 'ACTION', 'SHAPEKEY', 'GPENCIL'], default 'ACTION'

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_pose_markers

Show markers belonging to the active action instead of Scene markers (Action and Shape Key Editors only)

Type boolean, default False

show_seconds

Show timing in seconds not frames

Type boolean, default False, (readonly)

show_sliders

Show sliders beside F-Curve channels

Type boolean, default False

use_auto_merge_keyframes

Automatically merge nearby keyframes

Type boolean, default False

use_marker_sync
Sync Markers with keyframe edits

Type boolean, default False

use_realtime_update
When transforming keyframes, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.493 SpaceFileBrowser(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceFileBrowser**(*Space*)
File browser space data

operator

Type Operator, (readonly)

params
Parameters and Settings for the Filebrowser

Type FileSelectParams, (readonly)

Inherited Properties

- bpy_struct.id_data

- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.494 SpaceGraphEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceGraphEditor**(*Space*)

Graph Editor space data

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

cursor_position_y

Graph Editor 2D-Value cursor - Y-Value component

Type float in [-inf, inf], default 0.0

dopesheet

Settings for filtering animation data

Type DopeSheet, (readonly)

has_ghost_curves

Graph Editor instance has some ghost curves stored

Type boolean, default False

mode

Editing context being displayed

Type enum in ['FCURVES', 'DRIVERS'], default 'FCURVES'

pivot_point

Pivot center for rotation/scaling

Type enum in ['BOUNDING_BOX_CENTER', 'CURSOR', 'INDIVIDUAL_ORIGINS'], default 'BOUNDING_BOX_CENTER'

show_cursor
Show 2D cursor

Type boolean, default False

show_frame_indicator
Show frame number beside the current frame indicator line

Type boolean, default False

show_handles
Show handles of Bezier control points

Type boolean, default False

show_seconds
Show timing in seconds not frames

Type boolean, default False, (readonly)

show_sliders
Show sliders beside F-Curve channels

Type boolean, default False

use_auto_merge_keyframes
Automatically merge nearby keyframes

Type boolean, default False

use_fancy_drawing
Draw F-Curves using Anti-Aliasing and other fancy effects. Disable for better performance

Type boolean, default False

use_only_selected_curves_handles
Only keyframes of selected F-Curves are visible and editable

Type boolean, default False

use_only_selected_keyframe_handles
Only show and edit handles of selected keyframes

Type boolean, default False

use_realtime_update
When transforming keyframes, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.495 SpaceImageEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceImageEditor**(*Space*)

Image and UV editor space data

curves

Color curve mapping to use for displaying the image

Type CurveMapping, (readonly)

draw_channels

Channels of the image to draw

Type enum in ['COLOR', 'COLOR_ALPHA', 'ALPHA', 'Z_BUFFER'], default 'COLOR'

grease_pencil

Grease pencil data for this space

Type GreasePencil

image

Image displayed and edited in this space

Type Image

image_user

Parameters defining which layer, pass and frame of the image is displayed

Type ImageUser, (readonly, never None)

sample_histogram

Sampled colors along line

Type Histogram, (readonly)

scopes

Scopes to visualize image statistics.

Type Scopes, (readonly)

show_paint

Show paint related properties

Type boolean, default False, (readonly)

show_render

Show render related properties

Type boolean, default False, (readonly)

show_repeat
Draw the image repeated outside of the main view

Type boolean, default False

show_uvedit
Show UV editing related properties

Type boolean, default False, (readonly)

use_grease_pencil
Display and edit the grease pencil freehand annotations overlay

Type boolean, default False

use_image_paint
Enable image painting mode

Type boolean, default False

use_image_pin
Display current image regardless of object selection

Type boolean, default False

use_realtime_update
Update other affected window spaces automatically to reflect changes during interactive operations such as transform

Type boolean, default False

uv_editor
UV editor settings

Type SpaceUVEditor, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.496 SpaceInfo(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceInfo**(*Space*)

Info space data

show_report_debug

Display debug reporting info

Type boolean, default False

show_report_error

Display error text

Type boolean, default False

show_report_info

Display general information

Type boolean, default False

show_report_operator

Display the operator log

Type boolean, default False

show_report_warning

Display warnings

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.497 SpaceLogicEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceLogicEditor**(*Space*)

Logic editor space data

show_actuators_active_object

Show actuators of active object

Type boolean, default False

show_actuators_active_states

Show only actuators connected to active states

Type boolean, default False

show_actuators_linked_controller

Show linked objects to the actuator

Type boolean, default False

show_actuators_selected_objects

Show actuators of all selected objects

Type boolean, default False

show_controllers_active_object

Show controllers of active object

Type boolean, default False

show_controllers_linked_controller

Show linked objects to sensor/actuator

Type boolean, default False

show_controllers_selected_objects

Show controllers of all selected objects

Type boolean, default False

show_sensors_active_object

Show sensors of active object

Type boolean, default False

show_sensors_active_states

Show only sensors connected to active states

Type boolean, default False

show_sensors_linked_controller

Show linked objects to the controller

Type boolean, default False

show_sensors_selected_objects

Show sensors of all selected objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.498 SpaceNLA(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceNLA**(*Space*)

NLA editor space data

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

dopesheet

Settings for filtering animation data

Type DopeSheet, (readonly)

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_seconds

Show timing in seconds not frames

Type boolean, default False, (readonly)

show_strip_curves

Show influence curves on strips

Type boolean, default False

use_realtime_update

When transforming strips, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.499 SpaceNodeEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceNodeEditor**(*Space*)

Node editor space data

backdrop_channels

Channels of the image to draw

Type enum in ['COLOR', 'COLOR_ALPHA', 'ALPHA'], default 'COLOR'

backdrop_x

Backdrop X offset

Type float in [-inf, inf], default 0.0

backdrop_y

Backdrop Y offset

Type float in [-inf, inf], default 0.0

backdrop_zoom

Backdrop zoom factor

Type float in [0.01, inf], default 1.0

id

Datablock whose nodes are being edited

Type ID, (readonly)

id_from
Datablock from which the edited datablock is linked

Type ID, (readonly)

node_tree
Node tree being displayed and edited

Type NodeTree, (readonly)

show_backdrop
Use active Viewer Node output as backdrop for compositing nodes

Type boolean, default False

texture_type
Type of data to take texture from

Type enum in ['OBJECT', 'WORLD', 'BRUSH'], default 'OBJECT'

tree_type
Node tree type to display and edit

Type enum in ['MATERIAL', 'TEXTURE', 'COMPOSITING'], default 'MATERIAL'

use_auto_render
Re-render and composite changed layer on 3D edits

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.500 SpaceOutliner(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceOutliner**(*Space*)

Outliner space data

display_mode

Type of information to display

Type enum in ['ALL_SCENES', 'CURRENT_SCENE', 'VISIBLE_LAYERS', 'SELECTED', 'ACTIVE', 'SAME_TYPES', 'GROUPS', 'LIBRARIES', 'SEQUENCE', 'DATABLOCKS', 'USER_PREFERENCES', 'KEYMAPS'], default 'ALL_SCENES'

filter_text

Live search filtering string

Type string, default ""

show_restrict_columns

Show column

Type boolean, default False

use_filter_case_sensitive

Only use case sensitive matches of search string

Type boolean, default False

use_filter_complete

Only use complete matches of search string

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.501 SpaceProperties(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceProperties**(*Space*)

Properties space data

align

Arrangement of the panels

Type enum in ['HORIZONTAL', 'VERTICAL'], default 'HORIZONTAL'

context

Type of active data to display and edit

Type enum in ['SCENE', 'RENDER', 'WORLD', 'OBJECT', 'CONSTRAINT', 'MODIFIER', 'DATA', 'BONE', 'BONE_CONSTRAINT', 'MATERIAL', 'TEXTURE', 'PARTICLE', 'PHYSICS'], default 'RENDER'

pin_id

Type ID

texture_context

Type of texture data to display and edit

Type enum in ['MATERIAL'], default 'MATERIAL'

use_pin_id

Use the pinned context

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.502 SpaceSequenceEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceSequenceEditor**(*Space*)

Sequence editor space data

display_channel

The channel number shown in the image preview. 0 is the result of all strips combined

Type int in [-5, 32], default 0

display_mode

The view mode to use for displaying sequencer output

Type enum in ['IMAGE', 'WAVEFORM', 'VECTOR_SCOPE', 'HISTOGRAM'], default 'IMAGE'

draw_overexposed

Show overexposed areas with zebra stripes

Type int in [0, 110], default 0

grease_pencil

Grease pencil data for this space

Type UnknownType, (readonly)

offset_x

Offsets image horizontally from the view center

Type float in [-inf, inf], default 0.0

offset_y

Offsets image horizontally from the view center

Type float in [-inf, inf], default 0.0

proxy_render_size

Draw preview using full resolution or different proxy resolutions

Type enum in ['NONE', 'SCENE', 'PROXY_25', 'PROXY_50', 'PROXY_75', 'FULL'], default 'SCENE'

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_frames

Draw frames rather than seconds

Type boolean, default False

show_safe_margin

Draw title safe margins in preview

Type boolean, default False

show_separate_color

Separate color channels in preview

Type boolean, default False

use_grease_pencil

Display and edit the grease pencil freehand annotations overlay

Type boolean, default False

use_marker_sync
Transform markers as well as strips

Type boolean, default False

view_type
The type of the Sequencer view (sequencer, preview or both)

Type enum in ['SEQUENCER', 'PREVIEW', 'SEQUENCER_PREVIEW'], default 'SEQUENCER'

zoom
Display zoom level

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.503 SpaceTextEditor(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceTextEditor**(*Space*)
Text editor space data

find_text
Text to search for with the find tool

Type string, default ""

font_size
Font size to use for displaying the text

Type int in [8, 32], default 0

margin_column
Column number to show right margin at

Type int in [0, 1024], default 0

replace_text
Text to replace selected text with using the replace tool

Type string, default “”

show_line_highlight
Highlight the current line

Type boolean, default False

show_line_numbers
Show line numbers next to the text

Type boolean, default False

show_margin
Show right margin

Type boolean, default False

show_syntax_highlight
Syntax highlight for scripting

Type boolean, default False

show_word_wrap
Wrap words if there is not enough horizontal space

Type boolean, default False

tab_width
Number of spaces to display tabs with

Type int in [2, 8], default 0

text
Text displayed and edited in this space

Type Text

use_find_all
Search in all text datablocks, instead of only the active one

Type boolean, default False

use_find_wrap
Search again from the start of the file when reaching the end

Type boolean, default False

use_live_edit
Run python while editing

Type boolean, default False

use_overwrite
Overwrite characters when typing rather than inserting them

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.504 SpaceTimeline(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceTimeline**(*Space*)

Timeline editor space data

cache_cloth

Show the active object's cloth point cache

Type boolean, default False

cache_particles

Show the active object's particle point cache

Type boolean, default False

cache_smoke

Show the active object's smoke cache

Type boolean, default False

cache_softbody

Show the active object's softbody point cache

Type boolean, default False

show_cache

Show the status of cached frames in the timeline

Type boolean, default False

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_only_selected
Show keyframes for active Object and/or its selected channels only

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.505 SpaceUVEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**SpaceUVEditor** (*bpy_struct*)
UV editor data for the image editor space

cursor_location
2D cursor location for this view

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

draw_stretch_type
Type of stretch to draw

Type enum in ['ANGLE', 'AREA'], default 'ANGLE'

edge_draw_type
Draw type for drawing UV edges

Type enum in ['OUTLINE', 'DASH', 'BLACK', 'WHITE'], default 'OUTLINE'

lock_bounds
Constraint to stay within the image bounds while editing

Type boolean, default False

pivot_point
Rotation/Scaling Pivot

Type enum in ['CENTER', 'MEDIAN', 'CURSOR'], default 'CENTER'

show_modified_edges
Draw edges after modifiers are applied

Type boolean, default False

show_normalized_coords
Display UV coordinates from 0.0 to 1.0 rather than in pixels

Type boolean, default False

show_other_objects
Draw other selected objects that share the same image

Type boolean, default False

show_smooth_edges
Draw UV edges anti-aliased

Type boolean, default False

show_stretch
Draw faces colored according to the difference in shape between UVs and their 3D coordinates (blue for low distortion, red for high distortion)

Type boolean, default False

sticky_select_mode
Automatically select also UVs sharing the same vertex as the ones being selected

Type enum in ['DISABLED', 'SHARED_LOCATION', 'SHARED_VERTEX'], default 'SHARED_LOCATION'

use_live_unwrap
Continuously unwrap the selected UV island while transforming pinned vertices

Type boolean, default False

use_snap_to_pixels
Snap UVs to pixel locations while editing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceImageEditor.uv_editor

1.4.506 SpaceUserPreferences(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceUserPreferences**(*Space*)

User preferences space data

filter_text

Search term for filtering in the UI

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.507 SpaceView3D(Space)

base classes — bpy_struct, Space

class bpy.types.**SpaceView3D**(*Space*)

3D View space data

background_images

List of background images

Type Collection of BackgroundImage, (readonly)

camera

Active camera used in this view (when unlocked from the scene's active camera)

Type Object

clip_end

3D View far clipping distance

Type float in [1, inf], default 0.0

clip_start

3D View near clipping distance

Type float in [0, inf], default 0.0

current_orientation

Current Transformation orientation

Type TransformOrientation, (readonly)

cursor_location

3D cursor location for this view (dependent on local view setting)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid_lines

The number of grid lines to display in perspective view

Type int in [0, 1024], default 0

grid_scale

The distance between 3D View grid lines

Type float in [0, inf], default 0.0

grid_subdivisions

The number of subdivisions between grid lines

Type int in [1, 1024], default 0

layers

Layers visible in this 3D View

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False)

layers_used

Layers that contain something

Type boolean array of 20 items, default (False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False, False), (readonly)

lens

Lens angle (mm) in perspective view

Type float in [1, 250], default 0.0

local_view
Display an isolated sub-set of objects, apart from the scene visibility

Type SpaceView3D, (readonly)

lock_bone
3D View center is locked to this bone's position

Type string, default ""

lock_camera_and_layers
Use the scene's active camera and layers in this view, rather than local layers

Type boolean, default False

lock_cursor
3D View center is locked to the cursor's position

Type boolean, default False

lock_object
3D View center is locked to this object's position

Type Object

pivot_point
Pivot center for rotation/scaling

Type enum in ['BOUNDING_BOX_CENTER', 'CURSOR', 'INDIVIDUAL_ORIGINS', 'MEDIAN_POINT', 'ACTIVE_ELEMENT'], default 'BOUNDING_BOX_CENTER'

region_3d
3D region in this space, in case of quad view the camera region

Type RegionView3D, (readonly)

region_quadview
3D region that defines the quad view settings

Type RegionView3D, (readonly)

show_all_objects_origin
Show the object origin center dot for all (selected and unselected) objects

Type boolean, default False

show_axis_x
Show the X axis line in perspective view

Type boolean, default False

show_axis_y
Show the Y axis line in perspective view

Type boolean, default False

show_axis_z
Show the Z axis line in perspective view

Type boolean, default False

show_background_images
Display reference images behind objects in the 3D View

Type boolean, default False

show_floor
Show the ground plane grid in perspective view

Type boolean, default False

show_manipulator
Use a 3D manipulator widget for controlling transforms

Type boolean, default False

show_only_render
Display only objects which will be rendered

Type boolean, default False

show_outline_selected
Show an outline highlight around selected objects in non-wireframe views

Type boolean, default False

show_relationship_lines
Show dashed lines indicating parent or constraint relationships

Type boolean, default False

show_textured_solid
Display face-assigned textures in solid view

Type boolean, default False

transform_orientation
Transformation orientation

Type enum in ['GLOBAL', 'LOCAL', 'GIMBAL', 'NORMAL', 'VIEW', 'CUSTOM'], default 'GLOBAL'

use_manipulator_rotate
Use the manipulator for rotation transformations

Type boolean, default False

use_manipulator_scale
Use the manipulator for scale transformations

Type boolean, default False

use_manipulator_translate
Use the manipulator for movement transformations

Type boolean, default False

use_occlude_geometry
Limit selection to visible (clipped with depth buffer)

Type boolean, default False

use_pivot_point_align
Manipulate object centers only

Type boolean, default False

viewport_shade
Method to display/shade objects in the 3D View

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ObjectBase.layers_from_view
- SpaceView3D.local_view

1.4.508 SpeedControlSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.**SpeedControlSequence**(*EffectSequence*)

Sequence strip to control the speed of other strips

multiply_speed

Multiply the resulting speed after the speed factor

Type float in [0, inf], default 0.0

scale_to_length

Scale values from 0.0 to 1.0 to target sequence length

Type boolean, default False

use_as_speed

Interpret the value as speed instead of a frame number

Type boolean, default False

use_frame_blend

Blend two frames into the target for a smoother result

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.509 Spline(bpy_struct)

base class — bpy_struct

class bpy.types.**Spline**(*bpy_struct*)

Element of a curve, either Nurbs, Bezier or Polyline or a character with text objects

bezier_points

Collection of points for bezier curves only

Type SplineBezierPoints collection of BezierSplinePoint, (readonly)

character_index

Location of this character in the text data (only for text curves)

Type int in [0, inf], default 0, (readonly)

hide

Hide this curve in editmode

Type boolean, default False

material_index

Type int in [0, 32767], default 0

order_u

Nurbs order in the U direction (For splines and surfaces), Higher values let points influence a greater area

Type int in [2, 6], default 0

order_v

Nurbs order in the V direction (For surfaces only), Higher values let points influence a greater area

Type int in [2, 6], default 0

point_count_u

Total number points for the curve or surface in the U direction

Type int in [0, 32767], default 0, (readonly)

point_count_v

Total number points for the surface on the V direction

Type int in [0, 32767], default 0, (readonly)

points
Collection of points that make up this poly or nurbs spline

Type SplinePoints collection of SplinePoint, (readonly)

radius_interpolation
The type of radius interpolation for Bezier curves

Type enum in ['LINEAR', 'CARDINAL', 'BSPLINE', 'EASE'], default 'LINEAR'

resolution_u
Curve or Surface subdivisions per segment

Type int in [1, 32767], default 0

resolution_v
Surface subdivisions per segment

Type int in [1, 32767], default 0

tilt_interpolation
The type of tilt interpolation for 3D, Bezier curves

Type enum in ['LINEAR', 'CARDINAL', 'BSPLINE', 'EASE'], default 'LINEAR'

type
The interpolation type for this curve element

Type enum in ['POLY', 'BEZIER', 'BSPLINE', 'CARDINAL', 'NURBS'], default 'POLY'

use_bezier_u
Make this nurbs curve or surface act like a bezier spline in the U direction (Order U must be 3 or 4, Cyclic U must be disabled)

Type boolean, default False

use_bezier_v
Make this nurbs surface act like a bezier spline in the V direction (Order V must be 3 or 4, Cyclic V must be disabled)

Type boolean, default False

use_cyclic_u
Make this curve or surface a closed loop in the U direction

Type boolean, default False

use_cyclic_v
Make this surface a closed loop in the V direction

Type boolean, default False

use_endpoint_u
Make this nurbs curve or surface meet the endpoints in the U direction (Cyclic U must be disabled)

Type boolean, default False

use_endpoint_v
Make this nurbs surface meet the endpoints in the V direction (Cyclic V must be disabled)

Type boolean, default False

use_smooth
Smooth the normals of the surface or beveled curve

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Curve.splines
- CurveSplines.new
- CurveSplines.remove

1.4.510 SplineBezierPoints(bpy_struct)

base class — bpy_struct

class bpy.types.**SplineBezierPoints**(*bpy_struct*)

Collection of spline bezirt points

add(*count=1*)

Add a number of points to this spline.

Parameters **count** (*int in [-inf, inf], (optional)*) – Number, Number of points to add to the spline

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.bezier_points

1.4.511 SplineIKConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**SplineIKConstraint**(*Constraint*)

Align 'n' bones along a curve

chain_count

How many bones are included in the chain

Type int in [1, 255], default 0

joint_bindings

(EXPERIENCED USERS ONLY) The relative positions of the joints along the chain as percentages

Type float array of 32 items in [0, 1], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

target

Curve that controls this relationship

Type Object

use_chain_offset

Offset the entire chain relative to the root joint

Type boolean, default False

use_curve_radius

Average radius of the endpoints is used to tweak the X and Z Scaling of the bones, on top of XZ Scale mode

Type boolean, default False

use_even_divisions

Ignore the relative lengths of the bones when fitting to the curve

Type boolean, default False

use_y_stretch

Stretch the Y axis of the bones to fit the curve

Type boolean, default False

xz_scale_mode
Method used for determining the scaling of the X and Z axes of the bones

Type enum in ['NONE', 'BONE_ORIGINAL', 'VOLUME_PRESERVE'], default 'NONE'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.512 SplinePoint(bpy_struct)

base class — bpy_struct

class bpy.types.**SplinePoint**(*bpy_struct*)
Spline point without handles

co
Point coordinates

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

hide
Visibility status

Type boolean, default False

radius
Radius for bevelling

Type float in [0, inf], default 0.0

select
Selection status

Type boolean, default False

tilt
Tilt in 3D View

Type float in [-inf, inf], default 0.0

weight
Nurbs weight

Type float in [-inf, inf], default 0.0

weight_softbody
Softbody goal weight

Type float in [0.01, 100], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.points

1.4.513 SplinePoints(bpy_struct)

base class — bpy_struct

class bpy.types.**SplinePoints**(*bpy_struct*)
Collection of spline points

add(*count=1*)
Add a number of points to this spline.

Parameters **count** (*int in [1, inf], (optional)*) – Number, Number of points to add to the spline

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.points

1.4.514 SpotLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.**SpotLamp**(*Lamp*)
Directional cone lamp

compression_threshold
Deep shadow map compression threshold

Type float in [0, 1], default 0.0

falloff_curve
Custom Lamp Falloff Curve

Type CurveMapping, (readonly)

falloff_type
Intensity Decay with distance

Type enum in ['CONSTANT', 'INVERSE_LINEAR', 'INVERSE_SQUARE', 'CUSTOM_CURVE', 'LINEAR_QUADRATIC_WEIGHTED'], default 'CONSTANT'

halo_intensity
Brightness of the spotlight's halo cone (Buffer Shadows)

Type float in [-inf, inf], default 0.0

halo_step
Volumetric halo sampling frequency

Type int in [0, 12], default 0

linear_attenuation
Linear distance attenuation

Type float in [0, 1], default 0.0

quadratic_attenuation
Quadratic distance attenuation

Type float in [0, 1], default 0.0

shadow_adaptive_threshold
Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_buffer_bias
Shadow buffer sampling bias

Type float in [0.001, 5], default 0.0

shadow_buffer_clip_end
Shadow map clip end beyond which objects will not generate shadows

Type float in [0, 9999], default 0.0

shadow_buffer_clip_start
Shadow map clip start: objects closer will not generate shadows

Type float in [0, 9999], default 0.0

shadow_buffer_samples
Number of shadow buffer samples

Type int in [1, 16], default 0

shadow_buffer_size
Resolution of the shadow buffer, higher values give crisper shadows but use more memory

Type int in [512, 10240], default 0

shadow_buffer_soft
Size of shadow buffer sampling area

Type float in [0, 100], default 0.0

shadow_buffer_type
Type of shadow buffer

Type enum in ['REGULAR', 'HALFWAY', 'IRREGULAR', 'DEEP'], default 'REGULAR'

shadow_color
Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_filter_type
Type of shadow filter (Buffer Shadows)

Type enum in ['BOX', 'TENT', 'GAUSS'], default 'BOX'

shadow_method
Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'BUFFER_SHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method
Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples
Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_sample_buffers
Number of shadow buffers to render for better AA, this increases memory usage

Type enum in ['BUFFERS_1', 'BUFFERS_4', 'BUFFERS_9'], default 'BUFFERS_1'

shadow_soft_size
Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

show_cone
Draw transparent cone in 3D view to visualize which objects are contained in it

Type boolean, default False

spot_blend
The softness of the spotlight edge

Type float in [0, 1], default 0.0

spot_size
Angle of the spotlight beam in degrees

Type float in [0.0174533, 3.14159], default 0.0

use_auto_clip_end
Automatic calculation of clipping-end, based on visible vertices

Type boolean, default False

use_auto_clip_start
Automatic calculation of clipping-start, based on visible vertices

Type boolean, default False

use_halo
Renders spotlight with a volumetric halo (Buffer Shadows)

Type boolean, default False

use_only_shadow
Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer
Causes only objects on the same layer to cast shadows

Type boolean, default False

use_sphere
Sets light intensity to zero beyond lamp distance

Type boolean, default False

use_square
Casts a square spot light shape

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.515 StateActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**StateActuator** (*Actuator*)

Actuator to handle states

operation

Select the bit operation on object state mask

Type enum in ['SET', 'ADD', 'REMOVE', 'CHANGE'], default 'SET'

states

Type boolean array of 30 items, default (False, False)

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link

- Actuator.unlink

1.4.516 StretchToConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**StretchToConstraint**(*Constraint*)

Stretches to meet the target object

bulge

Factor between volume variation and stretching

Type float in [0, 100], default 0.0

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

keep_axis

Axis to maintain during stretch

Type enum in ['PLANE_X', 'PLANE_Z'], default 'PLANE_X'

rest_length

Length at rest position

Type float in [0, 100], default 0.0

subtarget

Type string, default ""

target

Target Object

Type Object

volume

Maintain the object's volume as it stretches

Type enum in ['VOLUME_XZX', 'VOLUME_X', 'VOLUME_Z', 'NO_VOLUME'], default 'VOLUME_XZX'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.517 StringProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**StringProperty** (*Property*)

RNA text string property definition

default

string default value

Type string, default "", (readonly)

length_max

Maximum length of the string, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_runtime
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.subtype
- Property.type

- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Struct.name_property

1.4.518 Struct(bpy_struct)

base class — bpy_struct

class bpy.types.**Struct**(*bpy_struct*)

RNA structure definition

base

Struct definition this is derived from

Type Struct, (readonly)

description

Description of the Struct's purpose

Type string, default "", (readonly)

functions

Type Collection of Function, (readonly)

identifier

Unique name used in the code and scripting

Type string, default "", (readonly)

name

Human readable name

Type string, default "", (readonly)

name_property
Property that gives the name of the struct

Type StringProperty, (readonly)

nested
Struct in which this struct is always nested, and to which it logically belongs

Type Struct, (readonly)

properties
Properties in the struct

Type Collection of Property, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlenderRNA.structs
- CollectionProperty.fixed_type
- PointerProperty.fixed_type
- Property.srna
- Struct.base
- Struct.nested

1.4.519 StucciTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**StucciTexture**(*Texture*)
Procedural noise texture

noise_basis
Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_scale
Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

stucci_type

Type enum in ['PLASTIC', 'WALL_IN', 'WALL_OUT'], default 'PLASTIC'

turbulence
Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.520 SubsurfModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SubsurfModifier**(*Modifier*)

Subdivision surface modifier

levels

Number of subdivisions to perform

Type int in [0, 32767], default 0

render_levels

Number of subdivisions to perform when rendering

Type int in [0, 32767], default 0

show_only_control_edges

Skip drawing/rendering of interior subdivided edges

Type boolean, default False

subdivision_type

Selects type of subdivision algorithm

Type enum in ['CATMULL_CLARK', 'SIMPLE'], default 'CATMULL_CLARK'

use_subsurf_uv

Use subsurf to subdivide UVs

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.521 SunLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.**SunLamp**(*Lamp*)

Constant direction parallel ray lamp

shadow_adaptive_threshold

Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method

Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method

Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples
Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size
Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

sky
Sky related settings for sun lamps

Type LampSkySettings, (readonly, never None)

use_only_shadow
Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer
Causes only objects on the same layer to cast shadows

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.522 SurfaceCurve(Curve)

base classes — bpy_struct, ID, Curve

class bpy.types.**SurfaceCurve**(*Curve*)

Curve datablock used for storing surfaces

use_uv_as_generated

Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Curve.animation_data
- Curve.use_auto_texspace
- Curve.use_fill_back
- Curve.bevel_depth
- Curve.bevel_object
- Curve.bevel_resolution
- Curve.use_deform_bounds
- Curve.dimensions
- Curve.show_handles
- Curve.show_normal_face
- Curve.eval_time
- Curve.extrude
- Curve.use_fill_deform
- Curve.use_path_follow
- Curve.use_fill_front
- Curve.materials
- Curve.offset
- Curve.use_time_offset
- Curve.use_path

- Curve.path_duration
- Curve.use_radius
- Curve.render_resolution_u
- Curve.render_resolution_v
- Curve.resolution_u
- Curve.resolution_v
- Curve.shape_keys
- Curve.splines
- Curve.use_stretch
- Curve.taper_object
- Curve.texspace_location
- Curve.texspace_size
- Curve.twist_mode
- Curve.twist_smooth
- Curve.use_uv_as_generated

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.523 SurfaceModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**SurfaceModifier**(*Modifier*)

Surface modifier defining modifier stack position used for surface fields

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline

- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.524 TexMapping(bpy_struct)

base class — bpy_struct

class bpy.types.**TexMapping**(*bpy_struct*)

Mapping settings

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

max

Maximum value for clipping

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

min

Minimum value for clipping

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scale

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_max

Whether to use maximum clipping value

Type boolean, default False

use_min
Whether to use minimum clipping value

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.525 Text(ID)

base classes — bpy_struct, ID

class bpy.types.**Text**(*ID*)
Text datablock referencing an external or packed text file

current_character
Index of current character in current line, and also start index of character in selection if one exists

Type int in [0, inf], default 0, (readonly)

current_line
Current line, and start line of selection if one exists

Type TextLine, (readonly, never None)

filepath
Filename of the text file

Type string, default “”

is_dirty
Text file has been edited since last save

Type boolean, default False, (readonly)

is_in_memory
Text file is in memory, without a corresponding file on disk

Type boolean, default False, (readonly)

is_modified
Text file on disk is different than the one in memory

Type boolean, default False, (readonly)

lines
Lines of text

Type Collection of TextLine, (readonly)

markers
Text markers highlighting part of the text

Type Collection of TextMarker, (readonly)

select_end_character
Index of character after end of selection in the selection end line

Type int in [0, inf], default 0, (readonly)

select_end_line
End line of selection

Type TextLine, (readonly, never None)

use_module
Register this text as a module on loading, Text name must end with ".py"

Type boolean, default False

use_tabs_as_spaces
Automatically converts all new tabs into spaces

Type boolean, default False

users_logic
Logic bricks that use this text (readonly)

clear()
clear the text block.

write(*text*)
write text at the cursor location and advance to the end of the text block.

Parameters **text** (*string*) – New text for this datablock.

static **as_string**(*self*)
Return the text as a string.

from_string(*string*)
Replace text with this string.

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.texts
- BlendDataTexts.load
- BlendDataTexts.new
- BlendDataTexts.remove
- Filter2DActuator.glsl_shader
- PythonConstraint.text
- PythonController.text
- SceneGameData.dome_text
- SpaceTextEditor.text

1.4.526 TextBox(bpy_struct)

base class — bpy_struct

class bpy.types.**TextBox**(*bpy_struct*)

Text bounding box for layout

height

Type float in [0, 50], default 0.0

width

Type float in [0, 50], default 0.0

x

Type float in [-50, 50], default 0.0

y

Type float in [-50, 50], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- TextCurve.text_boxes

1.4.527 TextCharacterFormat(bpy_struct)

base class — bpy_struct

class bpy.types.**TextCharacterFormat**(*bpy_struct*)

Text character formatting settings

use_bold

Type boolean, default False

use_italic

Type boolean, default False

use_small_caps

Type boolean, default False

use_underline

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- TextCurve.body_format
- TextCurve.edit_format

1.4.528 TextCurve(Curve)

base classes — bpy_struct, ID, Curve

class bpy.types.**TextCurve**(*Curve*)

Curve datablock used for storing text

active_textbox

Type int in [-inf, inf], default 0

align

Text align from the object center

Type enum in ['LEFT', 'CENTER', 'RIGHT', 'JUSTIFY', 'FLUSH'], default 'LEFT'

body

contents of this text object

Type string, default ""

body_format

Stores the style of each character

Type Collection of TextCharacterFormat, (readonly)

edit_format

Editing settings character formatting

Type TextCharacterFormat, (readonly)

family
Use Blender Objects as font characters. Give font objects a common name followed by the character it represents, eg. familya, familyb etc, and turn on Verts Duplication

Type string, default ""

follow_curve
Curve deforming text object

Type Object

font

Type VectorFont

font_bold

Type VectorFont

font_bold_italic

Type VectorFont

font_italic

Type VectorFont

offset_x
Horizontal offset from the object origin

Type float in [-50, 50], default 0.0

offset_y
Vertical offset from the object origin

Type float in [-50, 50], default 0.0

shear
Italic angle of the characters

Type float in [-1, 1], default 0.0

size

Type float in [0.0001, 10000], default 0.0

small_caps_scale
Scale of small capitals

Type float in [-inf, inf], default 0.0

space_character

Type float in [0, 10], default 0.0

space_line

Type float in [0, 10], default 0.0

space_word

Type float in [0, 10], default 0.0

text_boxes

Type Collection of TextBox, (readonly)

underline_height

Type float in [-0.2, 0.8], default 0.0

underline_position
Vertical position of underline

Type float in [-0.2, 0.8], default 0.0

use_fast_edit
Don't fill polygons while editing

Type boolean, default False

use_uv_as_generated
Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Curve.animation_data
- Curve.use_auto_texspace
- Curve.use_fill_back
- Curve.bevel_depth
- Curve.bevel_object
- Curve.bevel_resolution
- Curve.use_deform_bounds
- Curve.dimensions
- Curve.show_handles
- Curve.show_normal_face
- Curve.eval_time
- Curve.extrude
- Curve.use_fill_deform
- Curve.use_path_follow
- Curve.use_fill_front
- Curve.materials
- Curve.offset
- Curve.use_time_offset
- Curve.use_path
- Curve.path_duration
- Curve.use_radius
- Curve.render_resolution_u
- Curve.render_resolution_v
- Curve.resolution_u
- Curve.resolution_v
- Curve.shape_keys
- Curve.splines
- Curve.use_stretch
- Curve.taper_object

- Curve.texspace_location
- Curve.texspace_size
- Curve.twist_mode
- Curve.twist_smooth
- Curve.use_uv_as_generated

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.529 TextLine(bpy_struct)

base class — bpy_struct

class bpy.types.**TextLine** (*bpy_struct*)

Line of text in a Text datablock

body

Text in the line

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Text.current_line
- Text.lines
- Text.select_end_line

1.4.530 TextMarker(bpy_struct)

base class — bpy_struct

class bpy.types.**TextMarker**(*bpy_struct*)

Marker highlighting a portion of text in a Text datablock

character_index_end

Start position of the marker in the line

Type int in [0, inf], default 0, (readonly)

character_index_start

Start position of the marker in the line

Type int in [0, inf], default 0, (readonly)

color

Color to display the marker with

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

group

Type int in [0, 65535], default 0, (readonly)

is_temporary

Marker is temporary

Type boolean, default False, (readonly)

line

Line in which the marker is located

Type int in [0, inf], default 0, (readonly)

use_edit_all

Edit all markers of the same group as one

Type boolean, default False, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Text.markers

1.4.531 Texture(ID)

base classes — bpy_struct, ID

subclasses — ImageTexture, MarbleTexture, EnvironmentMapTexture, PointDensityTexture, VoxelDataTexture, BlendTexture, MusgraveTexture, StucciTexture, VoronoiTexture, MagicTexture, PluginTexture, WoodTexture, CloudsTexture, DistortedNoiseTexture, NoiseTexture

class bpy.types.**Texture**(*ID*)

Texture datablock used by materials, lamps, worlds and brushes

animation_data

Animation data for this datablock

Type AnimData, (readonly)

color_ramp

Type ColorRamp, (readonly)

contrast

Type float in [0.01, 5], default 0.0

factor_blue

Type float in [0, 2], default 0.0

factor_green

Type float in [0, 2], default 0.0

factor_red

Type float in [0, 2], default 0.0

intensity

Type float in [0, 2], default 0.0

node_tree
Node tree for node-based textures

Type NodeTree, (readonly)

saturation

Type float in [0, 2], default 0.0

type

Type enum in ['NONE', 'BLEND', 'CLOUDS', 'DISTORTED_NOISE', 'ENVIRONMENT_MAP', 'IMAGE', 'MAGIC', 'MARBLE', 'MUSGRAVE', 'NOISE', 'POINT_DENSITY', 'STUCCI', 'VORONOI', 'VOXEL_DATA', 'WOOD'], default 'NONE'

use_color_ramp
Toggle color ramp operations

Type boolean, default False

use_nodes
Make this a node-based texture

Type boolean, default False

use_preview_alpha
Show Alpha in Preview Render

Type boolean, default False

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.textures
- BlendDataTextures.new
- BlendDataTextures.remove
- Brush.texture
- CompositorNodeTexture.texture
- DisplaceModifier.texture
- FieldSettings.texture
- Lamp.active_texture
- Material.active_texture
- ParticleSettings.active_texture
- ShaderNodeTexture.texture
- TextureNodeTexture.texture
- TextureSlot.texture
- WaveModifier.texture
- World.active_texture

1.4.532 TextureNode(Node)

base classes — bpy_struct, Node

subclasses — TextureNodeScale, TextureNodeRGBToBW, TextureNodeTranslate, TextureNodeTexture, TextureNodeCompose, TextureNodeValToNor, TextureNodeDecompose, TextureNodeHueSaturation, TextureNodeImage, TextureNodeBricks, TextureNodeCurveTime, TextureNodeInvert, TextureNodeCurveRGB, TextureNodeDistance, TextureNodeRotate, TextureNodeMixRGB, TextureNodeChecker, TextureNodeOutput, TextureNodeCoordinates, TextureNodeValToRGB, TextureNodeMath, TextureNodeViewer

class bpy.types.**TextureNode**(*Node*)

type

Type enum in ['OUTPUT', 'CHECKER', 'TEXTURE', 'BRICKS', 'MATH', 'MIX_RGB', 'RGBTOBW', 'VALTORGB', 'IMAGE', 'CURVE_RGB', 'INVERT', 'HUE_SAT', 'CURVE_TIME', 'ROTATE', 'VIEWER', 'TRANSLATE', 'COORD', 'DISTANCE', 'COMPOSE', 'DECOMPOSE', 'VALTONOR', 'SCALE', 'SCRIPT', 'GROUP'], default 'OUTPUT', (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.533 TextureNodeBricks(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeBricks**(*TextureNode*)

offset

Type float in [0, 1], default 0.0

offset_frequency
Offset every N rows

Type int in [2, 99], default 0

squash

Type float in [0, 99], default 0.0

squash_frequency
Squash every N rows

Type int in [2, 99], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.534 TextureNodeChecker(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeChecker**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.535 TextureNodeCompose(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeCompose**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.536 TextureNodeCoordinates(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeCoordinates**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.537 TextureNodeCurveRGB(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeCurveRGB**(*TextureNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.538 TextureNodeCurveTime(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeCurveTime** (*TextureNode*)

curve

Type CurveMapping, (readonly)

frame_end

Type int in [-32768, 32767], default 0

frame_start

Type int in [-32768, 32767], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.539 TextureNodeDecompose(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeDecompose**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.540 TextureNodeDistance(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeDistance**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.541 TextureNodeHueSaturation(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeHueSaturation**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.542 TextureNodeImage(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeImage**(*TextureNode*)

image

Type Image

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.543 TextureNodeInvert(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeInvert**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.544 TextureNodeMath(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeMath**(*TextureNode*)

operation

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.545 TextureNodeMixRGB(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeMixRGB**(*TextureNode*)

blend_type

Type enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'SCREEN', 'OVERLAY', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'DODGE', 'BURN', 'COLOR', 'VALUE', 'SATURATION', 'HUE', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

use_alpha

Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.546 TextureNodeOutput(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeOutput**(*TextureNode*)

filepath

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.547 TextureNodeRGBToBW(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeRGBToBW**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.548 TextureNodeRotate(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeRotate**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name

- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.549 TextureNodeScale(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeScale**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.550 TextureNodeTexture(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeTexture**(*TextureNode*)

node_output

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

texture

Type Texture

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.551 TextureNodeTranslate(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeTranslate**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.552 TextureNodeTree(NodeTree)

base classes — bpy_struct, ID, NodeTree

class bpy.types.**TextureNodeTree**(*NodeTree*)

Node tree consisting of linked nodes used for textures

nodes

Type TextureNodes collection of Node, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag

- ID.users
- NodeTree.animation_data
- NodeTree.grease_pencil
- NodeTree.inputs
- NodeTree.links
- NodeTree.outputs
- NodeTree.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.553 TextureNodeValToNor(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeValToNor**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.554 TextureNodeValToRGB(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeValToRGB** (*TextureNode*)

color_ramp

Type ColorRamp, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.555 TextureNodeViewer(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.**TextureNodeViewer**(*TextureNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.556 TextureNodes(bpy_struct)

base class — bpy_struct

class bpy.types.**TextureNodes**(*bpy_struct*)

Collection of Texture Nodes

new(*type*, *group=None*)

Add a node to this node tree.

Parameters

- **type** (*enum in ['OUTPUT', 'CHECKER', 'TEXTURE', 'BRICKS', 'MATH', 'MIX_RGB', 'RGBTOBW', 'VALTORGB', 'IMAGE', 'CURVE_RGB', 'INVERT', 'HUE_SAT', 'CURVE_TIME', 'ROTATE', 'VIEWER', 'TRANSLATE', 'COORD', 'DISTANCE', 'COMPOSE', 'DECOMPOSE', 'VALTONOR', 'SCALE', 'SCRIPT', 'GROUP']*) – Type, Type of node to add
- **group** (NodeTree, (optional)) – The group tree

Returns New node.

Return type Node

remove (*node*)
remove a node from this node tree.

Parameters **node** (Node) – The node to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- TextureNodeTree.nodes

1.4.557 TextureSlot(bpy_struct)

base class — bpy_struct

subclasses — ParticleSettingsTextureSlot, MaterialTextureSlot, LampTextureSlot, BrushTextureSlot, WorldTextureSlot

class bpy.types.**TextureSlot** (*bpy_struct*)
Texture slot defining the mapping and influence of a texture

blend_type

Type enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'SCREEN', 'OVERLAY', 'DIFFERENCE', 'DIVIDE', 'DARKEN', 'LIGHTEN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

color
The default color for textures that don't return RGB or when RGB to intensity is enabled

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

default_value
Value to use for Ref, Spec, Amb, Emit, Alpha, RayMir, TransLu and Hard

Type float in [-inf, inf], default 0.0

invert
Inverts the values of the texture to reverse its effect

Type boolean, default False

name
Texture slot name

Type string, default "", (readonly)

offset
Fine tunes texture mapping X, Y and Z locations

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

output_node
Which output node to use, for node-based textures

Type enum in ['DUMMY'], default 'DUMMY'

scale
Sets scaling for the texture's X, Y and Z sizes

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texture
Texture datablock used by this texture slot

Type Texture

use_rgb_to_intensity
Converts texture RGB values to intensity (gray) values

Type boolean, default False

use_stencil
Use this texture as a blending value on the next texture

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UILayout.template_preview

1.4.558 Theme(bpy_struct)

base class — bpy_struct

class bpy.types.**Theme**(*bpy_struct*)

Theme settings defining draw style and colors in the user interface

bone_color_sets

Type Collection of ThemeBoneColorSet, (readonly, never None)

console

Type ThemeConsole, (readonly, never None)

dopesheet_editor

Type ThemeDopeSheet, (readonly, never None)

file_browser

Type ThemeFileBrowser, (readonly, never None)

graph_editor

Type ThemeGraphEditor, (readonly, never None)

image_editor

Type ThemeImageEditor, (readonly, never None)

info

Type ThemeInfo, (readonly, never None)

logic_editor

Type ThemeLogicEditor, (readonly, never None)

name

Name of the theme

Type string, default “”

nla_editor

Type ThemeNLAEditor, (readonly, never None)

node_editor

Type ThemeNodeEditor, (readonly, never None)

outliner

Type ThemeOutliner, (readonly, never None)

properties

Type ThemeProperties, (readonly, never None)

sequence_editor

Type ThemeSequenceEditor, (readonly, never None)

text_editor

Type ThemeTextEditor, (readonly, never None)

theme_area

Type enum in ['USER_INTERFACE', 'COLOR_SETS', 'VIEW_3D', 'TIMELINE', 'GRAPH_EDITOR', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'IMAGE_EDITOR', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'NODE_EDITOR', 'LOGIC_EDITOR', 'PROPERTIES', 'OUTLINER', 'USER_PREFERENCES', 'INFO', 'FILE_BROWSER', 'CONSOLE'], default 'USER_INTERFACE'

timeline

Type ThemeTimeline, (readonly, never None)

user_interface

Type ThemeUserInterface, (readonly, never None)

user_preferences

Type ThemeUserPreferences, (readonly, never None)

view_3d

Type ThemeView3D, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.themes

1.4.559 ThemeAudioWindow(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeAudioWindow**(*bpy_struct*)

Theme settings for the Audio Window

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

window_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.560 ThemeBoneColorSet(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeBoneColorSet**(*bpy_struct*)

Theme settings for bone color sets

active

Color used for active bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

normal

Color used for the surface of bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

select

Color used for selected bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

show_colored_constraints

Allow the use of colors indicating constraints/keyed status

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BoneGroup.colors
- Theme.bone_color_sets

1.4.561 ThemeConsole(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeConsole**(*bpy_struct*)

Theme settings for the Console

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_error

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_info

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_input

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_output

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.console

1.4.562 ThemeDopeSheet(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeDopeSheet**(*bpy_struct*)

Theme settings for the DopeSheet

active_channels_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channel_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_channel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_subchannel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

long_key

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

long_key_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

value_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.dopesheet_editor

1.4.563 ThemeFileBrowser(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeFileBrowser**(*bpy_struct*)

Theme settings for the File Browser

active_file

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

active_file_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scroll_handle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scrollbar

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_file

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tiles

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.file_browser

1.4.564 ThemeFontStyle(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeFontStyle**(*bpy_struct*)

Theme settings for Font

font_kerning_style

Which style to use for font kerning

Type enum in ['UNFITTED', 'DEFAULT'], default 'UNFITTED'

points

Type int in [6, 48], default 0

shadow

Shadow size in pixels (0, 3 and 5 supported)

Type int in [0, 5], default 0

shadow_offset_x

Shadow offset in pixels

Type int in [-10, 10], default 0

shadow_offset_y

Shadow offset in pixels

Type int in [-10, 10], default 0

shadowalpha

Type float in [0, 1], default 0.0

shadowcolor

Shadow color in grey value

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ThemeStyle.group_label
- ThemeStyle.panel_title
- ThemeStyle.widget
- ThemeStyle.widget_label

1.4.565 ThemeGraphEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeGraphEditor**(*bpy_struct*)

Theme settings for the graph editor

active_channels_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channel_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels_region

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_channel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_subchannel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_vect

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vect

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex_size

Type int in [0, 255], default 0

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lastsel_point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_size

Type int in [1, 10], default 0

window_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.graph_editor

1.4.566 ThemeImageEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeImageEditor**(*bpy_struct*)

Theme settings for the Image Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

editmesh_active

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face_dot

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face_select

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

facedot_size

Type int in [1, 10], default 0

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scope_back

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_size

Type int in [1, 10], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.image_editor

1.4.567 ThemeInfo(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeInfo**(*bpy_struct*)

Theme settings for Info

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.info

1.4.568 ThemeLogicEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeLogicEditor**(*bpy_struct*)

Theme settings for the Logic Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.logic_editor

1.4.569 ThemeNLAEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeNLAEditor**(*bpy_struct*)

Theme settings for the NLA Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bars

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bars_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

strips

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

strips_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.nla_editor

1.4.570 ThemeNodeEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeNodeEditor**(*bpy_struct*)

Theme settings for the Node Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

converter_node

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

group_node

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

in_out_node

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

node_backdrop

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

operator_node

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

wire

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

wire_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.node_editor

1.4.571 ThemeOutliner(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeOutliner** (*bpy_struct*)

Theme settings for the Outliner

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.outliner

1.4.572 ThemeProperties(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeProperties**(*bpy_struct*)

Theme settings for the Properties

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.properties

1.4.573 ThemeSequenceEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeSequenceEditor**(*bpy_struct*)

Theme settings for the Sequence Editor

audio_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

draw_action

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

effect_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

image_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

keyframe

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

meta_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

movie_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

plugin_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scene_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

transition_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

window_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.sequence_editor

1.4.574 ThemeStyle(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeStyle**(*bpy_struct*)

Theme settings for style sets

group_label

Type ThemeFontStyle, (readonly, never None)

panel_title

Type ThemeFontStyle, (readonly, never None)

panelzoom

Default zoom level for panel areas

Type float in [0.5, 2], default 0.0

widget

Type ThemeFontStyle, (readonly, never None)

widget_label

Type ThemeFontStyle, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.ui_styles

1.4.575 ThemeTextEditor(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeTextEditor**(*bpy_struct*)

Theme settings for the Text Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_numbers_background

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scroll_bar

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_builtin

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_comment

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_numbers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_special

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_string

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.text_editor

1.4.576 ThemeTimeline(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeTimeline**(*bpy_struct*)

Theme settings for the Timeline

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.timeline

1.4.577 ThemeUserInterface(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeUserInterface**(*bpy_struct*)

Theme settings for user interface elements

icon_file

Type string, default “”

wcol_box

Type ThemeWidgetColors, (readonly, never None)

wcol_list_item

Type ThemeWidgetColors, (readonly, never None)

wcol_menu

Type ThemeWidgetColors, (readonly, never None)

wcol_menu_back

Type ThemeWidgetColors, (readonly, never None)

wcol_menu_item

Type ThemeWidgetColors, (readonly, never None)

wcol_num

Type ThemeWidgetColors, (readonly, never None)

wcol_numslider

Type ThemeWidgetColors, (readonly, never None)

wcol_option

Type ThemeWidgetColors, (readonly, never None)

wcol_progress

Type ThemeWidgetColors, (readonly, never None)

wcol_pulldown

Type ThemeWidgetColors, (readonly, never None)

wcol_radio

Type ThemeWidgetColors, (readonly, never None)

wcol_regular

Type ThemeWidgetColors, (readonly, never None)

wcol_scroll

Type ThemeWidgetColors, (readonly, never None)

wcol_state

Type ThemeWidgetStateColors, (readonly, never None)

wcol_text

Type ThemeWidgetColors, (readonly, never None)

wcol_toggle

Type ThemeWidgetColors, (readonly, never None)

wcol_tool

Type ThemeWidgetColors, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.user_interface

1.4.578 ThemeUserPreferences(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeUserPreferences**(*bpy_struct*)

Theme settings for the User Preferences

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.user_preferences

1.4.579 ThemeView3D(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeView3D**(*bpy_struct*)

Theme settings for the 3D View

act_spline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bone_pose

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bone_solid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_crease

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_facesel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_seam

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_sharp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

editmesh_active

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

extra_edge_len

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

extra_face_angle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

extra_face_area

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face_dot

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face_select

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

facedot_size

Type int in [1, 10], default 0

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_vect

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vect

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lamp

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

lastsel_point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

normal

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_sel_uline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_sel_vline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_uline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_vline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_active

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_grouped

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_grouped_active

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

outline_width

Type int in [1, 5], default 0

panel

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

transform

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_normal

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_size

Type int in [1, 10], default 0

wire

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.view_3d

1.4.580 ThemeWidgetColors(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeWidgetColors**(*bpy_struct*)

Theme settings for widget color sets

inner

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

inner_sel

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

item

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

outline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadedown

Type int in [-100, 100], default 0

shadetop

Type int in [-100, 100], default 0

show_shaded

Type boolean, default False

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ThemeUserInterface.wcol_box
- ThemeUserInterface.wcol_list_item
- ThemeUserInterface.wcol_menu
- ThemeUserInterface.wcol_menu_back
- ThemeUserInterface.wcol_menu_item
- ThemeUserInterface.wcol_num
- ThemeUserInterface.wcol_numslider
- ThemeUserInterface.wcol_option
- ThemeUserInterface.wcol_progress
- ThemeUserInterface.wcol_pulldown
- ThemeUserInterface.wcol_radio
- ThemeUserInterface.wcol_regular
- ThemeUserInterface.wcol_scroll
- ThemeUserInterface.wcol_text
- ThemeUserInterface.wcol_toggle
- ThemeUserInterface.wcol_tool

1.4.581 ThemeWidgetStateColors(bpy_struct)

base class — bpy_struct

class bpy.types.**ThemeWidgetStateColors**(*bpy_struct*)

Theme settings for widget state colors

blend

Type float in [0, 1], default 0.0

inner_anim

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

inner_anim_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

inner_driven

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

inner_driven_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

inner_key

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

inner_key_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ThemeUserInterface.wcol_state

1.4.582 TimelineMarker(bpy_struct)

base class — bpy_struct

class bpy.types.**TimelineMarker**(*bpy_struct*)

Marker for noting points in the timeline

camera

Camera this timeline sets to active

Type Object

frame
The frame on which the timeline marker appears

Type int in [-inf, inf], default 0

name

Type string, default ""

select
Marker selection state

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.pose_markers
- ActionPoseMarkers.active
- ActionPoseMarkers.new
- ActionPoseMarkers.remove
- Scene.timeline_markers
- TimelineMarkers.new
- TimelineMarkers.remove

1.4.583 TimelineMarkers(bpy_struct)

base class — bpy_struct

class bpy.types.**TimelineMarkers**(*bpy_struct*)
Collection of timeline markers

new (*name*)
Add a keyframe to the curve.

Parameters **name** (*string*) – New name for the marker (not unique).

Returns Newly created timeline marker

Return type TimelineMarker

remove (*marker*)
Remove a timeline marker.

Parameters **marker** (TimelineMarker, (never None)) – Timeline marker to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.timeline_markers

1.4.584 ToolSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**ToolSettings** (*bpy_struct*)

auto_keying_mode
Mode of automatic keyframe insertion for Objects and Bones

Type enum in ['ADD_REPLACE_KEYS', 'REPLACE_KEYS'], default 'ADD_REPLACE_KEYS'

edge_path_live_unwrap
Changing edges seam re-calculates UV unwrap

Type boolean, default False

edge_path_mode
The edge flag to tag when selecting the shortest path

Type enum in ['SELECT', 'SEAM', 'SHARP', 'CREASE', 'BEVEL'], default 'SELECT'

etch_adaptive_limit
Number of bones in the subdivided stroke

Type float in [1e-05, 1], default 0.0

etch_convert_mode
Method used to convert stroke to bones

Type enum in ['FIXED', 'LENGTH', 'ADAPTIVE', 'RETARGET'], default 'FIXED'

etch_length_limit
Number of bones in the subdivided stroke

Type float in [1e-05, 100000], default 0.0

etch_number
DOC BROKEN

Type string, default ""

etch_roll_mode
Method used to adjust the roll of bones when retargeting

Type enum in ['NONE', 'VIEW', 'JOINT'], default 'NONE'

etch_side
DOC BROKEN

Type string, default ""

etch_subdivision_number
Number of bones in the subdivided stroke

Type int in [1, 255], default 0

etch_template
Template armature that will be retargeted to the stroke

Type `Object`

image_paint

Type `ImagePaint`, (readonly)

mesh_select_mode
Which mesh elements selection works on

Type boolean array of 3 items, default (False, False, False)

normal_size
Display size for normals in the 3D view

Type float in [1e-05, 1000], default 0.0

particle_edit

Type `ParticleEdit`, (readonly)

proportional_edit
Proportional editing mode

Type enum in ['DISABLED', 'ENABLED', 'CONNECTED'], default 'DISABLED'

proportional_edit_falloff
Falloff type for proportional editing mode

Type enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], default 'SMOOTH'

proportional_size
Display size for proportional editing circle

Type float in [1e-05, 5000], default 0.0

sculpt

Type `Sculpt`, (readonly)

sculpt_paint_use_unified_size
Instead of per brush radius, the radius is shared across brushes

Type boolean, default False

sculpt_paint_use_unified_strength
Instead of per brush strength, the strength is shared across brushes

Type boolean, default False

show_uv_local_view
Draw only faces with the currently displayed image assigned

Type boolean, default False

snap_element
Type of element to snap to

Type enum in ['INCREMENT', 'VERTEX', 'EDGE', 'FACE', 'VOLUME'], default 'INCREMENT'

snap_target
Which part to snap onto the target

Type enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], default 'CLOSEST'

use_auto_normalize
Ensure all bone-deforming vertex groups add up to 1.0 while weight painting

Type boolean, default False

use_bone_sketching
DOC BROKEN

Type boolean, default False

use_etch_autoname
DOC BROKEN

Type boolean, default False

use_etch_overdraw
DOC BROKEN

Type boolean, default False

use_etch_quick
DOC BROKEN

Type boolean, default False

use_grease_pencil_sessions
Allow drawing multiple strokes at a time with Grease Pencil

Type boolean, default False

use_keyframe_insert_auto
Automatic keyframe insertion for Objects and Bones

Type boolean, default False

use_keyframe_insert_keyingset
Automatic keyframe insertion using active Keying Set only

Type boolean, default False

use_mesh_automerge
Automatically merge vertices moved to the same location

Type boolean, default False

use_proportional_edit_objects
Proportional editing object mode

Type boolean, default False

use_record_with_nla
Add a new NLA Track + Strip for every loop/pass made over the animation to allow non-destructive tweaking

Type boolean, default False

use_snap
Snap during transform

Type boolean, default False

use_snap_align_rotation
Align rotation with the snapping target

Type boolean, default False

use_snap_peel_object
Consider objects as whole when finding volume center

Type boolean, default False

use_snap_project
Project individual elements on the surface of other objects

Type boolean, default False

use_uv_select_sync
Keep UV and edit mode mesh selection in sync

Type boolean, default False

uv_select_mode
UV selection and display mode

Type enum in ['VERTEX', 'EDGE', 'FACE', 'ISLAND'], default 'VERTEX'

vertex_group_weight
Weight to assign in vertex groups

Type float in [0, 1], default 0.0

vertex_paint

Type VertexPaint, (readonly)

weight_paint

Type VertexPaint, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.tool_settings
- Scene.tool_settings

1.4.585 TouchSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.**TouchSensor**(*Sensor*)
Sensor to detect objects colliding with the current object

material
Only look for objects with this material (blank = all objects)

Type Material

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

1.4.586 TrackToConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**TrackToConstraint**(*Constraint*)

Aims the constrained object toward the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

subtarget

Type string, default “”

target

Target Object

Type Object

track_axis
Axis that points to the target object

Type enum in ['TRACK_X', 'TRACK_Y', 'TRACK_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'TRACK_X'

up_axis
Axis that points upward

Type enum in ['UP_X', 'UP_Y', 'UP_Z'], default 'UP_X'

use_target_z
Target's Z axis, not World Z axis, will constraint the Up direction

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.587 TransformConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**TransformConstraint**(*Constraint*)

Maps transformations of the target to the object

from_max_x

Top range of X axis source motion

Type float in [-inf, inf], default 0.0

from_max_y

Top range of Y axis source motion

Type float in [-inf, inf], default 0.0

from_max_z

Top range of Z axis source motion

Type float in [-inf, inf], default 0.0

from_min_x

Bottom range of X axis source motion

Type float in [-inf, inf], default 0.0

from_min_y

Bottom range of Y axis source motion

Type float in [-inf, inf], default 0.0

from_min_z

Bottom range of Z axis source motion

Type float in [-inf, inf], default 0.0

map_from

The transformation type to use from the target

Type enum in ['LOCATION', 'ROTATION', 'SCALE'], default 'LOCATION'

map_to

The transformation type to affect of the constrained object

Type enum in ['LOCATION', 'ROTATION', 'SCALE'], default 'LOCATION'

map_to_x_from

The source axis constrained object's X axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

map_to_y_from

The source axis constrained object's Y axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

map_to_z_from

The source axis constrained object's Z axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

subtarget

Type string, default ""

target

Target Object

Type Object

to_max_x
Top range of X axis destination motion

Type float in [-inf, inf], default 0.0

to_max_y
Top range of Y axis destination motion

Type float in [-inf, inf], default 0.0

to_max_z
Top range of Z axis destination motion

Type float in [-inf, inf], default 0.0

to_min_x
Bottom range of X axis destination motion

Type float in [-inf, inf], default 0.0

to_min_y
Bottom range of Y axis destination motion

Type float in [-inf, inf], default 0.0

to_min_z
Bottom range of Z axis destination motion

Type float in [-inf, inf], default 0.0

use_motion_extrapolate
Extrapolate ranges

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.is_valid
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.588 TransformOrientation(bpy_struct)

base class — bpy_struct

class bpy.types.**TransformOrientation**(*bpy_struct*)

matrix

Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

name

Type string, default ""

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.orientations
- SpaceView3D.current_orientation

1.4.589 TransformSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.**TransformSequence**(*EffectSequence*)

Sequence strip applying affine transformations to other strips

interpolation

Type enum in ['NONE', 'BILINEAR', 'BICUBIC'], default 'NONE'

rotation_start

Type float in [-360, 360], default 0.0

scale_start_x

Type float in [0, inf], default 0.0

scale_start_y

Type float in [0, inf], default 0.0

translate_start_x

Type float in [-inf, inf], default 0.0

translate_start_y

Type float in [-inf, inf], default 0.0

translation_unit

Type enum in ['PIXELS', 'PERCENT'], default 'PIXELS'

use_uniform_scale

Scale uniformly, preserving aspect ratio

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select

- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.590 UILayout(bpy_struct)

base class — bpy_struct

class `bpy.types.UILayout` (*bpy_struct*)

User interface layout in a panel or header

active

Type boolean, default False

alert

Type boolean, default False

alignment

Type enum in ['EXPAND', 'LEFT', 'CENTER', 'RIGHT'], default 'EXPAND'

enabled

When false, this (sub)layout is greyed out.

Type boolean, default False

operator_context

Type enum in ['INVOKE_DEFAULT', 'INVOKE_REGION_WIN', 'INVOKE_REGION_CHANNELS', 'INVOKE_REGION_PREVIEW', 'INVOKE_AREA', 'INVOKE_SCREEN', 'EXEC_DEFAULT', 'EXEC_REGION_WIN', 'EXEC_REGION_CHANNELS', 'EXEC_REGION_PREVIEW', 'EXEC_AREA', 'EXEC_SCREEN'], default 'INVOKE_DEFAULT'

scale_x

Scale factor along the X for items in this (sub)layout.

Type float in [0, inf], default 0.0

scale_y

Scale factor along the Y for items in this (sub)layout.

Type float in [0, inf], default 0.0

row (*align=False*)

Sub-layout. Items placed in this sublayout are placed next to each other in a row.

Parameters **align** (*boolean, (optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type `UILayout`

column (*align=False*)

Sub-layout. Items placed in this sublayout are placed under each other in a column.

Parameters **align** (*boolean, (optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type `UILayout`

column_flow (*columns=0, align=False*)

column_flow

Parameters

- **columns** (*int in [0, inf], (optional)*) – Number of columns, 0 is automatic.
- **align** (*boolean, (optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type `UILayout`

box()

Sublayout. Items placed in this sublayout are placed under each other in a column and are surrounded by a box.

Returns Sub-layout to put items in.

Return type UILayout

split(*percentage=0.0*, *align=False*)

split

Parameters

- **percentage** (*float in [0, 1], (optional)*) – Percentage, Percentage of width to split at.
- **align** (*boolean, (optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type UILayout

prop(*data*, *property*, *text=""*, *icon='NONE'*, *expand=False*, *slider=False*, *toggle=False*, *icon_only=False*, *event=False*, *full_event=False*, *emboss=True*, *index=-1*)

Item. Exposes an RNA item and places it into the layout.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA',*

'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORT-

DISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

- **expand** (*boolean, (optional)*) – Expand button to show more detail.
- **slider** (*boolean, (optional)*) – Use slider widget for numeric values.
- **toggle** (*boolean, (optional)*) – Use toggle widget for boolean values.
- **icon_only** (*boolean, (optional)*) – Draw only icons in buttons, no text.
- **event** (*boolean, (optional)*) – Use button to input key events.
- **full_event** (*boolean, (optional)*) – Use button to input full events including modifiers.
- **emboss** (*boolean, (optional)*) – Draw the button itself, just the icon/text.
- **index** (*int in [-2, inf], (optional)*) – The index of this button, when set a single member of an array can be accessed, when set to -1 all array members are used.

props_enum(*data*, *property*)

props_enum

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

prop_menu_enum(*data*, *property*, *text=""*, *icon='NONE'*)

prop_menu_enum

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG',*

'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP',

'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

prop_enum(*data*, *property*, *value*, *text=""*, *icon='NONE'*)

prop_enum

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **value** (*string*) – Enum property value.
- **text** (*string, (optional)*) – Override automatic text of the item.

- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM',*

'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

prop_search (*data*, *property*, *search_data*, *search_property*, *text=""*, *icon='NONE'*)

prop_search

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.

- **property** (*string*) – Identifier of property in data.
- **search_data** (`AnyType`, (never None)) – Data from which to take collection to search in.
- **search_property** (*string*) – Identifier of search collection property.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER',*

'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

operator (*operator*, *text=""*, *icon='NONE'*, *emboss=True*)

Item. Places a button into the layout to call an Operator.

Parameters

- **operator** (*string*) – Identifier of the operator.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SUR-*

FACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC',

'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

- **emboss** (*boolean, (optional)*) – Draw the button itself, just the icon/text.

Returns Operator properties to fill in, return when 'properties' is set to true.

Return type `OperatorProperties`

operator_enum(*operator*, *property*)

operator_enum

Parameters

- **operator** (*string*) – Identifier of the operator.
- **property** (*string*) – Identifier of property in operator.

operator_menu_enum(*operator*, *property*, *text=""*, *icon='NONE'*)

operator_menu_enum

Parameters

- **operator** (*string*) – Identifier of the operator.
- **property** (*string*) – Identifier of property in operator.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS',*

'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED',

'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

label (*text=""*, *icon='NONE'*)

Item. Display text in the layout.

Parameters

- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS',*

'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED',

'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

menu (*menu*, *text=""*, *icon='NONE'*)

menu

Parameters

- **menu** (*string*) – Identifier of the menu.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'REN-*

DER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEL_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT',

'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSH_CREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

separator()

Item. Inserts empty space into the layout between items.

context_pointer_set(*name*, *data*)

context_pointer_set

Parameters

- **name** (*string*) – Name, Name of entry in the context.
- **data** (AnyType) – Pointer to put in context.

template_header(*menus=True*)

template_header

Parameters **menus** (*boolean, (optional)*) – The header has menus, and should show menu expander.

template_ID(*data*, *property*, *new=""*, *open=""*, *unlink=""*)

template_ID

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **new** (*string, (optional)*) – Operator identifier to create a new ID block.
- **open** (*string, (optional)*) – Operator identifier to open a file for creating a new ID block.
- **unlink** (*string, (optional)*) – Operator identifier to unlink the ID block.

template_ID_preview(*data*, *property*, *new=""*, *open=""*, *unlink=""*, *rows=0*, *cols=0*)

template_ID_preview

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **new** (*string, (optional)*) – Operator identifier to create a new ID block.
- **open** (*string, (optional)*) – Operator identifier to open a file for creating a new ID block.

- **unlink** (*string, (optional)*) – Operator identifier to unlink the ID block.
- **rows** (*int in [0, inf], (optional)*) – Number of thumbnail preview rows to display
- **cols** (*int in [0, inf], (optional)*) – Number of thumbnail preview columns to display

template_any_ID(*data*, *property*, *type_property*, *text=""*)

template_any_ID

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **type_property** (*string*) – Identifier of property in data giving the type of the ID-blocks to use.
- **text** (*string, (optional)*) – Custom label to display in UI.

template_path_builder(*data*, *property*, *root*, *text=""*)

template_path_builder

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **root** (ID) – ID-block from which path is evaluated from.
- **text** (*string, (optional)*) – Custom label to display in UI.

template_modifier(*data*)

Layout . Generates the UI layout for modifiers.

Parameters **data** (Modifier, (never None)) – Modifier data.

Returns Sub-layout to put items in.

Return type UILayout

template_constraint(*data*)

Layout . Generates the UI layout for constraints.

Parameters **data** (Constraint, (never None)) – Constraint data.

Returns Sub-layout to put items in.

Return type UILayout

template_preview(*id*, *show_buttons=True*, *parent=None*, *slot=None*)

Item. A preview window for materials, textures, lamps, etc.

Parameters

- **id** (ID) – ID datablock.
- **show_buttons** (*boolean, (optional)*) – Show preview buttons?
- **parent** (ID, (optional)) – ID datablock.
- **slot** (TextureSlot, (optional)) – Texture slot.

template_curve_mapping(*data*, *property*, *type='NONE'*, *levels=False*, *brush=False*)

Item. A curve mapping widget used for e.g falloff curves for lamps.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **type** (*enum in ['NONE', 'VECTOR', 'COLOR'], (optional)*) – Type, Type of curves to display.
- **levels** (*boolean, (optional)*) – Show black/white levels.
- **brush** (*boolean, (optional)*) – Show brush options.

template_color_ramp(*data*, *property*, *expand=False*)

Item. A color ramp widget.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **expand** (*boolean, (optional)*) – Expand button to show more detail.

template_histogram(*data*, *property*)

Item. A histogramm widget to analyze imaga data.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_waveform(*data*, *property*)

Item. A waveform widget to analyze imaga data.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_vectorscope(*data*, *property*)

Item. A vectorscope widget to analyze imaga data.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_layers(*data*, *property*, *used_layers_data*, *used_layers_property*, *active_layer*)

template_layers

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **used_layers_data** (AnyType) – Data from which to take property.
- **used_layers_property** (*string*) – Identifier of property in data.
- **active_layer** (*int in [0, inf]*) – Active Layer

template_color_wheel(*data*, *property*, *value_slider=False*, *lock=False*, *lock_luminosity=False*, *cubic=True*)

Item. A color wheel widget to pick colors.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **value_slider** (*boolean, (optional)*) – Display the value slider to the right of the color wheel
- **lock** (*boolean, (optional)*) – Lock the color wheel display to value 1.0 regardless of actual color
- **lock_luminosity** (*boolean, (optional)*) – Keep the color at its original vector length
- **cubic** (*boolean, (optional)*) – Cubic saturation for picking values close to white

template_image_layers(*image*, *image_user*)
template_image_layers

template_image(*data*, *property*, *image_user*, *compact=False*)
Item(s). User interface for selecting images and their source paths.

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **compact** (*boolean, (optional)*) – Use more compact layout.

template_list(*data*, *property*, *active_data*, *active_property*, *rows=5*, *maxrows=5*, *type='DEFAULT'*)
Item. A list widget to display data. e.g. vertexgroups.

Parameters

- **data** (AnyType) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **active_data** (AnyType, (never None)) – Data from which to take property for the active element.
- **active_property** (*string*) – Identifier of property in data, for the active element.
- **rows** (*int in [0, inf], (optional)*) – Number of rows to display.
- **maxrows** (*int in [0, inf], (optional)*) – Maximum number of rows to display.
- **type** (*enum in ['DEFAULT', 'COMPACT', 'ICONS'], (optional)*) – Type, Type of list to use.

template_running_jobs()
template_running_jobs

template_operator_search()
template_operator_search

template_header_3D()
template_header_3D

template_reports_banner()
template_reports_banner

introspect()
introspect

Returns Descr, DESCR

Return type string

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Header.layout
- Menu.layout
- Operator.layout
- Panel.layout
- UILayout.box
- UILayout.column
- UILayout.column_flow
- UILayout.row
- UILayout.split
- UILayout.template_constraint
- UILayout.template_modifier

1.4.591 UVProjectModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**UVProjectModifier**(*Modifier*)

UV projection modifier to sets UVs from a projector

aspect_x

Type float in [1, inf], default 0.0

aspect_y

Type float in [1, inf], default 0.0

image

Type Image

projector_count

Number of projectors to use

Type int in [1, 10], default 0

projectors

Type Collection of UVProjector, (readonly)

scale_x

Type float in [0, inf], default 0.0

scale_y

Type float in [0, inf], default 0.0

use_image_override

Override faces' current images with the given image

Type boolean, default False

uv_layer

UV layer name

Type string, default ""

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- bpy_struct.type_recast
- bpy_struct.values

1.4.592 UVProjector(bpy_struct)

base class — bpy_struct

class bpy.types.**UVProjector**(*bpy_struct*)

UV projector used by the UV project modifier

object

Object to use as projector transform

Type Object

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UVProjectModifier.projectors

1.4.593 UVTextures(bpy_struct)

base class — bpy_struct

class bpy.types.**UVTextures**(*bpy_struct*)

Collection of uv textures

active

Active UV texture

Type MeshTextureFaceLayer

active_index
Active UV texture index

Type int in [0, inf], default 0

new(*name="UVTex"*)
Add a UV texture layer to Mesh.

Parameters **name** (*string, (optional)*) – UV Texture name.

Returns The newly created layer.

Return type MeshTextureFaceLayer

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.uv_textures

1.4.594 UnitSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**UnitSettings**(*bpy_struct*)

scale_length
Scale to use when converting between blender units and dimensions

Type float in [1e-05, 100000], default 0.0

system
The unit system to use for button display

Type enum in ['NONE', 'METRIC', 'IMPERIAL'], default 'NONE'

system_rotation
Unit to use for displaying/editing rotation values

Type enum in ['DEGREES', 'RADIANS'], default 'DEGREES'

use_separate
Display units in pairs

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.unit_settings

1.4.595 UnknownType(bpy_struct)

base class — bpy_struct

class bpy.types.**UnknownType**(*bpy_struct*)
Stub RNA type used for pointers to unknown or internal data

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ShapeKey.data
- SpaceSequenceEditor.grease_pencil

1.4.596 UserPreferences(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferences**(*bpy_struct*)

Global user preferences

active_section

Active section of the user preferences shown in the user interface

Type enum in ['INTERFACE', 'EDITING', 'INPUT', 'ADDONS', 'THEMES', 'FILES', 'SYSTEM'], default 'INTERFACE'

addons

Type Addons collection of Addon, (readonly)

edit

Settings for interacting with Blender data

Type UserPreferencesEdit, (readonly, never None)

filepaths

Default paths for external files

Type UserPreferencesFilePaths, (readonly, never None)

inputs

Settings for input devices

Type UserPreferencesInput, (readonly, never None)

system

Graphics driver and operating system settings

Type UserPreferencesSystem, (readonly, never None)

themes

Type Collection of Theme, (readonly)

ui_styles

Type Collection of ThemeStyle, (readonly)

view

Preferences related to viewing data

Type UserPreferencesView, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.user_preferences

1.4.597 UserPreferencesEdit(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesEdit**(*bpy_struct*)

Settings for interacting with Blender data

auto_keying_mode

Mode of automatic keyframe insertion for Objects and Bones

Type enum in ['ADD_REPLACE_KEYS', 'REPLACE_KEYS'], default 'ADD_REPLACE_KEYS'

grease_pencil_eraser_radius
Radius of eraser 'brush'

Type int in [0, 100], default 0

grease_pencil_euclidean_distance
Distance moved by mouse when drawing stroke (in pixels) to include

Type int in [0, 100], default 0

grease_pencil_manhattan_distance
Pixels moved by mouse per axis when drawing stroke

Type int in [0, 100], default 0

keyframe_new_handle_type

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

keyframe_new_interpolation_type

Type enum in ['CONSTANT', 'LINEAR', 'BEZIER'], default 'CONSTANT'

material_link
Toggle whether the material is linked to object data or the object block

Type enum in ['OBDATA', 'OBJECT'], default 'OBDATA'

object_align
When adding objects from a 3D View menu, either align them to that view's direction or the world coordinates

Type enum in ['WORLD', 'VIEW'], default 'WORLD'

sculpt_paint_overlay_color
Color of texture overlay

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

undo_memory_limit
Maximum memory usage in megabytes (0 means unlimited)

Type int in [0, 32767], default 0

undo_steps
Number of undo steps available (smaller values conserve memory)

Type int in [0, 64], default 0

use_auto_keying
Automatic keyframe insertion for Objects and Bones

Type boolean, default False

use_drag_immediately
Moving things with a mouse drag confirms when releasing the button

Type boolean, default False

use_duplicate_action
Causes actions to be duplicated with the object

Type boolean, default False

use_duplicate_armature
Causes armature data to be duplicated with the object

Type boolean, default False

use_duplicate_curve
Causes curve data to be duplicated with the object

Type boolean, default False

use_duplicate_fcurve
Causes F-curve data to be duplicated with the object

Type boolean, default False

use_duplicate_lamp
Causes lamp data to be duplicated with the object

Type boolean, default False

use_duplicate_material
Causes material data to be duplicated with the object

Type boolean, default False

use_duplicate_mesh
Causes mesh data to be duplicated with the object

Type boolean, default False

use_duplicate_metaball
Causes metaball data to be duplicated with the object

Type boolean, default False

use_duplicate_particle
Causes particle systems to be duplicated with the object

Type boolean, default False

use_duplicate_surface
Causes surface data to be duplicated with the object

Type boolean, default False

use_duplicate_text
Causes text data to be duplicated with the object

Type boolean, default False

use_duplicate_texture
Causes texture data to be duplicated with the object

Type boolean, default False

use_enter_edit_mode
Enter Edit Mode automatically after adding a new object

Type boolean, default False

use_global_undo
Global undo works by keeping a full copy of the file itself in memory, so takes extra memory

Type boolean, default False

use_grease_pencil_simplify_stroke
Simplify the final stroke

Type boolean, default False

use_grease_pencil_smooth_stroke
Smooth the final stroke

Type boolean, default False

use_insertkey_xyz_to_rgb
Color for newly added transformation F-Curves (Location, Rotation, Scale) and also Color is based on the transform axis

Type boolean, default False

use_keyframe_insert_available
Automatic keyframe insertion in available curves

Type boolean, default False

use_keyframe_insert_needed
Keyframe insertion only when keyframe needed

Type boolean, default False

use_negative_frames
Current frame number can be manually set to a negative value

Type boolean, default False

use_visual_keying
Use Visual keying automatically for constrained objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.edit

1.4.598 UserPreferencesFilePaths(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesFilePaths**(*bpy_struct*)

Default paths for external files

animation_player

Path to a custom animation/frame sequence player

Type string, default “”

animation_player_preset

Preset configs for external animation players

Type enum in [’BLENDER24’, ‘DJV’, ‘FRAMECYCLER’, ‘RV’, ‘MPLAYER’, ‘CUSTOM’], default ‘BLENDER24’

auto_save_time

The time (in minutes) to wait between automatic temporary saves

Type int in [1, 60], default 0

font_directory

The default directory to search for loading fonts

Type string, default “”

hide_recent_locations

Hide recent locations in the file selector

Type boolean, default False

image_editor

Path to an image editor

Type string, default “”

recent_files

Maximum number of recently opened files to remember

Type int in [0, 30], default 0

render_output_directory

The default directory for rendering output, for new scenes

Type string, default “”

save_version

The number of old versions to maintain in the current directory, when manually saving

Type int in [0, 32], default 0

script_directory

The default directory to search for Python scripts (resets python module search path: sys.path)

Type string, default “”

sequence_plugin_directory

The default directory to search for sequence plugins

Type string, default “”

show_hidden_files_datablocks

Hide files/datablocks that start with a dot(.*)

Type boolean, default False

show_thumbnails
Open in thumbnail view for images and movies

Type boolean, default False

sound_directory
The default directory to search for sounds

Type string, default “”

temporary_directory
The directory for storing temporary save files

Type string, default “”

texture_directory
The default directory to search for textures

Type string, default “”

texture_plugin_directory
The default directory to search for texture plugins

Type string, default “”

use_auto_save_temporary_files
Automatic saving of temporary files in temp directory, uses process ID

Type boolean, default False

use_file_compression
Enable file compression when saving .blend files

Type boolean, default False

use_filter_files
Display only files with extensions in the image select window

Type boolean, default False

use_load_ui
Load user interface setup when loading .blend files

Type boolean, default False

use_relative_paths
Default relative path option for the file selector

Type boolean, default False

use_save_preview_images
Enables automatic saving of preview images in the .blend file

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.filepaths

1.4.599 UserPreferencesInput(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesInput** (*bpy_struct*)

Settings for input devices

active_keyconfig

The name of the active key configuration

Type string, default “”

drag_threshold

Amount of pixels you have to drag before dragging UI items happens

Type int in [3, 40], default 0

edited_keymaps

Type Collection of KeyMap, (readonly)

invert_mouse_wheel_zoom

Invert the axis of mouse movement for zooming

Type boolean, default False

invert_zoom_wheel

Swap the Mouse Wheel zoom direction

Type boolean, default False

mouse_double_click_time

The time (in ms) for a double click

Type int in [1, 1000], default 0

ndof_pan_speed
The overall panning speed of an NDOF device, as percent of standard

Type int in [0, 200], default 0

ndof_rotate_speed
The overall rotation speed of an NDOF device, as percent of standard

Type int in [0, 200], default 0

select_mouse
The mouse button used for selection

Type enum in ['LEFT', 'RIGHT'], default 'RIGHT'

use_emulate_numpad
Causes the 1 to 0 keys to act as the numpad (useful for laptops)

Type boolean, default False

use_mouse_continuous
Allow moving the mouse outside the view on some manipulations (transform, ui control drag)

Type boolean, default False

use_mouse_emulate_3_button
Emulates Middle Mouse with Alt+LeftMouse (doesn't work with Left Mouse Select option)

Type boolean, default False

use_mouse_mmb_paste
In text window, paste with middle mouse button instead of panning

Type boolean, default False

view_rotate_method
Rotation style in the viewport

Type enum in ['TURNTABLE', 'TRACKBALL'], default 'TURNTABLE'

view_zoom_axis
Axis of mouse movement to zoom in or out on

Type enum in ['VERTICAL', 'HORIZONTAL'], default 'VERTICAL'

view_zoom_method
Which style to use for viewport scaling

Type enum in ['CONTINUE', 'DOLLY', 'SCALE'], default 'CONTINUE'

wheel_scroll_lines
The number of lines scrolled at a time with the mouse wheel

Type int in [0, 32], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.inputs

1.4.600 UserPreferencesSystem(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesSystem**(*bpy_struct*)

Graphics driver and operating system settings

audio_channels

Sets the audio channel count

Type enum in ['MONO', 'STEREO', 'SURROUND4', 'SURROUND51', 'SURROUND71'], default 'MONO'

audio_device

Sets the audio output device

Type enum in ['NONE'], default 'NONE'

audio_mixing_buffer

Sets the number of samples used by the audio mixing buffer

Type enum in ['SAMPLES_256', 'SAMPLES_512', 'SAMPLES_1024', 'SAMPLES_2048', 'SAMPLES_4096', 'SAMPLES_8192', 'SAMPLES_16384', 'SAMPLES_32768'], default 'SAMPLES_256'

audio_sample_format

Sets the audio sample format

Type enum in ['U8', 'S16', 'S24', 'S32', 'FLOAT', 'DOUBLE'], default 'U8'

audio_sample_rate

Sets the audio sample rate

Type enum in ['RATE_44100', 'RATE_48000', 'RATE_96000', 'RATE_192000'], default 'RATE_44100'

author

Name that will be used in exported files when format supports such feature

Type string, default ""

color_picker_type
Different styles of displaying the color picker widget

Type enum in ['CIRCLE', 'SQUARE_SV', 'SQUARE_HS', 'SQUARE_HV'], default 'CIRCLE'

dpi
Font size and resolution for display

Type int in [48, 128], default 0

frame_server_port
Frameserver Port for Frameserver Rendering

Type int in [0, 32727], default 0

gl_clip_alpha
Clip alpha below this threshold in the 3D textured view

Type float in [0, 1], default 0.0

gl_texture_limit
Limit the texture size to save graphics memory

Type enum in ['CLAMP_OFF', 'CLAMP_8192', 'CLAMP_4096', 'CLAMP_2048', 'CLAMP_1024', 'CLAMP_512', 'CLAMP_256', 'CLAMP_128'], default 'CLAMP_OFF'

language
Language use for translation

Type enum in ['ENGLISH', 'JAPANESE', 'DUTCH', 'ITALIAN', 'GERMAN', 'FINNISH', 'SWEDISH', 'FRENCH', 'SPANISH', 'CATALAN', 'CZECH', 'BRAZILIAN_PORTUGUESE', 'SIMPLIFIED_CHINESE', 'RUSSIAN', 'CROATIAN', 'SERBIAN', 'UKRAINIAN', 'POLISH', 'ROMANIAN', 'ARABIC', 'BULGARIAN', 'GREEK', 'KOREAN'], default 'ENGLISH'

memory_cache_limit
Memory cache limit in sequencer (megabytes)

Type int in [0, 16384], default 0

prefetch_frames
Number of frames to render ahead during playback

Type int in [0, 500], default 0

screencast_fps
Frame rate for the screencast to be played back

Type int in [10, 50], default 0

screencast_wait_time
Time in milliseconds between each frame recorded for screencast

Type int in [50, 1000], default 0

scrollback
Maximum number of lines to store for the console buffer

Type int in [32, 32768], default 0

solid_lights
Lights user to display objects in solid draw mode

Type Collection of `UserSolidLight`, (readonly)

texture_collection_rate
Number of seconds between each run of the GL texture garbage collector

Type int in [1, 3600], default 0

texture_time_out
Time since last access of a GL texture in seconds after which it is freed. (Set to 0 to keep textures allocated.)

Type int in [0, 3600], default 0

use_antialiasing
Use anti-aliasing for the 3D view (may impact redraw performance)

Type boolean, default False

use_international_fonts
Use international fonts

Type boolean, default False

use_mipmaps
Scale textures for the 3D View (looks nicer but uses more memory and slows image reloading)

Type boolean, default False

use_preview_images
Enables automatic saving of preview images in the .blend file (Windows only)

Type boolean, default False

use_scripts_auto_execute
Allow any .blend file to run scripts automatically (unsafe with blend files from an untrusted source)

Type boolean, default False

use_tabs_as_spaces
Automatically converts all new tabs into spaces for new and loaded text files

Type boolean, default False

use_text_antialiasing
Draw user interface text anti-aliased

Type boolean, default False

use_textured_fonts
Use textures for drawing international fonts

Type boolean, default False

use_translate_buttons
Translate button labels

Type boolean, default False

use_translate_toolbox
Translate toolbox menu

Type boolean, default False

use_translate_tooltips
Translate Tooltips

Type boolean, default False

use_vertex_buffer_objects
Use Vertex Buffer Objects (or Vertex Arrays, if unsupported) for viewport rendering

Type boolean, default False

use_weight_color_range
Enable color range used for weight visualization in weight painting mode

Type boolean, default False

weight_color_range
Color range used for weight visualization in weight painting mode

Type ColorRamp, (readonly, never None)

window_draw_method
Drawing method used by the window manager

Type enum in ['AUTOMATIC', 'TRIPLE_BUFFER', 'OVERLAP', 'OVERLAP_FLIP', 'FULL'], default 'TRIPLE_BUFFER'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.system

1.4.601 UserPreferencesView(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesView**(*bpy_struct*)
Preferences related to viewing data

manipulator_handle_size
Size of widget handles as percentage of widget radius

Type int in [2, 40], default 0

manipulator_hotspot
Hotspot in pixels for clicking widget handles

Type int in [4, 40], default 0

manipulator_size
Diameter of widget, in 10 pixel units

Type int in [2, 40], default 0

mini_axis_brightness
The brightness of the icon

Type int in [0, 10], default 0

mini_axis_size
The axis icon's size

Type int in [10, 64], default 0

object_origin_size
Diameter in Pixels for Object/Lamp origin display

Type int in [4, 10], default 0

open_left_mouse_delay
Time in 1/10 seconds to hold the Left Mouse Button before opening the toolbox

Type int in [1, 40], default 0

open_right_mouse_delay
Time in 1/10 seconds to hold the Right Mouse Button before opening the toolbox

Type int in [1, 40], default 0

open_sublevel_delay
Time delay in 1/10 seconds before automatically opening sub level menus

Type int in [1, 40], default 0

open_toplevel_delay
Time delay in 1/10 seconds before automatically opening top level menus

Type int in [1, 40], default 0

rotation_angle
The rotation step for numerical pad keys (2 4 6 8)

Type int in [0, 90], default 0

show_column_layout
Use a column layout for toolbox

Type boolean, default False

show_large_cursors
Use large mouse cursors when available

Type boolean, default False

show_manipulator
Use 3D transform manipulator

Type boolean, default False

show_mini_axis
Show a small rotating 3D axis in the bottom left corner of the 3D View

Type boolean, default False

show_object_info
Display objects name and frame number in 3D view

Type boolean, default False

show_playback_fps
Show the frames per second screen refresh rate, while animation is played back

Type boolean, default False

show_splash
Display splash screen on startup

Type boolean, default False

show_tooltips
Display tooltips

Type boolean, default False

show_tooltips_python
Show Python references in tooltips

Type boolean, default False

show_view_name
Show the name of the view's direction in each 3D View

Type boolean, default False

smooth_view
The time to animate the view in milliseconds, zero to disable

Type int in [0, 1000], default 0

timecode_style
Format of Time Codes displayed when not displaying timing in terms of frames

Type enum in ['MINIMAL', 'SMPTE', 'SMPTE_COMPACT', 'MILLISECONDS', 'SECONDS_ONLY'], default 'MINIMAL'

use_auto_perspective
Automatically switch between orthographic and perspective when changing from top/front/side views

Type boolean, default False

use_directional_menus
Otherwise menus, etc will always be top to bottom, left to right, no matter opening direction

Type boolean, default False

use_global_pivot
Lock the same rotation/scaling pivot in all 3D Views

Type boolean, default False

use_global_scene
Forces the current Scene to be displayed in all Screens

Type boolean, default False

use_mouse_auto_depth
Use the depth under the mouse to improve view pan/rotate/zoom functionality

Type boolean, default False

use_mouse_over_open
Open menu buttons and pulldowns automatically when the mouse is hovering

Type boolean, default False

use_rotate_around_active
Use selection as the pivot point

Type boolean, default False

use_zoom_to_mouse
Zoom in towards the mouse pointer's position in the 3D view, rather than the 2D window center

Type boolean, default False

view2d_grid_spacing_min
Minimum number of pixels between each gridline in 2D Viewports

Type int in [1, 500], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.view

1.4.602 UserSolidLight(bpy_struct)

base class — bpy_struct

class bpy.types.**UserSolidLight** (*bpy_struct*)

Light used for OpenGL lighting in solid draw mode

diffuse_color

The diffuse color of the OpenGL light

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

direction

The direction that the OpenGL light is shining

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

specular_color

The color of the lights specular highlight

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use

Enable this OpenGL light in solid draw mode

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferencesSystem.solid_lights

1.4.603 ValueNodeSocket(NodeSocket)

base classes — bpy_struct, NodeSocket

class bpy.types.**ValueNodeSocket** (*NodeSocket*)
Input or output socket of a node

default_value
Default value of the socket when no link is attached

Type float array of 1 items in [-inf, inf], default (0.0)

Inherited Properties

- bpy_struct.id_data
- NodeSocket.name
- NodeSocket.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.604 VectorFont(ID)

base classes — bpy_struct, ID

class bpy.types.**VectorFont** (*ID*)
Vector font for Text objects

filepath

Type string, default "", (readonly)

packed_file

Type PackedFile, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library

- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.fonts
- BlendDataFonts.load
- BlendDataFonts.remove
- TextCurve.font
- TextCurve.font_bold
- TextCurve.font_bold_italic
- TextCurve.font_italic

1.4.605 VectorNodeSocket(NodeSocket)

base classes — bpy_struct, NodeSocket

class bpy.types.**VectorNodeSocket** (*NodeSocket*)

Input or output socket of a node

default_value

Default value of the socket when no link is attached

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

- NodeSocket.name
- NodeSocket.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.606 VertexColors(bpy_struct)

base class — bpy_struct

class bpy.types.**VertexColors**(*bpy_struct*)

Collection of vertex colors

active

Active vertex color layer

Type MeshColorLayer

active_index

Active vertex color index

Type int in [0, inf], default 0

new(*name="Col"*)

Add a vertex color layer to Mesh.

Parameters **name** (*string, (optional)*) – Vertex color name.

Returns The newly created layer.

Return type MeshColorLayer

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertex_colors

1.4.607 VertexGroup(bpy_struct)

base class — bpy_struct

class bpy.types.**VertexGroup**(*bpy_struct*)

Group of vertices, used for armature deform and other purposes

index

Index number of the vertex group

Type int in [0, inf], default 0, (readonly)

name

Vertex group name

Type string, default ""

add(*index*, *weight*, *type*)

Add vertices to the group.

Parameters

- **index** (*int array of 1 items in [-inf, inf]*) – Index List.
- **weight** (*float in [0, 1]*) – Vertex weight.
- **type** (*enum in ['REPLACE', 'ADD', 'SUBTRACT']*) – Vertex assign mode.

remove(*index*)

Remove a vertex from the group.

Parameters **index** (*int array of 1 items in [-inf, inf]*) – Index List.

weight(*index*)

Get a vertex weight from the group.

Parameters **index** (*int in [0, inf]*) – Index, The index of the vertex.

Returns Vertex weight.

Return type float in [0, 1]

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.vertex_groups
- VertexGroups.active
- VertexGroups.new
- VertexGroups.remove

1.4.608 VertexGroupElement(bpy_struct)

base class — bpy_struct

class bpy.types.**VertexGroupElement**(*bpy_struct*)

Weight value of a vertex in a vertex group

group

Type int in [0, inf], default 0, (readonly)

weight

Vertex Weight

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- LatticePoint.groups
- MeshVertex.groups

1.4.609 VertexGroups(bpy_struct)

base class — bpy_struct

class bpy.types.**VertexGroups**(*bpy_struct*)

Collection of vertex groups

active

Vertex groups of the object

Type VertexGroup, (readonly)

active_index

Active index in vertex group array

Type int in [-32768, 32767], default 0

new(*name="Group"*)

Add vertex group to object.

Parameters **name** (*string, (optional)*) – Vertex group name.

Returns New vertex group.

Return type VertexGroup

remove(*group*)

Delete vertex group from object.

Parameters **group** (VertexGroup, (never None)) – Vertex group to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.vertex_groups

1.4.610 VertexPaint(Paint)

base classes — bpy_struct, Paint

class bpy.types.**VertexPaint**(*Paint*)

Properties of vertex and weight paint mode

use_all_faces

Paint on all faces inside brush

Type boolean, default False

use_normal

Applies the vertex normal before painting

Type boolean, default False

use_spray

Keep applying paint effect while holding mouse

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Paint.brush

- Paint.show_low_resolution
- Paint.show_brush
- Paint.show_brush_on_surface

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.vertex_paint
- ToolSettings.weight_paint

1.4.611 VisibilityActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**VisibilityActuator** (*Actuator*)

Actuator to set visibility and occlusion of the object

apply_to_children

Set all the children of this object to the same visibility/occlusion recursively

Type boolean, default False

use_occlusion

Set the object to occlude objects behind it. Initialized from the object type in physics button

Type boolean, default False

use_visible

Set the objects visible. Initialized from the object render restriction toggle in physics button

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name

- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

1.4.612 VoronoiTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**VoronoiTexture**(*Texture*)

Procedural voronoi texture

color_mode

Type enum in ['INTENSITY', 'POSITION', 'POSITION_OUTLINE', 'POSITION_OUTLINE_INTENSITY'], default 'INTENSITY'

distance_metric

Type enum in ['DISTANCE', 'DISTANCE_SQUARED', 'MANHATTAN', 'CHEBYCHEV', 'MINKOVSKY_HALF', 'MINKOVSKY_FOUR', 'MINKOVSKY'], default 'DISTANCE'

minkovsky_exponent

Minkovsky exponent

Type float in [0.01, 10], default 0.0

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_intensity

Type float in [0.01, 10], default 0.0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

weight_1
Voronoi feature weight 1

Type float in [-2, 2], default 0.0

weight_2
Voronoi feature weight 2

Type float in [-2, 2], default 0.0

weight_3
Voronoi feature weight 3

Type float in [-2, 2], default 0.0

weight_4
Voronoi feature weight 4

Type float in [-2, 2], default 0.0

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.613 VoxelData(bpy_struct)

base class — bpy_struct

class bpy.types.**VoxelData**(*bpy_struct*)

Voxel data settings

domain_object

Object used as the smoke simulation domain

Type Object

extension

Sets how the texture is extrapolated past its original bounds

Type enum in ['EXTEND', 'CLIP', 'REPEAT'], default 'EXTEND'

file_format

Format of the source data set to render

Type enum in ['BLENDER_VOXEL', 'RAW_8BIT', 'IMAGE_SEQUENCE', 'SMOKE'], default 'BLENDER_VOXEL'

filepath

The external source data file to use

Type string, default ""

intensity

Multiplier for intensity values

Type float in [0.01, inf], default 0.0

interpolation

Method to interpolate/smooth values between voxel cells

Type enum in ['NEREASTNEIGHBOR', 'TRILINEAR', 'QUADRATIC', 'TRICUBIC_CATROM', 'TRICUBIC_BSPLINE'], default 'NEREASTNEIGHBOR'

resolution
Resolution of the voxel grid

Type int array of 3 items in [-inf, inf], default (0, 0, 0)

smoke_data_type
Simulation value to be used as a texture

Type enum in ['SMOKEDENSITY', 'SMOKEHEAT', 'SMOKEVEL'], default 'SMOKEDENSITY'

still_frame
The frame number to always use

Type int in [-300000, 300000], default 0

use_still_frame
Always render a still frame from the voxel data sequence

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- VoxelDataTexture.voxel_data

1.4.614 VoxelDataTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**VoxelDataTexture**(*Texture*)
Settings for the Voxel Data texture

image

Type Image

image_user

Parameters defining which layer, pass and frame of the image is displayed

Type ImageUser, (readonly)

voxel_data

The voxel data associated with this texture

Type VoxelData, (readonly)

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.615 WaveModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.**WaveModifier**(*Modifier*)

Wave effect modifier

damping_time

Type float in [-300000, 300000], default 0.0

falloff_radius

Type float in [0, inf], default 0.0

height

Type float in [-inf, inf], default 0.0

lifetime

Type float in [-300000, 300000], default 0.0

narrowness

Type float in [0, inf], default 0.0

speed

Type float in [-inf, inf], default 0.0

start_position_object

Type Object

start_position_x

Type float in [-inf, inf], default 0.0

start_position_y

Type float in [-inf, inf], default 0.0

texture

Texture for modulating the wave

Type Texture

texture_coords

Texture coordinates used for modulating input

Type enum in ['LOCAL', 'GLOBAL', 'OBJECT', 'MAP_UV'], default 'LOCAL'

texture_coords_object

Type Object

time_offset
Either the starting frame (for positive speed) or ending frame (for negative speed.)

Type float in [-300000, 300000], default 0.0

use_cyclic
Cyclic wave effect

Type boolean, default False

use_normal
Displace along normals

Type boolean, default False

use_normal_x
Enable displacement along the X normal

Type boolean, default False

use_normal_y
Enable displacement along the Y normal

Type boolean, default False

use_normal_z
Enable displacement along the Z normal

Type boolean, default False

use_x
X axis motion

Type boolean, default False

use_y
Y axis motion

Type boolean, default False

uv_layer
UV layer name

Type string, default ""

vertex_group
Vertex group name for modulating the wave

Type string, default ""

width

Type float in [0, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline

- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

1.4.616 Window(bpy_struct)

base class — bpy_struct

class bpy.types.**Window**(*bpy_struct*)

Open window

screen

Active screen showing in the window

Type Screen, (never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.window
- WindowManager.windows

1.4.617 WindowManager(ID)

base classes — bpy_struct, ID

class bpy.types.**WindowManager**(*ID*)

Window manager datablock defining open windows and other user interface data

clipboard

Type string, default ""

keyconfigs

Registered key configurations

Type KeyConfigurations collection of KeyConfig, (readonly)

operators

Operator registry

Type Collection of Operator, (readonly)

windows

Open windows

Type Collection of Window, (readonly)

classmethod fileselect_add(*operator*)

Show up the file selector.

Parameters **operator** (Operator) – Operator to call.

classmethod modal_handler_add(*operator*)

modal_handler_add

Parameters **operator** (Operator) – Operator to call.

Return type boolean

classmethod invoke_props_popup(*operator*, *event*)

Operator popup invoke.

Parameters

- **operator** (Operator) – Operator to call.
- **event** (Event) – Event.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

classmethod invoke_props_dialog(*operator*, *width=300*, *height=20*)

Operator dialog (non-autoexec popup) invoke.

Parameters

- **operator** (Operator) – Operator to call.
- **width** (*int in [0, inf], (optional)*) – Width of the popup.
- **height** (*int in [0, inf], (optional)*) – Height of the popup.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

classmethod invoke_search_popup(*operator*)

invoke_search_popup

Parameters **operator** (Operator) – Operator to call.

classmethod invoke_popup(*operator*, *width=300*, *height=20*)

Operator popup invoke.

Parameters

- **operator** (Operator) – Operator to call.
- **width** (*int in [0, inf], (optional)*) – Width of the popup.
- **height** (*int in [0, inf], (optional)*) – Height of the popup.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

classmethod invoke_confirm(*operator*, *event*)

Operator confirmation.

Parameters

- **operator** (Operator) – Operator to call.
- **event** (Event) – Event.

Returns result

Return type enum set in {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.window_managers
- Context.window_manager

1.4.618 WipeSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.**WipeSequence**(*EffectSequence*)

Sequence strip creating a wipe transition

angle

Edge angle

Type float in [-90, 90], default 0.0

blur_width

Width of the blur edge, in percentage relative to the image size

Type float in [0, 1], default 0.0

direction

Wipe direction

Type enum in ['OUT', 'IN'], default 'OUT'

transition_type

Type enum in ['SINGLE', 'DOUBLE', 'IRIS', 'CLOCK'], default 'SINGLE'

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

1.4.619 WoodTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**WoodTexture**(*Texture*)

Procedural noise texture

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

noisebasis_2

Type enum in ['SIN', 'SAW', 'TRI'], default 'SIN'

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

wood_type

Type enum in ['BANDS', 'RINGS', 'BANDNOISE', 'RINGNOISE'], default 'BANDS'

users_material

Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

1.4.620 World(ID)

base classes — bpy_struct, ID

class bpy.types.**World**(*ID*)

World datablock describing the environment and ambient lighting of a scene

active_texture

Active texture slot being displayed

Type Texture

active_texture_index

Index of active texture slot

Type int in [0, 17], default 0

ambient_color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

animation_data

Animation data for this datablock

Type AnimData, (readonly)

color_range

The color range that will be mapped to 0-1

Type float in [0.2, 5], default 0.0

exposure

Amount of exponential color correction for light

Type float in [0, 1], default 0.0

horizon_color

Color at the horizon

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

light_settings

World lighting settings

Type WorldLighting, (readonly, never None)

mist_settings

World mist settings

Type WorldMistSettings, (readonly, never None)

star_settings

World stars settings

Type WorldStarsSettings, (readonly, never None)

texture_slots

Texture slots defining the mapping and influence of textures

Type WorldTextureSlots collection of WorldTextureSlot, (readonly)

use_sky_blend

Render background with natural progression from horizon to zenith

Type boolean, default False

use_sky_paper
Flatten blend or texture coordinates

Type boolean, default False

use_sky_real
Render background with a real horizon, relative to the camera angle

Type boolean, default False

zenith_color
Color at the zenith

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.worlds
- BlendDataWorlds.new
- BlendDataWorlds.remove
- Scene.world

1.4.621 WorldLighting(bpy_struct)

base class — bpy_struct

class bpy.types.**WorldLighting**(*bpy_struct*)

Lighting for a World datablock

adapt_to_speed

Use the speed vector pass to reduce AO samples in fast moving pixels. Higher values result in more aggressive sample reduction. Requires Vec pass enabled (for Raytrace Adaptive QMC)

Type float in [0, 1], default 0.0

ao_blend_type

Defines how AO mixes with material shading

Type enum in ['MULTIPLY', 'ADD'], default 'ADD'

ao_factor

Factor for ambient occlusion blending

Type float in [0, inf], default 0.0

bias

Bias (in radians) to prevent smoothed faces from showing banding (for Raytrace Constant Jittered)

Type float in [0, 0.5], default 0.0

correction

Ad-hoc correction for over-occlusion due to the approximation (for Approximate)

Type float in [0, 1], default 0.0

distance

Length of rays, defines how far away other faces give occlusion effect

Type float in [-inf, inf], default 0.0

environment_color

Defines where the color of the environment light comes from

Type enum in ['PLAIN', 'SKY_COLOR', 'SKY_TEXTURE'], default 'PLAIN'

environment_energy

Defines the strength of environment light

Type float in [-inf, inf], default 0.0

error_threshold

Low values are slower and higher quality (for Approximate)

Type float in [0.0001, 10], default 0.0

falloff_strength

Distance attenuation factor, the higher, the less influence farther away objects have influence

Type float in [-inf, inf], default 0.0

gather_method

Type enum in ['RAYTRACE', 'APPROXIMATE'], default 'RAYTRACE'

indirect_bounces

Number of indirect diffuse light bounces to use for approximate ambient occlusion

Type int in [1, 32767], default 0

indirect_factor
Factor for how much surrounding objects contribute to light

Type float in [0, inf], default 0.0

passes
Number of preprocessing passes to reduce overocclusion (for approximate ambient occlusion)

Type int in [0, 10], default 0

sample_method
Method for generating shadow samples (for Raytrace)

Type enum in ['CONSTANT_JITTERED', 'ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'CONSTANT_JITTERED'

samples
Amount of ray samples. Higher values give smoother results and longer rendering times

Type int in [1, 32], default 0

threshold
Samples below this threshold will be considered fully shadowed/unshadowed and skipped (for Raytrace Adaptive QMC)

Type float in [0, 1], default 0.0

use_ambient_occlusion
Use Ambient Occlusion to add shadowing based on distance between objects

Type boolean, default False

use_cache
Cache AO results in pixels and interpolate over neighbouring pixels for speedup (for Approximate)

Type boolean, default False

use_environment_light
Add light coming from the environment

Type boolean, default False

use_falloff

Type boolean, default False

use_indirect_light
Add indirect light bouncing of surrounding objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.light_settings

1.4.622 WorldMistSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**WorldMistSettings**(*bpy_struct*)

Mist settings for a World data-block

depth

The distance over which the mist effect fades in

Type float in [0, inf], default 0.0

falloff

Type of transition used to fade mist

Type enum in ['QUADRATIC', 'LINEAR', 'INVERSE_QUADRATIC'], default 'QUADRATIC'

height

Control how much mist density decreases with height

Type float in [0, 100], default 0.0

intensity

Intensity of the mist effect

Type float in [0, 1], default 0.0

start

Starting distance of the mist, measured from the camera

Type float in [0, inf], default 0.0

use_mist

Occlude objects with the environment color as they are further away

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.mist_settings

1.4.623 WorldStarsSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**WorldStarsSettings**(*bpy_struct*)

Stars setting for a World data-block

average_separation

Average distance between any two stars

Type float in [2, 1000], default 0.0

color_random

Randomize star colors

Type float in [0, 1], default 0.0

distance_min

Minimum distance to the camera for stars

Type float in [0, 1000], default 0.0

size

Average screen dimension of stars

Type float in [0, 10], default 0.0

use_stars

Enable starfield generation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.star_settings

1.4.624 WorldTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.**WorldTextureSlot**(*TextureSlot*)

Texture slot for textures in a World datablock

blend_factor

Amount texture affects color progression of the background

Type float in [-inf, inf], default 0.0

horizon_factor

Amount texture affects color of the horizon

Type float in [-inf, inf], default 0.0

object

Object to use for mapping with Object texture coordinates

Type Object

texture_coords

Texture coordinates used to map the texture onto the background

Type enum in ['VIEW', 'GLOBAL', 'ANGMAP', 'SPHERE', 'TUBE', 'OBJECT'], default 'VIEW'

use_map_blend
Affect the color progression of the background

Type boolean, default False

use_map_horizon
Affect the color of the horizon

Type boolean, default False

use_map_zenith_down
Affect the color of the zenith below

Type boolean, default False

use_map_zenith_up
Affect the color of the zenith above

Type boolean, default False

zenith_down_factor
Amount texture affects color of the zenith below

Type float in [-inf, inf], default 0.0

zenith_up_factor
Amount texture affects color of the zenith above

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.texture_slots
- WorldTextureSlots.add
- WorldTextureSlots.create

1.4.625 WorldTextureSlots(bpy_struct)

base class — bpy_struct

class bpy.types.**WorldTextureSlots**(*bpy_struct*)

Collection of texture slots

classmethod add()

add

Returns The newly initialized mtex.

Return type WorldTextureSlot

classmethod create(*index*)

create

Parameters **index** (*int in [0, inf]*) – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type WorldTextureSlot

classmethod clear(*index*)

clear

Parameters **index** (*int in [0, inf]*) – Index, Slot index to clear.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.texture_slots

1.4.626 XnorController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**XnorController**(*Controller*)

Controller passing on events based on a logical XNOR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.627 XorController(Controller)

base classes — bpy_struct, Controller

class bpy.types.**XorController**(*Controller*)

Controller passing on events based on a logical XOR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

1.4.628 bpy_struct

subclasses — ActionFCurves, ActionGroup, ActionGroups, ActionPoseMarkers, Actuator, Addon, Addons, AnimData, AnimViz, AnimVizMotionPaths, AnimVizOnionSkinning, AnyType, Area, ArmatureBones, ArmatureEditBones, BackgroundImage, BezierSplinePoint, BlendData, BlendDataActions, BlendDataArmatures, BlendDataBrushes, BlendDataCameras, BlendDataCurves, BlendDataFonts, BlendDataGreasePencils, BlendDataGroups, BlendDataImages, BlendDataLamps, BlendDataLattices, BlendDataLibraries, BlendDataMaterials, BlendDataMeshes, BlendDataMetaBalls, BlendDataNodeTrees, BlendDataObjects, BlendDataParticles, BlendDataScenes, BlendDataScreens, BlendDataSounds, BlendDataTexts, BlendDataTextures, BlendDataWindowManagers, BlendDataWorlds, BlenderRNA, BoidRule, BoidSettings, BoidState, Bone, BoneGroup, BoneGroups, ChannelDriverVariables, ChildParticle, ClothCollisionSettings, ClothSettings, CollisionSettings, ColorRamp, ColorRampElement, ColorRampElements, CompositorNodes, ConsoleLine, Constraint,

ConstraintTarget, Context, Controller, CurveMap, CurveMapPoint, CurveMapping, CurveSplines, DopeSheet, Driver, DriverTarget, DriverVariable, DupliObject, EditBone, EffectorWeights, EnumPropertyItem, EnvironmentMap, Event, FCurve, FCurveKeyframePoints, FCurveModifiers, FCurveSample, FModifier, FModifierEnvelopeControlPoint, FieldSettings, FileSelectParams, FluidSettings, Function, GPencilFrame, GPencilLayer, GPencilStroke, GPencilStrokePoint, GameObjectSettings, GameProperty, GameSoftBodySettings, GroupInputs, GroupObjects, GroupOutputs, Header, Histogram, ID, IDMaterials, IKParam, ImageUser, KeyConfig, KeyConfigurations, KeyMap, KeyMapItem, KeyMapItems, KeyMaps, Keyframe, KeyingSet, KeyingSetInfo, KeyingSetPath, KeyingSetPaths, KeyingSets, KeyingSetsAll, LampSkySettings, LampTextureSlots, LatticePoint, Macro, MaterialHalo, MaterialPhysics, MaterialRaytraceMirror, MaterialRaytraceTransparency, MaterialSlot, MaterialStrand, MaterialSubsurfaceScattering, MaterialTextureSlots, MaterialVolume, Menu, MeshColor, MeshColorLayer, MeshEdge, MeshEdges, MeshFace, MeshFaces, MeshFloatProperty, MeshFloatPropertyLayer, MeshIntProperty, MeshIntPropertyLayer, MeshSticky, MeshStringProperty, MeshStringPropertyLayer, MeshTextureFace, MeshTextureFaceLayer, MeshVertex, MeshVertices, MetaBallElements, MetaElement, Modifier, MotionPath, MotionPathVert, NlaStrip, NlaStrips, NlaTrack, NlaTracks, Node, NodeLink, NodeLinks, NodeSocket, ObjectBase, ObjectConstraints, ObjectModifiers, Operator, OperatorProperties, OperatorTypeMacro, PackedFile, Paint, Panel, Particle, ParticleBrush, ParticleDupliWeight, ParticleEdit, ParticleHairKey, ParticleKey, ParticleSettingsTextureSlots, ParticleSystem, ParticleSystems, ParticleTarget, PointCache, PointCaches, PointDensity, Pose, PoseBone, PoseBoneConstraints, Property, PropertyGroup, PropertyGroupItem, Region, RegionView3D, RenderEngine, RenderLayer, RenderLayers, RenderPass, RenderResult, RenderSettings, SPHFluidSettings, SceneBases, SceneGameData, SceneObjects, SceneRenderLayer, Scopes, Sensor, Sequence, SequenceColorBalance, SequenceCrop, SequenceEditor, SequenceElement, SequenceProxy, SequenceTransform, ShaderNodes, ShapeKey, ShapeKeyBezierPoint, ShapeKeyCurvePoint, ShapeKeyPoint, SmokeCollSettings, SmokeDomainSettings, SmokeFlowSettings, SoftBodySettings, Space, SpaceUVEditor, Spline, SplineBezierPoints, SplinePoint, SplinePoints, Struct, TexMapping, TextBox, TextCharacterFormat, TextLine, TextMarker, TextureNodes, TextureSlot, Theme, ThemeAudioWindow, ThemeBoneColorSet, ThemeConsole, ThemeDopeSheet, ThemeFileBrowser, ThemeFontStyle, ThemeGraphEditor, ThemeImageEditor, ThemeInfo, ThemeLogicEditor, ThemeNLAEditor, ThemeNodeEditor, ThemeOutliner, ThemeProperties, ThemeSequenceEditor, ThemeStyle, ThemeTextEditor, ThemeTimeline, ThemeUserInterface, ThemeUserPreferences, ThemeView3D, ThemeWidgetColors, ThemeWidgetStateColors, TimelineMarker, TimelineMarkers, ToolSettings, TransformOrientation, UILayout, UVProjector, UVTextures, UnitSettings, UnknownType, UserPreferences, UserPreferencesEdit, UserPreferencesFilePaths, UserPreferencesInput, UserPreferencesSystem, UserPreferencesView, UserSolidLight, VertexColors, VertexGroup, VertexGroupElement, VertexGroups, VoxelData, Window, WorldLighting, WorldMistSettings, WorldStarsSettings, WorldTextureSlots

class bpy.types.**bpy_struct**

built-in base class for all classes in bpy.types.

Note: Note that bpy.types.bpy_struct is not actually available from within blender, it only exists for the purpose of documentation.

---

as_pointer()

Returns the memory address which holds a pointer to blenders internal data

Returns int (memory address).

Return type int

Note: This is intended only for advanced script writers who need to pass blender data to their own C/Python modules.

Undocumented (contribute)

Undocumented (contribute)

driver_add (*path*, *index=-1*)

Adds driver(s) to the given property

Parameters

- **path** (*string*) – path to the property to drive, analogous to the fcurve's data path.
- **index** (*int*) – array index of the property drive. Defaults to -1 for all indices or a single channel if the property is not an array.

Returns The driver(s) added.

Return type `FCurve` or list if index is -1 with an array property.

driver_remove (*path*, *index=-1*)

Remove driver(s) from the given property

Parameters

- **path** (*string*) – path to the property to drive, analogous to the fcurve's data path.
- **index** (*int*) – array index of the property drive. Defaults to -1 for all indices or a single channel if the property is not an array.

Returns Success of driver removal.

Return type boolean

get (*key*, *default=None*)

Returns the value of the custom property assigned to key or default when not found (matches pythons dictionary function of the same name).

Parameters

- **key** (*string*) – The key assosiated with the custom property.
- **default** (*Undefined*) – Optional argument for the value to return if *key* is not found.

Note: Only `ID`, `Bone` and `PoseBone` classes support custom properties.

---

is_property_hidden (*property*)

Check if a property is hidden.

Returns True when the property is hidden.

Return type boolean

is_property_set (*property*)

Check if a property is set, use for testing operator properties.

Returns True when the property has been set.

Return type boolean

items()

Returns the items of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property key, value pairs.

Return type list of key, value tuples

Note: Only `ID`, `Bone` and `PoseBone` classes support custom properties.

---

keyframe_delete(*data_path*, *index=-1*, *frame=bpy.context.scene.frame_current*, *group=""*)

Remove a keyframe from this properties fcurve.

Parameters

- **data_path** (*string*) – path to the property to remove a key, analogous to the fcurve's data path.
- **index** (*int*) – array index of the property to remove a key. Defaults to -1 removing all indices or a single channel if the property is not an array.
- **frame** (*float*) – The frame on which the keyframe is deleted, defaulting to the current frame.
- **group** (*str*) – The name of the group the F-Curve should be added to if it doesn't exist yet.

Returns Success of keyframe deleation.

Return type boolean

keyframe_insert(*data_path*, *index=-1*, *frame=bpy.context.scene.frame_current*, *group=""*)

Insert a keyframe on the property given, adding fcurves and animation data when necessary.

Parameters

- **data_path** (*string*) – path to the property to key, analogous to the fcurve's data path.
- **index** (*int*) – array index of the property to key. Defaults to -1 which will key all indices or a single channel if the property is not an array.
- **frame** (*float*) – The frame on which the keyframe is inserted, defaulting to the current frame.
- **group** (*str*) – The name of the group the F-Curve should be added to if it doesn't exist yet.

Returns Success of keyframe insertion.

Return type boolean

keys()

Returns the keys of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property keys.

Return type list of strings

Note: Only `ID`, `Bone` and `PoseBone` classes support custom properties.

---

path_from_id(*property=""*)

Returns the data path from the ID to this object (string).

Parameters **property** (*string*) – Optional property name which can be used if the path is to a property of this object.

Returns The path from `bpy_struct.id_data` to this struct and property (when given).

Return type str

path_resolve (*path*, *coerce=True*)
Returns the property from the path, raise an exception when not found.

Parameters

- **path** (*string*) – path which this property resolves.
- **coerce** (*boolean*) – optional argument, when True, the property will be converted into its python representation.

type_recast ()
Return a new instance, this is needed because types such as textures can be changed at runtime.

Returns a new instance of this object with the type initialized again.

Return type subclass of `bpy_struct`

values ()
Returns the values of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property values.

Return type list

Note: Only `ID`, `Bone` and `PoseBone` classes support custom properties.

---

id_data
The `ID` object this datablock is from or None, (not available for all data types)

1.5 Utilities (bpy.utils)

This module contains utility functions specific to blender but not assosiated with blenders internal data.

bpy.utils.**blend_paths** (*absolute=False*)
Returns a list of paths to external files referenced by the loaded .blend file.

Parameters **absolute** (*boolean*) – When true the paths returned are made absolute.

Returns path list.

Return type list of strigs

bpy.utils.**keyconfig_set** (*filepath*)

bpy.utils.**load_scripts** (*reload_scripts=False*, *refresh_scripts=False*)
Load scripts and run each modules register function.

Parameters

- **reload_scripts** (*bool*) – Causes all scripts to have their unregister method called before loading.
- **refresh_scripts** (*bool*) – only load scripts which are not already loaded as modules.

bpy.utils.**modules_from_path** (*path*, *loaded_modules*)
Load all modules in a path and return them as a list.

Parameters

- **path** (*string*) – this path is scanned for scripts and packages.
- **loaded_modules** (*set*) – already loaded module names, files matching these names will be ignored.

Returns all loaded modules.

Return type list

`bpy.utils.preset_find`(*name*, *preset_path*, *display_name=False*)

`bpy.utils.preset_paths`(*subdir*)
Returns a list of paths for a specific preset.

`bpy.utils.register_class`(*cls*)
Register a subclass of a blender type in (`Panel`, `Menu`, `Header`, `Operator`, `KeyingSetInfo`, `RenderEngine`).

Note: `ValueError` exception is raised if the class is not a subclass of a registerable blender class.

`bpy.utils.register_module`(*module*, *verbose=False*)

`bpy.utils.script_paths`(*subdir=None*, *user=True*)
Returns a list of valid script paths from the home directory and user preferences.

Accepts any number of string arguments which are joined to make a path.

`bpy.utils.smpte_from_frame`(*frame*, *fps=None*, *fps_base=None*)
Returns an SMPTE formatted string from the frame: "HH:MM:SS:FF".

If *fps* and *fps_base* are not given the current scene is used.

`bpy.utils.smpte_from_seconds`(*time*, *fps=None*)
Returns an SMPTE formatted string from the time in seconds: "HH:MM:SS:FF".

If the *fps* is not given the current scene is used.

`bpy.utils.unregister_class`(*cls*)
Unload the python class from blender.

`bpy.utils.unregister_module`(*module*, *verbose=False*)

`bpy.utils.user_resource`(*type*, *path=''*, *create=False*)
Return a user resource path (normally from the users home directory).

Parameters

- **type** (*string*) – Resource type in ['DATAFILES', 'CONFIG', 'SCRIPTS', 'AUTOSAVE'].
- **subdir** (*string*) – Optional subdirectory.
- **create** (*boolean*) – Treat the path as a directory and create it if its not existing.

Returns a path.

Return type string

`bpy.utils.user_script_path`()

1.6 Path Utilities (bpy.path)

This module has a similar scope to os.path, containing utility functions for dealing with paths in Blender.

`bpy.path.abspath` (*path*, *start=None*)
Returns the absolute path relative to the current blend file using the "//" prefix.

Parameters **start** (*string*) – Relative to this path, when not set the current filename is used.

`bpy.path.clean_name` (*name*, *replace='_'*)
Returns a name with characters replaced that may cause problems under various circumstances, such as writing to a file. All characters besides A-Z/a-z, 0-9 are replaced with "_" or the replace argument if defined.

`bpy.path.display_name` (*name*)
Creates a display string from name to be used menus and the user interface. Capitalize the first letter in all lowercase names, mixed case names are kept as is. Intended for use with filenames and module names.

`bpy.path.display_name_from_filepath` (*name*)
Returns the path stripped of directort and extension, ensured to be utf8 compatible.

`bpy.path.ensure_ext` (*filepath*, *ext*, *case_sensitive=False*)
Return the path with the extension added its its not alredy set.

Parameters

- **ext** (*string*) – The extension to check for.
- **case_sensitive** (*bool*) – Check for matching case when comparing extensions.

`bpy.path.is_subdir` (*path*, *directory*)
Returns true if *path* in a subdirectory of *directory*. Both paths must be absolute.

`bpy.path.module_names` (*path*, *recursive=False*)
Return a list of modules which can be imported from *path*.

Parameters

- **path** (*string*) – a directory to scan.
- **recursive** (*bool*) – Also return submodule names for packages.

Returns a list of string pairs (module_name, module_file).

Return type list

`bpy.path.relpath` (*path*, *start=None*)
Returns the path relative to the current blend file using the "//" prefix.

Parameters **start** (*string*) – Relative to this path, when not set the current filename is used.

`bpy.path.resolve_ncase` (*path*)
Resolve a case insensitive path on a case sensitive system, returning a string with the path if found else return the original path.

1.7 Application Data (bpy.app)

This module contains application values that remain unchanged during runtime.

`bpy.app.debug`
Boolean, set when blender is running in debug mode (started with -d)

`bpy.app.debug_value`
Int, number which can be set to non-zero values for testing purposes.

`bpy.app.driver_namespace`
Dictionary for drivers namespace, editable in-place, reset on file load (read-only)

bpy.app.**tempdir**
String, the temp directory used by blender (read-only)

bpy.app.**background**
Boolean, True when blender is running without a user interface (started with -b)

bpy.app.**binary_path**
The location of blenders executable, useful for utilities that spawn new instances

bpy.app.**build_cflags**
C compiler flags

bpy.app.**build_cxxflags**
C++ compiler flags

bpy.app.**build_date**
The date this blender instance was built

bpy.app.**build_linkflags**
Binary linking flags

bpy.app.**build_platform**
The platform this blender instance was built for

bpy.app.**build_revision**
The subversion revision this blender instance was built with

bpy.app.**build_system**
Build system used

bpy.app.**build_time**
The time this blender instance was built

bpy.app.**build_type**
The type of build (Release, Debug)

bpy.app.**version**
The Blender version as a tuple of 3 numbers. eg. (2, 50, 11)

bpy.app.**version_string**
The Blender version formatted as a string

T.count(value) -> integer – return number of occurrences of value

T.index(value, [start, [stop]]) -> integer – return first index of value. Raises ValueError if the value is not present.

1.8 Property Definitions (bpy.props)

This module defines properties to extend blenders internal data, the result of these functions is used to assign properties to classes registered with blender and can't be used directly.

1.8.1 Assigning to Existing Classes

Custom properties can be added to any subclass of an `ID`, `Bone` and `PoseBone`.

These properties can be animated, accessed by the user interface and python like blenders existing properties.

```
import bpy

# Assign a custom property to an existing type.
bpy.types.Material.custom_float = bpy.props.FloatProperty(name="Test Prob")

# Test the property is there.
bpy.data.materials[0].custom_float = 5.0
```

1.8.2 Operator Example

A common use of custom properties is for python based `Operator` classes.

```
import bpy


class DialogOperator(bpy.types.Operator):
    bl_idname = "object.dialog_operator"
    bl_label = "Property Example"

    my_float = bpy.props.FloatProperty(name="Some Floating Point")
    my_bool = bpy.props.BoolProperty(name="Toggle Option")
    my_string = bpy.props.StringProperty(name="String Value")

    def execute(self, context):
        print("Dialog Runs")
        return {'FINISHED'}

    def invoke(self, context, event):
        wm = context.window_manager
        return wm.invoke_props_dialog(self)


bpy.utils.register_class(DialogOperator)

# test call
bpy.ops.object.dialog_operator('INVOKE_DEFAULT')
```

1.8.3 PropertyGroup Example

PropertyGroups can be used for collecting custom settings into one value to avoid many indervidual settings mixed in together.

```
import bpy


class MaterialSettings(bpy.types.PropertyGroup):
    my_int = bpy.props.IntProperty()
    my_float = bpy.props.FloatProperty()
    my_string = bpy.props.StringProperty()

bpy.utils.register_class(MaterialSettings)

bpy.types.Material.my_settings = \
    bpy.props.PointerProperty(type=MaterialSettings)
```

```
# test the new settings work
material = bpy.data.materials[0]

material.my_settings.val_int = 5
material.my_settings.val_float = 3.0
material.my_settings.my_string = "Foo"
```

1.8.4 Collection Example

Custom properties can be added to any subclass of an `ID`, `Bone` and `PoseBone`.

```
import bpy


# Assign a collection
class SceneSettingItem(bpy.types.PropertyGroup):
    name = bpy.props.StringProperty(name="Test Prop", default="Unknown")
    value = bpy.props.IntProperty(name="Test Prop", default=22)

bpy.utils.register_class(SceneSettingItem)

bpy.types.Scene.my_settings = \
    bpy.props.CollectionProperty(type=SceneSettingItem)

# Assume an armature object selected
print("Adding 3 values!")

my_item = bpy.context.scene.my_settings.add()
my_item.name = "Spam"
my_item.value = 1000

my_item = bpy.context.scene.my_settings.add()
my_item.name = "Eggs"
my_item.value = 30

for my_item in bpy.context.scene.my_settings:
    print(my_item.name, my_item.value)
```

`bpy.props.`**`BoolProperty`**(*name=""*, *description=""*, *default=False*, *options={'ANIMATABLE'}*, *subtype='NONE'*)

Returns a new boolean property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'NONE'].

`bpy.props.`**`BoolVectorProperty`**(*name=""*, *description=""*, *default=(False, False, False)*, *options={'ANIMATABLE'}*, *subtype='NONE'*, *size=3*)

Returns a new vector boolean property definition.

Parameters

- **name** (*string*) – Name used in the user interface.

- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*sequence*) – sequence of booleans the length of *size*.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['COLOR', 'TRANSLATION', 'DIRECTION', 'VELOCITY', 'ACCELERATION', 'MATRIX', 'EULER', 'QUATERNION', 'AXISANGLE', 'XYZ', 'COLOR_GAMMA', 'LAYER', 'NONE'].
- **size** (*int*) – Vector dimensions in [1, and 32].

`bpy.props.`**`CollectionProperty`**(*items*, *type=""*, *description=""*, *default=""*, *options={'ANIMATABLE'}*)

Returns a new collection property definition.

Parameters

- **type** (*class*) – A subclass of `bpy.types.PropertyGroup`.
- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].

`bpy.props.`**`EnumProperty`**(*items*, *name=""*, *description=""*, *default=""*, *options={'ANIMATABLE'}*)

Returns a new enumerator property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*string or set*) – The default value for this enum, A string when *ENUM_FLAG* is disabled otherwise a set which may only contain string identifiers used in *items*.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE', 'ENUM_FLAG'].
- **items** (*sequence of string triplets*) – sequence of enum items formatted: [(identifier, name, description), ...] where the identifier is used for python access and other values are used for the interface.

`bpy.props.`**`FloatProperty`**(*name=""*, *description=""*, *default=0.0*, *min=sys.float_info.min*, *max=sys.float_info.max*, *soft_min=sys.float_info.min*, *soft_max=sys.float_info.max*, *step=3*, *precision=2*, *options={'ANIMATABLE'}*, *subtype='NONE'*, *unit='NONE'*)

Returns a new float property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'NONE'].
- **unit** (*string*) – Enumerator in ['NONE', 'LENGTH', 'AREA', 'VOLUME', 'ROTATION', 'TIME', 'VELOCITY', 'ACCELERATION'].

bpy.props.**FloatVectorProperty**(*name=""*, *description=""*, *default=(0.0, 0.0, 0.0)*, *min=sys.float_info.min*, *max=sys.float_info.max*, *soft_min=sys.float_info.min*, *soft_max=sys.float_info.max*, *step=3*, *precision=2*, *options={'ANIMATABLE'}*, *subtype='NONE'*, *size=3*)

Returns a new vector float property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*sequence*) – sequence of floats the length of *size*.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['COLOR', 'TRANSLATION', 'DIRECTION', 'VELOCITY', 'ACCELERATION', 'MATRIX', 'EULER', 'QUATERNION', 'AXISANGLE', 'XYZ', 'COLOR_GAMMA', 'LAYER', 'NONE'].
- **size** (*int*) – Vector dimensions in [1, and 32].

bpy.props.**IntProperty**(*name=""*, *description=""*, *default=0*, *min=-sys.maxint*, *max=sys.maxint*, *soft_min=-sys.maxint*, *soft_max=sys.maxint*, *step=1*, *options={'ANIMATABLE'}*, *subtype='NONE'*)

Returns a new int property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'NONE'].

bpy.props.**IntVectorProperty**(*name=""*, *description=""*, *default=(0, 0, 0)*, *min=-sys.maxint*, *max=sys.maxint*, *soft_min=-sys.maxint*, *soft_max=sys.maxint*, *options={'ANIMATABLE'}*, *subtype='NONE'*, *size=3*)

Returns a new vector int property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*sequence*) – sequence of ints the length of *size*.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['COLOR', 'TRANSLATION', 'DIRECTION', 'VELOCITY', 'ACCELERATION', 'MATRIX', 'EULER', 'QUATERNION', 'AXISANGLE', 'XYZ', 'COLOR_GAMMA', 'LAYER', 'NONE'].
- **size** (*int*) – Vector dimensions in [1, and 32].

bpy.props.**PointerProperty**(*type=""*, *description=""*, *options={'ANIMATABLE'}*)

Returns a new pointer property definition.

Parameters

- **type** (*class*) – A subclass of bpy.types.PropertyGroup.

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].

`bpy.props.`**`RemoveProperty`**(*attr*)

Removes a dynamically defined property.

Parameters **attr** (*string*) – Property name.

`bpy.props.`**`StringProperty`**(*name=""*, *description=""*, *default=""*, *maxlen=0*, *options={'ANIMATABLE'}*, *subtype='NONE'*)

Returns a new string property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['FILE_PATH', 'DIR_PATH', 'FILENAME', 'NONE'].

CHAPTER

TWO

STANDALONE MODULES

2.1 Math Types & Utilities (mathutils)

This module provides access to matrices, eulers, quaternions and vectors.

```
import mathutils
from math import radians

vec = mathutils.Vector((1.0, 2.0, 3.0))

mat_rot = mathutils.Matrix.Rotation(radians(90.0), 4, 'X')
mat_trans = mathutils.Matrix.Translation(vec)

mat = mat_trans * mat_rot
mat.invert()

mat3 = mat.to_3x3()
quat1 = mat.to_quaternion()
quat2 = mat3.to_quaternion()

angle = quat1.difference(quat2)

print(angle)
```

class `mathutils.Color`

This object gives access to Colors in Blender.

`copy()`

Returns a copy of this color.

Returns A copy of the color.

Return type `Color`

Note: use this to get a copy of a wrapped color with no reference to the original data.

`b`

Blue color channel.

Type float

`g`

Green color channel.

Type float

h
HSV Hue component in [0, 1].

Type float

hsv
HSV Values in [0, 1].

Type float triplet

is_wrapped
True when this object wraps external data (readonly).

Type boolean

owner
The item this is wrapping or None (readonly).

r
Red color channel.

Type float

s
HSV Saturation component in [0, 1].

Type float

v
HSV Value component in [0, 1].

Type float

class mathutils.**Euler**
This object gives access to Eulers in Blender.

```
import mathutils

# todo
```

copy()
Returns a copy of this euler.

Returns A copy of the euler.

Return type Euler

Note: use this to get a copy of a wrapped euler with no reference to the original data.

---

make_compatible(*other*)
Make this euler compatible with another, so interpolating between them works as intended.

Note: the rotation order is not taken into account for this function.

---

rotate(*other*)
Rotates the euler a by another mathutils value.

Parameters other (Euler, Quaternion or Matrix) – rotation component of mathutils value

rotate_axis (*axis*, *angle*)
Rotates the euler a certain amount and returning a unique euler rotation (no 720 degree pitches).

Parameters

- **axis** (*string*) – single character in ['X, 'Y', 'Z'].
- **angle** (*float*) – angle in radians.

to_matrix()
Return a matrix representation of the euler.

Returns A 3x3 roation matrix representation of the euler.

Return type Matrix

to_quaternion()
Return a quaternion representation of the euler.

Returns Quaternion representation of the euler.

Return type Quaternion

zero()
Set all values to zero.

is_wrapped
True when this object wraps external data (readonly).

Type boolean

order
Euler rotation order.

Type string in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX']

owner
The item this is wrapping or None (readonly).

x
Euler X axis in radians.

Type float

y
Euler Y axis in radians.

Type float

z
Euler Z axis in radians.

Type float

class mathutils.**Matrix**
This object gives access to Matrices in Blender.

```
import mathutils

# todo
```

classmethod OrthoProjection (*axis*, *size*)
Create a matrix to represent an orthographic projection.

Parameters

- **axis** (string or `Vector`) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix. Or a vector for an arbitrary axis
- **size** (*int*) – The size of the projection matrix to construct [2, 4].

Returns A new projection matrix.

Return type `Matrix`

classmethod `Rotation` (*angle*, *size*, *axis*)

Create a matrix representing a rotation.

Parameters

- **angle** (*float*) – The angle of rotation desired, in radians.
- **size** (*int*) – The size of the rotation matrix to construct [2, 4].
- **axis** (string or `Vector`) – a string in ['X', 'Y', 'Z'] or a 3D Vector Object (optional when size is 2).

Returns A new rotation matrix.

Return type `Matrix`

classmethod `Scale` (*factor*, *size*, *axis*)

Create a matrix representing a scaling.

Parameters

- **factor** (*float*) – The factor of scaling to apply.
- **size** (*int*) – The size of the scale matrix to construct [2, 4].
- **axis** (`Vector`) – Direction to influence scale. (optional).

Returns A new scale matrix.

Return type `Matrix`

classmethod `Shear` (*plane*, *size*, *factor*)

Create a matrix to represent an shear transformation.

Parameters

- **plane** (*string*) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix only.
- **size** (*int*) – The size of the shear matrix to construct [2, 4].
- **factor** (*float or float pair*) – The factor of shear to apply. For a 3 or 4 *size* matrix pass a pair of floats corrasponding with the *plane* axis.

Returns A new shear matrix.

Return type `Matrix`

classmethod `Translation` (*vector*)

Create a matrix representing a translation.

Parameters **vector** (`Vector`) – The translation vector.

Returns An identity matrix with a translation.

Return type `Matrix`

`copy` ()

Returns a copy of this matrix.

Returns an instance of itself

Return type `Matrix`

decompose()

Return the location, rotaion and scale components of this matrix.

Returns loc, rot, scale triple.

Return type (`Vector`, `Quaternion`, `Vector`)

determinant()

Return the determinant of a matrix.

Returns Return a the determinant of a matrix.

Return type float

See Also:

<http://en.wikipedia.org/wiki/Determinant>

identity()

Set the matrix to the identity matrix.

Note: An object with zero location and rotation, a scale of one, will have an identity matrix.

See Also:

<http://en.wikipedia.org/wiki/Identity_matrix>

invert()

Set the matrix to its inverse.

Note: `ValueError` exception is raised.

See Also:

<http://en.wikipedia.org/wiki/Inverse_matrix>

inverted()

Return an inverted copy of the matrix.

Returns the inverted matrix.

Return type `Matrix`

Note: `ValueError` exception is raised.

---

lerp(*other*, *factor*)

Returns the interpolation of two matricies.

Parameters

- **other** (`Matrix`) – value to interpolate with.
- **factor** (*float*) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type `Matrix`

resize_4x4()
Resize the matrix to 4x4.

rotate(*other*)
Rotates the matrix a by another mathutils value.

Parameters **other** (Euler, Quaternion or Matrix) – rotation component of mathutils value

---

Note: If any of the columns are not unit length this may not have desired results.

---

to_3x3()
Return a 3x3 copy of this matrix.

Returns a new matrix.

Return type Matrix

to_4x4()
Return a 4x4 copy of this matrix.

Returns a new matrix.

Return type Matrix

to_euler(*order*, *euler_compat*)
Return an Euler representation of the rotation matrix (3x3 or 4x4 matrix only).

Parameters

- **order** (*string*) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- **euler_compat** (Euler) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

Returns Euler representation of the matrix.

Return type Euler

to_quaternion()
Return a quaternion representation of the rotation matrix.

Returns Quaternion representation of the rotation matrix.

Return type Quaternion

to_scale()
Return a the scale part of a 3x3 or 4x4 matrix.

Returns Return a the scale of a matrix.

Return type Vector

Note: This method does not return negative a scale on any axis because it is not possible to obtain this data from the matrix alone.

---

to_translation()
Return a the translation part of a 4 row matrix.

Returns Return a the translation of a matrix.

Return type Vector

transpose()

Set the matrix to its transpose.

See Also:

<http://en.wikipedia.org/wiki/Transpose>

transposed()

Return a new, transposed matrix.

Returns a transposed matrix

Return type Matrix

zero()

Set all the matrix values to zero.

Returns an instance of itself

Return type Matrix

col_size

The column size of the matrix (readonly).

Type int

is_negative

True if this matrix results in a negative scale, 3x3 and 4x4 only, (readonly).

Type bool

is_wrapped

True when this object wraps external data (readonly).

Type boolean

median_scale

The average scale applied to each axis (readonly).

Type float

owner

The item this is wrapping or None (readonly).

row_size

The row size of the matrix (readonly).

Type int

class mathutils.**Quaternion**

This object gives access to Quaternions in Blender.

```
import mathutils

# todo
```

conjugate()

Set the quaternion to its conjugate (negate x, y, z).

conjugated()

Return a new conjugated quaternion.

Returns a new quaternion.

Return type Quaternion

copy()
Returns a copy of this quaternion.

Returns A copy of the quaternion.

Return type Quaternion

Note: use this to get a copy of a wrapped quaternion with no reference to the original data.

---

cross(*other*)
Return the cross product of this quaternion and another.

Parameters **other** (Quaternion) – The other quaternion to perform the cross product with.

Returns The cross product.

Return type Quaternion

difference(*other*)
Returns a quaternion representing the rotational difference.

Parameters **other** (Quaternion) – second quaternion.

Returns the rotational difference between the two quat rotations.

Return type Quaternion

dot(*other*)
Return the dot product of this quaternion and another.

Parameters **other** (Quaternion) – The other quaternion to perform the dot product with.

Returns The dot product.

Return type Quaternion

identity()
Set the quaternion to an identity quaternion.

Returns an instance of itself.

Return type Quaternion

invert()
Set the quaternion to its inverse.

inverted()
Return a new, inverted quaternion.

Returns the inverted value.

Return type Quaternion

negate()
Set the quaternion to its negative.

Returns an instance of itself.

Return type Quaternion

normalize()
Normalize the quaternion.

normalized()
Return a new normalized quaternion.

Returns a normalized copy.

Return type Quaternion

rotate(*other*)

Rotates the quaternion a by another mathutils value.

Parameters **other** (Euler, Quaternion or Matrix) – rotation component of mathutils value

slerp(*other*, *factor*)

Returns the interpolation of two quaternions.

Parameters

- **other** (Quaternion) – value to interpolate with.
- **factor** (*float*) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type Quaternion

to_euler(*order*, *euler_compat*)

Return Euler representation of the quaternion.

Parameters

- **order** (*string*) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- **euler_compat** (Euler) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

Returns Euler representation of the quaternion.

Return type Euler

to_matrix()

Return a matrix representation of the quaternion.

Returns A 3x3 rotation matrix representation of the quaternion.

Return type Matrix

angle

angle of the quaternion.

Type float

axis

quaternion axis as a vector.

Type Vector

is_wrapped

True when this object wraps external data (readonly).

Type boolean

magnitude

Size of the quaternion (readonly).

Type float

owner
The item this is wrapping or None (readonly).

w
Quaternion W value.

Type float

x
Quaternion X axis.

Type float

y
Quaternion Y axis.

Type float

z
Quaternion Z axis.

Type float

class mathutils.**Vector**
This object gives access to Vectors in Blender.

```
import mathutils

# zero length vector
vec = mathutils.Vector((0, 0, 1))

# unit length vector
vec_a = vec.copy().normalize()

vec_b = mathutils.Vector((0, 1, 2))

vec2d = mathutils.Vector((1, 2))
vec3d = mathutils.Vector((1, 0, 0))
vec4d = vec_a.to_4d()

# other mathutuls types
quat = mathutils.Quaternion()
matrix = mathutils.Matrix()

# Comparison operators can be done on Vector classes:

# greater and less then test vector length.
vec_a > vec_b
vec_a >= vec_b
vec_a < vec_b
vec_a <= vec_b

# ==, != test vector values e.g. 1,2,3 != 3,2,1 even if they are the same length
vec_a == vec_b
vec_a != vec_b


# Math can be performed on Vector classes
vec_a + vec_b
vec_a - vec_b
vec_a * vec_b
vec_a * 10.0
```

```
vec_a * matrix
vec_a * vec_b
vec_a * quat
-vec_a


# You can access a vector object like a sequence
x = vec_a[0]
len(vec)
vec_a[:] = vec_b
vec2d[:] = vec3d[:2]


# Vectors support 'swizzle' operations
# See http://en.wikipedia.org/wiki/Swizzling_(computer_graphics)
vec.xyz = vec.zyx
vec.xy = vec4d.zw
vec.xyz = vec4d.wzz
vec4d.wxyz = vec.yxyx
```

angle (*other*, *fallback*)

Return the angle between two vectors.

Parameters

- **other** (`Vector`) – another vector to compare the angle with
- **fallback** (*any*) – return this value when the angle cant be calculated (zero length vector)

Returns angle in radians or fallback when given

Return type float

Note: Zero length vectors raise an `AttributeError`.

---

copy ()

Returns a copy of this vector.

Returns A copy of the vector.

Return type `Vector`

Note: use this to get a copy of a wrapped vector with no reference to the original data.

---

cross (*other*)

Return the cross product of this vector and another.

Parameters **other** (`Vector`) – The other vector to perform the cross product with.

Returns The cross product.

Return type `Vector`

Note: both vectors must be 3D

---

difference (*other*)

Returns a quaternion representing the rotational difference between this vector and another.

Parameters **other** (`Vector`) – second vector.

Returns the rotational difference between the two vectors.

Return type `Quaternion`

Note: 2D vectors raise an `AttributeError`.

---

dot(*other*)

Return the dot product of this vector and another.

Parameters **other** (`Vector`) – The other vector to perform the dot product with.

Returns The dot product.

Return type `Vector`

lerp(*other*, *factor*)

Returns the interpolation of two vectors.

Parameters

- **other** (`Vector`) – value to interpolate with.
- **factor** (*float*) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type `Vector`

negate()

Set all values to their negative.

Returns an instance of itself

Return type `Vector`

normalize()

Normalize the vector, making the length of the vector always 1.0.

Warning: Normalizing a vector where all values are zero results in all axis having a nan value (not a number).

Note: Normalize works for vectors of all sizes, however 4D Vectors w axis is left untouched.

---

normalized()

Return a new, normalized vector.

Returns a normalized copy of the vector

Return type `Vector`

project(*other*)

Return the projection of this vector onto the *other*.

Parameters **other** (`Vector`) – second vector.

Returns the parallel projection vector

Return type `Vector`

reflect(*mirror*)

Return the reflection vector from the *mirror* argument.

Parameters **mirror** (`Vector`) – This vector could be a normal from the reflecting surface.

Returns The reflected vector matching the size of this vector.

Return type Vector

resize_2d()
Resize the vector to 2D (x, y).

Returns an instance of itself

Return type Vector

resize_3d()
Resize the vector to 3D (x, y, z).

Returns an instance of itself

Return type Vector

resize_4d()
Resize the vector to 4D (x, y, z, w).

Returns an instance of itself

Return type Vector

rotate(*other*)
Return vector by a rotation value.

Parameters **other** (Euler, Quaternion or Matrix) – rotation component of mathutils value

to_2d()
Return a 2d copy of the vector.

Returns a new vector

Return type Vector

to_3d()
Return a 3d copy of the vector.

Returns a new vector

Return type Vector

to_4d()
Return a 4d copy of the vector.

Returns a new vector

Return type Vector

to_track_quat(*track*, *up*)
Return a quaternion rotation from the vector and the track and up axis.

Parameters

- **track** (*string*) – Track axis in ['X', 'Y', 'Z', '-X', '-Y', '-Z'].
- **up** (*string*) – Up axis in ['X', 'Y', 'Z'].

Returns rotation from the vector and the track and up axis.

Return type Quaternion

to_tuple(*precision=-1*)
Return this vector as a tuple with.

Parameters **precision** (*int*) – The number to round the value to in [-1, 21].

Returns the values of the vector rounded by *precision*

Return type tuple

zero()

Set all values to zero.

is_wrapped

True when this object wraps external data (readonly).

Type boolean

length

Vector Length.

Type float

magnitude

Vector Length.

Type float

owner

The item this is wrapping or None (readonly).

w

Vector W axis (4D Vectors only).

Type float

ww

Undocumented (contribute)

www

Undocumented (contribute)

wwww

Undocumented (contribute)

wwwx

Undocumented (contribute)

wwwy

Undocumented (contribute)

wwwz

Undocumented (contribute)

wwx

Undocumented (contribute)

wwxw

Undocumented (contribute)

wwxx

Undocumented (contribute)

wwxy

Undocumented (contribute)

wwxz

Undocumented (contribute)

wwy
Undocumented (contribute)

wwyw
Undocumented (contribute)

wwyx
Undocumented (contribute)

wwyy
Undocumented (contribute)

wwyz
Undocumented (contribute)

wwz
Undocumented (contribute)

wwzw
Undocumented (contribute)

wwzx
Undocumented (contribute)

wwzy
Undocumented (contribute)

wwzz
Undocumented (contribute)

wx
Undocumented (contribute)

wxw
Undocumented (contribute)

wxww
Undocumented (contribute)

wxwx
Undocumented (contribute)

wxwy
Undocumented (contribute)

wxwz
Undocumented (contribute)

wxx
Undocumented (contribute)

wxxw
Undocumented (contribute)

wxxx
Undocumented (contribute)

wxxy
Undocumented (contribute)

wxxz
Undocumented (contribute)

wxy
Undocumented (contribute)

wxyw
Undocumented (contribute)

wxyx
Undocumented (contribute)

wxyy
Undocumented (contribute)

wxyz
Undocumented (contribute)

wxz
Undocumented (contribute)

wxzw
Undocumented (contribute)

wxzx
Undocumented (contribute)

wxzy
Undocumented (contribute)

wxzz
Undocumented (contribute)

wy
Undocumented (contribute)

wyw
Undocumented (contribute)

wyww
Undocumented (contribute)

wywx
Undocumented (contribute)

wywy
Undocumented (contribute)

wywz
Undocumented (contribute)

wyx
Undocumented (contribute)

wyxw
Undocumented (contribute)

wyxx
Undocumented (contribute)

wyxy
Undocumented (contribute)

wyxz
Undocumented (contribute)

wyy
Undocumented (contribute)

wyyw
Undocumented (contribute)

wyyx
Undocumented (contribute)

wyyy
Undocumented (contribute)

wyyz
Undocumented (contribute)

wyz
Undocumented (contribute)

wyzw
Undocumented (contribute)

wyzx
Undocumented (contribute)

wyzy
Undocumented (contribute)

wyzz
Undocumented (contribute)

wz
Undocumented (contribute)

wzw
Undocumented (contribute)

wzww
Undocumented (contribute)

wzwx
Undocumented (contribute)

wzwy
Undocumented (contribute)

wzwz
Undocumented (contribute)

wzx
Undocumented (contribute)

wzxw
Undocumented (contribute)

wzxx
Undocumented (contribute)

wzxy
Undocumented (contribute)

wzxz
Undocumented (contribute)

wzy
Undocumented (contribute)

wzyw
Undocumented (contribute)

wzyx
Undocumented (contribute)

wzyy
Undocumented (contribute)

wzyz
Undocumented (contribute)

wzz
Undocumented (contribute)

wzzw
Undocumented (contribute)

wzzx
Undocumented (contribute)

wzzy
Undocumented (contribute)

wzzz
Undocumented (contribute)

x
Vector X axis.

Type float

xw
Undocumented (contribute)

xww
Undocumented (contribute)

xwww
Undocumented (contribute)

xwwx
Undocumented (contribute)

xwwy
Undocumented (contribute)

xwwz
Undocumented (contribute)

xwx
Undocumented (contribute)

xwxw
Undocumented (contribute)

xwxx
Undocumented (contribute)

xwxy
Undocumented (contribute)

xwxz
Undocumented (contribute)

xwy
Undocumented (contribute)

xwyw
Undocumented (contribute)

xwyx
Undocumented (contribute)

xwyy
Undocumented (contribute)

xwyz
Undocumented (contribute)

xwz
Undocumented (contribute)

xwzw
Undocumented (contribute)

xwzx
Undocumented (contribute)

xwzy
Undocumented (contribute)

xwzz
Undocumented (contribute)

xx
Undocumented (contribute)

xxw
Undocumented (contribute)

xxww
Undocumented (contribute)

xxwx
Undocumented (contribute)

xxwy
Undocumented (contribute)

xxwz
Undocumented (contribute)

xxx
Undocumented (contribute)

xxxw
Undocumented (contribute)

xxxx
Undocumented (contribute)

xxxy
Undocumented (contribute)

xxxz
Undocumented (contribute)

xxy
Undocumented (contribute)

xxyw
Undocumented (contribute)

xxyx
Undocumented (contribute)

xxyy
Undocumented (contribute)

xxyz
Undocumented (contribute)

xxz
Undocumented (contribute)

xxzw
Undocumented (contribute)

xxzx
Undocumented (contribute)

xxzy
Undocumented (contribute)

xxzz
Undocumented (contribute)

xy
Undocumented (contribute)

xyw
Undocumented (contribute)

xyww
Undocumented (contribute)

xywx
Undocumented (contribute)

xywy
Undocumented (contribute)

xywz
Undocumented (contribute)

xyx
Undocumented (contribute)

xyxw
Undocumented (contribute)

xyxx
Undocumented (contribute)

xyxy
Undocumented (contribute)

xyxz
Undocumented (contribute)

xyy
Undocumented (contribute)

xyyw
Undocumented (contribute)

xyyx
Undocumented (contribute)

xyyy
Undocumented (contribute)

xyyz
Undocumented (contribute)

xyz
Undocumented (contribute)

xyzw
Undocumented (contribute)

xyzx
Undocumented (contribute)

xyzy
Undocumented (contribute)

xyzz
Undocumented (contribute)

xz
Undocumented (contribute)

xzw
Undocumented (contribute)

xzww
Undocumented (contribute)

xzwx
Undocumented (contribute)

xzwy
Undocumented (contribute)

xzwz
Undocumented (contribute)

xzx
Undocumented (contribute)

xzxw
Undocumented (contribute)

xzxx
Undocumented (contribute)

xzxy
Undocumented (contribute)

xzxz
Undocumented (contribute)

xzy
Undocumented (contribute)

xzyw
Undocumented (contribute)

xzyx
Undocumented (contribute)

xzyy
Undocumented (contribute)

xzyz
Undocumented (contribute)

xzz
Undocumented (contribute)

xzzw
Undocumented (contribute)

xzzx
Undocumented (contribute)

xzzy
Undocumented (contribute)

xzzz
Undocumented (contribute)

y
Vector Y axis.

Type float

yw
Undocumented (contribute)

yww
Undocumented (contribute)

ywww
Undocumented (contribute)

ywwx
Undocumented (contribute)

ywwy
Undocumented (contribute)

ywwz
Undocumented (contribute)

ywx
Undocumented (contribute)

ywxw
Undocumented (contribute)

ywxx
Undocumented (contribute)

ywxy
Undocumented (contribute)

ywxz
Undocumented (contribute)

ywy
Undocumented (contribute)

ywyw
Undocumented (contribute)

ywyx
Undocumented (contribute)

ywyy
Undocumented (contribute)

ywyz
Undocumented (contribute)

ywz
Undocumented (contribute)

ywzw
Undocumented (contribute)

ywzx
Undocumented (contribute)

ywzy
Undocumented (contribute)

ywzz
Undocumented (contribute)

yx
Undocumented (contribute)

yxw
Undocumented (contribute)

yxww
Undocumented (contribute)

yxwx
Undocumented (contribute)

yxwy
Undocumented (contribute)

yxwz
Undocumented (contribute)

yxx
Undocumented (contribute)

yxxw
Undocumented (contribute)

yxxx
Undocumented (contribute)

yxxy
Undocumented (contribute)

yxxz
Undocumented (contribute)

yxy
Undocumented (contribute)

yxyw
Undocumented (contribute)

yxyx
Undocumented (contribute)

yxyy
Undocumented (contribute)

yxyz
Undocumented (contribute)

yxz
Undocumented (contribute)

yxzw
Undocumented (contribute)

yxzx
Undocumented (contribute)

yxzy
Undocumented (contribute)

yxzz
Undocumented (contribute)

yy
Undocumented (contribute)

yyw
Undocumented (contribute)

yyww
Undocumented (contribute)

yywx
Undocumented (contribute)

yywy
Undocumented (contribute)

yywz
Undocumented (contribute)

yyx
Undocumented (contribute)

yyxw
Undocumented (contribute)

yyxx
Undocumented (contribute)

yyxy
Undocumented (contribute)

yyxz
Undocumented (contribute)

yyy
Undocumented (contribute)

yyyw
Undocumented (contribute)

yyyx
Undocumented (contribute)

yyyy
Undocumented (contribute)

yyyz
Undocumented (contribute)

yyz
Undocumented (contribute)

yyzw
Undocumented (contribute)

yyzx
Undocumented (contribute)

yyzy
Undocumented (contribute)

yyzz
Undocumented (contribute)

yz
Undocumented (contribute)

yzw
Undocumented (contribute)

yzww
Undocumented (contribute)

yzwx
Undocumented (contribute)

yzwy
Undocumented (contribute)

yzwz
Undocumented (contribute)

yzx
Undocumented (contribute)

yzxw
Undocumented (contribute)

yzxx
Undocumented (contribute)

yzxy
Undocumented (contribute)

yzxz
Undocumented (contribute)

yzy
Undocumented (contribute)

yzyw
Undocumented (contribute)

yzyx
Undocumented (contribute)

yzyy
Undocumented (contribute)

yzyz
Undocumented (contribute)

yzz
Undocumented (contribute)

yzzw
Undocumented (contribute)

yzzx
Undocumented (contribute)

yzzy
Undocumented (contribute)

yzzz
Undocumented (contribute)

z
Vector Z axis (3D Vectors only).

Type float

zw
Undocumented (contribute)

zww
Undocumented (contribute)

zwww
Undocumented (contribute)

zwwx
Undocumented (contribute)

zwwy
Undocumented (contribute)

zwwz
Undocumented (contribute)

zwx
Undocumented (contribute)

zwxw
Undocumented (contribute)

zwxx
Undocumented (contribute)

zwxy
Undocumented (contribute)

zwxz
Undocumented (contribute)

zwy
Undocumented (contribute)

zwyw
Undocumented (contribute)

zwyx
Undocumented (contribute)

zwyy
Undocumented (contribute)

zwyz
Undocumented (contribute)

zwz
Undocumented (contribute)

zwzw
Undocumented (contribute)

zwzx
Undocumented (contribute)

zwzy
Undocumented (contribute)

zwzz
Undocumented (contribute)

zx
Undocumented (contribute)

zxw
Undocumented (contribute)

zxww
Undocumented (contribute)

zxwx
Undocumented (contribute)

zxwy
Undocumented (contribute)

zxwz
Undocumented (contribute)

zxx
Undocumented (contribute)

zxxw
Undocumented (contribute)

zxxx
Undocumented (contribute)

zxxy
Undocumented (contribute)

zxxz
Undocumented (contribute)

zxy
Undocumented (contribute)

zxyw
Undocumented (contribute)

zxyx
Undocumented (contribute)

zxyy
Undocumented (contribute)

zxyz
Undocumented (contribute)

zxz
Undocumented (contribute)

zxzw
Undocumented (contribute)

zxzx
Undocumented (contribute)

zxzy
Undocumented (contribute)

zxzz
Undocumented (contribute)

zy
Undocumented (contribute)

zyw
Undocumented (contribute)

zyww
Undocumented (contribute)

zywx
Undocumented (contribute)

zywy
Undocumented (contribute)

zywz
Undocumented (contribute)

zyx
Undocumented (contribute)

zyxw
Undocumented (contribute)

zyxx
Undocumented (contribute)

zyxy
Undocumented (contribute)

zyxz
Undocumented (contribute)

zyy
Undocumented (contribute)

zyyw
Undocumented (contribute)

zyyx
Undocumented (contribute)

zyyy
Undocumented (contribute)

zyyz
Undocumented (contribute)

zyz
Undocumented (contribute)

zyzw
Undocumented (contribute)

zyzx
Undocumented (contribute)

zyzy
Undocumented (contribute)

zyzz
Undocumented (contribute)

zz
Undocumented (contribute)

zzw
Undocumented (contribute)

zzww
Undocumented (contribute)

zzwx
Undocumented (contribute)

zzwy
Undocumented (contribute)

zzwz
Undocumented (contribute)

zzx
Undocumented (contribute)

zzxw
Undocumented (contribute)

zzxx
Undocumented (contribute)

zzxy
Undocumented (contribute)

zzxz
Undocumented (contribute)

zzy
Undocumented (contribute)

zzyw
Undocumented (contribute)

zzyx
Undocumented (contribute)

zzyy
Undocumented (contribute)

zzyz
Undocumented (contribute)

zzz
Undocumented (contribute)

zzzw
Undocumented (contribute)

zzzx
Undocumented (contribute)

zzzy
Undocumented (contribute)

zzzz
Undocumented (contribute)

2.2 Geometry Utilities (mathutils.geometry)

The Blender geometry module

`mathutils.geometry.`**`area_tri`**(*v1*, *v2*, *v3*)
Returns the area size of the 2D or 3D triangle defined.

Parameters

- **v1** (`mathutils.Vector`) – Point1
- **v2** (`mathutils.Vector`) – Point2
- **v3** (`mathutils.Vector`) – Point3

Return type float

`mathutils.geometry.`**`barycentric_transform`**(*point*, *tri_a1*, *tri_a2*, *tri_a3*, *tri_b1*, *tri_b2*, *tri_b3*)
Return a transformed point, the transformation is defined by 2 triangles.

Parameters

- **point** (`mathutils.Vector`) – The point to transform.

- **tri_a1** (mathutils.Vector) – source triangle vertex.
- **tri_a2** (mathutils.Vector) – source triangle vertex.
- **tri_a3** (mathutils.Vector) – source triangle vertex.
- **tri_a1** – target triangle vertex.
- **tri_a2** – target triangle vertex.
- **tri_a3** – target triangle vertex.

Returns The transformed point

Return type mathutils.Vector's

mathutils.geometry.**box_pack_2d**(*boxes*)

Returns the normal of the 3D tri or quad.

Parameters **boxes** (*list*) – list of boxes, each box is a list where the first 4 items are [x,y, width, height, ...] other items are ignored.

Returns the width and height of the packed bounding box

Return type tuple, pair of floats

mathutils.geometry.**interpolate_bezier**(*knot1*, *handle1*, *handle2*, *knot2*, *resolution*)

Interpolate a bezier spline segment.

Parameters

- **knot1** (mathutils.Vector) – First bezier spline point.
- **handle1** (mathutils.Vector) – First bezier spline handle.
- **handle2** (mathutils.Vector) – Second bezier spline handle.
- **knot2** (mathutils.Vector) – Second bezier spline point.
- **resolution** (*int*) – Number of points to return.

Returns The interpolated points

Return type list of mathutils.Vector's

mathutils.geometry.**intersect_line_line**(*v1*, *v2*, *v3*, *v4*)

Returns a tuple with the points on each line respectively closest to the other.

Parameters

- **v1** (mathutils.Vector) – First point of the first line
- **v2** (mathutils.Vector) – Second point of the first line
- **v3** (mathutils.Vector) – First point of the second line
- **v4** (mathutils.Vector) – Second point of the second line

Return type tuple of mathutils.Vector's

mathutils.geometry.**intersect_line_line_2d**(*lineA_p1*, *lineA_p2*, *lineB_p1*, *lineB_p2*)

Takes 2 lines (as 4 vectors) and returns a vector for their point of intersection or None.

Parameters

- **lineA_p1** (mathutils.Vector) – First point of the first line
- **lineA_p2** (mathutils.Vector) – Second point of the first line
- **lineB_p1** (mathutils.Vector) – First point of the second line

- **lineB_p2** (mathutils.Vector) – Second point of the second line

Returns The point of intersection or None when not found

Return type mathutils.Vector or None

mathutils.geometry.**intersect_point_line**(*pt*, *line_p1*, *line_p2*)

Takes a point and a line and returns a tuple with the closest point on the line and its distance from the first point of the line as a percentage of the length of the line.

Parameters

- **pt** (mathutils.Vector) – Point
- **line_p1** (mathutils.Vector) – First point of the line
- **line_p1** – Second point of the line

Return type (mathutils.Vector, float)

mathutils.geometry.**intersect_point_quad_2d**(*pt*, *quad_p1*, *quad_p2*, *quad_p3*, *quad_p4*)

Takes 5 vectors (using only the x and y coordinates): one is the point and the next 4 define the quad, only the x and y are used from the vectors. Returns 1 if the point is within the quad, otherwise 0.

Parameters

- **pt** – Point
- **quad_p1** (mathutils.Vector) – First point of the quad
- **quad_p2** (mathutils.Vector) – Second point of the quad
- **quad_p3** (mathutils.Vector) – Third point of the quad
- **quad_p4** (mathutils.Vector) – Forth point of the quad

Return type int

mathutils.geometry.**intersect_point_tri_2d**(*pt*, *tri_p1*, *tri_p2*, *tri_p3*)

Takes 4 vectors (using only the x and y coordinates): one is the point and the next 3 define the triangle. Returns 1 if the point is within the triangle, otherwise 0.

Parameters

- **pt** – Point
- **tri_p1** (mathutils.Vector) – First point of the triangle
- **tri_p2** (mathutils.Vector) – Second point of the triangle
- **tri_p3** (mathutils.Vector) – Third point of the triangle

Return type int

mathutils.geometry.**intersect_ray_tri**(*v1*, *v2*, *v3*, *ray*, *orig*, *clip=True*)

Returns the intersection between a ray and a triangle, if possible, returns None otherwise.

Parameters

- **v1** (mathutils.Vector) – Point1
- **v2** (mathutils.Vector) – Point2
- **v3** (mathutils.Vector) – Point3
- **ray** (mathutils.Vector) – Direction of the projection
- **orig** (mathutils.Vector) – Origin

- **clip** (*boolean*) – Clip by the ray length

Returns The point of intersection or None if no intersection is found

Return type `mathutils.Vector` or None

`mathutils.geometry.normal`(*v1*, *v2*, *v3*, *v4=None*)
Returns the normal of the 3D tri or quad.

Parameters

- **v1** (`mathutils.Vector`) – Point1
- **v2** (`mathutils.Vector`) – Point2
- **v3** (`mathutils.Vector`) – Point3
- **v4** (`mathutils.Vector`) – Point4 (optional)

Return type `mathutils.Vector`

`mathutils.geometry.tesselate_polygon`(*veclist_list*)
Takes a list of polylines (each point a vector) and returns the point indices for a polyline filled with triangles.

Parameters **veclist_list** – list of polylines

Return type list

2.3 Font Drawing (blf)

This module provides access to blenders text drawing functions.

`blf.CLIPPING`
constant value 2

`blf.KERNING_DEFAULT`
constant value 8

`blf.ROTATION`
constant value 1

`blf.SHADOW`
constant value 4

`blf.aspect`(*fontid*, *aspect*)
Set the aspect for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **aspect** (*float*) – The aspect ratio for text drawing to use.

`blf.blur`(*fontid*, *radius*)
Set the blur radius for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **radius** (*int*) – The radius for blurring text (in pixels).

`blf.clipping`(*fontid*, *xmin*, *ymin*, *xmax*, *ymax*)
Set the clipping, enable/disable using CLIPPING.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **xmin** (*float*) – Clip the drawing area by these bounds.
- **ymin** (*float*) – Clip the drawing area by these bounds.
- **xmax** (*float*) – Clip the drawing area by these bounds.
- **ymax** (*float*) – Clip the drawing area by these bounds.

`blf.dimensions` (*fontid*, *text*)
Return the width and height of the text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **text** (*string*) – the text to draw.

Returns the width and height of the text.

Return type tuple of 2 floats

`blf.disable` (*fontid*, *option*)
Disable option.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **option** (*int*) – One of ROTATION, CLIPPING, SHADOW or KERNING_DEFAULT.

`blf.draw` (*fontid*, *text*)
Draw text in the current context.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **text** (*string*) – the text to draw.

`blf.enable` (*fontid*, *option*)
Enable option.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **option** (*int*) – One of ROTATION, CLIPPING, SHADOW or KERNING_DEFAULT.

`blf.load` (*filename*)
Load a new font.

Parameters **filename** (*string*) – the filename of the font.

Returns the new font's fontid or -1 if there was an error.

Return type integer

`blf.position` (*fontid*, *x*, *y*, *z*)
Set the position for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **x** (*float*) – X axis position to draw the text.

- **y** (*float*) – Y axis position to draw the text.
- **z** (*float*) – Z axis position to draw the text.

`blf.rotation`(*fontid*, *angle*)
Set the text rotation angle, enable/disable using ROTATION.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **angle** (*float*) – The angle for text drawing to use.

`blf.shadow`(*fontid*, *level*, *r*, *g*, *b*, *a*)
Shadow options, enable/disable using SHADOW .

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **level** (*int*) – The blur level, can be 3, 5 or 0.
- **r** (*float*) – Shadow color (red channel 0.0 - 1.0).
- **g** (*float*) – Shadow color (green channel 0.0 - 1.0).
- **b** (*float*) – Shadow color (blue channel 0.0 - 1.0).
- **a** (*float*) – Shadow color (alpha channel 0.0 - 1.0).

`blf.shadow_offset`(*fontid*, *x*, *y*)
Set the offset for shadow text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **x** (*float*) – Vertical shadow offset value in pixels.
- **y** (*float*) – Horizontal shadow offset value in pixels.

`blf.size`(*fontid*, *size*, *dpi*)
Set the size and dpi for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **size** (*int*) – Point size of the font.
- **dpi** (*int*) – dots per inch value to use for drawing.

2.4 Audio System (aud)

This module provides access to the audaspace audio library.

`aud.AUD_DEVICE_JACK`
constant value 3

`aud.AUD_DEVICE_NULL`
constant value 0

`aud.AUD_DEVICE_OPENAL`
constant value 1

aud.**AUD_DEVICE_SDL**
constant value 2

aud.**AUD_DISTANCE_MODEL_EXPONENT**
constant value 5

aud.**AUD_DISTANCE_MODEL_EXPONENT_CLAMPED**
constant value 6

aud.**AUD_DISTANCE_MODEL_INVALID**
constant value 0

aud.**AUD_DISTANCE_MODEL_INVERSE**
constant value 1

aud.**AUD_DISTANCE_MODEL_INVERSE_CLAMPED**
constant value 2

aud.**AUD_DISTANCE_MODEL_LINEAR**
constant value 3

aud.**AUD_DISTANCE_MODEL_LINEAR_CLAMPED**
constant value 4

aud.**AUD_FORMAT_FLOAT32**
constant value 36

aud.**AUD_FORMAT_FLOAT64**
constant value 40

aud.**AUD_FORMAT_INVALID**
constant value 0

aud.**AUD_FORMAT_S16**
constant value 18

aud.**AUD_FORMAT_S24**
constant value 19

aud.**AUD_FORMAT_S32**
constant value 20

aud.**AUD_FORMAT_U8**
constant value 1

aud.**AUD_STATUS_INVALID**
constant value 0

aud.**AUD_STATUS_PAUSED**
constant value 2

aud.**AUD_STATUS_PLAYING**
constant value 1

device()

Returns the application's `Device`.

return The application's `Device`.

rtype `Device`

class aud.**Device**
Device objects represent an audio output backend like OpenAL or SDL, but might also represent a file output or RAM buffer output.

lock()

Locks the device so that it's guaranteed, that no samples are read from the streams until `unlock()` is called. This is useful if you want to do start/stop/pause/resume some sounds at the same time.

Note: The device has to be unlocked as often as locked to be able to continue playback.

Warning: Make sure the time between locking and unlocking is as short as possible to avoid clicks.

play(factory, keep=False)

Plays a factory.

Parameters

- **factory** (`Factory`) – The factory to play.
- **keep** (*bool*) – See `Handle.keep`.

Returns The playback handle with which playback can be controlled with.

Return type `Handle`

unlock()

Unlocks the device after a lock call, see `lock()` for details.

channels
The channel count of the device.

distance_model
The distance model of the device.

See Also:

http://connect.creativelabs.com/openal/Documentation/OpenAL%201.1%20Specification.htm#_Toc199835864

doppler_factor
The doppler factor of the device. This factor is a scaling factor for the velocity vectors in doppler calculation. So a value bigger than 1 will exaggerate the effect as it raises the velocity.

format
The native sample format of the device.

listener_location
The listeners's location in 3D space, a 3D tuple of floats.

listener_orientation
The listener's orientation in 3D space as quaternion, a 4 float tuple.

listener_velocity
The listener's velocity in 3D space, a 3D tuple of floats.

rate
The sampling rate of the device in Hz.

speed_of_sound
The speed of sound of the device. The speed of sound in air is typically 343 m/s.

volume
The overall volume of the device.

class `aud.Factory`

Factory objects are immutable and represent a sound that can be played simultaneously multiple times. They are called factories because they create reader objects internally that are used for playback.

file(filename)

Creates a factory object of a sound file.

Parameters **filename** (*string*) – Path of the file.

Returns The created `Factory` object.

Return type `Factory`

> **Warning:** If the file doesn't exist or can't be read you will not get an exception immediately, but when you try to start playback of that factory.

sine(frequency, rate=44100)

Creates a sine factory which plays a sine wave.

Parameters

- **frequency** (*float*) – The frequency of the sine wave in Hz.
- **rate** (*int*) – The sampling rate in Hz. It's recommended to set this value to the playback device's samling rate to avoid resamping.

Returns The created `Factory` object.

Return type `Factory`

buffer()

Buffers a factory into RAM. This saves CPU usage needed for decoding and file access if the underlying factory reads from a file on the harddisk, but it consumes a lot of memory.

Returns The created `Factory` object.

Return type `Factory`

Note: Only known-length factories can be buffered.

> **Warning:** Raw PCM data needs a lot of space, only buffer short factories.

delay(time)

Delays by playing adding silence in front of the other factory's data.

Parameters **time** (*float*) – How many seconds of silence should be added before the factory.

Returns The created `Factory` object.

Return type `Factory`

fadein(start, length)

Fades a factory in by raising the volume linearly in the given time interval.

Parameters

- **start** (*float*) – Time in seconds when the fading should start.
- **length** (*float*) – Time in seconds how long the fading should last.

Returns The created `Factory` object.

Return type `Factory`

Note: Before the fade starts it plays silence.

---

fadeout(start, length)

Fades a factory in by lowering the volume linearly in the given time interval.

Parameters

- **start** (*float*) – Time in seconds when the fading should start.
- **length** (*float*) – Time in seconds how long the fading should last.

Returns The created `Factory` object.

Return type `Factory`

Note: After the fade this factory plays silence, so that the length of the factory is not altered.

---

filter(b, a = (1))

Filters a factory with the supplied IIR filter coefficients. Without the second parameter you'll get a FIR filter. If the first value of the a sequence is 0 it will be set to 1 automatically. If the first value of the a sequence is neither 0 nor 1, all filter coefficients will be scaled by this value so that it is 1 in the end, you don't have to scale yourself.

Parameters

- **b** (*sequence of float*) – The nominator filter coefficients.
- **a** (*sequence of float*) – The denominator filter coefficients.

Returns The created `Factory` object.

Return type `Factory`

highpass(frequency, Q=0.5)

Creates a second order highpass filter based on the transfer function H(s) = s^2 / (s^2 + s/Q + 1)

Parameters

- **frequency** (*float*) – The cut off trequency of the highpass.
- **Q** (*float*) – Q factor of the lowpass.

Returns The created `Factory` object.

Return type `Factory`

join(factory)

Plays two factories in sequence.

Parameters **factory** (`Factory`) – The factory to play second.

Returns The created `Factory` object.

Return type `Factory`

Note: The two factories have to have the same specifications (channels and samplerate).

limit(start, end)

Limits a factory within a specific start and end time.

Parameters

- **start** (*float*) – Start time in seconds.
- **end** (*float*) – End time in seconds.

Returns The created `Factory` object.

Return type `Factory`

loop(count)

Loops a factory.

Parameters **count** (*integer*) – How often the factory should be looped. Negative values mean endlessly.

Returns The created `Factory` object.

Return type `Factory`

Note: This is a filter function, you might consider using `Handle.loop_count` instead.

lowpass(frequency, Q=0.5)

Creates a second order lowpass filter based on the transfer function H(s) = 1 / (s^2 + s/Q + 1)

Parameters

- **frequency** (*float*) – The cut off trequency of the lowpass.
- **Q** (*float*) – Q factor of the lowpass.

Returns The created `Factory` object.

Return type `Factory`

mix(factory)

Mixes two factories.

Parameters **factory** (`Factory`) – The factory to mix over the other.

Returns The created `Factory` object.

Return type `Factory`

Note: The two factories have to have the same specifications (channels and samplerate).

pingpong()

Plays a factory forward and then backward. This is like joining a factory with its reverse.

Returns The created `Factory` object.

Return type `Factory`

pitch(factor)

Changes the pitch of a factory with a specific factor.

Parameters **factor** (*float*) – The factor to change the pitch with.

Returns The created `Factory` object.

Return type `Factory`

Note: This is done by changing the sample rate of the underlying factory, which has to be an integer, so the factor value rounded and the factor may not be 100 % accurate.

Note: This is a filter function, you might consider using `Handle.pitch` instead.

---

reverse()

Plays a factory reversed.

Returns The created `Factory` object.

Return type `Factory`

Note: The factory has to have a finite length and has to be seekable. It's recommended to use this only with factories with fast and accurate seeking, which is not true for encoded audio files, such ones should be buffered using `buffer()` before being played reversed.

Warning: If seeking is not accurate in the underlying factory you'll likely hear skips/jumps/cracks.

square(threshold = 0)

Makes a square wave out of an audio wave by setting all samples with a amplitude >= threshold to 1, all <= -threshold to -1 and all between to 0.

Parameters **threshold** (*float*) – Threshold value over which an amplitude counts non-zero.

Returns The created `Factory` object.

Return type `Factory`

volume(volume)

Changes the volume of a factory.

Parameters **volume** (*float*) – The new volume..

Returns The created `Factory` object.

Return type `Factory`

Note: Should be in the range [0, 1] to avoid clipping.

Note: This is a filter function, you might consider using `Handle.volume` instead.

---

class `aud.Handle`

Handle objects are playback handles that can be used to control playback of a sound. If a sound is played back multiple times then there are as many handles.

pause()

Pauses playback.

Returns Whether the action succeeded.

Return type bool

resume()

Resumes playback.

Returns Whether the action succeeded.

Return type bool

stop()

Stops playback.

Returns Whether the action succeeded.

Return type bool

Note: This makes the handle invalid.

---

attenuation

This factor is used for distance based attenuation of the source.

See Also:

`Device.distance_model`

cone_angle_inner

The opening angle of the inner cone of the source. If the cone values of a source are set there are two (audible) cones with the apex at the `location` of the source and with infinite height, heading in the direction of the source's `orientation`. In the inner cone the volume is normal. Outside the outer cone the volume will be `cone_volume_outer` and in the area between the volume will be interpolated linearly.

cone_angle_outer

The opening angle of the outer cone of the source.

See Also:

`cone_angle_inner`

cone_volume_outer

The volume outside the outer cone of the source.

See Also:

`cone_angle_inner`

distance_maximum

The maximum distance of the source. If the listener is further away the source volume will be 0.

See Also:

`Device.distance_model`

distance_reference

The reference distance of the source. At this distance the volume will be exactly `volume`.

See Also:

Device.distance_model

keep
Whether the sound should be kept paused in the device when its end is reached. This can be used to seek the sound to some position and start playback again.

> **Warning:** If this is set to true and you forget stopping this equals a memory leak as the handle exists until the device is destroyed.

location
The source's location in 3D space, a 3D tuple of floats.

loop_count
The (remaining) loop count of the sound. A negative value indicates infinity.

orientation
The source's orientation in 3D space as quaternion, a 4 float tuple.

pitch
The pitch of the sound.

position
The playback position of the sound in seconds.

relative
Whether the source's location, velocity and orientation is relative or absolute to the listener.

status
Whether the sound is playing, paused or stopped (=invalid).

velocity
The source's velocity in 3D space, a 3D tuple of floats.

volume
The volume of the sound.

volume_maximum
The maximum volume of the source.

See Also:

Device.distance_model

volume_minimum
The minimum volume of the source.

See Also:

Device.distance_model

class aud.**error**

CHAPTER

THREE

GAME ENGINE MODULES

3.1 Game Engine bge.types Module

class bge.types.**PyObjectPlus**

PyObjectPlus base class of most other types in the Game Engine.

invalid

Test if the object has been freed by the game engine and is no longer valid.

Normally this is not a problem but when storing game engine data in the GameLogic module, KX_Scenes or other KX_GameObjects its possible to hold a reference to invalid data. Calling an attribute or method on an invalid object will raise a SystemError.

The invalid attribute allows testing for this case without exception handling.

Type boolean

class bge.types.**CValue**(*PyObjectPlus*)

This class is a basis for other classes.

name

The name of this CValue derived object (read-only).

Type string

class bge.types.**CPropValue**(*CValue*)

This class has no python functions

class bge.types.**SCA_ILogicBrick**(*CValue*)

Base class for all logic bricks.

executePriority

This determines the order controllers are evaluated, and actuators are activated (lower priority is executed first).

Type executePriority: int

owner

The game object this logic brick is attached to (read-only).

Type KX_GameObject or None in exceptional cases.

name

The name of this logic brick (read-only).

Type string

class bge.types.**SCA_PythonKeyboard**(*PyObjectPlus*)
The current keyboard.

events
A dictionary containing the status of each keyboard event or key. (read-only).

Type dictionary {*keycode*:*status*, ...}

class bge.types.**SCA_PythonMouse**(*PyObjectPlus*)
The current mouse.

events
a dictionary containing the status of each mouse event. (read-only).

Type dictionary {*keycode*:*status*, ...}

position
The normalized x and y position of the mouse cursor.

Type list [x, y]

visible
The visibility of the mouse cursor.

Type boolean

class bge.types.**SCA_IObject**(*CValue*)
This class has no python functions

class bge.types.**SCA_ISensor**(*SCA_ILogicBrick*)
Base class for all sensor logic bricks.

usePosPulseMode
Flag to turn positive pulse mode on and off.

Type boolean

useNegPulseMode
Flag to turn negative pulse mode on and off.

Type boolean

frequency
The frequency for pulse mode sensors.

Type integer

level
level Option whether to detect level or edge transition when entering a state. It makes a difference only in case of logic state transition (state actuator). A level detector will immediately generate a pulse, negative or positive depending on the sensor condition, as soon as the state is activated. A edge detector will wait for a state change before generating a pulse. note: mutually exclusive with `tap`, enabling will disable `tap`.

Type boolean

tap
When enabled only sensors that are just activated will send a positive event, after this they will be detected as negative by the controllers. This will make a key thats held act as if its only tapped for an instant. note: mutually exclusive with `level`, enabling will disable `level`.

Type boolean

invert
Flag to set if this sensor activates on positive or negative events.

Type boolean

triggered
True if this sensor brick is in a positive state. (read-only).

Type boolean

positive
True if this sensor brick is in a positive state. (read-only).

Type boolean

status
The status of the sensor (read-only): can be one of *these constants*.

Type int

Note: This convenient attribute combines the values of triggered and positive attributes.

---

reset()
Reset sensor internal state, effect depends on the type of sensor and settings.

The sensor is put in its initial state as if it was just activated.

class bge.types.**SCA_IController**(*SCA_ILogicBrick*)
Base class for all controller logic bricks.

state
The controllers state bitmask. This can be used with the GameObject's state to test if the controller is active.

Type int bitmask

sensors
A list of sensors linked to this controller.

Type sequence supporting index/string lookups and iteration.

Note: The sensors are not necessarily owned by the same object.

Note: When objects are instanced in dupligroups links may be lost from objects outside the dupligroup.

---

actuators
A list of actuators linked to this controller.

Type sequence supporting index/string lookups and iteration.

Note: The sensors are not necessarily owned by the same object.

Note: When objects are instanced in dupligroups links may be lost from objects outside the dupligroup.

---

useHighPriority
When set the controller executes always before all other controllers that dont have this set.

Type boolen

Note: Order of execution between high priority controllers is not guaranteed.

class bge.types.**SCA_IActuator**(*SCA_ILogicBrick*)

Base class for all actuator logic bricks.

class bge.types.**BL_ActionActuator**(*SCA_IActuator*)

Action Actuators apply an action to an actor.

action

The name of the action to set as the current action.

Type string

channelNames

A list of channel names that may be used with `setChannel` and `getChannel`.

Type list of strings

frameStart

Specifies the starting frame of the animation.

Type float

frameEnd

Specifies the ending frame of the animation.

Type float

blendIn

Specifies the number of frames of animation to generate when making transitions between actions.

Type float

priority

Sets the priority of this actuator. Actuators will lower priority numbers will override actuators with higher numbers.

Type integer

frame

Sets the current frame for the animation.

Type float

propName

Sets the property to be used in FromProp playback mode.

Type string

blendTime

Sets the internal frame timer. This property must be in the range from 0.0 to blendIn.

Type float

mode

The operation mode of the actuator. Can be one of *these constants*.

Type integer

useContinue

The actions continue option, True or False. When True, the action will always play from where last left off, otherwise negative events to this actuator will reset it to its start frame.

Type boolean

framePropName
The name of the property that is set to the current frame number.

Type string

setChannel (*channel*, *matrix*)
Alternative to the 2 arguments, 4 arguments (channel, matrix, loc, size, quat) are also supported.

Parameters

- **channel** (*string*) – A string specifying the name of the bone channel, error raised if not in `channelNames`.
- **matrix** – A 4x4 matrix specifying the overriding transformation as an offset from the bone's rest position.
- **matrix** – list [[float]]

Note: These values are relative to the bones rest position, currently the api has no way to get this info (which is annoying), but can be worked around by using bones with a rest pose that has no translation.

---

getChannel (*channel*)

Parameters **channel** (*string*) – A string specifying the name of the bone channel. error raised if not in `channelNames`.

Returns (loc, size, quat)

Return type tuple

class bge.types.**BL_Shader** (*PyObjectPlus*)
BL_Shader GLSL shaders.

TODO - Description

setUniformfv (*name*, *fList*)
Set a uniform with a list of float values

Parameters

- **name** (*string*) – the uniform name
- **fList** (*list[float]*) – a list (2, 3 or 4 elements) of float values

delSource ()
Clear the shader. Use this method before the source is changed with `setSource`.

getFragmentProg ()
Returns the fragment program.

Returns The fragment program.

Return type string

getVertexProg ()
Get the vertex program.

Returns The vertex program.

Return type string

isValid ()
Check if the shader is valid.

Returns True if the shader is valid

Return type boolean

setAttrib(*enum*)

Set attribute location. (The parameter is ignored a.t.m. and the value of "tangent" is always used.)

Parameters **enum** (*integer*) – attribute location value

setNumberOfPasses(*max_pass*)

Set the maximum number of passes. Not used a.t.m.

Parameters **max_pass** (*integer*) – the maximum number of passes

setSampler(*name*, *index*)

Set uniform texture sample index.

Parameters

- **name** (*string*) – Uniform name
- **index** (*integer*) – Texture sample index.

setSource(*vertexProgram*, *fragmentProgram*)

Set the vertex and fragment programs

Parameters

- **vertexProgram** (*string*) – Vertex program
- **fragmentProgram** (*string*) – Fragment program

setUniform1f(*name*, *fx*)

Set a uniform with 1 float value.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – Uniform value

setUniform1i(*name*, *ix*)

Set a uniform with an integer value.

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – the uniform value

setUniform2f(*name*, *fx*, *fy*)

Set a uniform with 2 float values

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- **fy** (*float*) – second float value

setUniform2i(*name*, *ix*, *iy*)

Set a uniform with 2 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value

setUniform3f (*name*, *fx*, *fy*, *fz*)
Set a uniform with 3 float values.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- **fy** (*float*) – second float value
- **fz** (*float*) – third float value

setUniform3i (*name*, *ix*, *iy*, *iz*)
Set a uniform with 3 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value
- **iz** (*integer*) – third integer value

setUniform4f (*name*, *fx*, *fy*, *fz*, *fw*)
Set a uniform with 4 float values.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- **fy** (*float*) – second float value
- **fz** (*float*) – third float value
- **fw** (*float*) – fourth float value

setUniform4i (*name*, *ix*, *iy*, *iz*, *iw*)
Set a uniform with 4 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value
- **iz** (*integer*) – third integer value
- **iw** (*integer*) – fourth integer value

setUniformDef (*name*, *type*)
Define a new uniform

Parameters

- **name** (*string*) – the uniform name
- **type** (*UNI_NONE, UNI_INT, UNI_FLOAT, UNI_INT2, UNI_FLOAT2, UNI_INT3, UNI_FLOAT3, UNI_INT4, UNI_FLOAT4, UNI_MAT3, UNI_MAT4, UNI_MAX*) – uniform type

setUniformMatrix3 (*name*, *mat*, *transpose*)
Set a uniform with a 3x3 matrix value

Parameters

- **name** (*string*) – the uniform name
- **mat** (*3x3 matrix*) – A 3x3 matrix [[f, f, f], [f, f, f], [f, f, f]]
- **transpose** (*boolean*) – set to True to transpose the matrix

setUniformMatrix4 (*name*, *mat*, *transpose*)
Set a uniform with a 4x4 matrix value

Parameters

- **name** (*string*) – the uniform name
- **mat** (*4x4 matrix*) – A 4x4 matrix [[f, f, f, f], [f, f, f, f], [f, f, f, f], [f, f, f, f]]
- **transpose** (*boolean*) – set to True to transpose the matrix

setUniformiv (*name*, *iList*)
Set a uniform with a list of integer values

Parameters

- **name** (*string*) – the uniform name
- **iList** (*list[integer]*) – a list (2, 3 or 4 elements) of integer values

validate ()
Validate the shader object.

class bge.types.**BL_ShapeActionActuator** (*SCA_IActuator*)
ShapeAction Actuators apply an shape action to an mesh object.

action
The name of the action to set as the current shape action.

Type string

frameStart
Specifies the starting frame of the shape animation.

Type float

frameEnd
Specifies the ending frame of the shape animation.

Type float

blendIn
Specifies the number of frames of animation to generate when making transitions between actions.

Type float

priority
Sets the priority of this actuator. Actuators will lower priority numbers will override actuators with higher numbers.

Type integer

frame
Sets the current frame for the animation.

Type float

propName
Sets the property to be used in FromProp playback mode.

Type string

blendTime
Sets the internal frame timer. This property must be in the range from 0.0 to blendin.

Type float

mode
The operation mode of the actuator. Can be one of *these constants*.

Type integer

framePropName
The name of the property that is set to the current frame number.

Type string

class `bge.types.`**`CListValue`**(*CPropValue*)
This is a list like object used in the game engine internally that behaves similar to a python list in most ways.

As well as the normal index lookup (`val= clist[i]`), CListValue supports string lookups (`val= scene.objects["Cube"]`)

Other operations such as `len(clist)`, `list(clist)`, `clist[0:10]` are also supported.

append(*val*)
Add an item to the list (like pythons append)

> **Warning:** Appending values to the list can cause crashes when the list is used internally by the game engine.

count(*val*)
Count the number of instances of a value in the list.

Returns number of instances

Return type integer

index(*val*)
Return the index of a value in the list.

Returns The index of the value in the list.

Return type integer

reverse()
Reverse the order of the list.

get(*key*, *default=None*)
Return the value matching key, or the default value if its not found.

Returns The key value or a default.

from_id(*id*)
This is a funtion especially for the game engine to return a value with a spesific id.

Since object names are not always unique, the id of an object can be used to get an object from the CValueList.

Example:

```
myObID=id(gameObject)
ob= scene.objects.from_id(myObID)
```

Where `myObID` is an int or long from the id function.

This has the advantage that you can store the id in places you could not store a gameObject.

> **Warning:** The id is derived from a memory location and will be different each time the game engine starts.

class `bge.types.`**`KX_BlenderMaterial`**(*PyObjectPlus*)

KX_BlenderMaterial

`getShader`()

Returns the material's shader.

Returns the material's shader

Return type `BL_Shader`

`setBlending`(*src*, *dest*)

Set the pixel color arithmetic functions.

Parameters

- **src** – Specifies how the red, green, blue, and alpha source blending factors are computed.
- **dest** – Specifies how the red, green, blue, and alpha destination blending factors are computed.

`getMaterialIndex`()

Returns the material's index.

Returns the material's index

Return type integer

class `bge.types.`**`KX_CameraActuator`**(*SCA_IActuator*)

Applies changes to a camera.

`min`

minimum distance to the target object maintained by the actuator.

Type float

`max`

maximum distance to stay from the target object.

Type float

`height`

height to stay above the target object.

Type float

`useXY`

axis this actuator is tracking, True=X, False=Y.

Type boolean

`object`

the object this actuator tracks.

Type `KX_GameObject` or None

class `bge.types.`**`KX_ConstraintActuator`**(*SCA_IActuator*)

A constraint actuator limits the position, rotation, distance or orientation of an object.

damp
Time constant of the constraint expressed in frame (not use by Force field constraint).

Type integer

rotDamp
Time constant for the rotation expressed in frame (only for the distance constraint), 0 = use damp for rotation as well.

Type integer

direction
The reference direction in world coordinate for the orientation constraint.

Type 3-tuple of float: (x, y, z)

option
Binary combination of *these constants*

Type integer

time
activation time of the actuator. The actuator disables itself after this many frame. If set to 0, the actuator is not limited in time.

Type integer

propName
the name of the property or material for the ray detection of the distance constraint.

Type string

min
The lower bound of the constraint. For the rotation and orientation constraint, it represents radiant.

Type float

distance
the target distance of the distance constraint.

Type float

max
the upper bound of the constraint. For rotation and orientation constraints, it represents radiant.

Type float

rayLength
the length of the ray of the distance constraint.

Type float

limit
type of constraint. Use one of the *these constants*

Type integer.

class bge.types.**KX_ConstraintWrapper**(*PyObjectPlus*)
KX_ConstraintWrapper

getConstraintId(*val*)
Returns the contraint's ID

Returns the constraint's ID

Return type integer

class bge.types.**KX_GameActuator**(*SCA_IActuator*)

The game actuator loads a new .blend file, restarts the current .blend file or quits the game.

fileName

the new .blend file to load.

Type string

mode

The mode of this actuator. Can be on of *these constants*

Type Int

class bge.types.**KX_GameObject**(*SCA_IObject*)

All game objects are derived from this class.

Properties assigned to game objects are accessible as attributes of this class.

Note: Calling ANY method or attribute on an object that has been removed from a scene will raise a SystemError, if an object may have been removed since last accessing it use the `invalid` attribute to check.

---

name

The object's name. (read-only).

Type string

mass

The object's mass

Type float

Note: The object must have a physics controller for the mass to be applied, otherwise the mass value will be returned as 0.0.

---

linVelocityMin

Enforces the object keeps moving at a minimum velocity.

Type float

Note: Applies to dynamic and rigid body objects only.

Note: A value of 0.0 disables this option.

Note: While objects are stationary the minimum velocity will not be applied.

---

linVelocityMax

Clamp the maximum linear velocity to prevent objects moving beyond a set speed.

Type float

Note: Applies to dynamic and rigid body objects only.

Note: A value of 0.0 disables this option (rather then setting it stationary).

---

localInertia
the object's inertia vector in local coordinates. Read only.

Type list [ix, iy, iz]

parent
The object's parent object. (read-only).

Type `KX_GameObject` or None

visible
visibility flag.

Type boolean

Note: Game logic will still run for invisible objects.

---

color
The object color of the object. [r, g, b, a]

Type `mathutils.Vector`

occlusion
occlusion capability flag.

Type boolean

position
The object's position. [x, y, z] On write: local position, on read: world position Deprecated since version use: `localPosition` and `worldPosition`.

Type `mathurils.Vector`

orientation
The object's orientation. 3x3 Matrix. You can also write a Quaternion or Euler vector. On write: local orientation, on read: world orientation Deprecated since version use: `localOrientation` and `worldOrientation`.

Type `mathutils.Matrix`

scaling
The object's scaling factor. [sx, sy, sz] On write: local scaling, on read: world scaling Deprecated since version use: `localScale` and `worldScale`.

Type `mathutils.Vector`

localOrientation
The object's local orientation. 3x3 Matrix. You can also write a Quaternion or Euler vector.

Type `mathutils.Matrix`

worldOrientation
The object's world orientation. 3x3 Matrix.

Type `mathutils.Matrix`

localScale
The object's local scaling factor. [sx, sy, sz]

Type `mathutils.Vector`

worldScale
The object's world scaling factor. Read-only. [sx, sy, sz]

Type mathutils.Vector

localPosition
The object's local position. [x, y, z]

Type mathutils.Vector

worldPosition
The object's world position. [x, y, z]

Type mathutils.Vector

localLinearVelocity
The object's local linear velocity. [x, y, z]

Type mathutils.Vector

worldLinearVelocity
The object's world linear velocity. [x, y, z]

type mathutils.Vector

localAngularVelocity
The object's local angular velocity. [x, y, z]

type mathutils.Vector

worldAngularVelocity
The object's world angular velocity. [x, y, z]

type mathutils.Vector

timeOffset
adjust the slowparent delay at runtime.

Type float

state
the game object's state bitmask, using the first 30 bits, one bit must always be set.

Type int

meshes
a list meshes for this object.

Type list of KX_MeshProxy

Note: Most objects use only 1 mesh.

Note: Changes to this list will not update the KX_GameObject.

---

sensors
a sequence of SCA_ISensor objects with string/index lookups and iterator support.

Type list

Note: This attribute is experemental and may be removed (but probably wont be).

Note: Changes to this list will not update the KX_GameObject.

---

controllers
a sequence of SCA_IController objects with string/index lookups and iterator support.

Type list of SCA_ISensor

Note: This attribute is experemental and may be removed (but probably wont be).

Note: Changes to this list will not update the KX_GameObject.

actuators
a list of SCA_IActuator with string/index lookups and iterator support.

Type list

Note: This attribute is experemental and may be removed (but probably wont be).

Note: Changes to this list will not update the KX_GameObject.

attrDict
get the objects internal python attribute dictionary for direct (faster) access.

Type dict

children
direct children of this object, (read-only).

Type CListValue of KX_GameObject's

childrenRecursive
all children of this object including childrens children, (read-only).

Type CListValue of KX_GameObject's

endObject()
Delete this object, can be used in place of the EndObject Actuator.

The actual removal of the object from the scene is delayed.

replaceMesh(*mesh*, *useDisplayMesh=True*, *usePhysicsMesh=False*)
Replace the mesh of this object with a new mesh. This works the same was as the actuator.

Parameters

- **mesh** (MeshProxy or string) – mesh to replace or the meshes name.
- **useDisplayMesh** (*boolean*) – when enabled the display mesh will be replaced (optional argument).
- **usePhysicsMesh** (*boolean*) – when enabled the physics mesh will be replaced (optional argument).

setVisible(*visible*, *recursive*)
Sets the game object's visible flag.

Parameters

- **visible** (*boolean*) – the visible state to set.
- **recursive** (*boolean*) – optional argument to set all childrens visibility flag too.

setOcclusion (*occlusion*, *recursive*)
Sets the game object's occlusion capability.

Parameters

- **occlusion** (*boolean*) – the state to set the occlusion to.
- **recursive** (*boolean*) – optional argument to set all childrens occlusion flag too.

alignAxisToVect (*vect*, *axis=2*, *factor=1.0*)
Aligns any of the game object's axis along the given vector.

Parameters

- **vect** (*3D vector*) – a vector to align the axis.
- **axis** (*integer*) – The axis you want to align
  - 0: X axis
  - 1: Y axis
  - 2: Z axis
- **factor** (*float*) – Only rotate a feaction of the distance to the target vector (0.0 - 1.0)

getAxisVect (*vect*)
Returns the axis vector rotates by the objects worldspace orientation. This is the equivalent of multiplying the vector by the orientation matrix.

Parameters **vect** (*3D Vector*) – a vector to align the axis.

Returns The vector in relation to the objects rotation.

Return type 3d vector.

applyMovement (*movement*, *local=False*)
Sets the game object's movement.

Parameters

- **movement** (*3D Vector*) – movement vector.
- **local** –
  - False: you get the "global" movement ie: relative to world orientation.
  - True: you get the "local" movement ie: relative to object orientation.
- **local** – boolean

applyRotation (*rotation*, *local=False*)
Sets the game object's rotation.

Parameters

- **rotation** (*3D Vector*) – rotation vector.
- **local** –
  - False: you get the "global" rotation ie: relative to world orientation.
  - True: you get the "local" rotation ie: relative to object orientation.
- **local** – boolean

applyForce (*force*, *local=False*)
Sets the game object's force.

This requires a dynamic object.

Parameters

- **force** (*3D Vector*) – force vector.
- **local** (*boolean*) –
  - False: you get the "global" force ie: relative to world orientation.
  - True: you get the "local" force ie: relative to object orientation.

applyTorque (*torque*, *local=False*)
Sets the game object's torque.

This requires a dynamic object.

Parameters

- **torque** (*3D Vector*) – torque vector.
- **local** (*boolean*) –
  - False: you get the "global" torque ie: relative to world orientation.
  - True: you get the "local" torque ie: relative to object orientation.

getLinearVelocity (*local=False*)
Gets the game object's linear velocity.

This method returns the game object's velocity through it's centre of mass, ie no angular velocity component.

Parameters **local** (*boolean*) –

- False: you get the "global" velocity ie: relative to world orientation.
- True: you get the "local" velocity ie: relative to object orientation.

Returns the object's linear velocity.

Return type list [vx, vy, vz]

setLinearVelocity (*velocity*, *local=False*)
Sets the game object's linear velocity.

This method sets game object's velocity through it's centre of mass, ie no angular velocity component.

This requires a dynamic object.

Parameters

- **velocity** (*3D Vector*) – linear velocity vector.
- **local** (*boolean*) –
  - False: you get the "global" velocity ie: relative to world orientation.
  - True: you get the "local" velocity ie: relative to object orientation.

getAngularVelocity (*local=False*)
Gets the game object's angular velocity.

Parameters **local** (*boolean*) –

- False: you get the "global" velocity ie: relative to world orientation.

- True: you get the "local" velocity ie: relative to object orientation.

Returns the object's angular velocity.

Return type list [vx, vy, vz]

setAngularVelocity (*velocity*, *local=False*)

Sets the game object's angular velocity.

This requires a dynamic object.

Parameters

- **velocity** (*boolean*) – angular velocity vector.
- **local** –
  - False: you get the "global" velocity ie: relative to world orientation.
  - True: you get the "local" velocity ie: relative to object orientation.

getVelocity (*point=(0, 0, 0)*)

Gets the game object's velocity at the specified point.

Gets the game object's velocity at the specified point, including angular components.

Parameters **point** (*3D Vector*) – optional point to return the velocity for, in local coordinates.

Returns the velocity at the specified point.

Return type list [vx, vy, vz]

getReactionForce ()

Gets the game object's reaction force.

The reaction force is the force applied to this object over the last simulation timestep. This also includes impulses, eg from collisions.

Returns the reaction force of this object.

Return type list [fx, fy, fz]

Note: This is not implimented at the moment.

---

applyImpulse (*point*, *impulse*)

Applies an impulse to the game object.

This will apply the specified impulse to the game object at the specified point. If point != position, applyImpulse will also change the object's angular momentum. Otherwise, only linear momentum will change.

Parameters **point** (*the point to apply the impulse to (in world coordinates)*) – the point to apply the impulse to (in world coordinates)

suspendDynamics ()

Suspends physics for this object.

restoreDynamics ()

Resumes physics for this object.

Note: The objects linear velocity will be applied from when the dynamics were suspended.

---

enableRigidBody ()

Enables rigid body physics for this object.

Rigid body physics allows the object to roll on collisions.

Note: This is not working with bullet physics yet.

disableRigidBody()

Disables rigid body physics for this object.

Note: This is not working with bullet physics yet. The angular is removed but rigid body physics can still rotate it later.

setParent(*parent*, *compound=True*, *ghost=True*)

Sets this object's parent. Control the shape status with the optional compound and ghost parameters:

In that case you can control if it should be ghost or not:

Parameters

- **parent** (KX_GameObject) – new parent object.
- **compound** (*boolean*) – whether the shape should be added to the parent compound shape.
  - True: the object shape should be added to the parent compound shape.
  - False: the object should keep its individual shape.
- **ghost** (*boolean*) – whether the object should be ghost while parented.
  - True: if the object should be made ghost while parented.
  - False: if the object should be solid while parented.

Note: If the object type is sensor, it stays ghost regardless of ghost parameter

removeParent()

Removes this objects parent.

getPhysicsId()

Returns the user data object associated with this game object's physics controller.

getPropertyNames()

Gets a list of all property names.

Returns All property names for this object.

Return type list

getDistanceTo(*other*)

Parameters **other** (KX_GameObject or list [x, y, z]) – a point or another KX_GameObject to measure the distance to.

Returns distance to another object or point.

Return type float

getVectTo(*other*)

Returns the vector and the distance to another object or point. The vector is normalized unless the distance is 0, in which a zero length vector is returned.

Parameters **other** (KX_GameObject or list [x, y, z]) – a point or another KX_GameObject to get the vector and distance to.

Returns (distance, globalVector(3), localVector(3))

Return type 3-tuple (float, 3-tuple (x, y, z), 3-tuple (x, y, z))

rayCastTo(*other*, *dist*, *prop*)

Look towards another point/object and find first object hit within dist that matches prop.

The ray is always casted from the center of the object, ignoring the object itself. The ray is casted towards the center of another object or an explicit [x, y, z] point. Use rayCast() if you need to retrieve the hit point

Parameters

- **other** (KX_GameObject or 3-tuple) – [x, y, z] or object towards which the ray is casted
- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to other
- **prop** (*string*) – property name that object must have; can be omitted => detect any object

Returns the first object hit or None if no object or object does not match prop

Return type KX_GameObject

rayCast(*objto*, *objfrom*, *dist*, *prop*, *face*, *xray*, *poly*)

Look from a point/object to another point/object and find first object hit within dist that matches prop. if poly is 0, returns a 3-tuple with object reference, hit point and hit normal or (None, None, None) if no hit. if poly is 1, returns a 4-tuple with in addition a KX_PolyProxy as 4th element. if poly is 2, returns a 5-tuple with in addition a 2D vector with the UV mapping of the hit point as 5th element.

```
# shoot along the axis gun-gunAim (gunAim should be collision-free)
obj, point, normal = gun.rayCast(gunAim, None, 50)
if obj:
   # do something
   pass
```

The face paremeter determines the orientation of the normal.

•0 => hit normal is always oriented towards the ray origin (as if you casted the ray from outside)

•1 => hit normal is the real face normal (only for mesh object, otherwise face has no effect)

The ray has X-Ray capability if xray parameter is 1, otherwise the first object hit (other than self object) stops the ray. The prop and xray parameters interact as follow.

•prop off, xray off: return closest hit or no hit if there is no object on the full extend of the ray.

•prop off, xray on : idem.

•prop on, xray off: return closest hit if it matches prop, no hit otherwise.

•prop on, xray on : return closest hit matching prop or no hit if there is no object matching prop on the full extend of the ray.

The KX_PolyProxy 4th element of the return tuple when poly=1 allows to retrieve information on the polygon hit by the ray. If there is no hit or the hit object is not a static mesh, None is returned as 4th element.

The ray ignores collision-free objects and faces that dont have the collision flag enabled, you can however use ghost objects.

Parameters

- **objto** (KX_GameObject or 3-tuple) – [x, y, z] or object to which the ray is casted
- **objfrom** (KX_GameObject or 3-tuple or None) – [x, y, z] or object from which the ray is casted; None or omitted => use self object center

- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to to
- **prop** (*string*) – property name that object must have; can be omitted or "" => detect any object
- **face** (*integer*) – normal option: 1=>return face normal; 0 or omitted => normal is oriented towards origin
- **xray** (*integer*) – X-ray option: 1=>skip objects that don't match prop; 0 or omitted => stop on first object
- **poly** (*integer*) – polygon option: 0, 1 or 2 to return a 3-, 4- or 5-tuple with information on the face hit.
  - 0 or omitted: return value is a 3-tuple (object, hitpoint, hitnormal) or (None, None, None) if no hit
  - 1: return value is a 4-tuple and the 4th element is a `KX_PolyProxy` or None if no hit or the object doesn't use a mesh collision shape.
  - 2: return value is a 5-tuple and the 5th element is a 2-tuple (u, v) with the UV mapping of the hit point or None if no hit, or the object doesn't use a mesh collision shape, or doesn't have a UV mapping.

Returns

(object, hitpoint, hitnormal) or (object, hitpoint, hitnormal, polygon) or (object, hitpoint, hitnormal, polygon, hituv).

- object, hitpoint and hitnormal are None if no hit.
- polygon is valid only if the object is valid and is a static object, a dynamic object using mesh collision shape or a soft body object, otherwise it is None
- hituv is valid only if polygon is valid and the object has a UV mapping, otherwise it is None

Return type

- 3-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz))
- or 4-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz), `PolyProxy`)
- or 5-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz), `PolyProxy`, 2-tuple (u, v))

Note: The ray ignores the object on which the method is called. It is casted from/to object center or explicit [x, y, z] points.

---

setCollisionMargin(*margin*)

Set the objects collision margin.

Parameters **margin** (*float*) – the collision margin distance in blender units.

Note: If this object has no physics controller (a physics ID of zero), this function will raise RuntimeError.

---

sendMessage(*subject*, *body=""*, *to=""*)

Sends a message.

Parameters

- **subject** (*string*) – The subject of the message
- **body** (*string*) – The body of the message (optional)
- **to** (*string*) – The name of the object to send the message to (optional)

reinstancePhysicsMesh (*gameObject*, *meshObject*)

Updates the physics system with the changed mesh.

If no arguments are given the physics mesh will be re-created from the first mesh assigned to the game object.

Parameters

- **gameObject** (string, `KX_GameObject` or None) – optional argument, set the physics shape from this gameObjets mesh.
- **meshObject** (string, `MeshProxy` or None) – optional argument, set the physics shape from this mesh.

Returns True if reinstance succeeded, False if it failed.

Return type boolean

Note: If this object has instances the other instances will be updated too.

Note: The gameObject argument has an advantage that it can convert from a mesh with modifiers applied (such as subsurf).

Warning: Only triangle mesh type objects are supported currently (not convex hull)

Warning: If the object is a part of a combound object it will fail (parent or child)

Warning: Rebuilding the physics mesh can be slow, running many times per second will give a performance hit.

get (*key*, *default=None*)

Return the value matching key, or the default value if its not found. :return: The key value or a default.

class `bge.types.`**KX_IpoActuator** (*SCA_IActuator*)

IPO actuator activates an animation.

frameStart

Start frame.

Type float

frameEnd

End frame.

Type float

propName

Use this property to define the Ipo position.

Type string

framePropName

Assign this property this action current frame number.

Type string

mode
Play mode for the ipo. Can be on of *these constants*

Type integer

useIpoAsForce
Apply Ipo as a global or local force depending on the local option (dynamic objects only).

Type boolean

useIpoAdd
Ipo is added to the current loc/rot/scale in global or local coordinate according to Local flag.

Type boolean

useIpoLocal
Let the ipo acts in local coordinates, used in Force and Add mode.

Type boolean

useChildren
Update IPO on all children Objects as well.

Type boolean

class `bge.types.`**`KX_LightObject`**(*KX_GameObject*)
A Light object.

```
# Turn on a red alert light.
import bge

co = bge.logic.getCurrentController()
light = co.owner

light.energy = 1.0
light.colour = [1.0, 0.0, 0.0]
```

SPOT
A spot light source. See attribute `type`

SUN
A point light source with no attenuation. See attribute `type`

NORMAL
A point light source. See attribute `type`

type
The type of light - must be SPOT, SUN or NORMAL

layer
The layer mask that this light affects object on.

Type bitfield

energy
The brightness of this light.

Type float

distance
The maximum distance this light can illuminate. (SPOT and NORMAL lights only).

Type float

colour
The colour of this light. Black = [0.0, 0.0, 0.0], White = [1.0, 1.0, 1.0].

Type list [r, g, b]

color
Synonym for colour.

lin_attenuation
The linear component of this light's attenuation. (SPOT and NORMAL lights only).

Type float

quad_attenuation
The quadratic component of this light's attenuation (SPOT and NORMAL lights only).

Type float

spotsize
The cone angle of the spot light, in degrees (SPOT lights only).

Type float in [0 - 180].

spotblend
Specifies the intensity distribution of the spot light (SPOT lights only).

Type float in [0 - 1]

Note: Higher values result in a more focused light source.

---

class bge.types.**KX_MeshProxy**(*SCA_IObject*)
A mesh object.

You can only change the vertex properties of a mesh object, not the mesh topology.

To use mesh objects effectively, you should know a bit about how the game engine handles them.

1. Mesh Objects are converted from Blender at scene load.
2. The Converter groups polygons by Material. This means they can be sent to the renderer efficiently. A material holds:
   (a) The texture.
   (b) The Blender material.
   (c) The Tile properties
   (d) The face properties - (From the "Texture Face" panel)
   (e) Transparency & z sorting
   (f) Light layer
   (g) Polygon shape (triangle/quad)
   (h) Game Object
3. Verticies will be split by face if necessary. Verticies can only be shared between faces if:
   (a) They are at the same position
   (b) UV coordinates are the same
   (c) Their normals are the same (both polygons are "Set Smooth")
   (d) They are the same colour, for example: a cube has 24 verticies: 6 faces with 4 verticies per face.

The correct method of iterating over every KX_VertexProxy in a game object

```
import GameLogic

co = GameLogic.getCurrentController()
obj = co.owner

m_i = 0
mesh = obj.getMesh(m_i) # There can be more than one mesh...
while mesh != None:
   for mat in range(mesh.getNumMaterials()):
      for v_index in range(mesh.getVertexArrayLength(mat)):
         vertex = mesh.getVertex(mat, v_index)
         # Do something with vertex here...
         # ... eg: colour the vertex red.
         vertex.colour = [1.0, 0.0, 0.0, 1.0]
   m_i += 1
   mesh = obj.getMesh(m_i)
```

materials

Type list of KX_BlenderMaterial or KX_PolygonMaterial types

numPolygons

Type integer

numMaterials

Type integer

getNumMaterials()

Returns number of materials associated with this object

Return type integer

getMaterialName(*matid*)

Gets the name of the specified material.

Parameters **matid** (*integer*) – the specified material.

Returns the attached material name.

Return type string

getTextureName(*matid*)

Gets the name of the specified material's texture.

Parameters **matid** (*integer*) – the specified material

Returns the attached material's texture name.

Return type string

getVertexArrayLength(*matid*)

Gets the length of the vertex array associated with the specified material.

There is one vertex array for each material.

Parameters **matid** (*integer*) – the specified material

Returns the number of verticies in the vertex array.

Return type integer

getVertex (*matid*, *index*)
Gets the specified vertex from the mesh object.

Parameters

- **matid** (*integer*) – the specified material
- **index** (*integer*) – the index into the vertex array.

Returns a vertex object.

Return type KX_VertexProxy

getNumPolygons ()

Returns The number of polygon in the mesh.

Return type integer

getPolygon (*index*)
Gets the specified polygon from the mesh.

Parameters **index** (*integer*) – polygon number

Returns a polygon object.

Return type PolyProxy

class bge.types.**SCA_MouseSensor** (*SCA_ISensor*)
Mouse Sensor logic brick.

position
current [x, y] coordinates of the mouse, in frame coordinates (pixels).

Type [integer, interger]

mode
sensor mode.

Type integer

- KX_MOUSESENSORMODE_LEFTBUTTON(1)
- KX_MOUSESENSORMODE_MIDDLEBUTTON(2)
- KX_MOUSESENSORMODE_RIGHTBUTTON(3)
- KX_MOUSESENSORMODE_WHEELUP(4)
- KX_MOUSESENSORMODE_WHEELDOWN(5)
- KX_MOUSESENSORMODE_MOVEMENT(6)

getButtonStatus (*button*)
Get the mouse button status.

Parameters **button** (*int*) – The code that represents the key you want to get the state of, use one of *these constants*

Returns The state of the given key, can be one of *these constants*

Return type int

class bge.types.**KX_MouseFocusSensor** (*SCA_MouseSensor*)
The mouse focus sensor detects when the mouse is over the current game object.

The mouse focus sensor works by transforming the mouse coordinates from 2d device space to 3d space then raycasting away from the camera.

raySource
The worldspace source of the ray (the view position).

Type list (vector of 3 floats)

rayTarget
The worldspace target of the ray.

Type list (vector of 3 floats)

rayDirection
The `rayTarget` - `raySource` normalized.

Type list (normalized vector of 3 floats)

hitObject
the last object the mouse was over.

Type `KX_GameObject` or None

hitPosition
The worldspace position of the ray intersecton.

Type list (vector of 3 floats)

hitNormal
the worldspace normal from the face at point of intersection.

Type list (normalized vector of 3 floats)

hitUV
the UV coordinates at the point of intersection.

Type list (vector of 2 floats)

If the object has no UV mapping, it returns [0, 0].

The UV coordinates are not normalized, they can be < 0 or > 1 depending on the UV mapping.

usePulseFocus
When enabled, moving the mouse over a different object generates a pulse. (only used when the 'Mouse Over Any' sensor option is set).

Type boolean

class `bge.types.`**KX_TouchSensor**(*SCA_ISensor*)
Touch sensor detects collisions between objects.

propName
The property or material to collide with.

Type string

useMaterial
Determines if the sensor is looking for a property or material. KX_True = Find material; KX_False = Find property.

Type boolean

usePulseCollision
When enabled, changes to the set of colliding objects generate a pulse.

Type boolean

hitObject
The last collided object. (read-only).

Type KX_GameObject or None

hitObjectList
A list of colliding objects. (read-only).

Type CListValue of KX_GameObject

class bge.types.**KX_NearSensor**(*KX_TouchSensor*)
A near sensor is a specialised form of touch sensor.

distance
The near sensor activates when an object is within this distance.

Type float

resetDistance
The near sensor deactivates when the object exceeds this distance.

Type float

class bge.types.**KX_NetworkMessageActuator**(*SCA_IActuator*)
Message Actuator

propName
Messages will only be sent to objects with the given property name.

Type string

subject
The subject field of the message.

Type string

body
The body of the message.

Type string

usePropBody
Send a property instead of a regular body message.

Type boolean

class bge.types.**KX_NetworkMessageSensor**(*SCA_ISensor*)
The Message Sensor logic brick.

Currently only loopback (local) networks are supported.

subject
The subject the sensor is looking for.

Type string

frameMessageCount
The number of messages received since the last frame. (read-only).

Type integer

subjects
The list of message subjects received. (read-only).

Type list of strings

bodies
The list of message bodies received. (read-only).

Type list of strings

class `bge.types.KX_ObjectActuator`(*SCA_IActuator*)

The object actuator ("Motion Actuator") applies force, torque, displacement, angular displacement, velocity, or angular velocity to an object. Servo control allows to regulate force to achieve a certain speed target.

force

The force applied by the actuator.

Type list [x, y, z]

useLocalForce

A flag specifying if the force is local.

Type boolean

torque

The torque applied by the actuator.

Type list [x, y, z]

useLocalTorque

A flag specifying if the torque is local.

Type boolean

dLoc

The displacement vector applied by the actuator.

Type list [x, y, z]

useLocalDLoc

A flag specifying if the dLoc is local.

Type boolean

dRot

The angular displacement vector applied by the actuator

Type list [x, y, z]

Note: Since the displacement is applied every frame, you must adjust the displacement based on the frame rate, or you game experience will depend on the player's computer speed.

---

useLocalDRot

A flag specifying if the dRot is local.

Type boolean

linV

The linear velocity applied by the actuator.

Type list [x, y, z]

useLocalLinV

A flag specifying if the linear velocity is local.

Type boolean

Note: This is the target speed for servo controllers.

---

angV

The angular velocity applied by the actuator.

Type list [x, y, z]

useLocalAngV
A flag specifying if the angular velocity is local.

Type boolean

damping
The damping parameter of the servo controller.

Type short

forceLimitX
The min/max force limit along the X axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

forceLimitY
The min/max force limit along the Y axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

forceLimitZ
The min/max force limit along the Z axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

pid
The PID coefficients of the servo controller.

Type list of floats [proportional, integral, derivate]

reference
The object that is used as reference to compute the velocity for the servo controller.

Type `KX_GameObject` or None

class `bge.types.`**KX_ParentActuator**(*SCA_IActuator*)
The parent actuator can set or remove an objects parent object.

object
the object this actuator sets the parent too.

Type `KX_GameObject` or None

mode
The mode of this actuator.

Type integer from 0 to 1.

compound
Whether the object shape should be added to the parent compound shape when parenting.

Effective only if the parent is already a compound shape.

Type boolean

ghost
Whether the object should be made ghost when parenting Effective only if the shape is not added to the parent compound shape.

Type boolean

class `bge.types.`**KX_PhysicsObjectWrapper**(*PyObjectPlus*)
KX_PhysicsObjectWrapper

setActive(*active*)
Set the object to be active.

Parameters **active** (*boolean*) – set to True to be active

setAngularVelocity (*x*, *y*, *z*, *local*)
Set the angular velocity of the object.

Parameters

- **x** (*float*) – angular velocity for the x-axis
- **y** (*float*) – angular velocity for the y-axis
- **z** (*float*) – angular velocity for the z-axis
- **local** (*boolean*) – set to True for local axis

setLinearVelocity (*x*, *y*, *z*, *local*)
Set the linear velocity of the object.

Parameters

- **x** (*float*) – linear velocity for the x-axis
- **y** (*float*) – linear velocity for the y-axis
- **z** (*float*) – linear velocity for the z-axis
- **local** (*boolean*) – set to True for local axis

class bge.types.**KX_PolyProxy** (*SCA_IObject*)
A polygon holds the index of the vertex forming the poylgon.

Note: The polygon attributes are read-only, you need to retrieve the vertex proxy if you want to change the vertex settings.

matname
The name of polygon material, empty if no material.

Type string

material
The material of the polygon.

Type KX_PolygonMaterial or KX_BlenderMaterial

texture
The texture name of the polygon.

Type string

matid
The material index of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v1
vertex index of the first vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v2
vertex index of the second vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v3
vertex index of the third vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v4

Vertex index of the fourth vertex of the polygon, 0 if polygon has only 3 vertex Use this to retrieve vertex proxy from mesh proxy.

Type integer

visible

visible state of the polygon: 1=visible, 0=invisible.

Type integer

collide

collide state of the polygon: 1=receives collision, 0=collision free.

Type integer

getMaterialName()

Returns the polygon material name with MA prefix

Returns material name

Return type string

getMaterial()

Returns The polygon material

Return type `KX_PolygonMaterial` or `KX_BlenderMaterial`

getTextureName()

Returns The texture name

Return type string

getMaterialIndex()

Returns the material bucket index of the polygon. This index and the ones returned by getVertexIndex() are needed to retrieve the vertex proxy from `MeshProxy`.

Returns the material index in the mesh

Return type integer

getNumVertex()

Returns the number of vertex of the polygon.

Returns number of vertex, 3 or 4.

Return type integer

isVisible()

Returns whether the polygon is visible or not

Returns 0=invisible, 1=visible

Return type boolean

isCollider()

Returns whether the polygon is receives collision or not

Returns 0=collision free, 1=receives collision

Return type integer

getVertexIndex(*vertex*)

Returns the mesh vertex index of a polygon vertex This index and the one returned by getMaterialIndex() are needed to retrieve the vertex proxy from `MeshProxy`.

Parameters

- **vertex** – index of the vertex in the polygon: 0->3
- **vertex** – integer

Returns mesh vertex index

Return type integer

getMesh()

Returns a mesh proxy

Returns mesh proxy

Return type MeshProxy

class bge.types.**KX_PolygonMaterial**(*PyObjectPlus*)

This is the interface to materials in the game engine.

Materials define the render state to be applied to mesh objects.

> **Warning:** Some of the methods/variables are CObjects. If you mix these up, you will crash blender.

This example requires PyOpenGL and GLEWPy

```
import GameLogic
import OpenGL
from OpenGL.GL import *
from OpenGL.GLU import *
import glew
from glew import *

glewInit()

vertex_shader = """

void main(void)
{
   gl_Position = ftransform();
}
"""

fragment_shader ="""

void main(void)
{
   gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
}
"""

class MyMaterial:
   def __init__(self):
      self.pass_no = 0
      # Create a shader
      self.m_program = glCreateProgramObjectARB()
      # Compile the vertex shader
      self.shader(GL_VERTEX_SHADER_ARB, (vertex_shader))
      # Compile the fragment shader
      self.shader(GL_FRAGMENT_SHADER_ARB, (fragment_shader))
      # Link the shaders together
```

```
        self.link()

    def PrintInfoLog(self, tag, object):
        """
        PrintInfoLog prints the GLSL compiler log
        """
        print "Tag:    def PrintGLError(self, tag = ""):

    def PrintGLError(self, tag = ""):
        """
        Prints the current GL error status
        """
        if len(tag):
            print tag
        err = glGetError()
        if err != GL_NO_ERROR:
            print "GL Error: %s\\n"%(gluErrorString(err))

    def shader(self, type, shaders):
        """
        shader compiles a GLSL shader and attaches it to the current
        program.

        type should be either GL_VERTEX_SHADER_ARB or GL_FRAGMENT_SHADER_ARB
        shaders should be a sequence of shader source to compile.
        """
        # Create a shader object
        shader_object = glCreateShaderObjectARB(type)

        # Add the source code
        glShaderSourceARB(shader_object, len(shaders), shaders)

        # Compile the shader
        glCompileShaderARB(shader_object)

        # Print the compiler log
        self.PrintInfoLog("vertex shader", shader_object)

        # Check if compiled, and attach if it did
        compiled = glGetObjectParameterivARB(shader_object, GL_OBJECT_COMPILE_STATUS_ARB)
        if compiled:
            glAttachObjectARB(self.m_program, shader_object)

        # Delete the object (glAttachObjectARB makes a copy)
        glDeleteObjectARB(shader_object)

        # print the gl error log
        self.PrintGLError()

    def link(self):
        """
        Links the shaders together.
        """
        # clear error indicator
        glGetError()

        glLinkProgramARB(self.m_program)
```

```
      self.PrintInfoLog("link", self.m_program)

      linked = glGetObjectParameterivARB(self.m_program, GL_OBJECT_LINK_STATUS_ARB)
      if not linked:
         print "Shader failed to link"
         return

      glValidateProgramARB(self.m_program)
      valid = glGetObjectParameterivARB(self.m_program, GL_OBJECT_VALIDATE_STATUS_ARB)
      if not valid:
         print "Shader failed to validate"
         return

   def activate(self, rasty, cachingInfo, mat):
      self.pass_no+=1
      if (self.pass_no == 1):
         glDisable(GL_COLOR_MATERIAL)
         glUseProgramObjectARB(self.m_program)
         return True

      glEnable(GL_COLOR_MATERIAL)
      glUseProgramObjectARB(0)
      self.pass_no = 0
      return False

obj = GameLogic.getCurrentController().owner

mesh = obj.meshes[0]

for mat in mesh.materials:
   mat.setCustomMaterial(MyMaterial())
   print mat.texture
```

texture

Texture name.

Type string (read-only)

gl_texture

OpenGL texture handle (eg for glBindTexture(GL_TEXTURE_2D, gl_texture).

Type integer (read-only)

material

Material name.

Type string (read-only)

tface

Texture face properties.

Type CObject (read-only)

tile

Texture is tiling.

Type boolean

tilexrep

Number of tile repetitions in x direction.

Type integer

tileyrep
Number of tile repetitions in y direction.

Type integer

drawingmode
Drawing mode for the material. - 2 (drawingmode & 4) Textured - 4 (drawingmode & 16) Light - 14 (drawingmode & 16384) 3d Polygon Text.

Type bitfield

transparent
This material is transparent. All meshes with this material will be rendered after non transparent meshes from back to front.

Type boolean

zsort
Transparent polygons in meshes with this material will be sorted back to front before rendering. Non-Transparent polygons will be sorted front to back before rendering.

Type boolean

lightlayer
Light layers this material affects.

Type bitfield.

triangle
Mesh data with this material is triangles. It's probably not safe to change this.

Type boolean

diffuse
The diffuse colour of the material. black = [0.0, 0.0, 0.0] white = [1.0, 1.0, 1.0].

Type list [r, g, b]

specular
The specular colour of the material. black = [0.0, 0.0, 0.0] white = [1.0, 1.0, 1.0].

Type list [r, g, b]

shininess
The shininess (specular exponent) of the material. 0.0 <= shininess <= 128.0.

Type float

specularity
The amount of specular of the material. 0.0 <= specularity <= 1.0.

Type float

updateTexture (*tface*, *rasty*)
Updates a realtime animation.

Parameters

- **tface** (*CObject*) – Texture face (eg mat.tface)
- **rasty** (*CObject*) – Rasterizer

setTexture (*tface*)
Sets texture render state.

Parameters **tface** (*CObject*) – Texture face

```
mat.setTexture(mat.tface)
```

activate (*rasty*, *cachingInfo*)

Sets material parameters for this object for rendering.

Material Parameters set:

1. Texture
2. Backface culling
3. Line drawing
4. Specular Colour
5. Shininess
6. Diffuse Colour
7. Polygon Offset.

Parameters

- **rasty** (*CObject*) – Rasterizer instance.
- **cachingInfo** (*CObject*) – Material cache instance.

setCustomMaterial (*material*)

Sets the material state setup object.

Using this method, you can extend or completely replace the gameengine material to do your own advanced multipass effects.

Use this method to register your material class. Instead of the normal material, your class's activate method will be called just before rendering the mesh. This should setup the texture, material, and any other state you would like. It should return True to render the mesh, or False if you are finished. You should clean up any state Blender does not set before returning False.

Activate Method Definition:

```
def activate(self, rasty, cachingInfo, material):
```

Parameters **material** (*instance*) – The material object.

```
class PyMaterial:
  def __init__(self):
    self.pass_no = -1

  def activate(self, rasty, cachingInfo, material):
    # Activate the material here.
    #
    # The activate method will be called until it returns False.
    # Every time the activate method returns True the mesh will
    # be rendered.
    #
    # rasty is a CObject for passing to material.updateTexture()
    #       and material.activate()
    # cachingInfo is a CObject for passing to material.activate()
    # material is the KX_PolygonMaterial instance this material
    #          was added to
```

```
        # default material properties:
        self.pass_no += 1
        if self.pass_no == 0:
          material.activate(rasty, cachingInfo)
          # Return True to do this pass
          return True

        # clean up and return False to finish.
        self.pass_no = -1
        return False

    # Create a new Python Material and pass it to the renderer.
    mat.setCustomMaterial(PyMaterial())
```

class bge.types.**KX_RadarSensor**(*KX_NearSensor*)

Radar sensor is a near sensor with a conical sensor object.

coneOrigin

The origin of the cone with which to test. The origin is in the middle of the cone. (read-only).

Type list of floats [x, y, z]

coneTarget

The center of the bottom face of the cone with which to test. (read-only).

Type list of floats [x, y, z]

distance

The height of the cone with which to test.

Type float

angle

The angle of the cone (in degrees) with which to test.

Type float from 0 to 360

axis

The axis on which the radar cone is cast.

Type integer from 0 to 5

KX_RADAR_AXIS_POS_X, KX_RADAR_AXIS_POS_Y, KX_RADAR_AXIS_POS_Z, KX_RADAR_AXIS_NEG_X, KX_RADAR_AXIS_NEG_Y, KX_RADAR_AXIS_NEG_Z

getConeHeight()

Returns The height of the cone with which to test.

Return type float

class bge.types.**KX_RaySensor**(*SCA_ISensor*)

A ray sensor detects the first object in a given direction.

propName

The property the ray is looking for.

Type string

range

The distance of the ray.

Type float

useMaterial
Whether or not to look for a material (false = property).

Type boolean

useXRay
Whether or not to use XRay.

Type boolean

hitObject
The game object that was hit by the ray. (read-only).

Type KX_GameObject

hitPosition
The position (in worldcoordinates) where the object was hit by the ray. (read-only).

Type list [x, y, z]

hitNormal
The normal (in worldcoordinates) of the object at the location where the object was hit by the ray. (read-only).

Type list [x, y, z]

rayDirection
The direction from the ray (in worldcoordinates). (read-only).

Type list [x, y, z]

axis
The axis the ray is pointing on.

Type integer from 0 to 5

- KX_RAY_AXIS_POS_X
- KX_RAY_AXIS_POS_Y
- KX_RAY_AXIS_POS_Z
- KX_RAY_AXIS_NEG_X
- KX_RAY_AXIS_NEG_Y
- KX_RAY_AXIS_NEG_Z

class bge.types.**KX_SCA_AddObjectActuator**(*SCA_IActuator*)
Edit Object Actuator (in Add Object Mode)

Warning: An Add Object actuator will be ignored if at game start, the linked object doesn't exist (or is empty) or the linked object is in an active layer.

```
Error: GameObject 'Name' has a AddObjectActuator 'ActuatorName' without object (in 'nonactive'
```

object
the object this actuator adds.

Type KX_GameObject or None

objectLastCreated
the last added object from this actuator (read-only).

Type KX_GameObject or None

time
the lifetime of added objects, in frames. Set to 0 to disable automatic deletion.

Type integer

linearVelocity
the initial linear velocity of added objects.

Type list [vx, vy, vz]

angularVelocity
the initial angular velocity of added objects.

Type list [vx, vy, vz]

instantAddObject()
adds the object without needing to calling SCA_PythonController.activate()

Note: Use objectLastCreated to get the newly created object.

class bge.types.**KX_SCA_DynamicActuator**(*SCA_IActuator*)
Dynamic Actuator.

mode

Type integer

the type of operation of the actuator, 0-4

- KX_DYN_RESTORE_DYNAMICS(0)
- KX_DYN_DISABLE_DYNAMICS(1)
- KX_DYN_ENABLE_RIGID_BODY(2)
- KX_DYN_DISABLE_RIGID_BODY(3)
- KX_DYN_SET_MASS(4)

mass
the mass value for the KX_DYN_SET_MASS operation.

Type float

class bge.types.**KX_SCA_EndObjectActuator**(*SCA_IActuator*)
Edit Object Actuator (in End Object mode)

This actuator has no python methods.

class bge.types.**KX_SCA_ReplaceMeshActuator**(*SCA_IActuator*)
Edit Object actuator, in Replace Mesh mode.

Warning: Replace mesh actuators will be ignored if at game start, the named mesh doesn't exist. This will generate a warning in the console

```
Error: GameObject 'Name' ReplaceMeshActuator 'ActuatorName' without object
```

```
# Level-of-detail
# Switch a game object's mesh based on its depth in the camera view.
# +----------+     +-----------+     +-------------------------------------+
# | Always   +-----+ Python    +-----+ Edit Object (Replace Mesh) LOD.Mesh |
```

```
# +----------+     +-----------+     +-------------------------------------+
import GameLogic

# List detail meshes here
# Mesh (name, near, far)
# Meshes overlap so that they don't 'pop' when on the edge of the distance.
meshes = ((".Hi", 0.0, -20.0),
      (".Med", -15.0, -50.0),
      (".Lo", -40.0, -100.0)
    )

co = GameLogic.getCurrentController()
obj = co.owner
act = co.actuators["LOD." + obj.name]
cam = GameLogic.getCurrentScene().active_camera

def Depth(pos, plane):
  return pos[0]*plane[0] + pos[1]*plane[1] + pos[2]*plane[2] + plane[3]

# Depth is negative and decreasing further from the camera
depth = Depth(obj.position, cam.world_to_camera[2])

newmesh = None
curmesh = None
# Find the lowest detail mesh for depth
for mesh in meshes:
  if depth < mesh[1] and depth > mesh[2]:
    newmesh = mesh
  if "ME" + obj.name + mesh[0] == act.getMesh():
      curmesh = mesh

if newmesh != None and "ME" + obj.name + newmesh[0] != act.getMesh():
  # The mesh is a different mesh - switch it.
  # Check the current mesh is not a better fit.
  if curmesh == None or curmesh[1] < depth or curmesh[2] > depth:
    act.mesh = obj.getName() + newmesh[0]
    GameLogic.addActiveActuator(act, True)
```

mesh

`MeshProxy` or the name of the mesh that will replace the current one.

Set to None to disable actuator.

Type `MeshProxy` or None if no mesh is set

useDisplayMesh

when true the displayed mesh is replaced.

Type boolean

usePhysicsMesh

when true the physics mesh is replaced.

Type boolean

instantReplaceMesh()

Immediately replace mesh without delay.

class `bge.types.`**KX_Scene**(*PyObjectPlus*)

An active scene that gives access to objects, cameras, lights and scene attributes.

The activity culling stuff is supposed to disable logic bricks when their owner gets too far from the active camera. It was taken from some code lurking at the back of KX_Scene - who knows what it does!

```
import GameLogic

# get the scene
scene = GameLogic.getCurrentScene()

# print all the objects in the scene
for obj in scene.objects:
   print obj.name

# get an object named 'Cube'
obj = scene.objects["Cube"]

# get the first object in the scene.
obj = scene.objects[0]

# Get the depth of an object in the camera view.
import GameLogic

obj = GameLogic.getCurrentController().owner
cam = GameLogic.getCurrentScene().active_camera

# Depth is negative and decreasing further from the camera
depth = obj.position[0]*cam.world_to_camera[2][0] + obj.position[1]*cam.world_to_camera[2][1] +
```

@bug: All attributes are read only at the moment.

name

The scene's name, (read-only).

Type string

objects

A list of objects in the scene, (read-only).

Type `CListValue` of `KX_GameObject`

objectsInactive

A list of objects on background layers (used for the addObject actuator), (read-only).

Type `CListValue` of `KX_GameObject`

lights

A list of lights in the scene, (read-only).

Type `CListValue` of `KX_LightObject`

cameras

A list of cameras in the scene, (read-only).

Type `CListValue` of `KX_Camera`

active_camera

The current active camera.

Type `KX_Camera`

Note: This can be set directly from python to avoid using the `KX_SceneActuator`.

---

suspended
True if the scene is suspended, (read-only).

Type boolean

activity_culling
True if the scene is activity culling.

Type boolean

activity_culling_radius
The distance outside which to do activity culling. Measured in manhattan distance.

Type float

dbvt_culling
True when Dynamic Bounding box Volume Tree is set (read-only).

Type boolean

pre_draw
A list of callables to be run before the render step.

Type list

post_draw
A list of callables to be run after the render step.

Type list

addObject(*object*, *other*, *time=0*)
Adds an object to the scene like the Add Object Actuator would.

Parameters

- **object** (`KX_GameObject` or string) – The object to add
- **other** (`KX_GameObject` or string) – The object's center to use when adding the object
- **time** (*integer*) – The lifetime of the added object, in frames. A time of 0 means the object will last forever.

Returns The newly added object.

Return type `KX_GameObject`

end()
Removes the scene from the game.

restart()
Restarts the scene.

replace(*scene*)
Replaces this scene with another one.

Parameters **scene** (*string*) – The name of the scene to replace this scene with.

suspend()
Suspends this scene.

resume()
Resume this scene.

get(*key*, *default=None*)
Return the value matching key, or the default value if its not found. :return: The key value or a default.

class `bge.types.KX_SceneActuator`(*SCA_IActuator*)

Scene Actuator logic brick.

> **Warning:** Scene actuators that use a scene name will be ignored if at game start, the named scene doesn't exist or is empty
> This will generate a warning in the console:
>
> ```
> Error: GameObject 'Name' has a SceneActuator 'ActuatorName' (SetScene) without scene
> ```

scene

the name of the scene to change to/overlay/underlay/remove/suspend/resume.

Type string

camera

the camera to change to.

Type `KX_Camera` on read, string or `KX_Camera` on write

Note: When setting the attribute, you can use either a `KX_Camera` or the name of the camera.

---

useRestart

Set flag to True to restart the sene.

Type boolean

mode

The mode of the actuator.

Type integer from 0 to 5.

class `bge.types.KX_SoundActuator`(*SCA_IActuator*)

Sound Actuator.

The `startSound`, `pauseSound` and `stopSound` do not requirethe actuator to be activated - they act instantly provided that the actuator has been activated once at least.

fileName

The filename of the sound this actuator plays.

Type string

volume

The volume (gain) of the sound.

Type float

pitch

The pitch of the sound.

Type float

rollOffFactor

The roll off factor. Rolloff defines the rate of attenuation as the sound gets further away.

Type float

looping

The loop mode of the actuator.

Type integer

position
The position of the sound as a list: [x, y, z].

Type float array

velocity
The velocity of the emitter as a list: [x, y, z]. The relative velocity to the observer determines the pitch. List of 3 floats: [x, y, z].

Type float array

orientation
The orientation of the sound. When setting the orientation you can also use quaternion [float, float, float, float] or euler angles [float, float, float].

Type 3x3 matrix [[float]]

mode
The operation mode of the actuator. Can be one of *these constants*

Type integer

class `bge.types.`**`KX_StateActuator`**(*SCA_IActuator*)
State actuator changes the state mask of parent object.

operation
Type of bit operation to be applied on object state mask.

You can use one of *these constants*

Type integer

mask
Value that defines the bits that will be modified by the operation.

The bits that are 1 in the mask will be updated in the object state.

The bits that are 0 are will be left unmodified expect for the Copy operation which copies the mask to the object state.

Type integer

class `bge.types.`**`KX_TrackToActuator`**(*SCA_IActuator*)
Edit Object actuator in Track To mode.

> **Warning:** Track To Actuators will be ignored if at game start, the object to track to is invalid.
> This will generate a warning in the console:
>
> ```
> GameObject 'Name' no object in EditObjectActuator 'ActuatorName'
> ```

object
the object this actuator tracks.

Type `KX_GameObject` or None

time
the time in frames with which to delay the tracking motion.

Type integer

use3D
the tracking motion to use 3D.

Type boolean

class bge.types.**KX_VehicleWrapper**(*PyObjectPlus*)

KX_VehicleWrapper

TODO - description

addWheel(*wheel*, *attachPos*, *attachDir*, *axleDir*, *suspensionRestLength*, *wheelRadius*, *hasSteering*)

Add a wheel to the vehicle

Parameters

- **wheel** (KX_GameObject or a KX_GameObject name) – The object to use as a wheel.
- **attachPos** (*vector of 3 floats*) – The position that this wheel will attach to.
- **attachDir** (*vector of 3 floats*) – The direction this wheel points.
- **axleDir** (*vector of 3 floats*) – The direction of this wheels axle.
- **suspensionRestLength** (*float*) – TODO - Description
- **wheelRadius** (*float*) – The size of the wheel.

applyBraking(*force*, *wheelIndex*)

Apply a braking force to the specified wheel

Parameters

- **force** (*float*) – the brake force
- **wheelIndex** (*integer*) – index of the wheel where the force needs to be applied

applyEngineForce(*force*, *wheelIndex*)

Apply an engine force to the specified wheel

Parameters

- **force** (*float*) – the engine force
- **wheelIndex** (*integer*) – index of the wheel where the force needs to be applied

getConstraintId()

Get the constraint ID

Returns the constraint id

Return type integer

getConstraintType()

Returns the constraint type.

Returns constraint type

Return type integer

getNumWheels()

Returns the number of wheels.

Returns the number of wheels for this vehicle

Return type integer

getWheelOrientationQuaternion(*wheelIndex*)

Returns the wheel orientation as a quaternion.

Parameters **wheelIndex** (*integer*) – the wheel index

Returns TODO Description

Return type TODO - type should be quat as per method name but from the code it looks like a matrix

getWheelPosition (*wheelIndex*)
Returns the position of the specified wheel

Parameters **wheelIndex** (*integer*) – the wheel index

Returns position vector

Return type list[x, y, z]

getWheelRotation (*wheelIndex*)
Returns the rotation of the specified wheel

Parameters **wheelIndex** (*integer*) – the wheel index

Returns the wheel rotation

Return type float

setRollInfluence (*rollInfluece*, *wheelIndex*)
Set the specified wheel's roll influence. The higher the roll influence the more the vehicle will tend to roll over in corners.

Parameters

- **rollInfluece** (*float*) – the wheel roll influence
- **wheelIndex** (*integer*) – the wheel index

setSteeringValue (*steering*, *wheelIndex*)
Set the specified wheel's steering

Parameters

- **steering** (*float*) – the wheel steering
- **wheelIndex** (*integer*) – the wheel index

setSuspensionCompression (*compression*, *wheelIndex*)
Set the specified wheel's compression

Parameters

- **compression** (*float*) – the wheel compression
- **wheelIndex** (*integer*) – the wheel index

setSuspensionDamping (*damping*, *wheelIndex*)
Set the specified wheel's damping

Parameters

- **damping** (*float*) – the wheel damping
- **wheelIndex** (*integer*) – the wheel index

setSuspensionStiffness (*stiffness*, *wheelIndex*)
Set the specified wheel's stiffness

Parameters

- **stiffness** (*float*) – the wheel stiffness
- **wheelIndex** (*integer*) – the wheel index

setTyreFriction (*friction*, *wheelIndex*)
Set the specified wheel's tyre friction

Parameters

- **friction** (*float*) – the tyre friction
- **wheelIndex** (*integer*) – the wheel index

class bge.types.**KX_VertexProxy** (*SCA_IObject*)
A vertex holds position, UV, colour and normal information.

Note: The physics simulation is NOT currently updated - physics will not respond to changes in the vertex position.

XYZ
The position of the vertex.

Type list [x, y, z]

UV
The texture coordinates of the vertex.

Type list [u, v]

normal
The normal of the vertex.

Type list [nx, ny, nz]

colour
The colour of the vertex.

Type list [r, g, b, a]

Black = [0.0, 0.0, 0.0, 1.0], White = [1.0, 1.0, 1.0, 1.0]

color
Synonym for colour.

x
The x coordinate of the vertex.

Type float

y
The y coordinate of the vertex.

Type float

z
The z coordinate of the vertex.

Type float

u
The u texture coordinate of the vertex.

Type float

v
The v texture coordinate of the vertex.

Type float

u2
The second u texture coordinate of the vertex.

Type float

v2

The second v texture coordinate of the vertex.

Type float

r

The red component of the vertex colour. 0.0 <= r <= 1.0.

Type float

g

The green component of the vertex colour. 0.0 <= g <= 1.0.

Type float

b

The blue component of the vertex colour. 0.0 <= b <= 1.0.

Type float

a

The alpha component of the vertex colour. 0.0 <= a <= 1.0.

Type float

getXYZ()

Gets the position of this vertex.

Returns this vertexes position in local coordinates.

Return type list [x, y, z]

setXYZ(*pos*)

Sets the position of this vertex.

Type list [x, y, z]

Parameters **pos** – the new position for this vertex in local coordinates.

getUV()

Gets the UV (texture) coordinates of this vertex.

Returns this vertexes UV (texture) coordinates.

Return type list [u, v]

setUV(*uv*)

Sets the UV (texture) coordinates of this vertex.

Type list [u, v]

getUV2()

Gets the 2nd UV (texture) coordinates of this vertex.

Returns this vertexes UV (texture) coordinates.

Return type list [u, v]

setUV2(*uv*, *unit*)

Sets the 2nd UV (texture) coordinates of this vertex.

Type list [u, v]

Parameters

- **unit** – optional argument, FLAT==1, SECOND_UV==2, defaults to SECOND_UV

- **unit** – integer

getRGBA()

Gets the colour of this vertex.

The colour is represented as four bytes packed into an integer value. The colour is packed as RGBA.

Since Python offers no way to get each byte without shifting, you must use the struct module to access colour in an machine independent way.

Because of this, it is suggested you use the r, g, b and a attributes or the colour attribute instead.

```
import struct;
col = struct.unpack('4B', struct.pack('I', v.getRGBA()))
# col = (r, g, b, a)
# black = (  0, 0, 0, 255)
# white = (255, 255, 255, 255)
```

Returns packed colour. 4 byte integer with one byte per colour channel in RGBA format.

Return type integer

setRGBA(*col*)

Sets the colour of this vertex.

See getRGBA() for the format of col, and its relevant problems. Use the r, g, b and a attributes or the colour attribute instead.

setRGBA() also accepts a four component list as argument col. The list represents the colour as [r, g, b, a] with black = [0.0, 0.0, 0.0, 1.0] and white = [1.0, 1.0, 1.0, 1.0]

```
v.setRGBA(0xff0000ff) # Red
v.setRGBA(0xff00ff00) # Green on little endian, transparent purple on big endian
v.setRGBA([1.0, 0.0, 0.0, 1.0]) # Red
v.setRGBA([0.0, 1.0, 0.0, 1.0]) # Green on all platforms.
```

Parameters **col** (*integer or list [r, g, b, a]*) – the new colour of this vertex in packed RGBA format.

getNormal()

Gets the normal vector of this vertex.

Returns normalised normal vector.

Return type list [nx, ny, nz]

setNormal(*normal*)

Sets the normal vector of this vertex.

Type sequence of floats [r, g, b]

Parameters **normal** – the new normal of this vertex.

class bge.types.**KX_VisibilityActuator**(*SCA_IActuator*)

Visibility Actuator.

visibility

whether the actuator makes its parent object visible or invisible.

Type boolean

useOcclusion

whether the actuator makes its parent object an occluder or not.

Type boolean

useRecursion
whether the visibility/occlusion should be propagated to all children of the object.

Type boolean

class bge.types.**SCA_2DFilterActuator**(*SCA_IActuator*)
Create, enable and disable 2D filters

The following properties don't have an immediate effect. You must active the actuator to get the result. The actuator is not persistent: it automatically stops itself after setting up the filter but the filter remains active. To stop a filter you must activate the actuator with 'type' set to RAS_2DFILTER_DISABLED or RAS_2DFILTER_NOFILTER.

shaderText
shader source code for custom shader.

Type string

disableMotionBlur
action on motion blur: 0=enable, 1=disable.

Type integer

mode
Type of 2D filter, use one of *these constants*

Type integer

passNumber
order number of filter in the stack of 2D filters. Filters are executed in increasing order of passNb.

Only be one filter can be defined per passNb.

Type integer (0-100)

value
argument for motion blur filter.

Type float (0.0-100.0)

class bge.types.**SCA_ANDController**(*SCA_IController*)
An AND controller activates only when all linked sensors are activated.

There are no special python methods for this controller.

class bge.types.**SCA_ActuatorSensor**(*SCA_ISensor*)
Actuator sensor detect change in actuator state of the parent object. It generates a positive pulse if the corresponding actuator is activated and a negative pulse if the actuator is deactivated.

actuator
the name of the actuator that the sensor is monitoring.

Type string

class bge.types.**SCA_AlwaysSensor**(*SCA_ISensor*)
This sensor is always activated.

class bge.types.**SCA_DelaySensor**(*SCA_ISensor*)
The Delay sensor generates positive and negative triggers at precise time, expressed in number of frames. The delay parameter defines the length of the initial OFF period. A positive trigger is generated at the end of this period.

The duration parameter defines the length of the ON period following the OFF period. There is a negative trigger at the end of the ON period. If duration is 0, the sensor stays ON and there is no negative trigger.

The sensor runs the OFF-ON cycle once unless the repeat option is set: the OFF-ON cycle repeats indefinately (or the OFF cycle if duration is 0).

Use `SCA_ISensor.reset` at any time to restart sensor.

delay

length of the initial OFF period as number of frame, 0 for immediate trigger.

Type integer.

duration

length of the ON period in number of frame after the initial OFF period.

If duration is greater than 0, a negative trigger is sent at the end of the ON pulse.

Type integer

repeat

1 if the OFF-ON cycle should be repeated indefinately, 0 if it should run once.

Type integer

class `bge.types.`**`SCA_JoystickSensor`**(*SCA_ISensor*)

This sensor detects player joystick events.

axisValues

The state of the joysticks axis as a list of values `numAxis` long. (read-only).

Type list of ints.

Each spesifying the value of an axis between -32767 and 32767 depending on how far the axis is pushed, 0 for nothing. The first 2 values are used by most joysticks and gamepads for directional control. 3rd and 4th values are only on some joysticks and can be used for arbitary controls.

- left:[-32767, 0, ...]
- right:[32767, 0, ...]
- up:[0, -32767, ...]
- down:[0, 32767, ...]

axisSingle

like `axisValues` but returns a single axis value that is set by the sensor. (read-only).

Type integer

Note: Only use this for "Single Axis" type sensors otherwise it will raise an error.

---

hatValues

The state of the joysticks hats as a list of values `numHats` long. (read-only).

Type list of ints

Each spesifying the direction of the hat from 1 to 12, 0 when inactive.

Hat directions are as follows...

- 0:None
- 1:Up
- 2:Right

- 4:Down
- 8:Left
- 3:Up - Right
- 6:Down - Right
- 12:Down - Left
- 9:Up - Left

hatSingle

Like `hatValues` but returns a single hat direction value that is set by the sensor. (read-only).

Type integer

numAxis

The number of axes for the joystick at this index. (read-only).

Type integer

numButtons

The number of buttons for the joystick at this index. (read-only).

Type integer

numHats

The number of hats for the joystick at this index. (read-only).

Type integer

connected

True if a joystick is connected at this joysticks index. (read-only).

Type boolean

index

The joystick index to use (from 0 to 7). The first joystick is always 0.

Type integer

threshold

Axis threshold. Joystick axis motion below this threshold wont trigger an event. Use values between (0 and 32767), lower values are more sensitive.

Type integer

button

The button index the sensor reacts to (first button = 0). When the "All Events" toggle is set, this option has no effect.

Type integer

axis

The axis this sensor reacts to, as a list of two values [axisIndex, axisDirection]

- axisIndex: the axis index to use when detecting axis movement, 1=primary directional control, 2=secondary directional control.
- axisDirection: 0=right, 1=up, 2=left, 3=down.

Type [integer, integer]

hat

The hat the sensor reacts to, as a list of two values: [hatIndex, hatDirection]

- hatIndex: the hat index to use when detecting hat movement, 1=primary hat, 2=secondary hat (4 max).
- hatDirection: 1-12.

Type [integer, integer]

getButtonActiveList()

Returns A list containing the indicies of the currently pressed buttons.

Return type list

getButtonStatus(*buttonIndex*)

Parameters **buttonIndex** (*integer*) – the button index, 0=first button

Returns The current pressed state of the specified button.

Return type boolean

class bge.types.**SCA_KeyboardSensor**(*SCA_ISensor*)

A keyboard sensor detects player key presses.

See module bge.keys for keycode values.

key

The key code this sensor is looking for.

Type keycode from bge.keys module

hold1

The key code for the first modifier this sensor is looking for.

Type keycode from bge.keys module

hold2

The key code for the second modifier this sensor is looking for.

Type keycode from bge.keys module

toggleProperty

The name of the property that indicates whether or not to log keystrokes as a string.

Type string

targetProperty

The name of the property that receives keystrokes in case in case a string is logged.

Type string

useAllKeys

Flag to determine whether or not to accept all keys.

Type boolean

events

a list of pressed keys that have either been pressed, or just released, or are active this frame. (read-only).

Type list [[*keycode*, *status*], ...]

getKeyStatus(*keycode*)

Get the status of a key.

Parameters **keycode** (*integer*) – The code that represents the key you want to get the state of, use one of *these constants*

Returns The state of the given key, can be one of *these constants*

Return type int

class bge.types.**SCA_NANDController**(*SCA_IController*)
An NAND controller activates when all linked sensors are not active.

There are no special python methods for this controller.

class bge.types.**SCA_NORController**(*SCA_IController*)
An NOR controller activates only when all linked sensors are de-activated.

There are no special python methods for this controller.

class bge.types.**SCA_ORController**(*SCA_IController*)
An OR controller activates when any connected sensor activates.

There are no special python methods for this controller.

class bge.types.**SCA_PropertyActuator**(*SCA_IActuator*)
Property Actuator

propName
the property on which to operate.

Type string

value
the value with which the actuator operates.

Type string

mode
TODO - add constants to game logic dict!.

Type integer

class bge.types.**SCA_PropertySensor**(*SCA_ISensor*)
Activates when the game object property matches.

mode
Type of check on the property. Can be one of *these constants*

Type integer.

propName
the property the sensor operates.

Type string

value
the value with which the sensor compares to the value of the property.

Type string

min
the minimum value of the range used to evaluate the property when in interval mode.

Type string

max
the maximum value of the range used to evaluate the property when in interval mode.

Type string

class bge.types.**SCA_PythonController**(*SCA_IController*)
A Python controller uses a Python script to activate it's actuators, based on it's sensors.

script

The value of this variable depends on the execution methid.

- When 'Script' execution mode is set this value contains the entire python script as a single string (not the script name as you might expect) which can be modified to run different scripts.
- When 'Module' execution mode is set this value will contain a single line string - module name and function "module.func" or "package.modile.func" where the module names are python textblocks or external scripts.

Type string

Note: Once this is set the script name given for warnings will remain unchanged.

---

mode

the execution mode for this controller (read-only).

- Script: 0, Execite the `script` as a python code.
- Module: 1, Execite the `script` as a module and function.

Type integer

activate(*actuator*)

Activates an actuator attached to this controller.

Parameters **actuator** (*actuator or the actuator name as a string*) – The actuator to operate on.

deactivate(*actuator*)

Deactivates an actuator attached to this controller.

Parameters **actuator** (*actuator or the actuator name as a string*) – The actuator to operate on.

class bge.types.**SCA_RandomActuator**(*SCA_IActuator*)

Random Actuator

seed

Seed of the random number generator.

Type integer.

Equal seeds produce equal series. If the seed is 0, the generator will produce the same value on every call.

para1

the first parameter of the active distribution.

Type float, read-only.

Refer to the documentation of the generator types for the meaning of this value.

para2

the second parameter of the active distribution.

Type float, read-only

Refer to the documentation of the generator types for the meaning of this value.

distribution

Distribution type. (read-only). Can be one of *these constants*

Type integer

propName
the name of the property to set with the random value.

Type string

If the generator and property types do not match, the assignment is ignored.

setBoolConst(*value*)
Sets this generator to produce a constant boolean value.

Parameters **value** (*boolean*) – The value to return.

setBoolUniform()
Sets this generator to produce a uniform boolean distribution.

The generator will generate True or False with 50% chance.

setBoolBernouilli(*value*)
Sets this generator to produce a Bernouilli distribution.

Parameters **value** (*float*) – Specifies the proportion of False values to produce.

- 0.0: Always generate True
- 1.0: Always generate False

setIntConst(*value*)
Sets this generator to always produce the given value.

Parameters **value** (*integer*) – the value this generator produces.

setIntUniform(*lower_bound*, *upper_bound*)
Sets this generator to produce a random value between the given lower and upper bounds (inclusive).

setIntPoisson(*value*)
Generate a Poisson-distributed number.

This performs a series of Bernouilli tests with parameter value. It returns the number of tries needed to achieve succes.

setFloatConst(*value*)
Always generate the given value.

setFloatUniform(*lower_bound*, *upper_bound*)
Generates a random float between lower_bound and upper_bound with a uniform distribution.

setFloatNormal(*mean*, *standard_deviation*)
Generates a random float from the given normal distribution.

Parameters

- **mean** (*float*) – The mean (average) value of the generated numbers
- **standard_deviation** (*float*) – The standard deviation of the generated numbers.

setFloatNegativeExponential(*half_life*)
Generate negative-exponentially distributed numbers.

The half-life 'time' is characterized by half_life.

class bge.types.**SCA_RandomSensor**(*SCA_ISensor*)

This sensor activates randomly.

lastDraw

The seed of the random number generator.

Type integer

seed

The seed of the random number generator.

Type integer

setSeed(*seed*)

Sets the seed of the random number generator.

If the seed is 0, the generator will produce the same value on every call.

getSeed()

Returns The initial seed of the generator. Equal seeds produce equal random series.

Return type integer

getLastDraw()

Returns The last random number generated.

Return type integer

class bge.types.**SCA_XNORController**(*SCA_IController*)

An XNOR controller activates when all linked sensors are the same (activated or inative).

There are no special python methods for this controller.

class bge.types.**SCA_XORController**(*SCA_IController*)

An XOR controller activates when there is the input is mixed, but not when all are on or off.

There are no special python methods for this controller.

class bge.types.**KX_Camera**(*KX_GameObject*)

A Camera object.

INSIDE

See sphereInsideFrustum and boxInsideFrustum

INTERSECT

See sphereInsideFrustum and boxInsideFrustum

OUTSIDE

See sphereInsideFrustum and boxInsideFrustum

lens

The camera's lens value.

Type float

ortho_scale

The camera's view scale when in orthographic mode.

Type float

near
The camera's near clip distance.

Type float

far
The camera's far clip distance.

Type float

perspective
True if this camera has a perspective transform, False for an orthographic projection.

Type boolean

frustum_culling
True if this camera is frustum culling.

Type boolean

projection_matrix
This camera's 4x4 projection matrix.

Type 4x4 Matrix [[float]]

modelview_matrix
This camera's 4x4 model view matrix. (read-only).

Type 4x4 Matrix [[float]]

Note: This matrix is regenerated every frame from the camera's position and orientation.

---

camera_to_world
This camera's camera to world transform. (read-only).

Type 4x4 Matrix [[float]]

Note: This matrix is regenerated every frame from the camera's position and orientation.

---

world_to_camera
This camera's world to camera transform. (read-only).

Type 4x4 Matrix [[float]]

Note: Regenerated every frame from the camera's position and orientation.

Note: This is camera_to_world inverted.

---

useViewport
True when the camera is used as a viewport, set True to enable a viewport for this camera.

Type boolean

sphereInsideFrustum(*centre*, *radius*)
Tests the given sphere against the view frustum.

Parameters

- **centre** (*list [x, y, z]*) – The centre of the sphere (in world coordinates.)

- **radius** (*float*) – the radius of the sphere

Returns INSIDE, OUTSIDE or INTERSECT

Return type integer

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# A sphere of radius 4.0 located at [x, y, z] = [1.0, 1.0, 1.0]
if (cam.sphereInsideFrustum([1.0, 1.0, 1.0], 4) != cam.OUTSIDE):
    # Sphere is inside frustum !
    # Do something useful !
else:
    # Sphere is outside frustum
```

boxInsideFrustum(*box*)

Tests the given box against the view frustum.

Parameters **box** (*list of lists*) – Eight (8) corner points of the box (in world coordinates.)

Returns INSIDE, OUTSIDE or INTERSECT

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# Box to test...
box = []
box.append([-1.0, -1.0, -1.0])
box.append([-1.0, -1.0,  1.0])
box.append([-1.0,  1.0, -1.0])
box.append([-1.0,  1.0,  1.0])
box.append([ 1.0, -1.0, -1.0])
box.append([ 1.0, -1.0,  1.0])
box.append([ 1.0,  1.0, -1.0])
box.append([ 1.0,  1.0,  1.0])

if (cam.boxInsideFrustum(box) != cam.OUTSIDE):
  # Box is inside/intersects frustum !
  # Do something useful !
else:
  # Box is outside the frustum !
```

pointInsideFrustum(*point*)

Tests the given point against the view frustum.

Parameters **point** (*3D Vector*) – The point to test (in world coordinates.)

Returns True if the given point is inside this camera's viewing frustum.

Return type boolean

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# Test point [0.0, 0.0, 0.0]
if (cam.pointInsideFrustum([0.0, 0.0, 0.0])):
  # Point is inside frustum !
  # Do something useful !
else:
  # Box is outside the frustum !
```

getCameraToWorld()

Returns the camera-to-world transform.

Returns the camera-to-world transform matrix.

Return type matrix (4x4 list)

getWorldToCamera()

Returns the world-to-camera transform.

This returns the inverse matrix of getCameraToWorld().

Returns the world-to-camera transform matrix.

Return type matrix (4x4 list)

setOnTop()

Set this cameras viewport ontop of all other viewport.

setViewport(*left*, *bottom*, *right*, *top*)

Sets the region of this viewport on the screen in pixels.

Use `bge.render.getWindowHeight` and `bge.render.getWindowWidth` to calculate values relative to the entire display.

Parameters

- **left** (*integer*) – left pixel coordinate of this viewport
- **bottom** (*integer*) – bottom pixel coordinate of this viewport
- **right** (*integer*) – right pixel coordinate of this viewport
- **top** (*integer*) – top pixel coordinate of this viewport

getScreenPosition(*object*)

Gets the position of an object projected on screen space.

```
# For an object in the middle of the screen, coord = [0.5, 0.5]
coord = camera.getScreenPosition(object)
```

Parameters **object** (`KX_GameObject` or 3D Vector) – object name or list [x, y, z]

Returns the object's position in screen coordinates.

Return type list [x, y]

getScreenVect (*x*, *y*)

Gets the vector from the camera position in the screen coordinate direction.

Parameters

- **x** (*float*) – X Axis
- **y** (*float*) – Y Axis

Return type 3D Vector

Returns The vector from screen coordinate.

```
# Gets the vector of the camera front direction:
m_vect = camera.getScreenVect(0.5, 0.5)
```

getScreenRay (*x*, *y*, *dist=inf*, *property=None*)

Look towards a screen coordinate (x, y) and find first object hit within dist that matches prop. The ray is similar to KX_GameObject->rayCastTo.

Parameters

- **x** (*float*) – X Axis
- **y** (*float*) – Y Axis
- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to other
- **property** (*string*) – property name that object must have; can be omitted => detect any object

Return type KX_GameObject

Returns the first object hit or None if no object or object does not match prop

```
# Gets an object with a property "wall" in front of the camera within a distance of 100:
target = camera.getScreenRay(0.5, 0.5, 100, "wall")
```

class bge.types.**BL_ArmatureObject** (*KX_GameObject*)

An armature object.

constraints

The list of armature constraint defined on this armature. Elements of the list can be accessed by index or string. The key format for string access is '<bone_name>:<constraint_name>'.

Type list of BL_ArmatureConstraint

channels

The list of armature channels. Elements of the list can be accessed by index or name the bone.

Type list of BL_ArmatureChannel

update ()

Ensures that the armature will be updated on next graphic frame.

This action is unecessary if a KX_ArmatureActuator with mode run is active or if an action is playing. Use this function in other cases. It must be called on each frame to ensure that the armature is updated continously.

class bge.types.**BL_ArmatureActuator** (*SCA_IActuator*)

Armature Actuators change constraint condition on armatures. Constants related to type

KX_ACT_ARMATURE_RUN
Just make sure the armature will be updated on the next graphic frame. This is the only persistent mode of the actuator: it executes automatically once per frame until stopped by a controller

Value 0

KX_ACT_ARMATURE_ENABLE
Enable the constraint.

Value 1

KX_ACT_ARMATURE_DISABLE
Disable the constraint (runtime constraint values are not updated).

Value 2

KX_ACT_ARMATURE_SETTARGET
Change target and subtarget of constraint.

Value 3

KX_ACT_ARMATURE_SETWEIGHT
Change weight of (only for IK constraint).

Value 4

type
The type of action that the actuator executes when it is active.

Can be one of *these constants*

Type integer

constraint
The constraint object this actuator is controlling.

Type `BL_ArmatureConstraint`

target
The object that this actuator will set as primary target to the constraint it controls.

Type `KX_GameObject`

subtarget
The object that this actuator will set as secondary target to the constraint it controls.

Type `KX_GameObject`.

Note: Currently, the only secondary target is the pole target for IK constraint.

---

weight
The weight this actuator will set on the constraint it controls.

Type float.

Note: Currently only the IK constraint has a weight. It must be a value between 0 and 1.

Note: A weight of 0 disables a constraint while still updating constraint runtime values (see `BL_ArmatureConstraint`)

---

class bge.types.**KX_ArmatureSensor**(*SCA_ISensor*)

Armature sensor detect conditions on armatures. Constants related to type

KX_ARMSENSOR_STATE_CHANGED

Detect that the constraint is changing state (active/inactive)

Value 0

KX_ARMSENSOR_LIN_ERROR_BELOW

Detect that the constraint linear error is above a threshold

Value 1

KX_ARMSENSOR_LIN_ERROR_ABOVE

Detect that the constraint linear error is below a threshold

Value 2

KX_ARMSENSOR_ROT_ERROR_BELOW

Detect that the constraint rotation error is above a threshold

Value 3

KX_ARMSENSOR_ROT_ERROR_ABOVE

Detect that the constraint rotation error is below a threshold

Value 4

type

The type of measurement that the sensor make when it is active.

Can be one of *these constants*

Type integer.

constraint

The constraint object this sensor is watching.

Type BL_ArmatureConstraint

value

The threshold used in the comparison with the constraint error The linear error is only updated on CopyPose/Distance IK constraint with iTaSC solver The rotation error is only updated on CopyPose+rotation IK constraint with iTaSC solver The linear error on CopyPose is always >= 0: it is the norm of the distance between the target and the bone The rotation error on CopyPose is always >= 0: it is the norm of the equivalent rotation vector between the bone and the target orientations The linear error on Distance can be positive if the distance between the bone and the target is greater than the desired distance, and negative if the distance is smaller.

Type float

class bge.types.**BL_ArmatureConstraint**(*PyObjectPlus*)

Proxy to Armature Constraint. Allows to change constraint on the fly. Obtained through BL_ArmatureObject.constraints.

Note: Not all armature constraints are supported in the GE.

Constants related to type

CONSTRAINT_TYPE_TRACKTO

CONSTRAINT_TYPE_KINEMATIC

CONSTRAINT_TYPE_ROTLIKE

CONSTRAINT_TYPE_LOCLIKE

CONSTRAINT_TYPE_MINMAX

CONSTRAINT_TYPE_SIZELIKE

CONSTRAINT_TYPE_LOCKTRACK

CONSTRAINT_TYPE_STRETCHTO

CONSTRAINT_TYPE_CLAMPTO

CONSTRAINT_TYPE_TRANSFORM

CONSTRAINT_TYPE_DISTLIMIT

Constants related to `ik_type`

CONSTRAINT_IK_COPYPOSE
constraint is trying to match the position and eventually the rotation of the target.

Value 0

CONSTRAINT_IK_DISTANCE
Constraint is maintaining a certain distance to target subject to ik_mode

Value 1

Constants related to `ik_flag`

CONSTRAINT_IK_FLAG_TIP
Set when the constraint operates on the head of the bone and not the tail

Value 1

CONSTRAINT_IK_FLAG_ROT
Set when the constraint tries to match the orientation of the target

Value 2

CONSTRAINT_IK_FLAG_STRETCH
Set when the armature is allowed to stretch (only the bones with stretch factor > 0.0)

Value 16

CONSTRAINT_IK_FLAG_POS
Set when the constraint tries to match the position of the target.

Value 32

Constants related to `ik_mode`

CONSTRAINT_IK_MODE_INSIDE
The constraint tries to keep the bone within ik_dist of target

Value 0

CONSTRAINT_IK_MODE_OUTSIDE
The constraint tries to keep the bone outside ik_dist of the target

Value 1

CONSTRAINT_IK_MODE_ONSURFACE
The constraint tries to keep the bone exactly at ik_dist of the target.

Value 2

type

Type of constraint, (read-only).

Use one of *these constants*.

Type integer, one of CONSTRAINT_TYPE_* constants

name

Name of constraint constructed as <bone_name>:<constraint_name>. constraints list.

Type string

This name is also the key subscript on `BL_ArmatureObject`.

enforce

fraction of constraint effect that is enforced. Between 0 and 1.

Type float

headtail

Position of target between head and tail of the target bone: 0=head, 1=tail.

Type float.

Note: Only used if the target is a bone (i.e target object is an armature.

---

lin_error

runtime linear error (in Blender units) on constraint at the current frame.

This is a runtime value updated on each frame by the IK solver. Only available on IK constraint and iTaSC solver.

Type float

rot_error

Runtime rotation error (in radiant) on constraint at the current frame.

Type float.

This is a runtime value updated on each frame by the IK solver. Only available on IK constraint and iTaSC solver.

It is only set if the constraint has a rotation part, for example, a CopyPose+Rotation IK constraint.

target

Primary target object for the constraint. The position of this object in the GE will be used as target for the constraint.

Type `KX_GameObject`.

subtarget

Secondary target object for the constraint. The position of this object in the GE will be used as secondary target for the constraint.

Type `KX_GameObject`.

Currently this is only used for pole target on IK constraint.

active

True if the constraint is active.

Type boolean

Note: An inactive constraint does not update lin_error and rot_error.

ik_weight
Weight of the IK constraint between 0 and 1.

Only defined for IK constraint.

Type float

ik_type
Type of IK constraint, (read-only).

Use one of *these constants*.

Type integer.

ik_flag
Combination of IK constraint option flags, read-only.

Use one of *these constants*.

Type integer

ik_dist
Distance the constraint is trying to maintain with target, only used when ik_type=CONSTRAINT_IK_DISTANCE.

Type float

ik_mode
Use one of *these constants*.

Additional mode for IK constraint. Currently only used for Distance constraint:

Type integer

class bge.types.**BL_ArmatureChannel**(*PyObjectPlus*)
Proxy to armature pose channel. Allows to read and set armature pose. The attributes are identical to RNA attributes, but mostly in read-only mode.

See rotation_mode

PCHAN_ROT_QUAT

PCHAN_ROT_XYZ

PCHAN_ROT_XZY

PCHAN_ROT_YXZ

PCHAN_ROT_YZX

PCHAN_ROT_ZXY

PCHAN_ROT_ZYX

name
channel name (=bone name), read-only.

Type string

bone
return the bone object corresponding to this pose channel, read-only.

Type BL_ArmatureBone

parent
return the parent channel object, None if root channel, read-only.

Type BL_ArmatureChannel

has_ik
true if the bone is part of an active IK chain, read-only. This flag is not set when an IK constraint is defined but not enabled (miss target information for example).

Type boolean

ik_dof_x
true if the bone is free to rotation in the X axis, read-only.

Type boolean

ik_dof_y
true if the bone is free to rotation in the Y axis, read-only.

Type boolean

ik_dof_z
true if the bone is free to rotation in the Z axis, read-only.

Type boolean

ik_limit_x
true if a limit is imposed on X rotation, read-only.

Type boolean

ik_limit_y
true if a limit is imposed on Y rotation, read-only.

Type boolean

ik_limit_z
true if a limit is imposed on Z rotation, read-only.

Type boolean

ik_rot_control
true if channel rotation should applied as IK constraint, read-only.

Type boolean

ik_lin_control
true if channel size should applied as IK constraint, read-only.

Type boolean

location
displacement of the bone head in armature local space, read-write.

Type vector [X, Y, Z].

Note: You can only move a bone if it is unconnected to its parent. An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see BL_ArmatureObject.update).

---

scale

scale of the bone relative to its parent, read-write.

Type vector [sizeX, sizeY, sizeZ].

Note: An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

---

rotation_quaternion

rotation of the bone relative to its parent expressed as a quaternion, read-write.

Type vector [qr, qi, qj, qk].

Note: This field is only used if rotation_mode is 0. An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

---

rotation_euler

rotation of the bone relative to its parent expressed as a set of euler angles, read-write.

Type vector [X, Y, Z].

Note: This field is only used if rotation_mode is > 0. You must always pass the angles in [X, Y, Z] order; the order of applying the angles to the bone depends on rotation_mode. An action playing on the armature may change this field. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

---

rotation_mode

Method of updating the bone rotation, read-write.

Type integer

Use the following constants (euler mode are named as in Blender UI but the actual axis order is reversed).

- PCHAN_ROT_QUAT(0) : use quaternioin in rotation attribute to update bone rotation
- PCHAN_ROT_XYZ(1) : use euler_rotation and apply angles on bone's Z, Y, X axis successively
- PCHAN_ROT_XZY(2) : use euler_rotation and apply angles on bone's Y, Z, X axis successively
- PCHAN_ROT_YXZ(3) : use euler_rotation and apply angles on bone's Z, X, Y axis successively
- PCHAN_ROT_YZX(4) : use euler_rotation and apply angles on bone's X, Z, Y axis successively
- PCHAN_ROT_ZXY(5) : use euler_rotation and apply angles on bone's Y, X, Z axis successively
- PCHAN_ROT_ZYX(6) : use euler_rotation and apply angles on bone's X, Y, Z axis successively

channel_matrix
pose matrix in bone space (deformation of the bone due to action, constraint, etc), Read-only. This field is updated after the graphic render, it represents the current pose.

Type matrix [4][4]

pose_matrix
pose matrix in armature space, read-only, This field is updated after the graphic render, it represents the current pose.

Type matrix [4][4]

pose_head
position of bone head in armature space, read-only.

Type vector [x, y, z]

pose_tail
position of bone tail in armature space, read-only.

Type vector [x, y, z]

ik_min_x
minimum value of X rotation in degree (<= 0) when X rotation is limited (see ik_limit_x), read-only.

Type float

ik_max_x
maximum value of X rotation in degree (>= 0) when X rotation is limited (see ik_limit_x), read-only.

Type float

ik_min_y
minimum value of Y rotation in degree (<= 0) when Y rotation is limited (see ik_limit_y), read-only.

Type float

ik_max_y
maximum value of Y rotation in degree (>= 0) when Y rotation is limited (see ik_limit_y), read-only.

Type float

ik_min_z
minimum value of Z rotation in degree (<= 0) when Z rotation is limited (see ik_limit_z), read-only.

Type float

ik_max_z
maximum value of Z rotation in degree (>= 0) when Z rotation is limited (see ik_limit_z), read-only.

Type float

ik_stiffness_x
bone rotation stiffness in X axis, read-only.

Type float between 0 and 1

ik_stiffness_y
bone rotation stiffness in Y axis, read-only.

Type float between 0 and 1

ik_stiffness_z
bone rotation stiffness in Z axis, read-only.

Type float between 0 and 1

ik_stretch
ratio of scale change that is allowed, 0=bone can't change size, read-only.

Type float

ik_rot_weight
weight of rotation constraint when ik_rot_control is set, read-write.

Type float between 0 and 1

ik_lin_weight
weight of size constraint when ik_lin_control is set, read-write.

Type float between 0 and 1

joint_rotation
Control bone rotation in term of joint angle (for robotic applications), read-write.

When writing to this attribute, you pass a [x, y, z] vector and an appropriate set of euler angles or quaternion is calculated according to the rotation_mode.

When you read this attribute, the current pose matrix is converted into a [x, y, z] vector representing the joint angles.

The value and the meaning of the x, y, z depends on the ik_dof_x/ik_dof_y/ik_dof_z attributes:

- 1DoF joint X, Y or Z: the corresponding x, y, or z value is used an a joint angle in radiant
- 2DoF joint X+Y or Z+Y: treated as 2 successive 1DoF joints: first X or Z, then Y. The x or z value is used as a joint angle in radiant along the X or Z axis, followed by a rotation along the new Y axis of y radiants.
- 2DoF joint X+Z: treated as a 2DoF joint with rotation axis on the X/Z plane. The x and z values are used as the coordinates of the rotation vector in the X/Z plane.
- 3DoF joint X+Y+Z: treated as a revolute joint. The [x, y, z] vector represents the equivalent rotation vector to bring the joint from the rest pose to the new pose.

Type vector [x, y, z]

Note: The bone must be part of an IK chain if you want to set the ik_dof_x/ik_dof_y/ik_dof_z attributes via the UI, but this will interfere with this attribute since the IK solver will overwrite the pose. You can stay in control of the armature if you create an IK constraint but do not finalize it (e.g. don't set a target) the IK solver will not run but the IK panel will show up on the UI for each bone in the chain.

Note: [0, 0, 0] always corresponds to the rest pose.

Note: You must request the armature pose to update and wait for the next graphic frame to see the effect of setting this attribute (see `BL_ArmatureObject.update`).

Note: You can read the result of the calculation in rotation or euler_rotation attributes after setting this attribute.

---

class `bge.types.`**`BL_ArmatureBone`**(*PyObjectPlus*)
Proxy to Blender bone structure. All fields are read-only and comply to RNA names. All space attribute correspond to the rest pose.

name
bone name.

Type string

connected
true when the bone head is struck to the parent's tail.

Type boolean

hinge
true when bone doesn't inherit rotation or scale from parent bone.

Type boolean

inherit_scale
true when bone inherits scaling from parent bone.

Type boolean

bbone_segments
number of B-bone segments.

Type integer

roll
bone rotation around head-tail axis.

Type float

head
location of head end of the bone in parent bone space.

Type vector [x, y, z]

tail
location of head end of the bone in parent bone space.

Type vector [x, y, z]

length
bone length.

Type float

arm_head
location of head end of the bone in armature space.

Type vector [x, y, z]

arm_tail
location of tail end of the bone in armature space.

Type vector [x, y, z]

arm_mat
matrix of the bone head in armature space.

Type matrix [4][4]

Note: This matrix has no scale part.

---

bone_mat
rotation matrix of the bone in parent bone space.

Type matrix [3][3]

parent
parent bone, or None for root bone.

Type BL_ArmatureBone

children
list of bone's children.

Type list of BL_ArmatureBone

3.2 Game Engine bge.logic Module

3.2.1 Intro

Module to access logic functions, imported automatically into the python controllers namespace.

```
# To get the controller thats running this python script:
cont = bge.logic.getCurrentController() # bge.logic is automatically imported

# To get the game object this controller is on:
obj = cont.owner
```

KX_GameObject and KX_Camera or bge.types.~KX_LightObject methods are available depending on the type of object

```
# To get a sensor linked to this controller.
# "sensorname" is the name of the sensor as defined in the Blender interface.
# +---------------------+  +--------+
# | Sensor "sensorname" +--+ Python +
# +---------------------+  +--------+
sens = cont.sensors["sensorname"]

# To get a sequence of all sensors:
sensors = co.sensors
```

See the sensor's reference for available methods:

- KX_MouseFocusSensor
- KX_NearSensor
- KX_NetworkMessageSensor
- KX_RadarSensor
- KX_RaySensor
- KX_TouchSensor
- SCA_DelaySensor
- SCA_JoystickSensor
- SCA_KeyboardSensor
- SCA_MouseSensor
- SCA_PropertySensor
- SCA_RandomSensor

You can also access actuators linked to the controller

```
# To get an actuator attached to the controller:
#                          +--------+  +-------------------------+
#                          + Python +--+ Actuator "actuatorname" |
#                          +--------+  +-------------------------+
```

```
actuator = co.actuators["actuatorname"]

# Activate an actuator
controller.activate(actuator)
```

See the actuator's reference for available methods

- BL_ActionActuator
- BL_ShapeActionActuator
- KX_CameraActuator
- KX_ConstraintActuator
- KX_GameActuator
- KX_IpoActuator
- KX_NetworkMessageActuator
- KX_ObjectActuator
- KX_ParentActuator
- KX_SCA_AddObjectActuator
- KX_SCA_DynamicActuator
- KX_SCA_EndObjectActuator
- KX_SCA_ReplaceMeshActuator
- KX_SceneActuator
- KX_SoundActuator
- KX_StateActuator
- KX_TrackToActuator
- KX_VisibilityActuator
- SCA_2DFilterActuator
- SCA_PropertyActuator
- SCA_RandomActuator

Most logic brick's methods are accessors for the properties available in the logic buttons. Consult the logic bricks documentation for more information on how each logic brick works.

There are also methods to access the current bge.types.KX_Scene

```
# Get the current scene
scene = bge.logic.getCurrentScene()

# Get the current camera
cam = scene.active_camera
```

Matricies as used by the game engine are **row major** `matrix[row][col] = float`

bge.types.KX_Camera has some examples using matricies.

3.2.2 Variables

bge.logic.**globalDict**

A dictionary that is saved between loading blend files so you can use it to store inventory and other variables you want to store between scenes and blend files. It can also be written to a file and loaded later on with the game load/save actuators.

Note: only python built in types such as int/string/bool/float/tuples/lists can be saved, GameObjects, Actuators etc will not work as expected.

---

bge.logic.**keyboard**

The current keyboard wrapped in an SCA_PythonKeyboard object.

`bge.logic.mouse`
The current mouse wrapped in an `SCA_PythonMouse` object.

3.2.3 General functions

`bge.logic.getCurrentController()`
Gets the Python controller associated with this Python script.

Return type `bge.types.SCA_PythonController`

`bge.logic.getCurrentScene()`
Gets the current Scene.

Return type `bge.types.KX_Scene`

`bge.logic.getSceneList()`
Gets a list of the current scenes loaded in the game engine.

Return type list of `bge.types.KX_Scene`

Note: Scenes in your blend file that have not been converted wont be in this list. This list will only contain scenes such as overlays scenes.

`bge.logic.loadGlobalDict()`
Loads bge.logic.globalDict from a file.

`bge.logic.saveGlobalDict()`
Saves bge.logic.globalDict to a file.

`bge.logic.startGame(blend)`
Loads the blend file.

Parameters **blend** (*string*) – The name of the blend file

`bge.logic.endGame()`
Ends the current game.

`bge.logic.restartGame()`
Restarts the current game by reloading the .blend file (the last saved version, not what is currently running).

`bge.logic.LibLoad(blend, type, data)`
Converts the all of the datablocks of the given type from the given blend.

Parameters

- **blend** (*string*) – The path to the blend file (or the name to use for the library if data is supplied)
- **type** (*string*) – The datablock type (currently only "Action", "Mesh" and "Scene" are supported)
- **data** (*bytes*) – Binary data from a blend file (optional)

`bge.logic.LibNew(name, type, data)`
Uses existing datablock data and loads in as a new library.

Parameters

- **name** (*string*) – A unique library name used for removal later
- **type** (*string*) – The datablock type (currently only "Mesh" is supported)

- **data** (*list of strings*) – A list of names of the datablocks to load

`bge.logic.LibFree(name)`
Frees a library, removing all objects and meshes from the currently active scenes.

Parameters **name** (*string*) – The name of the library to free (the name used in LibNew)

`bge.logic.addScene(name, overlay=1)`
Loads a scene into the game engine.

Parameters

- **name** (*string*) – The name of the scene
- **overlay** (*integer*) – Overlay or underlay (optional)

`bge.logic.sendMessage(subject, body="", to="", message_from="")`
Sends a message to sensors in any active scene.

Parameters

- **subject** (*string*) – The subject of the message
- **body** (*string*) – The body of the message (optional)
- **to** (*string*) – The name of the object to send the message to (optional)
- **message_from** (*string*) – The name of the object that the message is coming from (optional)

`bge.logic.setGravity(gravity)`
Sets the world gravity.

`bge.logic.getSpectrum()`
Returns a 512 point list from the sound card. This only works if the fmod sound driver is being used.

Return type list [float], len(getSpectrum()) == 512

`bge.logic.stopDSP()`
Stops the sound driver using DSP effects.

Only the fmod sound driver supports this. DSP can be computationally expensive.

`bge.logic.getMaxLogicFrame()`
Gets the maximum number of logic frames per render frame.

Returns The maximum number of logic frames per render frame

Return type integer

`bge.logic.setMaxLogicFrame(maxlogic)`
Sets the maximum number of logic frames that are executed per render frame. This does not affect the physic system that still runs at full frame rate.

Parameters **maxlogic** (*integer*) – The new maximum number of logic frames per render frame. Valid values: 1..5

`bge.logic.getMaxPhysicsFrame()`
Gets the maximum number of physics frames per render frame.

Returns The maximum number of physics frames per render frame

Return type integer

`bge.logic.setMaxPhysicsFrame(maxphysics)`
Sets the maximum number of physics timestep that are executed per render frame. Higher value allows physics to keep up with realtime even if graphics slows down the game. Physics timestep is fixed and equal to 1/tickrate (see setLogicTicRate) maxphysics/ticrate is the maximum delay of the renderer that physics can compensate.

Parameters **maxphysics** (*integer*) – The new maximum number of physics timestep per render frame. Valid values: 1..5.

`bge.logic.getLogicTicRate()`
Gets the logic update frequency.

Returns The logic frequency in Hz

Return type float

`bge.logic.setLogicTicRate(ticrate)`
Sets the logic update frequency.

The logic update frequency is the number of times logic bricks are executed every second. The default is 60 Hz.

Parameters **ticrate** (*float*) – The new logic update frequency (in Hz).

`bge.logic.getPhysicsTicRate()`
Gets the physics update frequency

Returns The physics update frequency in Hz

Return type float

`bge.logic.setPhysicsTicRate(ticrate)`
Sets the physics update frequency

The physics update frequency is the number of times the physics system is executed every second. The default is 60 Hz.

Parameters **ticrate** (*float*) – The new update frequency (in Hz).

3.2.4 Utility functions

`bge.logic.expandPath(path)`
Converts a blender internal path into a proper file system path.

Use / as directory separator in path You can use '//' at the start of the string to define a relative path; Blender replaces that string by the directory of the startup .blend or runtime file to make a full path name (doesn't change during the game, even if you load other .blend). The function also converts the directory separator to the local file system format.

Parameters **path** (*string*) – The path string to be converted/expanded.

Returns The converted string

Return type string

`bge.logic.getAverageFrameRate()`
Gets the estimated average framerate

Returns The estimed average framerate in frames per second

Return type float

`bge.logic.getBlendFileList(path = "//")`
Returns a list of blend files in the same directory as the open blend file, or from using the option argument.

Parameters **path** (*string*) – Optional directory argument, will be expanded (like expandPath) into the full path.

Returns A list of filenames, with no directory prefix

Return type list

`bge.logic.getRandomFloat()`
Returns a random floating point value in the range [0 - 1)

`bge.logic.PrintGLInfo()`
Prints GL Extension Info into the console

3.2.5 Constants

`bge.logic.KX_TRUE`
True value used by some modules.

`bge.logic.KX_FALSE`
False value used by some modules.

Sensors

Sensor Status

`bge.logic.KX_SENSOR_INACTIVE`

`bge.logic.KX_SENSOR_JUST_ACTIVATED`

`bge.logic.KX_SENSOR_ACTIVE`

`bge.logic.KX_SENSOR_JUST_DEACTIVATED`

Property Sensor

`bge.logic.KX_PROPSENSOR_EQUAL`
Activate when the property is equal to the sensor value.

Value 1

`bge.logic.KX_PROPSENSOR_NOTEQUAL`
Activate when the property is not equal to the sensor value.

Value 2

`bge.logic.KX_PROPSENSOR_INTERVAL`
Activate when the property is between the specified limits.

Value 3

`bge.logic.KX_PROPSENSOR_CHANGED`
Activate when the property changes

Value 4

`bge.logic.KX_PROPSENSOR_EXPRESSION`
Activate when the expression matches

Value 5

Radar Sensor

See bge.types.KX_RadarSensor

bge.logic.**KX_RADAR_AXIS_POS_X**

bge.logic.**KX_RADAR_AXIS_POS_Y**

bge.logic.**KX_RADAR_AXIS_POS_Z**

bge.logic.**KX_RADAR_AXIS_NEG_X**

bge.logic.**KX_RADAR_AXIS_NEG_Y**

bge.logic.**KX_RADAR_AXIS_NEG_Z**

Ray Sensor

See bge.types.KX_RaySensor

bge.logic.**KX_RAY_AXIS_POS_X**

bge.logic.**KX_RAY_AXIS_POS_Y**

bge.logic.**KX_RAY_AXIS_POS_Z**

bge.logic.**KX_RAY_AXIS_NEG_X**

bge.logic.**KX_RAY_AXIS_NEG_Y**

bge.logic.**KX_RAY_AXIS_NEG_Z**

Actuators

Action Actuator

See bge.types.BL_ActionActuator

bge.logic.**KX_ACTIONACT_PLAY**

bge.logic.**KX_ACTIONACT_FLIPPER**

bge.logic.**KX_ACTIONACT_LOOPSTOP**

bge.logic.**KX_ACTIONACT_LOOPEND**

bge.logic.**KX_ACTIONACT_PROPERTY**

Constraint Actuator

See bge.types.KX_ConstraintActuator.option

- Applicable to Distance constraint:

  bge.logic.**KX_ACT_CONSTRAINT_NORMAL**
  Activate alignment to surface

  bge.logic.**KX_ACT_CONSTRAINT_DISTANCE**
  Activate distance control

bge.logic.**KX_ACT_CONSTRAINT_LOCAL**
Direction of the ray is along the local axis

- Applicable to Force field constraint:

bge.logic.**KX_ACT_CONSTRAINT_DOROTFH**
Force field act on rotation as well

- Applicable to both:

bge.logic.**KX_ACT_CONSTRAINT_MATERIAL**
Detect material rather than property

bge.logic.**KX_ACT_CONSTRAINT_PERMANENT**
No deactivation if ray does not hit target

See bge.types.KX_ConstraintActuator.limit

bge.logic.**KX_CONSTRAINTACT_LOCX**
Limit X coord.

bge.logic.**KX_CONSTRAINTACT_LOCY**
Limit Y coord

bge.logic.**KX_CONSTRAINTACT_LOCZ**
Limit Z coord

bge.logic.**KX_CONSTRAINTACT_ROTX**
Limit X rotation

bge.logic.**KX_CONSTRAINTACT_ROTY**
Limit Y rotation

bge.logic.**KX_CONSTRAINTACT_ROTZ**
Limit Z rotation

bge.logic.**KX_CONSTRAINTACT_DIRNX**
Set distance along negative X axis

bge.logic.**KX_CONSTRAINTACT_DIRNY**
Set distance along negative Y axis

bge.logic.**KX_CONSTRAINTACT_DIRNZ**
Set distance along negative Z axis

bge.logic.**KX_CONSTRAINTACT_DIRPX**
Set distance along positive X axis

bge.logic.**KX_CONSTRAINTACT_DIRPY**
Set distance along positive Y axis

bge.logic.**KX_CONSTRAINTACT_DIRPZ**
Set distance along positive Z axis

bge.logic.**KX_CONSTRAINTACT_ORIX**
Set orientation of X axis

bge.logic.**KX_CONSTRAINTACT_ORIY**
Set orientation of Y axis

bge.logic.**KX_CONSTRAINTACT_ORIZ**
Set orientation of Z axis

bge.logic.**KX_ACT_CONSTRAINT_FHNX**
Set force field along negative X axis

bge.logic.**KX_ACT_CONSTRAINT_FHNY**
Set force field along negative Y axis

bge.logic.**KX_ACT_CONSTRAINT_FHNZ**
Set force field along negative Z axis

bge.logic.**KX_ACT_CONSTRAINT_FHPX**
Set force field along positive X axis

bge.logic.**KX_ACT_CONSTRAINT_FHPY**
Set force field along positive Y axis

bge.logic.**KX_ACT_CONSTRAINT_FHPZ**
Set force field along positive Z axis

Dynamic Actuator

See bge.types.KX_SCA_DynamicActuator

bge.logic.**KX_DYN_RESTORE_DYNAMICS**

bge.logic.**KX_DYN_DISABLE_DYNAMICS**

bge.logic.**KX_DYN_ENABLE_RIGID_BODY**

bge.logic.**KX_DYN_DISABLE_RIGID_BODY**

bge.logic.**KX_DYN_SET_MASS**

Game Actuator

See bge.types.KX_GameActuator

bge.logic.**KX_GAME_LOAD**

bge.logic.**KX_GAME_START**

bge.logic.**KX_GAME_RESTART**

bge.logic.**KX_GAME_QUIT**

bge.logic.**KX_GAME_SAVECFG**

bge.logic.**KX_GAME_LOADCFG**

IPO Actuator

See bge.types.KX_IpoActuator

bge.logic.**KX_IPOACT_PLAY**

bge.logic.**KX_IPOACT_PINGPONG**

bge.logic.**KX_IPOACT_FLIPPER**

bge.logic.**KX_IPOACT_LOOPSTOP**

bge.logic.**KX_IPOACT_LOOPEND**

bge.logic.**KX_IPOACT_FROM_PROP**

Parent Actuator

bge.logic.**KX_PARENT_REMOVE**

bge.logic.**KX_PARENT_SET**

Random Distributions

See bge.types.SCA_RandomActuator

bge.logic.**KX_RANDOMACT_BOOL_CONST**

bge.logic.**KX_RANDOMACT_BOOL_UNIFORM**

bge.logic.**KX_RANDOMACT_BOOL_BERNOUILLI**

bge.logic.**KX_RANDOMACT_INT_CONST**

bge.logic.**KX_RANDOMACT_INT_UNIFORM**

bge.logic.**KX_RANDOMACT_INT_POISSON**

bge.logic.**KX_RANDOMACT_FLOAT_CONST**

bge.logic.**KX_RANDOMACT_FLOAT_UNIFORM**

bge.logic.**KX_RANDOMACT_FLOAT_NORMAL**

bge.logic.**KX_RANDOMACT_FLOAT_NEGATIVE_EXPONENTIAL**

Scene Actuator

See bge.types.KX_SceneActuator

bge.logic.**KX_SCENE_RESTART**

bge.logic.**KX_SCENE_SET_SCENE**

bge.logic.**KX_SCENE_SET_CAMERA**

bge.logic.**KX_SCENE_ADD_FRONT_SCENE**

bge.logic.**KX_SCENE_ADD_BACK_SCENE**

bge.logic.**KX_SCENE_REMOVE_SCENE**

bge.logic.**KX_SCENE_SUSPEND**

bge.logic.**KX_SCENE_RESUME**

Shape Action Actuator

See bge.types.BL_ActionActuator

bge.logic.**KX_ACTIONACT_PLAY**

bge.logic.**KX_ACTIONACT_FLIPPER**

bge.logic.**KX_ACTIONACT_LOOPSTOP**

bge.logic.**KX_ACTIONACT_LOOPEND**

bge.logic.**KX_ACTIONACT_PROPERTY**

Sound Actuator

See bge.types.KX_SoundActuator

bge.logic.**KX_SOUNDACT_PLAYSTOP**

Value 1

bge.logic.**KX_SOUNDACT_PLAYEND**

Value 2

bge.logic.**KX_SOUNDACT_LOOPSTOP**

Value 3

bge.logic.**KX_SOUNDACT_LOOPEND**

Value 4

bge.logic.**KX_SOUNDACT_LOOPBIDIRECTIONAL**

Value 5

bge.logic.**KX_SOUNDACT_LOOPBIDIRECTIONAL_STOP**

Value 6

Various

Input Status

See bge.types.SCA_PythonKeyboard, bge.types.SCA_PythonMouse, bge.types.SCA_MouseSensor, bge.types.SCA_KeyboardSensor

bge.logic.**KX_INPUT_NONE**

bge.logic.**KX_INPUT_JUST_ACTIVATED**

bge.logic.**KX_INPUT_ACTIVE**

bge.logic.**KX_INPUT_JUST_RELEASED**

Mouse Buttons

See bge.types.SCA_MouseSensor

bge.logic.**KX_MOUSE_BUT_LEFT**

bge.logic.**KX_MOUSE_BUT_MIDDLE**

bge.logic.**KX_MOUSE_BUT_RIGHT**

States

See bge.types.KX_StateActuator

bge.logic.**KX_STATE1**

bge.logic.**KX_STATE2**

bge.logic.**KX_STATE3**

bge.logic.**KX_STATE4**

bge.logic.**KX_STATE5**

bge.logic.**KX_STATE6**

bge.logic.**KX_STATE7**

bge.logic.**KX_STATE8**

bge.logic.**KX_STATE9**

bge.logic.**KX_STATE10**

bge.logic.**KX_STATE11**

bge.logic.**KX_STATE12**

bge.logic.**KX_STATE13**

bge.logic.**KX_STATE14**

bge.logic.**KX_STATE15**

bge.logic.**KX_STATE16**

bge.logic.**KX_STATE17**

bge.logic.**KX_STATE18**

bge.logic.**KX_STATE19**

bge.logic.**KX_STATE20**

bge.logic.**KX_STATE21**

bge.logic.**KX_STATE22**

bge.logic.**KX_STATE23**

bge.logic.**KX_STATE24**

bge.logic.**KX_STATE25**

bge.logic.**KX_STATE26**

bge.logic.**KX_STATE27**

bge.logic.**KX_STATE28**

bge.logic.**KX_STATE29**

bge.logic.**KX_STATE30**

See bge.types.KX_StateActuator.operation

bge.logic.**KX_STATE_OP_CLR**
Substract bits to state mask

Value 0

bge.logic.**KX_STATE_OP_CPY**
Copy state mask

Value 1

bge.logic.**KX_STATE_OP_NEG**
Invert bits to state mask

Value 2

bge.logic.**KX_STATE_OP_SET**
Add bits to state mask

Value 3

2D Filter

bge.logic.**RAS_2DFILTER_BLUR**

Value 2

bge.logic.**RAS_2DFILTER_CUSTOMFILTER**
Customer filter, the code code is set via shaderText property.

Value 12

bge.logic.**RAS_2DFILTER_DILATION**

Value 4

bge.logic.**RAS_2DFILTER_DISABLED**
Disable the filter that is currently active

Value -1

bge.logic.**RAS_2DFILTER_ENABLED**
Enable the filter that was previously disabled

Value -2

bge.logic.**RAS_2DFILTER_EROSION**

Value 5

bge.logic.**RAS_2DFILTER_GRAYSCALE**

Value 9

bge.logic.**RAS_2DFILTER_INVERT**

Value 11

bge.logic.**RAS_2DFILTER_LAPLACIAN**

Value 6

bge.logic.**RAS_2DFILTER_MOTIONBLUR**
Create and enable preset filters

Value 1

bge.logic.**RAS_2DFILTER_NOFILTER**
Disable and destroy the filter that is currently active

Value 0

bge.logic.**RAS_2DFILTER_PREWITT**

Value 8

bge.logic.**RAS_2DFILTER_SEPIA**

Value 10

bge.logic.**RAS_2DFILTER_SHARPEN**

Value 3

bge.logic.**RAS_2DFILTER_SOBEL**

Value 7

Shader

bge.logic.**VIEWMATRIX**

bge.logic.**VIEWMATRIX_INVERSE**

bge.logic.**VIEWMATRIX_INVERSETRANSPOSE**

bge.logic.**VIEWMATRIX_TRANSPOSE**

bge.logic.**MODELMATRIX**

bge.logic.**MODELMATRIX_INVERSE**

bge.logic.**MODELMATRIX_INVERSETRANSPOSE**

bge.logic.**MODELMATRIX_TRANSPOSE**

bge.logic.**MODELVIEWMATRIX**

bge.logic.**MODELVIEWMATRIX_INVERSE**

bge.logic.**MODELVIEWMATRIX_INVERSETRANSPOSE**

bge.logic.**MODELVIEWMATRIX_TRANSPOSE**

bge.logic.**CAM_POS**
Current camera position

bge.logic.**CONSTANT_TIMER**
User a timer for the uniform value.

bge.logic.**SHD_TANGENT**

Blender Material

bge.logic.**BL_DST_ALPHA**

bge.logic.**BL_DST_COLOR**

bge.logic.**BL_ONE**

bge.logic.**BL_ONE_MINUS_DST_ALPHA**

bge.logic.**BL_ONE_MINUS_DST_COLOR**

bge.logic.**BL_ONE_MINUS_SRC_ALPHA**

bge.logic.**BL_ONE_MINUS_SRC_COLOR**

bge.logic.**BL_SRC_ALPHA**

bge.logic.**BL_SRC_ALPHA_SATURATE**

bge.logic.**BL_SRC_COLOR**

bge.logic.**BL_ZERO**

3.3 Game Engine bge.render Module

3.3.1 Intro

```
# Example Uses an L{SCA_MouseSensor}, and two L{KX_ObjectActuator}s to implement MouseLook::
# To use a mouse movement sensor "Mouse" and a
# motion actuator to mouse look:
import bge.render
import bge.logic

# SCALE sets the speed of motion
SCALE=[1, 0.5]

co = bge.logic.getCurrentController()
obj = co.getOwner()
mouse = co.getSensor("Mouse")
lmotion = co.getActuator("LMove")
wmotion = co.getActuator("WMove")

# Transform the mouse coordinates to see how far the mouse has moved.
def mousePos():
   x = (bge.render.getWindowWidth()/2 - mouse.getXPosition())*SCALE[0]
   y = (bge.render.getWindowHeight()/2 - mouse.getYPosition())*SCALE[1]
   return (x, y)

pos = mousePos()

# Set the amount of motion: X is applied in world coordinates...
lmotion.setTorque(0.0, 0.0, pos[0], False)
# ...Y is applied in local coordinates
wmotion.setTorque(-pos[1], 0.0, 0.0, True)

# Activate both actuators
bge.logic.addActiveActuator(lmotion, True)
bge.logic.addActiveActuator(wmotion, True)

# Centre the mouse
bge.render.setMousePosition(bge.render.getWindowWidth()/2, bge.render.getWindowHeight()/2)
```

3.3.2 Constants

bge.render.**KX_TEXFACE_MATERIAL**
Materials as defined by the texture face settings.

bge.render.**KX_BLENDER_MULTITEX_MATERIAL**
Materials approximating blender materials with multitexturing.

bge.render.**KX_BLENDER_GLSL_MATERIAL**
Materials approximating blender materials with GLSL.

3.3.3 Functions

bge.render.**getWindowWidth**()
Gets the width of the window (in pixels)

Return type integer

`bge.render.getWindowHeight()`
Gets the height of the window (in pixels)

Return type integer

`bge.render.makeScreenshot(filename)`
Writes a screenshot to the given filename.

If filename starts with // the image will be saved relative to the current directory. If the filename contains # it will be replaced with the frame number.

The standalone player saves .png files. It does not support colour space conversion or gamma correction.

When run from Blender, makeScreenshot supports Iris, IrisZ, TGA, Raw TGA, PNG, HamX, and Jpeg. Gamma, Colourspace conversion and Jpeg compression are taken from the Render settings panels.

`bge.render.enableVisibility(visible)`
Doesn't really do anything...

`bge.render.showMouse(visible)`
Enables or disables the operating system mouse cursor.

`bge.render.setMousePosition(x, y)`
Sets the mouse cursor position.

`bge.render.setBackgroundColor(rgba)`
Sets the window background colour.

`bge.render.setMistColor(rgb)`
Sets the mist colour.

`bge.render.setAmbientColor(rgb)`
Sets the color of ambient light.

`bge.render.setMistStart(start)`
Sets the mist start value. Objects further away than start will have mist applied to them.

`bge.render.setMistEnd(end)`
Sets the mist end value. Objects further away from this will be coloured solid with the colour set by setMistColor().

`bge.render.disableMist()`
Disables mist.

Note: Set any of the mist properties to enable mist.

`bge.render.setEyeSeparation(eyesep)`
Sets the eye separation for stereo mode. Usually Focal Length/30 provides a confortable value.

Parameters **eyesep** (*float*) – The distance between the left and right eye.

`bge.render.getEyeSeparation()`
Gets the current eye separation for stereo mode.

Return type float

`bge.render.setFocalLength(focallength)`
Sets the focal length for stereo mode. It uses the current camera focal length as initial value.

Parameters **focallength** (*float*) – The focal length.

`bge.render.getFocalLength()`
Gets the current focal length for stereo mode.

Return type float

`bge.render.setMaterialMode(mode)`
Set the material mode to use for OpenGL rendering.

Note: Changes will only affect newly created scenes.

`bge.render.getMaterialMode(mode)`
Get the material mode to use for OpenGL rendering.

Return type KX_TEXFACE_MATERIAL, KX_BLENDER_MULTITEX_MATERIAL, KX_BLENDER_GLSL_MATERIAL

`bge.render.setGLSLMaterialSetting(setting, enable)`
Enables or disables a GLSL material setting.

`bge.render.getGLSLMaterialSetting(setting, enable)`
Get the state of a GLSL material setting.

Return type boolean

`bge.render.drawLine(fromVec, toVec, color)`
Draw a line in the 3D scene.

Parameters

- **fromVec** (*list [x, y, z]*) – the origin of the line
- **toVec** (*list [x, y, z]*) – the end of the line
- **color** (*list [r, g, b]*) – the color of the line

`bge.render.enableMotionBlur(factor)`
Enable the motion blur effect.

Parameters **factor** (*float [0.0 - 1.0]*) – the ammount of motion blur to display.

`bge.render.disableMotionBlur()`
Disable the motion blur effect.

3.4 Game Engine bge.events module

3.4.1 Intro

This module holds key constants for the SCA_KeyboardSensor.

```
# Set a connected keyboard sensor to accept F1
import bge

co = bge.logic.getCurrentController()
# 'Keyboard' is a keyboard sensor
sensor = co.sensors["Keyboard"]
sensor.key = bge.events.F1KEY

# Do the all keys thing
import bge

co = bge.logic.getCurrentController()
# 'Keyboard' is a keyboard sensor
sensor = co.sensors["Keyboard"]

for key,status in sensor.events:
        # key[0] == bge.events.keycode, key[1] = status
        if status == bge.logic.KX_INPUT_JUST_ACTIVATED:
                if key == bge.events.WKEY:
                        # Activate Forward!
                if key == bge.events.SKEY:
                        # Activate Backward!
                if key == bge.events.AKEY:
                        # Activate Left!
                if key == bge.events.DKEY:
                        # Activate Right!

# The all keys thing without a keyboard sensor (but you will
# need an always sensor with pulse mode on)
import bge

# Just shortening names here
keyboard = bge.logic.keyboard
JUST_ACTIVATED = bge.logic.KX_INPUT_JUST_ACTIVATED

if keyboard.events[bge.events.WKEY] == JUST_ACTIVATED:
        print("Activate Forward!")
if keyboard.events[bge.events.SKEY] == JUST_ACTIVATED:
        print("Activate Backward!")
if keyboard.events[bge.events.AKEY] == JUST_ACTIVATED:
        print("Activate Left!")
if keyboard.events[bge.events.DKEY] == JUST_ACTIVATED:
        print("Activate Right!")
```

3.4.2 Functions

`bge.events.`**`EventToString`**(*event*)

Return the string name of a key event. Will raise a ValueError error if its invalid.

Parameters **event** (*int*) – key event from bge.keys or the keyboard sensor.

Return type string

`bge.events.EventToCharacter`(*event*, *shift*)

Return the string name of a key event. Returns an empty string if the event cant be represented as a character.

Parameters

- **event** (*int*) – key event from `bge.keys` or the keyboard sensor.
- **shift** (*bool*) – set to true if shift is held.

Return type string

3.4.3 Keys (Constants)

Mouse Keys

`bge.events.LEFTMOUSE`

`bge.events.MIDDLEMOUSE`

`bge.events.RIGHTMOUSE`

`bge.events.WHEELUPMOUSE`

`bge.events.WHEELDOWNMOUSE`

`bge.events.MOUSEX`

`bge.events.MOUSEY`

Keyboard Keys

Alphabet keys

`bge.events.AKEY`

`bge.events.BKEY`

`bge.events.CKEY`

`bge.events.DKEY`

`bge.events.EKEY`

`bge.events.FKEY`

`bge.events.GKEY`

`bge.events.HKEY`

`bge.events.IKEY`

`bge.events.JKEY`

`bge.events.KKEY`

`bge.events.LKEY`

`bge.events.MKEY`

`bge.events.NKEY`

`bge.events.OKEY`

bge.events.**PKEY**

bge.events.**QKEY**

bge.events.**RKEY**

bge.events.**SKEY**

bge.events.**TKEY**

bge.events.**UKEY**

bge.events.**VKEY**

bge.events.**WKEY**

bge.events.**XKEY**

bge.events.**YKEY**

bge.events.**ZKEY**

Number keys

bge.events.**ZEROKEY**

bge.events.**ONEKEY**

bge.events.**TWOKEY**

bge.events.**THREEKEY**

bge.events.**FOURKEY**

bge.events.**FIVEKEY**

bge.events.**SIXKEY**

bge.events.**SEVENKEY**

bge.events.**EIGHTKEY**

bge.events.**NINEKEY**

Modifiers Keys

bge.events.**CAPSLOCKKEY**

bge.events.**LEFTCTRLKEY**

bge.events.**LEFTALTKEY**

bge.events.**RIGHTALTKEY**

bge.events.**RIGHTCTRLKEY**

bge.events.**RIGHTSHIFTKEY**

bge.events.**LEFTSHIFTKEY**

Arrow Keys

bge.events.**LEFTARROWKEY**

bge.events.**DOWNARROWKEY**

bge.events.**RIGHTARROWKEY**

bge.events.**UPARROWKEY**

Numberpad Keys

bge.events.**PAD0**

bge.events.**PAD1**

bge.events.**PAD2**

bge.events.**PAD3**

bge.events.**PAD4**

bge.events.**PAD5**

bge.events.**PAD6**

bge.events.**PAD7**

bge.events.**PAD8**

bge.events.**PAD9**

bge.events.**PADPERIOD**

bge.events.**PADSLASHKEY**

bge.events.**PADASTERKEY**

bge.events.**PADMINUS**

bge.events.**PADENTER**

bge.events.**PADPLUSKEY**

Function Keys

bge.events.**F1KEY**

bge.events.**F2KEY**

bge.events.**F3KEY**

bge.events.**F4KEY**

bge.events.**F5KEY**

bge.events.**F6KEY**

bge.events.**F7KEY**

bge.events.**F8KEY**

bge.events.**F9KEY**

bge.events.**F10KEY**

bge.events.**F11KEY**

bge.events.**F12KEY**

bge.events.**F13KEY**

bge.events.**F14KEY**

bge.events.**F15KEY**

bge.events.**F16KEY**

bge.events.**F17KEY**

bge.events.**F18KEY**

bge.events.**F19KEY**

Other Keys

bge.events.**ACCENTGRAVEKEY**

bge.events.**BACKSLASHKEY**

bge.events.**BACKSPACEKEY**

bge.events.**COMMAKEY**

bge.events.**DELKEY**

bge.events.**ENDKEY**

bge.events.**EQUALKEY**

bge.events.**ESCKEY**

bge.events.**HOMEKEY**

bge.events.**INSERTKEY**

bge.events.**LEFTBRACKETKEY**

bge.events.**LINEFEEDKEY**

bge.events.**MINUSKEY**

bge.events.**PAGEDOWNKEY**

bge.events.**PAGEUPKEY**

bge.events.**PAUSEKEY**

bge.events.**PERIODKEY**

bge.events.**QUOTEKEY**

bge.events.**RIGHTBRACKETKEY**

bge.events.**RETKEY** (*Deprecated: use bge.events.ENTERKEY*)

bge.events.**ENTERKEY**

bge.events.**SEMICOLONKEY**

bge.events.**SLASHKEY**

bge.events.**SPACEKEY**

bge.events.**TABKEY**

PYTHON MODULE INDEX

a

aud, 1073

b

bge.events, 1172
bge.logic, 1155
bge.render, 1169
bge.types, 1083
blf, 1071
bpy, 7
bpy.app, 1031
bpy.context, 3
bpy.ops.action, 8
bpy.ops.anim, 11
bpy.ops.armature, 14
bpy.ops.boid, 17
bpy.ops.brush, 17
bpy.ops.buttons, 18
bpy.ops.cloth, 18
bpy.ops.console, 19
bpy.ops.constraint, 20
bpy.ops.curve, 21
bpy.ops.ed, 25
bpy.ops.export_anim, 25
bpy.ops.export_mesh, 25
bpy.ops.export_scene, 26
bpy.ops.file, 29
bpy.ops.fluid, 31
bpy.ops.font, 31
bpy.ops.gpencil, 33
bpy.ops.graph, 34
bpy.ops.group, 38
bpy.ops.help, 38
bpy.ops.image, 38
bpy.ops.import_anim, 42
bpy.ops.import_mesh, 43
bpy.ops.import_scene, 43
bpy.ops.info, 44
bpy.ops.lamp, 45
bpy.ops.lattice, 45
bpy.ops.logic, 45
bpy.ops.marker, 47
bpy.ops.material, 47
bpy.ops.mball, 48
bpy.ops.mesh, 48
bpy.ops.nla, 60
bpy.ops.node, 63
bpy.ops.object, 66
bpy.ops.outliner, 81
bpy.ops.paint, 83
bpy.ops.particle, 86
bpy.ops.pose, 88
bpy.ops.poselib, 91
bpy.ops.ptcache, 92
bpy.ops.render, 92
bpy.ops.scene, 94
bpy.ops.screen, 94
bpy.ops.script, 97
bpy.ops.sculpt, 98
bpy.ops.sequencer, 98
bpy.ops.sketch, 104
bpy.ops.sound, 105
bpy.ops.surface, 106
bpy.ops.text, 108
bpy.ops.texture, 112
bpy.ops.time, 113
bpy.ops.transform, 113
bpy.ops.ui, 122
bpy.ops.uv, 122
bpy.ops.view2d, 127
bpy.ops.view3d, 129
bpy.ops.wm, 132
bpy.ops.world, 142
bpy.path, 1030
bpy.props, 1032
bpy.types, 1025
bpy.utils, 1029

m

mathutils, 1039
mathutils.geometry, 1068

INDEX

A

a (bge.types.KX_VertexProxy attribute), 1131
absorption (bpy.types.CollisionSettings attribute), 253
abspath() (in module bpy.path), 1030
ACCENTGRAVEKEY (in module bge.events), 1176
accuracy (bpy.types.BoidSettings attribute), 215
accuracy (bpy.types.Scopes attribute), 752
act_spline (bpy.types.ThemeView3D attribute), 929
action (bge.types.BL_ActionActuator attribute), 1086
action (bge.types.BL_ShapeActionActuator attribute), 1090
action (bpy.types.ActionActuator attribute), 144
action (bpy.types.ActionConstraint attribute), 145
action (bpy.types.AnimData attribute), 156
action (bpy.types.NlaStrip attribute), 589
action (bpy.types.ShapeActionActuator attribute), 788
action (bpy.types.SpaceDopeSheetEditor attribute), 816
Action (class in bpy.types), 142
Action.fcurves (in module bpy.types), 142
Action.frame_range (in module bpy.types), 142
Action.groups (in module bpy.types), 142
Action.pose_markers (in module bpy.types), 143
action_blend_type (bpy.types.AnimData attribute), 156
action_extrapolation (bpy.types.AnimData attribute), 156
action_frame_end (bpy.types.NlaStrip attribute), 589
action_frame_start (bpy.types.NlaStrip attribute), 590
action_influence (bpy.types.AnimData attribute), 156
action_sanitise() (in module bpy.ops.poselib), 91
action_sync_length() (in module bpy.ops.nla), 60
ActionActuator (class in bpy.types), 144
actionclip_add() (in module bpy.ops.nla), 60
ActionConstraint (class in bpy.types), 145
ActionFCurves (class in bpy.types), 146
ActionGroup (class in bpy.types), 147
ActionGroup.channels (in module bpy.types), 147
ActionGroups (class in bpy.types), 149
ActionPoseMarkers (class in bpy.types), 149
actionzone() (in module bpy.ops.screen), 94
activate() (bge.types.KX_PolygonMaterial method), 1119
activate() (bge.types.SCA_PythonController method), 1138
active (bge.types.BL_ArmatureConstraint attribute), 1148
active (bpy.types.ActionPoseMarkers attribute), 149
active (bpy.types.ArmatureBones attribute), 170
active (bpy.types.ArmatureEditBones attribute), 170
active (bpy.types.BoneGroups attribute), 224
active (bpy.types.Constraint attribute), 317
active (bpy.types.CurveSplines attribute), 340
active (bpy.types.FCurveModifiers attribute), 381
active (bpy.types.FModifier attribute), 383
active (bpy.types.GPencilLayer attribute), 409
active (bpy.types.KeyConfigurations attribute), 460
active (bpy.types.KeyingSetPaths attribute), 478
active (bpy.types.KeyingSets attribute), 480
active (bpy.types.KeyingSetsAll attribute), 481
active (bpy.types.KeyMapItem attribute), 463
active (bpy.types.MeshColorLayer attribute), 542
active (bpy.types.MeshFaces attribute), 548
active (bpy.types.MeshTextureFaceLayer attribute), 556
active (bpy.types.NlaTracks attribute), 594
active (bpy.types.ObjectConstraints attribute), 618
active (bpy.types.PoseBoneConstraints attribute), 692
active (bpy.types.RenderLayers attribute), 718
active (bpy.types.SceneBases attribute), 740
active (bpy.types.SceneObjects attribute), 744
active (bpy.types.ThemeBoneColorSet attribute), 898
active (bpy.types.UILayout attribute), 949
active (bpy.types.UVTextures attribute), 973
active (bpy.types.VertexColors attribute), 995
active() (bpy.types.KeyMap method), 462
active_base (in module bpy.context), 4, 5
active_blacklisted_slave_index (bpy.types.NetRenderSettings attribute), 586
active_boid_rule_index (bpy.types.BoidState attribute), 218
active_boid_state_index (bpy.types.BoidSettings attribute), 215
active_bone (in module bpy.context), 4
active_camera (bge.types.KX_Scene attribute), 1124
active_channels_group (bpy.types.ThemeDopeSheet attribute), 901

active_channels_group (bpy.types.ThemeGraphEditor attribute), 906
active_clone (bpy.types.MeshTextureFaceLayer attribute), 556
active_dupliweight_index (bpy.types.ParticleSettings attribute), 650
active_file (bpy.types.ThemeFileBrowser attribute), 903
active_file_text (bpy.types.ThemeFileBrowser attribute), 903
active_frame_delete() (in module bpy.ops.gpencil), 33
active_index (bpy.types.ActionPoseMarkers attribute), 150
active_index (bpy.types.BoneGroups attribute), 224
active_index (bpy.types.KeyingSetPaths attribute), 478
active_index (bpy.types.KeyingSets attribute), 480
active_index (bpy.types.KeyingSetsAll attribute), 481
active_index (bpy.types.ParticleSystems attribute), 671
active_index (bpy.types.PointCaches attribute), 679
active_index (bpy.types.RenderLayers attribute), 718
active_index (bpy.types.UVTextures attribute), 974
active_index (bpy.types.VertexColors attribute), 995
active_index (bpy.types.VertexGroups attribute), 998
active_job_index (bpy.types.NetRenderSettings attribute), 586
active_keyconfig (bpy.types.UserPreferencesInput attribute), 983
active_material (bpy.types.Object attribute), 603
active_material_index (bpy.types.Object attribute), 604
active_node_material (bpy.types.Material attribute), 509
active_object (in module bpy.context), 4, 5
active_particle_target_index (bpy.types.ParticleSystem attribute), 666
active_pose_bone (in module bpy.context), 4
active_render (bpy.types.MeshColorLayer attribute), 542
active_render (bpy.types.MeshTextureFaceLayer attribute), 557
active_section (bpy.types.UserPreferences attribute), 976
active_shape_key_index (bpy.types.Object attribute), 604
active_slave_index (bpy.types.NetRenderSettings attribute), 586
active_strip (bpy.types.SequenceEditor attribute), 764
active_textbox (bpy.types.TextCurve attribute), 867
active_texture (bpy.types.Lamp attribute), 484
active_texture (bpy.types.Material attribute), 509
active_texture (bpy.types.ParticleSettings attribute), 650
active_texture (bpy.types.World attribute), 1015
active_texture_index (bpy.types.Lamp attribute), 484
active_texture_index (bpy.types.Material attribute), 509
active_texture_index (bpy.types.ParticleSettings attribute), 650
active_texture_index (bpy.types.World attribute), 1015
activity_culling (bge.types.KX_Scene attribute), 1125
activity_culling_box_radius (bpy.types.SceneGameData attribute), 741
activity_culling_radius (bge.types.KX_Scene attribute), 1125
actuator (bge.types.SCA_ActuatorSensor attribute), 1133
actuator (bpy.types.ActuatorSensor attribute), 152
Actuator (class in bpy.types), 151
actuator_add() (in module bpy.ops.logic), 45
actuator_move() (in module bpy.ops.logic), 45
actuator_remove() (in module bpy.ops.logic), 45
actuators (bge.types.KX_GameObject attribute), 1097
actuators (bge.types.SCA_IController attribute), 1085
ActuatorSensor (class in bpy.types), 152
adapt_to_speed (bpy.types.WorldLighting attribute), 1017
adaptation (bpy.types.CompositorNodeTonemap attribute), 308
adaptive_angle (bpy.types.ParticleSettings attribute), 650
adaptive_pixel (bpy.types.ParticleSettings attribute), 650
add (bpy.types.MaterialHalo attribute), 515
add() (bpy.types.FCurveKeyframePoints method), 380
add() (bpy.types.KeyingSetPaths method), 478
add() (bpy.types.LampTextureSlots class method), 489
add() (bpy.types.MaterialTextureSlots class method), 531
add() (bpy.types.MeshEdges method), 546
add() (bpy.types.MeshFaces method), 548
add() (bpy.types.MeshVertices method), 559
add() (bpy.types.ParticleSettingsTextureSlots class method), 665
add() (bpy.types.SplineBezierPoints method), 843
add() (bpy.types.SplinePoints method), 847
add() (bpy.types.VertexGroup method), 996
add() (bpy.types.WorldTextureSlots class method), 1023
add() (in module bpy.ops.brush), 17
add() (in module bpy.ops.marker), 47
add() (in module bpy.ops.object), 66
add() (in module bpy.ops.ptcache), 92
add_file() (in module bpy.ops.node), 63
add_named() (in module bpy.ops.object), 66
add_named_cursor() (in module bpy.ops.object), 66
addObject() (bge.types.KX_Scene method), 1125
Addon (class in bpy.types), 153
addon_disable() (in module bpy.ops.wm), 132
addon_enable() (in module bpy.ops.wm), 133
addon_expand() (in module bpy.ops.wm), 133
addon_install() (in module bpy.ops.wm), 133
Addons (class in bpy.types), 153
addScene() (in module bge.logic), 1158
addWheel() (bge.types.KX_VehicleWrapper method), 1128
aero (bpy.types.SoftBodySettings attribute), 804
aerodynamics_type (bpy.types.SoftBodySettings attribute), 804
aggression (bpy.types.BoidSettings attribute), 215
air_acc_max (bpy.types.BoidSettings attribute), 215
air_ave_max (bpy.types.BoidSettings attribute), 215

air_damping (bpy.types.ClothSettings attribute), 246
air_personal_space (bpy.types.BoidSettings attribute), 215
air_speed_max (bpy.types.BoidSettings attribute), 216
air_speed_min (bpy.types.BoidSettings attribute), 216
AKEY (in module bge.events), 1173
alert (bpy.types.UILayout attribute), 949
align (bpy.types.SpaceProperties attribute), 828
align (bpy.types.TextCurve attribute), 867
align() (in module bpy.ops.armature), 14
align() (in module bpy.ops.object), 67
align() (in module bpy.ops.uv), 122
align_orientation() (bpy.types.EditBone method), 359
align_roll() (bpy.types.EditBone method), 359
alignAxisToVect() (bge.types.KX_GameObject method), 1098
alignment (bpy.types.UILayout attribute), 949
alive_state (bpy.types.Particle attribute), 639
all (bpy.types.EffectorWeights attribute), 365
alliance (bpy.types.ParticleTarget attribute), 672
alpha (bpy.types.CompositorNodeMapUV attribute), 292
alpha (bpy.types.GPencilLayer attribute), 410
alpha (bpy.types.Material attribute), 509
alpha (bpy.types.SmokeDomainSettings attribute), 798
alpha_factor (bpy.types.MaterialTextureSlot attribute), 526
alpha_influence (bpy.types.ParticleFluidSettings attribute), 645
alpha_mode (bpy.types.RenderSettings attribute), 721
alt (bpy.types.KeyMapItem attribute), 463
AlwaysSensor (class in bpy.types), 154
ambient (bpy.types.Material attribute), 509
ambient_color (bpy.types.World attribute), 1015
ambient_factor (bpy.types.MaterialTextureSlot attribute), 526
amplify (bpy.types.SmokeDomainSettings attribute), 798
amplitude (bpy.types.FModifierFunctionGenerator attribute), 387
AndController (class in bpy.types), 155
angle (bge.types.KX_RadarSensor attribute), 1120
angle (bpy.types.BrushTextureSlot attribute), 232
angle (bpy.types.Camera attribute), 234
angle (bpy.types.CompositorNodeDBlur attribute), 276
angle (bpy.types.CompositorNodeDefocus attribute), 277
angle (bpy.types.RadarSensor attribute), 703
angle (bpy.types.ScrewModifier attribute), 755
angle (bpy.types.WipeSequence attribute), 1011
angle (mathutils.Quaternion attribute), 1047
angle_limit (bpy.types.BevelModifier attribute), 177
angle_max (bpy.types.ConstraintActuator attribute), 319
angle_min (bpy.types.ConstraintActuator attribute), 319
angle_offset (bpy.types.CompositorNodeGlare attribute), 283
angular_velocity (bpy.types.EditObjectActuator attribute), 360
angular_velocity (bpy.types.ObjectActuator attribute), 614
angular_velocity (bpy.types.Particle attribute), 639
angular_velocity (bpy.types.ParticleKey attribute), 649
angular_velocity_factor (bpy.types.ParticleSettings attribute), 650
angular_velocity_mode (bpy.types.ParticleSettings attribute), 650
angularVelocity (bge.types.KX_SCA_AddObjectActuator attribute), 1122
angV (bge.types.KX_ObjectActuator attribute), 1111
animation_cancel() (in module bpy.ops.screen), 94
animation_data_clear() (bpy.types.ID method), 436
animation_data_create() (bpy.types.ID method), 436
animation_offset_end (bpy.types.ImageSequence attribute), 444
animation_offset_end (bpy.types.MetaSequence attribute), 566
animation_offset_end (bpy.types.MovieSequence attribute), 574
animation_offset_end (bpy.types.MulticamSequence attribute), 577
animation_offset_end (bpy.types.SceneSequence attribute), 749
animation_offset_end (bpy.types.SoundSequence attribute), 812
animation_offset_start (bpy.types.ImageSequence attribute), 444
animation_offset_start (bpy.types.MetaSequence attribute), 566
animation_offset_start (bpy.types.MovieSequence attribute), 574
animation_offset_start (bpy.types.MulticamSequence attribute), 577
animation_offset_start (bpy.types.SceneSequence attribute), 749
animation_offset_start (bpy.types.SoundSequence attribute), 812
animation_play() (in module bpy.ops.screen), 95
animation_player (bpy.types.UserPreferencesFilePaths attribute), 981
animation_player_preset (bpy.types.UserPreferencesFilePaths attribute), 981
animation_step() (in module bpy.ops.screen), 95
AnimData (class in bpy.types), 156
AnimData.drivers (in module bpy.types), 156
AnimData.nla_tracks (in module bpy.types), 156
AnimViz (class in bpy.types), 157
AnimViz.motion_path (in module bpy.types), 157
AnimViz.onion_skin_frames (in module bpy.types), 157
AnimVizMotionPaths (class in bpy.types), 158
AnimVizOnionSkinning (class in bpy.types), 160

antialiasing_samples (bpy.types.RenderSettings attribute), 721
any (bpy.types.KeyMapItem attribute), 463
AnyType (class in bpy.types), 161
ao_blend_type (bpy.types.WorldLighting attribute), 1017
ao_factor (bpy.types.WorldLighting attribute), 1017
append() (bge.types.CListValue method), 1091
append() (bpy.types.Header class method), 431
append() (bpy.types.IDMaterials method), 437
append() (bpy.types.InputKeyMapPanel class method), 452
append() (bpy.types.Menu class method), 536
append() (bpy.types.Panel class method), 638
apply_effector_to_children (bpy.types.ParticleSettings attribute), 650
apply_guide_to_children (bpy.types.ParticleSettings attribute), 651
apply_pose() (in module bpy.ops.poselib), 91
apply_scale() (in module bpy.ops.nla), 60
apply_to_children (bpy.types.FCurveActuator attribute), 378
apply_to_children (bpy.types.VisibilityActuator attribute), 1000
apply_to_hair_growing (bpy.types.EffectorWeights attribute), 365
apply_to_location (bpy.types.FieldSettings attribute), 393
apply_to_rotation (bpy.types.FieldSettings attribute), 393
applyBraking() (bge.types.KX_VehicleWrapper method), 1128
applyEngineForce() (bge.types.KX_VehicleWrapper method), 1128
applyForce() (bge.types.KX_GameObject method), 1098
applyImpulse() (bge.types.KX_GameObject method), 1100
applyMovement() (bge.types.KX_GameObject method), 1098
applyRotation() (bge.types.KX_GameObject method), 1098
applyTorque() (bge.types.KX_GameObject method), 1099
Area (class in bpy.types), 162
Area.active_space (in module bpy.types), 162
Area.regions (in module bpy.types), 162
Area.spaces (in module bpy.types), 162
area_dupli() (in module bpy.ops.screen), 95
area_join() (in module bpy.ops.screen), 95
area_move() (in module bpy.ops.screen), 95
area_options() (in module bpy.ops.screen), 95
area_split() (in module bpy.ops.screen), 95
area_swap() (in module bpy.ops.screen), 95
area_tri() (in module mathutils.geometry), 1068
AreaLamp (class in bpy.types), 163
arm_head (bge.types.BL_ArmatureBone attribute), 1154
arm_mat (bge.types.BL_ArmatureBone attribute), 1154
arm_tail (bge.types.BL_ArmatureBone attribute), 1154
armature (bpy.types.MaskModifier attribute), 507
Armature (class in bpy.types), 166
armature (in module bpy.context), 5
Armature.animation_data (in module bpy.types), 166
Armature.bones (in module bpy.types), 166
Armature.edit_bones (in module bpy.types), 166
armature_add() (in module bpy.ops.object), 67
armature_apply() (in module bpy.ops.pose), 88
armature_layers() (in module bpy.ops.armature), 14
armature_layers() (in module bpy.ops.pose), 88
ArmatureActuator (class in bpy.types), 168
ArmatureBones (class in bpy.types), 169
ArmatureEditBones (class in bpy.types), 170
ArmatureModifier (class in bpy.types), 171
ArmatureSensor (class in bpy.types), 172
array_index (bpy.types.FCurve attribute), 376
array_index (bpy.types.KeyingSetPath attribute), 477
ArrayModifier (class in bpy.types), 174
as_keywords() (bpy.types.Operator method), 627
as_pointer() (bpy.types.bpy_struct method), 1026
as_string() (bpy.types.Text static method), 864
aspect() (in module blf), 1071
aspect_correction (bpy.types.CompositorNodeBlur attribute), 262
aspect_x (bpy.types.UVProjectModifier attribute), 971
aspect_y (bpy.types.UVProjectModifier attribute), 971
asymmetry (bpy.types.MaterialVolume attribute), 532
atmosphere_distance_factor (bpy.types.LampSkySettings attribute), 486
atmosphere_extinction (bpy.types.LampSkySettings attribute), 486
atmosphere_inscattering (bpy.types.LampSkySettings attribute), 486
atmosphere_turbidity (bpy.types.LampSkySettings attribute), 486
attenuation (aud.Handle attribute), 1080
attenuation (bpy.types.SoundSequence attribute), 812
attraction_radius (bpy.types.ControlFluidSettings attribute), 324
attraction_strength (bpy.types.ControlFluidSettings attribute), 324
attrDict (bge.types.KX_GameObject attribute), 1097
aud (module), 1073
AUD_DEVICE_JACK (in module aud), 1073
AUD_DEVICE_NULL (in module aud), 1073
AUD_DEVICE_OPENAL (in module aud), 1073
AUD_DEVICE_SDL (in module aud), 1073
AUD_DISTANCE_MODEL_EXPONENT (in module aud), 1074
AUD_DISTANCE_MODEL_EXPONENT_CLAMPED (in module aud), 1074
AUD_DISTANCE_MODEL_INVALID (in module aud), 1074

AUD_DISTANCE_MODEL_INVERSE (in module aud), 1074
AUD_DISTANCE_MODEL_INVERSE_CLAMPED (in module aud), 1074
AUD_DISTANCE_MODEL_LINEAR (in module aud), 1074
AUD_DISTANCE_MODEL_LINEAR_CLAMPED (in module aud), 1074
AUD_FORMAT_FLOAT32 (in module aud), 1074
AUD_FORMAT_FLOAT64 (in module aud), 1074
AUD_FORMAT_INVALID (in module aud), 1074
AUD_FORMAT_S16 (in module aud), 1074
AUD_FORMAT_S24 (in module aud), 1074
AUD_FORMAT_S32 (in module aud), 1074
AUD_FORMAT_U8 (in module aud), 1074
AUD_STATUS_INVALID (in module aud), 1074
AUD_STATUS_PAUSED (in module aud), 1074
AUD_STATUS_PLAYING (in module aud), 1074
audio_channels (bpy.types.UserPreferencesSystem attribute), 985
audio_device (bpy.types.UserPreferencesSystem attribute), 985
audio_distance_model (bpy.types.Scene attribute), 735
audio_doppler_factor (bpy.types.Scene attribute), 735
audio_doppler_speed (bpy.types.Scene attribute), 735
audio_mixing_buffer (bpy.types.UserPreferencesSystem attribute), 985
audio_sample_format (bpy.types.UserPreferencesSystem attribute), 985
audio_sample_rate (bpy.types.UserPreferencesSystem attribute), 985
audio_strip (bpy.types.ThemeSequenceEditor attribute), 920
author (bpy.types.UserPreferencesSystem attribute), 985
auto_keying_mode (bpy.types.ToolSettings attribute), 937
auto_keying_mode (bpy.types.UserPreferencesEdit attribute), 977
auto_save_time (bpy.types.UserPreferencesFilePaths attribute), 981
auto_smooth_angle (bpy.types.Mesh attribute), 537
auto_smooth_factor (bpy.types.Brush attribute), 227
auto_snap (bpy.types.SpaceDopeSheetEditor attribute), 816
auto_snap (bpy.types.SpaceGraphEditor attribute), 818
auto_snap (bpy.types.SpaceNLA attribute), 824
autocomplete() (in module bpy.ops.console), 19
autodesk_3ds() (in module bpy.ops.export_scene), 26
autodesk_3ds() (in module bpy.ops.import_scene), 43
autoside_names() (in module bpy.ops.armature), 14
autoside_names() (in module bpy.ops.pose), 88
auxiliary_target (bpy.types.ShrinkwrapModifier attribute), 794
average_islands_scale() (in module bpy.ops.uv), 122
average_separation (bpy.types.WorldStarsSettings attribute), 1020
axis (bge.types.KX_RadarSensor attribute), 1120
axis (bge.types.KX_RaySensor attribute), 1121
axis (bge.types.SCA_JoystickSensor attribute), 1135
axis (bpy.types.CameraActuator attribute), 237
axis (bpy.types.CompositorNodeFlip attribute), 282
axis (bpy.types.CompositorNodeSplitViewer attribute), 306
axis (bpy.types.ParticleInstanceModifier attribute), 647
axis (bpy.types.RadarSensor attribute), 703
axis (bpy.types.RaySensor attribute), 707
axis (bpy.types.ScrewModifier attribute), 755
axis (mathutils.Quaternion attribute), 1047
axis_direction (bpy.types.JoystickSensor attribute), 456
axis_number (bpy.types.JoystickSensor attribute), 456
axis_threshold (bpy.types.JoystickSensor attribute), 456
axis_x (bpy.types.RigidBodyJointConstraint attribute), 730
axis_y (bpy.types.RigidBodyJointConstraint attribute), 730
axis_z (bpy.types.RigidBodyJointConstraint attribute), 730
axisSingle (bge.types.SCA_JoystickSensor attribute), 1134
axisValues (bge.types.SCA_JoystickSensor attribute), 1134

B

b (bge.types.KX_VertexProxy attribute), 1131
b (mathutils.Color attribute), 1039
back (bpy.types.MaterialSubsurfaceScattering attribute), 524
back (bpy.types.ThemeAudioWindow attribute), 897
back (bpy.types.ThemeConsole attribute), 899
back (bpy.types.ThemeDopeSheet attribute), 901
back (bpy.types.ThemeFileBrowser attribute), 903
back (bpy.types.ThemeGraphEditor attribute), 906
back (bpy.types.ThemeImageEditor attribute), 909
back (bpy.types.ThemeInfo attribute), 911
back (bpy.types.ThemeLogicEditor attribute), 912
back (bpy.types.ThemeNLAEditor attribute), 913
back (bpy.types.ThemeNodeEditor attribute), 915
back (bpy.types.ThemeOutliner attribute), 917
back (bpy.types.ThemeProperties attribute), 918
back (bpy.types.ThemeSequenceEditor attribute), 920
back (bpy.types.ThemeTextEditor attribute), 923
back (bpy.types.ThemeTimeline attribute), 925
back (bpy.types.ThemeUserPreferences attribute), 928
back (bpy.types.ThemeView3D attribute), 929
back_to_previous() (in module bpy.ops.screen), 95
backdrop_channels (bpy.types.SpaceNodeEditor attribute), 825
backdrop_x (bpy.types.SpaceNodeEditor attribute), 825

backdrop_y (bpy.types.SpaceNodeEditor attribute), 825
backdrop_zoom (bpy.types.SpaceNodeEditor attribute), 825
background (in module bpy.app), 1032
background_image_add() (in module bpy.ops.view3d), 129
background_image_remove() (in module bpy.ops.view3d), 129
background_set (bpy.types.Scene attribute), 735
BackgroundImage (class in bpy.types), 175
BackgroundImage.image_user (in module bpy.types), 175
backimage_move() (in module bpy.ops.node), 63
backimage_sample() (in module bpy.ops.node), 63
backimage_zoom() (in module bpy.ops.node), 63
backscattered_light (bpy.types.LampSkySettings attribute), 486
BACKSLASHKEY (in module bge.events), 1176
BACKSPACEKEY (in module bge.events), 1176
bake() (in module bpy.ops.fluid), 31
bake() (in module bpy.ops.graph), 34
bake() (in module bpy.ops.nla), 60
bake() (in module bpy.ops.ptcache), 92
bake_aa_mode (bpy.types.RenderSettings attribute), 721
bake_all() (in module bpy.ops.ptcache), 92
bake_bias (bpy.types.RenderSettings attribute), 721
bake_distance (bpy.types.RenderSettings attribute), 721
bake_from_cache() (in module bpy.ops.ptcache), 92
bake_image() (in module bpy.ops.object), 67
bake_location (bpy.types.AnimVizMotionPaths attribute), 158
bake_margin (bpy.types.RenderSettings attribute), 721
bake_normal_space (bpy.types.RenderSettings attribute), 721
bake_quad_split (bpy.types.RenderSettings attribute), 721
bake_type (bpy.types.RenderSettings attribute), 721
ball_damp (bpy.types.SoftBodySettings attribute), 804
ball_size (bpy.types.SoftBodySettings attribute), 804
ball_stiff (bpy.types.SoftBodySettings attribute), 804
bank (bpy.types.BoidSettings attribute), 216
banner() (in module bpy.ops.console), 19
bars (bpy.types.ThemeNLAEditor attribute), 913
bars_selected (bpy.types.ThemeNLAEditor attribute), 913
barycentric_transform() (in module mathutils.geometry), 1068
bbone_in (bpy.types.Bone attribute), 219
bbone_in (bpy.types.EditBone attribute), 356
bbone_out (bpy.types.Bone attribute), 219
bbone_out (bpy.types.EditBone attribute), 357
bbone_segments (bge.types.BL_ArmatureBone attribute), 1154
bbone_segments (bpy.types.Bone attribute), 219
bbone_segments (bpy.types.EditBone attribute), 357
bbone_x (bpy.types.Bone attribute), 219
bbone_x (bpy.types.EditBone attribute), 357
bbone_z (bpy.types.Bone attribute), 219
bbone_z (bpy.types.EditBone attribute), 357
beautify_fill() (in module bpy.ops.mesh), 48
begin_result() (bpy.types.RenderEngine method), 712
bend (bpy.types.SoftBodySettings attribute), 804
bending_stiffness (bpy.types.ClothSettings attribute), 246
bending_stiffness_max (bpy.types.ClothSettings attribute), 246
beta (bpy.types.SmokeDomainSettings attribute), 798
bevel_depth (bpy.types.Curve attribute), 332
bevel_object (bpy.types.Curve attribute), 332
bevel_resolution (bpy.types.Curve attribute), 332
bevel_weight (bpy.types.MeshEdge attribute), 544
bevel_weight (bpy.types.MeshVertex attribute), 558
BevelModifier (class in bpy.types), 177
BezierSplinePoint (class in bpy.types), 178
bge.events (module), 1172
bge.logic (module), 1155
bge.render (module), 1169
bge.types (module), 1083
bias (bpy.types.WorldLighting attribute), 1017
billboard_align (bpy.types.ParticleSettings attribute), 651
billboard_animation (bpy.types.ParticleSettings attribute), 651
billboard_normal_uv (bpy.types.ParticleSystem attribute), 666
billboard_object (bpy.types.ParticleSettings attribute), 651
billboard_offset (bpy.types.ParticleSettings attribute), 651
billboard_offset_split (bpy.types.ParticleSettings attribute), 651
billboard_split_uv (bpy.types.ParticleSystem attribute), 666
billboard_tilt (bpy.types.ParticleSettings attribute), 651
billboard_tilt_random (bpy.types.ParticleSettings attribute), 651
billboard_time_index_uv (bpy.types.ParticleSystem attribute), 666
billboard_uv_split (bpy.types.ParticleSettings attribute), 651
binary_path (in module bpy.app), 1032
birth_time (bpy.types.Particle attribute), 639
BKEY (in module bge.events), 1173
BL_ActionActuator (class in bge.types), 1086
BL_ArmatureActuator (class in bge.types), 1144
BL_ArmatureActuator.KX_ACT_ARMATURE_DISABLE (in module bge.types), 1145
BL_ArmatureActuator.KX_ACT_ARMATURE_ENABLE (in module bge.types), 1145
BL_ArmatureActuator.KX_ACT_ARMATURE_RUN (in module bge.types), 1144

BL_ArmatureActuator.KX_ACT_ARMATURE_SETTARGET (in module bge.types), 1145
BL_ArmatureActuator.KX_ACT_ARMATURE_SETWEIGHT (in module bge.types), 1145
BL_ArmatureBone (class in bge.types), 1153
BL_ArmatureChannel (class in bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_QUAT (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_XYZ (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_XZY (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_YXZ (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_YZX (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_ZXY (in module bge.types), 1149
BL_ArmatureChannel.PCHAN_ROT_ZYX (in module bge.types), 1149
BL_ArmatureConstraint (class in bge.types), 1146
BL_ArmatureConstraint.CONSTRAINT_IK_COPYPOSE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_DISTANCE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_POS (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_ROT (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_STRETCH (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_TIP (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_MODE_INSIDE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_MODE_ONSURFACE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_IK_MODE_OUTSIDE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_CLAMPTO (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_DISTLIMIT (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_KINEMATIC (in module bge.types), 1146
BL_ArmatureConstraint.CONSTRAINT_TYPE_LOCKTRACK (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_LOCLIKE (in module bge.types), 1146
BL_ArmatureConstraint.CONSTRAINT_TYPE_MINMAX (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_ROTLIKE (in module bge.types), 1146
BL_ArmatureConstraint.CONSTRAINT_TYPE_SIZELIKE (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_STRETCHTO (in module bge.types), 1147
BL_ArmatureConstraint.CONSTRAINT_TYPE_TRACKTO (in module bge.types), 1146
BL_ArmatureConstraint.CONSTRAINT_TYPE_TRANSFORM (in module bge.types), 1147
BL_ArmatureObject (class in bge.types), 1144
bl_context (bpy.types.Panel attribute), 637
bl_description (bpy.types.Macro attribute), 502
bl_description (bpy.types.Operator attribute), 625
BL_DST_ALPHA (in module bge.logic), 1168
BL_DST_COLOR (in module bge.logic), 1168
bl_idname (bpy.types.Header attribute), 431
bl_idname (bpy.types.KeyingSetInfo attribute), 476
bl_idname (bpy.types.Macro attribute), 502
bl_idname (bpy.types.Menu attribute), 535
bl_idname (bpy.types.Operator attribute), 626
bl_idname (bpy.types.Panel attribute), 637
bl_idname (bpy.types.RenderEngine attribute), 712
bl_label (bpy.types.KeyingSetInfo attribute), 476
bl_label (bpy.types.Macro attribute), 502
bl_label (bpy.types.Menu attribute), 535
bl_label (bpy.types.Operator attribute), 626
bl_label (bpy.types.Panel attribute), 637
bl_label (bpy.types.RenderEngine attribute), 712
BL_ONE (in module bge.logic), 1168
BL_ONE_MINUS_DST_ALPHA (in module bge.logic), 1168
BL_ONE_MINUS_DST_COLOR (in module bge.logic), 1168
BL_ONE_MINUS_SRC_ALPHA (in module bge.logic), 1168
BL_ONE_MINUS_SRC_COLOR (in module bge.logic), 1168
bl_options (bpy.types.KeyingSet attribute), 475
bl_options (bpy.types.KeyingSetInfo attribute), 476
bl_options (bpy.types.KeyingSetPath attribute), 477
bl_options (bpy.types.Macro attribute), 502
bl_options (bpy.types.Operator attribute), 626
bl_options (bpy.types.Panel attribute), 637
bl_region_type (bpy.types.Panel attribute), 637
BL_Shader (class in bge.types), 1087
BL_ShapeActionActuator (class in bge.types), 1090
bl_space_type (bpy.types.Header attribute), 431
bl_space_type (bpy.types.Panel attribute), 637
BL_SRC_ALPHA (in module bge.logic), 1168
BL_SRC_ALPHA_SATURATE (in module bge.logic), 1168
BL_SRC_COLOR (in module bge.logic), 1168
bl_use_postprocess (bpy.types.RenderEngine attribute), 712
bl_use_preview (bpy.types.RenderEngine attribute), 712

BL_ZERO (in module bge.logic), 1168
black_level (bpy.types.CurveMapping attribute), 337
blend (bpy.types.Brush attribute), 227
blend (bpy.types.ThemeWidgetStateColors attribute), 934
blend_alpha (bpy.types.Sequence attribute), 759
blend_distance (bpy.types.MaterialStrand attribute), 523
blend_factor (bpy.types.WorldTextureSlot attribute), 1021
blend_from_shape() (in module bpy.ops.mesh), 48
blend_in (bpy.types.NlaStrip attribute), 590
blend_out (bpy.types.NlaStrip attribute), 590
blend_paths() (in module bpy.utils), 1029
blend_type (bpy.types.CompositorNodeMixRGB attribute), 294
blend_type (bpy.types.FModifierNoise attribute), 390
blend_type (bpy.types.MeshTextureFace attribute), 554
blend_type (bpy.types.NlaStrip attribute), 590
blend_type (bpy.types.Sequence attribute), 759
blend_type (bpy.types.ShaderNodeMixRGB attribute), 776
blend_type (bpy.types.TextureNodeMixRGB attribute), 884
blend_type (bpy.types.TextureSlot attribute), 893
BlendData (class in bpy.types), 179
BlendData.actions (in module bpy.types), 179
BlendData.armatures (in module bpy.types), 179
BlendData.brushes (in module bpy.types), 180
BlendData.cameras (in module bpy.types), 180
BlendData.curves (in module bpy.types), 180
BlendData.filepath (in module bpy.types), 180
BlendData.fonts (in module bpy.types), 180
BlendData.grease_pencil (in module bpy.types), 180
BlendData.groups (in module bpy.types), 180
BlendData.images (in module bpy.types), 180
BlendData.is_dirty (in module bpy.types), 180
BlendData.lamps (in module bpy.types), 180
BlendData.lattices (in module bpy.types), 180
BlendData.libraries (in module bpy.types), 180
BlendData.materials (in module bpy.types), 180
BlendData.meshes (in module bpy.types), 181
BlendData.metaballs (in module bpy.types), 181
BlendData.node_groups (in module bpy.types), 181
BlendData.objects (in module bpy.types), 181
BlendData.particles (in module bpy.types), 181
BlendData.scenes (in module bpy.types), 181
BlendData.screens (in module bpy.types), 181
BlendData.scripts (in module bpy.types), 181
BlendData.shape_keys (in module bpy.types), 181
BlendData.sounds (in module bpy.types), 181
BlendData.texts (in module bpy.types), 181
BlendData.textures (in module bpy.types), 181
BlendData.window_managers (in module bpy.types), 181
BlendData.worlds (in module bpy.types), 181
BlendDataActions (class in bpy.types), 182
BlendDataArmatures (class in bpy.types), 183
BlendDataBrushes (class in bpy.types), 184
BlendDataCameras (class in bpy.types), 185
BlendDataCurves (class in bpy.types), 186
BlendDataFonts (class in bpy.types), 187
BlendDataGreasePencils (class in bpy.types), 188
BlendDataGroups (class in bpy.types), 189
BlendDataImages (class in bpy.types), 190
BlendDataLamps (class in bpy.types), 191
BlendDataLattices (class in bpy.types), 192
BlendDataLibraries (class in bpy.types), 193
BlendDataMaterials (class in bpy.types), 194
BlendDataMeshes (class in bpy.types), 195
BlendDataMetaBalls (class in bpy.types), 196
BlendDataNodeTrees (class in bpy.types), 197
BlendDataObjects (class in bpy.types), 198
BlendDataParticles (class in bpy.types), 199
BlendDataScenes (class in bpy.types), 200
BlendDataScreens (class in bpy.types), 201
BlendDataSounds (class in bpy.types), 202
BlendDataTexts (class in bpy.types), 203
BlendDataTextures (class in bpy.types), 204
BlendDataWindowManagers (class in bpy.types), 205
BlendDataWorlds (class in bpy.types), 206
BlenderRNA (class in bpy.types), 208
BlenderRNA.structs (in module bpy.types), 208
blendIn (bge.types.BL_ActionActuator attribute), 1086
blendIn (bge.types.BL_ShapeActionActuator attribute), 1090
BlendTexture (class in bpy.types), 207
BlendTexture.users_material (in module bpy.types), 207
BlendTexture.users_object_modifier (in module bpy.types), 207
blendTime (bge.types.BL_ActionActuator attribute), 1086
blendTime (bge.types.BL_ShapeActionActuator attribute), 1091
blf (module), 1071
blur() (in module blf), 1071
blur_max (bpy.types.CompositorNodeDefocus attribute), 277
blur_radius (bpy.types.GlowSequence attribute), 424
blur_width (bpy.types.WipeSequence attribute), 1011
bodies (bge.types.KX_NetworkMessageSensor attribute), 1110
body (bge.types.KX_NetworkMessageActuator attribute), 1110
body (bpy.types.ConsoleLine attribute), 316
body (bpy.types.TextCurve attribute), 867
body (bpy.types.TextLine attribute), 870
body_message (bpy.types.MessageActuator attribute), 559
body_property (bpy.types.MessageActuator attribute), 560

body_type (bpy.types.MessageActuator attribute), 560
boid (bpy.types.EffectorWeights attribute), 365
BoidRule (class in bpy.types), 209
BoidRule.type (in module bpy.types), 209
BoidRuleAverageSpeed (class in bpy.types), 210
BoidRuleAvoid (class in bpy.types), 211
BoidRuleAvoidCollision (class in bpy.types), 212
BoidRuleFight (class in bpy.types), 212
BoidRuleFollowLeader (class in bpy.types), 213
BoidRuleGoal (class in bpy.types), 214
BoidSettings (class in bpy.types), 215
BoidSettings.active_boid_state (in module bpy.types), 215
BoidSettings.states (in module bpy.types), 217
BoidState (class in bpy.types), 218
BoidState.active_boid_rule (in module bpy.types), 218
BoidState.rules (in module bpy.types), 218
bokeh (bpy.types.CompositorNodeDefocus attribute), 277
bone (bge.types.BL_ArmatureChannel attribute), 1149
bone (bpy.types.ArmatureActuator attribute), 168
bone (bpy.types.ArmatureSensor attribute), 172
Bone (class in bpy.types), 219
bone (in module bpy.context), 6
Bone.basename (in module bpy.types), 221
Bone.center (in module bpy.types), 221
Bone.children (in module bpy.types), 219, 221
Bone.children_recursive (in module bpy.types), 221
Bone.children_recursive_basename (in module bpy.types), 221
Bone.parent (in module bpy.types), 220
Bone.parent_recursive (in module bpy.types), 221
Bone.use_connect (in module bpy.types), 221
Bone.vector (in module bpy.types), 221
Bone.x_axis (in module bpy.types), 222
Bone.y_axis (in module bpy.types), 222
Bone.z_axis (in module bpy.types), 222
bone_group (bpy.types.PoseBone attribute), 687
bone_group_index (bpy.types.PoseBone attribute), 687
bone_layers() (in module bpy.ops.armature), 14
bone_layers() (in module bpy.ops.pose), 88
bone_mat (bge.types.BL_ArmatureBone attribute), 1154
bone_pose (bpy.types.ThemeView3D attribute), 929
bone_primitive_add() (in module bpy.ops.armature), 14
bone_solid (bpy.types.ThemeView3D attribute), 929
bone_target (bpy.types.DriverTarget attribute), 352
BoneGroup (class in bpy.types), 223
BoneGroup.colors (in module bpy.types), 223
BoneGroups (class in bpy.types), 224
bookmark_add() (in module bpy.ops.file), 29
bookmark_toggle() (in module bpy.ops.file), 29
BooleanModifier (class in bpy.types), 225
BooleanProperty (class in bpy.types), 225
BooleanProperty.array_length (in module bpy.types), 225
BooleanProperty.default (in module bpy.types), 226
BooleanProperty.default_array (in module bpy.types), 226
BoolProperty() (in module bpy.props), 1034
BoolVectorProperty() (in module bpy.props), 1034
boost_factor (bpy.types.GlowSequence attribute), 424
border_max_x (bpy.types.RenderSettings attribute), 721
border_max_y (bpy.types.RenderSettings attribute), 721
border_min_x (bpy.types.RenderSettings attribute), 721
border_min_y (bpy.types.RenderSettings attribute), 721
box() (bpy.types.UILayout method), 949
box_pack_2d() (in module mathutils.geometry), 1069
boxInsideFrustum() (bge.types.KX_Camera method), 1142
bpy (module), 7
bpy.app (module), 1031
bpy.context (module), 3
bpy.ops.action (module), 8
bpy.ops.anim (module), 11
bpy.ops.armature (module), 14
bpy.ops.boid (module), 17
bpy.ops.brush (module), 17
bpy.ops.buttons (module), 18
bpy.ops.cloth (module), 18
bpy.ops.console (module), 19
bpy.ops.constraint (module), 20
bpy.ops.curve (module), 21
bpy.ops.ed (module), 25
bpy.ops.export_anim (module), 25
bpy.ops.export_mesh (module), 25
bpy.ops.export_scene (module), 26
bpy.ops.file (module), 29
bpy.ops.fluid (module), 31
bpy.ops.font (module), 31
bpy.ops.gpencil (module), 33
bpy.ops.graph (module), 34
bpy.ops.group (module), 38
bpy.ops.help (module), 38
bpy.ops.image (module), 38
bpy.ops.import_anim (module), 42
bpy.ops.import_mesh (module), 43
bpy.ops.import_scene (module), 43
bpy.ops.info (module), 44
bpy.ops.lamp (module), 45
bpy.ops.lattice (module), 45
bpy.ops.logic (module), 45
bpy.ops.marker (module), 47
bpy.ops.material (module), 47
bpy.ops.mball (module), 48
bpy.ops.mesh (module), 48
bpy.ops.nla (module), 60
bpy.ops.node (module), 63
bpy.ops.object (module), 66
bpy.ops.outliner (module), 81

bpy.ops.paint (module), 83
bpy.ops.particle (module), 86
bpy.ops.pose (module), 88
bpy.ops.poselib (module), 91
bpy.ops.ptcache (module), 92
bpy.ops.render (module), 92
bpy.ops.scene (module), 94
bpy.ops.screen (module), 94
bpy.ops.script (module), 97
bpy.ops.sculpt (module), 98
bpy.ops.sequencer (module), 98
bpy.ops.sketch (module), 104
bpy.ops.sound (module), 105
bpy.ops.surface (module), 106
bpy.ops.text (module), 108
bpy.ops.texture (module), 112
bpy.ops.time (module), 113
bpy.ops.transform (module), 113
bpy.ops.ui (module), 122
bpy.ops.uv (module), 122
bpy.ops.view2d (module), 127
bpy.ops.view3d (module), 129
bpy.ops.wm (module), 132
bpy.ops.world (module), 142
bpy.path (module), 1030
bpy.props (module), 1032
bpy.types (module), 142, 144–147, 149, 150, 152–158, 160–163, 166, 168–172, 174, 175, 177–179, 182–215, 218, 219, 223–225, 227, 232–234, 237–240, 242, 243, 245, 246, 248, 250–254, 256, 257, 259–283, 285–317, 319, 322, 324, 325, 327, 328, 330–332, 335–337, 339–343, 345, 346, 349, 351, 352, 354–356, 360, 362, 365, 367–370, 372, 374–376, 378, 380–393, 397, 399, 400, 402–409, 411–416, 419, 420, 422, 423, 425, 427–435, 437, 438, 442, 444, 446, 450–453, 455, 456, 458–461, 463, 466, 469, 471, 473, 475–478, 480, 481, 484, 486, 488–490, 492–496, 498, 499, 501–503, 505–508, 515, 518–520, 522–524, 526, 531, 532, 534, 536, 541–544, 546–554, 556, 557, 559–561, 563–565, 568, 570–574, 577, 579, 581, 583–586, 589, 592–601, 603, 614, 617–621, 628–635, 638, 639, 641–643, 645–647, 649, 650, 662, 665, 666, 670–674, 676, 677, 679, 680, 682, 683, 685–687, 692, 693, 695, 696, 698–704, 706–709, 711, 714, 718–721, 730, 733, 735, 739–741, 744, 745, 749, 752, 753, 755–757, 759, 762–773, 775–789, 791–794, 796–798, 800–804, 808, 809, 811, 812, 814–818, 820, 822–826, 828–830, 832, 833, 835, 836, 839, 841, 843–845, 847, 851–855, 857, 858, 860–863, 865–867, 870–872, 874–893, 895, 897–899, 901, 903, 905, 906, 909, 911–913, 915, 917, 918, 920, 922, 923, 925, 926, 928, 929, 933–937, 941–943, 946–948, 971, 973–977, 981, 983, 985, 988, 991–1001, 1003, 1004, 1006, 1008, 1009, 1011, 1013, 1015, 1017, 1019–1021, 1023–1025
bpy.utils (module), 1029
bpy_struct (class in bpy.types), 1026
branch_threshold (bpy.types.ParticleSettings attribute), 651
breakdown() (in module bpy.ops.pose), 88
brownian_factor (bpy.types.ParticleSettings attribute), 651
browse_interactive() (in module bpy.ops.poselib), 91
brush (bpy.types.Paint attribute), 634
Brush (class in bpy.types), 227
brush (in module bpy.context), 6
Brush.curve (in module bpy.types), 227
Brush.texture_slot (in module bpy.types), 229
brush_edit() (in module bpy.ops.particle), 86
brush_radial_control() (in module bpy.ops.particle), 86
brush_stroke() (in module bpy.ops.sculpt), 98
BrushTextureSlot (class in bpy.types), 232
buffer_paste() (in module bpy.ops.font), 31
build_cflags (in module bpy.app), 1032
build_cxxflags (in module bpy.app), 1032
build_date (in module bpy.app), 1032
build_linkflags (in module bpy.app), 1032
build_platform (in module bpy.app), 1032
build_revision (in module bpy.app), 1032
build_system (in module bpy.app), 1032
build_time (in module bpy.app), 1032
build_type (in module bpy.app), 1032
BuildModifier (class in bpy.types), 233
bulge (bpy.types.StretchToConstraint attribute), 852
bump_method (bpy.types.MaterialTextureSlot attribute), 526
bump_objectspace (bpy.types.MaterialTextureSlot attribute), 526
buoyancy (bpy.types.SPHFluidSettings attribute), 733
button (bge.types.SCA_JoystickSensor attribute), 1135
button (bpy.types.ThemeAudioWindow attribute), 897
button (bpy.types.ThemeConsole attribute), 899
button (bpy.types.ThemeDopeSheet attribute), 901
button (bpy.types.ThemeFileBrowser attribute), 903
button (bpy.types.ThemeGraphEditor attribute), 906
button (bpy.types.ThemeImageEditor attribute), 909
button (bpy.types.ThemeInfo attribute), 911
button (bpy.types.ThemeLogicEditor attribute), 912
button (bpy.types.ThemeNLAEditor attribute), 913
button (bpy.types.ThemeNodeEditor attribute), 915
button (bpy.types.ThemeOutliner attribute), 917
button (bpy.types.ThemeProperties attribute), 919
button (bpy.types.ThemeSequenceEditor attribute), 920
button (bpy.types.ThemeTextEditor attribute), 923

button (bpy.types.ThemeTimeline attribute), 925
button (bpy.types.ThemeUserPreferences attribute), 928
button (bpy.types.ThemeView3D attribute), 929
button_number (bpy.types.JoystickSensor attribute), 456
button_text (bpy.types.ThemeAudioWindow attribute), 897
button_text (bpy.types.ThemeConsole attribute), 899
button_text (bpy.types.ThemeDopeSheet attribute), 901
button_text (bpy.types.ThemeFileBrowser attribute), 903
button_text (bpy.types.ThemeGraphEditor attribute), 906
button_text (bpy.types.ThemeImageEditor attribute), 909
button_text (bpy.types.ThemeInfo attribute), 911
button_text (bpy.types.ThemeLogicEditor attribute), 912
button_text (bpy.types.ThemeNLAEditor attribute), 913
button_text (bpy.types.ThemeNodeEditor attribute), 915
button_text (bpy.types.ThemeOutliner attribute), 917
button_text (bpy.types.ThemeProperties attribute), 919
button_text (bpy.types.ThemeSequenceEditor attribute), 920
button_text (bpy.types.ThemeTextEditor attribute), 923
button_text (bpy.types.ThemeTimeline attribute), 925
button_text (bpy.types.ThemeUserPreferences attribute), 928
button_text (bpy.types.ThemeView3D attribute), 929
button_text_hi (bpy.types.ThemeAudioWindow attribute), 897
button_text_hi (bpy.types.ThemeConsole attribute), 899
button_text_hi (bpy.types.ThemeDopeSheet attribute), 901
button_text_hi (bpy.types.ThemeFileBrowser attribute), 903
button_text_hi (bpy.types.ThemeGraphEditor attribute), 906
button_text_hi (bpy.types.ThemeImageEditor attribute), 909
button_text_hi (bpy.types.ThemeInfo attribute), 911
button_text_hi (bpy.types.ThemeLogicEditor attribute), 912
button_text_hi (bpy.types.ThemeNLAEditor attribute), 914
button_text_hi (bpy.types.ThemeNodeEditor attribute), 915
button_text_hi (bpy.types.ThemeOutliner attribute), 917
button_text_hi (bpy.types.ThemeProperties attribute), 919
button_text_hi (bpy.types.ThemeSequenceEditor attribute), 920
button_text_hi (bpy.types.ThemeTextEditor attribute), 923
button_text_hi (bpy.types.ThemeTimeline attribute), 925
button_text_hi (bpy.types.ThemeUserPreferences attribute), 928
button_text_hi (bpy.types.ThemeView3D attribute), 929
button_title (bpy.types.ThemeAudioWindow attribute), 897
button_title (bpy.types.ThemeConsole attribute), 899
button_title (bpy.types.ThemeDopeSheet attribute), 901
button_title (bpy.types.ThemeFileBrowser attribute), 903
button_title (bpy.types.ThemeGraphEditor attribute), 906
button_title (bpy.types.ThemeImageEditor attribute), 909
button_title (bpy.types.ThemeInfo attribute), 911
button_title (bpy.types.ThemeLogicEditor attribute), 912
button_title (bpy.types.ThemeNLAEditor attribute), 914
button_title (bpy.types.ThemeNodeEditor attribute), 915
button_title (bpy.types.ThemeOutliner attribute), 917
button_title (bpy.types.ThemeProperties attribute), 919
button_title (bpy.types.ThemeSequenceEditor attribute), 920
button_title (bpy.types.ThemeTextEditor attribute), 923
button_title (bpy.types.ThemeTimeline attribute), 925
button_title (bpy.types.ThemeUserPreferences attribute), 928
button_title (bpy.types.ThemeView3D attribute), 929
bvh() (in module bpy.ops.export_anim), 25
bvh() (in module bpy.ops.import_anim), 42

C

cache_cloth (bpy.types.SpaceTimeline attribute), 832
cache_particles (bpy.types.SpaceTimeline attribute), 832
cache_resolution (bpy.types.MaterialVolume attribute), 532
cache_smoke (bpy.types.SpaceTimeline attribute), 832
cache_softbody (bpy.types.SpaceTimeline attribute), 832
calc_normals() (bpy.types.Mesh method), 540
calculate_roll() (in module bpy.ops.armature), 15
call_menu() (in module bpy.ops.wm), 133
CAM_POS (in module bge.logic), 1168
camera (bge.types.KX_SceneActuator attribute), 1126
camera (bpy.types.Scene attribute), 735
camera (bpy.types.SceneActuator attribute), 739
camera (bpy.types.SpaceView3D attribute), 836
camera (bpy.types.TimelineMarker attribute), 935
Camera (class in bpy.types), 234
camera (in module bpy.context), 6
Camera.animation_data (in module bpy.types), 234
camera_add() (in module bpy.ops.object), 67
camera_bind() (in module bpy.ops.marker), 47
camera_to_view() (in module bpy.ops.view3d), 129
camera_to_world (bge.types.KX_Camera attribute), 1141
CameraActuator (class in bpy.types), 237
cameras (bge.types.KX_Scene attribute), 1124
cancel() (in module bpy.ops.file), 29
cancel_stroke() (in module bpy.ops.sketch), 104
CAPSLOCKKEY (in module bge.events), 1174
case_set() (in module bpy.ops.font), 31
case_toggle() (in module bpy.ops.font), 31
cast_type (bpy.types.CastModifier attribute), 238
CastModifier (class in bpy.types), 238

center_x (bpy.types.CompositorNodeDBlur attribute), 276
center_y (bpy.types.CompositorNodeDBlur attribute), 276
chain_count (bpy.types.KinematicConstraint attribute), 481
chain_count (bpy.types.SplineIKConstraint attribute), 844
chance (bpy.types.RandomActuator attribute), 704
change_character() (in module bpy.ops.font), 31
change_frame() (in module bpy.ops.anim), 11
change_spacing() (in module bpy.ops.font), 31
channel (bpy.types.CompositorNodeColorSpill attribute), 268
channel (bpy.types.CompositorNodeLevels attribute), 290
channel (bpy.types.Sequence attribute), 759
channel_group (bpy.types.ThemeDopeSheet attribute), 901
channel_group (bpy.types.ThemeGraphEditor attribute), 906
channel_matrix (bge.types.BL_ArmatureChannel attribute), 1151
ChannelDriverVariables (class in bpy.types), 239
channelNames (bge.types.BL_ActionActuator attribute), 1086
channels (aud.Device attribute), 1075
channels (bge.types.BL_ArmatureObject attribute), 1144
channels (bpy.types.ThemeDopeSheet attribute), 901
channels_click() (in module bpy.ops.anim), 11
channels_click() (in module bpy.ops.nla), 61
channels_collapse() (in module bpy.ops.anim), 11
channels_delete() (in module bpy.ops.anim), 11
channels_editable_toggle() (in module bpy.ops.anim), 11
channels_expand() (in module bpy.ops.anim), 11
channels_fcurves_enable() (in module bpy.ops.anim), 11
channels_move() (in module bpy.ops.anim), 11
channels_region (bpy.types.ThemeGraphEditor attribute), 906
channels_select_all_toggle() (in module bpy.ops.anim), 11
channels_select_border() (in module bpy.ops.anim), 11
channels_selected (bpy.types.ThemeDopeSheet attribute), 901
channels_setting_disable() (in module bpy.ops.anim), 12
channels_setting_enable() (in module bpy.ops.anim), 12
channels_setting_toggle() (in module bpy.ops.anim), 12
channels_visibility_set() (in module bpy.ops.anim), 12
channels_visibility_toggle() (in module bpy.ops.anim), 12
charge (bpy.types.EffectorWeights attribute), 365
check() (bpy.types.Operator method), 626
checker_distance (bpy.types.ImageTexture attribute), 446
child (bpy.types.RigidBodyJointConstraint attribute), 730
child_length (bpy.types.ParticleSettings attribute), 651
child_length_threshold (bpy.types.ParticleSettings attribute), 651
child_nbr (bpy.types.ParticleSettings attribute), 651
child_parting_factor (bpy.types.ParticleSettings attribute), 652
child_parting_max (bpy.types.ParticleSettings attribute), 652
child_parting_min (bpy.types.ParticleSettings attribute), 652
child_radius (bpy.types.ParticleSettings attribute), 652
child_roundness (bpy.types.ParticleSettings attribute), 652
child_seed (bpy.types.ParticleSystem attribute), 666
child_size (bpy.types.ParticleSettings attribute), 652
child_size_random (bpy.types.ParticleSettings attribute), 652
child_type (bpy.types.ParticleSettings attribute), 652
childof_clear_inverse() (in module bpy.ops.constraint), 20
childof_set_inverse() (in module bpy.ops.constraint), 20
ChildOfConstraint (class in bpy.types), 240
ChildParticle (class in bpy.types), 242
children (bge.types.BL_ArmatureBone attribute), 1155
children (bge.types.KX_GameObject attribute), 1097
childrenRecursive (bge.types.KX_GameObject attribute), 1097
choke (bpy.types.SoftBodySettings attribute), 804
chunks (bpy.types.NetRenderSettings attribute), 586
cineon_black (bpy.types.RenderSettings attribute), 722
cineon_gamma (bpy.types.RenderSettings attribute), 722
cineon_white (bpy.types.RenderSettings attribute), 722
circle_select() (in module bpy.ops.uv), 122
CKEY (in module bge.events), 1173
clamp (bpy.types.GlowSequence attribute), 424
ClampToConstraint (class in bpy.types), 242
clean() (in module bpy.ops.action), 8
clean() (in module bpy.ops.graph), 34
clean_name() (in module bpy.path), 1031
clear() (bpy.types.KeyingSetPaths method), 479
clear() (bpy.types.LampTextureSlots class method), 489
clear() (bpy.types.MaterialTextureSlots class method), 531
clear() (bpy.types.ParticleSettingsTextureSlots class method), 665
clear() (bpy.types.Text method), 864
clear() (bpy.types.WorldTextureSlots class method), 1023
clear() (in module bpy.ops.console), 19
clear_scale() (in module bpy.ops.nla), 61
click_extrude() (in module bpy.ops.armature), 15
click_insert() (in module bpy.ops.graph), 34
click_select() (in module bpy.ops.nla), 61
clickselect() (in module bpy.ops.action), 8
clickselect() (in module bpy.ops.graph), 34
clip_border() (in module bpy.ops.view3d), 129

clip_end (bpy.types.Camera attribute), 234
clip_end (bpy.types.EnvironmentMap attribute), 369
clip_end (bpy.types.SpaceView3D attribute), 836
clip_max_x (bpy.types.CurveMapping attribute), 337
clip_max_y (bpy.types.CurveMapping attribute), 337
clip_min_x (bpy.types.CurveMapping attribute), 337
clip_min_y (bpy.types.CurveMapping attribute), 337
clip_start (bpy.types.Camera attribute), 235
clip_start (bpy.types.EnvironmentMap attribute), 369
clip_start (bpy.types.SpaceView3D attribute), 836
clipboard (bpy.types.WindowManager attribute), 1009
CLIPPING (in module blf), 1071
clipping() (in module blf), 1071
CListValue (class in bge.types), 1091
clone_alpha (bpy.types.Brush attribute), 227
clone_cursor_set() (in module bpy.ops.paint), 83
clone_image (bpy.types.Brush attribute), 227
clone_offset (bpy.types.Brush attribute), 227
cloth (in module bpy.context), 6
ClothCollisionSettings (class in bpy.types), 243
ClothModifier (class in bpy.types), 245
ClothModifier.collision_settings (in module bpy.types), 245
ClothModifier.point_cache (in module bpy.types), 245
ClothModifier.settings (in module bpy.types), 245
ClothSettings (class in bpy.types), 246
ClothSettings.effector_weights (in module bpy.types), 246
cloud_type (bpy.types.CloudsTexture attribute), 248
CloudsTexture (class in bpy.types), 248
CloudsTexture.users_material (in module bpy.types), 249
CloudsTexture.users_object_modifier (in module bpy.types), 249
clump_factor (bpy.types.ParticleSettings attribute), 652
clump_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
clump_shape (bpy.types.ParticleSettings attribute), 652
cluster_iterations (bpy.types.GameSoftBodySettings attribute), 420
co (bpy.types.BezierSplinePoint attribute), 178
co (bpy.types.FCurveSample attribute), 382
co (bpy.types.GPencilStrokePoint attribute), 412
co (bpy.types.Keyframe attribute), 473
co (bpy.types.MeshSticky attribute), 552
co (bpy.types.MeshVertex attribute), 558
co (bpy.types.MetaElement attribute), 564
co (bpy.types.MotionPathVert attribute), 572
co (bpy.types.ParticleHairKey attribute), 646
co (bpy.types.ShapeKeyBezierPoint attribute), 791
co (bpy.types.ShapeKeyCurvePoint attribute), 791
co (bpy.types.ShapeKeyPoint attribute), 792
co (bpy.types.SplinePoint attribute), 845
co_deform (bpy.types.LatticePoint attribute), 493
co_hair_space (bpy.types.ParticleHairKey attribute), 646
coefficients (bpy.types.FModifierGenerator attribute), 388
col_size (mathutils.Matrix attribute), 1045
CollectionProperty (class in bpy.types), 250
CollectionProperty() (in module bpy.props), 1035
CollectionProperty.fixed_type (in module bpy.types), 250
collide (bge.types.KX_PolyProxy attribute), 1114
collider_friction (bpy.types.ClothSettings attribute), 246
collision (in module bpy.context), 6
collision_bounds_type (bpy.types.GameObjectSettings attribute), 416
collision_extents (bpy.types.SmokeDomainSettings attribute), 798
collision_group (bpy.types.SmokeDomainSettings attribute), 798
collision_margin (bpy.types.GameObjectSettings attribute), 416
collision_margin (bpy.types.GameSoftBodySettings attribute), 421
collision_quality (bpy.types.ClothCollisionSettings attribute), 243
collision_type (bpy.types.SoftBodySettings attribute), 804
CollisionModifier (class in bpy.types), 251
CollisionModifier.settings (in module bpy.types), 251
CollisionSensor (class in bpy.types), 252
CollisionSettings (class in bpy.types), 253
color (bge.types.KX_GameObject attribute), 1095
color (bge.types.KX_LightObject attribute), 1106
color (bge.types.KX_VertexProxy attribute), 1130
color (bpy.types.Brush attribute), 227
color (bpy.types.ColorRampElement attribute), 256
color (bpy.types.ColorSequence attribute), 257
color (bpy.types.FCurve attribute), 376
color (bpy.types.GPencilLayer attribute), 410
color (bpy.types.Lamp attribute), 484
color (bpy.types.MaterialSubsurfaceScattering attribute), 524
color (bpy.types.Object attribute), 604
color (bpy.types.TextMarker attribute), 871
color (bpy.types.TextureSlot attribute), 893
Color (class in mathutils), 1039
Color.copy() (in module mathutils), 1039
color1 (bpy.types.MeshColor attribute), 541
color2 (bpy.types.MeshColor attribute), 541
color3 (bpy.types.MeshColor attribute), 541
color4 (bpy.types.MeshColor attribute), 542
color_factor (bpy.types.LampTextureSlot attribute), 488
color_factor (bpy.types.MaterialSubsurfaceScattering attribute), 524
color_hue (bpy.types.CompositorNodeColorMatte attribute), 267
color_hue (bpy.types.CompositorNodeHueSat attribute), 286

color_layer (bpy.types.ShaderNodeGeometry attribute), 771
color_maximum (bpy.types.ParticleSettings attribute), 652
color_mode (bpy.types.FCurve attribute), 376
color_mode (bpy.types.RenderSettings attribute), 722
color_mode (bpy.types.VoronoiTexture attribute), 1001
color_modulation (bpy.types.CompositorNodeGlare attribute), 284
color_multiply (bpy.types.EffectSequence attribute), 362
color_multiply (bpy.types.ImageSequence attribute), 444
color_multiply (bpy.types.MetaSequence attribute), 566
color_multiply (bpy.types.MovieSequence attribute), 574
color_multiply (bpy.types.MulticamSequence attribute), 577
color_multiply (bpy.types.SceneSequence attribute), 749
color_picker_type (bpy.types.UserPreferencesSystem attribute), 986
color_random (bpy.types.WorldStarsSettings attribute), 1020
color_range (bpy.types.World attribute), 1015
color_saturation (bpy.types.CompositorNodeColorMatte attribute), 267
color_saturation (bpy.types.CompositorNodeHueSat attribute), 286
color_saturation (bpy.types.EffectSequence attribute), 362
color_saturation (bpy.types.ImageSequence attribute), 444
color_saturation (bpy.types.MetaSequence attribute), 566
color_saturation (bpy.types.MovieSequence attribute), 574
color_saturation (bpy.types.MulticamSequence attribute), 577
color_saturation (bpy.types.SceneSequence attribute), 749
color_set (bpy.types.BoneGroup attribute), 223
color_source (bpy.types.PointDensity attribute), 680
color_space (bpy.types.CompositorNodeChannelMatte attribute), 264
color_value (bpy.types.CompositorNodeColorMatte attribute), 267
color_value (bpy.types.CompositorNodeHueSat attribute), 286
ColorRamp (class in bpy.types), 254
ColorRamp.elements (in module bpy.types), 254
ColorRampElement (class in bpy.types), 256
ColorRampElements (class in bpy.types), 256
colors_mirror() (in module bpy.ops.mesh), 48
colors_rotate() (in module bpy.ops.mesh), 49
ColorSequence (class in bpy.types), 257
colour (bge.types.KX_LightObject attribute), 1105
colour (bge.types.KX_VertexProxy attribute), 1130
column() (bpy.types.UILayout method), 949
column_flow() (bpy.types.UILayout method), 949
COMMAKEY (in module bge.events), 1176
comment() (in module bpy.ops.text), 108
compare() (bpy.types.KeyMapItem method), 465
CompositorNode (class in bpy.types), 259
CompositorNode.type (in module bpy.types), 259
CompositorNodeAlphaOver (class in bpy.types), 260
CompositorNodeBilateralblur (class in bpy.types), 261
CompositorNodeBlur (class in bpy.types), 262
CompositorNodeBrightContrast (class in bpy.types), 263
CompositorNodeChannelMatte (class in bpy.types), 264
CompositorNodeChromaMatte (class in bpy.types), 265
CompositorNodeColorBalance (class in bpy.types), 266
CompositorNodeColorMatte (class in bpy.types), 267
CompositorNodeColorSpill (class in bpy.types), 268
CompositorNodeCombHSVA (class in bpy.types), 269
CompositorNodeCombRGBA (class in bpy.types), 270
CompositorNodeCombYCCA (class in bpy.types), 271
CompositorNodeCombYUVA (class in bpy.types), 271
CompositorNodeComposite (class in bpy.types), 272
CompositorNodeCrop (class in bpy.types), 273
CompositorNodeCurveRGB (class in bpy.types), 274
CompositorNodeCurveRGB.mapping (in module bpy.types), 274
CompositorNodeCurveVec (class in bpy.types), 275
CompositorNodeCurveVec.mapping (in module bpy.types), 275
CompositorNodeDBlur (class in bpy.types), 276
CompositorNodeDefocus (class in bpy.types), 277
CompositorNodeDiffMatte (class in bpy.types), 278
CompositorNodeDilateErode (class in bpy.types), 279
CompositorNodeDisplace (class in bpy.types), 280
CompositorNodeDistanceMatte (class in bpy.types), 280
CompositorNodeFilter (class in bpy.types), 281
CompositorNodeFlip (class in bpy.types), 282
CompositorNodeGamma (class in bpy.types), 283
CompositorNodeGlare (class in bpy.types), 283
CompositorNodeHueCorrect (class in bpy.types), 285
CompositorNodeHueCorrect.mapping (in module bpy.types), 285
CompositorNodeHueSat (class in bpy.types), 286
CompositorNodeIDMask (class in bpy.types), 287
CompositorNodeImage (class in bpy.types), 287
CompositorNodeInvert (class in bpy.types), 288
CompositorNodeLensdist (class in bpy.types), 289
CompositorNodeLevels (class in bpy.types), 290
CompositorNodeLumaMatte (class in bpy.types), 291
CompositorNodeMapUV (class in bpy.types), 292
CompositorNodeMapValue (class in bpy.types), 293
CompositorNodeMath (class in bpy.types), 294
CompositorNodeMixRGB (class in bpy.types), 294
CompositorNodeNormal (class in bpy.types), 295
CompositorNodeNormalize (class in bpy.types), 296
CompositorNodeOutputFile (class in bpy.types), 297

CompositorNodePremulKey (class in bpy.types), 298
CompositorNodeRGB (class in bpy.types), 298
CompositorNodeRGBToBW (class in bpy.types), 299
CompositorNodeRLayers (class in bpy.types), 300
CompositorNodeRotate (class in bpy.types), 301
CompositorNodes (class in bpy.types), 315
CompositorNodeScale (class in bpy.types), 301
CompositorNodeSepHSVA (class in bpy.types), 302
CompositorNodeSepRGBA (class in bpy.types), 303
CompositorNodeSepYCCA (class in bpy.types), 303
CompositorNodeSepYUVA (class in bpy.types), 304
CompositorNodeSetAlpha (class in bpy.types), 305
CompositorNodeSplitViewer (class in bpy.types), 306
CompositorNodeTexture (class in bpy.types), 306
CompositorNodeTime (class in bpy.types), 307
CompositorNodeTime.curve (in module bpy.types), 307
CompositorNodeTonemap (class in bpy.types), 308
CompositorNodeTranslate (class in bpy.types), 309
CompositorNodeTree (class in bpy.types), 310
CompositorNodeTree.nodes (in module bpy.types), 310
CompositorNodeValToRGB (class in bpy.types), 311
CompositorNodeValToRGB.color_ramp (in module bpy.types), 311
CompositorNodeValue (class in bpy.types), 312
CompositorNodeVecBlur (class in bpy.types), 312
CompositorNodeViewer (class in bpy.types), 313
CompositorNodeZcombine (class in bpy.types), 314
compound (bge.types.KX_ParentActuator attribute), 1112
compressibility (bpy.types.DomainFluidSettings attribute), 346
compression (bpy.types.PointCache attribute), 677
compression_threshold (bpy.types.SpotLamp attribute), 847
cone_angle_inner (aud.Handle attribute), 1080
cone_angle_outer (aud.Handle attribute), 1080
cone_inner_angle_3d (bpy.types.SoundActuator attribute), 811
cone_outer_angle_3d (bpy.types.SoundActuator attribute), 811
cone_outer_gain_3d (bpy.types.SoundActuator attribute), 811
cone_volume_outer (aud.Handle attribute), 1080
coneOrigin (bge.types.KX_RadarSensor attribute), 1120
coneTarget (bge.types.KX_RadarSensor attribute), 1120
connect_hair() (in module bpy.ops.particle), 86
connected (bge.types.BL_ArmatureBone attribute), 1154
connected (bge.types.SCA_JoystickSensor attribute), 1135
ConsoleLine (class in bpy.types), 316
constant_offset_displace (bpy.types.ArrayModifier attribute), 174
CONSTANT_TIMER (in module bge.logic), 1168
constraint (bge.types.BL_ArmatureActuator attribute), 1145
constraint (bge.types.KX_ArmatureSensor attribute), 1146
constraint (bpy.types.ArmatureActuator attribute), 168
constraint (bpy.types.ArmatureSensor attribute), 173
Constraint (class in bpy.types), 317
Constraint.error_location (in module bpy.types), 317
Constraint.error_rotation (in module bpy.types), 317
Constraint.is_valid (in module bpy.types), 317
Constraint.type (in module bpy.types), 318
constraint_add() (in module bpy.ops.object), 68
constraint_add() (in module bpy.ops.pose), 88
constraint_add_with_targets() (in module bpy.ops.object), 68
constraint_add_with_targets() (in module bpy.ops.pose), 88
ConstraintActuator (class in bpy.types), 319
constraints (bge.types.BL_ArmatureObject attribute), 1144
constraints_clear() (in module bpy.ops.object), 68
constraints_clear() (in module bpy.ops.pose), 89
constraints_copy() (in module bpy.ops.object), 68
constraints_copy() (in module bpy.ops.pose), 89
ConstraintTarget (class in bpy.types), 322
context (bpy.types.SpaceProperties attribute), 828
Context (class in bpy.types), 322
Context.area (in module bpy.types), 322
Context.blend_data (in module bpy.types), 322
Context.mode (in module bpy.types), 323
Context.region (in module bpy.types), 323
Context.region_data (in module bpy.types), 323
Context.scene (in module bpy.types), 323
Context.screen (in module bpy.types), 323
Context.space_data (in module bpy.types), 323
Context.tool_settings (in module bpy.types), 323
Context.user_preferences (in module bpy.types), 323
Context.window (in module bpy.types), 323
Context.window_manager (in module bpy.types), 323
context_cycle_array() (in module bpy.ops.wm), 133
context_cycle_enum() (in module bpy.ops.wm), 133
context_cycle_int() (in module bpy.ops.wm), 133
context_menu_enum() (in module bpy.ops.wm), 134
context_modal_mouse() (in module bpy.ops.wm), 134
context_pointer_set() (bpy.types.UILayout method), 967
context_scale_int() (in module bpy.ops.wm), 134
context_set_boolean() (in module bpy.ops.wm), 134
context_set_enum() (in module bpy.ops.wm), 134
context_set_float() (in module bpy.ops.wm), 134
context_set_id() (in module bpy.ops.wm), 135
context_set_int() (in module bpy.ops.wm), 135
context_set_string() (in module bpy.ops.wm), 135
context_set_value() (in module bpy.ops.wm), 135
context_toggle() (in module bpy.ops.wm), 135

context_toggle_enum() (in module bpy.ops.wm), 135
contrast (bpy.types.CompositorNodeTonemap attribute), 308
contrast (bpy.types.Texture attribute), 872
ControlFluidSettings (class in bpy.types), 324
Controller (class in bpy.types), 325
controller_add() (in module bpy.ops.logic), 45
controller_move() (in module bpy.ops.logic), 46
controller_remove() (in module bpy.ops.logic), 46
controllers (bge.types.KX_GameObject attribute), 1096
convert() (in module bpy.ops.gpencil), 33
convert() (in module bpy.ops.object), 68
convert() (in module bpy.ops.sketch), 104
convert_whitespace() (in module bpy.ops.text), 108
converter_node (bpy.types.ThemeNodeEditor attribute), 915
copy() (bpy.types.Context static method), 323
copy() (bpy.types.ID method), 435
copy() (in module bpy.ops.action), 9
copy() (in module bpy.ops.console), 19
copy() (in module bpy.ops.graph), 34
copy() (in module bpy.ops.material), 47
copy() (in module bpy.ops.pose), 89
copy() (in module bpy.ops.sequencer), 98
copy() (in module bpy.ops.text), 108
copy() (mathutils.Matrix method), 1042
copy_data_path_button() (in module bpy.ops.ui), 122
copy_driver_button() (in module bpy.ops.anim), 12
copy_to_selected_button() (in module bpy.ops.ui), 122
copy_to_user() (bpy.types.KeyMap method), 462
CopyLocationConstraint (class in bpy.types), 327
CopyRotationConstraint (class in bpy.types), 328
CopyScaleConstraint (class in bpy.types), 330
CopyTransformsConstraint (class in bpy.types), 331
correction (bpy.types.CompositorNodeTonemap attribute), 308
correction (bpy.types.WorldLighting attribute), 1017
correction_method (bpy.types.CompositorNodeColorBalance attribute), 266
count (bpy.types.ArrayModifier attribute), 174
count (bpy.types.ParticleBrush attribute), 641
count (bpy.types.ParticleDupliWeight attribute), 642
count (bpy.types.ParticleSettings attribute), 652
count() (bge.types.CListValue method), 1091
CPropValue (class in bge.types), 1083
crease (bpy.types.MeshEdge attribute), 545
crease_pinch_factor (bpy.types.Brush attribute), 227
create() (bpy.types.LampTextureSlots class method), 489
create() (bpy.types.MaterialTextureSlots class method), 531
create() (bpy.types.ParticleSettingsTextureSlots class method), 665
create() (bpy.types.WorldTextureSlots class method), 1023
create() (in module bpy.ops.group), 38
create_long_hair_children (bpy.types.ParticleSettings attribute), 652
create_orientation() (in module bpy.ops.transform), 113
crop_max_x (bpy.types.ImageTexture attribute), 447
crop_max_y (bpy.types.ImageTexture attribute), 447
crop_min_x (bpy.types.ImageTexture attribute), 447
crop_min_y (bpy.types.ImageTexture attribute), 447
cross() (mathutils.Quaternion method), 1046
cross() (mathutils.Vector method), 1049
crossfade_sounds() (in module bpy.ops.sequencer), 98
ctrl (bpy.types.KeyMapItem attribute), 463
cube_project() (in module bpy.ops.uv), 122
cull_face (bpy.types.ShrinkwrapModifier attribute), 794
current_character (bpy.types.ConsoleLine attribute), 316
cursor (bpy.types.ThemeConsole attribute), 899
cursor (bpy.types.ThemeTextEditor attribute), 923
cursor3d() (in module bpy.ops.view3d), 129
cursor_color_add (bpy.types.Brush attribute), 227
cursor_color_subtract (bpy.types.Brush attribute), 227
cursor_location (bpy.types.Scene attribute), 735
cursor_location (bpy.types.SpaceUVEditor attribute), 833
cursor_location (bpy.types.SpaceView3D attribute), 836
cursor_position_y (bpy.types.SpaceGraphEditor attribute), 818
cursor_set() (in module bpy.ops.graph), 34
cursor_set() (in module bpy.ops.text), 108
cursor_set() (in module bpy.ops.uv), 122
curve (bpy.types.ArrayModifier attribute), 174
Curve (class in bpy.types), 332
curve (in module bpy.context), 5
Curve.animation_data (in module bpy.types), 332
Curve.materials (in module bpy.types), 333
Curve.shape_keys (in module bpy.types), 333
Curve.splines (in module bpy.types), 333
curve_guide (bpy.types.EffectorWeights attribute), 365
curve_preset() (in module bpy.ops.brush), 17
CurveMap (class in bpy.types), 335
CurveMap.extend (in module bpy.types), 335
CurveMap.points (in module bpy.types), 336
CurveMapping (class in bpy.types), 337
CurveMapping.curves (in module bpy.types), 337
CurveMapPoint (class in bpy.types), 336
CurveMapPoint.handle_type (in module bpy.types), 336
CurveMapPoint.location (in module bpy.types), 336
CurveModifier (class in bpy.types), 339
curves_point_set() (in module bpy.ops.image), 38
CurveSplines (class in bpy.types), 340
custom_color (bpy.types.ActionGroup attribute), 147
custom_shape (bpy.types.PoseBone attribute), 687
custom_shape_transform (bpy.types.PoseBone attribute), 688
cut() (in module bpy.ops.sequencer), 98
cut() (in module bpy.ops.text), 109

cut_multicam() (in module bpy.ops.sequencer), 98
CValue (class in bge.types), 1083
cycle_render_slot() (in module bpy.ops.image), 38
cycles_after (bpy.types.FModifierCycles attribute), 384
cycles_before (bpy.types.FModifierCycles attribute), 384
cyclic_toggle() (in module bpy.ops.curve), 21
cylinder_project() (in module bpy.ops.uv), 123

D

damp (bge.types.KX_ConstraintActuator attribute), 1092
damp_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
DampedTrackConstraint (class in bpy.types), 341
damping (bge.types.KX_ObjectActuator attribute), 1112
damping (bpy.types.CollisionSettings attribute), 253
damping (bpy.types.ConstraintActuator attribute), 319
damping (bpy.types.GameObjectSettings attribute), 416
damping (bpy.types.ObjectActuator attribute), 614
damping (bpy.types.ParticleSettings attribute), 653
damping (bpy.types.SoftBodySettings attribute), 805
damping_epsilon (bpy.types.Itasc attribute), 455
damping_factor (bpy.types.CollisionSettings attribute), 253
damping_max (bpy.types.Itasc attribute), 455
damping_random (bpy.types.CollisionSettings attribute), 253
damping_rotation (bpy.types.ConstraintActuator attribute), 319
damping_time (bpy.types.WaveModifier attribute), 1006
darkness (bpy.types.Material attribute), 509
data (bpy.types.Object attribute), 604
data (in module bpy), 7
data_add() (in module bpy.ops.gpencil), 34
data_operation() (in module bpy.ops.outliner), 81
data_path (bpy.types.DriverTarget attribute), 352
data_path (bpy.types.FCurve attribute), 376
data_path (bpy.types.KeyingSetPath attribute), 477
data_unlink() (in module bpy.ops.gpencil), 34
dbvt_culling (bge.types.KX_Scene attribute), 1125
de_select_first() (in module bpy.ops.curve), 21
de_select_last() (in module bpy.ops.curve), 21
deactivate() (bge.types.SCA_PythonController method), 1138
debug (in module bpy.app), 1031
debug_menu() (in module bpy.ops.wm), 136
debug_value (in module bpy.app), 1031
DecimateModifier (class in bpy.types), 342
DecimateModifier.face_count (in module bpy.types), 342
decompose() (mathutils.Matrix method), 1043
default_key_count (bpy.types.ParticleEdit attribute), 643
default_max (bpy.types.FModifierEnvelope attribute), 385
default_min (bpy.types.FModifierEnvelope attribute), 385
default_value (bpy.types.RGBANodeSocket attribute), 703
default_value (bpy.types.TextureSlot attribute), 893
default_value (bpy.types.ValueNodeSocket attribute), 993
default_value (bpy.types.VectorNodeSocket attribute), 994
define() (bpy.types.Macro method), 503
deform_axis (bpy.types.CurveModifier attribute), 339
deform_method (bpy.types.SimpleDeformModifier attribute), 796
deinterlace_selected_movies() (in module bpy.ops.sequencer), 99
delay (bge.types.SCA_DelaySensor attribute), 1134
delay (bpy.types.DelaySensor attribute), 342
DelaySensor (class in bpy.types), 342
delete() (in module bpy.ops.action), 9
delete() (in module bpy.ops.armature), 15
delete() (in module bpy.ops.console), 19
delete() (in module bpy.ops.constraint), 20
delete() (in module bpy.ops.curve), 21
delete() (in module bpy.ops.file), 29
delete() (in module bpy.ops.font), 31
delete() (in module bpy.ops.graph), 34
delete() (in module bpy.ops.marker), 47
delete() (in module bpy.ops.mesh), 49
delete() (in module bpy.ops.nla), 61
delete() (in module bpy.ops.node), 63
delete() (in module bpy.ops.object), 68
delete() (in module bpy.ops.particle), 86
delete() (in module bpy.ops.scene), 94
delete() (in module bpy.ops.screen), 95
delete() (in module bpy.ops.sequencer), 99
delete() (in module bpy.ops.sketch), 105
delete() (in module bpy.ops.text), 109
delete_bookmark() (in module bpy.ops.file), 29
delete_edgeloop() (in module bpy.ops.mesh), 49
delete_metaelems() (in module bpy.ops.mball), 48
delete_orientation() (in module bpy.ops.transform), 113
delete_tracks() (in module bpy.ops.nla), 61
DELKEY (in module bge.events), 1176
delSource() (bge.types.BL_Shader method), 1087
delta_location (bpy.types.Object attribute), 604
delta_rotation_euler (bpy.types.Object attribute), 604
delta_rotation_quaternion (bpy.types.Object attribute), 604
delta_scale (bpy.types.Object attribute), 604
density (bpy.types.MaterialVolume attribute), 532
density (bpy.types.SmokeFlowSettings attribute), 800
density_factor (bpy.types.MaterialTextureSlot attribute), 526
density_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
density_scale (bpy.types.MaterialVolume attribute), 532
depth (bpy.types.EnvironmentMap attribute), 369

depth (bpy.types.FModifierNoise attribute), 390
depth (bpy.types.MaterialRaytraceMirror attribute), 519
depth (bpy.types.MaterialRaytraceTransparency attribute), 520
depth (bpy.types.SceneGameData attribute), 741
depth (bpy.types.WorldMistSettings attribute), 1019
depth_max (bpy.types.MaterialRaytraceTransparency attribute), 520
depth_threshold (bpy.types.MaterialVolume attribute), 532
derivate_coefficient (bpy.types.ObjectActuator attribute), 614
determinant() (mathutils.Matrix method), 1043
Device (class in aud), 1074
die_time (bpy.types.Particle attribute), 639
diffuse (bge.types.KX_PolygonMaterial attribute), 1118
diffuse_color (bpy.types.Material attribute), 509
diffuse_color (bpy.types.UserSolidLight attribute), 992
diffuse_color_factor (bpy.types.MaterialTextureSlot attribute), 526
diffuse_factor (bpy.types.MaterialTextureSlot attribute), 526
diffuse_fresnel (bpy.types.Material attribute), 509
diffuse_fresnel_factor (bpy.types.Material attribute), 509
diffuse_intensity (bpy.types.Material attribute), 509
diffuse_ramp_blend (bpy.types.Material attribute), 509
diffuse_ramp_factor (bpy.types.Material attribute), 509
diffuse_ramp_input (bpy.types.Material attribute), 510
diffuse_shader (bpy.types.Material attribute), 510
diffuse_toon_size (bpy.types.Material attribute), 510
diffuse_toon_smooth (bpy.types.Material attribute), 510
dimension_max (bpy.types.MusgraveTexture attribute), 581
dimensions (bpy.types.Curve attribute), 332
dimensions (bpy.types.Object attribute), 605
dimensions() (in module blf), 1072
direction (bge.types.KX_ConstraintActuator attribute), 1093
direction (bpy.types.Brush attribute), 227
direction (bpy.types.ConstraintActuator attribute), 319
direction (bpy.types.DisplaceModifier attribute), 344
direction (bpy.types.UserSolidLight attribute), 992
direction (bpy.types.WipeSequence attribute), 1011
direction_axis (bpy.types.ConstraintActuator attribute), 319
direction_axis_pos (bpy.types.ConstraintActuator attribute), 319
directory (bpy.types.FileSelectParams attribute), 397
directory (bpy.types.ImageSequence attribute), 444
directory (bpy.types.SequenceProxy attribute), 766
directory() (in module bpy.ops.file), 29
directory_new() (in module bpy.ops.file), 29
disable() (in module blf), 1072
disableMist() (in module bge.render), 1170
disableMotionBlur (bge.types.SCA_2DFilterActuator attribute), 1133
disableMotionBlur() (in module bge.render), 1171
disableRigidBody() (bge.types.KX_GameObject method), 1101
disconnect_hair() (in module bpy.ops.particle), 86
displacement_factor (bpy.types.MaterialTextureSlot attribute), 526
DisplaceModifier (class in bpy.types), 343
display_aspect (bpy.types.Image attribute), 439
display_channel (bpy.types.SpaceSequenceEditor attribute), 829
display_mode (bpy.types.RenderSettings attribute), 722
display_mode (bpy.types.SpaceOutliner attribute), 827
display_mode (bpy.types.SpaceSequenceEditor attribute), 829
display_name() (in module bpy.path), 1031
display_name_from_filepath() (in module bpy.path), 1031
display_type (bpy.types.FileSelectParams attribute), 398
dissolve_speed (bpy.types.SmokeDomainSettings attribute), 798
distance (bge.types.KX_ConstraintActuator attribute), 1093
distance (bge.types.KX_LightObject attribute), 1105
distance (bge.types.KX_NearSensor attribute), 1110
distance (bge.types.KX_RadarSensor attribute), 1120
distance (bpy.types.BoidRuleFight attribute), 212
distance (bpy.types.BoidRuleFollowLeader attribute), 213
distance (bpy.types.CompositorNodeDBlur attribute), 276
distance (bpy.types.CompositorNodeDilateErode attribute), 279
distance (bpy.types.ConstraintActuator attribute), 319
distance (bpy.types.KinematicConstraint attribute), 482
distance (bpy.types.Lamp attribute), 484
distance (bpy.types.LimitDistanceConstraint attribute), 495
distance (bpy.types.MaterialRaytraceMirror attribute), 519
distance (bpy.types.NearSensor attribute), 584
distance (bpy.types.RadarSensor attribute), 703
distance (bpy.types.ShrinkwrapConstraint attribute), 793
distance (bpy.types.WorldLighting attribute), 1017
distance_3d_max (bpy.types.SoundActuator attribute), 811
distance_3d_reference (bpy.types.SoundActuator attribute), 811
distance_max (bpy.types.FieldSettings attribute), 393
distance_maximum (aud.Handle attribute), 1080
distance_metric (bpy.types.VoronoiTexture attribute), 1001

distance_min (bpy.types.ClothCollisionSettings attribute), 243
distance_min (bpy.types.FieldSettings attribute), 393
distance_min (bpy.types.WorldStarsSettings attribute), 1020
distance_model (aud.Device attribute), 1075
distance_reference (aud.Handle attribute), 1080
DistortedNoiseTexture (class in bpy.types), 345
DistortedNoiseTexture.users_material (in module bpy.types), 345
DistortedNoiseTexture.users_object_modifier (in module bpy.types), 345
distortion (bpy.types.DistortedNoiseTexture attribute), 345
distribution (bge.types.SCA_RandomActuator attribute), 1138
distribution (bpy.types.ParticleSettings attribute), 653
distribution (bpy.types.RandomActuator attribute), 704
dither_intensity (bpy.types.RenderSettings attribute), 722
DKEY (in module bge.events), 1173
dLoc (bge.types.KX_ObjectActuator attribute), 1111
doc_edit() (in module bpy.ops.wm), 136
doc_view() (in module bpy.ops.wm), 136
dof_distance (bpy.types.Camera attribute), 235
dof_object (bpy.types.Camera attribute), 235
domain_object (bpy.types.VoxelData attribute), 1003
DomainFluidSettings (class in bpy.types), 346
DomainFluidSettings.memory_estimate (in module bpy.types), 347
dome_angle (bpy.types.SceneGameData attribute), 741
dome_buffer_resolution (bpy.types.SceneGameData attribute), 741
dome_mode (bpy.types.SceneGameData attribute), 741
dome_tesselation (bpy.types.SceneGameData attribute), 741
dome_text (bpy.types.SceneGameData attribute), 741
dome_tilt (bpy.types.SceneGameData attribute), 741
DopeSheet (class in bpy.types), 349
DopeSheet.source (in module bpy.types), 350
dopesheet_channel (bpy.types.ThemeDopeSheet attribute), 901
dopesheet_channel (bpy.types.ThemeGraphEditor attribute), 906
dopesheet_subchannel (bpy.types.ThemeDopeSheet attribute), 901
dopesheet_subchannel (bpy.types.ThemeGraphEditor attribute), 906
doppler_factor (aud.Device attribute), 1075
dot() (mathutils.Quaternion method), 1046
dot() (mathutils.Vector method), 1050
double (bpy.types.PropertyGroupItem attribute), 698
double_array (bpy.types.PropertyGroupItem attribute), 698
DOWNARROWKEY (in module bge.events), 1175
dpi (bpy.types.UserPreferencesSystem attribute), 986
drag (bpy.types.EffectorWeights attribute), 365
drag_factor (bpy.types.ParticleSettings attribute), 653
drag_threshold (bpy.types.UserPreferencesInput attribute), 983
draw() (bpy.types.Header method), 431
draw() (bpy.types.Macro method), 503
draw() (bpy.types.Menu method), 536
draw() (bpy.types.Operator method), 627
draw() (bpy.types.Panel method), 637
draw() (in module blf), 1072
draw() (in module bpy.ops.gpencil), 34
draw_action (bpy.types.ThemeSequenceEditor attribute), 920
draw_bounds_type (bpy.types.Object attribute), 605
draw_channels (bpy.types.SpaceImageEditor attribute), 820
draw_color (bpy.types.ParticleSettings attribute), 653
draw_entry() (bpy.types.InputKeyMapPanel method), 452
draw_filtered() (bpy.types.InputKeyMapPanel method), 452
draw_header() (bpy.types.Panel method), 637
draw_hierarchy() (bpy.types.InputKeyMapPanel method), 452
draw_keymaps() (bpy.types.InputKeyMapPanel method), 452
draw_km() (bpy.types.InputKeyMapPanel method), 452
draw_kmi() (bpy.types.InputKeyMapPanel method), 452
draw_kmi_properties() (bpy.types.InputKeyMapPanel static method), 452
draw_method (bpy.types.ParticleSettings attribute), 653
draw_mode (bpy.types.GreasePencil attribute), 425
draw_overexposed (bpy.types.SpaceSequenceEditor attribute), 829
draw_percentage (bpy.types.ParticleSettings attribute), 653
draw_preset() (bpy.types.Menu method), 536
draw_preview() (in module bpy.ops.sketch), 105
draw_size (bpy.types.Camera attribute), 235
draw_size (bpy.types.ParticleSettings attribute), 653
draw_step (bpy.types.ParticleEdit attribute), 643
draw_step (bpy.types.ParticleSettings attribute), 653
draw_stretch_type (bpy.types.SpaceUVEditor attribute), 833
draw_stroke() (in module bpy.ops.sketch), 105
draw_type (bpy.types.Armature attribute), 166
draw_type (bpy.types.Object attribute), 605
drawingmode (bge.types.KX_PolygonMaterial attribute), 1118
drawLine() (in module bge.render), 1171
Driver (class in bpy.types), 351
Driver.variables (in module bpy.types), 352
driver_add() (bpy.types.bpy_struct method), 1027

driver_button_add() (in module bpy.ops.anim), 12
driver_button_remove() (in module bpy.ops.anim), 12
driver_namespace (in module bpy.app), 1031
driver_remove() (bpy.types.bpy_struct method), 1027
drivers_add_selected() (in module bpy.ops.outliner), 81
drivers_delete_selected() (in module bpy.ops.outliner), 81
DriverTarget (class in bpy.types), 352
DriverVariable (class in bpy.types), 354
DriverVariable.targets (in module bpy.types), 354
drop_named_image() (in module bpy.ops.mesh), 49
drop_named_material() (in module bpy.ops.object), 68
dRot (bge.types.KX_ObjectActuator attribute), 1111
dupli_extrude_cursor() (in module bpy.ops.mesh), 49
dupli_faces_scale (bpy.types.Object attribute), 605
dupli_frames_end (bpy.types.Object attribute), 605
dupli_frames_off (bpy.types.Object attribute), 605
dupli_frames_on (bpy.types.Object attribute), 605
dupli_frames_start (bpy.types.Object attribute), 605
dupli_group (bpy.types.Object attribute), 605
dupli_group (bpy.types.ParticleSettings attribute), 653
dupli_list_clear() (bpy.types.Object method), 611
dupli_list_create() (bpy.types.Object method), 611
dupli_object (bpy.types.ParticleSettings attribute), 653
dupli_offset (bpy.types.Group attribute), 427
dupli_type (bpy.types.Object attribute), 605
duplicate() (in module bpy.ops.action), 9
duplicate() (in module bpy.ops.armature), 15
duplicate() (in module bpy.ops.curve), 21
duplicate() (in module bpy.ops.graph), 35
duplicate() (in module bpy.ops.marker), 47
duplicate() (in module bpy.ops.mesh), 49
duplicate() (in module bpy.ops.nla), 61
duplicate() (in module bpy.ops.node), 63
duplicate() (in module bpy.ops.object), 68
duplicate() (in module bpy.ops.sequencer), 99
duplicate_metaelems() (in module bpy.ops.mball), 48
duplicate_move() (in module bpy.ops.action), 9
duplicate_move() (in module bpy.ops.armature), 15
duplicate_move() (in module bpy.ops.graph), 35
duplicate_move() (in module bpy.ops.mesh), 49
duplicate_move() (in module bpy.ops.node), 63
duplicate_move() (in module bpy.ops.object), 68
duplicate_move_linked() (in module bpy.ops.object), 69
duplicates_make_real() (in module bpy.ops.object), 69
dupliob_copy() (in module bpy.ops.particle), 86
dupliob_move_down() (in module bpy.ops.particle), 86
dupliob_move_up() (in module bpy.ops.particle), 86
dupliob_remove() (in module bpy.ops.particle), 86
DupliObject (class in bpy.types), 355
DupliObject.object (in module bpy.types), 355
duration (bge.types.SCA_DelaySensor attribute), 1134
duration (bpy.types.DelaySensor attribute), 343
duration (bpy.types.ParticleTarget attribute), 672
dynamic_friction (bpy.types.GameSoftBodySettings attribute), 421
dynamic_operation (bpy.types.EditObjectActuator attribute), 361

E

edge_color (bpy.types.RenderSettings attribute), 722
edge_crease (bpy.types.ThemeView3D attribute), 930
edge_crease() (in module bpy.ops.transform), 113
edge_crease_inner (bpy.types.SolidifyModifier attribute), 808
edge_crease_outer (bpy.types.SolidifyModifier attribute), 808
edge_crease_rim (bpy.types.SolidifyModifier attribute), 808
edge_draw_type (bpy.types.SpaceUVEditor attribute), 833
edge_face_add() (in module bpy.ops.mesh), 49
edge_facesel (bpy.types.ThemeView3D attribute), 930
edge_flip() (in module bpy.ops.mesh), 49
edge_loops_from_edges() (bpy.types.Mesh method), 540
edge_loops_from_faces() (bpy.types.Mesh method), 540
edge_path_live_unwrap (bpy.types.ToolSettings attribute), 937
edge_path_mode (bpy.types.ToolSettings attribute), 938
edge_rotate() (in module bpy.ops.mesh), 49
edge_seam (bpy.types.ThemeView3D attribute), 930
edge_select (bpy.types.ThemeView3D attribute), 930
edge_sharp (bpy.types.ThemeView3D attribute), 930
edge_slide() (in module bpy.ops.transform), 113
edge_threshold (bpy.types.RenderSettings attribute), 722
edge_weight_method (bpy.types.BevelModifier attribute), 177
edgering_select() (in module bpy.ops.mesh), 49
edges_select_sharp() (in module bpy.ops.mesh), 50
EdgeSplitModifier (class in bpy.types), 355
edit_bone (in module bpy.context), 6
edit_image (in module bpy.context), 7
edit_mesh_extrude_individual_move() (in module bpy.ops.view3d), 129
edit_mesh_extrude_move_normal() (in module bpy.ops.view3d), 129
edit_object (in module bpy.context), 4
edit_text (in module bpy.context), 7
editable_bones (in module bpy.context), 3
EditBone (class in bpy.types), 356
EditBone.basename (in module bpy.types), 359
EditBone.center (in module bpy.types), 359
EditBone.children (in module bpy.types), 359
EditBone.children_recursive (in module bpy.types), 359
EditBone.children_recursive_basename (in module bpy.types), 359
EditBone.matrix (in module bpy.types), 357
EditBone.parent_recursive (in module bpy.types), 359

EditBone.vector (in module bpy.types), 359
EditBone.x_axis (in module bpy.types), 359
EditBone.y_axis (in module bpy.types), 359
EditBone.z_axis (in module bpy.types), 359
edited_clear() (in module bpy.ops.particle), 86
editmesh_active (bpy.types.ThemeImageEditor attribute), 909
editmesh_active (bpy.types.ThemeView3D attribute), 930
editmode_toggle() (in module bpy.ops.object), 69
EditObjectActuator (class in bpy.types), 360
effect_fader (bpy.types.Sequence attribute), 759
effect_hair (bpy.types.ParticleSettings attribute), 653
effect_strip (bpy.types.ThemeSequenceEditor attribute), 920
effect_strip_add() (in module bpy.ops.sequencer), 99
effector_add() (in module bpy.ops.object), 69
effector_amount (bpy.types.ParticleSettings attribute), 653
effector_group (bpy.types.SmokeDomainSettings attribute), 798
EffectorWeights (class in bpy.types), 365
EffectSequence (class in bpy.types), 362
EffectSequence.color_balance (in module bpy.types), 362
EffectSequence.crop (in module bpy.types), 362
EffectSequence.proxy (in module bpy.types), 363
EffectSequence.transform (in module bpy.types), 363
EIGHTKEY (in module bge.events), 1174
EKEY (in module bge.events), 1173
elasticity (bpy.types.MaterialPhysics attribute), 518
emission (bpy.types.MaterialVolume attribute), 532
emission_color (bpy.types.MaterialVolume attribute), 532
emission_color_factor (bpy.types.MaterialTextureSlot attribute), 526
emission_factor (bpy.types.MaterialTextureSlot attribute), 526
emit (bpy.types.Material attribute), 510
emit_factor (bpy.types.MaterialTextureSlot attribute), 526
emit_from (bpy.types.ParticleSettings attribute), 654
emitter_distance (bpy.types.ParticleEdit attribute), 643
empty_draw_size (bpy.types.Object attribute), 605
empty_draw_type (bpy.types.Object attribute), 605
enable() (in module blf), 1072
enable_manipulator() (in module bpy.ops.view3d), 129
enabled (bpy.types.UILayout attribute), 949
enableMotionBlur() (in module bge.render), 1171
enableRigidBody() (bge.types.KX_GameObject method), 1100
enableVisibility() (in module bge.render), 1170
end() (bge.types.KX_Scene method), 1125
end_cap (bpy.types.ArrayModifier attribute), 174
end_frame_set() (in module bpy.ops.time), 113
end_result() (bpy.types.RenderEngine method), 713
end_time (bpy.types.ControlFluidSettings attribute), 324
end_time (bpy.types.DomainFluidSettings attribute), 347
endGame() (in module bge.logic), 1157
ENDKEY (in module bge.events), 1176
endObject() (bge.types.KX_GameObject method), 1097
energy (bge.types.KX_LightObject attribute), 1105
energy (bpy.types.Lamp attribute), 484
enforce (bge.types.BL_ArmatureConstraint attribute), 1148
engine (bpy.types.RenderSettings attribute), 722
ensure_ext() (in module bpy.path), 1031
ENTERKEY (in module bge.events), 1176
EnumProperty (class in bpy.types), 367
EnumProperty() (in module bpy.props), 1035
EnumProperty.default (in module bpy.types), 367
EnumProperty.default_flag (in module bpy.types), 367
EnumProperty.items (in module bpy.types), 367
EnumPropertyItem (class in bpy.types), 368
EnumPropertyItem.description (in module bpy.types), 368
EnumPropertyItem.identifier (in module bpy.types), 368
EnumPropertyItem.name (in module bpy.types), 368
EnumPropertyItem.value (in module bpy.types), 368
envelope_distance (bpy.types.Bone attribute), 219
envelope_distance (bpy.types.EditBone attribute), 357
envelope_weight (bpy.types.Bone attribute), 219
envelope_weight (bpy.types.EditBone attribute), 357
environment_color (bpy.types.WorldLighting attribute), 1017
environment_energy (bpy.types.WorldLighting attribute), 1017
EnvironmentMap (class in bpy.types), 369
EnvironmentMapTexture (class in bpy.types), 370
EnvironmentMapTexture.environment_map (in module bpy.types), 370
EnvironmentMapTexture.image_user (in module bpy.types), 371
EnvironmentMapTexture.users_material (in module bpy.types), 371
EnvironmentMapTexture.users_object_modifier (in module bpy.types), 371
envmap_clear() (in module bpy.ops.texture), 112
envmap_clear_all() (in module bpy.ops.texture), 112
envmap_save() (in module bpy.ops.texture), 112
EQUALKEY (in module bge.events), 1176
error (class in aud), 1081
error_threshold (bpy.types.MaterialSubsurfaceScattering attribute), 524
error_threshold (bpy.types.SoftBodySettings attribute), 805
error_threshold (bpy.types.WorldLighting attribute), 1017
ESCKEY (in module bge.events), 1176
etch_adaptive_limit (bpy.types.ToolSettings attribute), 938
etch_convert_mode (bpy.types.ToolSettings attribute), 938

etch_length_limit (bpy.types.ToolSettings attribute), 938
etch_number (bpy.types.ToolSettings attribute), 938
etch_roll_mode (bpy.types.ToolSettings attribute), 938
etch_side (bpy.types.ToolSettings attribute), 938
etch_subdivision_number (bpy.types.ToolSettings attribute), 938
etch_template (bpy.types.ToolSettings attribute), 938
Euler (class in mathutils), 1040
Euler.copy() (in module mathutils), 1040
euler_filter() (in module bpy.ops.graph), 35
eval_time (bpy.types.Curve attribute), 332
evaluate() (bpy.types.ColorRamp method), 255
evaluate() (bpy.types.FCurve method), 377
evaluate_envelope() (bpy.types.Bone method), 222
evaluate_envelope() (bpy.types.PoseBone method), 691
evaluation_type (bpy.types.PropertySensor attribute), 699
Event (class in bpy.types), 372
Event.alt (in module bpy.types), 372
Event.ascii (in module bpy.types), 372
Event.ctrl (in module bpy.types), 372
Event.mouse_prev_x (in module bpy.types), 372
Event.mouse_prev_y (in module bpy.types), 372
Event.mouse_region_x (in module bpy.types), 372
Event.mouse_region_y (in module bpy.types), 372
Event.mouse_x (in module bpy.types), 373
Event.mouse_y (in module bpy.types), 373
Event.oskey (in module bpy.types), 373
Event.shift (in module bpy.types), 373
Event.type (in module bpy.types), 373
Event.value (in module bpy.types), 373
event_type (bpy.types.JoystickSensor attribute), 457
events (bge.types.SCA_KeyboardSensor attribute), 1136
events (bge.types.SCA_PythonKeyboard attribute), 1084
events (bge.types.SCA_PythonMouse attribute), 1084
EventToCharacter() (in module bge.events), 1173
EventToString() (in module bge.events), 1172
exclude_ambient_occlusion (bpy.types.SceneRenderLayer attribute), 745
exclude_emit (bpy.types.SceneRenderLayer attribute), 746
exclude_environment (bpy.types.SceneRenderLayer attribute), 746
exclude_indirect (bpy.types.SceneRenderLayer attribute), 746
exclude_reflection (bpy.types.SceneRenderLayer attribute), 746
exclude_refraction (bpy.types.SceneRenderLayer attribute), 746
exclude_shadow (bpy.types.SceneRenderLayer attribute), 746
exclude_specular (bpy.types.SceneRenderLayer attribute), 746
execute() (bpy.types.Operator method), 626
execute() (in module bpy.ops.console), 19
execute() (in module bpy.ops.file), 29
execute_preset() (in module bpy.ops.script), 97
executePriority (bge.types.SCA_ILogicBrick attribute), 1083
expanded_toggle() (in module bpy.ops.outliner), 81
expandPath() (in module bge.logic), 1159
explode_refresh() (in module bpy.ops.object), 69
ExplodeModifier (class in bpy.types), 374
export_layout() (in module bpy.ops.uv), 123
expose() (bpy.types.GroupInputs method), 428
expose() (bpy.types.GroupOutputs method), 430
exposure (bpy.types.World attribute), 1015
expression (bpy.types.Driver attribute), 351
expression (bpy.types.ExpressionController attribute), 375
ExpressionController (class in bpy.types), 375
exr_codec (bpy.types.CompositorNodeOutputFile attribute), 297
exr_codec (bpy.types.RenderSettings attribute), 722
exr_preview (bpy.types.RenderSettings attribute), 722
exr_zbuf (bpy.types.RenderSettings attribute), 722
extension (bpy.types.ImageTexture attribute), 447
extension (bpy.types.VoxelData attribute), 1003
external_edit() (in module bpy.ops.image), 38
extra_edge_len (bpy.types.ThemeView3D attribute), 930
extra_face_angle (bpy.types.ThemeView3D attribute), 930
extra_face_area (bpy.types.ThemeView3D attribute), 930
extrapolation (bpy.types.FCurve attribute), 377
extrapolation (bpy.types.NlaStrip attribute), 590
extrapolation_type() (in module bpy.ops.action), 9
extrapolation_type() (in module bpy.ops.graph), 35
extrude (bpy.types.Curve attribute), 332
extrude() (in module bpy.ops.armature), 15
extrude() (in module bpy.ops.curve), 21
extrude() (in module bpy.ops.mesh), 50
extrude_edges_move() (in module bpy.ops.mesh), 50
extrude_faces_move() (in module bpy.ops.mesh), 50
extrude_forked() (in module bpy.ops.armature), 15
extrude_move() (in module bpy.ops.armature), 15
extrude_region_move() (in module bpy.ops.mesh), 50
extrude_repeat() (in module bpy.ops.mesh), 50
extrude_vertices_move() (in module bpy.ops.mesh), 50
eyedropper() (in module bpy.ops.ui), 122

F

F10KEY (in module bge.events), 1175
F11KEY (in module bge.events), 1175
F12KEY (in module bge.events), 1176
F13KEY (in module bge.events), 1176
F14KEY (in module bge.events), 1176
F15KEY (in module bge.events), 1176
F16KEY (in module bge.events), 1176

F17KEY (in module bge.events), 1176
F18KEY (in module bge.events), 1176
F19KEY (in module bge.events), 1176
F1KEY (in module bge.events), 1175
F2KEY (in module bge.events), 1175
F3KEY (in module bge.events), 1175
F4KEY (in module bge.events), 1175
F5KEY (in module bge.events), 1175
F6KEY (in module bge.events), 1175
F7KEY (in module bge.events), 1175
F8KEY (in module bge.events), 1175
F9KEY (in module bge.events), 1175
f_stop (bpy.types.CompositorNodeDefocus attribute), 277
face (bpy.types.ThemeImageEditor attribute), 909
face (bpy.types.ThemeView3D attribute), 930
face_dot (bpy.types.ThemeImageEditor attribute), 909
face_dot (bpy.types.ThemeView3D attribute), 930
face_select (bpy.types.ThemeImageEditor attribute), 909
face_select (bpy.types.ThemeView3D attribute), 930
face_select_all() (in module bpy.ops.paint), 83
face_select_hide() (in module bpy.ops.paint), 83
face_select_inverse() (in module bpy.ops.paint), 83
face_select_linked() (in module bpy.ops.paint), 83
face_select_linked_pick() (in module bpy.ops.paint), 83
face_select_reveal() (in module bpy.ops.paint), 83
facedot_size (bpy.types.ThemeImageEditor attribute), 909
facedot_size (bpy.types.ThemeView3D attribute), 930
faces_miror_uv() (in module bpy.ops.mesh), 51
faces_select_interior() (in module bpy.ops.mesh), 51
faces_select_linked_flat() (in module bpy.ops.mesh), 51
faces_shade_flat() (in module bpy.ops.mesh), 51
faces_shade_smooth() (in module bpy.ops.mesh), 51
factor (bpy.types.CastModifier attribute), 238
factor (bpy.types.CompositorNodeBlur attribute), 262
factor (bpy.types.CompositorNodeSplitViewer attribute), 306
factor (bpy.types.CompositorNodeVecBlur attribute), 312
factor (bpy.types.SimpleDeformModifier attribute), 796
factor (bpy.types.SmoothModifier attribute), 802
factor_blue (bpy.types.Texture attribute), 872
factor_density (bpy.types.SPHFluidSettings attribute), 733
factor_green (bpy.types.Texture attribute), 872
factor_radius (bpy.types.SPHFluidSettings attribute), 733
factor_random (bpy.types.ParticleSettings attribute), 654
factor_red (bpy.types.Texture attribute), 873
factor_repulsion (bpy.types.SPHFluidSettings attribute), 733
factor_rest_length (bpy.types.SPHFluidSettings attribute), 733
factor_stiff_viscosity (bpy.types.SPHFluidSettings attribute), 733
factor_x (bpy.types.CompositorNodeBlur attribute), 262
factor_y (bpy.types.CompositorNodeBlur attribute), 262
Factory (class in aud), 1075
fade (bpy.types.CompositorNodeGlare attribute), 284
fade_frames (bpy.types.ParticleEdit attribute), 643
fade_to (bpy.types.MaterialRaytraceMirror attribute), 519
falloff (bpy.types.BoidState attribute), 218
falloff (bpy.types.CompositorNodeDiffMatte attribute), 278
falloff (bpy.types.CompositorNodeDistanceMatte attribute), 280
falloff (bpy.types.HookModifier attribute), 434
falloff (bpy.types.MaterialRaytraceTransparency attribute), 521
falloff (bpy.types.PointDensity attribute), 680
falloff (bpy.types.WorldMistSettings attribute), 1019
falloff_power (bpy.types.FieldSettings attribute), 394
falloff_radius (bpy.types.WaveModifier attribute), 1006
falloff_soft (bpy.types.PointDensity attribute), 680
falloff_strength (bpy.types.WorldLighting attribute), 1017
falloff_type (bpy.types.FieldSettings attribute), 394
falloff_type (bpy.types.PointLamp attribute), 683
falloff_type (bpy.types.SpotLamp attribute), 848
family (bpy.types.TextCurve attribute), 868
far (bge.types.KX_Camera attribute), 1141
fbx() (in module bpy.ops.export_scene), 26
FCurve (class in bpy.types), 376
FCurve.driver (in module bpy.types), 377
FCurve.keyframe_points (in module bpy.types), 377
FCurve.modifiers (in module bpy.types), 377
FCurve.sampled_points (in module bpy.types), 377
FCurveActuator (class in bpy.types), 378
FCurveKeyframePoints (class in bpy.types), 380
FCurveModifiers (class in bpy.types), 381
FCurveSample (class in bpy.types), 382
fear_factor (bpy.types.BoidRuleAvoid attribute), 211
feedback (bpy.types.Itasc attribute), 455
fgon_clear() (in module bpy.ops.mesh), 51
fgon_make() (in module bpy.ops.mesh), 51
fh_damping (bpy.types.ConstraintActuator attribute), 320
fh_damping (bpy.types.MaterialPhysics attribute), 518
fh_distance (bpy.types.MaterialPhysics attribute), 518
fh_force (bpy.types.ConstraintActuator attribute), 320
fh_force (bpy.types.MaterialPhysics attribute), 518
fh_height (bpy.types.ConstraintActuator attribute), 320
field_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
field_order (bpy.types.Image attribute), 439
field_order (bpy.types.RenderSettings attribute), 722
fields_per_frame (bpy.types.ImageUser attribute), 450
FieldSettings (class in bpy.types), 393
file_browse() (in module bpy.ops.buttons), 18
file_format (bpy.types.Image attribute), 439
file_format (bpy.types.RenderSettings attribute), 723

file_format (bpy.types.VoxelData attribute), 1003
file_paste() (in module bpy.ops.font), 31
file_quality (bpy.types.RenderSettings attribute), 723
fileName (bge.types.KX_GameActuator attribute), 1094
fileName (bge.types.KX_SoundActuator attribute), 1126
filename (bpy.types.FileSelectParams attribute), 398
filename (bpy.types.GameActuator attribute), 413
filename (bpy.types.SequenceElement attribute), 765
filenum() (in module bpy.ops.file), 29
filepath (bpy.types.CompositorNodeOutputFile attribute), 297
filepath (bpy.types.DomainFluidSettings attribute), 347
filepath (bpy.types.Image attribute), 439
filepath (bpy.types.Library attribute), 494
filepath (bpy.types.MovieSequence attribute), 574
filepath (bpy.types.MultiresModifier attribute), 579
filepath (bpy.types.ParticleFluidSettings attribute), 645
filepath (bpy.types.PointCache attribute), 677
filepath (bpy.types.RenderSettings attribute), 723
filepath (bpy.types.SequenceProxy attribute), 766
filepath (bpy.types.Sound attribute), 809
filepath (bpy.types.SoundSequence attribute), 812
filepath (bpy.types.Text attribute), 863
filepath (bpy.types.TextureNodeOutput attribute), 885
filepath (bpy.types.VoxelData attribute), 1003
filepath_raw (bpy.types.Image attribute), 439
fileselect_add() (bpy.types.WindowManager class method), 1009
FileSelectParams (class in bpy.types), 397
FileSelectParams.title (in module bpy.types), 398
fill() (in module bpy.ops.armature), 15
fill() (in module bpy.ops.mesh), 51
filter (bpy.types.MaterialRaytraceTransparency attribute), 521
Filter2DActuator (class in bpy.types), 399
filter_eccentricity (bpy.types.EnvironmentMapTexture attribute), 370
filter_eccentricity (bpy.types.ImageTexture attribute), 447
filter_glob (bpy.types.FileSelectParams attribute), 398
filter_group (bpy.types.DopeSheet attribute), 349
filter_pass (bpy.types.Filter2DActuator attribute), 399
filter_probes (bpy.types.EnvironmentMapTexture attribute), 370
filter_probes (bpy.types.ImageTexture attribute), 447
filter_size (bpy.types.EnvironmentMapTexture attribute), 370
filter_size (bpy.types.ImageTexture attribute), 447
filter_size (bpy.types.RenderSettings attribute), 723
filter_text (bpy.types.SpaceOutliner attribute), 827
filter_text (bpy.types.SpaceUserPreferences attribute), 835
filter_type (bpy.types.CompositorNodeBlur attribute), 262
filter_type (bpy.types.CompositorNodeFilter attribute), 281
filter_type (bpy.types.CompositorNodeRotate attribute), 301
filter_type (bpy.types.EnvironmentMapTexture attribute), 370
filter_type (bpy.types.ImageTexture attribute), 447
find() (bpy.types.KeyMaps method), 470
find() (in module bpy.ops.text), 109
find_armature() (bpy.types.Object method), 611
find_missing_files() (in module bpy.ops.file), 29
find_modal() (bpy.types.KeyMaps method), 470
find_set_selected() (in module bpy.ops.text), 109
find_text (bpy.types.SpaceTextEditor attribute), 830
finish_stroke() (in module bpy.ops.sketch), 105
fit_length (bpy.types.ArrayModifier attribute), 174
fit_type (bpy.types.ArrayModifier attribute), 174
FIVEKEY (in module bge.events), 1174
FKEY (in module bge.events), 1173
flags_set() (in module bpy.ops.armature), 15
flags_set() (in module bpy.ops.pose), 89
flare_boost (bpy.types.MaterialHalo attribute), 516
flare_seed (bpy.types.MaterialHalo attribute), 516
flare_size (bpy.types.MaterialHalo attribute), 516
flare_subflare_count (bpy.types.MaterialHalo attribute), 516
flare_subflare_size (bpy.types.MaterialHalo attribute), 516
flee_distance (bpy.types.BoidRuleFight attribute), 213
flip_names() (in module bpy.ops.armature), 16
flip_names() (in module bpy.ops.pose), 89
flip_normals() (in module bpy.ops.mesh), 51
float (bpy.types.PropertyGroupItem attribute), 698
float_array (bpy.types.PropertyGroupItem attribute), 698
float_max (bpy.types.RandomActuator attribute), 705
float_mean (bpy.types.RandomActuator attribute), 705
float_min (bpy.types.RandomActuator attribute), 705
float_value (bpy.types.RandomActuator attribute), 705
FloatProperty (class in bpy.types), 400
FloatProperty() (in module bpy.props), 1035
FloatProperty.array_length (in module bpy.types), 400
FloatProperty.default (in module bpy.types), 401
FloatProperty.default_array (in module bpy.types), 401
FloatProperty.hard_max (in module bpy.types), 401
FloatProperty.hard_min (in module bpy.types), 401
FloatProperty.precision (in module bpy.types), 401
FloatProperty.soft_max (in module bpy.types), 401
FloatProperty.soft_min (in module bpy.types), 401
FloatProperty.step (in module bpy.types), 401
FloatVectorProperty() (in module bpy.props), 1035
floor_location (bpy.types.FloorConstraint attribute), 402
FloorConstraint (class in bpy.types), 402
flow (bpy.types.FieldSettings attribute), 394
fluid (in module bpy.context), 6

fluid_group (bpy.types.SmokeDomainSettings attribute), 798
fluid_radius (bpy.types.SPHFluidSettings attribute), 733
FluidFluidSettings (class in bpy.types), 403
FluidSettings (class in bpy.types), 404
FluidSimulationModifier (class in bpy.types), 405
FluidSimulationModifier.settings (in module bpy.types), 405
fly() (in module bpy.ops.view3d), 129
FModifier (class in bpy.types), 383
FModifier.is_valid (in module bpy.types), 383
FModifier.type (in module bpy.types), 383
fmodifier_add() (in module bpy.ops.graph), 35
fmodifier_add() (in module bpy.ops.nla), 61
fmodifier_copy() (in module bpy.ops.graph), 35
fmodifier_copy() (in module bpy.ops.nla), 61
fmodifier_paste() (in module bpy.ops.graph), 35
fmodifier_paste() (in module bpy.ops.nla), 61
FModifierCycles (class in bpy.types), 384
FModifierEnvelope (class in bpy.types), 385
FModifierEnvelope.control_points (in module bpy.types), 385
FModifierEnvelopeControlPoint (class in bpy.types), 386
FModifierFunctionGenerator (class in bpy.types), 387
FModifierGenerator (class in bpy.types), 388
FModifierLimits (class in bpy.types), 389
FModifierNoise (class in bpy.types), 390
FModifierPython (class in bpy.types), 391
FModifierStepped (class in bpy.types), 392
follow_active_quads() (in module bpy.ops.uv), 123
follow_curve (bpy.types.TextCurve attribute), 868
FollowPathConstraint (class in bpy.types), 406
font (bpy.types.TextCurve attribute), 868
font_bold (bpy.types.TextCurve attribute), 868
font_bold_italic (bpy.types.TextCurve attribute), 868
font_directory (bpy.types.UserPreferencesFilePaths attribute), 981
font_italic (bpy.types.TextCurve attribute), 868
font_kerning_style (bpy.types.ThemeFontStyle attribute), 905
font_size (bpy.types.SpaceConsole attribute), 815
font_size (bpy.types.SpaceTextEditor attribute), 830
force (bge.types.KX_ObjectActuator attribute), 1111
force (bpy.types.EffectorWeights attribute), 365
force (bpy.types.HookModifier attribute), 434
force (bpy.types.ObjectActuator attribute), 614
force_max_x (bpy.types.ObjectActuator attribute), 614
force_max_y (bpy.types.ObjectActuator attribute), 614
force_max_z (bpy.types.ObjectActuator attribute), 614
force_min_x (bpy.types.ObjectActuator attribute), 614
force_min_y (bpy.types.ObjectActuator attribute), 615
force_min_z (bpy.types.ObjectActuator attribute), 615
forcefield_toggle() (in module bpy.ops.object), 69
forceLimitX (bge.types.KX_ObjectActuator attribute), 1112
forceLimitY (bge.types.KX_ObjectActuator attribute), 1112
forceLimitZ (bge.types.KX_ObjectActuator attribute), 1112
form_factor (bpy.types.GameObjectSettings attribute), 416
format (aud.Device attribute), 1075
forward_axis (bpy.types.FollowPathConstraint attribute), 406
FOURKEY (in module bge.events), 1174
fps (bpy.types.Image attribute), 439
fps (bpy.types.RenderSettings attribute), 723
fps (bpy.types.SceneGameData attribute), 741
fps_base (bpy.types.RenderSettings attribute), 723
frame (bge.types.BL_ActionActuator attribute), 1086
frame (bge.types.BL_ShapeActionActuator attribute), 1090
frame (bpy.types.FModifierEnvelopeControlPoint attribute), 386
frame (bpy.types.TimelineMarker attribute), 935
frame_after (bpy.types.AnimVizMotionPaths attribute), 158
frame_after (bpy.types.AnimVizOnionSkinning attribute), 160
frame_before (bpy.types.AnimVizMotionPaths attribute), 158
frame_before (bpy.types.AnimVizOnionSkinning attribute), 160
frame_blend_in (bpy.types.ActionActuator attribute), 144
frame_blend_in (bpy.types.ShapeActionActuator attribute), 788
frame_color (bpy.types.SceneGameData attribute), 741
frame_current (bpy.types.Scene attribute), 735
frame_current (bpy.types.ThemeAudioWindow attribute), 897
frame_current (bpy.types.ThemeDopeSheet attribute), 901
frame_current (bpy.types.ThemeGraphEditor attribute), 906
frame_current (bpy.types.ThemeNLAEditor attribute), 914
frame_current (bpy.types.ThemeSequenceEditor attribute), 920
frame_current (bpy.types.ThemeTimeline attribute), 925
frame_current (bpy.types.ThemeView3D attribute), 930
frame_duration (bpy.types.BuildModifier attribute), 233
frame_duration (bpy.types.CompositorNodeImage attribute), 287
frame_duration (bpy.types.ImageUser attribute), 450
frame_end (bpy.types.ActionActuator attribute), 144
frame_end (bpy.types.ActionConstraint attribute), 145

frame_end (bpy.types.AnimVizMotionPaths attribute), 158
frame_end (bpy.types.AnimVizOnionSkinning attribute), 160
frame_end (bpy.types.CompositorNodeOutputFile attribute), 297
frame_end (bpy.types.CompositorNodeTime attribute), 307
frame_end (bpy.types.FCurveActuator attribute), 378
frame_end (bpy.types.FModifierStepped attribute), 392
frame_end (bpy.types.Image attribute), 439
frame_end (bpy.types.NlaStrip attribute), 590
frame_end (bpy.types.ParticleSettings attribute), 654
frame_end (bpy.types.PointCache attribute), 677
frame_end (bpy.types.Scene attribute), 735
frame_end (bpy.types.ShapeActionActuator attribute), 788
frame_end (bpy.types.TextureNodeCurveTime attribute), 879
frame_final_duration (bpy.types.Sequence attribute), 760
frame_final_end (bpy.types.Sequence attribute), 760
frame_final_start (bpy.types.Sequence attribute), 760
frame_jump() (in module bpy.ops.action), 9
frame_jump() (in module bpy.ops.graph), 35
frame_jump() (in module bpy.ops.screen), 95
frame_map_new (bpy.types.RenderSettings attribute), 723
frame_map_old (bpy.types.RenderSettings attribute), 723
frame_number (bpy.types.GPencilFrame attribute), 408
frame_offset (bpy.types.CompositorNodeImage attribute), 287
frame_offset (bpy.types.FModifierStepped attribute), 392
frame_offset (bpy.types.ImageUser attribute), 450
frame_offset() (in module bpy.ops.screen), 96
frame_path() (bpy.types.RenderSettings method), 729
frame_preview_end (bpy.types.Scene attribute), 735
frame_preview_start (bpy.types.Scene attribute), 735
frame_property (bpy.types.ActionActuator attribute), 144
frame_property (bpy.types.FCurveActuator attribute), 379
frame_property (bpy.types.ShapeActionActuator attribute), 788
frame_server_port (bpy.types.UserPreferencesSystem attribute), 986
frame_set() (bpy.types.Scene method), 738
frame_start (bpy.types.ActionActuator attribute), 144
frame_start (bpy.types.ActionConstraint attribute), 145
frame_start (bpy.types.AnimVizMotionPaths attribute), 159
frame_start (bpy.types.AnimVizOnionSkinning attribute), 160
frame_start (bpy.types.BuildModifier attribute), 233
frame_start (bpy.types.CompositorNodeImage attribute), 288
frame_start (bpy.types.CompositorNodeOutputFile attribute), 297
frame_start (bpy.types.CompositorNodeTime attribute), 307
frame_start (bpy.types.FCurveActuator attribute), 379
frame_start (bpy.types.FModifierStepped attribute), 392
frame_start (bpy.types.Image attribute), 439
frame_start (bpy.types.ImageUser attribute), 450
frame_start (bpy.types.NlaStrip attribute), 590
frame_start (bpy.types.ParticleSettings attribute), 654
frame_start (bpy.types.PointCache attribute), 677
frame_start (bpy.types.Scene attribute), 736
frame_start (bpy.types.Sequence attribute), 760
frame_start (bpy.types.ShapeActionActuator attribute), 788
frame_start (bpy.types.TextureNodeCurveTime attribute), 879
frame_step (bpy.types.AnimVizMotionPaths attribute), 159
frame_step (bpy.types.AnimVizOnionSkinning attribute), 160
frame_step (bpy.types.FModifierStepped attribute), 392
frame_step (bpy.types.PointCache attribute), 677
frame_step (bpy.types.Scene attribute), 736
frame_type (bpy.types.SceneGameData attribute), 741
frameEnd (bge.types.BL_ActionActuator attribute), 1086
frameEnd (bge.types.BL_ShapeActionActuator attribute), 1090
frameEnd (bge.types.KX_IpoActuator attribute), 1104
frameMessageCount (bge.types.KX_NetworkMessageSensor attribute), 1110
framePropName (bge.types.BL_ActionActuator attribute), 1086
framePropName (bge.types.BL_ShapeActionActuator attribute), 1091
framePropName (bge.types.KX_IpoActuator attribute), 1104
frameStart (bge.types.BL_ActionActuator attribute), 1086
frameStart (bge.types.BL_ShapeActionActuator attribute), 1090
frameStart (bge.types.KX_IpoActuator attribute), 1104
free_axis (bpy.types.MaintainVolumeConstraint attribute), 505
free_bake() (in module bpy.ops.ptcache), 92
free_bake_all() (in module bpy.ops.ptcache), 92
frequency (bge.types.SCA_ISensor attribute), 1084
frequency (bpy.types.SceneGameData attribute), 741
frequency (bpy.types.Sensor attribute), 758
fresnel (bpy.types.MaterialRaytraceMirror attribute), 519
fresnel (bpy.types.MaterialRaytraceTransparency attribute), 521
fresnel_factor (bpy.types.MaterialRaytraceMirror attribute), 519

fresnel_factor (bpy.types.MaterialRaytraceTransparency attribute), 521
friction (bpy.types.ClothCollisionSettings attribute), 244
friction (bpy.types.MaterialPhysics attribute), 518
friction (bpy.types.SoftBodySettings attribute), 805
friction_coefficients (bpy.types.GameObjectSettings attribute), 416
friction_factor (bpy.types.CollisionSettings attribute), 253
friction_random (bpy.types.CollisionSettings attribute), 253
from_id() (bge.types.CListValue method), 1091
from_id() (bpy.types.KeyMapItems method), 468
from_max_x (bpy.types.TransformConstraint attribute), 944
from_max_y (bpy.types.TransformConstraint attribute), 944
from_max_z (bpy.types.TransformConstraint attribute), 944
from_min_x (bpy.types.TransformConstraint attribute), 944
from_min_y (bpy.types.TransformConstraint attribute), 944
from_min_z (bpy.types.TransformConstraint attribute), 944
from_pydata() (bpy.types.Mesh method), 540
from_string() (bpy.types.Text method), 864
front (bpy.types.MaterialSubsurfaceScattering attribute), 524
frustum_culling (bge.types.KX_Camera attribute), 1141
Function (class in bpy.types), 407
Function.description (in module bpy.types), 407
Function.identifier (in module bpy.types), 407
Function.is_registered (in module bpy.types), 407
Function.is_registered_optional (in module bpy.types), 408
Function.parameters (in module bpy.types), 408
Function.use_self (in module bpy.types), 408
function_type (bpy.types.FModifierFunctionGenerator attribute), 387
fuzzy (bpy.types.SoftBodySettings attribute), 805

G

g (bge.types.KX_VertexProxy attribute), 1131
g (mathutils.Color attribute), 1039
gain (bpy.types.CompositorNodeChromaMatte attribute), 265
gain (bpy.types.CompositorNodeColorBalance attribute), 266
gain (bpy.types.MusgraveTexture attribute), 581
gain (bpy.types.SequenceColorBalance attribute), 762
gain_3d_max (bpy.types.SoundActuator attribute), 811
gain_3d_min (bpy.types.SoundActuator attribute), 811
game_property_clear() (in module bpy.ops.object), 69
game_property_copy() (in module bpy.ops.object), 69
game_property_new() (in module bpy.ops.object), 70
game_property_remove() (in module bpy.ops.object), 70
game_start() (in module bpy.ops.view3d), 129
GameActuator (class in bpy.types), 413
GameBooleanProperty (class in bpy.types), 413
GameFloatProperty (class in bpy.types), 414
GameIntProperty (class in bpy.types), 415
GameObjectSettings (class in bpy.types), 416
GameObjectSettings.actuators (in module bpy.types), 416
GameObjectSettings.controllers (in module bpy.types), 416
GameObjectSettings.properties (in module bpy.types), 417
GameObjectSettings.sensors (in module bpy.types), 417
GameObjectSettings.soft_body (in module bpy.types), 418
GameObjectSettings.used_states (in module bpy.types), 419
GameProperty (class in bpy.types), 420
GameSoftBodySettings (class in bpy.types), 420
GameStringProperty (class in bpy.types), 422
GameTimerProperty (class in bpy.types), 423
gamma (bpy.types.AreaLamp attribute), 163
gamma (bpy.types.CompositorNodeColorBalance attribute), 266
gamma (bpy.types.CompositorNodeTonemap attribute), 308
gamma (bpy.types.SequenceColorBalance attribute), 762
gather_method (bpy.types.WorldLighting attribute), 1017
generate() (bpy.types.KeyingSetInfo method), 476
generate_particles (bpy.types.DomainFluidSettings attribute), 347
generated_height (bpy.types.Image attribute), 439
generated_type (bpy.types.Image attribute), 439
generated_width (bpy.types.Image attribute), 439
gesture() (in module bpy.ops.sketch), 105
get() (bge.types.CListValue method), 1091
get() (bge.types.KX_GameObject method), 1104
get() (bge.types.KX_Scene method), 1125
get() (bpy.types.bpy_struct method), 1027
getAngularVelocity() (bge.types.KX_GameObject method), 1099
getAverageFrameRate() (in module bge.logic), 1159
getAxisVect() (bge.types.KX_GameObject method), 1098
getBlendFileList() (in module bge.logic), 1159
getButtonActiveList() (bge.types.SCA_JoystickSensor method), 1136
getButtonStatus() (bge.types.SCA_JoystickSensor method), 1136
getButtonStatus() (bge.types.SCA_MouseSensor method), 1108

getCameraToWorld() (bge.types.KX_Camera method), 1143
getChannel() (bge.types.BL_ActionActuator method), 1087
getConeHeight() (bge.types.KX_RadarSensor method), 1120
getConstraintId() (bge.types.KX_ConstraintWrapper method), 1093
getConstraintId() (bge.types.KX_VehicleWrapper method), 1128
getConstraintType() (bge.types.KX_VehicleWrapper method), 1128
getCurrentController() (in module bge.logic), 1157
getCurrentScene() (in module bge.logic), 1157
getDistanceTo() (bge.types.KX_GameObject method), 1101
getEyeSeparation() (in module bge.render), 1171
getFocalLength() (in module bge.render), 1171
getFragmentProg() (bge.types.BL_Shader method), 1087
getGLSLMaterialSetting() (in module bge.render), 1171
getKeyStatus() (bge.types.SCA_KeyboardSensor method), 1136
getLastDraw() (bge.types.SCA_RandomSensor method), 1140
getLinearVelocity() (bge.types.KX_GameObject method), 1099
getLogicTicRate() (in module bge.logic), 1159
getMaterial() (bge.types.KX_PolyProxy method), 1114
getMaterialIndex() (bge.types.KX_BlenderMaterial method), 1092
getMaterialIndex() (bge.types.KX_PolyProxy method), 1114
getMaterialMode() (in module bge.render), 1171
getMaterialName() (bge.types.KX_MeshProxy method), 1107
getMaterialName() (bge.types.KX_PolyProxy method), 1114
getMaxLogicFrame() (in module bge.logic), 1158
getMaxPhysicsFrame() (in module bge.logic), 1158
getMesh() (bge.types.KX_PolyProxy method), 1115
getNormal() (bge.types.KX_VertexProxy method), 1132
getNumMaterials() (bge.types.KX_MeshProxy method), 1107
getNumPolygons() (bge.types.KX_MeshProxy method), 1108
getNumVertex() (bge.types.KX_PolyProxy method), 1114
getNumWheels() (bge.types.KX_VehicleWrapper method), 1128
getPhysicsId() (bge.types.KX_GameObject method), 1101
getPhysicsTicRate() (in module bge.logic), 1159
getPolygon() (bge.types.KX_MeshProxy method), 1108
getPropertyNames() (bge.types.KX_GameObject method), 1101
getRandomFloat() (in module bge.logic), 1160
getReactionForce() (bge.types.KX_GameObject method), 1100
getRGBA() (bge.types.KX_VertexProxy method), 1132
getSceneList() (in module bge.logic), 1157
getScreenPosition() (bge.types.KX_Camera method), 1143
getScreenRay() (bge.types.KX_Camera method), 1144
getScreenVect() (bge.types.KX_Camera method), 1143
getSeed() (bge.types.SCA_RandomSensor method), 1140
getShader() (bge.types.KX_BlenderMaterial method), 1092
getSpectrum() (in module bge.logic), 1158
getStripElem() (bpy.types.Sequence method), 761
getTextureName() (bge.types.KX_MeshProxy method), 1107
getTextureName() (bge.types.KX_PolyProxy method), 1114
getUV() (bge.types.KX_VertexProxy method), 1131
getUV2() (bge.types.KX_VertexProxy method), 1131
getVectTo() (bge.types.KX_GameObject method), 1101
getVelocity() (bge.types.KX_GameObject method), 1100
getVertex() (bge.types.KX_MeshProxy method), 1107
getVertexArrayLength() (bge.types.KX_MeshProxy method), 1107
getVertexIndex() (bge.types.KX_PolyProxy method), 1114
getVertexProg() (bge.types.BL_Shader method), 1087
getWheelOrientationQuaternion() (bge.types.KX_VehicleWrapper method), 1128
getWheelPosition() (bge.types.KX_VehicleWrapper method), 1129
getWheelRotation() (bge.types.KX_VehicleWrapper method), 1129
getWindowHeight() (in module bge.render), 1170
getWindowWidth() (in module bge.render), 1169
getWorldToCamera() (bge.types.KX_Camera method), 1143
getXYZ() (bge.types.KX_VertexProxy method), 1131
ghost (bge.types.KX_ParentActuator attribute), 1112
ghost_curves_clear() (in module bpy.ops.graph), 35
ghost_curves_create() (in module bpy.ops.graph), 35
ghost_frame_end (bpy.types.Armature attribute), 166
ghost_frame_start (bpy.types.Armature attribute), 166
ghost_range_max (bpy.types.GPencilLayer attribute), 410
ghost_size (bpy.types.Armature attribute), 166
ghost_step (bpy.types.Armature attribute), 166
ghost_type (bpy.types.Armature attribute), 166
GKEY (in module bge.events), 1173

gl_clip_alpha (bpy.types.UserPreferencesSystem attribute), 986
gl_free() (bpy.types.Image method), 441
gl_load() (bpy.types.Image method), 441
gl_texture (bge.types.KX_PolygonMaterial attribute), 1117
gl_texture_limit (bpy.types.UserPreferencesSystem attribute), 986
glare_type (bpy.types.CompositorNodeGlare attribute), 284
globalDict (in module bge.logic), 1156
gloss_anisotropic (bpy.types.MaterialRaytraceMirror attribute), 519
gloss_factor (bpy.types.MaterialRaytraceMirror attribute), 519
gloss_factor (bpy.types.MaterialRaytraceTransparency attribute), 521
gloss_samples (bpy.types.MaterialRaytraceMirror attribute), 519
gloss_samples (bpy.types.MaterialRaytraceTransparency attribute), 521
gloss_threshold (bpy.types.MaterialRaytraceMirror attribute), 519
gloss_threshold (bpy.types.MaterialRaytraceTransparency attribute), 521
GlowSequence (class in bpy.types), 423
glsl_shader (bpy.types.Filter2DActuator attribute), 399
goal_default (bpy.types.ClothSettings attribute), 246
goal_default (bpy.types.SoftBodySettings attribute), 805
goal_friction (bpy.types.ClothSettings attribute), 246
goal_friction (bpy.types.SoftBodySettings attribute), 805
goal_max (bpy.types.ClothSettings attribute), 246
goal_max (bpy.types.SoftBodySettings attribute), 805
goal_min (bpy.types.ClothSettings attribute), 246
goal_min (bpy.types.SoftBodySettings attribute), 805
goal_spring (bpy.types.ClothSettings attribute), 246
goal_spring (bpy.types.SoftBodySettings attribute), 805
GPencilFrame (class in bpy.types), 408
GPencilFrame.strokes (in module bpy.types), 409
GPencilLayer (class in bpy.types), 409
GPencilLayer.active_frame (in module bpy.types), 409
GPencilLayer.frames (in module bpy.types), 410
GPencilStroke (class in bpy.types), 411
GPencilStroke.points (in module bpy.types), 411
GPencilStrokePoint (class in bpy.types), 412
grab_clone() (in module bpy.ops.paint), 83
gravity (bpy.types.ClothSettings attribute), 246
gravity (bpy.types.DomainFluidSettings attribute), 347
gravity (bpy.types.EffectorWeights attribute), 365
gravity (bpy.types.Scene attribute), 736
gravity (bpy.types.SoftBodySettings attribute), 805
gravity_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
grease_pencil (bpy.types.NodeTree attribute), 600
grease_pencil (bpy.types.Object attribute), 606
grease_pencil (bpy.types.Scene attribute), 736
grease_pencil (bpy.types.SpaceImageEditor attribute), 820
grease_pencil_eraser_radius (bpy.types.UserPreferencesEdit attribute), 977
grease_pencil_euclidean_distance (bpy.types.UserPreferencesEdit attribute), 978
grease_pencil_manhattan_distance (bpy.types.UserPreferencesEdit attribute), 978
GreasePencil (class in bpy.types), 425
GreasePencil.layers (in module bpy.types), 426
grid (bpy.types.ThemeAudioWindow attribute), 897
grid (bpy.types.ThemeDopeSheet attribute), 901
grid (bpy.types.ThemeGraphEditor attribute), 907
grid (bpy.types.ThemeNLAEditor attribute), 914
grid (bpy.types.ThemeSequenceEditor attribute), 920
grid (bpy.types.ThemeTimeline attribute), 925
grid (bpy.types.ThemeView3D attribute), 930
grid_levels (bpy.types.DomainFluidSettings attribute), 347
grid_lines (bpy.types.SpaceView3D attribute), 836
grid_random (bpy.types.ParticleSettings attribute), 654
grid_resolution (bpy.types.ParticleSettings attribute), 654
grid_scale (bpy.types.SpaceView3D attribute), 836
grid_subdivisions (bpy.types.SpaceView3D attribute), 836
group (bpy.types.ClothCollisionSettings attribute), 244
group (bpy.types.EffectorWeights attribute), 365
group (bpy.types.FCurve attribute), 377
group (bpy.types.KeyingSetPath attribute), 477
Group (class in bpy.types), 427
Group.objects (in module bpy.types), 427
Group.users_dupli_group (in module bpy.types), 427
group_add() (in module bpy.ops.object), 70
group_add() (in module bpy.ops.pose), 89
group_assign() (in module bpy.ops.pose), 89
group_deselect() (in module bpy.ops.pose), 89
group_edit() (in module bpy.ops.node), 63
group_instance_add() (in module bpy.ops.object), 70
group_link() (in module bpy.ops.object), 70
group_make() (in module bpy.ops.node), 64
group_method (bpy.types.KeyingSetPath attribute), 477
group_node (bpy.types.ThemeNodeEditor attribute), 915
group_operation() (in module bpy.ops.outliner), 81
group_remove() (in module bpy.ops.object), 70
group_remove() (in module bpy.ops.pose), 89
group_select() (in module bpy.ops.pose), 89
group_socket_add() (in module bpy.ops.node), 64
group_socket_move_down() (in module bpy.ops.node), 64

group_socket_move_up() (in module bpy.ops.node), 64
group_socket_remove() (in module bpy.ops.node), 64
group_unassign() (in module bpy.ops.pose), 89
group_ungroup() (in module bpy.ops.node), 64
GroupInputs (class in bpy.types), 428
GroupObjects (class in bpy.types), 429
GroupOutputs (class in bpy.types), 430
guide_clump_amount (bpy.types.FieldSettings attribute), 394
guide_clump_shape (bpy.types.FieldSettings attribute), 394
guide_free (bpy.types.FieldSettings attribute), 394
guide_kink_amplitude (bpy.types.FieldSettings attribute), 394
guide_kink_axis (bpy.types.FieldSettings attribute), 394
guide_kink_frequency (bpy.types.FieldSettings attribute), 394
guide_kink_shape (bpy.types.FieldSettings attribute), 394
guide_kink_type (bpy.types.FieldSettings attribute), 394
guide_minimum (bpy.types.FieldSettings attribute), 394

H

h (mathutils.Color attribute), 1040
hair_length (bpy.types.ParticleSettings attribute), 654
hair_step (bpy.types.ParticleSettings attribute), 654
half_life_time (bpy.types.RandomActuator attribute), 705
halo_intensity (bpy.types.SpotLamp attribute), 848
halo_step (bpy.types.SpotLamp attribute), 848
Handle (class in aud), 1079
handle_align (bpy.types.ThemeGraphEditor attribute), 907
handle_align (bpy.types.ThemeView3D attribute), 930
handle_auto (bpy.types.ThemeGraphEditor attribute), 907
handle_auto (bpy.types.ThemeView3D attribute), 930
handle_free (bpy.types.ThemeGraphEditor attribute), 907
handle_free (bpy.types.ThemeView3D attribute), 930
handle_left (bpy.types.BezierSplinePoint attribute), 178
handle_left (bpy.types.Keyframe attribute), 473
handle_left (bpy.types.ShapeKeyBezierPoint attribute), 791
handle_left_type (bpy.types.BezierSplinePoint attribute), 178
handle_left_type (bpy.types.Keyframe attribute), 473
handle_right (bpy.types.BezierSplinePoint attribute), 178
handle_right (bpy.types.Keyframe attribute), 473
handle_right (bpy.types.ShapeKeyBezierPoint attribute), 791
handle_right_type (bpy.types.BezierSplinePoint attribute), 178
handle_right_type (bpy.types.Keyframe attribute), 473
handle_sel_align (bpy.types.ThemeGraphEditor attribute), 907
handle_sel_align (bpy.types.ThemeView3D attribute), 931
handle_sel_auto (bpy.types.ThemeGraphEditor attribute), 907
handle_sel_auto (bpy.types.ThemeView3D attribute), 931
handle_sel_free (bpy.types.ThemeGraphEditor attribute), 907
handle_sel_free (bpy.types.ThemeView3D attribute), 931
handle_sel_vect (bpy.types.ThemeGraphEditor attribute), 907
handle_sel_vect (bpy.types.ThemeView3D attribute), 931
handle_type() (in module bpy.ops.action), 9
handle_type() (in module bpy.ops.graph), 35
handle_type_set() (in module bpy.ops.curve), 21
handle_vect (bpy.types.ThemeGraphEditor attribute), 907
handle_vect (bpy.types.ThemeView3D attribute), 931
handle_vertex (bpy.types.ThemeGraphEditor attribute), 907
handle_vertex_select (bpy.types.ThemeGraphEditor attribute), 907
handle_vertex_size (bpy.types.ThemeGraphEditor attribute), 907
handles_view_toggle() (in module bpy.ops.graph), 35
hardness (bpy.types.MaterialHalo attribute), 516
hardness_factor (bpy.types.MaterialTextureSlot attribute), 526
harmonic (bpy.types.EffectorWeights attribute), 365
harmonic_damping (bpy.types.FieldSettings attribute), 394
has_ghost_curves (bpy.types.SpaceGraphEditor attribute), 818
has_ik (bge.types.BL_ArmatureChannel attribute), 1150
hat (bge.types.SCA_JoystickSensor attribute), 1135
hat_direction (bpy.types.JoystickSensor attribute), 457
hat_number (bpy.types.JoystickSensor attribute), 457
hatSingle (bge.types.SCA_JoystickSensor attribute), 1135
hatValues (bge.types.SCA_JoystickSensor attribute), 1134
head (bge.types.BL_ArmatureBone attribute), 1154
head (bpy.types.Bone attribute), 219
head (bpy.types.EditBone attribute), 357
head_local (bpy.types.Bone attribute), 219
head_radius (bpy.types.Bone attribute), 220
head_radius (bpy.types.EditBone attribute), 357
head_tail (bpy.types.CopyLocationConstraint attribute), 327
head_tail (bpy.types.CopyTransformsConstraint attribute), 331
head_tail (bpy.types.PivotConstraint attribute), 673
head_tail (bpy.types.StretchToConstraint attribute), 852
head_tail (bpy.types.TrackToConstraint attribute), 942
header (bpy.types.ThemeAudioWindow attribute), 897
header (bpy.types.ThemeConsole attribute), 899

header (bpy.types.ThemeDopeSheet attribute), 901
header (bpy.types.ThemeFileBrowser attribute), 903
header (bpy.types.ThemeGraphEditor attribute), 907
header (bpy.types.ThemeImageEditor attribute), 909
header (bpy.types.ThemeInfo attribute), 911
header (bpy.types.ThemeLogicEditor attribute), 912
header (bpy.types.ThemeNLAEditor attribute), 914
header (bpy.types.ThemeNodeEditor attribute), 916
header (bpy.types.ThemeOutliner attribute), 917
header (bpy.types.ThemeProperties attribute), 919
header (bpy.types.ThemeSequenceEditor attribute), 920
header (bpy.types.ThemeTextEditor attribute), 923
header (bpy.types.ThemeTimeline attribute), 925
header (bpy.types.ThemeUserPreferences attribute), 928
header (bpy.types.ThemeView3D attribute), 931
Header (class in bpy.types), 431
Header.layout (in module bpy.types), 431
header_flip() (in module bpy.ops.screen), 96
header_text (bpy.types.ThemeAudioWindow attribute), 897
header_text (bpy.types.ThemeConsole attribute), 899
header_text (bpy.types.ThemeDopeSheet attribute), 901
header_text (bpy.types.ThemeFileBrowser attribute), 903
header_text (bpy.types.ThemeGraphEditor attribute), 907
header_text (bpy.types.ThemeImageEditor attribute), 909
header_text (bpy.types.ThemeInfo attribute), 911
header_text (bpy.types.ThemeLogicEditor attribute), 912
header_text (bpy.types.ThemeNLAEditor attribute), 914
header_text (bpy.types.ThemeNodeEditor attribute), 916
header_text (bpy.types.ThemeOutliner attribute), 917
header_text (bpy.types.ThemeProperties attribute), 919
header_text (bpy.types.ThemeSequenceEditor attribute), 920
header_text (bpy.types.ThemeTextEditor attribute), 923
header_text (bpy.types.ThemeTimeline attribute), 925
header_text (bpy.types.ThemeUserPreferences attribute), 928
header_text (bpy.types.ThemeView3D attribute), 931
header_text_hi (bpy.types.ThemeAudioWindow attribute), 897
header_text_hi (bpy.types.ThemeConsole attribute), 900
header_text_hi (bpy.types.ThemeDopeSheet attribute), 902
header_text_hi (bpy.types.ThemeFileBrowser attribute), 903
header_text_hi (bpy.types.ThemeGraphEditor attribute), 907
header_text_hi (bpy.types.ThemeImageEditor attribute), 909
header_text_hi (bpy.types.ThemeInfo attribute), 911
header_text_hi (bpy.types.ThemeLogicEditor attribute), 912
header_text_hi (bpy.types.ThemeNLAEditor attribute), 914
header_text_hi (bpy.types.ThemeNodeEditor attribute), 916
header_text_hi (bpy.types.ThemeOutliner attribute), 918
header_text_hi (bpy.types.ThemeProperties attribute), 919
header_text_hi (bpy.types.ThemeSequenceEditor attribute), 920
header_text_hi (bpy.types.ThemeTextEditor attribute), 923
header_text_hi (bpy.types.ThemeTimeline attribute), 925
header_text_hi (bpy.types.ThemeUserPreferences attribute), 928
header_text_hi (bpy.types.ThemeView3D attribute), 931
header_text_set() (bpy.types.Area method), 163
header_toolbox() (in module bpy.ops.screen), 96
headtail (bge.types.BL_ArmatureConstraint attribute), 1148
health (bpy.types.BoidSettings attribute), 216
height (bge.types.KX_CameraActuator attribute), 1092
height (bpy.types.BoidSettings attribute), 216
height (bpy.types.Brush attribute), 227
height (bpy.types.CameraActuator attribute), 237
height (bpy.types.TextBox attribute), 865
height (bpy.types.WaveModifier attribute), 1006
height (bpy.types.WorldMistSettings attribute), 1019
HemiLamp (class in bpy.types), 432
hexagonal_grid (bpy.types.ParticleSettings attribute), 654
hide (bpy.types.BezierSplinePoint attribute), 178
hide (bpy.types.Bone attribute), 220
hide (bpy.types.EditBone attribute), 357
hide (bpy.types.FCurve attribute), 377
hide (bpy.types.GPencilLayer attribute), 410
hide (bpy.types.MeshEdge attribute), 545
hide (bpy.types.MeshFace attribute), 547
hide (bpy.types.MeshTextureFace attribute), 554
hide (bpy.types.MeshVertex attribute), 558
hide (bpy.types.MetaElement attribute), 564
hide (bpy.types.Object attribute), 606
hide (bpy.types.Spline attribute), 841
hide (bpy.types.SplinePoint attribute), 845
hide() (in module bpy.ops.armature), 16
hide() (in module bpy.ops.curve), 21
hide() (in module bpy.ops.mesh), 51
hide() (in module bpy.ops.particle), 86
hide() (in module bpy.ops.pose), 89
hide() (in module bpy.ops.uv), 123
hide_metaelems() (in module bpy.ops.mball), 48
hide_recent_locations (bpy.types.UserPreferencesFilePaths attribute), 981
hide_render (bpy.types.Object attribute), 606
hide_render_clear() (in module bpy.ops.object), 70
hide_render_clear_all() (in module bpy.ops.object), 70
hide_render_set() (in module bpy.ops.object), 70
hide_select (bpy.types.Bone attribute), 220

hide_select (bpy.types.EditBone attribute), 357
hide_select (bpy.types.Object attribute), 606
hide_socket_toggle() (in module bpy.ops.node), 64
hide_toggle() (in module bpy.ops.node), 64
hide_view_clear() (in module bpy.ops.object), 70
hide_view_set() (in module bpy.ops.object), 70
hidedot() (in module bpy.ops.file), 30
highlight() (in module bpy.ops.file), 30
hinge (bge.types.BL_ArmatureBone attribute), 1154
Histogram (class in bpy.types), 433
history_append() (in module bpy.ops.console), 19
history_cycle() (in module bpy.ops.console), 19
hitNormal (bge.types.KX_MouseFocusSensor attribute), 1109
hitNormal (bge.types.KX_RaySensor attribute), 1121
hitObject (bge.types.KX_MouseFocusSensor attribute), 1109
hitObject (bge.types.KX_RaySensor attribute), 1121
hitObject (bge.types.KX_TouchSensor attribute), 1109
hitObjectList (bge.types.KX_TouchSensor attribute), 1110
hitPosition (bge.types.KX_MouseFocusSensor attribute), 1109
hitPosition (bge.types.KX_RaySensor attribute), 1121
hitUV (bge.types.KX_MouseFocusSensor attribute), 1109
HKEY (in module bge.events), 1173
hold1 (bge.types.SCA_KeyboardSensor attribute), 1136
hold2 (bge.types.SCA_KeyboardSensor attribute), 1136
HOMEKEY (in module bge.events), 1176
hook_add_newob() (in module bpy.ops.object), 70
hook_add_selob() (in module bpy.ops.object), 71
hook_assign() (in module bpy.ops.object), 71
hook_recenter() (in module bpy.ops.object), 71
hook_remove() (in module bpy.ops.object), 71
hook_reset() (in module bpy.ops.object), 71
hook_select() (in module bpy.ops.object), 71
HookModifier (class in bpy.types), 434
horizon_brightness (bpy.types.LampSkySettings attribute), 486
horizon_color (bpy.types.World attribute), 1015
horizon_factor (bpy.types.WorldTextureSlot attribute), 1021
hsv (mathutils.Color attribute), 1040

I

icon_file (bpy.types.ThemeUserInterface attribute), 926
icon_filepath (bpy.types.Brush attribute), 227
id (bpy.types.DriverTarget attribute), 352
id (bpy.types.KeyingSetPath attribute), 477
ID (class in bpy.types), 435
ID.library (in module bpy.types), 435
ID.users (in module bpy.types), 435
id_data (bpy.types.bpy_struct attribute), 1029
id_operation() (in module bpy.ops.outliner), 81
id_type (bpy.types.DriverTarget attribute), 353
id_type (bpy.types.KeyingSetPath attribute), 477
identity() (mathutils.Matrix method), 1043
IDMaterials (class in bpy.types), 437
idname (bpy.types.KeyMapItem attribute), 463
ik_add() (in module bpy.ops.pose), 89
ik_clear() (in module bpy.ops.pose), 89
ik_dist (bge.types.BL_ArmatureConstraint attribute), 1149
ik_dof_x (bge.types.BL_ArmatureChannel attribute), 1150
ik_dof_y (bge.types.BL_ArmatureChannel attribute), 1150
ik_dof_z (bge.types.BL_ArmatureChannel attribute), 1150
ik_flag (bge.types.BL_ArmatureConstraint attribute), 1149
ik_limit_x (bge.types.BL_ArmatureChannel attribute), 1150
ik_limit_y (bge.types.BL_ArmatureChannel attribute), 1150
ik_limit_z (bge.types.BL_ArmatureChannel attribute), 1150
ik_lin_control (bge.types.BL_ArmatureChannel attribute), 1150
ik_lin_weight (bge.types.BL_ArmatureChannel attribute), 1153
ik_linear_weight (bpy.types.PoseBone attribute), 688
ik_max_x (bge.types.BL_ArmatureChannel attribute), 1152
ik_max_x (bpy.types.PoseBone attribute), 688
ik_max_y (bge.types.BL_ArmatureChannel attribute), 1152
ik_max_y (bpy.types.PoseBone attribute), 688
ik_max_z (bge.types.BL_ArmatureChannel attribute), 1152
ik_max_z (bpy.types.PoseBone attribute), 688
ik_min_x (bge.types.BL_ArmatureChannel attribute), 1152
ik_min_x (bpy.types.PoseBone attribute), 688
ik_min_y (bge.types.BL_ArmatureChannel attribute), 1152
ik_min_y (bpy.types.PoseBone attribute), 688
ik_min_z (bge.types.BL_ArmatureChannel attribute), 1152
ik_min_z (bpy.types.PoseBone attribute), 688
ik_mode (bge.types.BL_ArmatureConstraint attribute), 1149
ik_rot_control (bge.types.BL_ArmatureChannel attribute), 1150
ik_rot_weight (bge.types.BL_ArmatureChannel attribute), 1153
ik_rotation_weight (bpy.types.PoseBone attribute), 688

ik_solver (bpy.types.Pose attribute), 686
ik_stiffness_x (bge.types.BL_ArmatureChannel attribute), 1152
ik_stiffness_x (bpy.types.PoseBone attribute), 688
ik_stiffness_y (bge.types.BL_ArmatureChannel attribute), 1152
ik_stiffness_y (bpy.types.PoseBone attribute), 688
ik_stiffness_z (bge.types.BL_ArmatureChannel attribute), 1152
ik_stiffness_z (bpy.types.PoseBone attribute), 688
ik_stretch (bge.types.BL_ArmatureChannel attribute), 1152
ik_stretch (bpy.types.PoseBone attribute), 688
ik_type (bge.types.BL_ArmatureConstraint attribute), 1149
ik_type (bpy.types.KinematicConstraint attribute), 482
ik_weight (bge.types.BL_ArmatureConstraint attribute), 1149
IKEY (in module bge.events), 1173
IKParam (class in bpy.types), 438
IKParam.ik_solver (in module bpy.types), 438
image (bpy.types.BackgroundImage attribute), 175
image (bpy.types.CompositorNodeImage attribute), 288
image (bpy.types.EnvironmentMapTexture attribute), 370
image (bpy.types.ImageTexture attribute), 447
image (bpy.types.MeshTextureFace attribute), 554
image (bpy.types.SpaceImageEditor attribute), 820
image (bpy.types.TextureNodeImage attribute), 882
image (bpy.types.UVProjectModifier attribute), 971
image (bpy.types.VoxelDataTexture attribute), 1004
Image (class in bpy.types), 438
Image.bindcode (in module bpy.types), 439
Image.depth (in module bpy.types), 439
Image.has_data (in module bpy.types), 440
Image.is_dirty (in module bpy.types), 440
Image.packed_file (in module bpy.types), 440
Image.size (in module bpy.types), 440
Image.type (in module bpy.types), 440
image_editor (bpy.types.UserPreferencesFilePaths attribute), 981
image_from_view() (in module bpy.ops.paint), 83
image_paint() (in module bpy.ops.paint), 83
image_paint_radial_control() (in module bpy.ops.paint), 83
image_strip (bpy.types.ThemeSequenceEditor attribute), 921
image_strip_add() (in module bpy.ops.sequencer), 100
image_type (bpy.types.CompositorNodeOutputFile attribute), 297
ImagePaint (class in bpy.types), 442
imagepaint_tool (bpy.types.Brush attribute), 228
images_separate() (in module bpy.ops.sequencer), 100
ImageSequence (class in bpy.types), 444
ImageSequence.color_balance (in module bpy.types), 444
ImageSequence.crop (in module bpy.types), 444
ImageSequence.elements (in module bpy.types), 444
ImageSequence.proxy (in module bpy.types), 444
ImageSequence.transform (in module bpy.types), 444
ImageTexture (class in bpy.types), 446
ImageTexture.image_user (in module bpy.types), 447
ImageTexture.users_material (in module bpy.types), 448
ImageTexture.users_object_modifier (in module bpy.types), 448
ImageUser (class in bpy.types), 450
ImageUser.multilayer_layer (in module bpy.types), 450
ImageUser.multilayer_pass (in module bpy.types), 450
impact_factor (bpy.types.ObstacleFluidSettings attribute), 620
in_out_node (bpy.types.ThemeNodeEditor attribute), 916
indent() (in module bpy.ops.text), 109
indented_layout() (bpy.types.InputKeyMapPanel method), 452
index (bge.types.SCA_JoystickSensor attribute), 1135
index (bpy.types.CompositorNodeIDMask attribute), 287
index (bpy.types.PointCache attribute), 677
index() (bge.types.CListValue method), 1091
indirect_bounces (bpy.types.WorldLighting attribute), 1017
indirect_factor (bpy.types.WorldLighting attribute), 1017
inflow (bpy.types.FieldSettings attribute), 395
inflow_velocity (bpy.types.InflowFluidSettings attribute), 451
InflowFluidSettings (class in bpy.types), 451
influence (bpy.types.Constraint attribute), 317
influence (bpy.types.NlaStrip attribute), 590
info (bpy.types.GPencilLayer attribute), 410
inherit_scale (bge.types.BL_ArmatureBone attribute), 1154
initial_velocity (bpy.types.FluidFluidSettings attribute), 403
initial_velocity (bpy.types.SmokeFlowSettings attribute), 800
inner (bpy.types.ThemeWidgetColors attribute), 933
inner_anim (bpy.types.ThemeWidgetStateColors attribute), 934
inner_anim_sel (bpy.types.ThemeWidgetStateColors attribute), 934
inner_driven (bpy.types.ThemeWidgetStateColors attribute), 935
inner_driven_sel (bpy.types.ThemeWidgetStateColors attribute), 935
inner_key (bpy.types.ThemeWidgetStateColors attribute), 935
inner_key_sel (bpy.types.ThemeWidgetStateColors attribute), 935
inner_sel (bpy.types.ThemeWidgetColors attribute), 933
InputKeyMapPanel (class in bpy.types), 452
insert() (bpy.types.FCurveKeyframePoints method), 380

insert() (in module bpy.ops.console), 19
insert() (in module bpy.ops.text), 109
insert_lorem() (in module bpy.ops.font), 32
INSERTKEY (in module bge.events), 1176
instantAddObject() (bge.types.KX_SCA_AddObjectActuator method), 1122
instantReplaceMesh() (bge.types.KX_SCA_ReplaceMeshActuator method), 1123
int (bpy.types.PropertyGroupItem attribute), 698
int_array (bpy.types.PropertyGroupItem attribute), 698
int_max (bpy.types.RandomActuator attribute), 705
int_mean (bpy.types.RandomActuator attribute), 705
int_min (bpy.types.RandomActuator attribute), 705
int_value (bpy.types.RandomActuator attribute), 705
integral_coefficient (bpy.types.ObjectActuator attribute), 615
integrator (bpy.types.ParticleSettings attribute), 654
intensity (bpy.types.CompositorNodeTonemap attribute), 308
intensity (bpy.types.Texture attribute), 873
intensity (bpy.types.VoxelData attribute), 1003
intensity (bpy.types.WorldMistSettings attribute), 1019
interaction_preset_add() (in module bpy.ops.wm), 136
internal_friction (bpy.types.ClothSettings attribute), 247
interpolate_bezier() (in module mathutils.geometry), 1069
interpolation (bpy.types.ColorRamp attribute), 255
interpolation (bpy.types.Keyframe attribute), 473
interpolation (bpy.types.ShapeKey attribute), 789
interpolation (bpy.types.TransformSequence attribute), 947
interpolation (bpy.types.VoxelData attribute), 1003
interpolation_type() (in module bpy.ops.action), 9
interpolation_type() (in module bpy.ops.graph), 35
interpolation_type_u (bpy.types.Lattice attribute), 490
interpolation_type_v (bpy.types.Lattice attribute), 490
interpolation_type_w (bpy.types.Lattice attribute), 490
intersect_line_line() (in module mathutils.geometry), 1069
intersect_line_line_2d() (in module mathutils.geometry), 1069
intersect_point_line() (in module mathutils.geometry), 1070
intersect_point_quad_2d() (in module mathutils.geometry), 1070
intersect_point_tri_2d() (in module mathutils.geometry), 1070
intersect_ray_tri() (in module mathutils.geometry), 1070
IntProperty (class in bpy.types), 453
IntProperty() (in module bpy.props), 1036
IntProperty.array_length (in module bpy.types), 453
IntProperty.default (in module bpy.types), 453
IntProperty.default_array (in module bpy.types), 453
IntProperty.hard_max (in module bpy.types), 453
IntProperty.hard_min (in module bpy.types), 453
IntProperty.soft_max (in module bpy.types), 454
IntProperty.soft_min (in module bpy.types), 454
IntProperty.step (in module bpy.types), 454
introspect() (bpy.types.UILayout method), 970
IntVectorProperty() (in module bpy.props), 1036
invalid (bge.types.PyObjectPlus attribute), 1083
invert (bge.types.SCA_ISensor attribute), 1084
invert (bpy.types.Sensor attribute), 758
invert (bpy.types.TextureSlot attribute), 894
invert() (in module bpy.ops.image), 38
invert() (mathutils.Matrix method), 1043
invert_alpha (bpy.types.CompositorNodeInvert attribute), 288
invert_alpha (bpy.types.ImageTexture attribute), 447
invert_gain (bpy.types.SequenceColorBalance attribute), 762
invert_gamma (bpy.types.SequenceColorBalance attribute), 762
invert_grid (bpy.types.ParticleSettings attribute), 654
invert_lift (bpy.types.SequenceColorBalance attribute), 762
invert_mouse_wheel_zoom (bpy.types.UserPreferencesInput attribute), 983
invert_normal (bpy.types.ShaderNodeExtendedMaterial attribute), 770
invert_normal (bpy.types.ShaderNodeMaterial attribute), 775
invert_rgb (bpy.types.CompositorNodeInvert attribute), 289
invert_stencil (bpy.types.ImagePaint attribute), 442
invert_vertex_group (bpy.types.ArmatureModifier attribute), 171
invert_vertex_group (bpy.types.MaskModifier attribute), 508
invert_vertex_group (bpy.types.MeshDeformModifier attribute), 543
invert_vertex_group (bpy.types.SolidifyModifier attribute), 808
invert_vertex_group_clump (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_density (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_field (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_kink (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_length (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_rotation (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_roughness_1 (bpy.types.ParticleSystem attribute), 667

invert_vertex_group_roughness_2 (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_roughness_end (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_size (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_tangent (bpy.types.ParticleSystem attribute), 667
invert_vertex_group_velocity (bpy.types.ParticleSystem attribute), 668
invert_x (bpy.types.CopyLocationConstraint attribute), 327
invert_x (bpy.types.CopyRotationConstraint attribute), 328
invert_y (bpy.types.CopyLocationConstraint attribute), 327
invert_y (bpy.types.CopyRotationConstraint attribute), 328
invert_z (bpy.types.CopyLocationConstraint attribute), 327
invert_z (bpy.types.CopyRotationConstraint attribute), 328
invert_z (bpy.types.Material attribute), 510
invert_zmask (bpy.types.SceneRenderLayer attribute), 746
invert_zoom_wheel (bpy.types.UserPreferencesInput attribute), 983
inverted() (mathutils.Matrix method), 1043
invoke() (bpy.types.Operator method), 626
invoke_confirm() (bpy.types.WindowManager class method), 1010
invoke_popup() (bpy.types.WindowManager class method), 1010
invoke_props_dialog() (bpy.types.WindowManager class method), 1010
invoke_props_popup() (bpy.types.WindowManager class method), 1009
invoke_search_popup() (bpy.types.WindowManager class method), 1010
ior (bpy.types.MaterialRaytraceTransparency attribute), 521
ior (bpy.types.MaterialSubsurfaceScattering attribute), 525
is_edited (bpy.types.GPencilFrame attribute), 408
is_fgon (bpy.types.MeshEdge attribute), 545
is_loose (bpy.types.MeshEdge attribute), 545
is_modified (bpy.types.MotionPath attribute), 571
is_negative (mathutils.Matrix attribute), 1045
is_property_hidden() (bpy.types.bpy_struct method), 1027
is_property_set() (bpy.types.bpy_struct method), 1027
is_proxy_local (bpy.types.Constraint attribute), 317
is_start (bpy.types.OperatorStrokeElement attribute), 630
is_subdir() (in module bpy.path), 1031
is_user_defined (bpy.types.KeyMap attribute), 461
is_valid (bpy.types.Driver attribute), 351
is_valid (bpy.types.FCurve attribute), 377
is_valid (bpy.types.ParticleTarget attribute), 672
is_visible() (bpy.types.Object method), 611
is_wrapped (mathutils.Color attribute), 1040
is_wrapped (mathutils.Euler attribute), 1041
is_wrapped (mathutils.Matrix attribute), 1045
is_wrapped (mathutils.Quaternion attribute), 1047
is_wrapped (mathutils.Vector attribute), 1052
isCollider() (bge.types.KX_PolyProxy method), 1114
isolate_type_render() (in module bpy.ops.object), 71
isValid() (bge.types.BL_Shader method), 1087
isVisible() (bge.types.KX_PolyProxy method), 1114
Itasc (class in bpy.types), 455
item (bpy.types.ThemeWidgetColors attribute), 933
item_activate() (in module bpy.ops.outliner), 82
item_openclose() (in module bpy.ops.outliner), 82
item_rename() (in module bpy.ops.outliner), 82
items() (bpy.types.bpy_struct method), 1027
iterations (bpy.types.CompositorNodeBilateralblur attribute), 261
iterations (bpy.types.CompositorNodeDBlur attribute), 276
iterations (bpy.types.CompositorNodeGlare attribute), 284
iterations (bpy.types.Itasc attribute), 455
iterations (bpy.types.KinematicConstraint attribute), 482
iterations (bpy.types.ScrewModifier attribute), 755
iterations (bpy.types.SmoothModifier attribute), 802
iterator() (bpy.types.KeyingSetInfo method), 476

J

jitter (bpy.types.Brush attribute), 228
jitter_factor (bpy.types.ParticleSettings attribute), 655
JKEY (in module bge.events), 1173
job_category (bpy.types.NetRenderSettings attribute), 586
job_id (bpy.types.NetRenderSettings attribute), 586
job_name (bpy.types.NetRenderSettings attribute), 587
job_type (bpy.types.NetRenderSettings attribute), 587
join() (in module bpy.ops.object), 71
join_shapes() (in module bpy.ops.object), 71
join_uvs() (in module bpy.ops.object), 71
joint_bindings (bpy.types.SplineIKConstraint attribute), 844
joint_rotation (bge.types.BL_ArmatureChannel attribute), 1153
joystick_index (bpy.types.JoystickSensor attribute), 457
JoystickSensor (class in bpy.types), 456
jump() (in module bpy.ops.text), 109

K

keep (aud.Handle attribute), 1081

keep_axis (bpy.types.StretchToConstraint attribute), 852
KERNING_DEFAULT (in module blf), 1071
key (bge.types.SCA_KeyboardSensor attribute), 1136
key (bpy.types.CompositorNodeTonemap attribute), 308
key (bpy.types.KeyboardSensor attribute), 471
Key (class in bpy.types), 458
Key.animation_data (in module bpy.types), 458
Key.keys (in module bpy.types), 458
Key.reference_key (in module bpy.types), 458
Key.user (in module bpy.types), 458
key_modifier (bpy.types.KeyMapItem attribute), 464
keyboard (in module bge.logic), 1156
KeyboardSensor (class in bpy.types), 471
KeyConfig (class in bpy.types), 459
KeyConfig.is_user_defined (in module bpy.types), 459
KeyConfig.keymaps (in module bpy.types), 459
keyconfig_activate() (in module bpy.ops.wm), 136
keyconfig_export() (in module bpy.ops.wm), 136
keyconfig_import() (in module bpy.ops.wm), 136
keyconfig_preset_add() (in module bpy.ops.wm), 137
keyconfig_remove() (in module bpy.ops.wm), 137
keyconfig_set() (in module bpy.utils), 1029
keyconfig_test() (in module bpy.ops.wm), 137
KeyConfigurations (class in bpy.types), 460
KeyConfigurations.default (in module bpy.types), 460
keyed_loops (bpy.types.ParticleSettings attribute), 655
keyframe (bpy.types.ThemeSequenceEditor attribute), 921
Keyframe (class in bpy.types), 473
keyframe_delete() (bpy.types.bpy_struct method), 1028
keyframe_delete() (in module bpy.ops.anim), 12
keyframe_delete_button() (in module bpy.ops.anim), 12
keyframe_delete_v3d() (in module bpy.ops.anim), 13
keyframe_insert() (bpy.types.bpy_struct method), 1028
keyframe_insert() (in module bpy.ops.action), 9
keyframe_insert() (in module bpy.ops.anim), 13
keyframe_insert() (in module bpy.ops.graph), 36
keyframe_insert_button() (in module bpy.ops.anim), 13
keyframe_insert_menu() (in module bpy.ops.anim), 13
keyframe_jump() (in module bpy.ops.screen), 96
keyframe_new_handle_type (bpy.types.UserPreferencesEdit attribute), 978
keyframe_new_interpolation_type (bpy.types.UserPreferencesEdit attribute), 978
keyframe_type() (in module bpy.ops.action), 9
keying_set_active_set() (in module bpy.ops.anim), 13
keying_set_add() (in module bpy.ops.anim), 13
keying_set_export() (in module bpy.ops.anim), 13
keying_set_path_add() (in module bpy.ops.anim), 13
keying_set_path_remove() (in module bpy.ops.anim), 13
keying_set_remove() (in module bpy.ops.anim), 13
KeyingSet (class in bpy.types), 475
KeyingSet.is_path_absolute (in module bpy.types), 475
KeyingSet.paths (in module bpy.types), 475
KeyingSet.type_info (in module bpy.types), 475
keyingset_add_selected() (in module bpy.ops.outliner), 82
keyingset_button_add() (in module bpy.ops.anim), 13
keyingset_button_remove() (in module bpy.ops.anim), 14
keyingset_remove_selected() (in module bpy.ops.outliner), 82
KeyingSetInfo (class in bpy.types), 476
KeyingSetPath (class in bpy.types), 477
KeyingSetPaths (class in bpy.types), 478
KeyingSets (class in bpy.types), 480
KeyingSetsAll (class in bpy.types), 481
keyitem_add() (in module bpy.ops.wm), 137
keyitem_remove() (in module bpy.ops.wm), 137
keyitem_restore() (in module bpy.ops.wm), 137
KeyMap (class in bpy.types), 461
KeyMap.is_modal (in module bpy.types), 461
KeyMap.items (in module bpy.types), 461
KeyMap.name (in module bpy.types), 461
KeyMap.region_type (in module bpy.types), 462
KeyMap.space_type (in module bpy.types), 462
keymap_edit() (in module bpy.ops.wm), 137
keymap_restore() (in module bpy.ops.wm), 137
KeyMapItem (class in bpy.types), 463
KeyMapItem.id (in module bpy.types), 463
KeyMapItem.is_user_defined (in module bpy.types), 464
KeyMapItem.name (in module bpy.types), 464
KeyMapItem.properties (in module bpy.types), 464
KeyMapItems (class in bpy.types), 466
KeyMaps (class in bpy.types), 469
keys() (bpy.types.bpy_struct method), 1028
keys_step (bpy.types.ParticleSettings attribute), 655
KinematicConstraint (class in bpy.types), 481
kink (bpy.types.ParticleSettings attribute), 655
kink_amplitude (bpy.types.ParticleSettings attribute), 655
kink_amplitude_clump (bpy.types.ParticleSettings attribute), 655
kink_axis (bpy.types.ParticleSettings attribute), 655
kink_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
kink_flat (bpy.types.ParticleSettings attribute), 655
kink_frequency (bpy.types.ParticleSettings attribute), 655
kink_shape (bpy.types.ParticleSettings attribute), 655
KKEY (in module bge.events), 1173
knife_cut() (in module bpy.ops.mesh), 51
KX_ACT_CONSTRAINT_DISTANCE (in module bge.logic), 1161
KX_ACT_CONSTRAINT_DOROTFH (in module bge.logic), 1162
KX_ACT_CONSTRAINT_FHNX (in module bge.logic), 1162

KX_ACT_CONSTRAINT_FHNY (in module bge.logic), 1162
KX_ACT_CONSTRAINT_FHNZ (in module bge.logic), 1163
KX_ACT_CONSTRAINT_FHPX (in module bge.logic), 1163
KX_ACT_CONSTRAINT_FHPY (in module bge.logic), 1163
KX_ACT_CONSTRAINT_FHPZ (in module bge.logic), 1163
KX_ACT_CONSTRAINT_LOCAL (in module bge.logic), 1161
KX_ACT_CONSTRAINT_MATERIAL (in module bge.logic), 1162
KX_ACT_CONSTRAINT_NORMAL (in module bge.logic), 1161
KX_ACT_CONSTRAINT_PERMANENT (in module bge.logic), 1162
KX_ACTIONACT_FLIPPER (in module bge.logic), 1161, 1164
KX_ACTIONACT_LOOPEND (in module bge.logic), 1161, 1164
KX_ACTIONACT_LOOPSTOP (in module bge.logic), 1161, 1164
KX_ACTIONACT_PLAY (in module bge.logic), 1161, 1164
KX_ACTIONACT_PROPERTY (in module bge.logic), 1161, 1164
KX_ArmatureSensor (class in bge.types), 1145
KX_ArmatureSensor.KX_ARMSENSOR_LIN_ERROR_ABOVE (in module bge.types), 1146
KX_ArmatureSensor.KX_ARMSENSOR_LIN_ERROR_BELOW (in module bge.types), 1146
KX_ArmatureSensor.KX_ARMSENSOR_ROT_ERROR_ABOVE (in module bge.types), 1146
KX_ArmatureSensor.KX_ARMSENSOR_ROT_ERROR_BELOW (in module bge.types), 1146
KX_ArmatureSensor.KX_ARMSENSOR_STATE_CHANGED (in module bge.types), 1146
KX_BLENDER_GLSL_MATERIAL (in module bge.render), 1169
KX_BLENDER_MULTITEX_MATERIAL (in module bge.render), 1169
KX_BlenderMaterial (class in bge.types), 1092
KX_Camera (class in bge.types), 1140
KX_Camera.INSIDE (in module bge.types), 1140
KX_Camera.INTERSECT (in module bge.types), 1140
KX_Camera.OUTSIDE (in module bge.types), 1140
KX_CameraActuator (class in bge.types), 1092
KX_CONSTRAINTACT_DIRNX (in module bge.logic), 1162
KX_CONSTRAINTACT_DIRNY (in module bge.logic), 1162
KX_CONSTRAINTACT_DIRNZ (in module bge.logic), 1162
KX_CONSTRAINTACT_DIRPX (in module bge.logic), 1162
KX_CONSTRAINTACT_DIRPY (in module bge.logic), 1162
KX_CONSTRAINTACT_DIRPZ (in module bge.logic), 1162
KX_CONSTRAINTACT_LOCX (in module bge.logic), 1162
KX_CONSTRAINTACT_LOCY (in module bge.logic), 1162
KX_CONSTRAINTACT_LOCZ (in module bge.logic), 1162
KX_CONSTRAINTACT_ORIX (in module bge.logic), 1162
KX_CONSTRAINTACT_ORIY (in module bge.logic), 1162
KX_CONSTRAINTACT_ORIZ (in module bge.logic), 1162
KX_CONSTRAINTACT_ROTX (in module bge.logic), 1162
KX_CONSTRAINTACT_ROTY (in module bge.logic), 1162
KX_CONSTRAINTACT_ROTZ (in module bge.logic), 1162
KX_ConstraintActuator (class in bge.types), 1092
KX_ConstraintWrapper (class in bge.types), 1093
KX_DYN_DISABLE_DYNAMICS (in module bge.logic), 1163
KX_DYN_DISABLE_RIGID_BODY (in module bge.logic), 1163
KX_DYN_ENABLE_RIGID_BODY (in module bge.logic), 1163
KX_DYN_RESTORE_DYNAMICS (in module bge.logic), 1163
KX_DYN_SET_MASS (in module bge.logic), 1163
KX_FALSE (in module bge.logic), 1160
KX_GAME_LOAD (in module bge.logic), 1163
KX_GAME_LOADCFG (in module bge.logic), 1163
KX_GAME_QUIT (in module bge.logic), 1163
KX_GAME_RESTART (in module bge.logic), 1163
KX_GAME_SAVECFG (in module bge.logic), 1163
KX_GAME_START (in module bge.logic), 1163
KX_GameActuator (class in bge.types), 1093
KX_GameObject (class in bge.types), 1094
KX_INPUT_ACTIVE (in module bge.logic), 1165
KX_INPUT_JUST_ACTIVATED (in module bge.logic), 1165
KX_INPUT_JUST_RELEASED (in module bge.logic), 1165
KX_INPUT_NONE (in module bge.logic), 1165
KX_IPOACT_FLIPPER (in module bge.logic), 1163
KX_IPOACT_FROM_PROP (in module bge.logic), 1163

KX_IPOACT_LOOPEND (in module bge.logic), 1163
KX_IPOACT_LOOPSTOP (in module bge.logic), 1163
KX_IPOACT_PINGPONG (in module bge.logic), 1163
KX_IPOACT_PLAY (in module bge.logic), 1163
KX_IpoActuator (class in bge.types), 1104
KX_LightObject (class in bge.types), 1105
KX_LightObject.NORMAL (in module bge.types), 1105
KX_LightObject.SPOT (in module bge.types), 1105
KX_LightObject.SUN (in module bge.types), 1105
KX_MeshProxy (class in bge.types), 1106
KX_MOUSE_BUT_LEFT (in module bge.logic), 1165
KX_MOUSE_BUT_MIDDLE (in module bge.logic), 1165
KX_MOUSE_BUT_RIGHT (in module bge.logic), 1165
KX_MouseFocusSensor (class in bge.types), 1108
KX_NearSensor (class in bge.types), 1110
KX_NetworkMessageActuator (class in bge.types), 1110
KX_NetworkMessageSensor (class in bge.types), 1110
KX_ObjectActuator (class in bge.types), 1110
KX_PARENT_REMOVE (in module bge.logic), 1164
KX_PARENT_SET (in module bge.logic), 1164
KX_ParentActuator (class in bge.types), 1112
KX_PhysicsObjectWrapper (class in bge.types), 1112
KX_PolygonMaterial (class in bge.types), 1115
KX_PolyProxy (class in bge.types), 1113
KX_PROPSENSOR_CHANGED (in module bge.logic), 1160
KX_PROPSENSOR_EQUAL (in module bge.logic), 1160
KX_PROPSENSOR_EXPRESSION (in module bge.logic), 1160
KX_PROPSENSOR_INTERVAL (in module bge.logic), 1160
KX_PROPSENSOR_NOTEQUAL (in module bge.logic), 1160
KX_RADAR_AXIS_NEG_X (in module bge.logic), 1161
KX_RADAR_AXIS_NEG_Y (in module bge.logic), 1161
KX_RADAR_AXIS_NEG_Z (in module bge.logic), 1161
KX_RADAR_AXIS_POS_X (in module bge.logic), 1161
KX_RADAR_AXIS_POS_Y (in module bge.logic), 1161
KX_RADAR_AXIS_POS_Z (in module bge.logic), 1161
KX_RadarSensor (class in bge.types), 1120
KX_RANDOMACT_BOOL_BERNOUILLI (in module bge.logic), 1164
KX_RANDOMACT_BOOL_CONST (in module bge.logic), 1164
KX_RANDOMACT_BOOL_UNIFORM (in module bge.logic), 1164
KX_RANDOMACT_FLOAT_CONST (in module bge.logic), 1164
KX_RANDOMACT_FLOAT_NEGATIVE_EXPONENTIAL (in module bge.logic), 1164
KX_RANDOMACT_FLOAT_NORMAL (in module bge.logic), 1164
KX_RANDOMACT_FLOAT_UNIFORM (in module bge.logic), 1164
KX_RANDOMACT_INT_CONST (in module bge.logic), 1164
KX_RANDOMACT_INT_POISSON (in module bge.logic), 1164
KX_RANDOMACT_INT_UNIFORM (in module bge.logic), 1164
KX_RAY_AXIS_NEG_X (in module bge.logic), 1161
KX_RAY_AXIS_NEG_Y (in module bge.logic), 1161
KX_RAY_AXIS_NEG_Z (in module bge.logic), 1161
KX_RAY_AXIS_POS_X (in module bge.logic), 1161
KX_RAY_AXIS_POS_Y (in module bge.logic), 1161
KX_RAY_AXIS_POS_Z (in module bge.logic), 1161
KX_RaySensor (class in bge.types), 1120
KX_SCA_AddObjectActuator (class in bge.types), 1121
KX_SCA_DynamicActuator (class in bge.types), 1122
KX_SCA_EndObjectActuator (class in bge.types), 1122
KX_SCA_ReplaceMeshActuator (class in bge.types), 1122
KX_Scene (class in bge.types), 1123
KX_SCENE_ADD_BACK_SCENE (in module bge.logic), 1164
KX_SCENE_ADD_FRONT_SCENE (in module bge.logic), 1164
KX_SCENE_REMOVE_SCENE (in module bge.logic), 1164
KX_SCENE_RESTART (in module bge.logic), 1164
KX_SCENE_RESUME (in module bge.logic), 1164
KX_SCENE_SET_CAMERA (in module bge.logic), 1164
KX_SCENE_SET_SCENE (in module bge.logic), 1164
KX_SCENE_SUSPEND (in module bge.logic), 1164
KX_SceneActuator (class in bge.types), 1125
KX_SENSOR_ACTIVE (in module bge.logic), 1160
KX_SENSOR_INACTIVE (in module bge.logic), 1160
KX_SENSOR_JUST_ACTIVATED (in module bge.logic), 1160
KX_SENSOR_JUST_DEACTIVATED (in module bge.logic), 1160
KX_SOUNDACT_LOOPBIDIRECTIONAL (in module bge.logic), 1165
KX_SOUNDACT_LOOPBIDIRECTIONAL_STOP (in module bge.logic), 1165
KX_SOUNDACT_LOOPEND (in module bge.logic), 1165
KX_SOUNDACT_LOOPSTOP (in module bge.logic), 1165
KX_SOUNDACT_PLAYEND (in module bge.logic), 1165

KX_SOUNDACT_PLAYSTOP (in module bge.logic), 1165
KX_SoundActuator (class in bge.types), 1126
KX_STATE1 (in module bge.logic), 1165
KX_STATE10 (in module bge.logic), 1166
KX_STATE11 (in module bge.logic), 1166
KX_STATE12 (in module bge.logic), 1166
KX_STATE13 (in module bge.logic), 1166
KX_STATE14 (in module bge.logic), 1166
KX_STATE15 (in module bge.logic), 1166
KX_STATE16 (in module bge.logic), 1166
KX_STATE17 (in module bge.logic), 1166
KX_STATE18 (in module bge.logic), 1166
KX_STATE19 (in module bge.logic), 1166
KX_STATE2 (in module bge.logic), 1165
KX_STATE20 (in module bge.logic), 1166
KX_STATE21 (in module bge.logic), 1166
KX_STATE22 (in module bge.logic), 1166
KX_STATE23 (in module bge.logic), 1166
KX_STATE24 (in module bge.logic), 1166
KX_STATE25 (in module bge.logic), 1166
KX_STATE26 (in module bge.logic), 1166
KX_STATE27 (in module bge.logic), 1166
KX_STATE28 (in module bge.logic), 1166
KX_STATE29 (in module bge.logic), 1166
KX_STATE3 (in module bge.logic), 1165
KX_STATE30 (in module bge.logic), 1166
KX_STATE4 (in module bge.logic), 1165
KX_STATE5 (in module bge.logic), 1166
KX_STATE6 (in module bge.logic), 1166
KX_STATE7 (in module bge.logic), 1166
KX_STATE8 (in module bge.logic), 1166
KX_STATE9 (in module bge.logic), 1166
KX_STATE_OP_CLR (in module bge.logic), 1166
KX_STATE_OP_CPY (in module bge.logic), 1166
KX_STATE_OP_NEG (in module bge.logic), 1166
KX_STATE_OP_SET (in module bge.logic), 1166
KX_StateActuator (class in bge.types), 1127
KX_TEXFACE_MATERIAL (in module bge.render), 1169
KX_TouchSensor (class in bge.types), 1109
KX_TrackToActuator (class in bge.types), 1127
KX_TRUE (in module bge.logic), 1160
KX_VehicleWrapper (class in bge.types), 1127
KX_VertexProxy (class in bge.types), 1130
KX_VisibilityActuator (class in bge.types), 1132

L

label() (bpy.types.UILayout method), 963
lacunarity (bpy.types.MusgraveTexture attribute), 581
lamp (bpy.types.ThemeView3D attribute), 931
Lamp (class in bpy.types), 484
lamp (in module bpy.context), 6
Lamp.animation_data (in module bpy.types), 484
Lamp.texture_slots (in module bpy.types), 485
lamp_add() (in module bpy.ops.object), 71
LampSkySettings (class in bpy.types), 486
LampTextureSlot (class in bpy.types), 488
LampTextureSlots (class in bpy.types), 489
land_acc_max (bpy.types.BoidSettings attribute), 216
land_ave_max (bpy.types.BoidSettings attribute), 216
land_jump_speed (bpy.types.BoidSettings attribute), 216
land_personal_space (bpy.types.BoidSettings attribute), 216
land_smooth (bpy.types.BoidSettings attribute), 216
land_speed_max (bpy.types.BoidSettings attribute), 216
land_stick_force (bpy.types.BoidSettings attribute), 216
language (bpy.types.SpaceConsole attribute), 815
language (bpy.types.UserPreferencesSystem attribute), 986
language() (in module bpy.ops.console), 19
lastDraw (bge.types.SCA_RandomSensor attribute), 1140
lastsel_point (bpy.types.ThemeGraphEditor attribute), 907
lastsel_point (bpy.types.ThemeView3D attribute), 931
Lattice (class in bpy.types), 490
lattice (in module bpy.context), 5
Lattice.animation_data (in module bpy.types), 490
Lattice.points (in module bpy.types), 490
Lattice.shape_keys (in module bpy.types), 491
LatticeModifier (class in bpy.types), 492
LatticePoint (class in bpy.types), 493
LatticePoint.co (in module bpy.types), 493
LatticePoint.groups (in module bpy.types), 493
layer (bge.types.KX_LightObject attribute), 1105
layer (bpy.types.CompositorNodeImage attribute), 288
layer (bpy.types.CompositorNodeRLayers attribute), 300
layer_add() (in module bpy.ops.gpencil), 34
layers (bpy.types.Armature attribute), 166
layers (bpy.types.Bone attribute), 220
layers (bpy.types.EditBone attribute), 357
layers (bpy.types.Group attribute), 427
layers (bpy.types.Object attribute), 606
layers (bpy.types.ObjectBase attribute), 617
layers (bpy.types.Scene attribute), 736
layers (bpy.types.SceneRenderLayer attribute), 746
layers (bpy.types.SpaceView3D attribute), 836
layers() (in module bpy.ops.view3d), 129
layers_from_view() (bpy.types.ObjectBase method), 617
layers_ignore (bpy.types.EnvironmentMap attribute), 369
layers_protected (bpy.types.Armature attribute), 166
layers_show_all() (in module bpy.ops.armature), 16
layers_zmask (bpy.types.SceneRenderLayer attribute), 746
LEFTALTKEY (in module bge.events), 1174
LEFTARROWKEY (in module bge.events), 1175
LEFTBRACKETKEY (in module bge.events), 1176

LEFTCTRLKEY (in module bge.events), 1174
LEFTMOUSE (in module bge.events), 1173
LEFTSHIFTKEY (in module bge.events), 1174
length (bge.types.BL_ArmatureBone attribute), 1154
length (bpy.types.Bone attribute), 221
length (bpy.types.EditBone attribute), 359
length (bpy.types.PoseBone attribute), 691
length (mathutils.Vector attribute), 1052
length_factor (bpy.types.ParticleSettingsTextureSlot attribute), 662
length_mode (bpy.types.ParticleBrush attribute), 641
length_random (bpy.types.ParticleSettings attribute), 655
lennardjones (bpy.types.EffectorWeights attribute), 365
lens (bge.types.KX_Camera attribute), 1140
lens (bpy.types.Camera attribute), 235
lens (bpy.types.SpaceView3D attribute), 836
lens_unit (bpy.types.Camera attribute), 235
level (bge.types.SCA_ISensor attribute), 1084
level (bpy.types.BoidRuleAverageSpeed attribute), 210
levels (bpy.types.MultiresModifier attribute), 580
levels (bpy.types.SubsurfModifier attribute), 857
LibFree() (in module bge.logic), 1158
LibLoad() (in module bge.logic), 1157
LibNew() (in module bge.logic), 1157
Library (class in bpy.types), 494
Library.parent (in module bpy.types), 494
Library.users_id (in module bpy.types), 494
life_factor (bpy.types.ParticleSettingsTextureSlot attribute), 663
lifetime (bpy.types.Particle attribute), 640
lifetime (bpy.types.ParticleSettings attribute), 655
lifetime (bpy.types.WaveModifier attribute), 1006
lifetime_random (bpy.types.ParticleSettings attribute), 655
lift (bpy.types.CompositorNodeChromaMatte attribute), 265
lift (bpy.types.CompositorNodeColorBalance attribute), 266
lift (bpy.types.SequenceColorBalance attribute), 762
light_group (bpy.types.Material attribute), 510
light_method (bpy.types.MaterialVolume attribute), 532
light_override (bpy.types.SceneRenderLayer attribute), 746
lightlayer (bge.types.KX_PolygonMaterial attribute), 1118
lightmap_pack() (in module bpy.ops.uv), 123
lights (bge.types.KX_Scene attribute), 1124
limit (bge.types.KX_ConstraintActuator attribute), 1093
limit (bpy.types.ConstraintActuator attribute), 320
limit_angle_max_x (bpy.types.RigidBodyJointConstraint attribute), 730
limit_angle_max_y (bpy.types.RigidBodyJointConstraint attribute), 730
limit_angle_max_z (bpy.types.RigidBodyJointConstraint attribute), 730
limit_angle_min_x (bpy.types.RigidBodyJointConstraint attribute), 730
limit_angle_min_y (bpy.types.RigidBodyJointConstraint attribute), 730
limit_angle_min_z (bpy.types.RigidBodyJointConstraint attribute), 730
limit_channel (bpy.types.CompositorNodeChannelMatte attribute), 264
limit_channel (bpy.types.CompositorNodeColorSpill attribute), 268
limit_max (bpy.types.CompositorNodeChannelMatte attribute), 264
limit_max (bpy.types.CompositorNodeLumaMatte attribute), 291
limit_max (bpy.types.ConstraintActuator attribute), 320
limit_max_x (bpy.types.RigidBodyJointConstraint attribute), 731
limit_max_y (bpy.types.RigidBodyJointConstraint attribute), 731
limit_max_z (bpy.types.RigidBodyJointConstraint attribute), 731
limit_method (bpy.types.BevelModifier attribute), 177
limit_method (bpy.types.CompositorNodeChannelMatte attribute), 264
limit_method (bpy.types.CompositorNodeColorSpill attribute), 268
limit_min (bpy.types.CompositorNodeChannelMatte attribute), 264
limit_min (bpy.types.CompositorNodeLumaMatte attribute), 291
limit_min (bpy.types.ConstraintActuator attribute), 320
limit_min_x (bpy.types.RigidBodyJointConstraint attribute), 731
limit_min_y (bpy.types.RigidBodyJointConstraint attribute), 731
limit_min_z (bpy.types.RigidBodyJointConstraint attribute), 731
limit_mode (bpy.types.KinematicConstraint attribute), 482
limit_mode (bpy.types.LimitDistanceConstraint attribute), 495
limitdistance_reset() (in module bpy.ops.constraint), 20
LimitDistanceConstraint (class in bpy.types), 495
LimitLocationConstraint (class in bpy.types), 496
LimitRotationConstraint (class in bpy.types), 498
limits (bpy.types.SimpleDeformModifier attribute), 796
LimitScaleConstraint (class in bpy.types), 499
lin_attenuation (bge.types.KX_LightObject attribute), 1106
lin_error (bge.types.BL_ArmatureConstraint attribute), 1148
line_break() (in module bpy.ops.font), 32

line_break() (in module bpy.ops.text), 109
line_count (bpy.types.MaterialHalo attribute), 516
line_error (bpy.types.ThemeConsole attribute), 900
line_info (bpy.types.ThemeConsole attribute), 900
line_input (bpy.types.ThemeConsole attribute), 900
line_length_head (bpy.types.ParticleSettings attribute), 656
line_length_tail (bpy.types.ParticleSettings attribute), 656
line_number() (in module bpy.ops.text), 109
line_numbers_background (bpy.types.ThemeTextEditor attribute), 923
line_output (bpy.types.ThemeConsole attribute), 900
line_width (bpy.types.GPencilLayer attribute), 410
linear_attenuation (bpy.types.PointLamp attribute), 683
linear_attenuation (bpy.types.SpotLamp attribute), 848
linear_drag (bpy.types.FieldSettings attribute), 395
linear_stiffness (bpy.types.GameSoftBodySettings attribute), 421
linear_velocity (bpy.types.EditObjectActuator attribute), 361
linear_velocity (bpy.types.ObjectActuator attribute), 615
linear_viscosity (bpy.types.SPHFluidSettings attribute), 733
linearVelocity (bge.types.KX_SCA_AddObjectActuator attribute), 1122
LINEFEEDKEY (in module bge.events), 1176
link (bpy.types.MaterialSlot attribute), 522
link() (bpy.types.Actuator method), 151
link() (bpy.types.Controller method), 326
link() (bpy.types.GroupObjects method), 429
link() (bpy.types.SceneObjects method), 745
link() (bpy.types.Sensor method), 758
link() (in module bpy.ops.node), 64
link_append() (in module bpy.ops.wm), 137
link_make() (in module bpy.ops.node), 64
link_viewer() (in module bpy.ops.node), 64
links_cut() (in module bpy.ops.logic), 46
links_cut() (in module bpy.ops.node), 64
linV (bge.types.KX_ObjectActuator attribute), 1111
linVelocityMax (bge.types.KX_GameObject attribute), 1094
linVelocityMin (bge.types.KX_GameObject attribute), 1094
list (bpy.types.ThemeDopeSheet attribute), 902
list (bpy.types.ThemeFileBrowser attribute), 903
list (bpy.types.ThemeGraphEditor attribute), 907
list (bpy.types.ThemeNLAEditor attribute), 914
list (bpy.types.ThemeNodeEditor attribute), 916
list_text (bpy.types.ThemeDopeSheet attribute), 902
list_text (bpy.types.ThemeFileBrowser attribute), 903
list_text (bpy.types.ThemeGraphEditor attribute), 907
list_text (bpy.types.ThemeNLAEditor attribute), 914
list_text (bpy.types.ThemeNodeEditor attribute), 916
list_text_hi (bpy.types.ThemeDopeSheet attribute), 902
list_text_hi (bpy.types.ThemeFileBrowser attribute), 904
list_text_hi (bpy.types.ThemeGraphEditor attribute), 908
list_text_hi (bpy.types.ThemeNLAEditor attribute), 914
list_text_hi (bpy.types.ThemeNodeEditor attribute), 916
list_title (bpy.types.ThemeDopeSheet attribute), 902
list_title (bpy.types.ThemeFileBrowser attribute), 904
list_title (bpy.types.ThemeGraphEditor attribute), 908
list_title (bpy.types.ThemeNLAEditor attribute), 914
list_title (bpy.types.ThemeNodeEditor attribute), 916
listener_location (aud.Device attribute), 1075
listener_orientation (aud.Device attribute), 1075
listener_velocity (aud.Device attribute), 1075
LKEY (in module bge.events), 1173
load() (bpy.types.BlendDataFonts method), 187
load() (bpy.types.BlendDataImages method), 190
load() (bpy.types.BlendDataLibraries method), 193
load() (bpy.types.BlendDataTexts method), 203
load() (in module blf), 1072
load_from_file() (bpy.types.RenderLayer method), 717
load_from_file() (bpy.types.RenderResult method), 720
load_scripts() (in module bpy.utils), 1029
loadGlobalDict() (in module bge.logic), 1157
loc (bpy.types.OperatorMousePath attribute), 628
loc_clear() (in module bpy.ops.pose), 89
localAngularVelocity (bge.types.KX_GameObject attribute), 1096
localInertia (bge.types.KX_GameObject attribute), 1094
localLinearVelocity (bge.types.KX_GameObject attribute), 1096
localOrientation (bge.types.KX_GameObject attribute), 1095
localPosition (bge.types.KX_GameObject attribute), 1096
localScale (bge.types.KX_GameObject attribute), 1095
localview() (in module bpy.ops.view3d), 130
location (aud.Handle attribute), 1081
location (bge.types.BL_ArmatureChannel attribute), 1150
location (bpy.types.Node attribute), 595
location (bpy.types.Object attribute), 606
location (bpy.types.OperatorStrokeElement attribute), 630
location (bpy.types.Particle attribute), 640
location (bpy.types.ParticleKey attribute), 649
location (bpy.types.PoseBone attribute), 689
location (bpy.types.ShaderNodeMapping attribute), 773
location (bpy.types.TexMapping attribute), 862
location_apply() (in module bpy.ops.object), 71
location_clear() (in module bpy.ops.object), 72
location_iterations (bpy.types.GameSoftBodySettings attribute), 421
location_mass_center (bpy.types.SoftBodySettings attribute), 805
lock (bpy.types.ActionGroup attribute), 148

lock (bpy.types.EditBone attribute), 357
lock (bpy.types.FCurve attribute), 377
lock (bpy.types.GPencilLayer attribute), 410
lock (bpy.types.NlaTrack attribute), 593
lock (bpy.types.Sequence attribute), 760
lock() (in module bpy.ops.sequencer), 100
lock_axis (bpy.types.LockedTrackConstraint attribute), 501
lock_billboard (bpy.types.ParticleSettings attribute), 656
lock_boids_to_surface (bpy.types.ParticleSettings attribute), 656
lock_bone (bpy.types.SpaceView3D attribute), 837
lock_bounds (bpy.types.SpaceUVEditor attribute), 833
lock_camera_and_layers (bpy.types.SpaceView3D attribute), 837
lock_cursor (bpy.types.SpaceView3D attribute), 837
lock_frame (bpy.types.GPencilLayer attribute), 410
lock_ik_x (bpy.types.PoseBone attribute), 689
lock_ik_y (bpy.types.PoseBone attribute), 689
lock_ik_z (bpy.types.PoseBone attribute), 689
lock_location (bpy.types.Object attribute), 606
lock_location (bpy.types.PoseBone attribute), 689
lock_location_x (bpy.types.GameObjectSettings attribute), 416
lock_location_x (bpy.types.KinematicConstraint attribute), 482
lock_location_y (bpy.types.GameObjectSettings attribute), 416
lock_location_y (bpy.types.KinematicConstraint attribute), 482
lock_location_z (bpy.types.GameObjectSettings attribute), 416
lock_location_z (bpy.types.KinematicConstraint attribute), 482
lock_object (bpy.types.SpaceView3D attribute), 837
lock_rotation (bpy.types.Object attribute), 606
lock_rotation (bpy.types.PoseBone attribute), 689
lock_rotation (bpy.types.RegionView3D attribute), 710
lock_rotation_w (bpy.types.Object attribute), 606
lock_rotation_w (bpy.types.PoseBone attribute), 689
lock_rotation_x (bpy.types.GameObjectSettings attribute), 416
lock_rotation_x (bpy.types.KinematicConstraint attribute), 482
lock_rotation_y (bpy.types.GameObjectSettings attribute), 417
lock_rotation_y (bpy.types.KinematicConstraint attribute), 482
lock_rotation_z (bpy.types.GameObjectSettings attribute), 417
lock_rotation_z (bpy.types.KinematicConstraint attribute), 482
lock_rotations_4d (bpy.types.Object attribute), 606
lock_rotations_4d (bpy.types.PoseBone attribute), 689
lock_scale (bpy.types.Object attribute), 607
lock_scale (bpy.types.PoseBone attribute), 689
lock_x (bpy.types.Sculpt attribute), 756
lock_x (bpy.types.SimpleDeformModifier attribute), 796
lock_y (bpy.types.Sculpt attribute), 756
lock_y (bpy.types.SimpleDeformModifier attribute), 796
lock_z (bpy.types.Sculpt attribute), 756
LockedTrackConstraint (class in bpy.types), 501
log (bpy.types.KeyboardSensor attribute), 471
logic_bricks_copy() (in module bpy.ops.object), 72
logic_step_max (bpy.types.SceneGameData attribute), 742
long_key (bpy.types.ThemeDopeSheet attribute), 902
long_key_selected (bpy.types.ThemeDopeSheet attribute), 902
look_ahead (bpy.types.BoidRuleAvoidCollision attribute), 212
loop_count (aud.Handle attribute), 1081
loop_multi_select() (in module bpy.ops.mesh), 51
loop_select() (in module bpy.ops.mesh), 51
loop_to_region() (in module bpy.ops.mesh), 52
loopcut() (in module bpy.ops.mesh), 52
loopcut_slide() (in module bpy.ops.mesh), 52
looping (bge.types.KX_SoundActuator attribute), 1126

M

Macro (class in bpy.types), 502
Macro.name (in module bpy.types), 502
Macro.properties (in module bpy.types), 502
MagicTexture (class in bpy.types), 503
MagicTexture.users_material (in module bpy.types), 504
MagicTexture.users_object_modifier (in module bpy.types), 504
magnetic (bpy.types.EffectorWeights attribute), 366
magnitude (mathutils.Quaternion attribute), 1047
magnitude (mathutils.Vector attribute), 1052
main_axis (bpy.types.ClampToConstraint attribute), 242
MaintainVolumeConstraint (class in bpy.types), 505
make_compatible() (mathutils.Euler method), 1040
make_dupli_face() (in module bpy.ops.object), 72
make_internal() (in module bpy.ops.text), 109
make_links_data() (in module bpy.ops.object), 72
make_links_scene() (in module bpy.ops.marker), 47
make_links_scene() (in module bpy.ops.object), 72
make_local() (in module bpy.ops.object), 72
make_paths_absolute() (in module bpy.ops.file), 30
make_paths_relative() (in module bpy.ops.file), 30
make_regular() (in module bpy.ops.lattice), 45
make_segment() (in module bpy.ops.curve), 21
make_single_user() (in module bpy.ops.object), 72
makeScreenshot() (in module bge.render), 1170
manipulator() (in module bpy.ops.view3d), 130
manipulator_handle_size (bpy.types.UserPreferencesView attribute),

988
manipulator_hotspot (bpy.types.UserPreferencesView attribute), 989
manipulator_size (bpy.types.UserPreferencesView attribute), 989
map_from (bpy.types.TransformConstraint attribute), 944
map_mode (bpy.types.BrushTextureSlot attribute), 232
map_to (bpy.types.TransformConstraint attribute), 944
map_to_x_from (bpy.types.TransformConstraint attribute), 944
map_to_y_from (bpy.types.TransformConstraint attribute), 944
map_to_z_from (bpy.types.TransformConstraint attribute), 944
map_type (bpy.types.KeyMapItem attribute), 464
mapping (bpy.types.CompositorNodePremulKey attribute), 298
mapping (bpy.types.EnvironmentMap attribute), 369
mapping (bpy.types.Image attribute), 440
mapping (bpy.types.MaterialTextureSlot attribute), 527
mapping (bpy.types.ParticleSettingsTextureSlot attribute), 663
mapping_x (bpy.types.MaterialTextureSlot attribute), 527
mapping_x (bpy.types.ParticleSettingsTextureSlot attribute), 663
mapping_y (bpy.types.MaterialTextureSlot attribute), 527
mapping_y (bpy.types.ParticleSettingsTextureSlot attribute), 663
mapping_z (bpy.types.MaterialTextureSlot attribute), 527
mapping_z (bpy.types.ParticleSettingsTextureSlot attribute), 663
marble_type (bpy.types.MarbleTexture attribute), 506
MarbleTexture (class in bpy.types), 506
MarbleTexture.users_material (in module bpy.types), 506
MarbleTexture.users_object_modifier (in module bpy.types), 506
margin_column (bpy.types.SpaceTextEditor attribute), 831
mark_all() (in module bpy.ops.text), 109
mark_seam() (in module bpy.ops.mesh), 52
mark_sharp() (in module bpy.ops.mesh), 52
markers_clear() (in module bpy.ops.text), 109
markers_make_local() (in module bpy.ops.action), 9
mask (bge.types.KX_StateActuator attribute), 1127
MaskModifier (class in bpy.types), 507
mass (bge.types.KX_GameObject attribute), 1094
mass (bge.types.KX_SCA_DynamicActuator attribute), 1122
mass (bpy.types.ClothSettings attribute), 247
mass (bpy.types.EditObjectActuator attribute), 361
mass (bpy.types.GameObjectSettings attribute), 417
mass (bpy.types.ParticleSettings attribute), 656
mass (bpy.types.SoftBodySettings attribute), 805
material (bge.types.KX_PolygonMaterial attribute), 1117
material (bge.types.KX_PolyProxy attribute), 1113
material (bpy.types.CollisionSensor attribute), 252
material (bpy.types.ConstraintActuator attribute), 320
material (bpy.types.MaterialSlot attribute), 522
material (bpy.types.ParticleSettings attribute), 656
material (bpy.types.RaySensor attribute), 707
material (bpy.types.ShaderNodeExtendedMaterial attribute), 770
material (bpy.types.ShaderNodeMaterial attribute), 775
material (bpy.types.TouchSensor attribute), 941
Material (class in bpy.types), 508
material (in module bpy.context), 6
Material.animation_data (in module bpy.types), 509
Material.diffuse_ramp (in module bpy.types), 509
Material.halo (in module bpy.types), 510
Material.node_tree (in module bpy.types), 510
Material.physics (in module bpy.types), 510
Material.raytrace_mirror (in module bpy.types), 511
Material.raytrace_transparency (in module bpy.types), 511
Material.specular_ramp (in module bpy.types), 511
Material.strand (in module bpy.types), 512
Material.subsurface_scattering (in module bpy.types), 512
Material.texture_slots (in module bpy.types), 512
Material.volume (in module bpy.types), 514
material_index (bpy.types.MeshFace attribute), 547
material_index (bpy.types.Spline attribute), 841
material_link (bpy.types.UserPreferencesEdit attribute), 978
material_mode (bpy.types.SceneGameData attribute), 742
material_offset (bpy.types.SolidifyModifier attribute), 808
material_offset_rim (bpy.types.SolidifyModifier attribute), 808
material_override (bpy.types.SceneRenderLayer attribute), 746
material_slot (in module bpy.context), 6
material_slot_add() (in module bpy.ops.object), 72
material_slot_assign() (in module bpy.ops.object), 72
material_slot_copy() (in module bpy.ops.object), 72
material_slot_deselect() (in module bpy.ops.object), 72
material_slot_remove() (in module bpy.ops.object), 72
material_slot_select() (in module bpy.ops.object), 72
MaterialHalo (class in bpy.types), 515
MaterialPhysics (class in bpy.types), 518
MaterialRaytraceMirror (class in bpy.types), 519
MaterialRaytraceTransparency (class in bpy.types), 520
materials (bge.types.KX_MeshProxy attribute), 1107
MaterialSlot (class in bpy.types), 522
MaterialSlot.name (in module bpy.types), 522
MaterialStrand (class in bpy.types), 523

MaterialStrand.use_surface_diffuse (in module bpy.types), 523
MaterialSubsurfaceScattering (class in bpy.types), 524
MaterialTextureSlot (class in bpy.types), 526
MaterialTextureSlots (class in bpy.types), 531
MaterialVolume (class in bpy.types), 532
mathutils (module), 1039
mathutils.geometry (module), 1068
matid (bge.types.KX_PolyProxy attribute), 1113
matname (bge.types.KX_PolyProxy attribute), 1113
matrix (bpy.types.Bone attribute), 220
matrix (bpy.types.DupliObject attribute), 355
matrix (bpy.types.TransformOrientation attribute), 946
Matrix (class in mathutils), 1041
Matrix.lerp() (in module mathutils), 1043
matrix_basis (bpy.types.Object attribute), 607
matrix_basis (bpy.types.PoseBone attribute), 689
matrix_local (bpy.types.Bone attribute), 220
matrix_local (bpy.types.Object attribute), 607
matrix_original (bpy.types.DupliObject attribute), 355
matrix_world (bpy.types.Object attribute), 607
matte_channel (bpy.types.CompositorNodeChannelMatte attribute), 264
max (bge.types.KX_CameraActuator attribute), 1092
max (bge.types.KX_ConstraintActuator attribute), 1093
max (bge.types.SCA_PropertySensor attribute), 1137
max (bpy.types.ActionConstraint attribute), 145
max (bpy.types.CameraActuator attribute), 237
max (bpy.types.CompositorNodeMapValue attribute), 293
max (bpy.types.FModifierEnvelopeControlPoint attribute), 386
max (bpy.types.ShaderNodeMapping attribute), 774
max (bpy.types.TexMapping attribute), 862
max_x (bpy.types.CompositorNodeCrop attribute), 273
max_x (bpy.types.FModifierLimits attribute), 389
max_x (bpy.types.LimitLocationConstraint attribute), 496
max_x (bpy.types.LimitRotationConstraint attribute), 498
max_x (bpy.types.LimitScaleConstraint attribute), 499
max_x (bpy.types.SequenceCrop attribute), 763
max_y (bpy.types.CompositorNodeCrop attribute), 273
max_y (bpy.types.FModifierLimits attribute), 389
max_y (bpy.types.LimitLocationConstraint attribute), 496
max_y (bpy.types.LimitRotationConstraint attribute), 498
max_y (bpy.types.LimitScaleConstraint attribute), 499
max_y (bpy.types.SequenceCrop attribute), 763
max_z (bpy.types.LimitLocationConstraint attribute), 496
max_z (bpy.types.LimitRotationConstraint attribute), 498
max_z (bpy.types.LimitScaleConstraint attribute), 499
median_scale (mathutils.Matrix attribute), 1045
memory_cache_limit (bpy.types.UserPreferencesSystem attribute), 986
memory_statistics() (in module bpy.ops.wm), 138
Menu (class in bpy.types), 535
menu() (bpy.types.UILayout method), 965
Menu.layout (in module bpy.types), 535
merge() (in module bpy.ops.armature), 16
merge() (in module bpy.ops.mesh), 52
merge_threshold (bpy.types.ArrayModifier attribute), 174
merge_threshold (bpy.types.MirrorModifier attribute), 568
mesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1123
mesh (bpy.types.EditObjectActuator attribute), 361
Mesh (class in bpy.types), 536
mesh (in module bpy.context), 5
Mesh.animation_data (in module bpy.types), 536
Mesh.edge_face_count (in module bpy.types), 539
Mesh.edge_face_count_dict (in module bpy.types), 539
Mesh.edge_keys (in module bpy.types), 540
Mesh.edges (in module bpy.types), 537
Mesh.faces (in module bpy.types), 537
Mesh.layers_float (in module bpy.types), 537
Mesh.layers_int (in module bpy.types), 537
Mesh.layers_string (in module bpy.types), 537
Mesh.materials (in module bpy.types), 537
Mesh.shape_keys (in module bpy.types), 537
Mesh.sticky (in module bpy.types), 538
Mesh.total_edge_sel (in module bpy.types), 538
Mesh.total_face_sel (in module bpy.types), 538
Mesh.total_vert_sel (in module bpy.types), 539
Mesh.uv_textures (in module bpy.types), 539
Mesh.vertex_colors (in module bpy.types), 539
Mesh.vertices (in module bpy.types), 539
mesh_select_mode (bpy.types.ToolSettings attribute), 938
MeshColor (class in bpy.types), 541
MeshColorLayer (class in bpy.types), 542
MeshColorLayer.data (in module bpy.types), 542
meshdeform_bind() (in module bpy.ops.object), 73
MeshDeformModifier (class in bpy.types), 543
MeshDeformModifier.is_bound (in module bpy.types), 543
MeshEdge (class in bpy.types), 544
MeshEdge.index (in module bpy.types), 545
MeshEdge.key (in module bpy.types), 545
MeshEdges (class in bpy.types), 546
meshes (bge.types.KX_GameObject attribute), 1096
MeshFace (class in bpy.types), 547
MeshFace.area (in module bpy.types), 547
MeshFace.center (in module bpy.types), 547
MeshFace.edge_keys (in module bpy.types), 547
MeshFace.index (in module bpy.types), 547
MeshFace.normal (in module bpy.types), 547
MeshFaces (class in bpy.types), 548
MeshFaces.active_tface (in module bpy.types), 548

MeshFloatProperty (class in bpy.types), 549
MeshFloatPropertyLayer (class in bpy.types), 550
MeshFloatPropertyLayer.data (in module bpy.types), 550
MeshIntProperty (class in bpy.types), 550
MeshIntPropertyLayer (class in bpy.types), 551
MeshIntPropertyLayer.data (in module bpy.types), 551
MeshSticky (class in bpy.types), 552
MeshStringProperty (class in bpy.types), 553
MeshStringPropertyLayer (class in bpy.types), 553
MeshStringPropertyLayer.data (in module bpy.types), 553
MeshTextureFace (class in bpy.types), 554
MeshTextureFaceLayer (class in bpy.types), 556
MeshTextureFaceLayer.data (in module bpy.types), 557
MeshVertex (class in bpy.types), 557
MeshVertex.groups (in module bpy.types), 558
MeshVertex.index (in module bpy.types), 558
MeshVertices (class in bpy.types), 559
MessageActuator (class in bpy.types), 559
MessageSensor (class in bpy.types), 560
meta_add() (in module bpy.ops.nla), 61
meta_ball (in module bpy.context), 6
meta_make() (in module bpy.ops.sequencer), 100
meta_remove() (in module bpy.ops.nla), 61
meta_separate() (in module bpy.ops.sequencer), 100
meta_strip (bpy.types.ThemeSequenceEditor attribute), 921
meta_toggle() (in module bpy.ops.sequencer), 100
MetaBall (class in bpy.types), 561
MetaBall.animation_data (in module bpy.types), 561
MetaBall.elements (in module bpy.types), 561
MetaBall.materials (in module bpy.types), 562
metaball_add() (in module bpy.ops.object), 73
MetaBallElements (class in bpy.types), 563
MetaBallElements.active (in module bpy.types), 563
MetaElement (class in bpy.types), 564
MetaSequence (class in bpy.types), 565
MetaSequence.color_balance (in module bpy.types), 566
MetaSequence.crop (in module bpy.types), 566
MetaSequence.proxy (in module bpy.types), 566
MetaSequence.sequences (in module bpy.types), 566
MetaSequence.transform (in module bpy.types), 566
mid_level (bpy.types.DisplaceModifier attribute), 344
MIDDLEMOUSE (in module bge.events), 1173
min (bge.types.KX_CameraActuator attribute), 1092
min (bge.types.KX_ConstraintActuator attribute), 1093
min (bge.types.SCA_PropertySensor attribute), 1137
min (bpy.types.ActionConstraint attribute), 145
min (bpy.types.CameraActuator attribute), 237
min (bpy.types.CompositorNodeMapValue attribute), 293
min (bpy.types.FModifierEnvelopeControlPoint attribute), 386
min (bpy.types.ShaderNodeMapping attribute), 774
min (bpy.types.TexMapping attribute), 862
min_x (bpy.types.CompositorNodeCrop attribute), 273
min_x (bpy.types.FModifierLimits attribute), 389
min_x (bpy.types.LimitLocationConstraint attribute), 496
min_x (bpy.types.LimitRotationConstraint attribute), 498
min_x (bpy.types.LimitScaleConstraint attribute), 499
min_x (bpy.types.SequenceCrop attribute), 763
min_y (bpy.types.CompositorNodeCrop attribute), 273
min_y (bpy.types.FModifierLimits attribute), 389
min_y (bpy.types.LimitLocationConstraint attribute), 496
min_y (bpy.types.LimitRotationConstraint attribute), 498
min_y (bpy.types.LimitScaleConstraint attribute), 499
min_y (bpy.types.SequenceCrop attribute), 763
min_z (bpy.types.LimitLocationConstraint attribute), 496
min_z (bpy.types.LimitRotationConstraint attribute), 498
min_z (bpy.types.LimitScaleConstraint attribute), 500
mini_axis_brightness (bpy.types.UserPreferencesView attribute), 989
mini_axis_size (bpy.types.UserPreferencesView attribute), 989
minimize_stretch() (in module bpy.ops.uv), 124
minkovsky_exponent (bpy.types.VoronoiTexture attribute), 1001
MINUSKEY (in module bge.events), 1176
mirror() (in module bpy.ops.action), 9
mirror() (in module bpy.ops.graph), 36
mirror() (in module bpy.ops.particle), 86
mirror() (in module bpy.ops.transform), 114
mirror_color (bpy.types.Material attribute), 510
mirror_factor (bpy.types.MaterialTextureSlot attribute), 527
mirror_object (bpy.types.MirrorModifier attribute), 568
MirrorModifier (class in bpy.types), 568
mix (bpy.types.CompositorNodeGlare attribute), 284
MKEY (in module bge.events), 1173
modal() (bpy.types.Operator method), 627
modal_handler_add() (bpy.types.WindowManager class method), 1009
mode (bge.types.BL_ActionActuator attribute), 1086
mode (bge.types.BL_ShapeActionActuator attribute), 1091
mode (bge.types.KX_GameActuator attribute), 1094
mode (bge.types.KX_IpoActuator attribute), 1105
mode (bge.types.KX_ParentActuator attribute), 1112
mode (bge.types.KX_SCA_DynamicActuator attribute), 1122
mode (bge.types.KX_SceneActuator attribute), 1126
mode (bge.types.KX_SoundActuator attribute), 1127
mode (bge.types.SCA_2DFilterActuator attribute), 1133
mode (bge.types.SCA_MouseSensor attribute), 1108
mode (bge.types.SCA_PropertyActuator attribute), 1137
mode (bge.types.SCA_PropertySensor attribute), 1137
mode (bge.types.SCA_PythonController attribute), 1138
mode (bpy.types.ArmatureActuator attribute), 169

mode (bpy.types.CompositorNodeCombYCCA attribute), 271
mode (bpy.types.CompositorNodeSepYCCA attribute), 303
mode (bpy.types.ConstraintActuator attribute), 320
mode (bpy.types.EditObjectActuator attribute), 361
mode (bpy.types.Filter2DActuator attribute), 399
mode (bpy.types.FModifierGenerator attribute), 388
mode (bpy.types.GameActuator attribute), 413
mode (bpy.types.Histogram attribute), 433
mode (bpy.types.Itasc attribute), 455
mode (bpy.types.MaskModifier attribute), 508
mode (bpy.types.NetRenderSettings attribute), 587
mode (bpy.types.ObjectActuator attribute), 615
mode (bpy.types.ParentActuator attribute), 638
mode (bpy.types.PropertyActuator attribute), 695
mode (bpy.types.PythonController attribute), 701
mode (bpy.types.SceneActuator attribute), 739
mode (bpy.types.ShapeActionActuator attribute), 788
mode (bpy.types.SoundActuator attribute), 811
mode (bpy.types.SpaceDopeSheetEditor attribute), 816
mode (bpy.types.SpaceGraphEditor attribute), 818
mode_after (bpy.types.FModifierCycles attribute), 384
mode_before (bpy.types.FModifierCycles attribute), 384
mode_set() (in module bpy.ops.object), 73
MODELMATRIX (in module bge.logic), 1168
MODELMATRIX_INVERSE (in module bge.logic), 1168
MODELMATRIX_INVERSETRANSPOSE (in module bge.logic), 1168
MODELMATRIX_TRANSPOSE (in module bge.logic), 1168
modelview_matrix (bge.types.KX_Camera attribute), 1141
MODELVIEWMATRIX (in module bge.logic), 1168
MODELVIEWMATRIX_INVERSE (in module bge.logic), 1168
MODELVIEWMATRIX_INVERSETRANSPOSE (in module bge.logic), 1168
MODELVIEWMATRIX_TRANSPOSE (in module bge.logic), 1168
Modifier (class in bpy.types), 570
Modifier.type (in module bpy.types), 570
modifier_add() (in module bpy.ops.object), 73
modifier_apply() (in module bpy.ops.object), 73
modifier_convert() (in module bpy.ops.object), 73
modifier_copy() (in module bpy.ops.object), 74
modifier_key_1 (bpy.types.KeyboardSensor attribute), 471
modifier_key_2 (bpy.types.KeyboardSensor attribute), 472
modifier_move_down() (in module bpy.ops.object), 74
modifier_move_up() (in module bpy.ops.object), 74
modifier_remove() (in module bpy.ops.object), 74
module (bpy.types.Addon attribute), 153
module (bpy.types.PythonController attribute), 702
module_names() (in module bpy.path), 1031
modules_from_path() (in module bpy.utils), 1029
motion_blur_factor (bpy.types.Filter2DActuator attribute), 400
motion_blur_samples (bpy.types.RenderSettings attribute), 723
motion_blur_shutter (bpy.types.RenderSettings attribute), 723
MotionPath (class in bpy.types), 571
MotionPath.frame_end (in module bpy.types), 571
MotionPath.frame_start (in module bpy.types), 571
MotionPath.length (in module bpy.types), 571
MotionPath.points (in module bpy.types), 572
MotionPath.use_bone_head (in module bpy.types), 572
MotionPathVert (class in bpy.types), 572
mouse (bpy.types.OperatorStrokeElement attribute), 630
mouse (in module bge.logic), 1157
mouse_double_click_time (bpy.types.UserPreferencesInput attribute), 983
mouse_event (bpy.types.MouseSensor attribute), 573
MouseSensor (class in bpy.types), 573
MOUSEX (in module bge.events), 1173
MOUSEY (in module bge.events), 1173
move() (in module bpy.ops.console), 19
move() (in module bpy.ops.font), 32
move() (in module bpy.ops.marker), 47
move() (in module bpy.ops.text), 109
move() (in module bpy.ops.view3d), 130
move_down() (in module bpy.ops.constraint), 20
move_down() (in module bpy.ops.nla), 61
move_select() (in module bpy.ops.font), 32
move_select() (in module bpy.ops.text), 109
move_to_layer() (in module bpy.ops.object), 74
move_up() (in module bpy.ops.constraint), 20
move_up() (in module bpy.ops.nla), 61
movie_strip (bpy.types.ThemeSequenceEditor attribute), 921
movie_strip_add() (in module bpy.ops.sequencer), 101
MovieSequence (class in bpy.types), 574
MovieSequence.color_balance (in module bpy.types), 574
MovieSequence.crop (in module bpy.types), 574
MovieSequence.elements (in module bpy.types), 574
MovieSequence.proxy (in module bpy.types), 575
MovieSequence.transform (in module bpy.types), 575
mpeg_preseek (bpy.types.MovieSequence attribute), 575
ms_diffusion (bpy.types.MaterialVolume attribute), 532
ms_intensity (bpy.types.MaterialVolume attribute), 532
ms_spread (bpy.types.MaterialVolume attribute), 532
multicam_source (bpy.types.MulticamSequence attribute), 577

MulticamSequence (class in bpy.types), 577
MulticamSequence.color_balance (in module bpy.types), 577
MulticamSequence.crop (in module bpy.types), 577
MulticamSequence.proxy (in module bpy.types), 577
MulticamSequence.transform (in module bpy.types), 577
multiply_speed (bpy.types.SpeedControlSequence attribute), 839
multires_base_apply() (in module bpy.ops.object), 74
multires_external_pack() (in module bpy.ops.object), 74
multires_external_save() (in module bpy.ops.object), 74
multires_higher_levels_delete() (in module bpy.ops.object), 75
multires_reshape() (in module bpy.ops.object), 75
multires_subdivide() (in module bpy.ops.object), 75
MultiresModifier (class in bpy.types), 579
MultiresModifier.is_external (in module bpy.types), 580
MultiresModifier.total_levels (in module bpy.types), 580
musgrave_type (bpy.types.MusgraveTexture attribute), 581
MusgraveTexture (class in bpy.types), 581
MusgraveTexture.users_material (in module bpy.types), 582
MusgraveTexture.users_object_modifier (in module bpy.types), 582
mute (bpy.types.Constraint attribute), 317
mute (bpy.types.FCurve attribute), 377
mute (bpy.types.FModifier attribute), 383
mute (bpy.types.NlaStrip attribute), 590
mute (bpy.types.NlaTrack attribute), 593
mute (bpy.types.Sequence attribute), 760
mute (bpy.types.ShapeKey attribute), 789
mute() (in module bpy.ops.sequencer), 101
mute_toggle() (in module bpy.ops.nla), 62
mute_toggle() (in module bpy.ops.node), 65

N

nabla (bpy.types.CloudsTexture attribute), 248
nabla (bpy.types.DistortedNoiseTexture attribute), 345
nabla (bpy.types.MarbleTexture attribute), 506
nabla (bpy.types.MusgraveTexture attribute), 581
nabla (bpy.types.VoronoiTexture attribute), 1001
nabla (bpy.types.WoodTexture attribute), 1013
name (bge.types.BL_ArmatureBone attribute), 1153
name (bge.types.BL_ArmatureChannel attribute), 1149
name (bge.types.BL_ArmatureConstraint attribute), 1148
name (bge.types.CValue attribute), 1083
name (bge.types.KX_GameObject attribute), 1094
name (bge.types.KX_Scene attribute), 1124
name (bge.types.SCA_ILogicBrick attribute), 1083
name (bpy.types.ActionGroup attribute), 148
name (bpy.types.Actuator attribute), 151
name (bpy.types.BoidRule attribute), 209
name (bpy.types.BoidState attribute), 218
name (bpy.types.Bone attribute), 220
name (bpy.types.BoneGroup attribute), 223
name (bpy.types.Constraint attribute), 317
name (bpy.types.Controller attribute), 325
name (bpy.types.DriverVariable attribute), 354
name (bpy.types.EditBone attribute), 358
name (bpy.types.GameProperty attribute), 420
name (bpy.types.ID attribute), 435
name (bpy.types.KeyConfig attribute), 459
name (bpy.types.KeyingSet attribute), 475
name (bpy.types.MeshColorLayer attribute), 542
name (bpy.types.MeshFloatPropertyLayer attribute), 550
name (bpy.types.MeshIntPropertyLayer attribute), 551
name (bpy.types.MeshStringPropertyLayer attribute), 553
name (bpy.types.MeshTextureFaceLayer attribute), 557
name (bpy.types.Modifier attribute), 570
name (bpy.types.NetRenderJob attribute), 585
name (bpy.types.NetRenderSlave attribute), 589
name (bpy.types.NlaStrip attribute), 590
name (bpy.types.NlaTrack attribute), 593
name (bpy.types.Node attribute), 595
name (bpy.types.NodeSocket attribute), 599
name (bpy.types.OperatorFileListElement attribute), 628
name (bpy.types.ParticleSystem attribute), 668
name (bpy.types.PointCache attribute), 678
name (bpy.types.PoseBone attribute), 690
name (bpy.types.PropertyGroup attribute), 697
name (bpy.types.SceneRenderLayer attribute), 746
name (bpy.types.Sensor attribute), 758
name (bpy.types.Sequence attribute), 761
name (bpy.types.ShapeKey attribute), 789
name (bpy.types.Theme attribute), 895
name (bpy.types.TimelineMarker attribute), 936
name (bpy.types.TransformOrientation attribute), 946
name (bpy.types.VertexGroup attribute), 996
NandController (class in bpy.types), 584
narrowness (bpy.types.WaveModifier attribute), 1006
ndof_pan_speed (bpy.types.UserPreferencesInput attribute), 983
ndof_rotate_speed (bpy.types.UserPreferencesInput attribute), 984
near (bge.types.KX_Camera attribute), 1140
NearSensor (class in bpy.types), 584
negate() (mathutils.Vector method), 1050
NET_RENDER (class in bpy.types), 583
netclientanim() (in module bpy.ops.render), 92
netclientblacklistslave() (in module bpy.ops.render), 92
netclientcancel() (in module bpy.ops.render), 92
netclientcancelall() (in module bpy.ops.render), 92
netclientdownload() (in module bpy.ops.render), 93
netclientscan() (in module bpy.ops.render), 93
netclientsend() (in module bpy.ops.render), 93
netclientsendframe() (in module bpy.ops.render), 93
netclientslaves() (in module bpy.ops.render), 93

netclientstart() (in module bpy.ops.render), 93
netclientstatus() (in module bpy.ops.render), 93
netclientvcsguess() (in module bpy.ops.render), 93
netclientweb() (in module bpy.ops.render), 93
netclientwhitelistslave() (in module bpy.ops.render), 93
NetRenderJob (class in bpy.types), 585
NetRenderSettings (class in bpy.types), 586
NetRenderSettings.jobs (in module bpy.types), 587
NetRenderSettings.slaves (in module bpy.types), 587
NetRenderSettings.slaves_blacklist (in module bpy.types), 587
NetRenderSlave (class in bpy.types), 589
netslavebake() (in module bpy.ops.render), 93
new() (bpy.types.ActionFCurves method), 146
new() (bpy.types.ActionGroups method), 149
new() (bpy.types.ActionPoseMarkers method), 150
new() (bpy.types.Addons class method), 153
new() (bpy.types.ArmatureEditBones method), 170
new() (bpy.types.BlendDataActions method), 182
new() (bpy.types.BlendDataArmatures method), 183
new() (bpy.types.BlendDataBrushes method), 184
new() (bpy.types.BlendDataCameras method), 185
new() (bpy.types.BlendDataCurves method), 186
new() (bpy.types.BlendDataGroups method), 189
new() (bpy.types.BlendDataImages method), 190
new() (bpy.types.BlendDataLamps method), 191
new() (bpy.types.BlendDataLattices method), 192
new() (bpy.types.BlendDataMaterials method), 195
new() (bpy.types.BlendDataMeshes method), 195
new() (bpy.types.BlendDataMetaBalls method), 196
new() (bpy.types.BlendDataNodeTrees method), 197
new() (bpy.types.BlendDataObjects method), 198
new() (bpy.types.BlendDataParticles method), 199
new() (bpy.types.BlendDataScenes method), 200
new() (bpy.types.BlendDataTexts method), 203
new() (bpy.types.BlendDataTextures method), 204
new() (bpy.types.BlendDataWorlds method), 206
new() (bpy.types.ChannelDriverVariables method), 239
new() (bpy.types.ColorRampElements method), 256
new() (bpy.types.CompositorNodes method), 315
new() (bpy.types.CurveSplines method), 340
new() (bpy.types.FCurveModifiers method), 381
new() (bpy.types.GroupInputs method), 428
new() (bpy.types.GroupOutputs method), 430
new() (bpy.types.KeyConfigurations method), 460
new() (bpy.types.KeyingSets method), 480
new() (bpy.types.KeyMapItems method), 466
new() (bpy.types.KeyMaps method), 469
new() (bpy.types.MetaBallElements method), 563
new() (bpy.types.NlaStrips method), 592
new() (bpy.types.NlaTracks method), 594
new() (bpy.types.NodeLinks method), 598
new() (bpy.types.ObjectConstraints method), 618
new() (bpy.types.ObjectModifiers method), 619
new() (bpy.types.PoseBoneConstraints method), 692
new() (bpy.types.ShaderNodes method), 787
new() (bpy.types.TextureNodes method), 892
new() (bpy.types.TimelineMarkers method), 936
new() (bpy.types.UVTextures method), 974
new() (bpy.types.VertexColors method), 995
new() (bpy.types.VertexGroups method), 998
new() (in module bpy.ops.action), 9
new() (in module bpy.ops.image), 39
new() (in module bpy.ops.material), 48
new() (in module bpy.ops.particle), 86
new() (in module bpy.ops.poselib), 91
new() (in module bpy.ops.scene), 94
new() (in module bpy.ops.screen), 96
new() (in module bpy.ops.text), 109
new() (in module bpy.ops.texture), 112
new() (in module bpy.ops.world), 142
new_modal() (bpy.types.KeyMapItems method), 467
new_target() (in module bpy.ops.particle), 87
next() (in module bpy.ops.file), 30
next_edit() (in module bpy.ops.sequencer), 101
next_marker() (in module bpy.ops.text), 109
NINEKEY (in module bge.events), 1174
NKEY (in module bge.events), 1173
NlaStrip (class in bpy.types), 589
NlaStrip.active (in module bpy.types), 590
NlaStrip.fcurves (in module bpy.types), 590
NlaStrip.modifiers (in module bpy.types), 590
NlaStrip.strips (in module bpy.types), 591
NlaStrip.type (in module bpy.types), 591
NlaStrips (class in bpy.types), 592
NlaTrack (class in bpy.types), 593
NlaTrack.active (in module bpy.types), 593
NlaTrack.is_solo (in module bpy.types), 593
NlaTrack.strips (in module bpy.types), 593
NlaTracks (class in bpy.types), 594
Node (class in bpy.types), 595
Node.inputs (in module bpy.types), 595
Node.outputs (in module bpy.types), 595
node_backdrop (bpy.types.ThemeNodeEditor attribute), 916
node_output (bpy.types.CompositorNodeTexture attribute), 306
node_output (bpy.types.ShaderNodeTexture attribute), 782
node_output (bpy.types.TextureNodeTexture attribute), 888
node_tree (bpy.types.NodeGroup attribute), 596
NodeGroup (class in bpy.types), 596
NodeLink (class in bpy.types), 597
NodeLink.from_node (in module bpy.types), 597
NodeLink.from_socket (in module bpy.types), 597
NodeLink.to_node (in module bpy.types), 597
NodeLink.to_socket (in module bpy.types), 597

NodeLinks (class in bpy.types), 598
NodeSocket (class in bpy.types), 599
NodeSocket.type (in module bpy.types), 599
NodeTree (class in bpy.types), 600
NodeTree.animation_data (in module bpy.types), 600
NodeTree.inputs (in module bpy.types), 600
NodeTree.links (in module bpy.types), 600
NodeTree.outputs (in module bpy.types), 600
NodeTree.type (in module bpy.types), 600
noise (bpy.types.FieldSettings attribute), 395
noise() (in module bpy.ops.mesh), 52
noise_basis (bpy.types.CloudsTexture attribute), 248
noise_basis (bpy.types.DistortedNoiseTexture attribute), 345
noise_basis (bpy.types.MarbleTexture attribute), 506
noise_basis (bpy.types.MusgraveTexture attribute), 581
noise_basis (bpy.types.PointDensity attribute), 680
noise_basis (bpy.types.StucciTexture attribute), 855
noise_basis (bpy.types.WoodTexture attribute), 1013
noise_depth (bpy.types.CloudsTexture attribute), 249
noise_depth (bpy.types.MagicTexture attribute), 503
noise_depth (bpy.types.MarbleTexture attribute), 506
noise_distortion (bpy.types.DistortedNoiseTexture attribute), 345
noise_intensity (bpy.types.MusgraveTexture attribute), 581
noise_intensity (bpy.types.VoronoiTexture attribute), 1001
noise_scale (bpy.types.CloudsTexture attribute), 249
noise_scale (bpy.types.DistortedNoiseTexture attribute), 345
noise_scale (bpy.types.MarbleTexture attribute), 506
noise_scale (bpy.types.MusgraveTexture attribute), 581
noise_scale (bpy.types.StucciTexture attribute), 856
noise_scale (bpy.types.VoronoiTexture attribute), 1001
noise_scale (bpy.types.WoodTexture attribute), 1013
noise_type (bpy.types.CloudsTexture attribute), 249
noise_type (bpy.types.MarbleTexture attribute), 506
noise_type (bpy.types.SmokeDomainSettings attribute), 798
noise_type (bpy.types.StucciTexture attribute), 856
noise_type (bpy.types.WoodTexture attribute), 1013
noisebasis_2 (bpy.types.MarbleTexture attribute), 506
noisebasis_2 (bpy.types.WoodTexture attribute), 1013
NoiseTexture (class in bpy.types), 601
NoiseTexture.users_material (in module bpy.types), 602
NoiseTexture.users_object_modifier (in module bpy.types), 602
NorController (class in bpy.types), 603
normal (bge.types.KX_VertexProxy attribute), 1130
normal (bpy.types.MeshVertex attribute), 558
normal (bpy.types.ThemeBoneColorSet attribute), 898
normal (bpy.types.ThemeView3D attribute), 931
normal() (in module mathutils.geometry), 1071
normal_angle (bpy.types.ImagePaint attribute), 442
normal_factor (bpy.types.MaterialTextureSlot attribute), 527
normal_factor (bpy.types.ParticleSettings attribute), 656
normal_map_space (bpy.types.MaterialTextureSlot attribute), 527
normal_size (bpy.types.ToolSettings attribute), 938
normal_weight (bpy.types.Brush attribute), 228
normalize() (mathutils.Vector method), 1050
normalized() (mathutils.Vector method), 1050
normals_make_consistent() (in module bpy.ops.mesh), 52
numAxis (bge.types.SCA_JoystickSensor attribute), 1135
numButtons (bge.types.SCA_JoystickSensor attribute), 1135
numHats (bge.types.SCA_JoystickSensor attribute), 1135
numMaterials (bge.types.KX_MeshProxy attribute), 1107
numPolygons (bge.types.KX_MeshProxy attribute), 1107
nurb_sel_uline (bpy.types.ThemeView3D attribute), 931
nurb_sel_vline (bpy.types.ThemeView3D attribute), 931
nurb_uline (bpy.types.ThemeView3D attribute), 931
nurb_vline (bpy.types.ThemeView3D attribute), 931

O

obj() (in module bpy.ops.export_scene), 27
obj() (in module bpy.ops.import_scene), 43
object (bge.types.KX_CameraActuator attribute), 1092
object (bge.types.KX_ParentActuator attribute), 1112
object (bge.types.KX_SCA_AddObjectActuator attribute), 1121
object (bge.types.KX_TrackToActuator attribute), 1127
object (bpy.types.ArmatureModifier attribute), 171
object (bpy.types.BoidRuleAvoid attribute), 211
object (bpy.types.BoidRuleFollowLeader attribute), 213
object (bpy.types.BoidRuleGoal attribute), 214
object (bpy.types.BooleanModifier attribute), 225
object (bpy.types.CameraActuator attribute), 237
object (bpy.types.CastModifier attribute), 238
object (bpy.types.CurveModifier attribute), 339
object (bpy.types.EditObjectActuator attribute), 361
object (bpy.types.HookModifier attribute), 434
object (bpy.types.LampTextureSlot attribute), 488
object (bpy.types.LatticeModifier attribute), 492
object (bpy.types.MaterialTextureSlot attribute), 527
object (bpy.types.MeshDeformModifier attribute), 543
object (bpy.types.ParentActuator attribute), 638
object (bpy.types.ParticleInstanceModifier attribute), 647
object (bpy.types.ParticleSettingsTextureSlot attribute), 663
object (bpy.types.ParticleTarget attribute), 672
object (bpy.types.PointDensity attribute), 680
object (bpy.types.PropertyActuator attribute), 695
object (bpy.types.ScrewModifier attribute), 755
object (bpy.types.UVProjector attribute), 973
object (bpy.types.WorldTextureSlot attribute), 1021

Object (class in bpy.types), 603
object (in module bpy.context), 4, 5
Object.active_shape_key (in module bpy.types), 604
Object.animation_data (in module bpy.types), 604
Object.animation_visualisation (in module bpy.types), 604
Object.bound_box (in module bpy.types), 604
Object.children (in module bpy.types), 610
Object.collision (in module bpy.types), 604
Object.constraints (in module bpy.types), 604
Object.dupli_list (in module bpy.types), 605
Object.field (in module bpy.types), 606
Object.game (in module bpy.types), 606
Object.is_duplicator (in module bpy.types), 606
Object.material_slots (in module bpy.types), 607
Object.mode (in module bpy.types), 607
Object.modifiers (in module bpy.types), 607
Object.motion_path (in module bpy.types), 607
Object.parent_vertices (in module bpy.types), 607
Object.particle_systems (in module bpy.types), 608
Object.pose (in module bpy.types), 608
Object.proxy (in module bpy.types), 608
Object.proxy_group (in module bpy.types), 608
Object.soft_body (in module bpy.types), 609
Object.type (in module bpy.types), 609
Object.users_group (in module bpy.types), 610
Object.users_scene (in module bpy.types), 610
Object.vertex_groups (in module bpy.types), 610
object_active (bpy.types.ThemeView3D attribute), 931
object_align (bpy.types.UserPreferencesEdit attribute), 978
object_align_factor (bpy.types.ParticleSettings attribute), 656
object_as_camera() (in module bpy.ops.view3d), 130
object_factor (bpy.types.ParticleSettings attribute), 656
object_grouped (bpy.types.ThemeView3D attribute), 931
object_grouped_active (bpy.types.ThemeView3D attribute), 931
object_operation() (in module bpy.ops.outliner), 82
object_origin_size (bpy.types.UserPreferencesView attribute), 989
object_property (bpy.types.PropertyActuator attribute), 695
object_selected (bpy.types.ThemeView3D attribute), 932
ObjectActuator (class in bpy.types), 614
ObjectBase (class in bpy.types), 617
ObjectBase.object (in module bpy.types), 617
ObjectConstraints (class in bpy.types), 618
objectLastCreated (bge.types.KX_SCA_AddObjectActuator attribute), 1121
ObjectModifiers (class in bpy.types), 619
objects (bge.types.KX_Scene attribute), 1124
objects_add_active() (in module bpy.ops.group), 38
objects_remove() (in module bpy.ops.group), 38
objects_remove_active() (in module bpy.ops.group), 38
objectsInactive (bge.types.KX_Scene attribute), 1124
ObstacleFluidSettings (class in bpy.types), 620
occlusion (bge.types.KX_GameObject attribute), 1095
occlusion_culling_resolution (bpy.types.SceneGameData attribute), 742
octaves (bpy.types.MusgraveTexture attribute), 581
octree_resolution (bpy.types.RenderSettings attribute), 724
offset (bpy.types.CompositorNodeColorBalance attribute), 266
offset (bpy.types.CompositorNodeMapValue attribute), 293
offset (bpy.types.CompositorNodeTonemap attribute), 309
offset (bpy.types.Curve attribute), 333
offset (bpy.types.FloorConstraint attribute), 402
offset (bpy.types.FollowPathConstraint attribute), 406
offset (bpy.types.MusgraveTexture attribute), 581
offset (bpy.types.PivotConstraint attribute), 673
offset (bpy.types.ShrinkwrapModifier attribute), 794
offset (bpy.types.SolidifyModifier attribute), 808
offset (bpy.types.TextureNodeBricks attribute), 875
offset (bpy.types.TextureSlot attribute), 894
offset_factor (bpy.types.FollowPathConstraint attribute), 406
offset_frequency (bpy.types.TextureNodeBricks attribute), 875
offset_location (bpy.types.ObjectActuator attribute), 615
offset_object (bpy.types.ArrayModifier attribute), 174
offset_rotation (bpy.types.ObjectActuator attribute), 615
offset_x (bpy.types.BackgroundImage attribute), 176
offset_x (bpy.types.SequenceTransform attribute), 767
offset_x (bpy.types.SpaceSequenceEditor attribute), 829
offset_x (bpy.types.TextCurve attribute), 868
offset_y (bpy.types.BackgroundImage attribute), 176
offset_y (bpy.types.SequenceTransform attribute), 767
offset_y (bpy.types.SpaceSequenceEditor attribute), 829
offset_y (bpy.types.TextCurve attribute), 868
offset_z (bpy.types.Material attribute), 510
OKEY (in module bge.events), 1173
ONEKEY (in module bge.events), 1174
opacity (bpy.types.BackgroundImage attribute), 176
open() (in module bpy.ops.font), 32
open() (in module bpy.ops.image), 39
open() (in module bpy.ops.sound), 105
open() (in module bpy.ops.text), 110
open_left_mouse_delay (bpy.types.UserPreferencesView attribute), 989
open_mainfile() (in module bpy.ops.wm), 138
open_right_mouse_delay (bpy.types.UserPreferencesView attribute), 989

open_sublevel_delay (bpy.types.UserPreferencesView attribute), 989
open_toplevel_delay (bpy.types.UserPreferencesView attribute), 989
opengl() (in module bpy.ops.render), 93
operation (bge.types.KX_StateActuator attribute), 1127
operation (bpy.types.BooleanModifier attribute), 225
operation (bpy.types.CompositorNodeMath attribute), 294
operation (bpy.types.ShaderNodeMath attribute), 776
operation (bpy.types.ShaderNodeVectorMath attribute), 786
operation (bpy.types.StateActuator attribute), 851
operation (bpy.types.TextureNodeMath attribute), 883
operation() (in module bpy.ops.outliner), 82
Operator (class in bpy.types), 625
operator() (bpy.types.UILayout method), 958
Operator.has_reports (in module bpy.types), 626
Operator.layout (in module bpy.types), 626
Operator.name (in module bpy.types), 626
Operator.properties (in module bpy.types), 626
operator_cheat_sheet() (in module bpy.ops.help), 38
operator_context (bpy.types.UILayout attribute), 949
operator_enum() (bpy.types.UILayout method), 961
operator_menu_enum() (bpy.types.UILayout method), 961
operator_node (bpy.types.ThemeNodeEditor attribute), 916
operator_preset_add() (in module bpy.ops.wm), 139
OperatorFileListElement (class in bpy.types), 628
OperatorMousePath (class in bpy.types), 628
OperatorProperties (class in bpy.types), 629
OperatorStrokeElement (class in bpy.types), 630
OperatorTypeMacro (class in bpy.types), 631
OperatorTypeMacro.properties (in module bpy.types), 631
option (bge.types.KX_ConstraintActuator attribute), 1093
OrController (class in bpy.types), 631
order (mathutils.Euler attribute), 1041
order_u (bpy.types.Spline attribute), 841
order_v (bpy.types.Spline attribute), 841
orient_weight (bpy.types.KinematicConstraint attribute), 482
orientation (aud.Handle attribute), 1081
orientation (bge.types.KX_GameObject attribute), 1095
orientation (bge.types.KX_SoundActuator attribute), 1127
origin (bpy.types.SimpleDeformModifier attribute), 796
origin_clear() (in module bpy.ops.object), 75
origin_set() (in module bpy.ops.object), 75
ortho_scale (bge.types.KX_Camera attribute), 1140
ortho_scale (bpy.types.Camera attribute), 235
OrthoProjection() (mathutils.Matrix class method), 1041
oskey (bpy.types.KeyMapItem attribute), 464
OutflowFluidSettings (class in bpy.types), 632
outline (bpy.types.ThemeWidgetColors attribute), 933
outline_width (bpy.types.ThemeView3D attribute), 932
output_node (bpy.types.TextureSlot attribute), 894
overlay_frame (bpy.types.SequenceEditor attribute), 764
overlay_lock (bpy.types.SequenceEditor attribute), 764
overwrite_toggle() (in module bpy.ops.text), 110
owner (bge.types.SCA_ILogicBrick attribute), 1083
owner (mathutils.Color attribute), 1040
owner (mathutils.Euler attribute), 1041
owner (mathutils.Matrix attribute), 1045
owner (mathutils.Quaternion attribute), 1047
owner (mathutils.Vector attribute), 1052
owner_space (bpy.types.Constraint attribute), 318

P

pack() (in module bpy.ops.image), 39
pack() (in module bpy.ops.sound), 105
pack_all() (in module bpy.ops.file), 30
pack_islands() (in module bpy.ops.uv), 124
PackedFile (class in bpy.types), 633
PackedFile.size (in module bpy.types), 633
PAD0 (in module bge.events), 1175
PAD1 (in module bge.events), 1175
PAD2 (in module bge.events), 1175
PAD3 (in module bge.events), 1175
PAD4 (in module bge.events), 1175
PAD5 (in module bge.events), 1175
PAD6 (in module bge.events), 1175
PAD7 (in module bge.events), 1175
PAD8 (in module bge.events), 1175
PAD9 (in module bge.events), 1175
PADASTERKEY (in module bge.events), 1175
PADENTER (in module bge.events), 1175
PADMINUS (in module bge.events), 1175
PADPERIOD (in module bge.events), 1175
PADPLUSKEY (in module bge.events), 1175
PADSLASHKEY (in module bge.events), 1175
PAGEDOWNKEY (in module bge.events), 1176
PAGEUPKEY (in module bge.events), 1176
Paint (class in bpy.types), 634
pan() (in module bpy.ops.view2d), 127
panel (bpy.types.ThemeGraphEditor attribute), 908
panel (bpy.types.ThemeLogicEditor attribute), 912
panel (bpy.types.ThemeProperties attribute), 919
panel (bpy.types.ThemeView3D attribute), 932
Panel (class in bpy.types), 637
Panel.layout (in module bpy.types), 637
panelzoom (bpy.types.ThemeStyle attribute), 922
para1 (bge.types.SCA_RandomActuator attribute), 1138
para2 (bge.types.SCA_RandomActuator attribute), 1138
parent (bge.types.BL_ArmatureBone attribute), 1155
parent (bge.types.BL_ArmatureChannel attribute), 1149

parent (bge.types.KX_GameObject attribute), 1095
parent (bpy.types.EditBone attribute), 358
parent (bpy.types.Object attribute), 607
parent (bpy.types.ParticleSystem attribute), 668
parent() (in module bpy.ops.file), 30
parent_bone (bpy.types.Object attribute), 607
parent_clear() (in module bpy.ops.armature), 16
parent_clear() (in module bpy.ops.object), 75
parent_index() (bpy.types.Bone method), 222
parent_index() (bpy.types.EditBone method), 359
parent_index() (bpy.types.PoseBone method), 691
parent_no_inverse_set() (in module bpy.ops.object), 75
parent_set() (in module bpy.ops.armature), 16
parent_set() (in module bpy.ops.object), 75
parent_type (bpy.types.Object attribute), 607
ParentActuator (class in bpy.types), 638
partial_slip_factor (bpy.types.DomainFluidSettings attribute), 347
partial_slip_factor (bpy.types.ObstacleFluidSettings attribute), 620
Particle (class in bpy.types), 639
Particle.hair (in module bpy.types), 639
Particle.is_exist (in module bpy.types), 640
Particle.is_visible (in module bpy.types), 640
Particle.keys (in module bpy.types), 640
particle_cache_space (bpy.types.PointDensity attribute), 680
particle_edit_object (in module bpy.context), 4
particle_edit_toggle() (in module bpy.ops.particle), 87
particle_factor (bpy.types.ParticleSettings attribute), 656
particle_influence (bpy.types.ParticleFluidSettings attribute), 645
particle_size (bpy.types.ParticleSettings attribute), 656
particle_system (bpy.types.PointDensity attribute), 680
particle_system (bpy.types.SmokeFlowSettings attribute), 800
particle_system (in module bpy.context), 6
particle_system_add() (in module bpy.ops.object), 75
particle_system_editable (in module bpy.context), 6
particle_system_index (bpy.types.ParticleInstanceModifier attribute), 647
particle_system_remove() (in module bpy.ops.object), 75
particle_uv (bpy.types.ExplodeModifier attribute), 374
ParticleBrush (class in bpy.types), 641
ParticleBrush.curve (in module bpy.types), 641
ParticleDupliWeight (class in bpy.types), 642
ParticleDupliWeight.name (in module bpy.types), 642
ParticleEdit (class in bpy.types), 643
ParticleEdit.brush (in module bpy.types), 643
ParticleEdit.is_editable (in module bpy.types), 643
ParticleEdit.is_hair (in module bpy.types), 643
ParticleEdit.object (in module bpy.types), 644
ParticleFluidSettings (class in bpy.types), 645
ParticleHairKey (class in bpy.types), 646
ParticleInstanceModifier (class in bpy.types), 647
ParticleKey (class in bpy.types), 649
ParticleSettings (class in bpy.types), 650
ParticleSettings.active_dupliweight (in module bpy.types), 650
ParticleSettings.animation_data (in module bpy.types), 650
ParticleSettings.boids (in module bpy.types), 651
ParticleSettings.dupli_weights (in module bpy.types), 653
ParticleSettings.effector_weights (in module bpy.types), 653
ParticleSettings.fluid (in module bpy.types), 654
ParticleSettings.force_field_1 (in module bpy.types), 654
ParticleSettings.force_field_2 (in module bpy.types), 654
ParticleSettings.is_fluid (in module bpy.types), 655
ParticleSettings.texture_slots (in module bpy.types), 659
ParticleSettingsTextureSlot (class in bpy.types), 662
ParticleSettingsTextureSlots (class in bpy.types), 665
ParticleSystem (class in bpy.types), 666
ParticleSystem.active_particle_target (in module bpy.types), 666
ParticleSystem.child_particles (in module bpy.types), 666
ParticleSystem.cloth (in module bpy.types), 667
ParticleSystem.has_multiple_caches (in module bpy.types), 667
ParticleSystem.is_editable (in module bpy.types), 668
ParticleSystem.is_edited (in module bpy.types), 668
ParticleSystem.is_global_hair (in module bpy.types), 668
ParticleSystem.particles (in module bpy.types), 668
ParticleSystem.point_cache (in module bpy.types), 668
ParticleSystem.targets (in module bpy.types), 668
ParticleSystemModifier (class in bpy.types), 670
ParticleSystemModifier.particle_system (in module bpy.types), 670
ParticleSystems (class in bpy.types), 671
ParticleSystems.active (in module bpy.types), 671
ParticleTarget (class in bpy.types), 672
ParticleTarget.name (in module bpy.types), 672
parts_x (bpy.types.RenderSettings attribute), 724
parts_y (bpy.types.RenderSettings attribute), 724
pass_index (bpy.types.Object attribute), 608
passepartout_alpha (bpy.types.Camera attribute), 235
passes (bpy.types.WorldLighting attribute), 1018
passNumber (bge.types.SCA_2DFilterActuator attribute), 1133
paste() (in module bpy.ops.action), 10
paste() (in module bpy.ops.console), 20
paste() (in module bpy.ops.graph), 36
paste() (in module bpy.ops.material), 48
paste() (in module bpy.ops.pose), 89
paste() (in module bpy.ops.sequencer), 101
paste() (in module bpy.ops.text), 110
paste_driver_button() (in module bpy.ops.anim), 14
path (bpy.types.NetRenderSettings attribute), 587

path_duration (bpy.types.Curve attribute), 333
path_end (bpy.types.ParticleSettings attribute), 656
path_from_id() (bpy.types.bpy_struct method), 1028
path_menu() (bpy.types.Menu method), 536
path_open() (in module bpy.ops.wm), 139
path_resolve() (bpy.types.bpy_struct method), 1029
path_start (bpy.types.ParticleSettings attribute), 656
paths_calculate() (in module bpy.ops.object), 75
paths_calculate() (in module bpy.ops.pose), 90
paths_clear() (in module bpy.ops.object), 75
paths_clear() (in module bpy.ops.pose), 90
PAUSEKEY (in module bge.events), 1176
pen_flip (bpy.types.OperatorStrokeElement attribute), 630
PERIODKEY (in module bge.events), 1176
permeability (bpy.types.CollisionSettings attribute), 253
perspective (bge.types.KX_Camera attribute), 1141
phase (bpy.types.FModifierNoise attribute), 390
phase_factor (bpy.types.ParticleSettings attribute), 657
phase_factor_random (bpy.types.ParticleSettings attribute), 657
phase_multiplier (bpy.types.FModifierFunctionGenerator attribute), 387
phase_offset (bpy.types.FModifierFunctionGenerator attribute), 387
physics_engine (bpy.types.SceneGameData attribute), 742
physics_gravity (bpy.types.SceneGameData attribute), 742
physics_step_max (bpy.types.SceneGameData attribute), 742
physics_step_sub (bpy.types.SceneGameData attribute), 742
physics_type (bpy.types.GameObjectSettings attribute), 417
physics_type (bpy.types.ParticleSettings attribute), 657
pid (bge.types.KX_ObjectActuator attribute), 1112
pin (bpy.types.Actuator attribute), 151
pin (bpy.types.Sensor attribute), 758
pin() (in module bpy.ops.uv), 124
pin_id (bpy.types.SpaceProperties attribute), 828
pin_stiffness (bpy.types.ClothSettings attribute), 247
pin_uv (bpy.types.MeshTextureFace attribute), 554
pitch (aud.Handle attribute), 1081
pitch (bge.types.KX_SoundActuator attribute), 1126
pitch (bpy.types.BoidSettings attribute), 216
pitch (bpy.types.SoundActuator attribute), 811
pivot_point (bpy.types.SpaceGraphEditor attribute), 818
pivot_point (bpy.types.SpaceUVEditor attribute), 833
pivot_point (bpy.types.SpaceView3D attribute), 837
pivot_type (bpy.types.RigidBodyJointConstraint attribute), 731
pivot_x (bpy.types.RigidBodyJointConstraint attribute), 731
pivot_y (bpy.types.RigidBodyJointConstraint attribute), 731
pivot_z (bpy.types.RigidBodyJointConstraint attribute), 731
PivotConstraint (class in bpy.types), 673
pixel_aspect_x (bpy.types.RenderSettings attribute), 724
pixel_aspect_y (bpy.types.RenderSettings attribute), 724
pixel_filter_type (bpy.types.RenderSettings attribute), 724
PKEY (in module bge.events), 1173
plane_offset (bpy.types.Brush attribute), 228
plane_trim (bpy.types.Brush attribute), 228
plastic (bpy.types.SoftBodySettings attribute), 806
plasticity (bpy.types.SPHFluidSettings attribute), 733
play_mode (bpy.types.ActionActuator attribute), 144
play_rendered_anim() (in module bpy.ops.render), 94
play_type (bpy.types.FCurveActuator attribute), 379
plugin_strip (bpy.types.ThemeSequenceEditor attribute), 921
PluginSequence (class in bpy.types), 674
PluginSequence.filename (in module bpy.types), 674
PluginTexture (class in bpy.types), 676
PluginTexture.users_material (in module bpy.types), 676
PluginTexture.users_object_modifier (in module bpy.types), 676
ply() (in module bpy.ops.export_mesh), 25
ply() (in module bpy.ops.import_mesh), 43
point_cache_compress_type (bpy.types.SmokeDomainSettings attribute), 798
point_source (bpy.types.PointDensity attribute), 680
PointCache (class in bpy.types), 677
PointCache.frames_skipped (in module bpy.types), 677
PointCache.info (in module bpy.types), 678
PointCache.is_baked (in module bpy.types), 678
PointCache.is_baking (in module bpy.types), 678
PointCache.is_outdated (in module bpy.types), 678
PointCache.point_caches (in module bpy.types), 678
PointCaches (class in bpy.types), 679
PointDensity (class in bpy.types), 680
PointDensity.color_ramp (in module bpy.types), 680
PointDensityTexture (class in bpy.types), 682
PointDensityTexture.point_density (in module bpy.types), 682
PointDensityTexture.users_material (in module bpy.types), 682
PointDensityTexture.users_object_modifier (in module bpy.types), 682
PointerProperty (class in bpy.types), 685
PointerProperty() (in module bpy.props), 1036
PointerProperty.fixed_type (in module bpy.types), 685
pointInsideFrustum() (bge.types.KX_Camera method), 1142
PointLamp (class in bpy.types), 683

PointLamp.falloff_curve (in module bpy.types), 683
points (bpy.types.ThemeFontStyle attribute), 905
points_u (bpy.types.Lattice attribute), 490
points_v (bpy.types.Lattice attribute), 491
points_w (bpy.types.Lattice attribute), 491
pole_angle (bpy.types.KinematicConstraint attribute), 482
pole_subtarget (bpy.types.KinematicConstraint attribute), 482
pole_target (bpy.types.KinematicConstraint attribute), 482
poll() (bpy.types.KeyingSetInfo method), 476
poll() (bpy.types.Macro class method), 503
poll() (bpy.types.Menu class method), 535
poll() (bpy.types.Operator class method), 626
poll() (bpy.types.Panel class method), 637
poly_order (bpy.types.FModifierGenerator attribute), 388
pop() (bpy.types.IDMaterials method), 437
Pose (class in bpy.types), 686
Pose.animation_visualisation (in module bpy.types), 686
Pose.bone_groups (in module bpy.types), 686
Pose.bones (in module bpy.types), 686
Pose.ik_param (in module bpy.types), 686
pose_add() (in module bpy.ops.poselib), 91
pose_bone (in module bpy.context), 6
pose_head (bge.types.BL_ArmatureChannel attribute), 1152
pose_library (bpy.types.Object attribute), 608
pose_matrix (bge.types.BL_ArmatureChannel attribute), 1152
pose_position (bpy.types.Armature attribute), 167
pose_remove() (in module bpy.ops.poselib), 92
pose_rename() (in module bpy.ops.poselib), 92
pose_tail (bge.types.BL_ArmatureChannel attribute), 1152
PoseBone (class in bpy.types), 687
PoseBone.basename (in module bpy.types), 691
PoseBone.bone (in module bpy.types), 687
PoseBone.center (in module bpy.types), 691
PoseBone.child (in module bpy.types), 687
PoseBone.children (in module bpy.types), 691
PoseBone.children_recursive (in module bpy.types), 691
PoseBone.children_recursive_basename (in module bpy.types), 691
PoseBone.constraints (in module bpy.types), 687
PoseBone.head (in module bpy.types), 688
PoseBone.is_in_ik_chain (in module bpy.types), 689
PoseBone.matrix (in module bpy.types), 689
PoseBone.matrix_channel (in module bpy.types), 689
PoseBone.motion_path (in module bpy.types), 690
PoseBone.parent (in module bpy.types), 690
PoseBone.parent_recursive (in module bpy.types), 691
PoseBone.tail (in module bpy.types), 690
PoseBone.vector (in module bpy.types), 691
PoseBone.x_axis (in module bpy.types), 691
PoseBone.y_axis (in module bpy.types), 691
PoseBone.z_axis (in module bpy.types), 691
PoseBoneConstraints (class in bpy.types), 692
posemode_toggle() (in module bpy.ops.object), 76
position (aud.Handle attribute), 1081
position (bge.types.KX_GameObject attribute), 1095
position (bge.types.KX_SoundActuator attribute), 1126
position (bge.types.SCA_MouseSensor attribute), 1108
position (bge.types.SCA_PythonMouse attribute), 1084
position (bpy.types.ColorRampElement attribute), 256
position (bpy.types.ParticleInstanceModifier attribute), 647
position() (in module blf), 1072
positive (bge.types.SCA_ISensor attribute), 1085
post_draw (bge.types.KX_Scene attribute), 1125
power (bpy.types.CompositorNodeColorBalance attribute), 266
pre_draw (bge.types.KX_Scene attribute), 1125
pre_roll (bpy.types.ClothSettings attribute), 247
precision (bpy.types.Itasc attribute), 455
precision (bpy.types.MeshDeformModifier attribute), 543
prefetch_frames (bpy.types.UserPreferencesSystem attribute), 986
premul (bpy.types.CompositorNodeAlphaOver attribute), 260
prepend() (bpy.types.Header class method), 431
prepend() (bpy.types.InputKeyMapPanel class method), 452
prepend() (bpy.types.Menu class method), 536
prepend() (bpy.types.Panel class method), 638
preset_add() (in module bpy.ops.cloth), 18
preset_add() (in module bpy.ops.render), 94
preset_find() (in module bpy.utils), 1030
preset_paths() (in module bpy.utils), 1030
pressure (bpy.types.GPencilStrokePoint attribute), 412
pressure (bpy.types.OperatorStrokeElement attribute), 630
prev_angular_velocity (bpy.types.Particle attribute), 640
prev_location (bpy.types.Particle attribute), 640
prev_rotation (bpy.types.Particle attribute), 640
prev_velocity (bpy.types.Particle attribute), 640
preview_render_type (bpy.types.Material attribute), 510
preview_resolution (bpy.types.DomainFluidSettings attribute), 347
preview_toggle() (in module bpy.ops.node), 65
previewrange_clear() (in module bpy.ops.anim), 14
previewrange_set() (in module bpy.ops.action), 10
previewrange_set() (in module bpy.ops.anim), 14
previewrange_set() (in module bpy.ops.graph), 36
previous() (in module bpy.ops.file), 30
previous_edit() (in module bpy.ops.sequencer), 101
previous_marker() (in module bpy.ops.text), 110

primitive_bezier_circle_add() (in module bpy.ops.curve), 21
primitive_bezier_curve_add() (in module bpy.ops.curve), 22
primitive_circle_add() (in module bpy.ops.mesh), 52
primitive_cone_add() (in module bpy.ops.mesh), 53
primitive_cube_add() (in module bpy.ops.mesh), 53
primitive_cylinder_add() (in module bpy.ops.mesh), 53
primitive_grid_add() (in module bpy.ops.mesh), 54
primitive_ico_sphere_add() (in module bpy.ops.mesh), 54
primitive_monkey_add() (in module bpy.ops.mesh), 55
primitive_nurbs_circle_add() (in module bpy.ops.curve), 22
primitive_nurbs_curve_add() (in module bpy.ops.curve), 22
primitive_nurbs_path_add() (in module bpy.ops.curve), 23
primitive_nurbs_surface_circle_add() (in module bpy.ops.surface), 106
primitive_nurbs_surface_curve_add() (in module bpy.ops.surface), 106
primitive_nurbs_surface_cylinder_add() (in module bpy.ops.surface), 107
primitive_nurbs_surface_sphere_add() (in module bpy.ops.surface), 107
primitive_nurbs_surface_surface_add() (in module bpy.ops.surface), 107
primitive_nurbs_surface_torus_add() (in module bpy.ops.surface), 108
primitive_plane_add() (in module bpy.ops.mesh), 55
primitive_torus_add() (in module bpy.ops.mesh), 55
primitive_uv_sphere_add() (in module bpy.ops.mesh), 56
PrintGLInfo() (in module bge.logic), 1160
priority (bge.types.BL_ActionActuator attribute), 1086
priority (bge.types.BL_ShapeActionActuator attribute), 1090
priority (bpy.types.ActionActuator attribute), 144
priority (bpy.types.NetRenderSettings attribute), 587
priority (bpy.types.ShapeActionActuator attribute), 788
progression (bpy.types.BlendTexture attribute), 207
project_apply() (in module bpy.ops.image), 39
project_edit() (in module bpy.ops.image), 40
project_from_view() (in module bpy.ops.uv), 124
project_image() (in module bpy.ops.paint), 84
projection_matrix (bge.types.KX_Camera attribute), 1141
projector_count (bpy.types.UVProjectModifier attribute), 972
prompt (bpy.types.SpaceConsole attribute), 815
prop() (bpy.types.UILayout method), 950
prop_enum() (bpy.types.UILayout method), 954
prop_menu_enum() (bpy.types.UILayout method), 952
prop_search() (bpy.types.UILayout method), 956
properties() (in module bpy.ops.graph), 36
properties() (in module bpy.ops.image), 40
properties() (in module bpy.ops.logic), 46
properties() (in module bpy.ops.nla), 62
properties() (in module bpy.ops.node), 65
properties() (in module bpy.ops.sequencer), 101
properties() (in module bpy.ops.text), 110
properties() (in module bpy.ops.view3d), 130
properties_add() (in module bpy.ops.wm), 139
properties_edit() (in module bpy.ops.wm), 139
properties_remove() (in module bpy.ops.wm), 139
property (bpy.types.ActionActuator attribute), 144
property (bpy.types.CollisionSensor attribute), 252
property (bpy.types.ConstraintActuator attribute), 320
property (bpy.types.FCurveActuator attribute), 379
property (bpy.types.NearSensor attribute), 584
property (bpy.types.PropertyActuator attribute), 696
property (bpy.types.PropertySensor attribute), 699
property (bpy.types.RadarSensor attribute), 703
property (bpy.types.RandomActuator attribute), 705
property (bpy.types.RaySensor attribute), 707
property (bpy.types.ShapeActionActuator attribute), 788
Property (class in bpy.types), 693
Property.description (in module bpy.types), 693
Property.identifier (in module bpy.types), 693
Property.is_enum_flag (in module bpy.types), 693
Property.is_hidden (in module bpy.types), 694
Property.is_never_none (in module bpy.types), 694
Property.is_output (in module bpy.types), 694
Property.is_readonly (in module bpy.types), 694
Property.is_registered (in module bpy.types), 694
Property.is_registered_optional (in module bpy.types), 694
Property.is_required (in module bpy.types), 694
Property.is_runtime (in module bpy.types), 694
Property.name (in module bpy.types), 694
Property.srna (in module bpy.types), 694
Property.subtype (in module bpy.types), 694
Property.type (in module bpy.types), 694
Property.unit (in module bpy.types), 695
PropertyActuator (class in bpy.types), 695
PropertyGroup (class in bpy.types), 697
PropertyGroupItem (class in bpy.types), 698
PropertyGroupItem.collection (in module bpy.types), 698
PropertyGroupItem.group (in module bpy.types), 698
PropertyGroupItem.idp_array (in module bpy.types), 698
PropertySensor (class in bpy.types), 699
propName (bge.types.BL_ActionActuator attribute), 1086
propName (bge.types.BL_ShapeActionActuator attribute), 1090
propName (bge.types.KX_ConstraintActuator attribute), 1093
propName (bge.types.KX_IpoActuator attribute), 1104

propName (bge.types.KX_NetworkMessageActuator attribute), 1110
propName (bge.types.KX_RaySensor attribute), 1120
propName (bge.types.KX_TouchSensor attribute), 1109
propName (bge.types.SCA_PropertyActuator attribute), 1137
propName (bge.types.SCA_PropertySensor attribute), 1137
propName (bge.types.SCA_RandomActuator attribute), 1138
proportional_coefficient (bpy.types.ObjectActuator attribute), 615
proportional_edit (bpy.types.ToolSettings attribute), 938
proportional_edit_falloff (bpy.types.ToolSettings attribute), 939
proportional_size (bpy.types.ToolSettings attribute), 939
props_enum() (bpy.types.UILayout method), 952
propvalue (bpy.types.KeyMapItem attribute), 464
protect (bpy.types.ExplodeModifier attribute), 374
proxy_make() (in module bpy.ops.object), 76
proxy_render_size (bpy.types.SpaceSequenceEditor attribute), 829
puff_mode (bpy.types.ParticleBrush attribute), 641
pull (bpy.types.SoftBodySettings attribute), 806
push (bpy.types.SoftBodySettings attribute), 806
push() (in module bpy.ops.pose), 90
push_pull() (in module bpy.ops.transform), 114
PyObjectPlus (class in bge.types), 1083
python_file_run() (in module bpy.ops.script), 97
PythonConstraint (class in bpy.types), 700
PythonConstraint.has_script_error (in module bpy.types), 700
PythonConstraint.targets (in module bpy.types), 700
PythonController (class in bpy.types), 701

Q

QKEY (in module bge.events), 1174
quad_attenuation (bge.types.KX_LightObject attribute), 1106
quadratic_attenuation (bpy.types.PointLamp attribute), 683
quadratic_attenuation (bpy.types.SpotLamp attribute), 848
quadratic_drag (bpy.types.FieldSettings attribute), 395
quads_convert_to_tris() (in module bpy.ops.mesh), 56
quality (bpy.types.ClothSettings attribute), 247
quality (bpy.types.CompositorNodeGlare attribute), 284
quality (bpy.types.CompositorNodeOutputFile attribute), 297
quality (bpy.types.ControlFluidSettings attribute), 324
quality (bpy.types.GlowSequence attribute), 424
Quaternion (class in mathutils), 1045
Quaternion.conjugate() (in module mathutils), 1045
Quaternion.conjugated() (in module mathutils), 1045
Quaternion.copy() (in module mathutils), 1045
Quaternion.difference() (in module mathutils), 1046
Quaternion.identity() (in module mathutils), 1046
Quaternion.invert() (in module mathutils), 1046
Quaternion.inverted() (in module mathutils), 1046
Quaternion.negate() (in module mathutils), 1046
Quaternion.normalize() (in module mathutils), 1046
Quaternion.normalized() (in module mathutils), 1046
Quaternion.slerp() (in module mathutils), 1047
quaternions_flip() (in module bpy.ops.pose), 90
queue_count (bpy.types.BoidRuleFollowLeader attribute), 213
quit_blender() (in module bpy.ops.wm), 139
QUOTEKEY (in module bge.events), 1176

R

r (bge.types.KX_VertexProxy attribute), 1131
r (mathutils.Color attribute), 1040
RadarSensor (class in bpy.types), 703
radial_control() (in module bpy.ops.sculpt), 98
radial_falloff (bpy.types.FieldSettings attribute), 395
radial_max (bpy.types.FieldSettings attribute), 395
radial_min (bpy.types.FieldSettings attribute), 395
radial_symmetry (bpy.types.Sculpt attribute), 756
radius (bpy.types.BezierSplinePoint attribute), 178
radius (bpy.types.CastModifier attribute), 238
radius (bpy.types.GameObjectSettings attribute), 417
radius (bpy.types.MaterialSubsurfaceScattering attribute), 525
radius (bpy.types.MetaElement attribute), 564
radius (bpy.types.PointDensity attribute), 681
radius (bpy.types.SplinePoint attribute), 846
radius_interpolation (bpy.types.Spline attribute), 842
radius_set() (in module bpy.ops.curve), 23
random_position (bpy.types.ParticleInstanceModifier attribute), 647
RandomActuator (class in bpy.types), 704
randomize_transform() (in module bpy.ops.object), 76
RandomSensor (class in bpy.types), 706
range (bge.types.KX_RaySensor attribute), 1120
range (bpy.types.BoidSettings attribute), 217
range (bpy.types.ConstraintActuator attribute), 320
range (bpy.types.RaySensor attribute), 707
range() (bpy.types.FCurve method), 378
RAS_2DFILTER_BLUR (in module bge.logic), 1167
RAS_2DFILTER_CUSTOMFILTER (in module bge.logic), 1167
RAS_2DFILTER_DILATION (in module bge.logic), 1167
RAS_2DFILTER_DISABLED (in module bge.logic), 1167
RAS_2DFILTER_ENABLED (in module bge.logic), 1167
RAS_2DFILTER_EROSION (in module bge.logic), 1167

RAS_2DFILTER_GRAYSCALE (in module bge.logic), 1167
RAS_2DFILTER_INVERT (in module bge.logic), 1167
RAS_2DFILTER_LAPLACIAN (in module bge.logic), 1167
RAS_2DFILTER_MOTIONBLUR (in module bge.logic), 1167
RAS_2DFILTER_NOFILTER (in module bge.logic), 1167
RAS_2DFILTER_PREWITT (in module bge.logic), 1167
RAS_2DFILTER_SEPIA (in module bge.logic), 1167
RAS_2DFILTER_SHARPEN (in module bge.logic), 1167
RAS_2DFILTER_SOBEL (in module bge.logic), 1167
rate (aud.Device attribute), 1075
rate (bpy.types.Brush attribute), 228
ratio (bpy.types.CompositorNodeColorSpill attribute), 268
ratio (bpy.types.DecimateModifier attribute), 342
ray_cast() (bpy.types.Object method), 611
ray_type (bpy.types.RaySensor attribute), 707
rayCast() (bge.types.KX_GameObject method), 1102
rayCastTo() (bge.types.KX_GameObject method), 1102
rayDirection (bge.types.KX_MouseFocusSensor attribute), 1109
rayDirection (bge.types.KX_RaySensor attribute), 1121
rayLength (bge.types.KX_ConstraintActuator attribute), 1093
raymir_factor (bpy.types.MaterialTextureSlot attribute), 527
RaySensor (class in bpy.types), 707
raySource (bge.types.KX_MouseFocusSensor attribute), 1108
rayTarget (bge.types.KX_MouseFocusSensor attribute), 1109
raytrace_method (bpy.types.RenderSettings attribute), 724
react_event (bpy.types.ParticleSettings attribute), 657
reactor_factor (bpy.types.ParticleSettings attribute), 657
reactor_target_object (bpy.types.ParticleSystem attribute), 668
reactor_target_particle_system (bpy.types.ParticleSystem attribute), 668
read_factory_settings() (in module bpy.ops.wm), 140
read_fullsamplelayers() (in module bpy.ops.node), 65
read_homefile() (in module bpy.ops.wm), 140
read_renderlayers() (in module bpy.ops.node), 65
reassign_inputs() (in module bpy.ops.sequencer), 101
recent_files (bpy.types.UserPreferencesFilePaths attribute), 981
record_composite() (in module bpy.ops.image), 40
recover_auto_save() (in module bpy.ops.wm), 140
recover_last_session() (in module bpy.ops.wm), 140
rect (bpy.types.RenderLayer attribute), 715
rect (bpy.types.RenderPass attribute), 719
redo() (in module bpy.ops.ed), 25
redo_last() (in module bpy.ops.screen), 96
redraw_timer() (in module bpy.ops.wm), 140
reference (bge.types.KX_ObjectActuator attribute), 1112
reference_axis (bpy.types.KinematicConstraint attribute), 483
reference_object (bpy.types.ObjectActuator attribute), 615
reference_value (bpy.types.FModifierEnvelope attribute), 385
reflect() (mathutils.Vector method), 1050
reflect_factor (bpy.types.MaterialRaytraceMirror attribute), 520
reflection (bpy.types.MaterialVolume attribute), 532
reflection_color (bpy.types.MaterialVolume attribute), 533
reflection_color_factor (bpy.types.MaterialTextureSlot attribute), 527
reflection_factor (bpy.types.MaterialTextureSlot attribute), 527
refresh() (in module bpy.ops.file), 30
refresh_all() (in module bpy.ops.sequencer), 102
refresh_pyconstraints() (in module bpy.ops.text), 110
Region (class in bpy.types), 708
Region.height (in module bpy.types), 708
Region.id (in module bpy.types), 709
Region.type (in module bpy.types), 709
Region.width (in module bpy.types), 709
region_flip() (in module bpy.ops.screen), 96
region_quadview() (in module bpy.ops.screen), 96
region_scale() (in module bpy.ops.screen), 96
region_to_loop() (in module bpy.ops.mesh), 57
RegionView3D (class in bpy.types), 709
RegionView3D.perspective_matrix (in module bpy.types), 710
RegionView3D.view_matrix (in module bpy.types), 710
register_class() (in module bpy.utils), 1030
register_module() (in module bpy.utils), 1030
regrow_hair (bpy.types.ParticleSettings attribute), 657
reinstancePhysicsMesh() (bge.types.KX_GameObject method), 1104
reiteration_method (bpy.types.Itasc attribute), 455
rekey() (in module bpy.ops.particle), 87
rel_max_x (bpy.types.CompositorNodeCrop attribute), 273
rel_max_y (bpy.types.CompositorNodeCrop attribute), 273
rel_min_x (bpy.types.CompositorNodeCrop attribute), 273
rel_min_y (bpy.types.CompositorNodeCrop attribute), 273
relative (aud.Handle attribute), 1081
relative (bpy.types.CompositorNodeCrop attribute), 273

relative_key (bpy.types.ShapeKey attribute), 790
relative_offset_displace (bpy.types.ArrayModifier attribute), 174
relax() (in module bpy.ops.pose), 90
reload() (bpy.types.Image method), 441
reload() (in module bpy.ops.image), 40
reload() (in module bpy.ops.script), 97
reload() (in module bpy.ops.sequencer), 102
reload() (in module bpy.ops.text), 110
relpath() (in module bpy.path), 1031
remove() (bpy.types.ActionFCurves method), 147
remove() (bpy.types.ActionGroups method), 149
remove() (bpy.types.ActionPoseMarkers method), 150
remove() (bpy.types.Addons class method), 154
remove() (bpy.types.ArmatureEditBones method), 170
remove() (bpy.types.BlendDataActions method), 182
remove() (bpy.types.BlendDataArmatures method), 183
remove() (bpy.types.BlendDataBrushes method), 184
remove() (bpy.types.BlendDataCameras method), 185
remove() (bpy.types.BlendDataCurves method), 186
remove() (bpy.types.BlendDataFonts method), 187
remove() (bpy.types.BlendDataGroups method), 189
remove() (bpy.types.BlendDataImages method), 190
remove() (bpy.types.BlendDataLamps method), 191
remove() (bpy.types.BlendDataLattices method), 192
remove() (bpy.types.BlendDataMaterials method), 195
remove() (bpy.types.BlendDataMeshes method), 196
remove() (bpy.types.BlendDataMetaBalls method), 197
remove() (bpy.types.BlendDataNodeTrees method), 198
remove() (bpy.types.BlendDataObjects method), 199
remove() (bpy.types.BlendDataParticles method), 200
remove() (bpy.types.BlendDataScenes method), 201
remove() (bpy.types.BlendDataTexts method), 203
remove() (bpy.types.BlendDataTextures method), 204
remove() (bpy.types.BlendDataWorlds method), 206
remove() (bpy.types.ChannelDriverVariables method), 239
remove() (bpy.types.ColorRampElements method), 257
remove() (bpy.types.CompositorNodes method), 315
remove() (bpy.types.CurveSplines method), 340
remove() (bpy.types.FCurveKeyframePoints method), 380
remove() (bpy.types.FCurveModifiers method), 381
remove() (bpy.types.Header class method), 431
remove() (bpy.types.InputKeyMapPanel class method), 452
remove() (bpy.types.KeyConfigurations method), 460
remove() (bpy.types.KeyingSetPaths method), 479
remove() (bpy.types.KeyMapItems method), 468
remove() (bpy.types.Menu class method), 536
remove() (bpy.types.MetaBallElements method), 563
remove() (bpy.types.NlaStrips method), 592
remove() (bpy.types.NlaTracks method), 594
remove() (bpy.types.NodeLinks method), 598
remove() (bpy.types.ObjectConstraints method), 618
remove() (bpy.types.ObjectModifiers method), 619
remove() (bpy.types.Panel class method), 638
remove() (bpy.types.PoseBoneConstraints method), 693
remove() (bpy.types.ShaderNodes method), 787
remove() (bpy.types.TextureNodes method), 893
remove() (bpy.types.TimelineMarkers method), 937
remove() (bpy.types.VertexGroup method), 996
remove() (bpy.types.VertexGroups method), 998
remove() (in module bpy.ops.ptcache), 92
remove_doubles() (in module bpy.ops.mesh), 57
remove_doubles() (in module bpy.ops.particle), 87
removeParent() (bge.types.KX_GameObject method), 1101
RemoveProperty() (in module bpy.props), 1037
rename() (in module bpy.ops.file), 30
rename() (in module bpy.ops.marker), 47
render() (bpy.types.NET_RENDER method), 583
render() (bpy.types.RenderEngine method), 712
render() (in module bpy.ops.render), 94
render_border() (in module bpy.ops.view3d), 130
render_changed() (in module bpy.ops.node), 65
render_client() (bpy.types.NET_RENDER method), 583
render_display_mode (bpy.types.DomainFluidSettings attribute), 347
render_layer_add() (in module bpy.ops.scene), 94
render_layer_remove() (in module bpy.ops.scene), 94
render_levels (bpy.types.MultiresModifier attribute), 580
render_levels (bpy.types.SubsurfModifier attribute), 857
render_master() (bpy.types.NET_RENDER method), 583
render_output_directory (bpy.types.UserPreferencesFilePaths attribute), 981
render_resolution (bpy.types.MetaBall attribute), 562
render_resolution_u (bpy.types.Curve attribute), 333
render_resolution_v (bpy.types.Curve attribute), 333
render_slave() (bpy.types.NET_RENDER method), 583
render_step (bpy.types.ParticleSettings attribute), 657
render_steps (bpy.types.ScrewModifier attribute), 755
render_type (bpy.types.ParticleSettings attribute), 657
renderability_toggle() (in module bpy.ops.outliner), 82
rendered_child_count (bpy.types.ParticleSettings attribute), 657
RenderEngine (class in bpy.types), 712
RenderLayer (class in bpy.types), 714
RenderLayer.exclude_ambient_occlusion (in module bpy.types), 714
RenderLayer.exclude_emit (in module bpy.types), 714
RenderLayer.exclude_environment (in module bpy.types), 714
RenderLayer.exclude_indirect (in module bpy.types), 714
RenderLayer.exclude_reflection (in module bpy.types), 714
RenderLayer.exclude_refraction (in module bpy.types), 714

RenderLayer.exclude_shadow (in module bpy.types), 714
RenderLayer.exclude_specular (in module bpy.types), 714
RenderLayer.invert_zmask (in module bpy.types), 714
RenderLayer.layers (in module bpy.types), 714
RenderLayer.layers_zmask (in module bpy.types), 714
RenderLayer.light_override (in module bpy.types), 715
RenderLayer.material_override (in module bpy.types), 715
RenderLayer.name (in module bpy.types), 715
RenderLayer.passes (in module bpy.types), 715
RenderLayer.use (in module bpy.types), 715
RenderLayer.use_all_z (in module bpy.types), 715
RenderLayer.use_edge_enhance (in module bpy.types), 715
RenderLayer.use_halo (in module bpy.types), 715
RenderLayer.use_pass_ambient_occlusion (in module bpy.types), 715
RenderLayer.use_pass_color (in module bpy.types), 715
RenderLayer.use_pass_combined (in module bpy.types), 715
RenderLayer.use_pass_diffuse (in module bpy.types), 715
RenderLayer.use_pass_emit (in module bpy.types), 716
RenderLayer.use_pass_environment (in module bpy.types), 716
RenderLayer.use_pass_indirect (in module bpy.types), 716
RenderLayer.use_pass_mist (in module bpy.types), 716
RenderLayer.use_pass_normal (in module bpy.types), 716
RenderLayer.use_pass_object_index (in module bpy.types), 716
RenderLayer.use_pass_reflection (in module bpy.types), 716
RenderLayer.use_pass_refraction (in module bpy.types), 716
RenderLayer.use_pass_shadow (in module bpy.types), 716
RenderLayer.use_pass_specular (in module bpy.types), 716
RenderLayer.use_pass_uv (in module bpy.types), 716
RenderLayer.use_pass_vector (in module bpy.types), 716
RenderLayer.use_pass_z (in module bpy.types), 716
RenderLayer.use_sky (in module bpy.types), 716
RenderLayer.use_solid (in module bpy.types), 717
RenderLayer.use_strand (in module bpy.types), 717
RenderLayer.use_zmask (in module bpy.types), 717
RenderLayer.use_ztransp (in module bpy.types), 717
RenderLayers (class in bpy.types), 718
RenderPass (class in bpy.types), 719
RenderPass.channel_id (in module bpy.types), 719
RenderPass.channels (in module bpy.types), 719
RenderPass.name (in module bpy.types), 719
RenderPass.type (in module bpy.types), 719
RenderResult (class in bpy.types), 720
RenderResult.layers (in module bpy.types), 720
RenderResult.resolution_x (in module bpy.types), 720
RenderResult.resolution_y (in module bpy.types), 720
RenderSettings (class in bpy.types), 721
RenderSettings.file_extension (in module bpy.types), 723
RenderSettings.has_multiple_engines (in module bpy.types), 723
RenderSettings.is_movie_format (in module bpy.types), 723
RenderSettings.layers (in module bpy.types), 723
RenderSettings.use_game_engine (in module bpy.types), 727
rendersize() (in module bpy.ops.sequencer), 102
repeat (bge.types.SCA_DelaySensor attribute), 1134
repeat (bpy.types.NlaStrip attribute), 590
repeat_history() (in module bpy.ops.screen), 96
repeat_last() (in module bpy.ops.screen), 96
repeat_x (bpy.types.ImageTexture attribute), 447
repeat_y (bpy.types.ImageTexture attribute), 447
replace() (bge.types.KX_Scene method), 1125
replace() (in module bpy.ops.image), 40
replace() (in module bpy.ops.text), 110
replace_set_selected() (in module bpy.ops.text), 110
replace_text (bpy.types.SpaceTextEditor attribute), 831
replaceMesh() (bge.types.KX_GameObject method), 1097
report() (bpy.types.Macro method), 502
report() (bpy.types.Operator method), 626
report_copy() (in module bpy.ops.info), 44
report_delete() (in module bpy.ops.info), 44
report_missing_files() (in module bpy.ops.file), 30
report_replay() (in module bpy.ops.info), 44
reports_display_update() (in module bpy.ops.info), 44
reports_to_textblock() (in module bpy.ops.ui), 122
repulsion (bpy.types.SPHFluidSettings attribute), 733
reset() (bge.types.SCA_ISensor method), 1085
reset() (in module bpy.ops.brush), 17
reset() (in module bpy.ops.uv), 125
reset() (in module bpy.ops.view2d), 127
reset_default_button() (in module bpy.ops.ui), 122
reset_default_theme() (in module bpy.ops.ui), 122
reset_distance (bpy.types.NearSensor attribute), 584
resetDistance (bge.types.KX_NearSensor attribute), 1110
resize() (in module bpy.ops.node), 65
resize() (in module bpy.ops.transform), 115
resize_2d() (mathutils.Vector method), 1051
resize_3d() (mathutils.Vector method), 1051
resize_4d() (mathutils.Vector method), 1051
resize_4x4() (mathutils.Matrix method), 1043
resolution (bpy.types.DomainFluidSettings attribute), 347
resolution (bpy.types.EnvironmentMap attribute), 369
resolution (bpy.types.MetaBall attribute), 562
resolution (bpy.types.VoxelData attribute), 1003

resolution_max (bpy.types.SmokeDomainSettings attribute), 799
resolution_percentage (bpy.types.RenderSettings attribute), 724
resolution_u (bpy.types.Curve attribute), 333
resolution_u (bpy.types.Spline attribute), 842
resolution_v (bpy.types.Curve attribute), 333
resolution_v (bpy.types.Spline attribute), 842
resolution_x (bpy.types.RenderSettings attribute), 724
resolution_x (bpy.types.SceneGameData attribute), 742
resolution_y (bpy.types.RenderSettings attribute), 724
resolution_y (bpy.types.SceneGameData attribute), 742
resolve_conflict() (in module bpy.ops.text), 110
resolve_ncase() (in module bpy.path), 1031
rest_density (bpy.types.SPHFluidSettings attribute), 733
rest_length (bpy.types.FieldSettings attribute), 395
rest_length (bpy.types.SPHFluidSettings attribute), 733
rest_length (bpy.types.StretchToConstraint attribute), 852
rest_shape_key (bpy.types.ClothSettings attribute), 247
restart() (bge.types.KX_Scene method), 1125
restartGame() (in module bge.logic), 1157
restore_item_to_default() (bpy.types.KeyMap method), 462
restore_to_default() (bpy.types.KeyMap method), 462
restoreDynamics() (bge.types.KX_GameObject method), 1100
resume() (bge.types.KX_Scene method), 1125
RETKEY (in module bge.events), 1176
reveal() (in module bpy.ops.armature), 16
reveal() (in module bpy.ops.curve), 23
reveal() (in module bpy.ops.mesh), 57
reveal() (in module bpy.ops.particle), 87
reveal() (in module bpy.ops.pose), 90
reveal() (in module bpy.ops.uv), 125
reveal_metaelems() (in module bpy.ops.mball), 48
reverse() (bge.types.CListValue method), 1091
RGBANodeSocket (class in bpy.types), 702
RIGHTALTKEY (in module bge.events), 1174
RIGHTARROWKEY (in module bge.events), 1175
RIGHTBRACKETKEY (in module bge.events), 1176
RIGHTCTRLKEY (in module bge.events), 1174
RIGHTMOUSE (in module bge.events), 1173
RIGHTSHIFTKEY (in module bge.events), 1174
RigidBodyJointConstraint (class in bpy.types), 730
ring_count (bpy.types.MaterialHalo attribute), 516
rip() (in module bpy.ops.mesh), 57
rip_move() (in module bpy.ops.mesh), 57
RKEY (in module bge.events), 1174
roll (bge.types.BL_ArmatureBone attribute), 1154
roll (bpy.types.EditBone attribute), 358
rolloff_factor_3d (bpy.types.SoundActuator attribute), 811
rollOffFactor (bge.types.KX_SoundActuator attribute), 1126
root_size (bpy.types.MaterialStrand attribute), 523
rot_clear() (in module bpy.ops.pose), 90
rot_error (bge.types.BL_ArmatureConstraint attribute), 1148
rotate() (in module bpy.ops.transform), 115
rotate() (in module bpy.ops.view3d), 130
rotate() (mathutils.Euler method), 1040
rotate() (mathutils.Matrix method), 1044
rotate() (mathutils.Quaternion method), 1047
rotate_axis() (mathutils.Euler method), 1040
rotation (bpy.types.MetaElement attribute), 564
rotation (bpy.types.Particle attribute), 640
rotation (bpy.types.ParticleKey attribute), 649
rotation (bpy.types.ShaderNodeMapping attribute), 774
rotation (bpy.types.TexMapping attribute), 862
ROTATION (in module blf), 1071
rotation() (in module blf), 1073
Rotation() (mathutils.Matrix class method), 1042
rotation_angle (bpy.types.UserPreferencesView attribute), 989
rotation_apply() (in module bpy.ops.object), 76
rotation_axis_angle (bpy.types.Object attribute), 608
rotation_axis_angle (bpy.types.PoseBone attribute), 690
rotation_clear() (in module bpy.ops.object), 76
rotation_damping (bpy.types.GameObjectSettings attribute), 417
rotation_estimate (bpy.types.SoftBodySettings attribute), 806
rotation_euler (bge.types.BL_ArmatureChannel attribute), 1151
rotation_euler (bpy.types.Object attribute), 608
rotation_euler (bpy.types.PoseBone attribute), 690
rotation_factor_random (bpy.types.ParticleSettings attribute), 657
rotation_max (bpy.types.ConstraintActuator attribute), 320
rotation_mode (bge.types.BL_ArmatureChannel attribute), 1151
rotation_mode (bpy.types.Object attribute), 608
rotation_mode (bpy.types.ParticleSettings attribute), 657
rotation_mode (bpy.types.PoseBone attribute), 690
rotation_quaternion (bge.types.BL_ArmatureChannel attribute), 1151
rotation_quaternion (bpy.types.Object attribute), 608
rotation_quaternion (bpy.types.PoseBone attribute), 690
rotation_range (bpy.types.PivotConstraint attribute), 673
rotation_start (bpy.types.TransformSequence attribute), 947
rotDamp (bge.types.KX_ConstraintActuator attribute), 1093
rough_factor (bpy.types.ParticleSettingsTextureSlot attribute), 663
roughness (bpy.types.Material attribute), 511
roughness_1 (bpy.types.ParticleSettings attribute), 657

roughness_1_size (bpy.types.ParticleSettings attribute), 657
roughness_2 (bpy.types.ParticleSettings attribute), 658
roughness_2_size (bpy.types.ParticleSettings attribute), 658
roughness_2_threshold (bpy.types.ParticleSettings attribute), 658
roughness_end_shape (bpy.types.ParticleSettings attribute), 658
roughness_endpoint (bpy.types.ParticleSettings attribute), 658
row() (bpy.types.UILayout method), 949
row_size (mathutils.Matrix attribute), 1045
rule_add() (in module bpy.ops.boid), 17
rule_del() (in module bpy.ops.boid), 17
rule_fuzzy (bpy.types.BoidState attribute), 218
rule_move_down() (in module bpy.ops.boid), 17
rule_move_up() (in module bpy.ops.boid), 17
ruleset_type (bpy.types.BoidState attribute), 218
run_script() (in module bpy.ops.text), 111

S

s (mathutils.Color attribute), 1040
sample() (in module bpy.ops.action), 10
sample() (in module bpy.ops.graph), 36
sample() (in module bpy.ops.image), 40
sample_color() (in module bpy.ops.paint), 84
sample_line() (in module bpy.ops.image), 40
sample_method (bpy.types.WorldLighting attribute), 1018
samples (bpy.types.CompositorNodeDefocus attribute), 277
samples (bpy.types.CompositorNodeVecBlur attribute), 312
samples (bpy.types.WorldLighting attribute), 1018
saturation (bpy.types.Texture attribute), 873
save() (bpy.types.Image method), 441
save() (in module bpy.ops.image), 41
save() (in module bpy.ops.text), 111
save_as() (in module bpy.ops.image), 41
save_as() (in module bpy.ops.text), 111
save_as_mainfile() (in module bpy.ops.wm), 140
save_dirty() (in module bpy.ops.image), 41
save_homefile() (in module bpy.ops.wm), 141
save_mainfile() (in module bpy.ops.wm), 141
save_render() (bpy.types.Image method), 441
save_sequence() (in module bpy.ops.image), 41
save_version (bpy.types.UserPreferencesFilePaths attribute), 981
saveGlobalDict() (in module bge.logic), 1157
SCA_2DFilterActuator (class in bge.types), 1133
SCA_ActuatorSensor (class in bge.types), 1133
SCA_AlwaysSensor (class in bge.types), 1133
SCA_ANDController (class in bge.types), 1133
SCA_DelaySensor (class in bge.types), 1133
SCA_IActuator (class in bge.types), 1086
SCA_IController (class in bge.types), 1085
SCA_ILogicBrick (class in bge.types), 1083
SCA_IObject (class in bge.types), 1084
SCA_ISensor (class in bge.types), 1084
SCA_JoystickSensor (class in bge.types), 1134
SCA_KeyboardSensor (class in bge.types), 1136
SCA_MouseSensor (class in bge.types), 1108
SCA_NANDController (class in bge.types), 1137
SCA_NORController (class in bge.types), 1137
SCA_ORController (class in bge.types), 1137
SCA_PropertyActuator (class in bge.types), 1137
SCA_PropertySensor (class in bge.types), 1137
SCA_PythonController (class in bge.types), 1137
SCA_PythonKeyboard (class in bge.types), 1083
SCA_PythonMouse (class in bge.types), 1084
SCA_RandomActuator (class in bge.types), 1138
SCA_RandomSensor (class in bge.types), 1140
SCA_XNORController (class in bge.types), 1140
SCA_XORController (class in bge.types), 1140
scale (bge.types.BL_ArmatureChannel attribute), 1150
scale (bpy.types.FModifierNoise attribute), 391
scale (bpy.types.MaterialSubsurfaceScattering attribute), 525
scale (bpy.types.NlaStrip attribute), 590
scale (bpy.types.Object attribute), 608
scale (bpy.types.PoseBone attribute), 690
scale (bpy.types.ShaderNodeMapping attribute), 774
scale (bpy.types.TexMapping attribute), 862
scale (bpy.types.TextureSlot attribute), 894
Scale() (mathutils.Matrix class method), 1042
scale_apply() (in module bpy.ops.object), 76
scale_clear() (in module bpy.ops.object), 76
scale_clear() (in module bpy.ops.pose), 90
scale_estimate (bpy.types.SoftBodySettings attribute), 806
scale_length (bpy.types.UnitSettings attribute), 974
scale_size() (in module bpy.ops.brush), 17
scale_start_x (bpy.types.TransformSequence attribute), 947
scale_start_y (bpy.types.TransformSequence attribute), 947
scale_to_length (bpy.types.SpeedControlSequence attribute), 839
scale_x (bpy.types.UILayout attribute), 949
scale_x (bpy.types.UVProjectModifier attribute), 972
scale_y (bpy.types.UILayout attribute), 949
scale_y (bpy.types.UVProjectModifier attribute), 972
scaling (bge.types.KX_GameObject attribute), 1095
scattering (bpy.types.MaterialVolume attribute), 533
scattering_factor (bpy.types.MaterialTextureSlot attribute), 527
scene (bge.types.KX_SceneActuator attribute), 1126

scene (bpy.types.CompositorNodeRLayers attribute), 300
scene (bpy.types.SceneActuator attribute), 739
scene (bpy.types.SceneSequence attribute), 750
scene (bpy.types.Screen attribute), 753
Scene (class in bpy.types), 735
scene (in module bpy.context), 3
Scene.animation_data (in module bpy.types), 735
Scene.game_settings (in module bpy.types), 736
Scene.is_nla_tweakmode (in module bpy.types), 736
Scene.keying_sets (in module bpy.types), 736
Scene.keying_sets_all (in module bpy.types), 736
Scene.network_render (in module bpy.types), 736
Scene.node_tree (in module bpy.types), 736
Scene.object_bases (in module bpy.types), 736
Scene.objects (in module bpy.types), 736
Scene.orientations (in module bpy.types), 736
Scene.render (in module bpy.types), 736
Scene.sequence_editor (in module bpy.types), 737
Scene.timeline_markers (in module bpy.types), 737
Scene.tool_settings (in module bpy.types), 737
Scene.unit_settings (in module bpy.types), 737
scene_camera (bpy.types.SceneSequence attribute), 750
scene_strip (bpy.types.ThemeSequenceEditor attribute), 921
scene_strip_add() (in module bpy.ops.sequencer), 102
SceneActuator (class in bpy.types), 739
SceneBases (class in bpy.types), 740
SceneGameData (class in bpy.types), 741
SceneObjects (class in bpy.types), 744
SceneRenderLayer (class in bpy.types), 745
SceneSequence (class in bpy.types), 749
SceneSequence.color_balance (in module bpy.types), 749
SceneSequence.crop (in module bpy.types), 749
SceneSequence.proxy (in module bpy.types), 750
SceneSequence.transform (in module bpy.types), 750
scope_back (bpy.types.ThemeImageEditor attribute), 910
Scopes (class in bpy.types), 752
scopes() (in module bpy.ops.image), 41
Scopes.histogram (in module bpy.types), 752
screen (bpy.types.Window attribute), 1008
Screen (class in bpy.types), 753
Screen.areas (in module bpy.types), 753
Screen.is_animation_playing (in module bpy.types), 753
Screen.show_fullscreen (in module bpy.types), 753
screen_full_area() (in module bpy.ops.screen), 96
screen_grab_size (bpy.types.ImagePaint attribute), 442
screen_set() (in module bpy.ops.screen), 96
screencast() (in module bpy.ops.screen), 96
screencast_fps (bpy.types.UserPreferencesSystem attribute), 986
screencast_wait_time (bpy.types.UserPreferencesSystem attribute), 986
screenshot() (in module bpy.ops.screen), 96
screw() (in module bpy.ops.mesh), 57
screw_offset (bpy.types.ScrewModifier attribute), 755
ScrewModifier (class in bpy.types), 755
script (bge.types.SCA_PythonController attribute), 1137
script_directory (bpy.types.UserPreferencesFilePaths attribute), 981
script_paths() (in module bpy.utils), 1030
scroll() (in module bpy.ops.text), 111
scroll_bar (bpy.types.ThemeTextEditor attribute), 923
scroll_bar() (in module bpy.ops.text), 111
scroll_down() (in module bpy.ops.view2d), 127
scroll_handle (bpy.types.ThemeFileBrowser attribute), 904
scroll_left() (in module bpy.ops.view2d), 127
scroll_page() (in module bpy.ops.outliner), 82
scroll_right() (in module bpy.ops.view2d), 127
scroll_up() (in module bpy.ops.view2d), 128
scrollback (bpy.types.UserPreferencesSystem attribute), 986
scrollback_append() (in module bpy.ops.console), 20
scrollbar (bpy.types.ThemeFileBrowser attribute), 904
scroller_activate() (in module bpy.ops.view2d), 128
Sculpt (class in bpy.types), 756
sculpt_levels (bpy.types.MultiresModifier attribute), 580
sculpt_object (in module bpy.context), 4
sculpt_paint_overlay_color (bpy.types.UserPreferencesEdit attribute), 978
sculpt_paint_use_unified_size (bpy.types.ToolSettings attribute), 939
sculpt_paint_use_unified_strength (bpy.types.ToolSettings attribute), 939
sculpt_plane (bpy.types.Brush attribute), 228
sculpt_tool (bpy.types.Brush attribute), 228
sculptmode_toggle() (in module bpy.ops.sculpt), 98
seam_bleed (bpy.types.ImagePaint attribute), 442
search_menu() (in module bpy.ops.wm), 142
secondary_target (bpy.types.ArmatureActuator attribute), 169
seed (bge.types.SCA_RandomActuator attribute), 1138
seed (bge.types.SCA_RandomSensor attribute), 1140
seed (bpy.types.BuildModifier attribute), 233
seed (bpy.types.FieldSettings attribute), 395
seed (bpy.types.MaterialHalo attribute), 516
seed (bpy.types.ParticleSystem attribute), 668
seed (bpy.types.RandomActuator attribute), 705
seed (bpy.types.RandomSensor attribute), 706
select (bpy.types.ActionGroup attribute), 148
select (bpy.types.Bone attribute), 220
select (bpy.types.CurveMapPoint attribute), 336
select (bpy.types.EditBone attribute), 358
select (bpy.types.FCurve attribute), 377
select (bpy.types.FCurveSample attribute), 382
select (bpy.types.GPencilFrame attribute), 409
select (bpy.types.GPencilLayer attribute), 410

select (bpy.types.MeshEdge attribute), 545
select (bpy.types.MeshFace attribute), 547
select (bpy.types.MeshVertex attribute), 558
select (bpy.types.MotionPathVert attribute), 572
select (bpy.types.NlaStrip attribute), 591
select (bpy.types.NlaTrack attribute), 593
select (bpy.types.Object attribute), 608
select (bpy.types.ObjectBase attribute), 617
select (bpy.types.Sequence attribute), 761
select (bpy.types.SplinePoint attribute), 846
select (bpy.types.ThemeBoneColorSet attribute), 898
select (bpy.types.TimelineMarker attribute), 936
select() (in module bpy.ops.file), 30
select() (in module bpy.ops.marker), 47
select() (in module bpy.ops.node), 65
select() (in module bpy.ops.sequencer), 102
select() (in module bpy.ops.sketch), 105
select() (in module bpy.ops.uv), 125
select() (in module bpy.ops.view3d), 130
select_active_side() (in module bpy.ops.sequencer), 102
select_all() (in module bpy.ops.armature), 16
select_all() (in module bpy.ops.curve), 23
select_all() (in module bpy.ops.lattice), 45
select_all() (in module bpy.ops.marker), 47
select_all() (in module bpy.ops.mball), 48
select_all() (in module bpy.ops.mesh), 57
select_all() (in module bpy.ops.node), 65
select_all() (in module bpy.ops.object), 76
select_all() (in module bpy.ops.particle), 87
select_all() (in module bpy.ops.pose), 90
select_all() (in module bpy.ops.text), 111
select_all() (in module bpy.ops.uv), 125
select_all_toggle() (in module bpy.ops.action), 10
select_all_toggle() (in module bpy.ops.file), 30
select_all_toggle() (in module bpy.ops.graph), 36
select_all_toggle() (in module bpy.ops.info), 44
select_all_toggle() (in module bpy.ops.nla), 62
select_all_toggle() (in module bpy.ops.sequencer), 102
select_axis() (in module bpy.ops.mesh), 57
select_bookmark() (in module bpy.ops.file), 30
select_border() (in module bpy.ops.action), 10
select_border() (in module bpy.ops.file), 30
select_border() (in module bpy.ops.graph), 36
select_border() (in module bpy.ops.info), 44
select_border() (in module bpy.ops.marker), 47
select_border() (in module bpy.ops.nla), 62
select_border() (in module bpy.ops.node), 65
select_border() (in module bpy.ops.sequencer), 102
select_border() (in module bpy.ops.uv), 125
select_border() (in module bpy.ops.view3d), 130
select_by_layer() (in module bpy.ops.object), 76
select_by_number_vertices() (in module bpy.ops.mesh), 58
select_by_type() (in module bpy.ops.object), 77
select_camera() (in module bpy.ops.object), 77
select_circle() (in module bpy.ops.view3d), 131
select_column() (in module bpy.ops.action), 10
select_column() (in module bpy.ops.graph), 36
select_constraint_target() (in module bpy.ops.pose), 90
select_control_point (bpy.types.BezierSplinePoint attribute), 178
select_control_point (bpy.types.Keyframe attribute), 474
select_end (bpy.types.SpaceConsole attribute), 815
select_flip_active() (in module bpy.ops.pose), 90
select_grouped() (in module bpy.ops.object), 77
select_grouped() (in module bpy.ops.pose), 90
select_handles() (in module bpy.ops.sequencer), 102
select_head (bpy.types.Bone attribute), 220
select_head (bpy.types.EditBone attribute), 358
select_hierarchy() (in module bpy.ops.armature), 16
select_hierarchy() (in module bpy.ops.object), 77
select_hierarchy() (in module bpy.ops.pose), 91
select_inverse() (in module bpy.ops.armature), 16
select_inverse() (in module bpy.ops.curve), 23
select_inverse() (in module bpy.ops.mesh), 58
select_inverse() (in module bpy.ops.object), 77
select_inverse() (in module bpy.ops.particle), 87
select_inverse() (in module bpy.ops.pose), 91
select_inverse() (in module bpy.ops.sequencer), 103
select_inverse() (in module bpy.ops.uv), 125
select_inverse_metaelems() (in module bpy.ops.mball), 48
select_lasso() (in module bpy.ops.view3d), 131
select_left_handle (bpy.types.BezierSplinePoint attribute), 178
select_left_handle (bpy.types.Keyframe attribute), 474
select_left_handle (bpy.types.Sequence attribute), 761
select_leftright() (in module bpy.ops.action), 10
select_leftright() (in module bpy.ops.graph), 36
select_leftright() (in module bpy.ops.nla), 62
select_less() (in module bpy.ops.action), 10
select_less() (in module bpy.ops.curve), 23
select_less() (in module bpy.ops.graph), 37
select_less() (in module bpy.ops.mesh), 58
select_less() (in module bpy.ops.particle), 87
select_less() (in module bpy.ops.sequencer), 103
select_line() (in module bpy.ops.text), 111
select_link_viewer() (in module bpy.ops.node), 65
select_linked() (in module bpy.ops.action), 10
select_linked() (in module bpy.ops.armature), 16
select_linked() (in module bpy.ops.curve), 23
select_linked() (in module bpy.ops.graph), 37
select_linked() (in module bpy.ops.mesh), 58
select_linked() (in module bpy.ops.object), 77
select_linked() (in module bpy.ops.particle), 87
select_linked() (in module bpy.ops.pose), 91
select_linked() (in module bpy.ops.sequencer), 103
select_linked() (in module bpy.ops.uv), 125

select_linked_from() (in module bpy.ops.node), 65
select_linked_pick() (in module bpy.ops.curve), 23
select_linked_pick() (in module bpy.ops.mesh), 58
select_linked_pick() (in module bpy.ops.sequencer), 103
select_linked_pick() (in module bpy.ops.uv), 125
select_linked_to() (in module bpy.ops.node), 65
select_loop() (in module bpy.ops.uv), 125
select_mirror() (in module bpy.ops.mesh), 58
select_mirror() (in module bpy.ops.object), 77
select_mode (bpy.types.ParticleEdit attribute), 644
select_more() (in module bpy.ops.action), 10
select_more() (in module bpy.ops.curve), 24
select_more() (in module bpy.ops.graph), 37
select_more() (in module bpy.ops.mesh), 58
select_more() (in module bpy.ops.particle), 87
select_more() (in module bpy.ops.sequencer), 103
select_mouse (bpy.types.UserPreferencesInput attribute), 984
select_name() (in module bpy.ops.object), 78
select_next() (in module bpy.ops.curve), 24
select_non_manifold() (in module bpy.ops.mesh), 58
select_nth() (in module bpy.ops.curve), 24
select_nth() (in module bpy.ops.mesh), 58
select_orientation() (in module bpy.ops.transform), 116
select_parent() (in module bpy.ops.pose), 91
select_pattern() (in module bpy.ops.object), 78
select_pick() (in module bpy.ops.info), 44
select_pinned() (in module bpy.ops.uv), 126
select_previous() (in module bpy.ops.curve), 24
select_random() (in module bpy.ops.curve), 24
select_random() (in module bpy.ops.mesh), 58
select_random() (in module bpy.ops.object), 78
select_random_metaelems() (in module bpy.ops.mball), 48
select_right_handle (bpy.types.BezierSplinePoint attribute), 178
select_right_handle (bpy.types.Keyframe attribute), 474
select_right_handle (bpy.types.Sequence attribute), 761
select_roots() (in module bpy.ops.particle), 87
select_row() (in module bpy.ops.curve), 24
select_same_group() (in module bpy.ops.object), 78
select_same_type() (in module bpy.ops.node), 66
select_same_type_next() (in module bpy.ops.node), 66
select_same_type_prev() (in module bpy.ops.node), 66
select_set() (in module bpy.ops.console), 20
select_shortest_path() (in module bpy.ops.mesh), 58
select_similar() (in module bpy.ops.mesh), 58
select_start (bpy.types.SpaceConsole attribute), 815
select_tail (bpy.types.Bone attribute), 220
select_tail (bpy.types.EditBone attribute), 358
select_tips() (in module bpy.ops.particle), 87
select_uv (bpy.types.MeshTextureFace attribute), 554
select_vertex_path() (in module bpy.ops.mesh), 59
select_word() (in module bpy.ops.text), 111
selectability_toggle() (in module bpy.ops.outliner), 82
selectable_bases (in module bpy.context), 3, 5
selectable_objects (in module bpy.context), 3, 5
selected_bases (in module bpy.context), 3, 5
selected_bones (in module bpy.context), 4
selected_editable_bases (in module bpy.context), 3, 5
selected_editable_bones (in module bpy.context), 4
selected_editable_objects (in module bpy.context), 3, 5
selected_editable_sequences (in module bpy.context), 4
selected_file (bpy.types.ThemeFileBrowser attribute), 904
selected_nodes (in module bpy.context), 7
selected_objects (in module bpy.context), 3, 5
selected_pose_bones (in module bpy.context), 4
selected_sequences (in module bpy.context), 4
selected_text (bpy.types.ThemeNodeEditor attribute), 916
selected_text (bpy.types.ThemeTextEditor attribute), 923
selected_toggle() (in module bpy.ops.outliner), 82
selection_set() (in module bpy.ops.text), 111
self_collision_quality (bpy.types.ClothCollisionSettings attribute), 244
self_distance_min (bpy.types.ClothCollisionSettings attribute), 244
self_friction (bpy.types.ClothCollisionSettings attribute), 244
SEMICOLONKEY (in module bge.events), 1176
sendMessage() (bge.types.KX_GameObject method), 1103
sendMessage() (in module bge.logic), 1158
Sensor (class in bpy.types), 758
sensor_add() (in module bpy.ops.logic), 46
sensor_move() (in module bpy.ops.logic), 46
sensor_remove() (in module bpy.ops.logic), 46
sensors (bge.types.KX_GameObject attribute), 1096
sensors (bge.types.SCA_IController attribute), 1085
separate() (in module bpy.ops.armature), 16
separate() (in module bpy.ops.curve), 24
separate() (in module bpy.ops.mesh), 59
separator() (bpy.types.UILayout method), 967
seq_slide() (in module bpy.ops.transform), 116
Sequence (class in bpy.types), 759
Sequence.frame_duration (in module bpy.types), 760
Sequence.frame_offset_end (in module bpy.types), 760
Sequence.frame_offset_start (in module bpy.types), 760
Sequence.frame_still_end (in module bpy.types), 760
Sequence.frame_still_start (in module bpy.types), 760
Sequence.input_1 (in module bpy.types), 760
Sequence.input_2 (in module bpy.types), 760
Sequence.input_3 (in module bpy.types), 760
Sequence.input_count (in module bpy.types), 760
Sequence.type (in module bpy.types), 761
sequence_plugin_directory (bpy.types.UserPreferencesFilePaths attribute),

981
SequenceColorBalance (class in bpy.types), 762
SequenceCrop (class in bpy.types), 763
SequenceEditor (class in bpy.types), 764
SequenceEditor.meta_stack (in module bpy.types), 764
SequenceEditor.sequences (in module bpy.types), 765
SequenceEditor.sequences_all (in module bpy.types), 765
SequenceElement (class in bpy.types), 765
SequenceElement.orig_height (in module bpy.types), 765
SequenceElement.orig_width (in module bpy.types), 766
SequenceProxy (class in bpy.types), 766
sequencer_gl_preview (bpy.types.RenderSettings attribute), 724
sequencer_gl_render (bpy.types.RenderSettings attribute), 724
sequences (in module bpy.context), 4
SequenceTransform (class in bpy.types), 767
server_address (bpy.types.NetRenderSettings attribute), 587
server_port (bpy.types.NetRenderSettings attribute), 587
set_active_number() (in module bpy.ops.brush), 17
set_persistent_base() (in module bpy.ops.sculpt), 98
setActive() (bge.types.KX_PhysicsObjectWrapper method), 1112
setAmbientColor() (in module bge.render), 1170
setAngularVelocity() (bge.types.KX_GameObject method), 1100
setAngularVelocity() (bge.types.KX_PhysicsObjectWrapper method), 1113
setAttrib() (bge.types.BL_Shader method), 1088
setBackgroundColor() (in module bge.render), 1170
setBlending() (bge.types.KX_BlenderMaterial method), 1092
setBoolBernouilli() (bge.types.SCA_RandomActuator method), 1139
setBoolConst() (bge.types.SCA_RandomActuator method), 1139
setBoolUniform() (bge.types.SCA_RandomActuator method), 1139
setChannel() (bge.types.BL_ActionActuator method), 1087
setCollisionMargin() (bge.types.KX_GameObject method), 1103
setCustomMaterial() (bge.types.KX_PolygonMaterial method), 1119
setEyeSeparation() (in module bge.render), 1170
setFloatConst() (bge.types.SCA_RandomActuator method), 1139
setFloatNegativeExponential() (bge.types.SCA_RandomActuator method), 1139
setFloatNormal() (bge.types.SCA_RandomActuator method), 1139
setFloatUniform() (bge.types.SCA_RandomActuator method), 1139
setFocalLength() (in module bge.render), 1171
setGLSLMaterialSetting() (in module bge.render), 1171
setGravity() (in module bge.logic), 1158
setIntConst() (bge.types.SCA_RandomActuator method), 1139
setIntPoisson() (bge.types.SCA_RandomActuator method), 1139
setIntUniform() (bge.types.SCA_RandomActuator method), 1139
setLinearVelocity() (bge.types.KX_GameObject method), 1099
setLinearVelocity() (bge.types.KX_PhysicsObjectWrapper method), 1113
setLogicTicRate() (in module bge.logic), 1159
setMaterialMode() (in module bge.render), 1171
setMaxLogicFrame() (in module bge.logic), 1158
setMaxPhysicsFrame() (in module bge.logic), 1158
setMistColor() (in module bge.render), 1170
setMistEnd() (in module bge.render), 1170
setMistStart() (in module bge.render), 1170
setMousePosition() (in module bge.render), 1170
setNormal() (bge.types.KX_VertexProxy method), 1132
setNumberOfPasses() (bge.types.BL_Shader method), 1088
setOcclusion() (bge.types.KX_GameObject method), 1097
setOnTop() (bge.types.KX_Camera method), 1143
setParent() (bge.types.KX_GameObject method), 1101
setPhysicsTicRate() (in module bge.logic), 1159
setRGBA() (bge.types.KX_VertexProxy method), 1132
setRollInfluence() (bge.types.KX_VehicleWrapper method), 1129
setSampler() (bge.types.BL_Shader method), 1088
setSeed() (bge.types.SCA_RandomSensor method), 1140
setSource() (bge.types.BL_Shader method), 1088
setSteeringValue() (bge.types.KX_VehicleWrapper method), 1129
setSuspensionCompression() (bge.types.KX_VehicleWrapper method), 1129
setSuspensionDamping() (bge.types.KX_VehicleWrapper method), 1129
setSuspensionStiffness() (bge.types.KX_VehicleWrapper method), 1129
setTexture() (bge.types.KX_PolygonMaterial method), 1118
settings (bpy.types.ParticleSystem attribute), 668
setTyreFriction() (bge.types.KX_VehicleWrapper method), 1129
setUniform1f() (bge.types.BL_Shader method), 1088
setUniform1i() (bge.types.BL_Shader method), 1088

setUniform2f() (bge.types.BL_Shader method), 1088
setUniform2i() (bge.types.BL_Shader method), 1088
setUniform3f() (bge.types.BL_Shader method), 1088
setUniform3i() (bge.types.BL_Shader method), 1089
setUniform4f() (bge.types.BL_Shader method), 1089
setUniform4i() (bge.types.BL_Shader method), 1089
setUniformDef() (bge.types.BL_Shader method), 1089
setUniformfv() (bge.types.BL_Shader method), 1087
setUniformiv() (bge.types.BL_Shader method), 1090
setUniformMatrix3() (bge.types.BL_Shader method), 1089
setUniformMatrix4() (bge.types.BL_Shader method), 1090
setUV() (bge.types.KX_VertexProxy method), 1131
setUV2() (bge.types.KX_VertexProxy method), 1131
setViewport() (bge.types.KX_Camera method), 1143
setVisible() (bge.types.KX_GameObject method), 1097
setXYZ() (bge.types.KX_VertexProxy method), 1131
SEVENKEY (in module bge.events), 1174
shade_flat() (in module bpy.ops.curve), 24
shade_flat() (in module bpy.ops.object), 78
shade_smooth() (in module bpy.ops.curve), 24
shade_smooth() (in module bpy.ops.object), 78
shadedown (bpy.types.ThemeWidgetColors attribute), 933
ShaderNode (class in bpy.types), 768
ShaderNode.type (in module bpy.types), 768
ShaderNodeCameraData (class in bpy.types), 769
ShaderNodeCombineRGB (class in bpy.types), 770
ShaderNodeExtendedMaterial (class in bpy.types), 770
ShaderNodeGeometry (class in bpy.types), 771
ShaderNodeHueSaturation (class in bpy.types), 772
ShaderNodeInvert (class in bpy.types), 773
ShaderNodeMapping (class in bpy.types), 773
ShaderNodeMaterial (class in bpy.types), 775
ShaderNodeMath (class in bpy.types), 776
ShaderNodeMixRGB (class in bpy.types), 776
ShaderNodeNormal (class in bpy.types), 777
ShaderNodeOutput (class in bpy.types), 778
ShaderNodeRGB (class in bpy.types), 779
ShaderNodeRGBCurve (class in bpy.types), 779
ShaderNodeRGBCurve.mapping (in module bpy.types), 779
ShaderNodeRGBToBW (class in bpy.types), 780
ShaderNodes (class in bpy.types), 787
ShaderNodeSeparateRGB (class in bpy.types), 781
ShaderNodeSqueeze (class in bpy.types), 781
ShaderNodeTexture (class in bpy.types), 782
ShaderNodeTree (class in bpy.types), 783
ShaderNodeTree.nodes (in module bpy.types), 783
ShaderNodeValToRGB (class in bpy.types), 784
ShaderNodeValToRGB.color_ramp (in module bpy.types), 784
ShaderNodeValue (class in bpy.types), 785
ShaderNodeVectorCurve (class in bpy.types), 785
ShaderNodeVectorCurve.mapping (in module bpy.types), 785
ShaderNodeVectorMath (class in bpy.types), 786
shaderText (bge.types.SCA_2DFilterActuator attribute), 1133
shadetop (bpy.types.ThemeWidgetColors attribute), 933
shadow (bpy.types.ThemeFontStyle attribute), 905
SHADOW (in module blf), 1071
shadow() (in module blf), 1073
shadow_adaptive_threshold (bpy.types.AreaLamp attribute), 164
shadow_adaptive_threshold (bpy.types.PointLamp attribute), 683
shadow_adaptive_threshold (bpy.types.SpotLamp attribute), 848
shadow_adaptive_threshold (bpy.types.SunLamp attribute), 858
shadow_adjust (bpy.types.CompositorNodeChromaMatte attribute), 265
shadow_buffer_bias (bpy.types.Material attribute), 511
shadow_buffer_bias (bpy.types.SpotLamp attribute), 848
shadow_buffer_clip_end (bpy.types.SpotLamp attribute), 848
shadow_buffer_clip_start (bpy.types.SpotLamp attribute), 848
shadow_buffer_samples (bpy.types.SpotLamp attribute), 848
shadow_buffer_size (bpy.types.SpotLamp attribute), 848
shadow_buffer_soft (bpy.types.SpotLamp attribute), 848
shadow_buffer_type (bpy.types.SpotLamp attribute), 848
shadow_cast_alpha (bpy.types.Material attribute), 511
shadow_color (bpy.types.AreaLamp attribute), 164
shadow_color (bpy.types.PointLamp attribute), 683
shadow_color (bpy.types.SpotLamp attribute), 848
shadow_color (bpy.types.SunLamp attribute), 858
shadow_factor (bpy.types.LampTextureSlot attribute), 488
shadow_filter_type (bpy.types.SpotLamp attribute), 849
shadow_method (bpy.types.AreaLamp attribute), 164
shadow_method (bpy.types.PointLamp attribute), 684
shadow_method (bpy.types.SpotLamp attribute), 849
shadow_method (bpy.types.SunLamp attribute), 858
shadow_offset() (in module blf), 1073
shadow_offset_x (bpy.types.ThemeFontStyle attribute), 905
shadow_offset_y (bpy.types.ThemeFontStyle attribute), 905
shadow_only_type (bpy.types.Material attribute), 511
shadow_ray_bias (bpy.types.Material attribute), 511
shadow_ray_sample_method (bpy.types.AreaLamp attribute), 164
shadow_ray_sample_method (bpy.types.PointLamp attribute), 684

shadow_ray_sample_method (bpy.types.SpotLamp attribute), 849
shadow_ray_sample_method (bpy.types.SunLamp attribute), 858
shadow_ray_samples (bpy.types.PointLamp attribute), 684
shadow_ray_samples (bpy.types.SpotLamp attribute), 849
shadow_ray_samples (bpy.types.SunLamp attribute), 859
shadow_ray_samples_x (bpy.types.AreaLamp attribute), 164
shadow_ray_samples_y (bpy.types.AreaLamp attribute), 164
shadow_sample_buffers (bpy.types.SpotLamp attribute), 849
shadow_soft_size (bpy.types.AreaLamp attribute), 164
shadow_soft_size (bpy.types.PointLamp attribute), 684
shadow_soft_size (bpy.types.SpotLamp attribute), 849
shadow_soft_size (bpy.types.SunLamp attribute), 859
shadowalpha (bpy.types.ThemeFontStyle attribute), 905
shadowcolor (bpy.types.ThemeFontStyle attribute), 905
shape (bpy.types.AreaLamp attribute), 164
shape (bpy.types.FieldSettings attribute), 395
shape (bpy.types.MaterialStrand attribute), 523
shape_key_add() (bpy.types.Object method), 611
shape_key_add() (in module bpy.ops.object), 78
shape_key_clear() (in module bpy.ops.object), 78
shape_key_mirror() (in module bpy.ops.object), 78
shape_key_move() (in module bpy.ops.object), 78
shape_key_remove() (in module bpy.ops.object), 78
shape_key_transfer() (in module bpy.ops.object), 78
shape_propagate_to_all() (in module bpy.ops.mesh), 59
shape_threshold (bpy.types.GameSoftBodySettings attribute), 421
ShapeActionActuator (class in bpy.types), 788
ShapeKey (class in bpy.types), 789
ShapeKey.data (in module bpy.types), 789
ShapeKey.frame (in module bpy.types), 789
ShapeKeyBezierPoint (class in bpy.types), 791
ShapeKeyCurvePoint (class in bpy.types), 791
ShapeKeyPoint (class in bpy.types), 792
SHD_TANGENT (in module bge.logic), 1168
shear (bpy.types.SoftBodySettings attribute), 806
shear (bpy.types.TextCurve attribute), 868
shear() (in module bpy.ops.transform), 117
Shear() (mathutils.Matrix class method), 1042
shift (bpy.types.KeyMapItem attribute), 464
shift_x (bpy.types.Camera attribute), 235
shift_y (bpy.types.Camera attribute), 235
shininess (bge.types.KX_PolygonMaterial attribute), 1118
show_active() (in module bpy.ops.outliner), 82
show_actuators (bpy.types.GameObjectSettings attribute), 417
show_actuators_active_object (bpy.types.SpaceLogicEditor attribute), 823
show_actuators_active_states (bpy.types.SpaceLogicEditor attribute), 823
show_actuators_linked_controller (bpy.types.SpaceLogicEditor attribute), 823
show_actuators_selected_objects (bpy.types.SpaceLogicEditor attribute), 823
show_alive (bpy.types.ExplodeModifier attribute), 374
show_alive (bpy.types.ParticleInstanceModifier attribute), 647
show_all_edges (bpy.types.Mesh attribute), 537
show_all_objects_origin (bpy.types.SpaceView3D attribute), 837
show_armatures (bpy.types.DopeSheet attribute), 349
show_axes (bpy.types.Armature attribute), 167
show_axis (bpy.types.Object attribute), 608
show_axis_x (bpy.types.SpaceView3D attribute), 837
show_axis_y (bpy.types.SpaceView3D attribute), 837
show_axis_z (bpy.types.SpaceView3D attribute), 837
show_backdrop (bpy.types.SpaceNodeEditor attribute), 826
show_background_images (bpy.types.SpaceView3D attribute), 837
show_bone_custom_shapes (bpy.types.Armature attribute), 167
show_bounds (bpy.types.Object attribute), 609
show_brush (bpy.types.Paint attribute), 634
show_brush_on_surface (bpy.types.Paint attribute), 634
show_cache (bpy.types.SpaceTimeline attribute), 832
show_cameras (bpy.types.DopeSheet attribute), 349
show_colored_constraints (bpy.types.ThemeBoneColorSet attribute), 898
show_column_layout (bpy.types.UserPreferencesView attribute), 989
show_cone (bpy.types.SpotLamp attribute), 849
show_controllers (bpy.types.GameObjectSettings attribute), 417
show_controllers_active_object (bpy.types.SpaceLogicEditor attribute), 823
show_controllers_linked_controller (bpy.types.SpaceLogicEditor attribute), 823
show_controllers_selected_objects (bpy.types.SpaceLogicEditor attribute), 823
show_cursor (bpy.types.SpaceGraphEditor attribute), 818
show_curves (bpy.types.DopeSheet attribute), 349
show_cyclic_dependencies() (in module bpy.ops.node), 66
show_dead (bpy.types.ExplodeModifier attribute), 374
show_dead (bpy.types.ParticleInstanceModifier attribute), 647
show_debug (bpy.types.GameProperty attribute), 420
show_debug_info (bpy.types.Driver attribute), 351

show_debug_properties (bpy.types.SceneGameData attribute), 742
show_debug_state (bpy.types.GameObjectSettings attribute), 417
show_double_sided (bpy.types.Mesh attribute), 537
show_edge_bevel_weight (bpy.types.Mesh attribute), 537
show_edge_crease (bpy.types.Mesh attribute), 537
show_edge_seams (bpy.types.Mesh attribute), 537
show_edge_sharp (bpy.types.Mesh attribute), 537
show_edges (bpy.types.Mesh attribute), 537
show_expanded (bpy.types.ActionGroup attribute), 148
show_expanded (bpy.types.Actuator attribute), 151
show_expanded (bpy.types.BackgroundImage attribute), 176
show_expanded (bpy.types.Constraint attribute), 318
show_expanded (bpy.types.Controller attribute), 325
show_expanded (bpy.types.FModifier attribute), 383
show_expanded (bpy.types.KeyMapItem attribute), 464
show_expanded (bpy.types.Modifier attribute), 570
show_expanded (bpy.types.Sensor attribute), 758
show_expanded_children (bpy.types.KeyMap attribute), 462
show_expanded_items (bpy.types.KeyMap attribute), 462
show_expanded_summary (bpy.types.DopeSheet attribute), 349
show_extra_edge_length (bpy.types.Mesh attribute), 538
show_extra_face_angle (bpy.types.Mesh attribute), 538
show_extra_face_area (bpy.types.Mesh attribute), 538
show_faces (bpy.types.Mesh attribute), 538
show_floor (bpy.types.SpaceView3D attribute), 837
show_frame_indicator (bpy.types.SpaceDopeSheetEditor attribute), 816
show_frame_indicator (bpy.types.SpaceGraphEditor attribute), 819
show_frame_indicator (bpy.types.SpaceNLA attribute), 824
show_frame_indicator (bpy.types.SpaceSequenceEditor attribute), 829
show_frame_indicator (bpy.types.SpaceTimeline attribute), 832
show_frame_numbers (bpy.types.AnimVizMotionPaths attribute), 159
show_framerate_profile (bpy.types.SceneGameData attribute), 742
show_frames (bpy.types.SpaceSequenceEditor attribute), 829
show_fullscreen (bpy.types.SceneGameData attribute), 742
show_group_colors (bpy.types.Armature attribute), 167
show_handles (bpy.types.Curve attribute), 333
show_handles (bpy.types.SpaceGraphEditor attribute), 819
show_health (bpy.types.ParticleSettings attribute), 658
show_hidden (bpy.types.DopeSheet attribute), 349
show_hidden (bpy.types.FileSelectParams attribute), 398
show_hidden_files_datablocks (bpy.types.UserPreferencesFilePaths attribute), 981
show_hierarchy() (in module bpy.ops.outliner), 82
show_high_resolution (bpy.types.SmokeDomainSettings attribute), 799
show_in_editmode (bpy.types.Modifier attribute), 570
show_keyframe_action_all (bpy.types.AnimVizMotionPaths attribute), 159
show_keyframe_highlight (bpy.types.AnimVizMotionPaths attribute), 159
show_keyframe_numbers (bpy.types.AnimVizMotionPaths attribute), 159
show_lamps (bpy.types.DopeSheet attribute), 349
show_large_cursors (bpy.types.UserPreferencesView attribute), 989
show_lattices (bpy.types.DopeSheet attribute), 349
show_limits (bpy.types.Camera attribute), 235
show_line_highlight (bpy.types.SpaceTextEditor attribute), 831
show_line_numbers (bpy.types.SpaceTextEditor attribute), 831
show_low_resolution (bpy.types.Paint attribute), 634
show_manipulator (bpy.types.SpaceView3D attribute), 838
show_manipulator (bpy.types.UserPreferencesView attribute), 989
show_margin (bpy.types.SpaceTextEditor attribute), 831
show_materials (bpy.types.DopeSheet attribute), 349
show_menus (bpy.types.Area attribute), 162
show_meshes (bpy.types.DopeSheet attribute), 349
show_metaballs (bpy.types.DopeSheet attribute), 350
show_mini_axis (bpy.types.UserPreferencesView attribute), 989
show_missing_nla (bpy.types.DopeSheet attribute), 350
show_mist (bpy.types.Camera attribute), 235
show_modified_edges (bpy.types.SpaceUVEditor attribute), 834
show_mouse (bpy.types.SceneGameData attribute), 742
show_name (bpy.types.Camera attribute), 235
show_name (bpy.types.Object attribute), 609
show_names (bpy.types.Armature attribute), 167
show_nodes (bpy.types.DopeSheet attribute), 350
show_normal_face (bpy.types.Curve attribute), 333
show_normal_face (bpy.types.Mesh attribute), 538
show_normal_vertex (bpy.types.Mesh attribute), 538
show_normalized_coords (bpy.types.SpaceUVEditor attribute), 834
show_number (bpy.types.ParticleSettings attribute), 658

show_object_info (bpy.types.UserPreferencesView attribute), 990
show_on_cage (bpy.types.Modifier attribute), 570
show_one_level() (in module bpy.ops.outliner), 82
show_only_control_edges (bpy.types.MultiresModifier attribute), 580
show_only_control_edges (bpy.types.SubsurfModifier attribute), 857
show_only_ghost_selected (bpy.types.Armature attribute), 167
show_only_group_objects (bpy.types.DopeSheet attribute), 350
show_only_render (bpy.types.SpaceView3D attribute), 838
show_only_selected (bpy.types.AnimVizOnionSkinning attribute), 160
show_only_selected (bpy.types.DopeSheet attribute), 350
show_only_selected (bpy.types.SpaceTimeline attribute), 833
show_only_shape_key (bpy.types.Object attribute), 609
show_other_objects (bpy.types.SpaceUVEditor attribute), 834
show_outline_selected (bpy.types.SpaceView3D attribute), 838
show_overlay (bpy.types.SequenceEditor attribute), 765
show_particles (bpy.types.DopeSheet attribute), 350
show_particles (bpy.types.ParticleEdit attribute), 644
show_passepartout (bpy.types.Camera attribute), 235
show_physics_visualization (bpy.types.SceneGameData attribute), 743
show_pivot (bpy.types.RigidBodyJointConstraint attribute), 731
show_playback_fps (bpy.types.UserPreferencesView attribute), 990
show_points (bpy.types.GPencilLayer attribute), 410
show_pose_markers (bpy.types.SpaceDopeSheetEditor attribute), 816
show_relationship_lines (bpy.types.SpaceView3D attribute), 838
show_render (bpy.types.Modifier attribute), 570
show_repeat (bpy.types.SpaceImageEditor attribute), 821
show_report_debug (bpy.types.SpaceInfo attribute), 822
show_report_error (bpy.types.SpaceInfo attribute), 822
show_report_info (bpy.types.SpaceInfo attribute), 822
show_report_operator (bpy.types.SpaceInfo attribute), 822
show_report_warning (bpy.types.SpaceInfo attribute), 822
show_restrict_columns (bpy.types.SpaceOutliner attribute), 827
show_safe_margin (bpy.types.SpaceSequenceEditor attribute), 829
show_scenes (bpy.types.DopeSheet attribute), 350
show_sensors (bpy.types.GameObjectSettings attribute), 417
show_sensors_active_object (bpy.types.SpaceLogicEditor attribute), 823
show_sensors_active_states (bpy.types.SpaceLogicEditor attribute), 823
show_sensors_linked_controller (bpy.types.SpaceLogicEditor attribute), 823
show_sensors_selected_objects (bpy.types.SpaceLogicEditor attribute), 823
show_separate_color (bpy.types.SpaceSequenceEditor attribute), 829
show_shaded (bpy.types.ThemeWidgetColors attribute), 933
show_shapekeys (bpy.types.DopeSheet attribute), 350
show_size (bpy.types.ParticleSettings attribute), 658
show_sliders (bpy.types.SpaceDopeSheetEditor attribute), 816
show_sliders (bpy.types.SpaceGraphEditor attribute), 819
show_smooth_edges (bpy.types.SpaceUVEditor attribute), 834
show_splash (bpy.types.UserPreferencesView attribute), 990
show_state_panel (bpy.types.GameObjectSettings attribute), 417
show_stretch (bpy.types.SpaceUVEditor attribute), 834
show_strip_curves (bpy.types.SpaceNLA attribute), 824
show_summary (bpy.types.DopeSheet attribute), 350
show_sync_view (bpy.types.RegionView3D attribute), 710
show_syntax_highlight (bpy.types.SpaceTextEditor attribute), 831
show_texture_space (bpy.types.Object attribute), 609
show_textured_solid (bpy.types.SpaceView3D attribute), 838
show_textures (bpy.types.DopeSheet attribute), 350
show_thumbnails (bpy.types.UserPreferencesFilePaths attribute), 982
show_title_safe (bpy.types.Camera attribute), 236
show_tooltips (bpy.types.UserPreferencesView attribute), 990
show_tooltips_python (bpy.types.UserPreferencesView attribute), 990
show_tracer (bpy.types.ParticleFluidSettings attribute), 645
show_transforms (bpy.types.DopeSheet attribute), 350
show_transparent (bpy.types.Object attribute), 609
show_unborn (bpy.types.ExplodeModifier attribute), 374
show_unborn (bpy.types.ParticleInstanceModifier attribute), 648
show_unborn (bpy.types.ParticleSettings attribute), 658
show_uv_local_view (bpy.types.ToolSettings attribute), 939
show_velocity (bpy.types.ParticleSettings attribute), 658

show_view_name (bpy.types.UserPreferencesView attribute), 990
show_viewport (bpy.types.Modifier attribute), 570
show_wire (bpy.types.Bone attribute), 220
show_wire (bpy.types.EditBone attribute), 358
show_wire (bpy.types.Object attribute), 609
show_word_wrap (bpy.types.SpaceTextEditor attribute), 831
show_worlds (bpy.types.DopeSheet attribute), 350
show_x_ray (bpy.types.Object attribute), 609
showMouse() (in module bge.render), 1170
shrink_fatten() (in module bpy.ops.transform), 117
shrinkwrap_type (bpy.types.ShrinkwrapConstraint attribute), 793
ShrinkwrapConstraint (class in bpy.types), 793
ShrinkwrapModifier (class in bpy.types), 794
sigma_color (bpy.types.CompositorNodeBilateralblur attribute), 261
sigma_space (bpy.types.CompositorNodeBilateralblur attribute), 261
SimpleDeformModifier (class in bpy.types), 796
simplify_ao_sss (bpy.types.RenderSettings attribute), 725
simplify_child_particles (bpy.types.RenderSettings attribute), 725
simplify_rate (bpy.types.ParticleSettings attribute), 658
simplify_refsize (bpy.types.ParticleSettings attribute), 658
simplify_shadow_samples (bpy.types.RenderSettings attribute), 725
simplify_subdivision (bpy.types.RenderSettings attribute), 725
simplify_transition (bpy.types.ParticleSettings attribute), 658
simplify_viewport (bpy.types.ParticleSettings attribute), 658
simulation_scale (bpy.types.DomainFluidSettings attribute), 347
single_axis_number (bpy.types.JoystickSensor attribute), 457
SIXKEY (in module bge.events), 1174
size (bpy.types.AreaLamp attribute), 164
size (bpy.types.BackgroundImage attribute), 176
size (bpy.types.Brush attribute), 228
size (bpy.types.CastModifier attribute), 238
size (bpy.types.CompositorNodeGlare attribute), 284
size (bpy.types.CompositorNodeMapValue attribute), 293
size (bpy.types.FieldSettings attribute), 395
size (bpy.types.MaterialHalo attribute), 516
size (bpy.types.Particle attribute), 640
size (bpy.types.ParticleBrush attribute), 641
size (bpy.types.TextCurve attribute), 868
size (bpy.types.WorldStarsSettings attribute), 1020
size() (in module blf), 1073
size_factor (bpy.types.ParticleSettingsTextureSlot attribute), 663
size_min (bpy.types.MaterialStrand attribute), 523
size_random (bpy.types.ParticleSettings attribute), 659
size_x (bpy.types.CompositorNodeBlur attribute), 262
size_x (bpy.types.MetaElement attribute), 564
size_y (bpy.types.AreaLamp attribute), 164
size_y (bpy.types.CompositorNodeBlur attribute), 262
size_y (bpy.types.MetaElement attribute), 564
size_z (bpy.types.MetaElement attribute), 564
SKEY (in module bge.events), 1174
sky_blend (bpy.types.LampSkySettings attribute), 486
sky_blend_type (bpy.types.LampSkySettings attribute), 486
sky_color_space (bpy.types.LampSkySettings attribute), 487
sky_exposure (bpy.types.LampSkySettings attribute), 487
SLASHKEY (in module bge.events), 1176
slider_max (bpy.types.ShapeKey attribute), 790
slider_min (bpy.types.ShapeKey attribute), 790
slip_type (bpy.types.DomainFluidSettings attribute), 347
slip_type (bpy.types.ObstacleFluidSettings attribute), 620
slope (bpy.types.CompositorNodeColorBalance attribute), 266
slot_copy() (in module bpy.ops.texture), 112
slot_move() (in module bpy.ops.texture), 113
slot_paste() (in module bpy.ops.texture), 113
slow_parent_clear() (in module bpy.ops.object), 79
slow_parent_set() (in module bpy.ops.object), 79
slurph (bpy.types.Key attribute), 458
small_caps_scale (bpy.types.TextCurve attribute), 868
smart_project() (in module bpy.ops.uv), 126
smoke (in module bpy.context), 6
smoke_data_type (bpy.types.VoxelData attribute), 1004
smoke_type (bpy.types.SmokeModifier attribute), 801
SmokeCollSettings (class in bpy.types), 797
SmokeDomainSettings (class in bpy.types), 798
SmokeDomainSettings.effector_weights (in module bpy.types), 798
SmokeDomainSettings.point_cache (in module bpy.types), 798
SmokeFlowSettings (class in bpy.types), 800
SmokeModifier (class in bpy.types), 801
SmokeModifier.coll_settings (in module bpy.types), 801
SmokeModifier.domain_settings (in module bpy.types), 801
SmokeModifier.flow_settings (in module bpy.types), 801
smooth() (in module bpy.ops.curve), 24
smooth() (in module bpy.ops.graph), 37
smooth_emitter (bpy.types.SmokeDomainSettings attribute), 799
smooth_radius() (in module bpy.ops.curve), 24
smooth_stroke_factor (bpy.types.Brush attribute), 228
smooth_stroke_radius (bpy.types.Brush attribute), 228

smooth_view (bpy.types.UserPreferencesView attribute), 990
SmoothModifier (class in bpy.types), 802
smoothscroll() (in module bpy.ops.file), 31
smoothview() (in module bpy.ops.view3d), 131
smpte_from_frame() (in module bpy.utils), 1030
smpte_from_seconds() (in module bpy.utils), 1030
snap() (in module bpy.ops.action), 10
snap() (in module bpy.ops.graph), 37
snap() (in module bpy.ops.nla), 62
snap() (in module bpy.ops.sequencer), 103
snap_cursor() (in module bpy.ops.uv), 126
snap_cursor_to_active() (in module bpy.ops.view3d), 131
snap_cursor_to_center() (in module bpy.ops.view3d), 131
snap_cursor_to_grid() (in module bpy.ops.view3d), 131
snap_cursor_to_selected() (in module bpy.ops.view3d), 131
snap_element (bpy.types.ToolSettings attribute), 939
snap_selected_to_cursor() (in module bpy.ops.view3d), 131
snap_selected_to_grid() (in module bpy.ops.view3d), 131
snap_selection() (in module bpy.ops.uv), 126
snap_target (bpy.types.ToolSettings attribute), 939
snap_type() (in module bpy.ops.transform), 118
soft_body (in module bpy.context), 6
SoftBodyModifier (class in bpy.types), 803
SoftBodyModifier.point_cache (in module bpy.types), 803
SoftBodyModifier.settings (in module bpy.types), 803
SoftBodySettings (class in bpy.types), 804
SoftBodySettings.effector_weights (in module bpy.types), 805
solidify() (in module bpy.ops.mesh), 59
SolidifyModifier (class in bpy.types), 808
solver (bpy.types.Itasc attribute), 455
sort_faces() (in module bpy.ops.mesh), 59
sort_method (bpy.types.FileSelectParams attribute), 398
sound (bpy.types.SoundActuator attribute), 811
Sound (class in bpy.types), 809
Sound.packed_file (in module bpy.types), 810
sound_bake() (in module bpy.ops.graph), 37
sound_directory (bpy.types.UserPreferencesFilePaths attribute), 982
sound_strip_add() (in module bpy.ops.sequencer), 103
SoundActuator (class in bpy.types), 811
SoundSequence (class in bpy.types), 812
SoundSequence.sound (in module bpy.types), 813
source (bpy.types.EnvironmentMap attribute), 369
source (bpy.types.Image attribute), 440
space (bpy.types.CompositorNodeScale attribute), 301
Space (class in bpy.types), 814
Space.type (in module bpy.types), 814
space_character (bpy.types.TextCurve attribute), 868
space_line (bpy.types.TextCurve attribute), 868
space_word (bpy.types.TextCurve attribute), 868
SpaceConsole (class in bpy.types), 815
SpaceConsole.history (in module bpy.types), 815
SpaceConsole.scrollback (in module bpy.types), 815
spacedata_cleanup() (in module bpy.ops.screen), 97
SpaceDopeSheetEditor (class in bpy.types), 816
SpaceDopeSheetEditor.dopesheet (in module bpy.types), 816
SpaceDopeSheetEditor.show_seconds (in module bpy.types), 816
SpaceFileBrowser (class in bpy.types), 817
SpaceFileBrowser.operator (in module bpy.types), 817
SpaceFileBrowser.params (in module bpy.types), 817
SpaceGraphEditor (class in bpy.types), 818
SpaceGraphEditor.dopesheet (in module bpy.types), 818
SpaceGraphEditor.show_seconds (in module bpy.types), 819
SpaceImageEditor (class in bpy.types), 820
SpaceImageEditor.curves (in module bpy.types), 820
SpaceImageEditor.image_user (in module bpy.types), 820
SpaceImageEditor.sample_histogram (in module bpy.types), 820
SpaceImageEditor.scopes (in module bpy.types), 820
SpaceImageEditor.show_paint (in module bpy.types), 820
SpaceImageEditor.show_render (in module bpy.types), 820
SpaceImageEditor.show_uvedit (in module bpy.types), 821
SpaceImageEditor.uv_editor (in module bpy.types), 821
SpaceInfo (class in bpy.types), 822
SPACEKEY (in module bge.events), 1176
SpaceLogicEditor (class in bpy.types), 823
SpaceNLA (class in bpy.types), 824
SpaceNLA.dopesheet (in module bpy.types), 824
SpaceNLA.show_seconds (in module bpy.types), 824
SpaceNodeEditor (class in bpy.types), 825
SpaceNodeEditor.id (in module bpy.types), 825
SpaceNodeEditor.id_from (in module bpy.types), 825
SpaceNodeEditor.node_tree (in module bpy.types), 826
SpaceOutliner (class in bpy.types), 826
SpaceProperties (class in bpy.types), 828
SpaceSequenceEditor (class in bpy.types), 829
SpaceSequenceEditor.grease_pencil (in module bpy.types), 829
SpaceTextEditor (class in bpy.types), 830
SpaceTimeline (class in bpy.types), 832
SpaceUserPreferences (class in bpy.types), 835
SpaceUVEditor (class in bpy.types), 833
SpaceView3D (class in bpy.types), 836
SpaceView3D.background_images (in module bpy.types), 836
SpaceView3D.current_orientation (in module bpy.types), 836
SpaceView3D.layers_used (in module bpy.types), 836

SpaceView3D.local_view (in module bpy.types), 837
SpaceView3D.region_3d (in module bpy.types), 837
SpaceView3D.region_quadview (in module bpy.types), 837
spacing (bpy.types.Brush attribute), 228
specular (bge.types.KX_PolygonMaterial attribute), 1118
specular_alpha (bpy.types.Material attribute), 511
specular_color (bpy.types.Material attribute), 511
specular_color (bpy.types.UserSolidLight attribute), 992
specular_color_factor (bpy.types.MaterialTextureSlot attribute), 527
specular_factor (bpy.types.MaterialTextureSlot attribute), 527
specular_hardness (bpy.types.Material attribute), 511
specular_intensity (bpy.types.Material attribute), 511
specular_ior (bpy.types.Material attribute), 511
specular_ramp_blend (bpy.types.Material attribute), 511
specular_ramp_factor (bpy.types.Material attribute), 512
specular_ramp_input (bpy.types.Material attribute), 512
specular_shader (bpy.types.Material attribute), 512
specular_slope (bpy.types.Material attribute), 512
specular_toon_size (bpy.types.Material attribute), 512
specular_toon_smooth (bpy.types.Material attribute), 512
specularity (bge.types.KX_PolygonMaterial attribute), 1118
speed (bpy.types.BoidRuleAverageSpeed attribute), 210
speed (bpy.types.SoftBodySettings attribute), 806
speed (bpy.types.WaveModifier attribute), 1006
speed_factor (bpy.types.Sequence attribute), 761
speed_max (bpy.types.CompositorNodeVecBlur attribute), 312
speed_min (bpy.types.CompositorNodeVecBlur attribute), 313
speed_of_sound (aud.Device attribute), 1075
speed_scale (bpy.types.PointDensity attribute), 681
SpeedControlSequence (class in bpy.types), 839
sphere_project() (in module bpy.ops.uv), 126
sphereInsideFrustum() (bge.types.KX_Camera method), 1141
SPHFluidSettings (class in bpy.types), 733
spin (bpy.types.CompositorNodeDBlur attribute), 276
spin() (in module bpy.ops.curve), 24
spin() (in module bpy.ops.mesh), 59
splash() (in module bpy.ops.wm), 142
Spline (class in bpy.types), 841
Spline.bezier_points (in module bpy.types), 841
Spline.character_index (in module bpy.types), 841
Spline.point_count_u (in module bpy.types), 841
Spline.point_count_v (in module bpy.types), 841
Spline.points (in module bpy.types), 842
spline_type_set() (in module bpy.ops.curve), 24
spline_weight_set() (in module bpy.ops.curve), 24
SplineBezierPoints (class in bpy.types), 843
SplineIKConstraint (class in bpy.types), 844
SplinePoint (class in bpy.types), 845
SplinePoints (class in bpy.types), 847
split() (bpy.types.UILayout method), 950
split() (in module bpy.ops.mesh), 59
split() (in module bpy.ops.nla), 62
split_angle (bpy.types.EdgeSplitModifier attribute), 356
spot_blend (bpy.types.SpotLamp attribute), 849
spot_size (bpy.types.SpotLamp attribute), 849
spotblend (bge.types.KX_LightObject attribute), 1106
SpotLamp (class in bpy.types), 847
SpotLamp.falloff_curve (in module bpy.types), 847
spotsize (bge.types.KX_LightObject attribute), 1106
spread (bpy.types.LampSkySettings attribute), 487
spring_damping (bpy.types.ClothSettings attribute), 247
spring_force (bpy.types.SPHFluidSettings attribute), 733
spring_frames (bpy.types.SPHFluidSettings attribute), 734
spring_length (bpy.types.SoftBodySettings attribute), 806
squash (bpy.types.TextureNodeBricks attribute), 875
squash_frequency (bpy.types.TextureNodeBricks attribute), 875
sss_preset_add() (in module bpy.ops.material), 48
stamp_background (bpy.types.RenderSettings attribute), 725
stamp_font_size (bpy.types.RenderSettings attribute), 725
stamp_foreground (bpy.types.RenderSettings attribute), 725
stamp_note_text (bpy.types.RenderSettings attribute), 725
standard_derivation (bpy.types.RandomActuator attribute), 705
star_tip_count (bpy.types.MaterialHalo attribute), 516
start (bpy.types.WorldMistSettings attribute), 1019
start_cap (bpy.types.ArrayModifier attribute), 174
start_frame_set() (in module bpy.ops.time), 113
start_position_object (bpy.types.WaveModifier attribute), 1006
start_position_x (bpy.types.WaveModifier attribute), 1006
start_position_y (bpy.types.WaveModifier attribute), 1006
start_time (bpy.types.ControlFluidSettings attribute), 324
start_time (bpy.types.DomainFluidSettings attribute), 347
startGame() (in module bge.logic), 1157
state (bge.types.KX_GameObject attribute), 1096
state (bge.types.SCA_IController attribute), 1085
state_add() (in module bpy.ops.boid), 17
state_del() (in module bpy.ops.boid), 17
state_move_down() (in module bpy.ops.boid), 17
state_move_up() (in module bpy.ops.boid), 17
StateActuator (class in bpy.types), 851
states (bpy.types.Controller attribute), 326
states (bpy.types.StateActuator attribute), 851

states_initial (bpy.types.GameObjectSettings attribute), 418
states_visible (bpy.types.GameObjectSettings attribute), 418
statistics() (bpy.types.Scene method), 738
status (aud.Handle attribute), 1081
status (bge.types.SCA_ISensor attribute), 1085
step_count (bpy.types.Itasc attribute), 455
step_max (bpy.types.Itasc attribute), 455
step_max (bpy.types.SoftBodySettings attribute), 806
step_method (bpy.types.MaterialVolume attribute), 533
step_min (bpy.types.Itasc attribute), 455
step_min (bpy.types.SoftBodySettings attribute), 806
step_size (bpy.types.MaterialVolume attribute), 533
steps (bpy.types.ParticleBrush attribute), 641
steps (bpy.types.ScrewModifier attribute), 755
stereo (bpy.types.SceneGameData attribute), 743
stereo_eye_separation (bpy.types.SceneGameData attribute), 743
stereo_mode (bpy.types.SceneGameData attribute), 743
stickness (bpy.types.CollisionSettings attribute), 253
sticky_add() (in module bpy.ops.mesh), 59
sticky_remove() (in module bpy.ops.mesh), 59
sticky_select_mode (bpy.types.SpaceUVEditor attribute), 834
stiff_viscosity (bpy.types.SPHFluidSettings attribute), 734
stiffness (bpy.types.MetaElement attribute), 565
stiffness (bpy.types.SPHFluidSettings attribute), 734
still_frame (bpy.types.VoxelData attribute), 1004
stitch() (in module bpy.ops.uv), 126
stl() (in module bpy.ops.export_mesh), 26
stl() (in module bpy.ops.import_mesh), 43
stopDSP() (in module bge.logic), 1158
streaks (bpy.types.CompositorNodeGlare attribute), 284
strength (bpy.types.BoidSettings attribute), 217
strength (bpy.types.Brush attribute), 228
strength (bpy.types.DisplaceModifier attribute), 344
strength (bpy.types.FieldSettings attribute), 395
strength (bpy.types.FModifierNoise attribute), 391
strength (bpy.types.ParticleBrush attribute), 641
strength (bpy.types.SmokeDomainSettings attribute), 799
stretchto_reset() (in module bpy.ops.constraint), 21
StretchToConstraint (class in bpy.types), 852
string (bpy.types.PropertyGroupItem attribute), 698
StringProperty (class in bpy.types), 853
StringProperty() (in module bpy.props), 1037
StringProperty.default (in module bpy.types), 853
StringProperty.length_max (in module bpy.types), 853
strip_time (bpy.types.NlaStrip attribute), 591
strips (bpy.types.ThemeNLAEditor attribute), 914
strips_selected (bpy.types.ThemeNLAEditor attribute), 914
strobe (bpy.types.EffectSequence attribute), 363
strobe (bpy.types.ImageSequence attribute), 444
strobe (bpy.types.MetaSequence attribute), 566
strobe (bpy.types.MovieSequence attribute), 575
strobe (bpy.types.MulticamSequence attribute), 577
strobe (bpy.types.SceneSequence attribute), 750
stroke_method (bpy.types.Brush attribute), 228
Struct (class in bpy.types), 854
Struct.base (in module bpy.types), 854
Struct.description (in module bpy.types), 854
Struct.functions (in module bpy.types), 854
Struct.identifier (in module bpy.types), 854
Struct.name (in module bpy.types), 854
Struct.name_property (in module bpy.types), 854
Struct.nested (in module bpy.types), 855
Struct.properties (in module bpy.types), 855
structural_stiffness (bpy.types.ClothSettings attribute), 247
structural_stiffness_max (bpy.types.ClothSettings attribute), 247
stucci_type (bpy.types.StucciTexture attribute), 856
StucciTexture (class in bpy.types), 855
StucciTexture.users_material (in module bpy.types), 856
StucciTexture.users_object_modifier (in module bpy.types), 856
style_set() (in module bpy.ops.font), 33
style_toggle() (in module bpy.ops.font), 33
subdivide() (in module bpy.ops.armature), 17
subdivide() (in module bpy.ops.curve), 24
subdivide() (in module bpy.ops.mesh), 59
subdivide() (in module bpy.ops.particle), 87
subdivision_set() (in module bpy.ops.object), 79
subdivision_type (bpy.types.MultiresModifier attribute), 580
subdivision_type (bpy.types.SubsurfModifier attribute), 857
subframes (bpy.types.ParticleSettings attribute), 659
subject (bge.types.KX_NetworkMessageActuator attribute), 1110
subject (bge.types.KX_NetworkMessageSensor attribute), 1110
subject (bpy.types.MessageActuator attribute), 560
subject (bpy.types.MessageSensor attribute), 561
subjects (bge.types.KX_NetworkMessageSensor attribute), 1110
subsurf_levels (bpy.types.ShrinkwrapModifier attribute), 794
SubsurfModifier (class in bpy.types), 857
subtarget (bge.types.BL_ArmatureActuator attribute), 1145
subtarget (bge.types.BL_ArmatureConstraint attribute), 1148
subtarget (bpy.types.ActionConstraint attribute), 145
subtarget (bpy.types.ChildOfConstraint attribute), 240
subtarget (bpy.types.ConstraintTarget attribute), 322

subtarget (bpy.types.CopyLocationConstraint attribute), 327
subtarget (bpy.types.CopyRotationConstraint attribute), 329
subtarget (bpy.types.CopyScaleConstraint attribute), 330
subtarget (bpy.types.CopyTransformsConstraint attribute), 331
subtarget (bpy.types.DampedTrackConstraint attribute), 341
subtarget (bpy.types.FloorConstraint attribute), 402
subtarget (bpy.types.HookModifier attribute), 434
subtarget (bpy.types.KinematicConstraint attribute), 483
subtarget (bpy.types.LimitDistanceConstraint attribute), 495
subtarget (bpy.types.LockedTrackConstraint attribute), 501
subtarget (bpy.types.PivotConstraint attribute), 673
subtarget (bpy.types.StretchToConstraint attribute), 852
subtarget (bpy.types.TrackToConstraint attribute), 942
subtarget (bpy.types.TransformConstraint attribute), 944
sun_brightness (bpy.types.LampSkySettings attribute), 487
sun_intensity (bpy.types.LampSkySettings attribute), 487
sun_size (bpy.types.LampSkySettings attribute), 487
SunLamp (class in bpy.types), 858
SunLamp.sky (in module bpy.types), 859
sunsky_preset_add() (in module bpy.ops.lamp), 45
surface_smooth (bpy.types.DomainFluidSettings attribute), 347
surface_subdivisions (bpy.types.DomainFluidSettings attribute), 348
SurfaceCurve (class in bpy.types), 860
SurfaceModifier (class in bpy.types), 861
suspend() (bge.types.KX_Scene method), 1125
suspendDynamics() (bge.types.KX_GameObject method), 1100
suspended (bge.types.KX_Scene attribute), 1124
swap() (bpy.types.Sequence method), 761
swap() (in module bpy.ops.nla), 62
swap() (in module bpy.ops.sequencer), 104
swap_data() (in module bpy.ops.sequencer), 104
swap_inputs() (in module bpy.ops.sequencer), 104
switch_direction() (in module bpy.ops.armature), 17
switch_direction() (in module bpy.ops.curve), 25
sync_mode (bpy.types.Scene attribute), 737
syntax_builtin (bpy.types.ThemeTextEditor attribute), 923
syntax_comment (bpy.types.ThemeTextEditor attribute), 924
syntax_numbers (bpy.types.ThemeTextEditor attribute), 924
syntax_special (bpy.types.ThemeTextEditor attribute), 924
syntax_string (bpy.types.ThemeTextEditor attribute), 924
sysinfo() (in module bpy.ops.wm), 142
system (bpy.types.ParticleTarget attribute), 672
system (bpy.types.UnitSettings attribute), 974
system_rotation (bpy.types.UnitSettings attribute), 975

T

tab_width (bpy.types.SpaceTextEditor attribute), 831
TABKEY (in module bge.events), 1176
tag (bpy.types.ID attribute), 435
tag() (bpy.types.BlendDataActions method), 182
tag() (bpy.types.BlendDataArmatures method), 183
tag() (bpy.types.BlendDataBrushes method), 184
tag() (bpy.types.BlendDataCameras method), 185
tag() (bpy.types.BlendDataCurves method), 186
tag() (bpy.types.BlendDataFonts method), 187
tag() (bpy.types.BlendDataGreasePencils method), 188
tag() (bpy.types.BlendDataGroups method), 189
tag() (bpy.types.BlendDataImages method), 190
tag() (bpy.types.BlendDataLamps method), 191
tag() (bpy.types.BlendDataLattices method), 192
tag() (bpy.types.BlendDataLibraries method), 193
tag() (bpy.types.BlendDataMaterials method), 195
tag() (bpy.types.BlendDataMeshes method), 196
tag() (bpy.types.BlendDataMetaBalls method), 197
tag() (bpy.types.BlendDataNodeTrees method), 198
tag() (bpy.types.BlendDataObjects method), 199
tag() (bpy.types.BlendDataParticles method), 200
tag() (bpy.types.BlendDataScreens method), 201
tag() (bpy.types.BlendDataSounds method), 202
tag() (bpy.types.BlendDataTexts method), 203
tag() (bpy.types.BlendDataTextures method), 204
tag() (bpy.types.BlendDataWindowManagers method), 205
tag() (bpy.types.BlendDataWorlds method), 206
tag_redraw() (bpy.types.Area method), 163
tag_redraw() (bpy.types.Region method), 709
tail (bge.types.BL_ArmatureBone attribute), 1154
tail (bpy.types.Bone attribute), 220
tail (bpy.types.EditBone attribute), 358
tail_local (bpy.types.Bone attribute), 220
tail_radius (bpy.types.Bone attribute), 221
tail_radius (bpy.types.EditBone attribute), 358
tangent_factor (bpy.types.ParticleSettings attribute), 659
tangent_phase (bpy.types.ParticleSettings attribute), 659
tap (bge.types.SCA_ISensor attribute), 1084
taper_object (bpy.types.Curve attribute), 333
target (bge.types.BL_ArmatureActuator attribute), 1145
target (bge.types.BL_ArmatureConstraint attribute), 1148
target (bpy.types.ActionConstraint attribute), 145
target (bpy.types.ArmatureActuator attribute), 169
target (bpy.types.ChildOfConstraint attribute), 240
target (bpy.types.ClampToConstraint attribute), 242
target (bpy.types.ConstraintTarget attribute), 322
target (bpy.types.CopyLocationConstraint attribute), 327

target (bpy.types.CopyRotationConstraint attribute), 329
target (bpy.types.CopyScaleConstraint attribute), 330
target (bpy.types.CopyTransformsConstraint attribute), 331
target (bpy.types.DampedTrackConstraint attribute), 341
target (bpy.types.FloorConstraint attribute), 402
target (bpy.types.FollowPathConstraint attribute), 406
target (bpy.types.KeyboardSensor attribute), 472
target (bpy.types.KinematicConstraint attribute), 483
target (bpy.types.LimitDistanceConstraint attribute), 495
target (bpy.types.LockedTrackConstraint attribute), 501
target (bpy.types.PivotConstraint attribute), 673
target (bpy.types.RigidBodyJointConstraint attribute), 731
target (bpy.types.ShrinkwrapConstraint attribute), 793
target (bpy.types.ShrinkwrapModifier attribute), 794
target (bpy.types.SplineIKConstraint attribute), 844
target (bpy.types.StretchToConstraint attribute), 852
target (bpy.types.TrackToConstraint attribute), 942
target (bpy.types.TransformConstraint attribute), 944
target_count (bpy.types.PythonConstraint attribute), 700
target_move_down() (in module bpy.ops.particle), 87
target_move_up() (in module bpy.ops.particle), 87
target_remove() (in module bpy.ops.particle), 87
target_space (bpy.types.Constraint attribute), 318
targetProperty (bge.types.SCA_KeyboardSensor attribute), 1136
tempdir (in module bpy.app), 1031
temperature (bpy.types.SmokeFlowSettings attribute), 800
template_any_ID() (bpy.types.UILayout method), 968
template_color_ramp() (bpy.types.UILayout method), 969
template_color_wheel() (bpy.types.UILayout method), 969
template_constraint() (bpy.types.UILayout method), 968
template_curve_mapping() (bpy.types.UILayout method), 968
template_header() (bpy.types.UILayout method), 967
template_header_3D() (bpy.types.UILayout method), 970
template_histogram() (bpy.types.UILayout method), 969
template_ID() (bpy.types.UILayout method), 967
template_ID_preview() (bpy.types.UILayout method), 967
template_image() (bpy.types.UILayout method), 970
template_image_layers() (bpy.types.UILayout method), 970
template_layers() (bpy.types.UILayout method), 969
template_list() (bpy.types.UILayout method), 970
template_modifier() (bpy.types.UILayout method), 968
template_operator_search() (bpy.types.UILayout method), 970
template_path_builder() (bpy.types.UILayout method), 968
template_preview() (bpy.types.UILayout method), 968
template_reports_banner() (bpy.types.UILayout method), 970
template_running_jobs() (bpy.types.UILayout method), 970
template_vectorscope() (bpy.types.UILayout method), 969
template_waveform() (bpy.types.UILayout method), 969
temporary_directory (bpy.types.UserPreferencesFilePaths attribute), 982
tesselate_polygon() (in module mathutils.geometry), 1071
test_break() (bpy.types.RenderEngine method), 713
test_type (bpy.types.ArmatureSensor attribute), 173
texco_mesh (bpy.types.Mesh attribute), 538
TexMapping (class in bpy.types), 862
texspace_location (bpy.types.Curve attribute), 333
texspace_location (bpy.types.Mesh attribute), 538
texspace_location (bpy.types.MetaBall attribute), 562
texspace_size (bpy.types.Curve attribute), 334
texspace_size (bpy.types.Mesh attribute), 538
texspace_size (bpy.types.MetaBall attribute), 562
text (bpy.types.Panel attribute), 637
text (bpy.types.PythonConstraint attribute), 701
text (bpy.types.PythonController attribute), 702
text (bpy.types.SpaceTextEditor attribute), 831
text (bpy.types.ThemeAudioWindow attribute), 897
text (bpy.types.ThemeConsole attribute), 900
text (bpy.types.ThemeDopeSheet attribute), 902
text (bpy.types.ThemeFileBrowser attribute), 904
text (bpy.types.ThemeGraphEditor attribute), 908
text (bpy.types.ThemeImageEditor attribute), 910
text (bpy.types.ThemeInfo attribute), 911
text (bpy.types.ThemeLogicEditor attribute), 912
text (bpy.types.ThemeNLAEditor attribute), 914
text (bpy.types.ThemeNodeEditor attribute), 916
text (bpy.types.ThemeOutliner attribute), 918
text (bpy.types.ThemeProperties attribute), 919
text (bpy.types.ThemeSequenceEditor attribute), 921
text (bpy.types.ThemeTextEditor attribute), 924
text (bpy.types.ThemeTimeline attribute), 925
text (bpy.types.ThemeUserPreferences attribute), 928
text (bpy.types.ThemeView3D attribute), 932
text (bpy.types.ThemeWidgetColors attribute), 933
Text (class in bpy.types), 863
Text.current_character (in module bpy.types), 863
Text.current_line (in module bpy.types), 863
Text.is_dirty (in module bpy.types), 863
Text.is_in_memory (in module bpy.types), 863
Text.is_modified (in module bpy.types), 864
Text.lines (in module bpy.types), 864
Text.markers (in module bpy.types), 864
Text.select_end_character (in module bpy.types), 864
Text.select_end_line (in module bpy.types), 864

Text.users_logic (in module bpy.types), 864
text_add() (in module bpy.ops.object), 79
text_copy() (in module bpy.ops.font), 33
text_cut() (in module bpy.ops.font), 33
text_hi (bpy.types.ThemeAudioWindow attribute), 897
text_hi (bpy.types.ThemeConsole attribute), 900
text_hi (bpy.types.ThemeDopeSheet attribute), 902
text_hi (bpy.types.ThemeFileBrowser attribute), 904
text_hi (bpy.types.ThemeGraphEditor attribute), 908
text_hi (bpy.types.ThemeImageEditor attribute), 910
text_hi (bpy.types.ThemeInfo attribute), 911
text_hi (bpy.types.ThemeLogicEditor attribute), 912
text_hi (bpy.types.ThemeNLAEditor attribute), 914
text_hi (bpy.types.ThemeNodeEditor attribute), 916
text_hi (bpy.types.ThemeOutliner attribute), 918
text_hi (bpy.types.ThemeProperties attribute), 919
text_hi (bpy.types.ThemeSequenceEditor attribute), 921
text_hi (bpy.types.ThemeTextEditor attribute), 924
text_hi (bpy.types.ThemeTimeline attribute), 925
text_hi (bpy.types.ThemeUserPreferences attribute), 928
text_hi (bpy.types.ThemeView3D attribute), 932
text_insert() (in module bpy.ops.font), 33
text_paste() (in module bpy.ops.font), 33
text_sel (bpy.types.ThemeWidgetColors attribute), 933
TextBox (class in bpy.types), 865
textbox_add() (in module bpy.ops.font), 33
textbox_remove() (in module bpy.ops.font), 33
TextCharacterFormat (class in bpy.types), 866
TextCurve (class in bpy.types), 867
TextCurve.body_format (in module bpy.types), 867
TextCurve.edit_format (in module bpy.types), 867
TextCurve.text_boxes (in module bpy.types), 868
TextLine (class in bpy.types), 870
TextMarker (class in bpy.types), 871
TextMarker.character_index_end (in module bpy.types), 871
TextMarker.character_index_start (in module bpy.types), 871
TextMarker.group (in module bpy.types), 871
TextMarker.is_temporary (in module bpy.types), 871
TextMarker.line (in module bpy.types), 871
TextMarker.use_edit_all (in module bpy.types), 871
texture (bge.types.KX_PolygonMaterial attribute), 1117
texture (bge.types.KX_PolyProxy attribute), 1113
texture (bpy.types.Brush attribute), 229
texture (bpy.types.CompositorNodeTexture attribute), 306
texture (bpy.types.DisplaceModifier attribute), 344
texture (bpy.types.EffectorWeights attribute), 366
texture (bpy.types.FieldSettings attribute), 395
texture (bpy.types.ShaderNodeTexture attribute), 782
texture (bpy.types.TextureNodeTexture attribute), 888
texture (bpy.types.TextureSlot attribute), 894
texture (bpy.types.WaveModifier attribute), 1006
Texture (class in bpy.types), 872
texture (in module bpy.context), 6
Texture.animation_data (in module bpy.types), 872
Texture.color_ramp (in module bpy.types), 872
Texture.node_tree (in module bpy.types), 873
Texture.users_material (in module bpy.types), 873
Texture.users_object_modifier (in module bpy.types), 873
texture_angle_source_no_random (bpy.types.Brush attribute), 229
texture_angle_source_random (bpy.types.Brush attribute), 229
texture_collection_rate (bpy.types.UserPreferencesSystem attribute), 986
texture_context (bpy.types.SpaceProperties attribute), 828
texture_coordinate_object (bpy.types.DisplaceModifier attribute), 344
texture_coords (bpy.types.DisplaceModifier attribute), 344
texture_coords (bpy.types.LampTextureSlot attribute), 488
texture_coords (bpy.types.MaterialTextureSlot attribute), 527
texture_coords (bpy.types.ParticleSettingsTextureSlot attribute), 663
texture_coords (bpy.types.WaveModifier attribute), 1006
texture_coords (bpy.types.WorldTextureSlot attribute), 1021
texture_coords_object (bpy.types.WaveModifier attribute), 1007
texture_directory (bpy.types.UserPreferencesFilePaths attribute), 982
texture_factor (bpy.types.MaterialSubsurfaceScattering attribute), 525
texture_mesh (bpy.types.Mesh attribute), 538
texture_mode (bpy.types.FieldSettings attribute), 396
texture_nabla (bpy.types.FieldSettings attribute), 396
texture_overlay_alpha (bpy.types.Brush attribute), 229
texture_paint_object (in module bpy.context), 4
texture_paint_radial_control() (in module bpy.ops.paint), 84
texture_paint_toggle() (in module bpy.ops.paint), 84
texture_plugin_directory (bpy.types.UserPreferencesFilePaths attribute), 982
texture_sample_bias (bpy.types.Brush attribute), 229
texture_slot (in module bpy.context), 6
texture_time_out (bpy.types.UserPreferencesSystem attribute), 987
texture_type (bpy.types.SpaceNodeEditor attribute), 826
TextureNode (class in bpy.types), 874
TextureNode.type (in module bpy.types), 874
TextureNodeBricks (class in bpy.types), 875
TextureNodeChecker (class in bpy.types), 876
TextureNodeCompose (class in bpy.types), 877
TextureNodeCoordinates (class in bpy.types), 877

TextureNodeCurveRGB (class in bpy.types), 878
TextureNodeCurveRGB.mapping (in module bpy.types), 878
TextureNodeCurveTime (class in bpy.types), 879
TextureNodeCurveTime.curve (in module bpy.types), 879
TextureNodeDecompose (class in bpy.types), 880
TextureNodeDistance (class in bpy.types), 880
TextureNodeHueSaturation (class in bpy.types), 881
TextureNodeImage (class in bpy.types), 882
TextureNodeInvert (class in bpy.types), 883
TextureNodeMath (class in bpy.types), 883
TextureNodeMixRGB (class in bpy.types), 884
TextureNodeOutput (class in bpy.types), 885
TextureNodeRGBToBW (class in bpy.types), 886
TextureNodeRotate (class in bpy.types), 886
TextureNodes (class in bpy.types), 892
TextureNodeScale (class in bpy.types), 887
TextureNodeTexture (class in bpy.types), 888
TextureNodeTranslate (class in bpy.types), 889
TextureNodeTree (class in bpy.types), 889
TextureNodeTree.nodes (in module bpy.types), 889
TextureNodeValToNor (class in bpy.types), 890
TextureNodeValToRGB (class in bpy.types), 891
TextureNodeValToRGB.color_ramp (in module bpy.types), 891
TextureNodeViewer (class in bpy.types), 892
TextureSlot (class in bpy.types), 893
TextureSlot.name (in module bpy.types), 894
tface (bge.types.KX_PolygonMaterial attribute), 1117
Theme (class in bpy.types), 895
Theme.bone_color_sets (in module bpy.types), 895
Theme.console (in module bpy.types), 895
Theme.dopesheet_editor (in module bpy.types), 895
Theme.file_browser (in module bpy.types), 895
Theme.graph_editor (in module bpy.types), 895
Theme.image_editor (in module bpy.types), 895
Theme.info (in module bpy.types), 895
Theme.logic_editor (in module bpy.types), 895
Theme.nla_editor (in module bpy.types), 895
Theme.node_editor (in module bpy.types), 895
Theme.outliner (in module bpy.types), 895
Theme.properties (in module bpy.types), 896
Theme.sequence_editor (in module bpy.types), 896
Theme.text_editor (in module bpy.types), 896
Theme.timeline (in module bpy.types), 896
Theme.user_interface (in module bpy.types), 896
Theme.user_preferences (in module bpy.types), 896
Theme.view_3d (in module bpy.types), 896
theme_area (bpy.types.Theme attribute), 896
ThemeAudioWindow (class in bpy.types), 897
ThemeBoneColorSet (class in bpy.types), 898
ThemeConsole (class in bpy.types), 899
ThemeDopeSheet (class in bpy.types), 901
ThemeFileBrowser (class in bpy.types), 903
ThemeFontStyle (class in bpy.types), 905
ThemeGraphEditor (class in bpy.types), 906
ThemeImageEditor (class in bpy.types), 909
ThemeInfo (class in bpy.types), 911
ThemeLogicEditor (class in bpy.types), 912
ThemeNLAEditor (class in bpy.types), 913
ThemeNodeEditor (class in bpy.types), 915
ThemeOutliner (class in bpy.types), 917
ThemeProperties (class in bpy.types), 918
ThemeSequenceEditor (class in bpy.types), 920
ThemeStyle (class in bpy.types), 922
ThemeStyle.group_label (in module bpy.types), 922
ThemeStyle.panel_title (in module bpy.types), 922
ThemeStyle.widget (in module bpy.types), 922
ThemeStyle.widget_label (in module bpy.types), 922
ThemeTextEditor (class in bpy.types), 923
ThemeTimeline (class in bpy.types), 925
ThemeUserInterface (class in bpy.types), 926
ThemeUserInterface.wcol_box (in module bpy.types), 926
ThemeUserInterface.wcol_list_item (in module bpy.types), 926
ThemeUserInterface.wcol_menu (in module bpy.types), 926
ThemeUserInterface.wcol_menu_back (in module bpy.types), 926
ThemeUserInterface.wcol_menu_item (in module bpy.types), 926
ThemeUserInterface.wcol_num (in module bpy.types), 926
ThemeUserInterface.wcol_numslider (in module bpy.types), 926
ThemeUserInterface.wcol_option (in module bpy.types), 927
ThemeUserInterface.wcol_progress (in module bpy.types), 927
ThemeUserInterface.wcol_pulldown (in module bpy.types), 927
ThemeUserInterface.wcol_radio (in module bpy.types), 927
ThemeUserInterface.wcol_regular (in module bpy.types), 927
ThemeUserInterface.wcol_scroll (in module bpy.types), 927
ThemeUserInterface.wcol_state (in module bpy.types), 927
ThemeUserInterface.wcol_text (in module bpy.types), 927
ThemeUserInterface.wcol_toggle (in module bpy.types), 927
ThemeUserInterface.wcol_tool (in module bpy.types), 927
ThemeUserPreferences (class in bpy.types), 928
ThemeView3D (class in bpy.types), 929

ThemeWidgetColors (class in bpy.types), 933
ThemeWidgetStateColors (class in bpy.types), 934
thickness (bpy.types.SolidifyModifier attribute), 808
thickness_inner (bpy.types.CollisionSettings attribute), 253
thickness_outer (bpy.types.CollisionSettings attribute), 254
threads (bpy.types.RenderSettings attribute), 725
threads_mode (bpy.types.RenderSettings attribute), 725
THREEKEY (in module bge.events), 1174
threshold (bge.types.SCA_JoystickSensor attribute), 1135
threshold (bpy.types.CompositorNodeChromaMatte attribute), 265
threshold (bpy.types.CompositorNodeDefocus attribute), 277
threshold (bpy.types.CompositorNodeGlare attribute), 284
threshold (bpy.types.GlowSequence attribute), 424
threshold (bpy.types.MetaBall attribute), 562
threshold (bpy.types.WorldLighting attribute), 1018
tile (bge.types.KX_PolygonMaterial attribute), 1117
tile_set() (in module bpy.ops.uv), 127
tiles (bpy.types.ThemeFileBrowser attribute), 904
tiles_x (bpy.types.Image attribute), 440
tiles_y (bpy.types.Image attribute), 440
tilexrep (bge.types.KX_PolygonMaterial attribute), 1117
tileyrep (bge.types.KX_PolygonMaterial attribute), 1117
tilt (bpy.types.BezierSplinePoint attribute), 179
tilt (bpy.types.ShapeKeyCurvePoint attribute), 791
tilt (bpy.types.SplinePoint attribute), 846
tilt() (in module bpy.ops.transform), 118
tilt_clear() (in module bpy.ops.curve), 25
tilt_interpolation (bpy.types.Spline attribute), 842
time (bge.types.KX_ConstraintActuator attribute), 1093
time (bge.types.KX_SCA_AddObjectActuator attribute), 1122
time (bge.types.KX_TrackToActuator attribute), 1127
time (bpy.types.ConstraintActuator attribute), 320
time (bpy.types.EditObjectActuator attribute), 361
time (bpy.types.OperatorMousePath attribute), 628
time (bpy.types.OperatorStrokeElement attribute), 630
time (bpy.types.ParticleHairKey attribute), 646
time (bpy.types.ParticleKey attribute), 649
time (bpy.types.ParticleTarget attribute), 672
time_factor (bpy.types.ParticleSettingsTextureSlot attribute), 663
time_offset (bpy.types.Object attribute), 609
time_offset (bpy.types.WaveModifier attribute), 1007
time_scale (bpy.types.SmokeDomainSettings attribute), 799
time_toggle() (in module bpy.ops.anim), 14
time_tweak (bpy.types.ParticleSettings attribute), 659
timecode_style (bpy.types.UserPreferencesView attribute), 990
TimelineMarker (class in bpy.types), 935
TimelineMarkers (class in bpy.types), 936
timeOffset (bge.types.KX_GameObject attribute), 1096
tip_size (bpy.types.MaterialStrand attribute), 523
title (bpy.types.ThemeAudioWindow attribute), 897
title (bpy.types.ThemeConsole attribute), 900
title (bpy.types.ThemeDopeSheet attribute), 902
title (bpy.types.ThemeFileBrowser attribute), 904
title (bpy.types.ThemeGraphEditor attribute), 908
title (bpy.types.ThemeImageEditor attribute), 910
title (bpy.types.ThemeInfo attribute), 911
title (bpy.types.ThemeLogicEditor attribute), 913
title (bpy.types.ThemeNLAEditor attribute), 914
title (bpy.types.ThemeNodeEditor attribute), 916
title (bpy.types.ThemeOutliner attribute), 918
title (bpy.types.ThemeProperties attribute), 919
title (bpy.types.ThemeSequenceEditor attribute), 921
title (bpy.types.ThemeTextEditor attribute), 924
title (bpy.types.ThemeTimeline attribute), 925
title (bpy.types.ThemeUserPreferences attribute), 928
title (bpy.types.ThemeView3D attribute), 932
TKEY (in module bge.events), 1174
to_2d() (mathutils.Vector method), 1051
to_3d() (mathutils.Vector method), 1051
to_3d_object() (in module bpy.ops.text), 112
to_3x3() (mathutils.Matrix method), 1044
to_4d() (mathutils.Vector method), 1051
to_4x4() (mathutils.Matrix method), 1044
to_euler() (mathutils.Matrix method), 1044
to_euler() (mathutils.Quaternion method), 1047
to_matrix() (mathutils.Euler method), 1041
to_matrix() (mathutils.Quaternion method), 1047
to_max_x (bpy.types.TransformConstraint attribute), 944
to_max_y (bpy.types.TransformConstraint attribute), 945
to_max_z (bpy.types.TransformConstraint attribute), 945
to_mesh() (bpy.types.Object method), 610
to_min_x (bpy.types.TransformConstraint attribute), 945
to_min_y (bpy.types.TransformConstraint attribute), 945
to_min_z (bpy.types.TransformConstraint attribute), 945
to_property (bpy.types.MessageActuator attribute), 560
to_quaternion() (mathutils.Euler method), 1041
to_quaternion() (mathutils.Matrix method), 1044
to_scale() (mathutils.Matrix method), 1044
to_track_quat() (mathutils.Vector method), 1051
to_translation() (mathutils.Matrix method), 1044
to_tuple() (mathutils.Vector method), 1051
toggleProperty (bge.types.SCA_KeyboardSensor attribute), 1136
tolerance (bpy.types.CompositorNodeChromaMatte attribute), 265
tolerance (bpy.types.CompositorNodeDiffMatte attribute), 278

tolerance (bpy.types.CompositorNodeDistanceMatte attribute), 280
tonemap_type (bpy.types.CompositorNodeTonemap attribute), 309
tool (bpy.types.ParticleEdit attribute), 644
toolbox() (in module bpy.ops.buttons), 18
toolbox() (in module bpy.ops.image), 41
ToolSettings (class in bpy.types), 937
ToolSettings.image_paint (in module bpy.types), 938
ToolSettings.particle_edit (in module bpy.types), 938
ToolSettings.sculpt (in module bpy.types), 939
ToolSettings.vertex_paint (in module bpy.types), 941
ToolSettings.weight_paint (in module bpy.types), 941
toolshelf() (in module bpy.ops.view3d), 131
torque (bge.types.KX_ObjectActuator attribute), 1111
torque (bpy.types.ObjectActuator attribute), 615
tosphere() (in module bpy.ops.transform), 118
TouchSensor (class in bpy.types), 941
tracer_particles (bpy.types.DomainFluidSettings attribute), 348
track_axis (bpy.types.DampedTrackConstraint attribute), 341
track_axis (bpy.types.LockedTrackConstraint attribute), 501
track_axis (bpy.types.Object attribute), 609
track_axis (bpy.types.TrackToConstraint attribute), 942
track_clear() (in module bpy.ops.object), 79
track_object (bpy.types.EditObjectActuator attribute), 361
track_set() (in module bpy.ops.object), 79
trackball() (in module bpy.ops.transform), 119
tracks_add() (in module bpy.ops.nla), 62
TrackToConstraint (class in bpy.types), 942
trail_count (bpy.types.ParticleSettings attribute), 659
transform (bpy.types.ThemeView3D attribute), 932
transform() (bpy.types.EditBone method), 360
transform() (bpy.types.Mesh method), 540
transform() (in module bpy.ops.transform), 119
transform_channel (bpy.types.ActionConstraint attribute), 145
transform_orientation (bpy.types.SpaceView3D attribute), 838
transform_type (bpy.types.DriverTarget attribute), 353
TransformConstraint (class in bpy.types), 943
TransformOrientation (class in bpy.types), 946
transforms_clear() (in module bpy.ops.pose), 91
TransformSequence (class in bpy.types), 947
transition_add() (in module bpy.ops.nla), 62
transition_strip (bpy.types.ThemeSequenceEditor attribute), 921
transition_type (bpy.types.WipeSequence attribute), 1011
translate() (bpy.types.Bone method), 222
translate() (bpy.types.EditBone method), 360
translate() (bpy.types.PoseBone method), 691
translate() (in module bpy.ops.transform), 120
translate_start_x (bpy.types.TransformSequence attribute), 947
translate_start_y (bpy.types.TransformSequence attribute), 947
Translation() (mathutils.Matrix class method), 1042
translation_unit (bpy.types.TransformSequence attribute), 947
translucency (bpy.types.Material attribute), 512
translucency_factor (bpy.types.MaterialTextureSlot attribute), 528
transmission_color (bpy.types.MaterialVolume attribute), 533
transmission_color_factor (bpy.types.MaterialTextureSlot attribute), 528
transparency_method (bpy.types.Material attribute), 512
transparent (bge.types.KX_PolygonMaterial attribute), 1118
transpose() (mathutils.Matrix method), 1045
transposed() (mathutils.Matrix method), 1045
tree_type (bpy.types.SpaceNodeEditor attribute), 826
triangle (bge.types.KX_PolygonMaterial attribute), 1118
triggered (bge.types.SCA_ISensor attribute), 1085
tris_convert_to_quads() (in module bpy.ops.mesh), 60
turbulence (bpy.types.EffectorWeights attribute), 366
turbulence (bpy.types.MagicTexture attribute), 503
turbulence (bpy.types.MarbleTexture attribute), 506
turbulence (bpy.types.StucciTexture attribute), 856
turbulence (bpy.types.WoodTexture attribute), 1013
turbulence_depth (bpy.types.PointDensity attribute), 681
turbulence_influence (bpy.types.PointDensity attribute), 681
turbulence_scale (bpy.types.PointDensity attribute), 681
turbulence_strength (bpy.types.PointDensity attribute), 681
tweakmode_enter() (in module bpy.ops.nla), 62
tweakmode_exit() (in module bpy.ops.nla), 62
twist_mode (bpy.types.Curve attribute), 334
twist_smooth (bpy.types.Curve attribute), 334
TWOKEY (in module bge.events), 1174
type (bge.types.BL_ArmatureActuator attribute), 1145
type (bge.types.BL_ArmatureConstraint attribute), 1147
type (bge.types.KX_ArmatureSensor attribute), 1146
type (bge.types.KX_LightObject attribute), 1105
type (bpy.types.Actuator attribute), 151
type (bpy.types.AnimVizMotionPaths attribute), 159
type (bpy.types.AnimVizOnionSkinning attribute), 160
type (bpy.types.Area attribute), 162
type (bpy.types.Camera attribute), 236
type (bpy.types.Controller attribute), 326
type (bpy.types.Driver attribute), 351
type (bpy.types.DriverVariable attribute), 354
type (bpy.types.FieldSettings attribute), 396

type (bpy.types.FluidSettings attribute), 404
type (bpy.types.GameProperty attribute), 420
type (bpy.types.Keyframe attribute), 474
type (bpy.types.KeyMapItem attribute), 465
type (bpy.types.Lamp attribute), 485
type (bpy.types.Material attribute), 512
type (bpy.types.MetaElement attribute), 565
type (bpy.types.ParticleEdit attribute), 644
type (bpy.types.ParticleSettings attribute), 659
type (bpy.types.Sensor attribute), 758
type (bpy.types.Spline attribute), 842
type (bpy.types.Texture attribute), 873
type_recast() (bpy.types.bpy_struct method), 1029

U

u (bge.types.KX_VertexProxy attribute), 1130
u2 (bge.types.KX_VertexProxy attribute), 1130
UILayout (class in bpy.types), 948
UKEY (in module bge.events), 1174
uncomment() (in module bpy.ops.text), 112
underline_height (bpy.types.TextCurve attribute), 868
underline_position (bpy.types.TextCurve attribute), 869
undo() (in module bpy.ops.ed), 25
undo_memory_limit (bpy.types.UserPreferencesEdit attribute), 978
undo_push() (in module bpy.ops.ed), 25
undo_steps (bpy.types.UserPreferencesEdit attribute), 978
unindent() (in module bpy.ops.text), 112
UnitSettings (class in bpy.types), 974
UnknownType (class in bpy.types), 975
unlink() (bpy.types.Actuator method), 151
unlink() (bpy.types.Controller method), 326
unlink() (bpy.types.GroupObjects method), 429
unlink() (bpy.types.SceneObjects method), 745
unlink() (bpy.types.Sensor method), 758
unlink() (in module bpy.ops.font), 33
unlink() (in module bpy.ops.poselib), 92
unlink() (in module bpy.ops.text), 112
unlink_selection() (in module bpy.ops.uv), 127
unlock() (in module bpy.ops.sequencer), 104
unmute() (in module bpy.ops.sequencer), 104
unpack() (in module bpy.ops.image), 41
unpack() (in module bpy.ops.sound), 106
unpack_all() (in module bpy.ops.file), 31
unprojected_radius (bpy.types.Brush attribute), 229
unregister_class() (in module bpy.utils), 1030
unregister_module() (in module bpy.utils), 1030
unspill_blue (bpy.types.CompositorNodeColorSpill attribute), 268
unspill_green (bpy.types.CompositorNodeColorSpill attribute), 268
unspill_red (bpy.types.CompositorNodeColorSpill attribute), 269
unwrap() (in module bpy.ops.uv), 127
up_axis (bpy.types.FollowPathConstraint attribute), 406
up_axis (bpy.types.Object attribute), 609
up_axis (bpy.types.TrackToConstraint attribute), 943
UPARROWKEY (in module bge.events), 1175
update() (bge.types.BL_ArmatureObject method), 1144
update() (bpy.types.Image method), 441
update() (bpy.types.Mesh method), 540
update() (bpy.types.Scene method), 738
update_data_paths() (in module bpy.ops.anim), 14
update_method (bpy.types.MetaBall attribute), 562
update_result() (bpy.types.RenderEngine method), 713
update_stats() (bpy.types.RenderEngine method), 713
update_tag() (bpy.types.ID method), 436
updateTexture() (bge.types.KX_PolygonMaterial method), 1118
url_open() (in module bpy.ops.wm), 142
use (bpy.types.CollisionSettings attribute), 254
use (bpy.types.ControlFluidSettings attribute), 325
use (bpy.types.FluidFluidSettings attribute), 403
use (bpy.types.InflowFluidSettings attribute), 451
use (bpy.types.MaterialRaytraceMirror attribute), 520
use (bpy.types.MaterialSubsurfaceScattering attribute), 525
use (bpy.types.MaterialTextureSlot attribute), 528
use (bpy.types.ObstacleFluidSettings attribute), 620
use (bpy.types.OutflowFluidSettings attribute), 632
use (bpy.types.SceneRenderLayer attribute), 747
use (bpy.types.UserSolidLight attribute), 992
use3D (bge.types.KX_TrackToActuator attribute), 1127
use_2d_force (bpy.types.FieldSettings attribute), 396
use_3d_tracking (bpy.types.EditObjectActuator attribute), 361
use_absolute (bpy.types.SmokeFlowSettings attribute), 800
use_absolute_path_time (bpy.types.ParticleSettings attribute), 659
use_absorption (bpy.types.FieldSettings attribute), 396
use_accumulate (bpy.types.Brush attribute), 229
use_activity_culling (bpy.types.GameObjectSettings attribute), 418
use_activity_culling (bpy.types.SceneGameData attribute), 743
use_actor (bpy.types.GameObjectSettings attribute), 418
use_adaptive_space (bpy.types.Brush attribute), 229
use_add_linear_velocity (bpy.types.ObjectActuator attribute), 615
use_additive (bpy.types.FCurveActuator attribute), 379
use_additive (bpy.types.FModifierFunctionGenerator attribute), 387
use_additive (bpy.types.FModifierGenerator attribute), 388
use_advanced_hair (bpy.types.ParticleSettings attribute), 659

use_airbrush (bpy.types.Brush attribute), 229
use_all_events (bpy.types.JoystickSensor attribute), 457
use_all_faces (bpy.types.VertexPaint attribute), 999
use_all_keys (bpy.types.KeyboardSensor attribute), 472
use_all_states (bpy.types.GameObjectSettings attribute), 418
use_all_z (bpy.types.SceneRenderLayer attribute), 747
use_alpha (bpy.types.Brush attribute), 229
use_alpha (bpy.types.CompositorNodeMixRGB attribute), 294
use_alpha (bpy.types.CompositorNodeZcombine attribute), 314
use_alpha (bpy.types.ImageTexture attribute), 448
use_alpha (bpy.types.ShaderNodeMixRGB attribute), 777
use_alpha (bpy.types.TextureNodeMixRGB attribute), 884
use_alpha_sort (bpy.types.MeshTextureFace attribute), 555
use_always_true (bpy.types.RandomActuator attribute), 705
use_ambient_occlusion (bpy.types.WorldLighting attribute), 1018
use_anchor (bpy.types.Brush attribute), 229
use_angular_limit_x (bpy.types.RigidBodyJointConstraint attribute), 731
use_angular_limit_y (bpy.types.RigidBodyJointConstraint attribute), 731
use_angular_limit_z (bpy.types.RigidBodyJointConstraint attribute), 731
use_animated_influence (bpy.types.NlaStrip attribute), 591
use_animated_mesh (bpy.types.FluidFluidSettings attribute), 403
use_animated_mesh (bpy.types.InflowFluidSettings attribute), 451
use_animated_mesh (bpy.types.ObstacleFluidSettings attribute), 620
use_animated_mesh (bpy.types.OutflowFluidSettings attribute), 632
use_animated_time (bpy.types.NlaStrip attribute), 591
use_animated_time_cyclic (bpy.types.NlaStrip attribute), 591
use_animation (bpy.types.Image attribute), 440
use_animation_record (bpy.types.SceneGameData attribute), 743
use_anisotropic_friction (bpy.types.GameObjectSettings attribute), 418
use_antialiasing (bpy.types.RenderSettings attribute), 725
use_antialiasing (bpy.types.UserPreferencesSystem attribute), 987
use_apply_on_spline (bpy.types.Modifier attribute), 570
use_as_speed (bpy.types.SpeedControlSequence attribute), 839
use_atmosphere (bpy.types.LampSkySettings attribute), 487
use_audio (bpy.types.Scene attribute), 737
use_audio_scrub (bpy.types.Scene attribute), 737
use_audio_sync (bpy.types.Scene attribute), 737
use_auto_blend (bpy.types.NlaStrip attribute), 591
use_auto_clip_end (bpy.types.SpotLamp attribute), 849
use_auto_clip_start (bpy.types.SpotLamp attribute), 849
use_auto_handle_clamp (bpy.types.FCurve attribute), 377
use_auto_ik (bpy.types.Armature attribute), 167
use_auto_keying (bpy.types.UserPreferencesEdit attribute), 978
use_auto_merge_keyframes (bpy.types.SpaceDopeSheetEditor attribute), 816
use_auto_merge_keyframes (bpy.types.SpaceGraphEditor attribute), 819
use_auto_normalize (bpy.types.ToolSettings attribute), 939
use_auto_perspective (bpy.types.UserPreferencesView attribute), 990
use_auto_refresh (bpy.types.CompositorNodeImage attribute), 288
use_auto_refresh (bpy.types.ImageUser attribute), 450
use_auto_render (bpy.types.SpaceNodeEditor attribute), 826
use_auto_save_temporary_files (bpy.types.UserPreferencesFilePaths attribute), 982
use_auto_smooth (bpy.types.Mesh attribute), 539
use_auto_start (bpy.types.SceneGameData attribute), 743
use_auto_step (bpy.types.Itasc attribute), 456
use_auto_step (bpy.types.SoftBodySettings attribute), 806
use_auto_texspace (bpy.types.Curve attribute), 334
use_auto_texspace (bpy.types.Mesh attribute), 539
use_auto_texspace (bpy.types.MetaBall attribute), 562
use_auto_velocity (bpy.types.ParticleEdit attribute), 644
use_avoid (bpy.types.BoidRuleAvoidCollision attribute), 212
use_avoid_collision (bpy.types.BoidRuleAvoidCollision attribute), 212
use_backface_culling (bpy.types.ImagePaint attribute), 443
use_bake_antialiasing (bpy.types.RenderSettings attribute), 725
use_bake_clear (bpy.types.RenderSettings attribute), 725
use_bake_normalize (bpy.types.RenderSettings attribute), 725
use_bake_selected_to_active (bpy.types.RenderSettings attribute), 726
use_bending_constraints (bpy.types.GameSoftBodySettings attribute), 421

use_bezier_u (bpy.types.Spline attribute), 842
use_bezier_v (bpy.types.Spline attribute), 842
use_billboard (bpy.types.MeshTextureFace attribute), 555
use_bitmap_text (bpy.types.MeshTextureFace attribute), 555
use_blend_shared (bpy.types.MeshTextureFace attribute), 555
use_blender_units (bpy.types.MaterialStrand attribute), 523
use_bokeh (bpy.types.CompositorNodeBlur attribute), 262
use_bold (bpy.types.TextCharacterFormat attribute), 866
use_bone_envelopes (bpy.types.ArmatureModifier attribute), 171
use_bone_sketching (bpy.types.ToolSettings attribute), 939
use_border (bpy.types.RenderSettings attribute), 726
use_box_clip (bpy.types.RegionView3D attribute), 710
use_cache (bpy.types.WorldLighting attribute), 1018
use_calculate_alpha (bpy.types.ImageTexture attribute), 448
use_cast_approximate (bpy.types.Material attribute), 512
use_cast_buffer_shadows (bpy.types.Material attribute), 512
use_cast_shadows_only (bpy.types.Material attribute), 513
use_chain_offset (bpy.types.SplineIKConstraint attribute), 844
use_checker_even (bpy.types.ImageTexture attribute), 448
use_checker_odd (bpy.types.ImageTexture attribute), 448
use_children (bpy.types.ParticleInstanceModifier attribute), 648
use_cineon_log (bpy.types.RenderSettings attribute), 726
use_clamp_x (bpy.types.Image attribute), 440
use_clamp_y (bpy.types.Image attribute), 440
use_climb (bpy.types.BoidSettings attribute), 217
use_clip (bpy.types.CurveMapping attribute), 338
use_clip (bpy.types.MirrorModifier attribute), 568
use_clone_layer (bpy.types.ImagePaint attribute), 443
use_cluster_rigid_to_softbody (bpy.types.GameSoftBodySettings attribute), 421
use_cluster_soft_to_softbody (bpy.types.GameSoftBodySettings attribute), 421
use_collision (bpy.types.ClothCollisionSettings attribute), 244
use_collision (bpy.types.MeshTextureFace attribute), 555
use_collision_bounds (bpy.types.GameObjectSettings attribute), 418
use_collision_compound (bpy.types.GameObjectSettings attribute), 418
use_color_balance (bpy.types.EffectSequence attribute), 363
use_color_balance (bpy.types.ImageSequence attribute), 444
use_color_balance (bpy.types.MetaSequence attribute), 566
use_color_balance (bpy.types.MovieSequence attribute), 575
use_color_balance (bpy.types.MulticamSequence attribute), 577
use_color_balance (bpy.types.SceneSequence attribute), 750
use_color_management (bpy.types.RenderSettings attribute), 726
use_color_ramp (bpy.types.Texture attribute), 873
use_compositing (bpy.types.RenderSettings attribute), 726
use_compound (bpy.types.ParentActuator attribute), 638
use_connect (bpy.types.EditBone attribute), 358
use_constant_offset (bpy.types.ArrayModifier attribute), 174
use_continue_last_frame (bpy.types.ActionActuator attribute), 144
use_continue_last_frame (bpy.types.ShapeActionActuator attribute), 788
use_crop (bpy.types.EffectSequence attribute), 363
use_crop (bpy.types.ImageSequence attribute), 445
use_crop (bpy.types.MetaSequence attribute), 566
use_crop (bpy.types.MovieSequence attribute), 575
use_crop (bpy.types.MulticamSequence attribute), 578
use_crop (bpy.types.SceneSequence attribute), 750
use_crop_size (bpy.types.CompositorNodeCrop attribute), 273
use_crop_to_border (bpy.types.RenderSettings attribute), 726
use_cubic (bpy.types.Material attribute), 513
use_curve_follow (bpy.types.FollowPathConstraint attribute), 406
use_curve_radius (bpy.types.FollowPathConstraint attribute), 406
use_curve_radius (bpy.types.SplineIKConstraint attribute), 844
use_curved (bpy.types.CompositorNodeVecBlur attribute), 313
use_custom_icon (bpy.types.Brush attribute), 229
use_cyclic (bpy.types.ClampToConstraint attribute), 243
use_cyclic (bpy.types.CompositorNodeImage attribute), 288
use_cyclic (bpy.types.ImageUser attribute), 450
use_cyclic (bpy.types.WaveModifier attribute), 1007
use_cyclic_offset (bpy.types.Bone attribute), 221
use_cyclic_offset (bpy.types.EditBone attribute), 358
use_cyclic_u (bpy.types.Spline attribute), 842

use_cyclic_v (bpy.types.Spline attribute), 842
use_dead (bpy.types.ParticleSettings attribute), 659
use_debug (bpy.types.PythonController attribute), 702
use_default_fade (bpy.types.Sequence attribute), 761
use_default_interpolate (bpy.types.ParticleEdit attribute), 644
use_deform (bpy.types.Bone attribute), 221
use_deform (bpy.types.EditBone attribute), 358
use_deform_bounds (bpy.types.Curve attribute), 334
use_deform_delay (bpy.types.Armature attribute), 167
use_deform_envelopes (bpy.types.Armature attribute), 167
use_deform_preserve_volume (bpy.types.Armature attribute), 167
use_deform_preserve_volume (bpy.types.ArmatureModifier attribute), 171
use_deform_vertex_groups (bpy.types.Armature attribute), 167
use_deinterlace (bpy.types.EffectSequence attribute), 363
use_deinterlace (bpy.types.ImageSequence attribute), 445
use_deinterlace (bpy.types.MetaSequence attribute), 566
use_deinterlace (bpy.types.MovieSequence attribute), 575
use_deinterlace (bpy.types.MulticamSequence attribute), 578
use_deinterlace (bpy.types.SceneSequence attribute), 750
use_deprecation_warnings (bpy.types.SceneGameData attribute), 743
use_diagnose (bpy.types.SoftBodySettings attribute), 806
use_die_on_collision (bpy.types.ParticleSettings attribute), 659
use_diffuse (bpy.types.Lamp attribute), 485
use_diffuse (bpy.types.ShaderNodeExtendedMaterial attribute), 771
use_diffuse (bpy.types.ShaderNodeMaterial attribute), 775
use_diffuse_ramp (bpy.types.Material attribute), 513
use_directional_menus (bpy.types.UserPreferencesView attribute), 990
use_disk_cache (bpy.types.PointCache attribute), 678
use_display_lists (bpy.types.SceneGameData attribute), 743
use_dissolve_smoke (bpy.types.SmokeDomainSettings attribute), 799
use_dissolve_smoke_log (bpy.types.SmokeDomainSettings attribute), 799
use_dither (bpy.types.AreaLamp attribute), 164
use_drag_immediately (bpy.types.UserPreferencesEdit attribute), 978
use_drops (bpy.types.ParticleFluidSettings attribute), 645
use_dupli_faces_scale (bpy.types.Object attribute), 609
use_dupli_frames_speed (bpy.types.Object attribute), 610
use_dupli_vertices_rotation (bpy.types.Object attribute), 610
use_duplicate_action (bpy.types.UserPreferencesEdit attribute), 978
use_duplicate_armature (bpy.types.UserPreferencesEdit attribute), 978
use_duplicate_curve (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_fcurve (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_lamp (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_material (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_mesh (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_metaball (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_particle (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_surface (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_text (bpy.types.UserPreferencesEdit attribute), 979
use_duplicate_texture (bpy.types.UserPreferencesEdit attribute), 979
use_dynamic_bind (bpy.types.MeshDeformModifier attribute), 544
use_dynamic_rotation (bpy.types.ParticleSettings attribute), 659
use_edge_angle (bpy.types.EdgeSplitModifier attribute), 356
use_edge_collision (bpy.types.SoftBodySettings attribute), 806
use_edge_cut (bpy.types.ExplodeModifier attribute), 374
use_edge_enhance (bpy.types.RenderSettings attribute), 726
use_edge_enhance (bpy.types.SceneRenderLayer attribute), 747
use_edge_sharp (bpy.types.EdgeSplitModifier attribute), 356
use_edge_sharp (bpy.types.MeshEdge attribute), 545
use_edge_to_edge (bpy.types.Brush attribute), 229
use_edges (bpy.types.SoftBodySettings attribute), 806
use_emit_random (bpy.types.ParticleSettings attribute), 660
use_emitter_deflect (bpy.types.ParticleEdit attribute), 644
use_emulate_numpad (bpy.types.UserPreferencesInput attribute), 984
use_endpoint_u (bpy.types.Spline attribute), 842
use_endpoint_v (bpy.types.Spline attribute), 842
use_enter_edit_mode (bpy.types.UserPreferencesEdit attribute), 979
use_entire_array (bpy.types.KeyingSetPath attribute), 478

use_envelope_multiply (bpy.types.Bone attribute), 221
use_envelope_multiply (bpy.types.EditBone attribute), 358
use_environment_light (bpy.types.WorldLighting attribute), 1018
use_envmaps (bpy.types.RenderSettings attribute), 726
use_estimate_matrix (bpy.types.SoftBodySettings attribute), 807
use_etch_autoname (bpy.types.ToolSettings attribute), 939
use_etch_overdraw (bpy.types.ToolSettings attribute), 939
use_etch_quick (bpy.types.ToolSettings attribute), 939
use_even_distribution (bpy.types.ParticleSettings attribute), 660
use_even_divisions (bpy.types.SplineIKConstraint attribute), 844
use_even_offset (bpy.types.SolidifyModifier attribute), 808
use_exr_half (bpy.types.CompositorNodeOutputFile attribute), 297
use_exr_half (bpy.types.RenderSettings attribute), 726
use_external (bpy.types.PointCache attribute), 678
use_external_shadows (bpy.types.MaterialVolume attribute), 533
use_extreme_alpha (bpy.types.MaterialHalo attribute), 516
use_face_collision (bpy.types.SoftBodySettings attribute), 807
use_face_texture (bpy.types.Material attribute), 513
use_face_texture_alpha (bpy.types.Material attribute), 513
use_fade_time (bpy.types.ParticleEdit attribute), 644
use_fake_user (bpy.types.ID attribute), 435
use_falloff (bpy.types.WorldLighting attribute), 1018
use_fancy_drawing (bpy.types.SpaceGraphEditor attribute), 819
use_fast_edit (bpy.types.TextCurve attribute), 869
use_fh_normal (bpy.types.ConstraintActuator attribute), 320
use_fh_normal (bpy.types.MaterialPhysics attribute), 518
use_fh_paralel_axis (bpy.types.ConstraintActuator attribute), 320
use_fields (bpy.types.Image attribute), 440
use_fields (bpy.types.RenderSettings attribute), 726
use_fields_still (bpy.types.RenderSettings attribute), 726
use_file_compression (bpy.types.UserPreferencesFilePaths attribute), 982
use_file_extension (bpy.types.RenderSettings attribute), 726
use_fill_back (bpy.types.Curve attribute), 334
use_fill_deform (bpy.types.Curve attribute), 334
use_fill_front (bpy.types.Curve attribute), 334
use_filter (bpy.types.FileSelectParams attribute), 398
use_filter_blender (bpy.types.FileSelectParams attribute), 398
use_filter_case_sensitive (bpy.types.SpaceOutliner attribute), 827
use_filter_complete (bpy.types.SpaceOutliner attribute), 827
use_filter_files (bpy.types.UserPreferencesFilePaths attribute), 982
use_filter_folder (bpy.types.FileSelectParams attribute), 398
use_filter_font (bpy.types.FileSelectParams attribute), 398
use_filter_image (bpy.types.FileSelectParams attribute), 398
use_filter_movie (bpy.types.FileSelectParams attribute), 398
use_filter_script (bpy.types.FileSelectParams attribute), 398
use_filter_size_min (bpy.types.EnvironmentMapTexture attribute), 371
use_filter_size_min (bpy.types.ImageTexture attribute), 448
use_filter_sound (bpy.types.FileSelectParams attribute), 399
use_filter_text (bpy.types.FileSelectParams attribute), 399
use_find_all (bpy.types.SpaceTextEditor attribute), 831
use_find_wrap (bpy.types.SpaceTextEditor attribute), 831
use_fit (bpy.types.CompositorNodeLensdist attribute), 289
use_fixed_location (bpy.types.FollowPathConstraint attribute), 406
use_fixed_texture (bpy.types.Brush attribute), 229
use_flare_mode (bpy.types.MaterialHalo attribute), 516
use_flight (bpy.types.BoidSettings attribute), 217
use_flip_axis (bpy.types.BlendTexture attribute), 207
use_flip_axis (bpy.types.ImageTexture attribute), 448
use_flip_x (bpy.types.EffectSequence attribute), 363
use_flip_x (bpy.types.ImageSequence attribute), 445
use_flip_x (bpy.types.MetaSequence attribute), 566
use_flip_x (bpy.types.MovieSequence attribute), 575
use_flip_x (bpy.types.MulticamSequence attribute), 578
use_flip_x (bpy.types.SceneSequence attribute), 750
use_flip_y (bpy.types.EffectSequence attribute), 363
use_flip_y (bpy.types.ImageSequence attribute), 445
use_flip_y (bpy.types.MetaSequence attribute), 566
use_flip_y (bpy.types.MovieSequence attribute), 575
use_flip_y (bpy.types.MulticamSequence attribute), 578
use_flip_y (bpy.types.SceneSequence attribute), 750
use_float (bpy.types.EffectSequence attribute), 363
use_float (bpy.types.ImageSequence attribute), 445
use_float (bpy.types.MetaSequence attribute), 567
use_float (bpy.types.MovieSequence attribute), 575
use_float (bpy.types.MulticamSequence attribute), 578
use_float (bpy.types.SceneSequence attribute), 750

use_floats (bpy.types.ParticleFluidSettings attribute), 645
use_force (bpy.types.FCurveActuator attribute), 379
use_force_distance (bpy.types.ConstraintActuator attribute), 320
use_frame_blend (bpy.types.SpeedControlSequence attribute), 839
use_frame_drop (bpy.types.Scene attribute), 737
use_frame_end (bpy.types.FModifierStepped attribute), 392
use_frame_rate (bpy.types.SceneGameData attribute), 743
use_frame_start (bpy.types.FModifierStepped attribute), 392
use_free_image_textures (bpy.types.RenderSettings attribute), 726
use_free_unused_nodes (bpy.types.RenderSettings attribute), 727
use_from_dupli (bpy.types.MaterialTextureSlot attribute), 528
use_from_original (bpy.types.MaterialTextureSlot attribute), 528
use_frontface (bpy.types.Brush attribute), 230
use_full_oversampling (bpy.types.Material attribute), 513
use_full_resolution (bpy.types.Scopes attribute), 752
use_full_sample (bpy.types.RenderSettings attribute), 727
use_gamma_correction (bpy.types.CompositorNodeBlur attribute), 262
use_gamma_correction (bpy.types.CompositorNodeDefocus attribute), 277
use_ghost (bpy.types.GameObjectSettings attribute), 418
use_ghost (bpy.types.ParentActuator attribute), 638
use_global_coords (bpy.types.FieldSettings attribute), 396
use_global_dupli (bpy.types.ParticleSettings attribute), 660
use_global_pivot (bpy.types.UserPreferencesView attribute), 990
use_global_scene (bpy.types.UserPreferencesView attribute), 990
use_global_undo (bpy.types.UserPreferencesEdit attribute), 979
use_glsl_extra_textures (bpy.types.SceneGameData attribute), 743
use_glsl_lights (bpy.types.SceneGameData attribute), 743
use_glsl_nodes (bpy.types.SceneGameData attribute), 743
use_glsl_ramps (bpy.types.SceneGameData attribute), 744
use_glsl_shaders (bpy.types.SceneGameData attribute), 744
use_glsl_shadows (bpy.types.SceneGameData attribute), 744
use_goal (bpy.types.SoftBodySettings attribute), 807
use_gravity (bpy.types.Scene attribute), 737
use_grease_pencil (bpy.types.SpaceImageEditor attribute), 821
use_grease_pencil (bpy.types.SpaceSequenceEditor attribute), 829
use_grease_pencil_sessions (bpy.types.ToolSettings attribute), 940
use_grease_pencil_simplify_stroke (bpy.types.UserPreferencesEdit attribute), 979
use_grease_pencil_smooth_stroke (bpy.types.UserPreferencesEdit attribute), 979
use_group_count (bpy.types.ParticleSettings attribute), 660
use_group_pick_random (bpy.types.ParticleSettings attribute), 660
use_guide_path_add (bpy.types.FieldSettings attribute), 396
use_guide_path_weight (bpy.types.FieldSettings attribute), 396
use_hair_bspline (bpy.types.ParticleSettings attribute), 660
use_hair_dynamics (bpy.types.ParticleSystem attribute), 668
use_halo (bpy.types.MeshTextureFace attribute), 555
use_halo (bpy.types.SceneRenderLayer attribute), 747
use_halo (bpy.types.SpotLamp attribute), 849
use_high_resolution (bpy.types.SmokeDomainSettings attribute), 799
use_ik_limit_x (bpy.types.PoseBone attribute), 690
use_ik_limit_y (bpy.types.PoseBone attribute), 690
use_ik_limit_z (bpy.types.PoseBone attribute), 690
use_ik_linear_control (bpy.types.PoseBone attribute), 690
use_ik_rotation_control (bpy.types.PoseBone attribute), 691
use_image (bpy.types.MeshTextureFace attribute), 555
use_image_override (bpy.types.UVProjectModifier attribute), 972
use_image_paint (bpy.types.SpaceImageEditor attribute), 821
use_image_pin (bpy.types.SpaceImageEditor attribute), 821
use_in_air (bpy.types.BoidRule attribute), 209
use_indirect_light (bpy.types.WorldLighting attribute), 1018
use_inherit_rotation (bpy.types.Bone attribute), 221
use_inherit_rotation (bpy.types.EditBone attribute), 358
use_inherit_scale (bpy.types.Bone attribute), 221
use_inherit_scale (bpy.types.EditBone attribute), 359
use_initial_rest_length (bpy.types.SPHFluidSettings attribute), 734

use_insertkey_xyz_to_rgb (bpy.types.UserPreferencesEdit attribute), 980
use_instances (bpy.types.RenderSettings attribute), 727
use_international_fonts (bpy.types.UserPreferencesSystem attribute), 987
use_interpolation (bpy.types.ImageTexture attribute), 448
use_inverse_smooth_pressure (bpy.types.Brush attribute), 230
use_italic (bpy.types.TextCharacterFormat attribute), 866
use_jitter (bpy.types.AreaLamp attribute), 164
use_jitter (bpy.types.CompositorNodeLensdist attribute), 289
use_keep_above_surface (bpy.types.ShrinkwrapModifier attribute), 794
use_keyed_timing (bpy.types.ParticleSystem attribute), 669
use_keyframe_insert_auto (bpy.types.ToolSettings attribute), 940
use_keyframe_insert_available (bpy.types.UserPreferencesEdit attribute), 980
use_keyframe_insert_keyingset (bpy.types.ToolSettings attribute), 940
use_keyframe_insert_needed (bpy.types.UserPreferencesEdit attribute), 980
use_land (bpy.types.BoidSettings attribute), 217
use_level (bpy.types.Sensor attribute), 758
use_library_path (bpy.types.PointCache attribute), 678
use_light (bpy.types.MeshTextureFace attribute), 555
use_light_cache (bpy.types.MaterialVolume attribute), 533
use_light_group_exclusive (bpy.types.Material attribute), 513
use_limit_x (bpy.types.LimitRotationConstraint attribute), 498
use_limit_x (bpy.types.RigidBodyJointConstraint attribute), 731
use_limit_y (bpy.types.LimitRotationConstraint attribute), 498
use_limit_y (bpy.types.RigidBodyJointConstraint attribute), 732
use_limit_z (bpy.types.LimitRotationConstraint attribute), 498
use_limit_z (bpy.types.RigidBodyJointConstraint attribute), 732
use_line (bpy.types.BoidRuleFollowLeader attribute), 214
use_lines (bpy.types.MaterialHalo attribute), 517
use_linked_collision (bpy.types.RigidBodyJointConstraint attribute), 732
use_live_edit (bpy.types.SpaceTextEditor attribute), 831
use_live_unwrap (bpy.types.SpaceUVEditor attribute), 834
use_load_ui (bpy.types.UserPreferencesFilePaths attribute), 982
use_local (bpy.types.ConstraintActuator attribute), 321
use_local (bpy.types.FCurveActuator attribute), 379
use_local_angular_velocity (bpy.types.EditObjectActuator attribute), 361
use_local_angular_velocity (bpy.types.ObjectActuator attribute), 615
use_local_coords (bpy.types.InflowFluidSettings attribute), 451
use_local_coords (bpy.types.RenderSettings attribute), 727
use_local_force (bpy.types.ObjectActuator attribute), 615
use_local_linear_velocity (bpy.types.EditObjectActuator attribute), 361
use_local_linear_velocity (bpy.types.ObjectActuator attribute), 616
use_local_location (bpy.types.Bone attribute), 221
use_local_location (bpy.types.EditBone attribute), 359
use_local_location (bpy.types.ObjectActuator attribute), 616
use_local_rotation (bpy.types.ObjectActuator attribute), 616
use_local_space_transform (bpy.types.DriverTarget attribute), 353
use_local_torque (bpy.types.ObjectActuator attribute), 616
use_location (bpy.types.KinematicConstraint attribute), 483
use_location_x (bpy.types.ChildOfConstraint attribute), 240
use_location_y (bpy.types.ChildOfConstraint attribute), 240
use_location_z (bpy.types.ChildOfConstraint attribute), 240
use_locked_size (bpy.types.Brush attribute), 230
use_manipulator_rotate (bpy.types.SpaceView3D attribute), 838
use_manipulator_scale (bpy.types.SpaceView3D attribute), 838
use_manipulator_translate (bpy.types.SpaceView3D attribute), 838
use_map_alpha (bpy.types.MaterialTextureSlot attribute), 528
use_map_ambient (bpy.types.MaterialTextureSlot attribute), 528
use_map_blend (bpy.types.WorldTextureSlot attribute), 1021
use_map_clump (bpy.types.ParticleSettingsTextureSlot attribute), 663

use_map_color (bpy.types.LampTextureSlot attribute), 488
use_map_color_diffuse (bpy.types.MaterialTextureSlot attribute), 528
use_map_color_emission (bpy.types.MaterialTextureSlot attribute), 528
use_map_color_reflection (bpy.types.MaterialTextureSlot attribute), 528
use_map_color_spec (bpy.types.MaterialTextureSlot attribute), 528
use_map_color_transmission (bpy.types.MaterialTextureSlot attribute), 528
use_map_damp (bpy.types.ParticleSettingsTextureSlot attribute), 663
use_map_density (bpy.types.MaterialTextureSlot attribute), 528
use_map_density (bpy.types.ParticleSettingsTextureSlot attribute), 663
use_map_diffuse (bpy.types.MaterialTextureSlot attribute), 529
use_map_displacement (bpy.types.MaterialTextureSlot attribute), 529
use_map_emission (bpy.types.MaterialTextureSlot attribute), 529
use_map_emit (bpy.types.MaterialTextureSlot attribute), 529
use_map_field (bpy.types.ParticleSettingsTextureSlot attribute), 663
use_map_gravity (bpy.types.ParticleSettingsTextureSlot attribute), 663
use_map_hardness (bpy.types.MaterialTextureSlot attribute), 529
use_map_horizon (bpy.types.WorldTextureSlot attribute), 1022
use_map_kink (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_length (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_life (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_mirror (bpy.types.MaterialTextureSlot attribute), 529
use_map_normal (bpy.types.MaterialTextureSlot attribute), 529
use_map_raymir (bpy.types.MaterialTextureSlot attribute), 529
use_map_reflect (bpy.types.MaterialTextureSlot attribute), 529
use_map_rough (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_scatter (bpy.types.MaterialTextureSlot attribute), 529
use_map_shadow (bpy.types.LampTextureSlot attribute), 488
use_map_size (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_specular (bpy.types.MaterialTextureSlot attribute), 529
use_map_time (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_translucency (bpy.types.MaterialTextureSlot attribute), 529
use_map_velocity (bpy.types.ParticleSettingsTextureSlot attribute), 664
use_map_warp (bpy.types.MaterialTextureSlot attribute), 529
use_map_zenith_down (bpy.types.WorldTextureSlot attribute), 1022
use_map_zenith_up (bpy.types.WorldTextureSlot attribute), 1022
use_marker_sync (bpy.types.SpaceDopeSheetEditor attribute), 817
use_marker_sync (bpy.types.SpaceSequenceEditor attribute), 830
use_master_broadcast (bpy.types.NetRenderSettings attribute), 587
use_master_clear (bpy.types.NetRenderSettings attribute), 587
use_material (bpy.types.CollisionSensor attribute), 252
use_material_detect (bpy.types.ConstraintActuator attribute), 321
use_material_physics_fh (bpy.types.GameObjectSettings attribute), 418
use_max (bpy.types.CompositorNodeMapValue attribute), 293
use_max (bpy.types.ShaderNodeMapping attribute), 774
use_max (bpy.types.TexMapping attribute), 862
use_max_distance (bpy.types.FieldSettings attribute), 396
use_max_x (bpy.types.FModifierLimits attribute), 389
use_max_x (bpy.types.LimitLocationConstraint attribute), 496
use_max_x (bpy.types.LimitScaleConstraint attribute), 500
use_max_y (bpy.types.FModifierLimits attribute), 389
use_max_y (bpy.types.LimitLocationConstraint attribute), 496
use_max_y (bpy.types.LimitScaleConstraint attribute), 500
use_max_z (bpy.types.LimitLocationConstraint attribute), 496
use_max_z (bpy.types.LimitScaleConstraint attribute), 500
use_memory_cache (bpy.types.Sound attribute), 810
use_merge_vertices (bpy.types.ArrayModifier attribute), 174

use_merge_vertices_cap (bpy.types.ArrayModifier attribute), 174
use_mesh_automerge (bpy.types.ToolSettings attribute), 940
use_min (bpy.types.CompositorNodeMapValue attribute), 293
use_min (bpy.types.ShaderNodeMapping attribute), 774
use_min (bpy.types.TexMapping attribute), 863
use_min_distance (bpy.types.FieldSettings attribute), 396
use_min_x (bpy.types.FModifierLimits attribute), 389
use_min_x (bpy.types.LimitLocationConstraint attribute), 497
use_min_x (bpy.types.LimitScaleConstraint attribute), 500
use_min_y (bpy.types.FModifierLimits attribute), 390
use_min_y (bpy.types.LimitLocationConstraint attribute), 497
use_min_y (bpy.types.LimitScaleConstraint attribute), 500
use_min_z (bpy.types.LimitLocationConstraint attribute), 497
use_min_z (bpy.types.LimitScaleConstraint attribute), 500
use_mipmap (bpy.types.EnvironmentMapTexture attribute), 371
use_mipmap (bpy.types.ImageTexture attribute), 448
use_mipmap_gauss (bpy.types.EnvironmentMapTexture attribute), 371
use_mipmap_gauss (bpy.types.ImageTexture attribute), 448
use_mipmaps (bpy.types.UserPreferencesSystem attribute), 987
use_mirror_merge (bpy.types.MirrorModifier attribute), 568
use_mirror_topology (bpy.types.Mesh attribute), 539
use_mirror_u (bpy.types.MirrorModifier attribute), 568
use_mirror_v (bpy.types.MirrorModifier attribute), 569
use_mirror_vertex_groups (bpy.types.MirrorModifier attribute), 569
use_mirror_x (bpy.types.Armature attribute), 167
use_mirror_x (bpy.types.ImageTexture attribute), 448
use_mirror_x (bpy.types.Mesh attribute), 539
use_mirror_y (bpy.types.ImageTexture attribute), 448
use_mist (bpy.types.Material attribute), 513
use_mist (bpy.types.WorldMistSettings attribute), 1019
use_module (bpy.types.Text attribute), 864
use_motion_blur (bpy.types.Filter2DActuator attribute), 400
use_motion_blur (bpy.types.RenderSettings attribute), 727
use_motion_extrapolate (bpy.types.TransformConstraint attribute), 945
use_mouse_auto_depth (bpy.types.UserPreferencesView attribute), 990
use_mouse_continuous (bpy.types.UserPreferencesInput attribute), 984
use_mouse_emulate_3_button (bpy.types.UserPreferencesInput attribute), 984
use_mouse_mmb_paste (bpy.types.UserPreferencesInput attribute), 984
use_mouse_over_open (bpy.types.UserPreferencesView attribute), 991
use_multi_modifier (bpy.types.ArmatureModifier attribute), 172
use_multiple_springs (bpy.types.FieldSettings attribute), 396
use_multiply_size_mass (bpy.types.ParticleSettings attribute), 660
use_negative (bpy.types.Lamp attribute), 485
use_negative (bpy.types.MetaElement attribute), 565
use_negative_direction (bpy.types.ShrinkwrapModifier attribute), 795
use_negative_frames (bpy.types.UserPreferencesEdit attribute), 980
use_nla (bpy.types.AnimData attribute), 156
use_nodes (bpy.types.Material attribute), 513
use_nodes (bpy.types.Scene attribute), 737
use_nodes (bpy.types.Texture attribute), 873
use_normal (bpy.types.ConstraintActuator attribute), 321
use_normal (bpy.types.ParticleInstanceModifier attribute), 648
use_normal (bpy.types.VertexPaint attribute), 999
use_normal (bpy.types.WaveModifier attribute), 1007
use_normal_calculate (bpy.types.ScrewModifier attribute), 755
use_normal_falloff (bpy.types.ImagePaint attribute), 443
use_normal_flip (bpy.types.ScrewModifier attribute), 755
use_normal_map (bpy.types.ImageTexture attribute), 448
use_normal_x (bpy.types.WaveModifier attribute), 1007
use_normal_y (bpy.types.WaveModifier attribute), 1007
use_normal_z (bpy.types.WaveModifier attribute), 1007
use_object_color (bpy.types.Material attribute), 513
use_object_color (bpy.types.MeshTextureFace attribute), 555
use_object_coords (bpy.types.FieldSettings attribute), 396
use_object_offset (bpy.types.ArrayModifier attribute), 175
use_object_screw_offset (bpy.types.ScrewModifier attribute), 755
use_occlude (bpy.types.ImagePaint attribute), 443
use_occlude_geometry (bpy.types.SpaceView3D attribute), 838
use_occlusion (bpy.types.VisibilityActuator attribute), 1000
use_occlusion_culling (bpy.types.SceneGameData attribute), 744

use_offset (bpy.types.CopyLocationConstraint attribute), 327
use_offset (bpy.types.CopyRotationConstraint attribute), 329
use_offset (bpy.types.CopyScaleConstraint attribute), 330
use_offset_pressure (bpy.types.Brush attribute), 230
use_on_land (bpy.types.BoidRule attribute), 209
use_onion_skinning (bpy.types.GPencilLayer attribute), 410
use_only_boost (bpy.types.GlowSequence attribute), 424
use_only_selected_curves_handles (bpy.types.SpaceGraphEditor attribute), 819
use_only_selected_keyframe_handles (bpy.types.SpaceGraphEditor attribute), 819
use_only_shadow (bpy.types.AreaLamp attribute), 164
use_only_shadow (bpy.types.Material attribute), 513
use_only_shadow (bpy.types.PointLamp attribute), 684
use_only_shadow (bpy.types.SpotLamp attribute), 849
use_only_shadow (bpy.types.SunLamp attribute), 859
use_only_vertices (bpy.types.BevelModifier attribute), 177
use_original_normal (bpy.types.Brush attribute), 230
use_outflow (bpy.types.SmokeFlowSettings attribute), 800
use_outside (bpy.types.Lattice attribute), 491
use_overwrite (bpy.types.RenderSettings attribute), 727
use_overwrite (bpy.types.SpaceTextEditor attribute), 831
use_own_layer (bpy.types.Lamp attribute), 485
use_paint_mask (bpy.types.Mesh attribute), 539
use_paint_sculpt (bpy.types.Brush attribute), 230
use_paint_texture (bpy.types.Brush attribute), 230
use_paint_vertex (bpy.types.Brush attribute), 230
use_paint_weight (bpy.types.Brush attribute), 230
use_panorama (bpy.types.Camera attribute), 236
use_parent_particles (bpy.types.ParticleSettings attribute), 660
use_particle_kill (bpy.types.CollisionSettings attribute), 254
use_pass_ambient_occlusion (bpy.types.SceneRenderLayer attribute), 747
use_pass_color (bpy.types.SceneRenderLayer attribute), 747
use_pass_combined (bpy.types.SceneRenderLayer attribute), 747
use_pass_diffuse (bpy.types.SceneRenderLayer attribute), 747
use_pass_emit (bpy.types.SceneRenderLayer attribute), 747
use_pass_environment (bpy.types.SceneRenderLayer attribute), 747
use_pass_indirect (bpy.types.SceneRenderLayer attribute), 747
use_pass_mist (bpy.types.SceneRenderLayer attribute), 747
use_pass_normal (bpy.types.SceneRenderLayer attribute), 747
use_pass_object_index (bpy.types.SceneRenderLayer attribute), 747
use_pass_reflection (bpy.types.SceneRenderLayer attribute), 748
use_pass_refraction (bpy.types.SceneRenderLayer attribute), 748
use_pass_shadow (bpy.types.SceneRenderLayer attribute), 748
use_pass_specular (bpy.types.SceneRenderLayer attribute), 748
use_pass_uv (bpy.types.SceneRenderLayer attribute), 748
use_pass_vector (bpy.types.SceneRenderLayer attribute), 748
use_pass_z (bpy.types.SceneRenderLayer attribute), 748
use_path (bpy.types.Curve attribute), 334
use_path (bpy.types.ParticleInstanceModifier attribute), 648
use_path_follow (bpy.types.Curve attribute), 334
use_persistent (bpy.types.Brush attribute), 230
use_persistent (bpy.types.ConstraintActuator attribute), 321
use_pin_cloth (bpy.types.ClothSettings attribute), 247
use_pin_id (bpy.types.SpaceProperties attribute), 828
use_pivot_point_align (bpy.types.SpaceView3D attribute), 838
use_placeholder (bpy.types.RenderSettings attribute), 727
use_plane_trim (bpy.types.Brush attribute), 230
use_play_3d_editors (bpy.types.Screen attribute), 753
use_play_animation_editors (bpy.types.Screen attribute), 753
use_play_image_editors (bpy.types.Screen attribute), 753
use_play_node_editors (bpy.types.Screen attribute), 754
use_play_properties_editors (bpy.types.Screen attribute), 754
use_play_sequence_editors (bpy.types.Screen attribute), 754
use_play_top_left_3d_editor (bpy.types.Screen attribute), 754
use_positive_direction (bpy.types.ShrinkwrapModifier attribute), 795
use_predict (bpy.types.BoidRuleAvoid attribute), 211
use_predict (bpy.types.BoidRuleGoal attribute), 214
use_premultiply (bpy.types.CompositorNodeAlphaOver attribute), 260
use_premultiply (bpy.types.EffectSequence attribute), 363
use_premultiply (bpy.types.Image attribute), 440
use_premultiply (bpy.types.ImageSequence attribute), 445

use_premultiply (bpy.types.MetaSequence attribute), 567
use_premultiply (bpy.types.MovieSequence attribute), 575
use_premultiply (bpy.types.MulticamSequence attribute), 578
use_premultiply (bpy.types.SceneSequence attribute), 750
use_preserve_length (bpy.types.ParticleEdit attribute), 644
use_preserve_root (bpy.types.ParticleEdit attribute), 644
use_preserve_shape (bpy.types.ParticleInstanceModifier attribute), 648
use_pressure_jitter (bpy.types.Brush attribute), 230
use_pressure_size (bpy.types.Brush attribute), 230
use_pressure_spacing (bpy.types.Brush attribute), 231
use_pressure_strength (bpy.types.Brush attribute), 231
use_preview (bpy.types.CompositorNodeDefocus attribute), 277
use_preview_alpha (bpy.types.Texture attribute), 873
use_preview_images (bpy.types.UserPreferencesSystem attribute), 987
use_preview_range (bpy.types.Scene attribute), 737
use_priority (bpy.types.Controller attribute), 326
use_project_x (bpy.types.ShrinkwrapModifier attribute), 795
use_project_y (bpy.types.ShrinkwrapModifier attribute), 795
use_project_z (bpy.types.ShrinkwrapModifier attribute), 795
use_projection (bpy.types.ImagePaint attribute), 443
use_projector (bpy.types.CompositorNodeLensdist attribute), 289
use_proportional_edit_objects (bpy.types.ToolSettings attribute), 940
use_proxy (bpy.types.EffectSequence attribute), 363
use_proxy (bpy.types.ImageSequence attribute), 445
use_proxy (bpy.types.MetaSequence attribute), 567
use_proxy (bpy.types.MovieSequence attribute), 575
use_proxy (bpy.types.MulticamSequence attribute), 578
use_proxy (bpy.types.SceneSequence attribute), 750
use_proxy_custom_directory (bpy.types.EffectSequence attribute), 363
use_proxy_custom_directory (bpy.types.ImageSequence attribute), 445
use_proxy_custom_directory (bpy.types.MetaSequence attribute), 567
use_proxy_custom_directory (bpy.types.MovieSequence attribute), 575
use_proxy_custom_directory (bpy.types.MulticamSequence attribute), 578
use_proxy_custom_directory (bpy.types.SceneSequence attribute), 750
use_proxy_custom_file (bpy.types.EffectSequence attribute), 363
use_proxy_custom_file (bpy.types.ImageSequence attribute), 445
use_proxy_custom_file (bpy.types.MetaSequence attribute), 567
use_proxy_custom_file (bpy.types.MovieSequence attribute), 575
use_proxy_custom_file (bpy.types.MulticamSequence attribute), 578
use_proxy_custom_file (bpy.types.SceneSequence attribute), 751
use_puff_volume (bpy.types.ParticleBrush attribute), 641
use_pulse (bpy.types.CollisionSensor attribute), 252
use_pulse_false_level (bpy.types.Sensor attribute), 758
use_pulse_true_level (bpy.types.Sensor attribute), 758
use_quality_normals (bpy.types.SolidifyModifier attribute), 809
use_quick_cache (bpy.types.PointCache attribute), 678
use_radial_max (bpy.types.FieldSettings attribute), 396
use_radial_min (bpy.types.FieldSettings attribute), 397
use_radiosity (bpy.types.RenderSettings attribute), 727
use_radius (bpy.types.Curve attribute), 334
use_radius_as_size (bpy.types.CastModifier attribute), 238
use_rake (bpy.types.Brush attribute), 231
use_random_order (bpy.types.BuildModifier attribute), 233
use_random_rotation (bpy.types.Brush attribute), 231
use_ray_shadow_bias (bpy.types.Material attribute), 513
use_raytrace (bpy.types.Material attribute), 513
use_raytrace (bpy.types.RenderSettings attribute), 727
use_react_multiple (bpy.types.ParticleSettings attribute), 660
use_react_start_end (bpy.types.ParticleSettings attribute), 660
use_realtime_update (bpy.types.SpaceDopeSheetEditor attribute), 817
use_realtime_update (bpy.types.SpaceGraphEditor attribute), 819
use_realtime_update (bpy.types.SpaceImageEditor attribute), 821
use_realtime_update (bpy.types.SpaceNLA attribute), 824
use_record_with_nla (bpy.types.ToolSettings attribute), 940
use_relative (bpy.types.CompositorNodeBlur attribute), 262
use_relative (bpy.types.Key attribute), 458
use_relative (bpy.types.SimpleDeformModifier attribute), 796
use_relative_location (bpy.types.PivotConstraint attribute), 673

use_relative_offset (bpy.types.ArrayModifier attribute), 175
use_relative_paths (bpy.types.UserPreferencesFilePaths attribute), 982
use_render_adaptive (bpy.types.ParticleSettings attribute), 660
use_render_emitter (bpy.types.ParticleSettings attribute), 660
use_repeat (bpy.types.DelaySensor attribute), 343
use_replace_display_mesh (bpy.types.EditObjectActuator attribute), 361
use_replace_physics_mesh (bpy.types.EditObjectActuator attribute), 361
use_restore_mesh (bpy.types.Brush attribute), 231
use_reverse (bpy.types.NlaStrip attribute), 591
use_reverse_frames (bpy.types.ControlFluidSettings attribute), 325
use_reverse_frames (bpy.types.DomainFluidSettings attribute), 348
use_reverse_frames (bpy.types.EffectSequence attribute), 363
use_reverse_frames (bpy.types.ImageSequence attribute), 445
use_reverse_frames (bpy.types.MetaSequence attribute), 567
use_reverse_frames (bpy.types.MovieSequence attribute), 576
use_reverse_frames (bpy.types.MulticamSequence attribute), 578
use_reverse_frames (bpy.types.SceneSequence attribute), 751
use_rgb_to_intensity (bpy.types.TextureSlot attribute), 894
use_rim (bpy.types.SolidifyModifier attribute), 809
use_ring (bpy.types.MaterialHalo attribute), 517
use_root_coords (bpy.types.FieldSettings attribute), 397
use_rotate_45 (bpy.types.CompositorNodeGlare attribute), 284
use_rotate_around_active (bpy.types.UserPreferencesView attribute), 991
use_rotate_from_normal (bpy.types.GameObjectSettings attribute), 418
use_rotation (bpy.types.FloorConstraint attribute), 402
use_rotation (bpy.types.KinematicConstraint attribute), 483
use_rotation_x (bpy.types.ChildOfConstraint attribute), 240
use_rotation_y (bpy.types.ChildOfConstraint attribute), 240
use_rotation_z (bpy.types.ChildOfConstraint attribute), 241
use_save_buffers (bpy.types.RenderSettings attribute), 727
use_save_preview_images (bpy.types.UserPreferencesFilePaths attribute), 982
use_scale_x (bpy.types.ChildOfConstraint attribute), 241
use_scale_y (bpy.types.ChildOfConstraint attribute), 241
use_scale_z (bpy.types.ChildOfConstraint attribute), 241
use_scripts_auto_execute (bpy.types.UserPreferencesSystem attribute), 987
use_seam (bpy.types.MeshEdge attribute), 545
use_self_collision (bpy.types.ClothCollisionSettings attribute), 244
use_self_collision (bpy.types.SoftBodySettings attribute), 807
use_self_effect (bpy.types.ParticleSettings attribute), 660
use_separate (bpy.types.UnitSettings attribute), 975
use_sequencer (bpy.types.RenderSettings attribute), 727
use_sequencer_gl_preview (bpy.types.RenderSettings attribute), 728
use_sequencer_gl_render (bpy.types.RenderSettings attribute), 728
use_servo_limit_x (bpy.types.ObjectActuator attribute), 616
use_servo_limit_y (bpy.types.ObjectActuator attribute), 616
use_servo_limit_z (bpy.types.ObjectActuator attribute), 616
use_shaded (bpy.types.MaterialHalo attribute), 517
use_shadeless (bpy.types.Material attribute), 514
use_shadow_cast (bpy.types.MeshTextureFace attribute), 555
use_shadow_layer (bpy.types.AreaLamp attribute), 165
use_shadow_layer (bpy.types.PointLamp attribute), 684
use_shadow_layer (bpy.types.SpotLamp attribute), 850
use_shadow_layer (bpy.types.SunLamp attribute), 859
use_shadows (bpy.types.Material attribute), 514
use_shadows (bpy.types.RenderSettings attribute), 728
use_shape_key_edit_mode (bpy.types.Object attribute), 610
use_shape_match (bpy.types.GameSoftBodySettings attribute), 421
use_simplify (bpy.types.ParticleSettings attribute), 660
use_simplify (bpy.types.RenderSettings attribute), 728
use_simplify_triangulate (bpy.types.RenderSettings attribute), 728
use_simplify_viewport (bpy.types.ParticleSettings attribute), 661
use_single_layer (bpy.types.RenderSettings attribute), 728
use_size (bpy.types.ExplodeModifier attribute), 375
use_size (bpy.types.ParticleInstanceModifier attribute), 648

use_size_deflect (bpy.types.ParticleSettings attribute), 661
use_sky (bpy.types.LampSkySettings attribute), 487
use_sky (bpy.types.Material attribute), 514
use_sky (bpy.types.SceneRenderLayer attribute), 748
use_sky_blend (bpy.types.World attribute), 1015
use_sky_paper (bpy.types.World attribute), 1015
use_sky_real (bpy.types.World attribute), 1016
use_slave_clear (bpy.types.NetRenderSettings attribute), 587
use_slave_output_log (bpy.types.NetRenderSettings attribute), 587
use_slave_thumb (bpy.types.NetRenderSettings attribute), 588
use_sleep (bpy.types.GameObjectSettings attribute), 419
use_slow_parent (bpy.types.Object attribute), 610
use_small_caps (bpy.types.TextCharacterFormat attribute), 866
use_smooth (bpy.types.MeshFace attribute), 547
use_smooth (bpy.types.Spline attribute), 842
use_smooth_stroke (bpy.types.Brush attribute), 231
use_snap (bpy.types.ToolSettings attribute), 940
use_snap_align_rotation (bpy.types.ToolSettings attribute), 940
use_snap_peel_object (bpy.types.ToolSettings attribute), 940
use_snap_project (bpy.types.ToolSettings attribute), 940
use_snap_to_pixels (bpy.types.SpaceUVEditor attribute), 834
use_soft (bpy.types.MaterialHalo attribute), 517
use_solid (bpy.types.SceneRenderLayer attribute), 748
use_sound_3d (bpy.types.SoundActuator attribute), 811
use_space (bpy.types.Brush attribute), 231
use_space_atten (bpy.types.Brush attribute), 231
use_specular (bpy.types.Lamp attribute), 485
use_specular (bpy.types.ShaderNodeExtendedMaterial attribute), 771
use_specular (bpy.types.ShaderNodeMaterial attribute), 775
use_specular_ramp (bpy.types.Material attribute), 514
use_speed_vectors (bpy.types.DomainFluidSettings attribute), 348
use_sphere (bpy.types.PointLamp attribute), 684
use_sphere (bpy.types.SpotLamp attribute), 850
use_spray (bpy.types.VertexPaint attribute), 999
use_square (bpy.types.SpotLamp attribute), 850
use_sss (bpy.types.RenderSettings attribute), 728
use_stamp (bpy.types.RenderSettings attribute), 728
use_stamp_camera (bpy.types.RenderSettings attribute), 728
use_stamp_date (bpy.types.RenderSettings attribute), 728
use_stamp_filename (bpy.types.RenderSettings attribute), 728
use_stamp_frame (bpy.types.RenderSettings attribute), 728
use_stamp_lens (bpy.types.RenderSettings attribute), 728
use_stamp_marker (bpy.types.RenderSettings attribute), 728
use_stamp_note (bpy.types.RenderSettings attribute), 729
use_stamp_note (bpy.types.Scene attribute), 737
use_stamp_render_time (bpy.types.RenderSettings attribute), 729
use_stamp_scene (bpy.types.RenderSettings attribute), 729
use_stamp_sequencer_strip (bpy.types.RenderSettings attribute), 729
use_stamp_time (bpy.types.RenderSettings attribute), 729
use_star (bpy.types.MaterialHalo attribute), 517
use_stars (bpy.types.WorldStarsSettings attribute), 1020
use_stencil (bpy.types.TextureSlot attribute), 894
use_stencil_layer (bpy.types.ImagePaint attribute), 443
use_sticky (bpy.types.FloorConstraint attribute), 402
use_stiff_quads (bpy.types.SoftBodySettings attribute), 807
use_stiffness_scale (bpy.types.ClothSettings attribute), 247
use_still_frame (bpy.types.VoxelData attribute), 1004
use_strand (bpy.types.SceneRenderLayer attribute), 748
use_strand_primitive (bpy.types.ParticleSettings attribute), 661
use_stretch (bpy.types.Curve attribute), 334
use_stretch (bpy.types.KinematicConstraint attribute), 483
use_stroke_endpoints (bpy.types.GreasePencil attribute), 426
use_subsurf_uv (bpy.types.SubsurfModifier attribute), 857
use_symmetry_feather (bpy.types.Sculpt attribute), 756
use_symmetry_x (bpy.types.Sculpt attribute), 757
use_symmetry_y (bpy.types.Sculpt attribute), 757
use_symmetry_z (bpy.types.Sculpt attribute), 757
use_tabs_as_spaces (bpy.types.Text attribute), 864
use_tabs_as_spaces (bpy.types.UserPreferencesSystem attribute), 987
use_tail (bpy.types.KinematicConstraint attribute), 483
use_tangent_shading (bpy.types.Material attribute), 514
use_tangent_shading (bpy.types.MaterialStrand attribute), 523
use_tap (bpy.types.Sensor attribute), 758
use_target (bpy.types.KinematicConstraint attribute), 483
use_target_z (bpy.types.TrackToConstraint attribute), 943
use_targets (bpy.types.PythonConstraint attribute), 701
use_text_antialiasing (bpy.types.UserPreferencesSystem attribute), 987
use_texture (bpy.types.MaterialHalo attribute), 517
use_texture_overlay (bpy.types.Brush attribute), 231

use_textured_fonts (bpy.types.UserPreferencesSystem attribute), 987
use_textures (bpy.types.Material attribute), 514
use_textures (bpy.types.RenderSettings attribute), 729
use_threaded (bpy.types.Sculpt attribute), 757
use_tiff_16bit (bpy.types.RenderSettings attribute), 729
use_tiles (bpy.types.Image attribute), 441
use_time_offset (bpy.types.Curve attribute), 334
use_time_offset_add_parent (bpy.types.Object attribute), 610
use_time_offset_edit (bpy.types.Object attribute), 610
use_time_offset_parent (bpy.types.Object attribute), 610
use_time_offset_particle (bpy.types.Object attribute), 610
use_time_override (bpy.types.DomainFluidSettings attribute), 348
use_transform (bpy.types.CastModifier attribute), 238
use_transform_limit (bpy.types.LimitLocationConstraint attribute), 497
use_transform_limit (bpy.types.LimitRotationConstraint attribute), 498
use_transform_limit (bpy.types.LimitScaleConstraint attribute), 500
use_translate_buttons (bpy.types.UserPreferencesSystem attribute), 987
use_translate_toolbox (bpy.types.UserPreferencesSystem attribute), 987
use_translate_tooltips (bpy.types.UserPreferencesSystem attribute), 987
use_translation (bpy.types.EffectSequence attribute), 364
use_translation (bpy.types.ImageSequence attribute), 445
use_translation (bpy.types.MetaSequence attribute), 567
use_translation (bpy.types.MovieSequence attribute), 576
use_translation (bpy.types.MulticamSequence attribute), 578
use_translation (bpy.types.SceneSequence attribute), 751
use_transparency (bpy.types.Material attribute), 514
use_transparent_shadows (bpy.types.Material attribute), 514
use_turbulence (bpy.types.PointDensity attribute), 681
use_twoside (bpy.types.MeshTextureFace attribute), 555
use_umbra (bpy.types.AreaLamp attribute), 165
use_underline (bpy.types.TextCharacterFormat attribute), 866
use_uniform_scale (bpy.types.TransformSequence attribute), 947
use_unspill (bpy.types.CompositorNodeColorSpill attribute), 269
use_uv_as_generated (bpy.types.Curve attribute), 334
use_uv_as_generated (bpy.types.SurfaceCurve attribute), 860
use_uv_as_generated (bpy.types.TextCurve attribute), 869
use_uv_select_sync (bpy.types.ToolSettings attribute), 940
use_velocity_length (bpy.types.ParticleSettings attribute), 661
use_vertex_buffer_objects (bpy.types.UserPreferencesSystem attribute), 987
use_vertex_color_light (bpy.types.Material attribute), 514
use_vertex_color_paint (bpy.types.Material attribute), 514
use_vertex_groups (bpy.types.ArmatureModifier attribute), 172
use_vertex_normal (bpy.types.MaterialHalo attribute), 517
use_viscoelastic_springs (bpy.types.SPHFluidSettings attribute), 734
use_visible (bpy.types.VisibilityActuator attribute), 1000
use_visual_keying (bpy.types.UserPreferencesEdit attribute), 980
use_weight_color_range (bpy.types.UserPreferencesSystem attribute), 988
use_whole_group (bpy.types.ParticleSettings attribute), 661
use_wrap (bpy.types.Brush attribute), 231
use_wrap (bpy.types.CompositorNodeDBlur attribute), 276
use_x (bpy.types.CastModifier attribute), 238
use_x (bpy.types.CopyLocationConstraint attribute), 327
use_x (bpy.types.CopyRotationConstraint attribute), 329
use_x (bpy.types.CopyScaleConstraint attribute), 330
use_x (bpy.types.MirrorModifier attribute), 569
use_x (bpy.types.ShrinkwrapConstraint attribute), 793
use_x (bpy.types.SmoothModifier attribute), 802
use_x (bpy.types.WaveModifier attribute), 1007
use_x_ray (bpy.types.RaySensor attribute), 708
use_y (bpy.types.CastModifier attribute), 238
use_y (bpy.types.CopyLocationConstraint attribute), 327
use_y (bpy.types.CopyRotationConstraint attribute), 329
use_y (bpy.types.CopyScaleConstraint attribute), 330
use_y (bpy.types.MirrorModifier attribute), 569
use_y (bpy.types.ShrinkwrapConstraint attribute), 793
use_y (bpy.types.SmoothModifier attribute), 802
use_y (bpy.types.WaveModifier attribute), 1007
use_y_stretch (bpy.types.SplineIKConstraint attribute), 844
use_z (bpy.types.CastModifier attribute), 238
use_z (bpy.types.CopyLocationConstraint attribute), 327
use_z (bpy.types.CopyRotationConstraint attribute), 329
use_z (bpy.types.CopyScaleConstraint attribute), 330
use_z (bpy.types.MirrorModifier attribute), 569
use_z (bpy.types.ShrinkwrapConstraint attribute), 793
use_z (bpy.types.SmoothModifier attribute), 802
use_zbuffer (bpy.types.CompositorNodeDefocus attribute), 277
use_zmask (bpy.types.SceneRenderLayer attribute), 748

use_zoom_to_mouse (bpy.types.UserPreferencesView attribute), 991
use_ztransp (bpy.types.SceneRenderLayer attribute), 748
useAllKeys (bge.types.SCA_KeyboardSensor attribute), 1136
useChildren (bge.types.KX_IpoActuator attribute), 1105
useContinue (bge.types.BL_ActionActuator attribute), 1086
useDisplayMesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1123
useHighPriority (bge.types.SCA_IController attribute), 1085
useIpoAdd (bge.types.KX_IpoActuator attribute), 1105
useIpoAsForce (bge.types.KX_IpoActuator attribute), 1105
useIpoLocal (bge.types.KX_IpoActuator attribute), 1105
useLocalAngV (bge.types.KX_ObjectActuator attribute), 1112
useLocalDLoc (bge.types.KX_ObjectActuator attribute), 1111
useLocalDRot (bge.types.KX_ObjectActuator attribute), 1111
useLocalForce (bge.types.KX_ObjectActuator attribute), 1111
useLocalLinV (bge.types.KX_ObjectActuator attribute), 1111
useLocalTorque (bge.types.KX_ObjectActuator attribute), 1111
useMaterial (bge.types.KX_RaySensor attribute), 1120
useMaterial (bge.types.KX_TouchSensor attribute), 1109
useNegPulseMode (bge.types.SCA_ISensor attribute), 1084
useOcclusion (bge.types.KX_VisibilityActuator attribute), 1132
usePhysicsMesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1123
usePosPulseMode (bge.types.SCA_ISensor attribute), 1084
usePropBody (bge.types.KX_NetworkMessageActuator attribute), 1110
usePulseCollision (bge.types.KX_TouchSensor attribute), 1109
usePulseFocus (bge.types.KX_MouseFocusSensor attribute), 1109
user_clear() (bpy.types.ID method), 436
user_resource() (in module bpy.utils), 1030
user_script_path() (in module bpy.utils), 1030
useRecursion (bge.types.KX_VisibilityActuator attribute), 1133
useRestart (bge.types.KX_SceneActuator attribute), 1126
userjit (bpy.types.ParticleSettings attribute), 661
userpref_show() (in module bpy.ops.screen), 97
UserPreferences (class in bpy.types), 976
UserPreferences.addons (in module bpy.types), 976
UserPreferences.edit (in module bpy.types), 976
UserPreferences.filepaths (in module bpy.types), 976
UserPreferences.inputs (in module bpy.types), 976
UserPreferences.system (in module bpy.types), 976
UserPreferences.themes (in module bpy.types), 977
UserPreferences.ui_styles (in module bpy.types), 977
UserPreferences.view (in module bpy.types), 977
UserPreferencesEdit (class in bpy.types), 977
UserPreferencesFilePaths (class in bpy.types), 981
UserPreferencesInput (class in bpy.types), 983
UserPreferencesInput.edited_keymaps (in module bpy.types), 983
UserPreferencesSystem (class in bpy.types), 985
UserPreferencesSystem.solid_lights (in module bpy.types), 986
UserPreferencesSystem.weight_color_range (in module bpy.types), 988
UserPreferencesView (class in bpy.types), 988
UserSolidLight (class in bpy.types), 991
useViewport (bge.types.KX_Camera attribute), 1141
useXRay (bge.types.KX_RaySensor attribute), 1121
useXY (bge.types.KX_CameraActuator attribute), 1092
UV (bge.types.KX_VertexProxy attribute), 1130
uv (bpy.types.MeshTextureFace attribute), 555
uv1 (bpy.types.MeshTextureFace attribute), 555
uv2 (bpy.types.MeshTextureFace attribute), 555
uv3 (bpy.types.MeshTextureFace attribute), 556
uv4 (bpy.types.MeshTextureFace attribute), 556
uv_layer (bpy.types.DisplaceModifier attribute), 344
uv_layer (bpy.types.MaterialStrand attribute), 523
uv_layer (bpy.types.MaterialTextureSlot attribute), 529
uv_layer (bpy.types.ParticleSettingsTextureSlot attribute), 664
uv_layer (bpy.types.ShaderNodeGeometry attribute), 771
uv_layer (bpy.types.UVProjectModifier attribute), 972
uv_layer (bpy.types.WaveModifier attribute), 1007
uv_raw (bpy.types.MeshTextureFace attribute), 556
uv_select_mode (bpy.types.ToolSettings attribute), 940
uv_texture_add() (in module bpy.ops.mesh), 60
uv_texture_clone (bpy.types.Mesh attribute), 539
uv_texture_clone_index (bpy.types.Mesh attribute), 539
uv_texture_remove() (in module bpy.ops.mesh), 60
uv_texture_stencil (bpy.types.Mesh attribute), 539
uv_texture_stencil_index (bpy.types.Mesh attribute), 539
UVProjectModifier (class in bpy.types), 971
UVProjectModifier.projectors (in module bpy.types), 972
UVProjector (class in bpy.types), 973
uvs_mirror() (in module bpy.ops.mesh), 60
uvs_rotate() (in module bpy.ops.mesh), 60
UVTextures (class in bpy.types), 973

V

v (bge.types.KX_VertexProxy attribute), 1130
v (mathutils.Color attribute), 1040

v1 (bge.types.KX_PolyProxy attribute), 1113
v2 (bge.types.KX_PolyProxy attribute), 1113
v2 (bge.types.KX_VertexProxy attribute), 1131
v3 (bge.types.KX_PolyProxy attribute), 1113
v4 (bge.types.KX_PolyProxy attribute), 1113
validate() (bge.types.BL_Shader method), 1090
validate() (bpy.types.Mesh method), 540
value (bge.types.KX_ArmatureSensor attribute), 1146
value (bge.types.SCA_2DFilterActuator attribute), 1133
value (bge.types.SCA_PropertyActuator attribute), 1137
value (bge.types.SCA_PropertySensor attribute), 1137
value (bpy.types.ArmatureSensor attribute), 173
value (bpy.types.GameBooleanProperty attribute), 414
value (bpy.types.GameFloatProperty attribute), 414
value (bpy.types.GameIntProperty attribute), 415
value (bpy.types.GameStringProperty attribute), 422
value (bpy.types.GameTimerProperty attribute), 423
value (bpy.types.KeyMapItem attribute), 465
value (bpy.types.MeshFloatProperty attribute), 549
value (bpy.types.MeshIntProperty attribute), 550
value (bpy.types.MeshStringProperty attribute), 553
value (bpy.types.PropertyActuator attribute), 696
value (bpy.types.PropertySensor attribute), 699
value (bpy.types.ShapeKey attribute), 790
value_max (bpy.types.PropertySensor attribute), 699
value_min (bpy.types.PropertySensor attribute), 699
value_offset (bpy.types.FModifierFunctionGenerator attribute), 387
value_sliders (bpy.types.ThemeDopeSheet attribute), 902
ValueNodeSocket (class in bpy.types), 992
values() (bpy.types.bpy_struct method), 1029
vcs_revision (bpy.types.NetRenderSettings attribute), 588
vcs_rpath (bpy.types.NetRenderSettings attribute), 588
vcs_system (bpy.types.NetRenderSettings attribute), 588
vcs_wpath (bpy.types.NetRenderSettings attribute), 588
Vector (class in mathutils), 1048
Vector.angle() (in module mathutils), 1049
Vector.copy() (in module mathutils), 1049
Vector.difference() (in module mathutils), 1049
Vector.lerp() (in module mathutils), 1050
Vector.project() (in module mathutils), 1050
Vector.rotate() (in module mathutils), 1051
VectorFont (class in bpy.types), 993
VectorFont.filepath (in module bpy.types), 993
VectorFont.packed_file (in module bpy.types), 993
VectorNodeSocket (class in bpy.types), 994
vectorscope_alpha (bpy.types.Scopes attribute), 752
velocity (aud.Handle attribute), 1081
velocity (bge.types.KX_SoundActuator attribute), 1127
velocity (bpy.types.Particle attribute), 640
velocity (bpy.types.ParticleKey attribute), 649
velocity_factor (bpy.types.ParticleSettingsTextureSlot attribute), 664
velocity_factor (bpy.types.SmokeFlowSettings attribute), 800
velocity_max (bpy.types.GameObjectSettings attribute), 419
velocity_max (bpy.types.Itasc attribute), 456
velocity_min (bpy.types.GameObjectSettings attribute), 419
velocity_radius (bpy.types.ControlFluidSettings attribute), 325
velocity_strength (bpy.types.ControlFluidSettings attribute), 325
version (in module bpy.app), 1032
version_string (in module bpy.app), 1032
vertex (bpy.types.ThemeGraphEditor attribute), 908
vertex (bpy.types.ThemeImageEditor attribute), 910
vertex (bpy.types.ThemeView3D attribute), 932
vertex_add() (in module bpy.ops.curve), 25
vertex_cache_space (bpy.types.PointDensity attribute), 681
vertex_color_add() (in module bpy.ops.mesh), 60
vertex_color_dirt() (in module bpy.ops.paint), 84
vertex_color_remove() (in module bpy.ops.mesh), 60
vertex_color_set() (in module bpy.ops.paint), 84
vertex_group (bpy.types.ArmatureModifier attribute), 172
vertex_group (bpy.types.CastModifier attribute), 238
vertex_group (bpy.types.CurveModifier attribute), 339
vertex_group (bpy.types.DisplaceModifier attribute), 344
vertex_group (bpy.types.ExplodeModifier attribute), 375
vertex_group (bpy.types.HookModifier attribute), 434
vertex_group (bpy.types.Lattice attribute), 491
vertex_group (bpy.types.LatticeModifier attribute), 492
vertex_group (bpy.types.MaskModifier attribute), 508
vertex_group (bpy.types.MeshDeformModifier attribute), 544
vertex_group (bpy.types.ShapeKey attribute), 790
vertex_group (bpy.types.ShrinkwrapModifier attribute), 795
vertex_group (bpy.types.SimpleDeformModifier attribute), 796
vertex_group (bpy.types.SmoothModifier attribute), 802
vertex_group (bpy.types.SolidifyModifier attribute), 809
vertex_group (bpy.types.WaveModifier attribute), 1007
vertex_group_add() (in module bpy.ops.object), 79
vertex_group_assign() (in module bpy.ops.object), 79
vertex_group_bending (bpy.types.ClothSettings attribute), 247
vertex_group_blend() (in module bpy.ops.object), 80
vertex_group_clean() (in module bpy.ops.object), 80
vertex_group_clump (bpy.types.ParticleSystem attribute), 669
vertex_group_copy() (in module bpy.ops.object), 80
vertex_group_copy_to_linked() (in module bpy.ops.object), 80

vertex_group_copy_to_selected() (in module bpy.ops.object), 80
vertex_group_density (bpy.types.ParticleSystem attribute), 669
vertex_group_deselect() (in module bpy.ops.object), 80
vertex_group_field (bpy.types.ParticleSystem attribute), 669
vertex_group_goal (bpy.types.SoftBodySettings attribute), 807
vertex_group_invert() (in module bpy.ops.object), 80
vertex_group_kink (bpy.types.ParticleSystem attribute), 669
vertex_group_length (bpy.types.ParticleSystem attribute), 669
vertex_group_levels() (in module bpy.ops.object), 80
vertex_group_mass (bpy.types.ClothSettings attribute), 247
vertex_group_mass (bpy.types.SoftBodySettings attribute), 807
vertex_group_mirror() (in module bpy.ops.object), 80
vertex_group_move() (in module bpy.ops.object), 80
vertex_group_normalize() (in module bpy.ops.object), 81
vertex_group_normalize_all() (in module bpy.ops.object), 81
vertex_group_remove() (in module bpy.ops.object), 81
vertex_group_remove_from() (in module bpy.ops.object), 81
vertex_group_rotation (bpy.types.ParticleSystem attribute), 669
vertex_group_roughness_1 (bpy.types.ParticleSystem attribute), 669
vertex_group_roughness_2 (bpy.types.ParticleSystem attribute), 669
vertex_group_roughness_end (bpy.types.ParticleSystem attribute), 669
vertex_group_select() (in module bpy.ops.object), 81
vertex_group_set_active() (in module bpy.ops.object), 81
vertex_group_size (bpy.types.ParticleSystem attribute), 669
vertex_group_sort() (in module bpy.ops.object), 81
vertex_group_spring (bpy.types.SoftBodySettings attribute), 807
vertex_group_structural_stiffness (bpy.types.ClothSettings attribute), 248
vertex_group_tangent (bpy.types.ParticleSystem attribute), 669
vertex_group_velocity (bpy.types.ParticleSystem attribute), 669
vertex_group_weight (bpy.types.ToolSettings attribute), 940
vertex_normal (bpy.types.ThemeView3D attribute), 932
vertex_paint() (in module bpy.ops.paint), 84
vertex_paint_object (in module bpy.context), 4
vertex_paint_radial_control() (in module bpy.ops.paint), 85
vertex_paint_toggle() (in module bpy.ops.paint), 85
vertex_parent_set() (in module bpy.ops.object), 81
vertex_select (bpy.types.ThemeGraphEditor attribute), 908
vertex_select (bpy.types.ThemeImageEditor attribute), 910
vertex_select (bpy.types.ThemeView3D attribute), 932
vertex_size (bpy.types.ThemeGraphEditor attribute), 908
vertex_size (bpy.types.ThemeImageEditor attribute), 910
vertex_size (bpy.types.ThemeView3D attribute), 932
VertexColors (class in bpy.types), 995
VertexGroup (class in bpy.types), 996
VertexGroup.index (in module bpy.types), 996
VertexGroupElement (class in bpy.types), 997
VertexGroupElement.group (in module bpy.types), 997
VertexGroups (class in bpy.types), 998
VertexGroups.active (in module bpy.types), 998
VertexPaint (class in bpy.types), 999
vertexpaint_tool (bpy.types.Brush attribute), 231
vertices (bpy.types.MeshEdge attribute), 545
vertices (bpy.types.MeshFace attribute), 547
vertices_randomize() (in module bpy.ops.mesh), 60
vertices_raw (bpy.types.MeshFace attribute), 547
vertices_smooth() (in module bpy.ops.mesh), 60
vertices_sort() (in module bpy.ops.mesh), 60
view2d_grid_spacing_min (bpy.types.UserPreferencesView attribute), 991
view_all() (in module bpy.ops.action), 11
view_all() (in module bpy.ops.graph), 38
view_all() (in module bpy.ops.image), 42
view_all() (in module bpy.ops.node), 66
view_all() (in module bpy.ops.sequencer), 104
view_all() (in module bpy.ops.time), 113
view_all() (in module bpy.ops.view3d), 131
view_all_preview() (in module bpy.ops.sequencer), 104
view_axis (bpy.types.BackgroundImage attribute), 176
view_cancel() (in module bpy.ops.render), 94
view_center_camera() (in module bpy.ops.view3d), 131
view_center_cursor() (in module bpy.ops.view3d), 132
view_distance (bpy.types.RegionView3D attribute), 710
view_ghost_border() (in module bpy.ops.sequencer), 104
view_location (bpy.types.RegionView3D attribute), 710
view_orbit() (in module bpy.ops.view3d), 132
view_pan() (in module bpy.ops.image), 42
view_pan() (in module bpy.ops.view3d), 132
view_perspective (bpy.types.RegionView3D attribute), 710
view_persportho() (in module bpy.ops.view3d), 132
view_rotate_method (bpy.types.UserPreferencesInput attribute), 984
view_rotation (bpy.types.RegionView3D attribute), 710

view_selected() (in module bpy.ops.image), 42
view_selected() (in module bpy.ops.sequencer), 104
view_selected() (in module bpy.ops.view3d), 132
view_show() (in module bpy.ops.render), 94
view_sliders (bpy.types.ThemeDopeSheet attribute), 902
view_sliders (bpy.types.ThemeNLAEditor attribute), 914
view_toggle() (in module bpy.ops.sequencer), 104
view_type (bpy.types.SpaceSequenceEditor attribute), 830
view_zoom() (in module bpy.ops.image), 42
view_zoom_axis (bpy.types.UserPreferencesInput attribute), 984
view_zoom_in() (in module bpy.ops.image), 42
view_zoom_method (bpy.types.UserPreferencesInput attribute), 984
view_zoom_out() (in module bpy.ops.image), 42
view_zoom_ratio() (in module bpy.ops.image), 42
view_zoom_ratio() (in module bpy.ops.sequencer), 104
VIEWMATRIX (in module bge.logic), 1168
VIEWMATRIX_INVERSE (in module bge.logic), 1168
VIEWMATRIX_INVERSETRANSPOSE (in module bge.logic), 1168
VIEWMATRIX_TRANSPOSE (in module bge.logic), 1168
viewnumpad() (in module bpy.ops.view3d), 132
viewpoint_object (bpy.types.EnvironmentMap attribute), 369
viewport_display_mode (bpy.types.DomainFluidSettings attribute), 348
viewport_shade (bpy.types.SpaceView3D attribute), 838
virtual_parents (bpy.types.ParticleSettings attribute), 661
viscosity_base (bpy.types.DomainFluidSettings attribute), 348
viscosity_exponent (bpy.types.DomainFluidSettings attribute), 348
viscosity_preset (bpy.types.DomainFluidSettings attribute), 348
visibility (bge.types.KX_VisibilityActuator attribute), 1132
visibility_toggle() (in module bpy.ops.node), 66
visibility_toggle() (in module bpy.ops.outliner), 82
VisibilityActuator (class in bpy.types), 1000
visible (bge.types.KX_GameObject attribute), 1095
visible (bge.types.KX_PolyProxy attribute), 1114
visible (bge.types.SCA_PythonMouse attribute), 1084
visible_bases (in module bpy.context), 3, 5
visible_bones (in module bpy.context), 3
visible_objects (in module bpy.context), 3, 5
visible_pose_bones (in module bpy.context), 4
visual_transform_apply() (in module bpy.ops.object), 81
visual_transform_apply() (in module bpy.ops.pose), 91
VKEY (in module bge.events), 1174
volume (aud.Device attribute), 1075
volume (aud.Handle attribute), 1081
volume (bge.types.KX_SoundActuator attribute), 1126
volume (bpy.types.BoidState attribute), 218
volume (bpy.types.MaintainVolumeConstraint attribute), 505
volume (bpy.types.SoundActuator attribute), 811
volume (bpy.types.SoundSequence attribute), 813
volume (bpy.types.StretchToConstraint attribute), 852
volume_initialization (bpy.types.FluidFluidSettings attribute), 404
volume_initialization (bpy.types.InflowFluidSettings attribute), 451
volume_initialization (bpy.types.ObstacleFluidSettings attribute), 620
volume_initialization (bpy.types.OutflowFluidSettings attribute), 632
volume_maximum (aud.Handle attribute), 1081
volume_minimum (aud.Handle attribute), 1081
VoronoiTexture (class in bpy.types), 1001
VoronoiTexture.users_material (in module bpy.types), 1002
VoronoiTexture.users_object_modifier (in module bpy.types), 1002
vortex (bpy.types.EffectorWeights attribute), 366
vorticity (bpy.types.SmokeDomainSettings attribute), 799
VoxelData (class in bpy.types), 1003
VoxelDataTexture (class in bpy.types), 1004
VoxelDataTexture.image_user (in module bpy.types), 1005
VoxelDataTexture.users_material (in module bpy.types), 1005
VoxelDataTexture.users_object_modifier (in module bpy.types), 1005
VoxelDataTexture.voxel_data (in module bpy.types), 1005

W

w (mathutils.Quaternion attribute), 1048
w (mathutils.Vector attribute), 1052
wander (bpy.types.BoidRuleAverageSpeed attribute), 210
warp() (in module bpy.ops.transform), 121
warp_factor (bpy.types.MaterialTextureSlot attribute), 530
waveform_alpha (bpy.types.Scopes attribute), 752
waveform_mode (bpy.types.Scopes attribute), 752
WaveModifier (class in bpy.types), 1006
weight (bge.types.BL_ArmatureActuator attribute), 1145
weight (bpy.types.ArmatureActuator attribute), 169
weight (bpy.types.BezierSplinePoint attribute), 179
weight (bpy.types.KinematicConstraint attribute), 483
weight (bpy.types.ParticleHairKey attribute), 646
weight (bpy.types.SplinePoint attribute), 846
weight (bpy.types.VertexGroupElement attribute), 997
weight() (bpy.types.VertexGroup method), 996
weight_1 (bpy.types.VoronoiTexture attribute), 1002

weight_2 (bpy.types.VoronoiTexture attribute), 1002
weight_3 (bpy.types.VoronoiTexture attribute), 1002
weight_4 (bpy.types.VoronoiTexture attribute), 1002
weight_from_bones() (in module bpy.ops.paint), 85
weight_paint() (in module bpy.ops.paint), 85
weight_paint_object (in module bpy.context), 4
weight_paint_radial_control() (in module bpy.ops.paint), 85
weight_paint_toggle() (in module bpy.ops.paint), 85
weight_set() (in module bpy.ops.paint), 85
weight_set() (in module bpy.ops.particle), 87
weight_softbody (bpy.types.SplinePoint attribute), 846
weld() (in module bpy.ops.uv), 127
weld_threshold (bpy.types.GameSoftBodySettings attribute), 421
wheel_scroll_lines (bpy.types.UserPreferencesInput attribute), 984
WHEELDOWNMOUSE (in module bge.events), 1173
WHEELUPMOUSE (in module bge.events), 1173
white_level (bpy.types.CurveMapping attribute), 338
width (bpy.types.BevelModifier attribute), 177
width (bpy.types.TextBox attribute), 865
width (bpy.types.WaveModifier attribute), 1007
width_fade (bpy.types.MaterialStrand attribute), 523
wind (bpy.types.EffectorWeights attribute), 366
Window (class in bpy.types), 1008
window_draw_method (bpy.types.UserPreferencesSystem attribute), 988
window_duplicate() (in module bpy.ops.wm), 142
window_fullscreen_toggle() (in module bpy.ops.wm), 142
window_sliders (bpy.types.ThemeAudioWindow attribute), 897
window_sliders (bpy.types.ThemeGraphEditor attribute), 908
window_sliders (bpy.types.ThemeSequenceEditor attribute), 921
WindowManager (class in bpy.types), 1009
WindowManager.keyconfigs (in module bpy.types), 1009
WindowManager.operators (in module bpy.types), 1009
WindowManager.windows (in module bpy.types), 1009
WipeSequence (class in bpy.types), 1011
wire (bpy.types.ThemeNodeEditor attribute), 916
wire (bpy.types.ThemeView3D attribute), 932
wire_select (bpy.types.ThemeNodeEditor attribute), 916
WKEY (in module bge.events), 1174
wood_type (bpy.types.WoodTexture attribute), 1013
WoodTexture (class in bpy.types), 1013
WoodTexture.users_material (in module bpy.types), 1013
WoodTexture.users_object_modifier (in module bpy.types), 1013
world (bpy.types.Scene attribute), 737
World (class in bpy.types), 1015
world (in module bpy.context), 5
World.animation_data (in module bpy.types), 1015
World.light_settings (in module bpy.types), 1015
World.mist_settings (in module bpy.types), 1015
World.star_settings (in module bpy.types), 1015
World.texture_slots (in module bpy.types), 1015
world_to_camera (bge.types.KX_Camera attribute), 1141
worldAngularVelocity (bge.types.KX_GameObject attribute), 1096
WorldLighting (class in bpy.types), 1017
worldLinearVelocity (bge.types.KX_GameObject attribute), 1096
WorldMistSettings (class in bpy.types), 1019
worldOrientation (bge.types.KX_GameObject attribute), 1095
worldPosition (bge.types.KX_GameObject attribute), 1096
worldScale (bge.types.KX_GameObject attribute), 1095
WorldStarsSettings (class in bpy.types), 1020
WorldTextureSlot (class in bpy.types), 1021
WorldTextureSlots (class in bpy.types), 1023
wrap_method (bpy.types.ShrinkwrapModifier attribute), 795
write() (bpy.types.Text method), 864
ww (mathutils.Vector attribute), 1052
www (mathutils.Vector attribute), 1052
wwww (mathutils.Vector attribute), 1052
wwwx (mathutils.Vector attribute), 1052
wwwy (mathutils.Vector attribute), 1052
wwwz (mathutils.Vector attribute), 1052
wwx (mathutils.Vector attribute), 1052
wwxw (mathutils.Vector attribute), 1052
wwxx (mathutils.Vector attribute), 1052
wwxy (mathutils.Vector attribute), 1052
wwxz (mathutils.Vector attribute), 1052
wwy (mathutils.Vector attribute), 1052
wwyw (mathutils.Vector attribute), 1053
wwyx (mathutils.Vector attribute), 1053
wwyy (mathutils.Vector attribute), 1053
wwyz (mathutils.Vector attribute), 1053
wwz (mathutils.Vector attribute), 1053
wwzw (mathutils.Vector attribute), 1053
wwzx (mathutils.Vector attribute), 1053
wwzy (mathutils.Vector attribute), 1053
wwzz (mathutils.Vector attribute), 1053
wx (mathutils.Vector attribute), 1053
wxw (mathutils.Vector attribute), 1053
wxww (mathutils.Vector attribute), 1053
wxwx (mathutils.Vector attribute), 1053
wxwy (mathutils.Vector attribute), 1053
wxwz (mathutils.Vector attribute), 1053
wxx (mathutils.Vector attribute), 1053
wxxw (mathutils.Vector attribute), 1053
wxxx (mathutils.Vector attribute), 1053
wxxy (mathutils.Vector attribute), 1053

wxxz (mathutils.Vector attribute), 1053
wxy (mathutils.Vector attribute), 1053
wxyw (mathutils.Vector attribute), 1054
wxyx (mathutils.Vector attribute), 1054
wxyy (mathutils.Vector attribute), 1054
wxyz (mathutils.Vector attribute), 1054
wxz (mathutils.Vector attribute), 1054
wxzw (mathutils.Vector attribute), 1054
wxzx (mathutils.Vector attribute), 1054
wxzy (mathutils.Vector attribute), 1054
wxzz (mathutils.Vector attribute), 1054
wy (mathutils.Vector attribute), 1054
wyw (mathutils.Vector attribute), 1054
wyww (mathutils.Vector attribute), 1054
wywx (mathutils.Vector attribute), 1054
wywy (mathutils.Vector attribute), 1054
wywz (mathutils.Vector attribute), 1054
wyx (mathutils.Vector attribute), 1054
wyxw (mathutils.Vector attribute), 1054
wyxx (mathutils.Vector attribute), 1054
wyxy (mathutils.Vector attribute), 1054
wyxz (mathutils.Vector attribute), 1054
wyy (mathutils.Vector attribute), 1054
wyyw (mathutils.Vector attribute), 1055
wyyx (mathutils.Vector attribute), 1055
wyyy (mathutils.Vector attribute), 1055
wyyz (mathutils.Vector attribute), 1055
wyz (mathutils.Vector attribute), 1055
wyzw (mathutils.Vector attribute), 1055
wyzx (mathutils.Vector attribute), 1055
wyzy (mathutils.Vector attribute), 1055
wyzz (mathutils.Vector attribute), 1055
wz (mathutils.Vector attribute), 1055
wzw (mathutils.Vector attribute), 1055
wzww (mathutils.Vector attribute), 1055
wzwx (mathutils.Vector attribute), 1055
wzwy (mathutils.Vector attribute), 1055
wzwz (mathutils.Vector attribute), 1055
wzx (mathutils.Vector attribute), 1055
wzxw (mathutils.Vector attribute), 1055
wzxx (mathutils.Vector attribute), 1055
wzxy (mathutils.Vector attribute), 1055
wzxz (mathutils.Vector attribute), 1055
wzy (mathutils.Vector attribute), 1055
wzyw (mathutils.Vector attribute), 1056
wzyx (mathutils.Vector attribute), 1056
wzyy (mathutils.Vector attribute), 1056
wzyz (mathutils.Vector attribute), 1056
wzz (mathutils.Vector attribute), 1056
wzzw (mathutils.Vector attribute), 1056
wzzx (mathutils.Vector attribute), 1056
wzzy (mathutils.Vector attribute), 1056
wzzz (mathutils.Vector attribute), 1056

X

x (bge.types.KX_VertexProxy attribute), 1130
x (bpy.types.TextBox attribute), 865
x (mathutils.Euler attribute), 1041
x (mathutils.Quaternion attribute), 1048
x (mathutils.Vector attribute), 1056
x3d() (in module bpy.ops.export_scene), 28
x3d() (in module bpy.ops.import_scene), 44
XKEY (in module bge.events), 1174
XnorController (class in bpy.types), 1024
XorController (class in bpy.types), 1025
xw (mathutils.Vector attribute), 1056
xww (mathutils.Vector attribute), 1056
xwww (mathutils.Vector attribute), 1056
xwwx (mathutils.Vector attribute), 1056
xwwy (mathutils.Vector attribute), 1056
xwwz (mathutils.Vector attribute), 1056
xwx (mathutils.Vector attribute), 1056
xwxw (mathutils.Vector attribute), 1056
xwxx (mathutils.Vector attribute), 1056
xwxy (mathutils.Vector attribute), 1056
xwxz (mathutils.Vector attribute), 1056
xwy (mathutils.Vector attribute), 1057
xwyw (mathutils.Vector attribute), 1057
xwyx (mathutils.Vector attribute), 1057
xwyy (mathutils.Vector attribute), 1057
xwyz (mathutils.Vector attribute), 1057
xwz (mathutils.Vector attribute), 1057
xwzw (mathutils.Vector attribute), 1057
xwzx (mathutils.Vector attribute), 1057
xwzy (mathutils.Vector attribute), 1057
xwzz (mathutils.Vector attribute), 1057
xx (mathutils.Vector attribute), 1057
xxw (mathutils.Vector attribute), 1057
xxww (mathutils.Vector attribute), 1057
xxwx (mathutils.Vector attribute), 1057
xxwy (mathutils.Vector attribute), 1057
xxwz (mathutils.Vector attribute), 1057
xxx (mathutils.Vector attribute), 1057
xxxw (mathutils.Vector attribute), 1057
xxxx (mathutils.Vector attribute), 1057
xxxy (mathutils.Vector attribute), 1057
xxxz (mathutils.Vector attribute), 1057
xxy (mathutils.Vector attribute), 1058
xxyw (mathutils.Vector attribute), 1058
xxyx (mathutils.Vector attribute), 1058
xxyy (mathutils.Vector attribute), 1058
xxyz (mathutils.Vector attribute), 1058
xxz (mathutils.Vector attribute), 1058
xxzw (mathutils.Vector attribute), 1058
xxzx (mathutils.Vector attribute), 1058
xxzy (mathutils.Vector attribute), 1058
xxzz (mathutils.Vector attribute), 1058
xy (mathutils.Vector attribute), 1058

xyw (mathutils.Vector attribute), 1058
xyww (mathutils.Vector attribute), 1058
xywx (mathutils.Vector attribute), 1058
xywy (mathutils.Vector attribute), 1058
xywz (mathutils.Vector attribute), 1058
xyx (mathutils.Vector attribute), 1058
xyxw (mathutils.Vector attribute), 1058
xyxx (mathutils.Vector attribute), 1058
xyxy (mathutils.Vector attribute), 1058
xyxz (mathutils.Vector attribute), 1058
xyy (mathutils.Vector attribute), 1059
xyyw (mathutils.Vector attribute), 1059
xyyx (mathutils.Vector attribute), 1059
xyyy (mathutils.Vector attribute), 1059
xyyz (mathutils.Vector attribute), 1059
XYZ (bge.types.KX_VertexProxy attribute), 1130
xyz (mathutils.Vector attribute), 1059
xyzw (mathutils.Vector attribute), 1059
xyzx (mathutils.Vector attribute), 1059
xyzy (mathutils.Vector attribute), 1059
xyzz (mathutils.Vector attribute), 1059
xz (mathutils.Vector attribute), 1059
xz_scale_mode (bpy.types.SplineIKConstraint attribute), 845
xzw (mathutils.Vector attribute), 1059
xzww (mathutils.Vector attribute), 1059
xzwx (mathutils.Vector attribute), 1059
xzwy (mathutils.Vector attribute), 1059
xzwz (mathutils.Vector attribute), 1059
xzx (mathutils.Vector attribute), 1059
xzxw (mathutils.Vector attribute), 1059
xzxx (mathutils.Vector attribute), 1059
xzxy (mathutils.Vector attribute), 1059
xzxz (mathutils.Vector attribute), 1059
xzy (mathutils.Vector attribute), 1060
xzyw (mathutils.Vector attribute), 1060
xzyx (mathutils.Vector attribute), 1060
xzyy (mathutils.Vector attribute), 1060
xzyz (mathutils.Vector attribute), 1060
xzz (mathutils.Vector attribute), 1060
xzzw (mathutils.Vector attribute), 1060
xzzx (mathutils.Vector attribute), 1060
xzzy (mathutils.Vector attribute), 1060
xzzz (mathutils.Vector attribute), 1060

Y

y (bge.types.KX_VertexProxy attribute), 1130
y (bpy.types.TextBox attribute), 865
y (mathutils.Euler attribute), 1041
y (mathutils.Quaternion attribute), 1048
y (mathutils.Vector attribute), 1060
yield_ratio (bpy.types.SPHFluidSettings attribute), 734
YKEY (in module bge.events), 1174
yw (mathutils.Vector attribute), 1060
yww (mathutils.Vector attribute), 1060
ywww (mathutils.Vector attribute), 1060
ywwx (mathutils.Vector attribute), 1060
ywwy (mathutils.Vector attribute), 1060
ywwz (mathutils.Vector attribute), 1060
ywx (mathutils.Vector attribute), 1060
ywxw (mathutils.Vector attribute), 1060
ywxx (mathutils.Vector attribute), 1060
ywxy (mathutils.Vector attribute), 1060
ywxz (mathutils.Vector attribute), 1061
ywy (mathutils.Vector attribute), 1061
ywyw (mathutils.Vector attribute), 1061
ywyx (mathutils.Vector attribute), 1061
ywyy (mathutils.Vector attribute), 1061
ywyz (mathutils.Vector attribute), 1061
ywz (mathutils.Vector attribute), 1061
ywzw (mathutils.Vector attribute), 1061
ywzx (mathutils.Vector attribute), 1061
ywzy (mathutils.Vector attribute), 1061
ywzz (mathutils.Vector attribute), 1061
yx (mathutils.Vector attribute), 1061
yxw (mathutils.Vector attribute), 1061
yxww (mathutils.Vector attribute), 1061
yxwx (mathutils.Vector attribute), 1061
yxwy (mathutils.Vector attribute), 1061
yxwz (mathutils.Vector attribute), 1061
yxx (mathutils.Vector attribute), 1061
yxxw (mathutils.Vector attribute), 1061
yxxx (mathutils.Vector attribute), 1061
yxxy (mathutils.Vector attribute), 1061
yxxz (mathutils.Vector attribute), 1062
yxy (mathutils.Vector attribute), 1062
yxyw (mathutils.Vector attribute), 1062
yxyx (mathutils.Vector attribute), 1062
yxyy (mathutils.Vector attribute), 1062
yxyz (mathutils.Vector attribute), 1062
yxz (mathutils.Vector attribute), 1062
yxzw (mathutils.Vector attribute), 1062
yxzx (mathutils.Vector attribute), 1062
yxzy (mathutils.Vector attribute), 1062
yxzz (mathutils.Vector attribute), 1062
yy (mathutils.Vector attribute), 1062
yyw (mathutils.Vector attribute), 1062
yyww (mathutils.Vector attribute), 1062
yywx (mathutils.Vector attribute), 1062
yywy (mathutils.Vector attribute), 1062
yywz (mathutils.Vector attribute), 1062
yyx (mathutils.Vector attribute), 1062
yyxw (mathutils.Vector attribute), 1062
yyxx (mathutils.Vector attribute), 1062
yyxy (mathutils.Vector attribute), 1062
yyxz (mathutils.Vector attribute), 1063
yyy (mathutils.Vector attribute), 1063
yyyw (mathutils.Vector attribute), 1063

yyyx (mathutils.Vector attribute), 1063
yyyy (mathutils.Vector attribute), 1063
yyyz (mathutils.Vector attribute), 1063
yyz (mathutils.Vector attribute), 1063
yyzw (mathutils.Vector attribute), 1063
yyzx (mathutils.Vector attribute), 1063
yyzy (mathutils.Vector attribute), 1063
yyzz (mathutils.Vector attribute), 1063
yz (mathutils.Vector attribute), 1063
yzw (mathutils.Vector attribute), 1063
yzww (mathutils.Vector attribute), 1063
yzwx (mathutils.Vector attribute), 1063
yzwy (mathutils.Vector attribute), 1063
yzwz (mathutils.Vector attribute), 1063
yzx (mathutils.Vector attribute), 1063
yzxw (mathutils.Vector attribute), 1063
yzxx (mathutils.Vector attribute), 1063
yzxy (mathutils.Vector attribute), 1063
yzxz (mathutils.Vector attribute), 1064
yzy (mathutils.Vector attribute), 1064
yzyw (mathutils.Vector attribute), 1064
yzyx (mathutils.Vector attribute), 1064
yzyy (mathutils.Vector attribute), 1064
yzyz (mathutils.Vector attribute), 1064
yzz (mathutils.Vector attribute), 1064
yzzw (mathutils.Vector attribute), 1064
yzzx (mathutils.Vector attribute), 1064
yzzy (mathutils.Vector attribute), 1064
yzzz (mathutils.Vector attribute), 1064

Z

z (bge.types.KX_VertexProxy attribute), 1130
z (mathutils.Euler attribute), 1041
z (mathutils.Quaternion attribute), 1048
z (mathutils.Vector attribute), 1064
z_direction (bpy.types.FieldSettings attribute), 397
z_scale (bpy.types.CompositorNodeDefocus attribute), 277
zenith_color (bpy.types.World attribute), 1016
zenith_down_factor (bpy.types.WorldTextureSlot attribute), 1022
zenith_up_factor (bpy.types.WorldTextureSlot attribute), 1022
zero() (mathutils.Euler method), 1041
zero() (mathutils.Matrix method), 1045
zero() (mathutils.Vector method), 1052
ZEROKEY (in module bge.events), 1174
ZKEY (in module bge.events), 1174
zoom (bpy.types.CompositorNodeDBlur attribute), 276
zoom (bpy.types.EnvironmentMap attribute), 369
zoom (bpy.types.SpaceSequenceEditor attribute), 830
zoom() (in module bpy.ops.view2d), 128
zoom() (in module bpy.ops.view3d), 132
zoom_border() (in module bpy.ops.view2d), 128
zoom_border() (in module bpy.ops.view3d), 132
zoom_camera_1_to_1() (in module bpy.ops.view3d), 132
zoom_in() (in module bpy.ops.view2d), 128
zoom_out() (in module bpy.ops.view2d), 128
zsort (bge.types.KX_PolygonMaterial attribute), 1118
zw (mathutils.Vector attribute), 1064
zww (mathutils.Vector attribute), 1064
zwww (mathutils.Vector attribute), 1064
zwwx (mathutils.Vector attribute), 1064
zwwy (mathutils.Vector attribute), 1064
zwwz (mathutils.Vector attribute), 1064
zwx (mathutils.Vector attribute), 1064
zwxw (mathutils.Vector attribute), 1064
zwxx (mathutils.Vector attribute), 1064
zwxy (mathutils.Vector attribute), 1065
zwxz (mathutils.Vector attribute), 1065
zwy (mathutils.Vector attribute), 1065
zwyw (mathutils.Vector attribute), 1065
zwyx (mathutils.Vector attribute), 1065
zwyy (mathutils.Vector attribute), 1065
zwyz (mathutils.Vector attribute), 1065
zwz (mathutils.Vector attribute), 1065
zwzw (mathutils.Vector attribute), 1065
zwzx (mathutils.Vector attribute), 1065
zwzy (mathutils.Vector attribute), 1065
zwzz (mathutils.Vector attribute), 1065
zx (mathutils.Vector attribute), 1065
zxw (mathutils.Vector attribute), 1065
zxww (mathutils.Vector attribute), 1065
zxwx (mathutils.Vector attribute), 1065
zxwy (mathutils.Vector attribute), 1065
zxwz (mathutils.Vector attribute), 1065
zxx (mathutils.Vector attribute), 1065
zxxw (mathutils.Vector attribute), 1065
zxxx (mathutils.Vector attribute), 1065
zxxy (mathutils.Vector attribute), 1066
zxxz (mathutils.Vector attribute), 1066
zxy (mathutils.Vector attribute), 1066
zxyw (mathutils.Vector attribute), 1066
zxyx (mathutils.Vector attribute), 1066
zxyy (mathutils.Vector attribute), 1066
zxyz (mathutils.Vector attribute), 1066
zxz (mathutils.Vector attribute), 1066
zxzw (mathutils.Vector attribute), 1066
zxzx (mathutils.Vector attribute), 1066
zxzy (mathutils.Vector attribute), 1066
zxzz (mathutils.Vector attribute), 1066
zy (mathutils.Vector attribute), 1066
zyw (mathutils.Vector attribute), 1066
zyww (mathutils.Vector attribute), 1066
zywx (mathutils.Vector attribute), 1066
zywy (mathutils.Vector attribute), 1066
zywz (mathutils.Vector attribute), 1066
zyx (mathutils.Vector attribute), 1066

zyxw (mathutils.Vector attribute), 1066
zyxx (mathutils.Vector attribute), 1066
zyxy (mathutils.Vector attribute), 1067
zyxz (mathutils.Vector attribute), 1067
zyy (mathutils.Vector attribute), 1067
zyyw (mathutils.Vector attribute), 1067
zyyx (mathutils.Vector attribute), 1067
zyyy (mathutils.Vector attribute), 1067
zyyz (mathutils.Vector attribute), 1067
zyz (mathutils.Vector attribute), 1067
zyzw (mathutils.Vector attribute), 1067
zyzx (mathutils.Vector attribute), 1067
zyzy (mathutils.Vector attribute), 1067
zyzz (mathutils.Vector attribute), 1067
zz (mathutils.Vector attribute), 1067
zzw (mathutils.Vector attribute), 1067
zzww (mathutils.Vector attribute), 1067
zzwx (mathutils.Vector attribute), 1067
zzwy (mathutils.Vector attribute), 1067
zzwz (mathutils.Vector attribute), 1067
zzx (mathutils.Vector attribute), 1067
zzxw (mathutils.Vector attribute), 1067
zzxx (mathutils.Vector attribute), 1067
zzxy (mathutils.Vector attribute), 1068
zzxz (mathutils.Vector attribute), 1068
zzy (mathutils.Vector attribute), 1068
zzyw (mathutils.Vector attribute), 1068
zzyx (mathutils.Vector attribute), 1068
zzyy (mathutils.Vector attribute), 1068
zzyz (mathutils.Vector attribute), 1068
zzz (mathutils.Vector attribute), 1068
zzzw (mathutils.Vector attribute), 1068
zzzx (mathutils.Vector attribute), 1068
zzzy (mathutils.Vector attribute), 1068
zzzz (mathutils.Vector attribute), 1068