
Blender Index

Release 2.58.1 - API

Blender Foundation

July 01, 2011

CONTENTS

1	Blender/Python Documentation	3
2	Application Modules	5
2.1	Context Access (bpy.context)	5
2.2	Data Access (bpy.data)	9
2.3	Operators (bpy.ops)	10
2.4	Types (bpy.types)	146
2.5	Utilities (bpy.utils)	1044
2.6	Path Utilities (bpy.path)	1046
2.7	Application Data (bpy.app)	1047
2.8	Property Definitions (bpy.props)	1048
3	Standalone Modules	1055
3.1	Math Types & Utilities (mathutils)	1055
3.2	Geometry Utilities (mathutils.geometry)	1084
3.3	bgl module (OpenGL wrapper)	1088
3.4	Font Drawing (blf)	1118
3.5	Audio System (aud)	1120
3.6	Extra Utilities (bpy_extras)	1129
4	Game Engine Modules	1133
4.1	Game Engine bge.types Module	1133
4.2	Game Engine bge.logic Module	1205
4.3	Game Engine bge.render Module	1219
4.4	Game Engine bge.events module	1222
5	API Info	1227
5.1	Blender API Change Log	1227
Python Module Index		1245
Index		1247

Welcome, this document is an API reference for Blender 2.58.1. built Unknown.

A PDF version of this document is also available

BLENDER/PYTHON DOCUMENTATION

- [Quickstart Intro](#) if you are new to scripting in blender and want to get you're feet wet!
- [Blender/Python Overview](#) for a more complete explanation of python integration in blender

APPLICATION MODULES

2.1 Context Access (`bpy.context`)

The context members available depend on the area of blender which is currently being accessed.

Note that all context values are readonly, but may be modified through the data api or by running operators

2.1.1 Screen Context

```
bpy.context.scene
    Type bpy.types.Scene
bpy.context.visible_objects
    Type sequence of bpy.types.Object
bpy.context.visible_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.selectable_objects
    Type sequence of bpy.types.Object
bpy.context.selectable_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.selected_objects
    Type sequence of bpy.types.Object
bpy.context.selected_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.selected_editable_objects
    Type sequence of bpy.types.Object
bpy.context.selected_editable_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.visible_bones
    Type sequence of bpy.types.Object
bpy.context.editable_bones
```

Type sequence of `bpy.types.EditBone`
`bpy.context.selected_bones`

Type sequence of `bpy.types.Bone`
`bpy.context.selected_editable_bones`

Type sequence of `bpy.types.Bone`
`bpy.context.visible_pose_bones`

Type sequence of `bpy.types.PoseBone`
`bpy.context.selected_pose_bones`

Type sequence of `bpy.types.PoseBone`
`bpy.context.active_bone`

Type `bpy.types.Bone`
`bpy.context.active_pose_bone`

Type `bpy.types.PoseBone`
`bpy.context.active_base`

Type `bpy.types.ObjectBase`
`bpy.context.active_object`

Type `bpy.types.Object`
`bpy.context.object`

Type `bpy.types.Object`
`bpy.context.edit_object`

Type `bpy.types.Object`
`bpy.context.sculpt_object`

Type `bpy.types.Object`
`bpy.context.vertex_paint_object`

Type `bpy.types.Object`
`bpy.context.weight_paint_object`

Type `bpy.types.Object`
`bpy.context.image_paint_object`

Type `bpy.types.Object`
`bpy.context.particle_edit_object`

Type `bpy.types.Object`
`bpy.context.sequences`

Type sequence of `bpy.types.Sequence`
`bpy.context.selected_sequences`

Type sequence of `bpy.types.Sequence`
`bpy.context.selected_editable_sequences`

Type sequence of `bpy.types.Sequence`

2.1.2 View3D Context

```
bpy.context.selected_objects
    Type sequence of bpy.types.Object
bpy.context.selected_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.selected_editable_objects
    Type sequence of bpy.types.Object
bpy.context.selected_editable_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.visible_objects
    Type sequence of bpy.types.Object
bpy.context.visible_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.selectable_objects
    Type sequence of bpy.types.Object
bpy.context.selectable_bases
    Type sequence of bpy.types.ObjectBase
bpy.context.active_base
    Type bpy.types.ObjectBase
bpy.context.active_object
    Type bpy.types.Object
```

2.1.3 Buttons Context

```
bpy.context.world
    Type bpy.types.World
bpy.context.object
    Type bpy.types.Object
bpy.context.mesh
    Type bpy.types.Mesh
bpy.context.armature
    Type bpy.types.Armature
bpy.context.lattice
    Type bpy.types.Lattice
bpy.context.curve
```

```
Type bpy.types.Curve
bpy.context.meta_ball
    Type bpy.types.MetaBall
bpy.context.lamp
    Type bpy.types.Lamp
bpy.context.camera
    Type bpy.types.Camera
bpy.context.material
    Type bpy.types.Material
bpy.context.material_slot
    Type bpy.types.MaterialSlot
bpy.context.texture
    Type bpy.types.Texture
bpy.context.texture_slot
    Type bpy.types.MaterialTextureSlot
bpy.context.bone
    Type bpy.types.Bone
bpy.context.edit_bone
    Type bpy.types.EditBone
bpy.context.pose_bone
    Type bpy.types.PoseBone
bpy.context.particle_system
    Type bpy.types.ParticleSystem
bpy.context.particle_system_editable
    Type bpy.types.ParticleSystem
bpy.context.cloth
    Type bpy.types.ClothModifier
bpy.context.soft_body
    Type bpy.types.SoftBodyModifier
bpy.context.fluid
    Type bpy.types.FluidSimulationModifier
bpy.context.smoke
    Type bpy.types.SmokeModifier
bpy.context.collision
    Type bpy.types.CollisionModifier
bpy.context.brush
```

Type bpy.types.Brush

2.1.4 Image Context

bpy.context.edit_image

Type bpy.types.Image

2.1.5 Node Context

bpy.context.selected_nodes

Type sequence of bpy.types.Node

2.1.6 Text Context

bpy.context.edit_text

Type bpy.types.Text

2.2 Data Access (bpy.data)

This module is used for all blender/python access.

bpy.data

Access to blenders internal data

Type bpy.types.BlendData

import bpy

```
# print all objects
for obj in bpy.data.objects:
    print(obj.name)
```

```
# print all scene names in a list
print(bpy.data.scenes.keys())
```

```
# remove mesh Cube
if "Cube" in bpy.data.meshes:
    mesh = bpy.data.meshes["Cube"]
    print("removing mesh", mesh)
    bpy.data.meshes.remove(mesh)
```

```
# write images into a file next to the blend
import os
file = open(os.path.splitext(bpy.data.filepath)[0] + ".txt", 'w')

for image in bpy.data.images:
    file.write("%s %d x %d\n" % (image.filepath, image.size[0], image.size[1]))
```

```
file.close()
```

2.3 Operators (bpy.ops)

2.3.1 Calling Operators

Provides python access to calling operators, this includes operators written in C, Python or Macros.

Only keyword arguments can be used to pass operator properties.

Operators don't have return values as you might expect, instead they return a set() which is made up of: {'RUNNING_MODAL', 'CANCELLED', 'FINISHED', 'PASS_THROUGH'}. Common return values are {'FINISHED'} and {'CANCELLED'}.

Calling an operator in the wrong context will raise a RuntimeError, there is a poll() method to avoid this problem.

Note that the operator ID (bl_idname) in this example is 'mesh.subdivide', 'bpy.ops' is just the access path for python.

```
import bpy

# calling an operator
bpy.ops.mesh.subdivide(number_cuts=3, smoothness=0.5)

# check poll() to avoid exception.
if bpy.ops.object.mode_set.poll():
    bpy.ops.object.mode_set(mode='EDIT')
```

2.3.2 Execution Context

When calling an operator you may want to pass the execution context.

This determines the context that's given to the operator to run in, and whether invoke() is called or execute().

'EXEC_DEFAULT' is used by default but you may want the operator to take user interaction with 'INVOKE_DEFAULT'.

The execution context is as a non keyword, string argument in: ('INVOKE_DEFAULT', 'INVOKE_REGION_WIN', 'INVOKE_REGION_CHANNELS', 'INVOKE_REGION_PREVIEW', 'INVOKE_AREA', 'INVOKE_SCREEN', 'EXEC_DEFAULT', 'EXEC_REGION_WIN', 'EXEC_REGION_CHANNELS', 'EXEC_REGION_PREVIEW', 'EXEC_AREA', 'EXEC_SCREEN')

```
# group add popup
import bpy
bpy.ops.object.group_instance_add('INVOKE_DEFAULT')
```

Action Operators

```
bpy.ops.action.clean(threshold=0.001)
Simplify F-Curves by removing closely spaced keyframes
```

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold

```
bpy.ops.action.clickselect(extend=False, column=False)
Select keyframes by clicking on them
```

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **column** (*boolean, (optional)*) – Column Select

bpy.ops.action.**copy**()

Copy selected keyframes to the copy/paste buffer

bpy.ops.action.**delete**()

Remove all selected keyframes

bpy.ops.action.**duplicate** (*mode='TRANSLATION'*)

Make a copy of all selected keyframes

Parameters mode (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO-SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode

bpy.ops.action.**duplicate_move** (*ACTION_OT_duplicate=None, FORM_OT_transform=None*)

TRANS-

Undocumented ([contribute](#))

Parameters

- **ACTION_OT_duplicate** (*ACTION_OT_duplicate, (optional)*) – Duplicate Keyframes, Make a copy of all selected keyframes
- **TRANSFORM_OT_transform** (*TRANSFORM_OT_transform, (optional)*) – Transform, Transform selected items by mode type

bpy.ops.action.**extrapolation_type** (*type='CONSTANT'*)

Set extrapolation mode for selected F-Curves

Parameters type (*enum in ['CONSTANT', 'LINEAR'], (optional)*) – Type

bpy.ops.action.**frame_jump**()

Set the current frame to the average frame of the selected keyframes

bpy.ops.action.**handle_type** (*type='FREE'*)

Set type of handle for selected keyframes

Parameters type (*enum in ['FREE', 'VECTOR', 'ALIGNED', 'AUTO', 'ANIM_CLAMPED'], (optional)*) – Type

bpy.ops.action.**interpolation_type** (*type='CONSTANT'*)

Set interpolation mode for the F-Curve segments starting from the selected keyframes

Parameters type (*enum in ['CONSTANT', 'LINEAR', 'BEZIER'], (optional)*) – Type

bpy.ops.action.**keyframe_insert** (*type='ALL'*)

Insert keyframes for the specified channels

Parameters type (*enum in ['ALL', 'SEL', 'GROUP'], (optional)*) – Type

bpy.ops.action.**keyframe_type** (*type='KEYFRAME'*)

Set type of keyframe for the selected keyframes

Parameters type (*enum in ['KEYFRAME', 'BREAKDOWN', 'EXTREME', 'JITTER'], (optional)*) – Type

bpy.ops.action.markers_make_local()

Move selected scene markers to the active Action as local ‘pose’ markers

bpy.ops.action.mirror(type='CFRA')

Flip selected keyframes over the selected mirror line

Parameters **type** (enum in ['CFRA', 'XAXIS', 'MARKER'], (optional)) – Type

bpy.ops.action.new()

Create new action

bpy.ops.action.paste(offset='START', merge='MIX')

Paste keyframes from copy/paste buffer for the selected channels, starting on the current frame

Parameters

- **offset** (enum in ['START', 'END', 'RELATIVE', 'NONE'], (optional)) – Offset, Paste time offset of keys
- **merge** (enum in ['MIX', 'OVER_ALL', 'OVER_RANGE', 'OVER_RANGE_ALL'], (optional)) – Type, Method of merging pasted keys and existing

bpy.ops.action.previewrange_set()

Set Preview Range based on extents of selected Keyframes

bpy.ops.action.sample()

Add keyframes on every frame between the selected keyframes

bpy.ops.action.select_all_toggle(invert=False)

Toggle selection of all keyframes

Parameters **invert** (boolean, (optional)) – Invert

bpy.ops.action.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, axis_range=False)

Select all keyframes within the specified region

Parameters

- **gesture_mode** (int in [-inf, inf], (optional)) – Gesture Mode
- **xmin** (int in [-inf, inf], (optional)) – X Min
- **xmax** (int in [-inf, inf], (optional)) – X Max
- **ymin** (int in [-inf, inf], (optional)) – Y Min
- **ymax** (int in [-inf, inf], (optional)) – Y Max
- **axis_range** (boolean, (optional)) – Axis Range

bpy.ops.action.select_column(mode='KEYS')

Select all keyframes on the specified frame(s)

Parameters **mode** (enum in ['KEYS', 'CFRA', 'MARKERS_COLUMN', 'MARKERS_BETWEEN'], (optional)) – Mode

bpy.ops.action.select_leftright(mode='CHECK', extend=False)

Select keyframes to the left or the right of the current frame

Parameters

- **mode** (enum in ['CHECK', 'LEFT', 'RIGHT'], (optional)) – Mode
- **extend** (boolean, (optional)) – Extend Select

```
bpy.ops.action.select_less()  
    Deselect keyframes on ends of selection islands  
  
bpy.ops.action.select_linked()  
    Select keyframes occurring the same F-Curves as selected ones  
  
bpy.ops.action.select_more()  
    Select keyframes beside already selected ones  
  
bpy.ops.action.snap(type='CFRA')  
    Snap selected keyframes to the times specified  
  
    Parameters type (enum in ['CFRA', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER'], (optional)) – Type  
  
bpy.ops.action.view_all()  
    Reset viewable area to show full keyframe range  
  
bpy.ops.action.view_selected()  
    Reset viewable area to show selected keyframes range
```

Anim Operators

```
bpy.ops.anim.change_frame(frame=0)  
    Interactively change the current frame number  
  
    Parameters frame (int in [-300000, 300000], (optional)) – Frame  
  
bpy.ops.anim.channels_click(extend=False, children_only=False)  
    Handle mouse-clicks over animation channels  
  
    Parameters

- extend (boolean, (optional)) – Extend Select
- children_only (boolean, (optional)) – Select Children Only

  
bpy.ops.anim.channels_collapse(all=True)  
    Collapse (i.e. close) all selected expandable animation channels  
  
    Parameters all (boolean, (optional)) – All, Collapse all channels (not just selected ones)  
  
bpy.ops.anim.channels_delete()  
    Delete all selected animation channels  
  
bpy.ops.anim.channels_editable_toggle(mode='TOGGLE', type='PROTECT')  
    Toggle editability of selected channels  
  
    Parameters

- mode (enum in ['TOGGLE', 'DISABLE', 'ENABLE', 'INVERT'], (optional)) – Mode
- type (enum in ['PROTECT', 'MUTE'], (optional)) – Type

  
bpy.ops.anim.channels_expand(all=True)  
    Expand (i.e. open) all selected expandable animation channels  
  
    Parameters all (boolean, (optional)) – All, Expand all channels (not just selected ones)  
  
bpy.ops.anim.channels_fcurves_enable()  
    Clears ‘disabled’ tag from all F-Curves to get broken F-Curves working again  
  
bpy.ops.anim.channels_move(direction='DOWN')  
    Rearrange selected animation channels
```

Parameters **direction** (*enum in [‘TOP’, ‘UP’, ‘DOWN’, ‘BOTTOM’]*, *(optional)*) – Direction
bpy.ops.anim.channels_select_all_toggle (*invert=False*)
Toggle selection of all animation channels

Parameters **invert** (*boolean, (optional)*) – Invert
bpy.ops.anim.channels_select_border (*gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0*)
Select all animation channels within the specified region

Parameters

- **gesture_mode** (*int in [-inf, inf]*, *(optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf]*, *(optional)*) – X Min
- **xmax** (*int in [-inf, inf]*, *(optional)*) – X Max
- **ymin** (*int in [-inf, inf]*, *(optional)*) – Y Min
- **ymax** (*int in [-inf, inf]*, *(optional)*) – Y Max

bpy.ops.anim.channels_setting_disable (*mode=‘DISABLE’*, *type=‘PROTECT’*)
Disable specified setting on all selected animation channels

Parameters

- **mode** (*enum in [‘TOGGLE’, ‘DISABLE’, ‘ENABLE’, ‘INVERT’]*, *(optional)*) – Mode
- **type** (*enum in [‘PROTECT’, ‘MUTE’]*, *(optional)*) – Type

bpy.ops.anim.channels_setting_enable (*mode=‘ENABLE’*, *type=‘PROTECT’*)
Enable specified setting on all selected animation channels

Parameters

- **mode** (*enum in [‘TOGGLE’, ‘DISABLE’, ‘ENABLE’, ‘INVERT’]*, *(optional)*) – Mode
- **type** (*enum in [‘PROTECT’, ‘MUTE’]*, *(optional)*) – Type

bpy.ops.anim.channels_setting_toggle (*mode=‘INVERT’*, *type=‘PROTECT’*)
Invert specified setting on all selected animation channels

Parameters

- **mode** (*enum in [‘TOGGLE’, ‘DISABLE’, ‘ENABLE’, ‘INVERT’]*, *(optional)*) – Mode
- **type** (*enum in [‘PROTECT’, ‘MUTE’]*, *(optional)*) – Type

bpy.ops.anim.channels_visibility_set()
Make only the selected animation channels visible in the Graph Editor

bpy.ops.anim.channels_visibility_toggle()
Toggle visibility in Graph Editor of all selected animation channels

bpy.ops.anim.copy_driver_button()
Copy the driver for the highlighted button

bpy.ops.anim.driver_button_add (*all=True*)
Add driver(s) for the property(s) connected represented by the highlighted button

Parameters **all** (*boolean, (optional)*) – All, Create drivers for all elements of the array.

bpy.ops.anim.driver_button_remove (*all=True*)
Remove the driver(s) for the property(s) connected represented by the highlighted button

Parameters **all** (*boolean, (optional)*) – All, Delete drivers for all elements of the array.

bpy.ops.anim.**keyframe_delete**(*type='DEFAULT'*, *confirm_success=True*)
Delete keyframes on the current frame for all properties in the specified Keying Set

Parameters

- **type** (*enum in ['DEFAULT']*, *(optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean*, *(optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added

bpy.ops.anim.**keyframe_delete_button**(*all=True*)
Undocumented ([contribute](#))

Parameters **all** (*boolean*, *(optional)*) – All, Delete keyfames from all elements of the array.

bpy.ops.anim.**keyframe_delete_v3d**()
Remove keyframes on current frame for selected object

bpy.ops.anim.**keyframe_insert**(*type='DEFAULT'*, *confirm_success=True*)
Insert keyframes on the current frame for all properties in the specified Keying Set

Parameters

- **type** (*enum in ['DEFAULT']*, *(optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean*, *(optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added

bpy.ops.anim.**keyframe_insert_button**(*all=True*)
Undocumented ([contribute](#))

Parameters **all** (*boolean*, *(optional)*) – All, Insert a keyframe for all element of the array.

bpy.ops.anim.**keyframe_insert_menu**(*type='DEFAULT'*, *confirm_success=False*, *always_prompt=False*)
Insert Keyframes for specified Keying Set, with menu of available Keying Sets if undefined

Parameters

- **type** (*enum in ['DEFAULT']*, *(optional)*) – Keying Set, The Keying Set to use
- **confirm_success** (*boolean*, *(optional)*) – Confirm Successful Insert, Show a popup when the keyframes get successfully added
- **always_prompt** (*boolean*, *(optional)*) – Always Show Menu

bpy.ops.anim.**keying_set_active_set**(*type=0*)
Undocumented ([contribute](#))

Parameters **type** (*int in [-inf, inf]*, *(optional)*) – Keying Set Number, Index (determined internally) of the Keying Set to use

bpy.ops.anim.**keying_set_add**()
Add a new (empty) Keying Set to the active Scene

bpy.ops.anim.**keying_set_export**(*filepath=""*, *filter_folder=True*, *filter_text=True*, *filter_python=True*)
Export Keying Set to a python script.

Parameters

- **filepath** (*string*, *(optional)*) – File Path, Filepath to write file to.
- **filter_folder** (*boolean*, *(optional)*) – Filter folders
- **filter_text** (*boolean*, *(optional)*) – Filter text

Parameters **type** (*enum in ['XAXIS', 'YAXIS', 'ZAXIS']*, *(optional)*) – Axis, Axis tag names with.
 bpy.ops.armature.bone_layers (*layers=(False, False, False, False, False, False, False, False,*
 False, False, False,
 False, False, False,
 False, False))

Change the layers that the selected bones belong to

Parameters **layers** (*boolean array of 32 items*, *(optional)*) – Layer, Armature layers that bone belongs to

bpy.ops.armature.bone_primitive_add (*name="Bone"*)
 Add a new bone located at the 3D-Cursor

Parameters **name** (*string*, *(optional)*) – Name, Name of the newly created bone

bpy.ops.armature.calculate_roll (*type='X'*, *axis_flip=False*, *axis_only=False*)
 Automatically fix alignment of select bones' axes

Parameters

- **type** (*enum in ['X', 'Y', 'Z', 'ACTIVE', 'VIEW', 'CURSOR']*, *(optional)*) – Type
- **axis_flip** (*boolean*, *(optional)*) – Flip Axis, Negate the alignment axis.
- **axis_only** (*boolean*, *(optional)*) – Shortest Rotation, Ignore the axis direction, use the shortest rotation to align.

bpy.ops.armature.click_extrude ()
 Create a new bone going from the last selected joint to the mouse position

bpy.ops.armature.delete ()
 Remove selected bones from the armature

bpy.ops.armature.duplicate ()
 Make copies of the selected bones within the same armature

bpy.ops.armature.duplicate_move (*ARMATURE_OT_duplicate=None*,
 FORM_OT_translate=None)
 TRANSPORT
 Undocumented ([contribute](#))

Parameters

- **ARMATURE_OT_duplicate** (*ARMATURE_OT_duplicate*, *(optional)*) – Duplicate Selected Bone(s), Make copies of the selected bones within the same armature
- **TRANSFORM_OT_translate** (*TRANSFORM_OT_translate*, *(optional)*) – Translate, Translate selected items

bpy.ops.armature.extrude (*forked=False*)
 Create new bones from the selected joints

Parameters **forked** (*boolean*, *(optional)*) – Forked

bpy.ops.armature.extrude_forked (*ARMATURE_OT_extrude=None*,
 FORM_OT_translate=None)
 TRANSPORT
 Undocumented ([contribute](#))

Parameters

- **ARMATURE_OT_extrude** (*ARMATURE_OT_extrude*, *(optional)*) – Extrude, Create new bones from the selected joints
- **TRANSFORM_OT_translate** (*TRANSFORM_OT_translate*, *(optional)*) – Translate, Translate selected items

bpy.ops.armature.**extrude_move** (ARMATURE_OT_extrude=None,
 FORM_OT_translate=None)
 TRANSPORT
Undocumented ([contribute](#))

Parameters

- **ARMATURE_OT_extrude** (ARMATURE_OT_extrude, (optional)) – Extrude, Create new bones from the selected joints
- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

bpy.ops.armature.**fill**()
Add bone between selected joint(s) and/or 3D-Cursor

bpy.ops.armature.**flip_names**()
Flips (and corrects) the axis suffixes of the names of selected bones

bpy.ops.armature.**hide** (unselected=False)
Tag selected bones to not be visible in Edit Mode

Parameters unselected (boolean, (optional)) – Unselected, Hide unselected rather than selected.

bpy.ops.armature.**layers_show_all** (all=True)
Make all armature layers visible

Parameters all (boolean, (optional)) – All Layers, Enable all layers or just the first 16 (top row)

bpy.ops.armature.**merge** (type='WITHIN_CHAIN')
Merge continuous chains of selected bones

Parameters type (enum in ['WITHIN_CHAIN'], (optional)) – Type

bpy.ops.armature.**parent_clear** (type='CLEAR')
Remove the parent-child relationship between selected bones and their parents

Parameters type (enum in ['CLEAR', 'DISCONNECT'], (optional)) – ClearType, What way to clear parenting

bpy.ops.armature.**parent_set** (type='CONNECTED')
Set the active bone as the parent of the selected bones

Parameters type (enum in ['CONNECTED', 'OFFSET'], (optional)) – ParentType, Type of parenting

bpy.ops.armature.**reveal**()
Unhide all bones that have been tagged to be hidden in Edit Mode

bpy.ops.armature.**select_all** (action='TOGGLE')
Toggle selection status of all bones

Parameters action (enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)) – Action, Selection action to execute

bpy.ops.armature.**select_hierarchy** (direction='PARENT', extend=False)
Select immediate parent/children of selected bones

Parameters

- **direction** (enum in ['PARENT', 'CHILD'], (optional)) – Direction
- **extend** (boolean, (optional)) – Add to Selection

bpy.ops.armature.**select_inverse**()
Flip the selection status of bones (selected -> unselected, unselected -> selected)

```
bpy.ops.armature.select_linked(extend=False)
    Select bones related to selected ones by parent/child relationships

Parameters extend (boolean, (optional)) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.armature.separate()
    Isolate selected bones into a separate armature

bpy.ops.armature.subdivide(number_cuts=1)
    Break selected bones into chains of smaller bones

Parameters number_cuts (int in [1, inf], (optional)) – Number of Cuts

bpy.ops.armature.switch_direction()
    Change the direction that a chain of bones points in (head <-> tail swap)
```

Boid Operators

```
bpy.ops.boid.rule_add(type='GOAL')
    Add a boid rule to the current boid state

Parameters type (enum in ['GOAL', 'AVOID', 'AVOID_COLLISION', 'SEPARATE', 'FLOCK', 'FOLLOW_LEADER', 'AVERAGE_SPEED', 'FIGHT'], (optional)) – Type

bpy.ops.boid.rule_del()
    Undocumented (contribute)

bpy.ops.boid.rule_move_down()
    Move boid rule down in the list

bpy.ops.boid.rule_move_up()
    Move boid rule up in the list

bpy.ops.boid.state_add()
    Add a boid state to the particle system

bpy.ops.boid.state_del()
    Undocumented (contribute)

bpy.ops.boid.state_move_down()
    Move boid state down in the list

bpy.ops.boid.state_move_up()
    Move boid state up in the list
```

Brush Operators

```
bpy.ops.brush.active_index_set(mode=""", index=0)
    Set active sculpt/paint brush from it's number

Parameters
    • mode (string, (optional)) – mode, Paint mode to set brush for
    • index (int in [-inf, inf], (optional)) – number, Brush number

File startup/bl_operators/wm.py:94

bpy.ops.brush.add()
    Add brush by mode type
```

```
bpy.ops.brush.curve_preset(shape='SMOOTH')
    Set brush shape

Parameters shape (enum in ['SHARP', 'SMOOTH', 'MAX', 'LINE', 'ROUND', 'ROOT'], (optional)) – Mode

bpy.ops.brush.image_tool_set(tool='DRAW')
    Set the image tool

Parameters tool (enum in ['DRAW', 'SOFTEN', 'SMEAR', 'CLONE'], (optional)) – Tool

bpy.ops.brush.reset()
    Return brush to defaults based on current tool

bpy.ops.brush.scale_size(scalar=1.0)
    Change brush size by a scalar

Parameters scalar (float in [0, 2], (optional)) – Scalar, Factor to scale brush size by

bpy.ops.brush.sculpt_tool_set(tool='BLOB')
    Set the sculpt tool

Parameters tool (enum in ['BLOB', 'CLAY', 'CREASE', 'DRAW', 'FILL', 'FLATTEN', 'GRAB', 'INFLATE', 'LAYER', 'NUUDGE', 'PINCH', 'ROTATE', 'SCRAPE', 'SMOOTH', 'SNAKE_HOOK', 'THUMB'], (optional)) – Tool

bpy.ops.brush.vertex_tool_set(tool='MIX')
    Set the vertex paint tool

Parameters tool (enum in ['MIX', 'ADD', 'SUB', 'MUL', 'BLUR', 'LIGHTEN', 'DARKEN'], (optional)) – Tool

bpy.ops.brush.weight_tool_set(tool='MIX')
    Set the weight paint tool

Parameters tool (enum in ['MIX', 'ADD', 'SUB', 'MUL', 'BLUR', 'LIGHTEN', 'DARKEN'], (optional)) – Tool
```

Buttons Operators

```
bpy.ops.buttons.directory_browse(directory=""", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=9, relative_path=False)
```

Open a directory browser, Hold Shift to open the file, Alt to browse containing directory

Parameters

- **directory** (*string, (optional)*) – Directory, Directory of the file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files

- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

```
bpy.ops.buttons.file_browser(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=9, relative_path=False)
```

Open a file browser, Hold Shift to open the file, Alt to browse containing directory

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

```
bpy.ops.buttons.toolbox()
```

Display button panel toolbox

Cloth Operators

```
bpy.ops.cloth.preset_add(name="", remove_active=False)
```

Add a Cloth Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File startup/bl_operators/presets.py:42

Console Operators

```
bpy.ops.console.autocomplete()
```

Evaluate the namespace up until the cursor and give a list of options or complete the name if there is only one

File startup/bl_ui/space_console.py:108

bpy.ops.console.banner()

Print a message when the terminal initializes

File startup/bl_ui/space_console.py:125

bpy.ops.console.clear(scrollback=True, history=False)

Clear text by type

Parameters

- **scrollback** (boolean, (optional)) – Scrollback, Clear the scrollback history
- **history** (boolean, (optional)) – History, Clear the command history

bpy.ops.console.copy()

Copy selected text to clipboard

bpy.ops.console.delete(type='NEXT_CHARACTER')

Delete text by cursor position

Parameters **type** (enum in ['NEXT_CHARACTER', 'PREVIOUS_CHARACTER'], (optional)) – Type, Which part of the text to delete.

bpy.ops.console.execute()

Execute the current console line as a python expression

File startup/bl_ui/space_console.py:90

bpy.ops.console.history_append(text="", current_character=0, remove_duplicates=False)

Append history at cursor position

Parameters

- **text** (string, (optional)) – Text, Text to insert at the cursor position.
- **current_character** (int in [0, inf], (optional)) – Cursor, The index of the cursor.
- **remove_duplicates** (boolean, (optional)) – Remove Duplicates, Remove duplicate items in the history

bpy.ops.console.history_cycle(reverse=False)

Cycle through history

Parameters **reverse** (boolean, (optional)) – Reverse, reverse cycle history

bpy.ops.console.insert(text="")

Insert text at cursor position

Parameters **text** (string, (optional)) – Text, Text to insert at the cursor position.

bpy.ops.console.language(language="")

Set the current language for this console

Parameters **language** (string, (optional)) – Language

File startup/bl_ui/space_console.py:148

bpy.ops.console.move(type='LINE_BEGIN')

Move cursor position

Parameters **type** (enum in ['LINE_BEGIN', 'LINE_END', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD'], (optional)) – Type, Where to move cursor to.

```
bpy.ops.console.paste()  
    Paste text from clipboard
```

```
bpy.ops.console.scrollback_append(text=""", type='OUTPUT')  
    Append scrollback text by type
```

Parameters

- **text** (*string, (optional)*) – Text, Text to insert at the cursor position.
- **type** (*enum in ['OUTPUT', 'INPUT', 'INFO', 'ERROR'], (optional)*) – Type, Console output type.

```
bpy.ops.console.select_set()  
    Set the console selection
```

Constraint Operators

```
bpy.ops.constraint.childof_clear_inverse(constraint=""", owner='OBJECT')  
    Clear inverse correction for ChildOf constraint
```

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

```
bpy.ops.constraint.childof_set_inverse(constraint=""", owner='OBJECT')  
    Set inverse correction for ChildOf constraint
```

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

```
bpy.ops.constraint.delete()  
    Remove constraint from constraint stack
```

```
bpy.ops.constraint.limitdistance_reset(constraint=""", owner='OBJECT')  
    Reset limiting distance for Limit Distance Constraint
```

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

```
bpy.ops.constraint.move_down(constraint=""", owner='OBJECT')  
    Move constraint down in constraint stack
```

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

```
bpy.ops.constraint.move_up(constraint=""", owner='OBJECT')  
    Move constraint up in constraint stack
```

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

bpy.ops.constraint.**stretchto_reset**(constraint=""", owner='OBJECT')

Reset original length of bone for Stretch To Constraint

Parameters

- **constraint** (*string, (optional)*) – Constraint, Name of the constraint to edit
- **owner** (*enum in ['OBJECT', 'BONE'], (optional)*) – Owner, The owner of this constraint

Curve Operators

bpy.ops.curve.**cyclic_toggle**(direction='CYCLIC_U')

Make active spline closed/opened loop

Parameters direction (*enum in ['CYCLIC_U', 'CYCLIC_V'], (optional)*) – Direction, Direction to make surface cyclic in.

bpy.ops.curve.**de_select_first**()

Undocumented (contribute)

bpy.ops.curve.**de_select_last**()

Undocumented (contribute)

bpy.ops.curve.**delete**(type='SELECTED')

Delete selected control points or segments

Parameters type (*enum in ['SELECTED', 'SEGMENT', 'ALL'], (optional)*) – Type, Which elements to delete.

bpy.ops.curve.**duplicate**(mode='TRANSLATION')

Duplicate selected control points and segments between them

Parameters mode (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO_SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode

bpy.ops.curve.**extrude**(mode='TRANSLATION')

Extrude selected control point(s) and move

Parameters mode (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO_SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode

bpy.ops.curve.**handle_type_set**(type='AUTOMATIC')

Set type of handles for selected control points

Parameters type (*enum in ['AUTOMATIC', 'VECTOR', 'ALIGNED', 'FREE_ALIGN', 'TOGGLE_FREE_ALIGN'], (optional)*) – Type, Spline type

bpy.ops.curve.**hide**(unselected=False)

Undocumented (contribute)

Parameters unselected (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

bpy.ops.curve.**make_segment**()

Undocumented (contribute)

```
bpy.ops.curve.primitive_bezier_circle_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Bezier Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.curve.primitive_bezier_curve_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Bezier Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.curve.primitive_nurbs_circle_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurbs Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object

- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.curve.primitive_nurbs_curve_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurb Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.curve.primitive_nurbs_path_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Path

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.curve.radius_set(radius=1.0)
```

Set per-point radius which is used for bevel tapering

Parameters **radius** (*float in [0, inf], (optional)*) – Radius

```
bpy.ops.curve.reveal()
```

Undocumented (contribute)

```
bpy.ops.curve.select_all(action='TOGGLE')
```

Undocumented (contribute)

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

```
bpy.ops.curve.select_inverse()
```

Undocumented (contribute)

```
bpy.ops.curve.select_less()
```

Undocumented (contribute)

```
bpy.ops.curve.select_linked()  
    Undocumented (contribute)  
  
bpy.ops.curve.select_linked_pick(deselect=False)  
    Undocumented (contribute)  
  
    Parameters deselect (boolean, (optional)) – Deselect, Deselect linked control points rather than  
        selecting them.  
  
bpy.ops.curve.select_more()  
    Undocumented (contribute)  
  
bpy.ops.curve.select_next()  
    Undocumented (contribute)  
  
bpy.ops.curve.select_nth(nth=2)  
    Undocumented (contribute)  
  
    Parameters nth (int in [2, 100], (optional)) – Nth Selection  
  
bpy.ops.curve.select_previous()  
    Undocumented (contribute)  
  
bpy.ops.curve.select_random(percent=50.0, extend=False)  
    Undocumented (contribute)  
  
    Parameters  
        • percent (float in [0, 100], (optional)) – Percent, Percentage of elements to select randomly.  
        • extend (boolean, (optional)) – Extend Selection, Extend selection instead of deselecting  
            everything first.  
  
bpy.ops.curve.select_row()  
    Undocumented (contribute)  
  
bpy.ops.curve.separate()  
    Undocumented (contribute)  
  
bpy.ops.curve.shade_flat()  
    Undocumented (contribute)  
  
bpy.ops.curve.shade_smooth()  
    Undocumented (contribute)  
  
bpy.ops.curve.smooth()  
    Flatten angles of selected points  
  
bpy.ops.curve.smooth_radius()  
    Flatten radiiuses of selected points  
  
bpy.ops.curve.spin(center=(0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0))  
    Undocumented (contribute)  
  
    Parameters  
        • center (float array of 3 items in [-inf, inf], (optional)) – Center, Center in global view space  
        • axis (float array of 3 items in [-1, 1], (optional)) – Axis, Axis in global view space  
  
bpy.ops.curve.spline_type_set(type='POLY')  
    Set type of active spline  
  
    Parameters type (enum in ['POLY', 'BEZIER', 'NURBS'], (optional)) – Type, Spline type
```

```
bpy.ops.curve.spline_weight_set (weight=1.0)
    Set softbody goal weight for selected points

Parameters weight (float in [0, 1], (optional)) – Weight

bpy.ops.curve.subdivide (number_cuts=1)
    Subdivide selected segments

Parameters number_cuts (int in [1, inf], (optional)) – Number of cuts

bpy.ops.curve.switch_direction ()
    Switch direction of selected splines

bpy.ops.curve.tilt_clear ()
    Undocumented (contribute)

bpy.ops.curve.vertex_add (location=(0.0, 0.0, 0.0))
    Undocumented (contribute)

Parameters location (float array of 3 items in [-inf, inf], (optional)) – Location, Location to add new vertex at.
```

Ed Operators

```
bpy.ops.ed.redo ()
    Redo previous action

bpy.ops.ed.undo ()
    Undo previous action

bpy.ops.ed.undo_history (item=0)
    Redo specific action in history

Parameters item (int in [0, inf], (optional)) – Item

bpy.ops.ed.undo_push (message="Add an undo step *function may be moved*")
    Add an undo state (internal use only)

Parameters message (string, (optional)) – Undo Message
```

Export Anim Operators

```
bpy.ops.export_anim.bvh (filepath=""“, check_existing=True, filter_glob="*.bvh”, global_scale=1.0,
                           frame_start=0, frame_end=0, rotate_mode='NATIVE’)
    Save a BVH motion capture file from an armature

Parameters

- filepath (string, (optional)) – File Path, Filepath used for exporting the file
- check_existing (boolean, (optional)) – Check Existing, Check and warn on overwriting existing files
- global_scale (float in [0.0001, 1e+06], (optional)) – Scale, Scale the BVH by this value
- frame_start (int in [-inf, inf], (optional)) – Start Frame, Starting frame to export
- frame_end (int in [-inf, inf], (optional)) – End Frame, End frame to export
- rotate_mode (enum in ['NATIVE’, ‘XYZ’, ‘XZY’, ‘YXZ’, ‘YZX’, ‘ZXY’, ‘ZYX’], (optional))
      – Rotation, Rotation conversion.

```

File `addons/io_anim_bvh/_init__.py:123`

Export Mesh Operators

```
bpy.ops.export_mesh.ply(filepath="", check_existing=True, filter_glob="*.ply",
                      use_modifiers=True, use_normals=True, use_uv_coords=True,
                      use_colors=True)
```

Export a single object as a stanford PLY with normals, colours and texture coordinates.

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply Modifiers to the exported mesh
- **use_normals** (*boolean, (optional)*) – Normals, Export Normals for smooth and hard shaded faces
- **use_uv_coords** (*boolean, (optional)*) – UVs, Export the active UV layer
- **use_colors** (*boolean, (optional)*) – Vertex Colors, Export the active vertex color layer

File addons/io_mesh_ply/__init__.py:95

```
bpy.ops.export_mesh.stl(filepath="", check_existing=True, ascii=False, apply_modifiers=True)
```

Save STL triangle mesh data from the active object

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **ascii** (*boolean, (optional)*) – Ascii, Save the file in ASCII file format
- **apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply the modifiers before saving

File addons/io_mesh_stl/__init__.py:123

Export Scene Operators

```
bpy.ops.export_scene.autodesk_3ds(filepath="", check_existing=True, filter_glob="*.3ds",
                                    use_selection=False, axis_forward='Y', axis_up='Z')
```

Export to 3DS file format (.3ds)

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only
- **axis_forward** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Forward
- **axis_up** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Up

File addons/io_scene_3ds/__init__.py:130

```
bpy.ops.export_scene.fbx(filepath="", check_existing=True, filter_glob="*.fbx",
    use_selection=False, global_scale=1.0, axis_forward='-Z', axis_up='Y',
    object_types={'ARMATURE', 'LAMP', 'CAMERA', 'MESH',
    'EMPTY'}, mesh_apply_modifiers=True, mesh_smooth_type='FACE',
    ANIM_ENABLE=True, ANIM_OPTIMIZE=True,
    ANIM_OPTIMIZE_PRECISION=6.0, ANIM_ACTION_ALL=False,
    batch_mode='OFF', BATCH_own_DIR=True, use_metadata=True,
    path_mode='AUTO')
```

Selection to an ASCII Autodesk FBX

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selected Objects, Export selected objects on visible layers
- **global_scale** (*float in [0.01, 1000], (optional)*) – Scale, Scale all data, (Note! some imports dont support scaled armatures)
- **axis_forward** (*enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)*) – Forward
- **axis_up** (*enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)*) – Up
- **object_types** (*enum set in {'EMPTY', 'CAMERA', 'LAMP', 'ARMATURE', 'MESH'}, (optional)*) – Object Types
- **mesh_apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply modifiers to mesh objects
- **mesh_smooth_type** (*enum in ['OFF', 'FACE', 'EDGE'], (optional)*) – Smoothing
- **ANIM_ENABLE** (*boolean, (optional)*) – Enable Animation, Export keyframe animation
- **ANIM_OPTIMIZE** (*boolean, (optional)*) – Optimize Keyframes, Remove double keyframes
- **ANIM_OPTIMIZE_PRECISION** (*float in [1, 16], (optional)*) – Precision, Tolerance for comparing double keyframes (higher for greater accuracy)
- **ANIM_ACTION_ALL** (*boolean, (optional)*) – All Actions, Use all actions for armatures, if false, use current action
- **batch_mode** (*enum in ['OFF', 'SCENE', 'GROUP'], (optional)*) – Batch Mode
- **BATCH_own_DIR** (*boolean, (optional)*) – Own Dir, Create a dir for each exported file
- **use_metadata** (*boolean, (optional)*) – Use Metadata
- **path_mode** (*enum in ['AUTO', 'ABSOLUTE', 'RELATIVE', 'MATCH', 'STRIP', 'COPY'], (optional)*) – Path Mode, Method used to reference paths

File [addons/io_scene_fbx/_init_.py:135](#)

```
bpy.ops.export_scene.obj(filepath="", check_existing=True, filter_glob="*.obj;*.mtl",
use_selection=False, use_all_scenes=False, use_animation=False,
use_apply_modifiers=True, use_edges=True, use_normals=False,
use_hq_normals=True, useUvs=True, use_materials=True,
use_triangles=False, use_vertex_groups=False, use_nurbs=False,
use_blen_objects=True, group_by_object=False,
group_by_material=False, keep_vertex_order=False, global_scale=1.0,
axis_forward='Z', axis_up='Y', path_mode='AUTO')
```

Save a Wavefront OBJ File

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only
- **use_all_scenes** (*boolean, (optional)*) – All Scenes
- **use_animation** (*boolean, (optional)*) – Animation
- **use_apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Apply modifiers (preview resolution)
- **use_edges** (*boolean, (optional)*) – Edges
- **use_normals** (*boolean, (optional)*) – Normals
- **use_hq_normals** (*boolean, (optional)*) – High Quality Normals
- **useUvs** (*boolean, (optional)*) – UVs
- **use_materials** (*boolean, (optional)*) – Materials
- **use_triangles** (*boolean, (optional)*) – Triangulate
- **use_vertex_groups** (*boolean, (optional)*) – Polygroups
- **use_nurbs** (*boolean, (optional)*) – Nurb
- **use_blen_objects** (*boolean, (optional)*) – Objects as OBJ Objects
- **group_by_object** (*boolean, (optional)*) – Objects as OBJ Groups
- **group_by_material** (*boolean, (optional)*) – Material Groups
- **keep_vertex_order** (*boolean, (optional)*) – Keep Vertex Order
- **global_scale** (*float in [0.01, 1000], (optional)*) – Scale, Scale all data, (Note! some imports dont support scaled armatures)
- **axis_forward** (*enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)*) – Forward
- **axis_up** (*enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)*) – Up
- **path_mode** (*enum in ['AUTO', 'ABSOLUTE', 'RELATIVE', 'MATCH', 'STRIP', 'COPY'], (optional)*) – Path Mode, Method used to reference paths

File [addons/io_scene_obj/_init_.py:217](#)

```
bpy.ops.export_scene.x3d(filepath="", check_existing=True, filter_glob="*.x3d",
use_selection=False, use_apply_modifiers=True, useTriangulate=True,
use_normals=False, use_compress=False, use_hierarchy=True,
use_h3d=False, axis_forward='Z', axis_up='Y', path_mode='AUTO')
```

Export selection to Extensible 3D file (.x3d)

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for exporting the file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **use_selection** (*boolean, (optional)*) – Selection Only, Export selected objects only
- **use_apply_modifiers** (*boolean, (optional)*) – Apply Modifiers, Use transformed mesh data from each object
- **use_triangulate** (*boolean, (optional)*) – Triangulate, Write quads into ‘IndexedTriangleSet’
- **use_normals** (*boolean, (optional)*) – Normals, Write normals with geometry
- **use_compress** (*boolean, (optional)*) – Compress, GZip the resulting file, requires a full python install
- **use_hierarchy** (*boolean, (optional)*) – Hierarchy, Export parent child relationships
- **use_h3d** (*boolean, (optional)*) – H3D Extensions, Export shaders for H3D
- **axis_forward** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Forward
- **axis_up** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Up
- **path_mode** (*enum in [‘AUTO’, ‘ABSOLUTE’, ‘RELATIVE’, ‘MATCH’, ‘STRIP’, ‘COPY’], (optional)*) – Path Mode, Method used to reference paths

File `addons/io_scene_x3d/__init__.py:131`

File Operators

`bpy.ops.file.bookmark_add()`

Add a bookmark for the selected/active directory

`bpy.ops.file.bookmark_toggle()`

Toggle bookmarks display

`bpy.ops.file.cancel()`

Cancel loading of selected file

`bpy.ops.file.delete()`

Delete selected file

`bpy.ops.file.delete_bookmark(index=-1)`

Delete selected bookmark

Parameters `index (int in [-1, 20000], (optional))` – Index

`bpy.ops.file.directory()`

Enter a directory name

`bpy.ops.file.directory_new(directory="")`

Create a new directory

Parameters `directory (string, (optional))` – Directory, Name of new directory

`bpy.ops.file.execute(need_active=False)`

Execute selected file

Parameters `need_active (boolean, (optional))` – Need Active, Only execute if there’s an active selected file in the file list.

bpy.ops.file.**filenum**(*increment=1*)

Increment number in filename

Parameters increment (*int in [-100, 100], (optional)*) – Increment

bpy.ops.file.**find_missing_files**(*filepath=""*, *filter_blender=False*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=False*, *filemode=9*)

Undocumented ([contribute](#))

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

bpy.ops.file.**hidedot**()

Toggle hide hidden dot files

bpy.ops.file.**highlight**()

Highlight selected file(s)

bpy.ops.file.**make_paths_absolute**()

Undocumented ([contribute](#))

bpy.ops.file.**make_paths_relative**()

Undocumented ([contribute](#))

bpy.ops.file.**next**()

Move to next folder

bpy.ops.file.**pack_all**()

Undocumented ([contribute](#))

bpy.ops.file.**parent**()

Move to parent directory

bpy.ops.file.**previous**()

Move to previous folder

bpy.ops.file.**refresh**()

Refresh the file list

bpy.ops.file.**rename**()

Rename file or file directory

bpy.ops.file.report_missing_files()
Undocumented ([contribute](#))

bpy.ops.file.select (extend=False, fill=False)
Activate/select file

Parameters

- **extend** (boolean, (optional)) – Extend, Extend selection instead of deselecting everything first.
- **fill** (boolean, (optional)) – Fill, Select everything beginning with the last selection.

bpy.ops.file.select_all_toggle()
Select/deselect all files

bpy.ops.file.select_bookmark (dir="")
Select a bookmarked directory

Parameters **dir** (string, (optional)) – Dir

bpy.ops.file.select_border (gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)
Activate/select the file(s) contained in the border

Parameters

- **gesture_mode** (int in [-inf, inf], (optional)) – Gesture Mode
- **xmin** (int in [-inf, inf], (optional)) – X Min
- **xmax** (int in [-inf, inf], (optional)) – X Max
- **ymin** (int in [-inf, inf], (optional)) – Y Min
- **ymax** (int in [-inf, inf], (optional)) – Y Max

bpy.ops.file.smoothscroll()
Smooth scroll to make editable file visible.

bpy.ops.file.unpack_all (method='USE_LOCAL')
Undocumented ([contribute](#))

Parameters **method** (enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL', 'KEEP', 'ASK'], (optional)) – Method, How to unpack.

Fluid Operators

bpy.ops.fluid.bake()
Bake fluid simulation

Font Operators

bpy.ops.font.buffer_paste()
Paste text from OS buffer

bpy.ops.font.case_set (case='LOWER')
Set font case

Parameters **case** (enum in ['LOWER', 'UPPER'], (optional)) – Case, Lower or upper case.

bpy.ops.font.case_toggle()
Toggle font case

```
bpy.ops.font.change_character(delta=1)
```

Change font character code

Parameters **delta** (*int in [-255, 255], (optional)*) – Delta, Number to increase or decrease character code with.

```
bpy.ops.font.change_spacing(delta=1)
```

Change font spacing

Parameters **delta** (*int in [-20, 20], (optional)*) – Delta, Amount to decrease or increasing character spacing with.

```
bpy.ops.font.delete(type='ALL')
```

Delete text by cursor position

Parameters **type** (*enum in ['ALL', 'NEXT_CHARACTER', 'PREVIOUS_CHARACTER', 'SELECTION', 'NEXT_OR_SELECTION', 'PREVIOUS_OR_SELECTION'], (optional)*) – Type, Which part of the text to delete.

```
bpy.ops.font.file_paste(filepath="", filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9)
```

Paste contents from file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

```
bpy.ops.font.insert_lorem()
```

Insert placeholder text

```
bpy.ops.font.line_break(ctrl=False)
```

Insert line break at cursor position

Parameters **ctrl** (*boolean, (optional)*) – Ctrl

```
bpy.ops.font.move(type='LINE_BEGIN')
```

Move cursor to position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE',*

‘NEXT_LINE’, ‘PREVIOUS_PAGE’, ‘NEXT_PAGE’], (optional)) – Type, Where to move cursor to.

bpy.ops.font.move_select(type=’LINE_BEGIN’)

Make selection from current cursor position to new cursor position type

Parameters **type** (enum in [’LINE_BEGIN’, ’LINE_END’, ’PREVIOUS_CHARACTER’, ’NEXT_CHARACTER’, ’PREVIOUS_WORD’, ’NEXT_WORD’, ’PREVIOUS_LINE’, ’NEXT_LINE’, ’PREVIOUS_PAGE’, ’NEXT_PAGE’], (optional)) – Type, Where to move cursor to, to make a selection.

bpy.ops.font.open(filepath=”“, filter_blender=False, filter_image=False, filter_movie=False, filter_python=False, filter_font=True, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)

Undocumented ([contribute](#))

Parameters

- **filepath** (string, (optional)) – File Path, Path to file
- **filter_blender** (boolean, (optional)) – Filter .blend files
- **filter_image** (boolean, (optional)) – Filter image files
- **filter_movie** (boolean, (optional)) – Filter movie files
- **filter_python** (boolean, (optional)) – Filter python files
- **filter_font** (boolean, (optional)) – Filter font files
- **filter_sound** (boolean, (optional)) – Filter sound files
- **filter_text** (boolean, (optional)) – Filter text files
- **filter_btx** (boolean, (optional)) – Filter btx files
- **filter_collada** (boolean, (optional)) – Filter COLLADA files
- **filter_folder** (boolean, (optional)) – Filter folders
- **filemode** (int in [1, 9], (optional)) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (boolean, (optional)) – Relative Path, Select the file relative to the blend file

bpy.ops.font.style_set(style=’BOLD’, clear=False)

Set font style

Parameters

- **style** (enum in [’BOLD’, ’ITALIC’, ’UNDERLINE’, ’SMALL_CAPS’], (optional)) – Style, Style to set selection to.
- **clear** (boolean, (optional)) – Clear, Clear style rather than setting it.

bpy.ops.font.style_toggle(style=’BOLD’)

Toggle font style

Parameters **style** (enum in [’BOLD’, ’ITALIC’, ’UNDERLINE’, ’SMALL_CAPS’], (optional)) – Style, Style to set selection to.

bpy.ops.font.text_copy()

Copy selected text to clipboard

bpy.ops.font.text_cut()

Cut selected text to clipboard

```
bpy.ops.font.text_insert(text=""", accent=False)
```

Insert text at cursor position

Parameters

- **text** (*string, (optional)*) – Text, Text to insert at the cursor position.
- **accent** (*boolean, (optional)*) – Accent mode, Next typed character will strike through previous, for special character input.

```
bpy.ops.font.text_paste()
```

Paste text from clipboard

```
bpy.ops.font.textbox_add()
```

Add a new text box

```
bpy.ops.font.textbox_remove(index=0)
```

Remove the textbox

Parameters **index** (*int in [0, inf], (optional)*) – Index, The current text box.

```
bpy.ops.font.unlink()
```

Unlink active font data block

Gpencil Operators

```
bpy.ops.gpencil.active_frame_delete()
```

Delete the active frame for the active Grease Pencil datablock

```
bpy.ops.gpencil.convert(type='PATH')
```

Convert the active Grease Pencil layer to a new Object

Parameters **type** (*enum in ['PATH', 'CURVE'], (optional)*) – Type

```
bpy.ops.gpencil.data_add()
```

Add new Grease Pencil datablock

```
bpy.ops.gpencil.data_unlink()
```

Unlink active Grease Pencil datablock

```
bpy.ops.gpencil.draw(mode='DRAW', stroke=None)
```

Make annotations on the active data

Parameters

- **mode** (*enum in ['DRAW', 'DRAW_STRAIGHT', 'ERASER'], (optional)*) – Mode, Way to interpret mouse movements.
- **stroke** (*bpy_prop_collection of OperatorStrokeElement, (optional)*) – Stroke

```
bpy.ops.gpencil.layer_add()
```

Add new Grease Pencil layer for the active Grease Pencil datablock

Graph Operators

```
bpy.ops.graph.bake()
```

Bake selected F-Curves to a set of sampled points defining a similar curve

```
bpy.ops.graph.clean(threshold=0.001)
```

Simplify F-Curves by removing closely spaced keyframes

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold

bpy.ops.graph.click_insert (*frame=1.0, value=1.0*)

Insert new keyframe at the cursor position for the active F-Curve

Parameters

- **frame** (*float in [-inf, inf], (optional)*) – Frame Number, Frame to insert keyframe on
- **value** (*float in [-inf, inf], (optional)*) – Value, Value for keyframe on

bpy.ops.graph.clickselect (*extend=False, column=False, curves=False*)

Select keyframes by clicking on them

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **column** (*boolean, (optional)*) – Column Select, Select all keyframes that occur on the same frame as the one under the mouse
- **curves** (*boolean, (optional)*) – Only Curves, Select all the keyframes in the curve

bpy.ops.graph.copy ()

Copy selected keyframes to the copy/paste buffer

bpy.ops.graph.cursor_set (*frame=0, value=0.0*)

Interactively set the current frame number and value cursor

Parameters

- **frame** (*int in [-300000, 300000], (optional)*) – Frame
- **value** (*float in [1.17549e-38, inf], (optional)*) – Value

bpy.ops.graph.delete ()

Remove all selected keyframes

bpy.ops.graph.duplicate (*mode='TRANSLATION'*)

Make a copy of all selected keyframes

Parameters **mode** (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO-SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode

bpy.ops.graph.duplicate_move (*GRAPH_OT_duplicate=None, FORM_OT_transform=None*)

Undocumented (contribute)

TRANS-

Parameters

- **GRAPH_OT_duplicate** (*GRAPH_OT_duplicate, (optional)*) – Duplicate Keyframes, Make a copy of all selected keyframes
- **TRANSFORM_OT_transform** (*TRANSFORM_OT_transform, (optional)*) – Transform, Transform selected items by mode type

bpy.ops.graph.euler_filter ()

Fixes the most common causes of gimbal lock in the selected Euler Rotation F-Curves

bpy.ops.graph.extrapolation_type (*type='CONSTANT'*)

Set extrapolation mode for selected F-Curves

Parameters **type** (*enum in* ['CONSTANT', 'LINEAR'], *(optional)*) – Type

bpy.ops.graph.**fmodifier_add**(*type='NULL'*, *only_active=True*)
Add F-Modifiers to the selected F-Curves

Parameters

- **type** (*enum in* ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED'], *(optional)*) – Type
- **only_active** (*boolean*, *(optional)*) – Only Active, Only add F-Modifier to active F-Curve.

bpy.ops.graph.**fmodifier_copy**()
Copy the F-Modifier(s) of the active F-Curve.

bpy.ops.graph.**fmodifier_paste**()
Add copied F-Modifiers to the selected F-Curves

bpy.ops.graph.**frame_jump**()
Set the current frame to the average frame of the selected keyframes

bpy.ops.graph.**ghost_curves_clear**()
Clear F-Curve snapshots (Ghosts) for active Graph Editor

bpy.ops.graph.**ghost_curves_create**()
Create snapshot (Ghosts) of selected F-Curves as background aid for active Graph Editor

bpy.ops.graph.**handle_type**(*type='FREE_ALIGN'*)
Set type of handle for selected keyframes

Parameters **type** (*enum in* ['AUTO', 'VECTOR', 'ALIGNED', 'FREE_ALIGN', 'ANIM_CLAMPED'], *(optional)*) – Type

bpy.ops.graph.**handles_view_toggle**()
Toggle whether handles are drawn on all keyframes that need them

bpy.ops.graph.**interpolation_type**(*type='CONSTANT'*)
Set interpolation mode for the F-Curve segments starting from the selected keyframes

Parameters **type** (*enum in* ['CONSTANT', 'LINEAR', 'BEZIER'], *(optional)*) – Type

bpy.ops.graph.**keyframe_insert**(*type='ALL'*)
Insert keyframes for the specified channels

Parameters **type** (*enum in* ['ALL', 'SEL'], *(optional)*) – Type

bpy.ops.graph.**mirror**(*type='CFRA'*)
Flip selected keyframes over the selected mirror line

Parameters **type** (*enum in* ['CFRA', 'VALUE', 'YAXIS', 'XAXIS', 'MARKER'], *(optional)*) – Type

bpy.ops.graph.**paste**(*offset='START'*, *merge='MIX'*)
Paste keyframes from copy/paste buffer for the selected channels, starting on the current frame

Parameters

- **offset** (*enum in* ['START', 'END', 'RELATIVE', 'NONE'], *(optional)*) – Offset, Paste time offset of keys
- **merge** (*enum in* ['MIX', 'OVER_ALL', 'OVER_RANGE', 'OVER_RANGE_ALL'], *(optional)*) – Type, Method of merging pasted keys and existing

bpy.ops.graph.**previewrange_set**()
Automatically set Preview Range based on range of keyframes

bpy.ops.graph.**properties**()

Toggle display properties panel

bpy.ops.graph.**sample**()

Add keyframes on every frame between the selected keyframes

bpy.ops.graph.**select_all_toggle**(*invert=False*)

Toggle selection of all keyframes

Parameters **invert** (*boolean, (optional)*) – Invert

bpy.ops.graph.**select_border**(*gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0,*

axis_range=False, include_handles=False)

Select all keyframes within the specified region

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **axis_range** (*boolean, (optional)*) – Axis Range
- **include_handles** (*boolean, (optional)*) – Include Handles, Are handles tested individually against the selection criteria

bpy.ops.graph.**select_column**(*mode='KEYS'*)

Select all keyframes on the specified frame(s)

Parameters **mode** (*enum in ['KEYS', 'CFRA', 'MARKERS_COLUMN', 'MARKERS_BETWEEN'], (optional)*) – Mode

bpy.ops.graph.**select_leftright**(*mode='CHECK', extend=False*)

Select keyframes to the left or the right of the current frame

Parameters

- **mode** (*enum in ['CHECK', 'LEFT', 'RIGHT'], (optional)*) – Mode
- **extend** (*boolean, (optional)*) – Extend Select

bpy.ops.graph.**select_less**()

Deselect keyframes on ends of selection islands

bpy.ops.graph.**select_linked**()

Select keyframes occurring the same F-Curves as selected ones

bpy.ops.graph.**select_more**()

Select keyframes beside already selected ones

bpy.ops.graph.**smooth**()

Apply weighted moving means to make selected F-Curves less bumpy

bpy.ops.graph.**snap**(*type='CFRA'*)

Snap selected keyframes to the chosen times/values

Parameters **type** (*enum in ['CFRA', 'VALUE', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER', 'HORIZONTAL'], (optional)*) – Type

```
bpy.ops.graph.sound_bake(filepath="", filter blender=False, filter image=False, filter movie=True, filter python=False, filter font=False, filter sound=True, filter text=False, filter btx=False, filter collada=False, filter folder=True, filemode=9, low=0.0, high=100000.0, attack=0.005, release=0.2, threshold=0.0, accumulate=False, use additive=False, square=False, sthreshold=0.1)
```

Bakes a sound wave to selected F-Curves

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter blender** (*boolean, (optional)*) – Filter .blend files
- **filter image** (*boolean, (optional)*) – Filter image files
- **filter movie** (*boolean, (optional)*) – Filter movie files
- **filter python** (*boolean, (optional)*) – Filter python files
- **filter font** (*boolean, (optional)*) – Filter font files
- **filter sound** (*boolean, (optional)*) – Filter sound files
- **filter text** (*boolean, (optional)*) – Filter text files
- **filter btx** (*boolean, (optional)*) – Filter btx files
- **filter collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **low** (*float in [0, 100000], (optional)*) – Lowest frequency
- **high** (*float in [0, 100000], (optional)*) – Highest frequency
- **attack** (*float in [0, 2], (optional)*) – Attack time
- **release** (*float in [0, 5], (optional)*) – Release time
- **threshold** (*float in [0, 1], (optional)*) – Threshold
- **accumulate** (*boolean, (optional)*) – Accumulate
- **use additive** (*boolean, (optional)*) – Additive
- **square** (*boolean, (optional)*) – Square
- **sthreshold** (*float in [0, 1], (optional)*) – Square Threshold

```
bpy.ops.graph.view_all()
```

Reset viewable area to show full keyframe range

```
bpy.ops.graph.view_selected()
```

Reset viewable area to show selected keyframe range

Group Operators

```
bpy.ops.group.create(name="Group")
```

Create an object group from selected objects

Parameters **name** (*string, (optional)*) – Name, Name of the new group

bpy.ops.group.objects_add_active()
Add the object to an object group that contains the active object

bpy.ops.group.objects_remove()
Remove selected objects from all groups

bpy.ops.group.objects_remove_active()
Remove the object from an object group that contains the active object

Help Operators

bpy.ops.help.operator_cheat_sheet()
Undocumented ([contribute](#))

File [startup/bl_ui/space_info.py:384](#)

Image Operators

bpy.ops.image.curves_point_set(*point='BLACK_POINT'*)
Undocumented ([contribute](#))

Parameters **point** (*enum in ['BLACK_POINT', 'WHITE_POINT']*, *(optional)*) – Point, Set black point or white point for curves.

bpy.ops.image.cycle_render_slot(*reverse=False*)
Undocumented ([contribute](#))

Parameters **reverse** (*boolean, (optional)*) – Cycle in Reverse

bpy.ops.image.external_edit(*filepath=""*)
Edit image in an external application

Parameters **filepath** (*string, (optional)*) – File Path, Path to an image file

File [startup/bl_operators/image.py:57](#)

bpy.ops.image.invert(*invert_r=False, invert_g=False, invert_b=False, invert_a=False*)
Undocumented ([contribute](#))

Parameters

- **invert_r** (*boolean, (optional)*) – Red, Invert Red Channel
- **invert_g** (*boolean, (optional)*) – Green, Invert Green Channel
- **invert_b** (*boolean, (optional)*) – Blue, Invert Blue Channel
- **invert_a** (*boolean, (optional)*) – Alpha, Invert Alpha Channel

bpy.ops.image.new(*name="untitled", width=1024, height=1024, color=(0.0, 0.0, 0.0, 1.0), alpha=True, uv_test_grid=False, float=False*)

Create a new image

Parameters

- **name** (*string, (optional)*) – Name, Image datablock name.
- **width** (*int in [1, inf], (optional)*) – Width, Image width.
- **height** (*int in [1, inf], (optional)*) – Height, Image height.
- **color** (*float array of 4 items in [0, inf], (optional)*) – Color, Default fill color.
- **alpha** (*boolean, (optional)*) – Alpha, Create an image with an alpha channel.

- **uv_test_grid** (*boolean, (optional)*) – UV Test Grid, Fill the image with a grid for UV map testing.
- **float** (*boolean, (optional)*) – 32 bit Float, Create image with 32 bit floating point bit depth.

```
bpy.ops.image.open(filepath=""", filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)
```

Open image

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

```
bpy.ops.image.pack(as_png=False)
```

Pack an image as embedded data into the .blend file

Parameters **as_png** (*boolean, (optional)*) – Pack As PNG, Pack image as lossless PNG.

```
bpy.ops.image.project_apply()
```

Project edited image back onto the object

File `startup/bl_operators/image.py:188`

```
bpy.ops.image.project_edit()
```

Edit a snapshot of the viewport in an external image editor

File `startup/bl_operators/image.py:122`

```
bpy.ops.image.properties()
```

Toggle display properties panel

```
bpy.ops.image.record_composite()
```

Undocumented ([contribute](#))

```
bpy.ops.image.reload()
```

Undocumented ([contribute](#))

```
bpy.ops.image.replace(filepath="", filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)
```

Undocumented ([contribute](#))

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

```
bpy.ops.image.sample()
```

Undocumented ([contribute](#))

```
bpy.ops.image.sample_line(xstart=0, xend=0, ystart=0, yend=0, cursor=1002)
```

Undocumented ([contribute](#))

Parameters

- **xstart** (*int in [-inf, inf], (optional)*) – X Start
- **xend** (*int in [-inf, inf], (optional)*) – X End
- **ystart** (*int in [-inf, inf], (optional)*) – Y Start
- **yend** (*int in [-inf, inf], (optional)*) – Y End
- **cursor** (*int in [0, inf], (optional)*) – Cursor, Mouse cursor style to use during the modal operator

```
bpy.ops.image.save()
```

Undocumented ([contribute](#))

```
bpy.ops.image.save_as(file_type='PNG', filepath="", check_existing=True, filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, copy=False)
```

Undocumented ([contribute](#))

Parameters

- **file_type** (*enum in ['TARGA', 'TARGA RAW', 'PNG', 'BMP', 'JPEG', 'IRIS'], (optional)*) – File Type, File type to save image as.

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **copy** (*boolean, (optional)*) – Copy, Create a new image file without modifying the current image in blender

bpy.ops.image.**save_dirty**()

Save all modified textures

File startup/bl_operators/image.py:99

bpy.ops.image.**save_sequence**()

Undocumented (contribute)

bpy.ops.image.**scopes**()

Toggle display scopes panel

bpy.ops.image.**unpack**(method='USE_LOCAL', id="")

Save an image packed in the .blend file to disk

Parameters

- **method** (*enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL'], (optional)*) – Method, How to unpack.
- **id** (*string, (optional)*) – Image Name, Image datablock name to unpack.

bpy.ops.image.**view_all**()

Undocumented (contribute)

bpy.ops.image.**view_pan**(offset=(0.0, 0.0))

Undocumented (contribute)

Parameters **offset** (*float array of 2 items in [-inf, inf], (optional)*) – Offset, Offset in floating point units, 1.0 is the width and height of the image.

bpy.ops.image.**view_selected**()

Undocumented (contribute)

```
bpy.ops.image.view_zoom(factor=0.0)
Undocumented (contribute)
```

Parameters **factor** (*float in [0, inf], (optional)*) – Factor, Zoom factor, values higher than 1.0 zoom in, lower values zoom out.

```
bpy.ops.image.view_zoom_in()
Undocumented (contribute)
```

```
bpy.ops.image.view_zoom_out()
Undocumented (contribute)
```

```
bpy.ops.image.view_zoom_ratio(ratio=0.0)
Undocumented (contribute)
```

Parameters **ratio** (*float in [0, inf], (optional)*) – Ratio, Zoom ratio, 1.0 is 1:1, higher is zoomed in, lower is zoomed out.

Import Anim Operators

```
bpy.ops.import_anim.bvh(filepath="",
                        filter_glob="*.bvh",
                        target='ARMATURE',
                        global_scale=1.0,
                        frame_start=1,
                        use_cyclic=False,
                        rotate_mode='NATIVE')
```

Load a BVH motion capture file

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **target** (*enum in ['ARMATURE', 'OBJECT'], (optional)*) – Target, Import target type.
- **global_scale** (*float in [0.0001, 1e+06], (optional)*) – Scale, Scale the BVH by this value
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Starting frame for the animation
- **use_cyclic** (*boolean, (optional)*) – Loop, Loop the animation playback
- **rotate_mode** (*enum in ['QUATERNION', 'NATIVE', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'], (optional)*) – Rotation, Rotation conversion.

File addons/io_anim_bvh/__init__.py:82

Import Curve Operators

```
bpy.ops.import_curve.svg(filepath="",
                        filter_glob="*.svg")
```

Load a SVG file

Parameters **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file

File addons/io_curve_svg/__init__.py:57

Import Mesh Operators

```
bpy.ops.import_mesh.ply(filepath="",
                        files=None,
                        directory="",
                        filter_glob="*.ply")
```

Load a PLY geometry file

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file

- **files** (bpy_prop_collection of OperatorFileListElement, (optional)) – File Path, File path used for importing the PLY file

File addons/io_mesh_ply/__init__.py:65

```
bpy.ops.import_mesh.stl(filepath="", filter_glob="*.stl", files=None, directory="")
```

Load STL triangle mesh data

Parameters

- **filepath** (string, (optional)) – File Path, Filepath used for importing the file
- **files** (bpy_prop_collection of OperatorFileListElement, (optional)) – File Path, File path used for importing the STL file

File addons/io_mesh_stl/__init__.py:82

Import Scene Operators

```
bpy.ops.import_scene.autodesk_3ds(filepath="", filter_glob="*.3ds", constrain_size=10.0,  
use_image_search=True, use_apply_transform=True,  
axis_forward='Y', axis_up='Z')
```

Import from 3DS file format (.3ds)

Parameters

- **filepath** (string, (optional)) – File Path, Filepath used for importing the file
- **constrain_size** (float in [0, 1000], (optional)) – Size Constraint, Scale the model by 10 until it reaches the size constraint. Zero Disables.
- **use_image_search** (boolean, (optional)) – Image Search, Search subdirectories for any associated images (Warning, may be slow)
- **use_apply_transform** (boolean, (optional)) – Apply Transform, Workaround for object transformations importing incorrectly
- **axis_forward** (enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)) – Forward
- **axis_up** (enum in ['X', 'Y', 'Z', '-X', '-Y', '-Z'], (optional)) – Up

File addons/io_scene_3ds/__init__.py:85

```
bpy.ops.import_scene.obj(filepath="", filter_glob="*.obj;*.mtl", use_ngons=True,  
use_edges=True, use_smooth_groups=True, use_split_objects=True,  
use_split_groups=True, use_groups_as_vgroups=False,  
use_image_search=True, split_mode='ON', global_clamp_size=0.0,  
axis_forward='-Z', axis_up='Y')
```

Load a Wavefront OBJ File

Parameters

- **filepath** (string, (optional)) – File Path, Filepath used for importing the file
- **use_ngons** (boolean, (optional)) – NGons, Import faces with more than 4 verts as fgons
- **use_edges** (boolean, (optional)) – Lines, Import lines and faces with 2 verts as edge
- **use_smooth_groups** (boolean, (optional)) – Smooth Groups, Surround smooth groups by sharp edges
- **use_split_objects** (boolean, (optional)) – Object, Import OBJ Objects into Blender Objects
- **use_split_groups** (boolean, (optional)) – Group, Import OBJ Groups into Blender Objects

- **use_groups_as_vgroups** (*boolean, (optional)*) – Poly Groups, Import OBJ groups as vertex groups.
- **use_image_search** (*boolean, (optional)*) – Image Search, Search subdirs for any assosiated images (Warning, may be slow)
- **split_mode** (*enum in [‘ON’, ‘OFF’], (optional)*) – Split
- **global_clamp_size** (*float in [0, 1000], (optional)*) – Clamp Scale, Clamp the size to this maximum (Zero to Disable)
- **axis_forward** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Forward
- **axis_up** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Up

File addons/io_scene_obj/__init__.py:104

```
bpy.ops.import_scene.x3d(filepath="", filter_glob="*.x3d;*.wrl", axis_forward='Z',  
axis_up='Y')
```

Import and X3D or VRML file

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath used for importing the file
- **axis_forward** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Forward
- **axis_up** (*enum in [‘X’, ‘Y’, ‘Z’, ‘-X’, ‘-Y’, ‘-Z’], (optional)*) – Up

File addons/io_scene_x3d/__init__.py:79

Info Operators

bpy.ops.info.report_copy()

Copy selected reports to Clipboard

bpy.ops.info.report_delete()

Delete selected reports

bpy.ops.info.report_replay()

Replay selected reports

bpy.ops.info.reports_display_update()

Undocumented (contribute)

bpy.ops.info.select_all_toggle()

(de)select all reports

bpy.ops.info.select_border(*gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0*)

Toggle border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.info.select_pick(*report_index=0*)

Select reports by index

Parameters `report_index` (*int in [0, inf], (optional)*) – Report, The index of the report.

Lamp Operators

`bpy.ops.lamp.sunsky_preset_add(name=""", remove_active=False)`
Add a Sky & Atmosphere Preset

Parameters `name` (*string, (optional)*) – Name, Name of the preset, used to make the path name

File `startup/bl_operators/presets.py:42`

Lattice Operators

`bpy.ops.lattice.make_regular()`
Set UVW control points a uniform distance apart

`bpy.ops.lattice.select_all(action='TOGGLE')`
Change selection of all UVW control points

Parameters `action` (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

Logic Operators

`bpy.ops.logic.actuator_add(type='', name=""", object=""")`
Add a actuator to the active object

Parameters

- `type` (*enum in [], (optional)*) – Type, Type of actuator to add
- `name` (*string, (optional)*) – Name, Name of the Actuator to add
- `object` (*string, (optional)*) – Object, Name of the Object to add the Actuator to

`bpy.ops.logic.actuator_move(actuator=""", object=""", direction='UP')`
Move Actuator

Parameters

- `actuator` (*string, (optional)*) – Actuator, Name of the actuator to edit
- `object` (*string, (optional)*) – Object, Name of the object the actuator belongs to
- `direction` (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Move Up or Down

`bpy.ops.logic.actuator_remove(actuator=""", object=""")`
Remove a actuator from the active object

Parameters

- `actuator` (*string, (optional)*) – Actuator, Name of the actuator to edit
- `object` (*string, (optional)*) – Object, Name of the object the actuator belongs to

`bpy.ops.logic.controller_add(type='LOGIC_AND', name=""", object=""")`
Add a controller to the active object

Parameters

- **type** (*enum in ['LOGIC_AND', 'LOGIC_OR', 'LOGIC_NAND', 'LOGIC_NOR', 'LOGIC_XOR', 'LOGIC_XNOR', 'EXPRESSION', 'PYTHON']*, *(optional)*) – Type, Type of controller to add
- **name** (*string, (optional)*) – Name, Name of the Controller to add
- **object** (*string, (optional)*) – Object, Name of the Object to add the Controller to

bpy.ops.logic.controller_move(controller="“, object=““, direction='UP')

Move Controller

Parameters

- **controller** (*string, (optional)*) – Controller, Name of the controller to edit
- **object** (*string, (optional)*) – Object, Name of the object the controller belongs to
- **direction** (*enum in ['UP', 'DOWN']*, *(optional)*) – Direction, Move Up or Down

bpy.ops.logic.controller_remove(controller="“, object=““)

Remove a controller from the active object

Parameters

- **controller** (*string, (optional)*) – Controller, Name of the controller to edit
- **object** (*string, (optional)*) – Object, Name of the object the controller belongs to

bpy.ops.logic.links_cut(path=None, cursor=9)

Remove logic brick connections

Parameters

- **path** (*bpy_prop_collection of OperatorMousePath, (optional)*) – path
- **cursor** (*int in [0, inf], (optional)*) – Cursor

bpy.ops.logic.properties()

Toggle display properties panel

bpy.ops.logic.sensor_add(type="“, name=““, object=““)

Add a sensor to the active object

Parameters

- **type** (*enum in [], (optional)*) – Type, Type of sensor to add
- **name** (*string, (optional)*) – Name, Name of the Sensor to add
- **object** (*string, (optional)*) – Object, Name of the Object to add the Sensor to

bpy.ops.logic.sensor_move(sensor="“, object=““, direction='UP')

Move Sensor

Parameters

- **sensor** (*string, (optional)*) – Sensor, Name of the sensor to edit
- **object** (*string, (optional)*) – Object, Name of the object the sensor belongs to
- **direction** (*enum in ['UP', 'DOWN']*, *(optional)*) – Direction, Move Up or Down

bpy.ops.logic.sensor_remove(sensor="“, object=““)

Remove a sensor from the active object

Parameters

- **sensor** (*string, (optional)*) – Sensor, Name of the sensor to edit

- **object** (*string, (optional)*) – Object, Name of the object the sensor belongs to

Marker Operators

bpy.ops.marker.**add()**

Add a new time marker

bpy.ops.marker.**camera_bind()**

Bind the active camera to selected markers(s)

bpy.ops.marker.**delete()**

Delete selected time marker(s)

bpy.ops.marker.**duplicate(frames=0)**

Duplicate selected time marker(s)

Parameters frames (*int in [-inf, inf], (optional)*) – Frames

bpy.ops.marker.**make_links_scene(scene='')**

Copy selected markers to another scene

Parameters scene (*enum in [], (optional)*) – Scene

bpy.ops.marker.**move(frames=0)**

Move selected time marker(s)

Parameters frames (*int in [-inf, inf], (optional)*) – Frames

bpy.ops.marker.**rename(name="RenamedMarker")**

Rename first selected time marker

Parameters name (*string, (optional)*) – Name, New name for marker

bpy.ops.marker.**select(extend=False, camera=False)**

Select time marker(s)

Parameters

- **extend** (*boolean, (optional)*) – Extend, extend the selection
- **camera** (*boolean, (optional)*) – Camera, Select the camera

bpy.ops.marker.**select_all(action='TOGGLE')**

Change selection of all time markers

Parameters action (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.marker.**select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)**

Select all time markers using border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

Material Operators

```
bpy.ops.material.copy()  
    Copy the material settings and nodes
```

```
bpy.ops.material.new()  
    Add a new material
```

```
bpy.ops.material.paste()  
    Paste the material settings and nodes
```

```
bpy.ops.material.sss_preset_add(name=""“, remove_active=False)  
    Add a Subsurface Scattering Preset
```

Parameters `name` (*string, (optional)*) – Name, Name of the preset, used to make the path name

File `startup/bl_operators/presets.py:42`

Mball Operators

```
bpy.ops.mball.delete_metaelems()  
    Delete selected metaelement(s)
```

```
bpy.ops.mball.duplicate_metaelems(mode='TRANSLATION')  
    Delete selected metaelement(s)
```

Parameters `mode` (*enum in [‘INIT’, ‘DUMMY’, ‘TRANSLATION’, ‘ROTATION’, ‘RESIZE’, ‘TOPSPHERE’, ‘SHEAR’, ‘WARP’, ‘SHRINKFATTEN’, ‘TILT’, ‘TRACKBALL’, ‘PUSHPULL’, ‘CREASE’, ‘MIRROR’, ‘BONE_SIZE’, ‘BONE_ENVELOPE’, ‘CURVE_SHRINKFATTEN’, ‘BONE_ROLL’, ‘TIME_TRANSLATE’, ‘TIME_SLIDE’, ‘TIME_SCALE’, ‘TIME_EXTEND’, ‘BAKE_TIME’, ‘BEVEL’, ‘BWEIGHT’, ‘ALIGN’, ‘EDGESLIDE’, ‘SEQSLIDE’], (optional)*) – Mode

```
bpy.ops.mball.hide_metaelems(unselected=False)  
    Hide (un)selected metaelement(s)
```

Parameters `unselected` (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

```
bpy.ops.mball.reveal_metaelems()  
    Reveal all hidden metaelements
```

```
bpy.ops.mball.select_all(action='TOGGLE')  
    Change selection of all meta elements
```

Parameters `action` (*enum in [‘TOGGLE’, ‘SELECT’, ‘DESELECT’, ‘INVERT’], (optional)*) – Action, Selection action to execute

```
bpy.ops.mball.select_inverse_metaelems()  
    Select inverse of (un)selected metaelements
```

```
bpy.ops.mball.select_random_metaelems(percent=0.5)  
    Randomly select metaelements
```

Parameters `percent` (*float in [0, 1], (optional)*) – Percent, Percentage of metaelems to select randomly.

Mesh Operators

```
bpy.ops.mesh.beautify_fill()  
    Rearrange geometry on a selected surface to avoid skinny faces
```

bpy.ops.mesh.blend_from_shape(*shape*='', *blend*=1.0, *add*=False)
Blend in shape from a shape key

Parameters

- **shape** (*enum in []*, *(optional)*) – Shape, Shape key to use for blending.
- **blend** (*float in [-inf, inf]*, *(optional)*) – Blend, Blending factor.
- **add** (*boolean*, *(optional)*) – Add, Add rather than blend between shapes.

bpy.ops.mesh.colors_mirror(*axis*='X')
Mirror UV/image color layer

Parameters **axis** (*enum in ['X', 'Y']*, *(optional)*) – Axis, Axis to mirror colors around.

bpy.ops.mesh.colors_rotate(*direction*='CW')
Rotate UV/image color layer

Parameters **direction** (*enum in ['CW', 'CCW']*, *(optional)*) – Direction, Direction to rotate edge around.

bpy.ops.mesh.delete(*type*='VERT')
Delete selected vertices, edges or faces

Parameters **type** (*enum in ['VERT', 'EDGE', 'FACE', 'ALL', 'EDGE_FACE', 'ONLY_FACE', 'EDGE_LOOP']*, *(optional)*) – Type, Method used for deleting mesh data

bpy.ops.mesh.delete_edgeloop()
Delete an edge loop by merging the faces on each side to a single face loop

File startup/bl_operators/wm.py:33

bpy.ops.mesh.drop_named_image(*name*="Image", *filepath*="Path")
Assigns Image to active UV layer, or creates a UV layer

Parameters

- **name** (*string*, *(optional)*) – Name, Image name to assign.
- **filepath** (*string*, *(optional)*) – Filepath, Path to image file

bpy.ops.mesh.dupli_extrude_cursor(*rotate_source*=True)
Duplicate and extrude selected vertices, edges or faces towards 3D Cursor

Parameters **rotate_source** (*boolean*, *(optional)*) – Rotate Source, Rotate initial selection giving better shape

bpy.ops.mesh.duplicate(*mode*='TRANSLATION')
Duplicate selected vertices, edges or faces

Parameters **mode** (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO_SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE']*, *(optional)*) – Mode

bpy.ops.mesh.duplicate_move(*MESH_OT_duplicate*=None, *TRANSFORM_OT_translate*=None)
Undocumented ([contribute](#))

Parameters

- **MESH_OT_duplicate** (*MESH_OT_duplicate*, *(optional)*) – Duplicate Mesh, Duplicate selected vertices, edges or faces

- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

bpy.ops.mesh.edge_face_add()
Add an edge or face to selected

bpy.ops.mesh.edge_flip()
Flip selected edge or adjoining faces

bpy.ops.mesh.edge_rotate(*direction='CW'*)
Rotate selected edge or adjoining faces

Parameters **direction** (*enum in ['CW', 'CCW'], (optional)*) – Direction, Direction to rotate the edge around.

bpy.ops.mesh.edgering_select(*extend=False*)
Select an edge ring

Parameters **extend** (*boolean, (optional)*) – Extend, Extend the selection

bpy.ops.mesh.edges_select_sharp(*sharpness=0.01*)
Marked selected edges as sharp

Parameters **sharpness** (*float in [0, inf], (optional)*) – sharpness

bpy.ops.mesh.extrude(*type='REGION'*)
Extrude selected vertices, edges or faces

Parameters **type** (*enum in ['REGION', 'FACES', 'EDGES', 'VERTS'], (optional)*) – Type

bpy.ops.mesh.extrude_edges_move(*MESH_OT_extrude=None,* *TRANS-*
FORM_OT_translate=None)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (MESH_OT_extrude, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

bpy.ops.mesh.extrude_faces_move(*MESH_OT_extrude=None,* *TRANS-*
FORM_OT_shrink_fatten=None)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (MESH_OT_extrude, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_shrink_fatten** (TRANSFORM_OT_shrink_fatten, (optional)) – Shrink/Fatten, Shrink/fatten selected vertices along normals

bpy.ops.mesh.extrude_region_move(*MESH_OT_extrude=None,* *TRANS-*
FORM_OT_translate=None)
Undocumented (contribute)

Parameters

- **MESH_OT_extrude** (MESH_OT_extrude, (optional)) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

bpy.ops.mesh.**extrude_repeat** (*offset=2.0, steps=10, direction=(0.0, 0.0, 0.0)*)
Extrude selected vertices, edges or faces repeatedly

Parameters

- **offset** (*float in [0, 100], (optional)*) – Offset
- **steps** (*int in [0, 180], (optional)*) – Steps
- **direction** (*float array of 3 items in [-inf, inf], (optional)*) – Direction, Direction of extrude

bpy.ops.mesh.**extrude_vertices_move** (*MESH_OT_extrude=None, FORM_OT_translate=None*)
TRANS-
Undocumented ([contribute](#))

Parameters

- **MESH_OT_extrude** (*MESH_OT_extrude, (optional)*) – Extrude, Extrude selected vertices, edges or faces
- **TRANSFORM_OT_translate** (*TRANSFORM_OT_translate, (optional)*) – Translate, Translate selected items

bpy.ops.mesh.**faces_mirror_uv** (*direction='POSITIVE'*)
Copy mirror UV coordinates on the X axis based on a mirrored mesh

Parameters **direction** (*enum in ['POSITIVE', 'NEGATIVE'], (optional)*) – Axis Direction

File [startup/bl_operators/mesh.py:87](#)

bpy.ops.mesh.**faces_select_interior**()
Select faces where all edges have more then 2 face users.

File [startup/bl_operators/mesh.py:38](#)

bpy.ops.mesh.**faces_select_linked_flat** (*sharpness=135.0*)
Select linked faces by angle

Parameters **sharpness** (*float in [0, inf], (optional)*) – sharpness

bpy.ops.mesh.**faces_shade_flat**()
Display faces ‘flat’

bpy.ops.mesh.**faces_shade_smooth**()
Display faces ‘smooth’ (using vertex normals)

bpy.ops.mesh.**fgon_clear**()
Clear fgons from selected face

bpy.ops.mesh.**fgon_make**()
Make fgons from selected faces

bpy.ops.mesh.**fill**()
Create a segment, edge or face

bpy.ops.mesh.**flip_normals**()
Toggle the direction of selected face’s vertex and face normals

bpy.ops.mesh.**hide** (*unselected=False*)
Hide (un)selected vertices, edges or faces

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

bpy.ops.mesh.**knife_cut** (*type='EXACT', path=None, num_cuts=1, cursor=9*)
Cut selected edges and faces into parts

Parameters

- **type** (*enum in ['EXACT', 'MIDPOINTS', 'MULTICUT']*, *(optional)*) – Type
- **path** (*bpy_prop_collection of OperatorMousePath*, *(optional)*) – path
- **num_cuts** (*int in [1, 256]*, *(optional)*) – Number of Cuts, Only for Multi-Cut
- **cursor** (*int in [0, inf]*, *(optional)*) – Cursor

`bpy.ops.mesh.loop_multi_select(ring=False)`

Select a loop of connected edges by connection type

Parameters **ring** (*boolean, (optional)*) – Ring

`bpy.ops.mesh.loop_select(extend=False, ring=False)`

Select a loop of connected edges

Parameters

- **extend** (*boolean, (optional)*) – Extend Select
- **ring** (*boolean, (optional)*) – Select Ring

`bpy.ops.mesh.loop_to_region()`

Select a loop of connected edges as a region

`bpy.ops.mesh.loopcut(number_cuts=1)`

Add a new loop between existing loops

Parameters **number_cuts** (*int in [1, inf]*, *(optional)*) – Number of Cuts

`bpy.ops.mesh.loopcut_slide(MESH_OT_loopcut=None, TRANSFORM_OT_edge_slide=None)`

Undocumented ([contribute](#))

Parameters

- **MESH_OT_loopcut** (*MESH_OT_loopcut, (optional)*) – Loop Cut, Add a new loop between existing loops
- **TRANSFORM_OT_edge_slide** (*TRANSFORM_OT_edge_slide, (optional)*) – Edge Slide, Slide an edge loop along a mesh

`bpy.ops.mesh.mark_seam(clear=False)`

(un)mark selected edges as a seam

Parameters **clear** (*boolean, (optional)*) – Clear

`bpy.ops.mesh.mark_sharp(clear=False)`

(un)mark selected edges as sharp

Parameters **clear** (*boolean, (optional)*) – Clear

`bpy.ops.mesh.merge(type='CENTER', uvs=False)`

Merge selected vertices

Parameters

- **type** (*enum in ['FIRST', 'LAST', 'CENTER', 'CURSOR', 'COLLAPSE']*, *(optional)*) – Type, Merge method to use.
- **uvs** (*boolean, (optional)*) – UVs, Move UVs according to merge.

`bpy.ops.mesh.noise(factor=0.1)`

Use vertex coordinate as texture coordinate

Parameters **factor** (*float in [-inf, inf]*, *(optional)*) – Factor

```
bpy.ops.mesh.normals_make_consistent(inside=False)
Flip all selected vertex and face normals in a consistent direction
```

Parameters **inside** (*boolean, (optional)*) – Inside

```
bpy.ops.mesh.primitive_circle_add(vertices=32, radius=1.0, fill=False, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a circle mesh

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **fill** (*boolean, (optional)*) – Fill
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_cone_add(vertices=32, radius=1.0, depth=2.0, cap_end=True, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a conic mesh (ends filled)

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **depth** (*float in [0, inf], (optional)*) – Depth
- **cap_end** (*boolean, (optional)*) – Cap End
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_cube_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a cube mesh

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_cylinder_add(vertices=32, radius=1.0, depth=2.0, cap_ends=True, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a cylinder mesh

Parameters

- **vertices** (*int in [-inf, inf], (optional)*) – Vertices
- **radius** (*float in [0, inf], (optional)*) – Radius
- **depth** (*float in [0, inf], (optional)*) – Depth
- **cap_ends** (*boolean, (optional)*) – Cap Ends
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_grid_add(x_subdivisions=10, y_subdivisions=10, size=1.0, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a grid mesh

Parameters

- **x_subdivisions** (*int in [-inf, inf], (optional)*) – X Subdivisions
- **y_subdivisions** (*int in [-inf, inf], (optional)*) – Y Subdivisions

- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_ico_sphere_add(subdivisions=2, size=1.0, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct an Icosphere mesh

Parameters

- **subdivisions** (*int in [0, inf], (optional)*) – Subdivisions
- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_monkey_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Suzanne mesh

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_plane_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a filled planar mesh with 4 vertices

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.mesh.primitive_torus_add(major_radius=1.0, minor_radius=0.25, major_segments=48, minor_segments=12, use_abso=False, abso_major_rad=1.0, abso_minor_rad=0.5, view_align=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0))
```

Add a torus mesh

Parameters

- **major_radius** (*float in [0.01, 100], (optional)*) – Major Radius, Radius from the origin to the center of the cross sections
- **minor_radius** (*float in [0.01, 100], (optional)*) – Minor Radius, Radius of the torus' cross section
- **major_segments** (*int in [3, 256], (optional)*) – Major Segments, Number of segments for the main ring of the torus
- **minor_segments** (*int in [3, 256], (optional)*) – Minor Segments, Number of segments for the minor ring of the torus
- **use_abso** (*boolean, (optional)*) – Use Int+Ext Controls, Use the Int / Ext controls for torus dimensions
- **abso_major_rad** (*float in [0.01, 100], (optional)*) – Exterior Radius, Total Exterior Radius of the torus
- **abso_minor_rad** (*float in [0.01, 100], (optional)*) – Inside Radius, Total Interior Radius of the torus
- **view_align** (*boolean, (optional)*) – Align to View
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation

File `startup/bl_operators/add_mesh_torus.py:114`

```
bpy.ops.mesh.primitive_uv_sphere_add(segments=32, ring_count=16, size=1.0, view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a UV sphere mesh

Parameters

- **segments** (*int in [-inf, inf], (optional)*) – Segments
- **ring_count** (*int in [-inf, inf], (optional)*) – Rings
- **size** (*float in [0, inf], (optional)*) – Size
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.mesh.**quads_convert_to_tris()**

Convert selected quads to triangles

bpy.ops.mesh.**region_to_loop()**

Select a region as a loop of connected edges

bpy.ops.mesh.**remove_doubles** (*limit=0.0001*)

Remove duplicate vertices

Parameters **limit** (*float in [1e-06, 50], (optional)*) – Merge Threshold, Minimum distance between merged verts

bpy.ops.mesh.**reveal()**

Reveal all hidden vertices, edges and faces

bpy.ops.mesh.**rip** (*constraint_axis=(False, False, False)*, *constraint_orientation=''*, *mirror=False*, *release_confirm=False*)

Rip selection from mesh (quads only)

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.mesh.**rip_move** (*MESH_OT_rip=None*, *TRANSFORM_OT_translate=None*)

Undocumented ([contribute](#))

Parameters

- **MESH_OT_rip** (*MESH_OT_rip, (optional)*) – Rip, Rip selection from mesh (quads only)
- **TRANSFORM_OT_translate** (*TRANSFORM_OT_translate, (optional)*) – Translate, Translate selected items

bpy.ops.mesh.**screw** (*steps=9*, *turns=1*, *center=(0.0, 0.0, 0.0)*, *axis=(0.0, 0.0, 0.0)*)

Extrude selected vertices in screw-shaped rotation around the cursor in indicated viewport

Parameters

- **steps** (*int in [0, inf], (optional)*) – Steps, Steps
- **turns** (*int in [0, inf], (optional)*) – Turns, Turns
- **center** (*float array of 3 items in [-inf, inf], (optional)*) – Center, Center in global view space
- **axis** (*float array of 3 items in [-1, 1], (optional)*) – Axis, Axis in global view space

bpy.ops.mesh.**select_all** (*action='TOGGLE'*)

Change selection of all vertices, edges or faces

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.mesh.**select_axis** (*mode='POSITIVE', axis='X_AXIS'*)

Select all data in the mesh on a single axis

Parameters

- **mode** (*enum in ['POSITIVE', 'NEGATIVE', 'ALIGNED'], (optional)*) – Axis Mode, Axis side to use when selecting
- **axis** (*enum in ['X_AXIS', 'Y_AXIS', 'Z_AXIS'], (optional)*) – Axis, Select the axis to compare each vertex on

bpy.ops.mesh.**select_by_number_vertices** (*type='TRIANGLES'*)

Select vertices or faces by vertex count

Parameters **type** (*enum in ['TRIANGLES', 'QUADS', 'OTHER'], (optional)*) – Type, Type of elements to select.

bpy.ops.mesh.**select_inverse** ()

Select inverse of (un)selected vertices, edges or faces

bpy.ops.mesh.**select_less** ()

Select less vertices, edges or faces connected to initial selection

bpy.ops.mesh.**select_linked** (*limit=False*)

Select all vertices linked to the active mesh

Parameters **limit** (*boolean, (optional)*) – Limit by Seams, Limit selection by seam boundaries (faces only)

bpy.ops.mesh.**select_linked_pick** (*deselect=False, limit=False*)

(un)select all vertices linked to the active mesh

Parameters

- **deselect** (*boolean, (optional)*) – Deselect
- **limit** (*boolean, (optional)*) – Limit by Seams, Limit selection by seam boundaries (faces only)

bpy.ops.mesh.**select_mirror** (*extend=False*)

Select mesh items at mirrored locations

Parameters **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

bpy.ops.mesh.**select_more** ()

Select more vertices, edges or faces connected to initial selection

bpy.ops.mesh.**select_non_manifold** ()

Select all non-manifold vertices or edges

bpy.ops.mesh.**select_nth** (*nth=2*)

Undocumented ([contribute](#))

Parameters **nth** (*int in [2, 100], (optional)*) – Nth Selection

bpy.ops.mesh.select_random(*percent=50.0, extend=False*)
Randomly select vertices

Parameters

- **percent** (*float in [0, 100], (optional)*) – Percent, Percentage of elements to select randomly.
- **extend** (*boolean, (optional)*) – Extend Selection, Extend selection instead of deselecting everything first.

bpy.ops.mesh.select_shortest_path(*extend=False*)
Select shortest path between two selections

Parameters **extend** (*boolean, (optional)*) – Extend Select

bpy.ops.mesh.select_similar(*type='NORMAL', threshold=0.01*)
Select similar vertices, edges or faces by property types

Parameters

- **type** (*enum in ['NORMAL', 'FACE', 'VGROUP', 'LENGTH', 'DIR', 'FACE', 'FACE_ANGLE', 'CREASE', 'SEAM', 'SHARP', 'MATERIAL', 'IMAGE', 'AREA', 'PERIMETER', 'NORMAL', 'COPLANAR'], (optional)*) – Type
- **threshold** (*float in [0, inf], (optional)*) – Threshold

bpy.ops.mesh.select_vertex_path(*type='EDGE_LENGTH'*)
Select shortest path between two vertices by distance type

Parameters **type** (*enum in ['EDGE_LENGTH', 'TOPOLOGICAL'], (optional)*) – Type, Method to compute distance.

bpy.ops.mesh.separate(*type='SELECTED'*)
Separate selected geometry into a new mesh

Parameters **type** (*enum in ['SELECTED', 'MATERIAL', 'LOOSE'], (optional)*) – Type

bpy.ops.mesh.shape_propagate_to_all()
Apply selected vertex locations to all other shape keys

bpy.ops.mesh.solidify(*thickness=0.01*)
Create a solid skin by extruding, compensating for sharp angles

Parameters **thickness** (*float in [-inf, inf], (optional)*) – Thickness

bpy.ops.mesh.sort_faces(*type='VIEW_AXIS'*)
The faces of the active Mesh Object are sorted, based on the current view.

Parameters **type** (*enum in ['VIEW_AXIS', 'CURSOR_DISTANCE', 'MATERIAL', 'SELECTED', 'RANDOMIZE'], (optional)*) – Type

bpy.ops.mesh.spin(*steps=9, dupli=False, degrees=90.0, center=(0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0)*)
Extrude selected vertices in a circle around the cursor in indicated viewport

Parameters

- **steps** (*int in [0, inf], (optional)*) – Steps, Steps
- **dupli** (*boolean, (optional)*) – Dupli, Make Duplicates
- **degrees** (*float in [-inf, inf], (optional)*) – Degrees, Degrees
- **center** (*float array of 3 items in [-inf, inf], (optional)*) – Center, Center in global view space
- **axis** (*float array of 3 items in [-1, 1], (optional)*) – Axis, Axis in global view space

bpy.ops.mesh.**split()**

Split selected geometry into separate disconnected mesh

bpy.ops.mesh.**sticky_add()**

Add sticky UV texture layer

bpy.ops.mesh.**sticky_remove()**

Remove sticky UV texture layer

bpy.ops.mesh.**subdivide**(*number_cuts=1*, *smoothness=0.0*, *fractal=0.0*, *corner_cut_pattern='INNER_VERTEX'*)

Subdivide selected edges

Parameters

- **number_cuts** (*int in [1, inf], (optional)*) – Number of Cuts
- **smoothness** (*float in [0, inf], (optional)*) – Smoothness, Smoothness factor.
- **fractal** (*float in [0, inf], (optional)*) – Fractal, Fractal randomness factor.
- **corner_cut_pattern** (*enum in ['PATH', 'INNER_VERTEX', 'FAN'], (optional)*) – Corner Cut Pattern, Topology pattern to use to fill a face after cutting across its corner

bpy.ops.mesh.**tris_convert_to_quads()**

Convert selected triangles to quads

bpy.ops.mesh.**uv_texture_add()**

Add UV texture layer

bpy.ops.mesh.**uv_texture_remove()**

Remove UV texture layer

bpy.ops.mesh.**uvs_mirror**(*axis='X'*)

Mirror selected UVs

Parameters axis (*enum in ['X', 'Y'], (optional)*) – Axis, Axis to mirror UVs around.

bpy.ops.mesh.**uvs_rotate**(*direction='CW'*)

Rotate selected UVs

Parameters direction (*enum in ['CW', 'CCW'], (optional)*) – Direction, Direction to rotate UVs around.

bpy.ops.mesh.**vertex_color_add()**

Add vertex color layer

bpy.ops.mesh.**vertex_color_remove()**

Remove vertex color layer

bpy.ops.mesh.**vertices_randomize()**

Randomize vertex order

bpy.ops.mesh.**vertices_smooth**(*repeat=1*, *xaxis=True*, *yaxis=True*, *zaxis=True*)

Flatten angles of selected vertices

Parameters

- **repeat** (*int in [1, 100], (optional)*) – Smooth Iterations
- **xaxis** (*boolean, (optional)*) – X-Axis, Smooth along the X axis.
- **yaxis** (*boolean, (optional)*) – Y-Axis, Smooth along the Y axis.
- **zaxis** (*boolean, (optional)*) – Z-Axis, Smooth along the Z axis.

```
bpy.ops.mesh.vertices_sort()  
    Sort vertex order
```

Nla Operators

```
bpy.ops.nla.action_sync_length(active=True)  
    Synchronise the length of the referenced Action with the lengths used in the strip  
Parameters active (boolean, (optional)) – Active Strip Only, Only sync the active length for the active strip.
```

```
bpy.ops.nla.actionclip_add(action='')  
    Add an Action-Clip strip (i.e. an NLA Strip referencing an Action) to the active track
```

Parameters action (enum in [], (optional)) – Action

```
bpy.ops.nla.apply_scale()  
    Apply scaling of selected strips to their referenced Actions
```

```
bpy.ops.nla.bake(frame_start=1, frame_end=250, step=1, only_selected=True,  
                  clear_constraints=False, bake_types={'POSE'})  
    Bake animation to an Action
```

Parameters

- **frame_start** (int in [1, 300000], (optional)) – Start Frame, Start frame for baking
- **frame_end** (int in [1, 300000], (optional)) – End Frame, End frame for baking
- **step** (int in [1, 120], (optional)) – Frame Step, Frame Step
- **only_selected** (boolean, (optional)) – Only Selected
- **clear_constraints** (boolean, (optional)) – Clear Constraints
- **bake_types** (enum set in {'POSE', 'OBJECT'}, (optional)) – Bake Data

File startup/bl_operators/nla.py:222

```
bpy.ops.nla.channels_click(extend=False)  
    Handle clicks to select NLA channels
```

Parameters extend (boolean, (optional)) – Extend Select

```
bpy.ops.nla.clear_scale()  
    Reset scaling of selected strips
```

```
bpy.ops.nla.click_select(extend=False)  
    Handle clicks to select NLA Strips
```

Parameters extend (boolean, (optional)) – Extend Select

```
bpy.ops.nla.delete()  
    Delete selected strips
```

```
bpy.ops.nla.delete_tracks()  
    Delete selected NLA-Tracks and the strips they contain
```

```
bpy.ops.nla.duplicate(mode='TRANSLATION')  
    Duplicate selected NLA-Strips, adding the new strips in new tracks above the originals
```

Parameters mode (enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO-SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN',

`'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE']`, (optional)) – Mode

`bpy.ops.nla.fmodifier_add(type='NULL', only_active=False)`
Add F-Modifier of the specified type to the selected NLA-Strips

Parameters

- **type** (*enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED']*, *(optional)*) – Type
 - **only_active** (*boolean, (optional)*) – Only Active, Only add F-Modifier of the specified type to the active strip.

`bpy.ops.nla.fmodifier_copy()`

Copy the F-Modifier(s) of the active NLA-Strip

```
bpy.ops.nla.fmodifier_paste()
```

Add copied F-Modifiers to the selected NLA-Strips

`bpy.ops.nla.meta_add()`

Add new meta-strips incorporating the selected strips

```
bpy.ops.nla.meta_remove()
```

Separate out the strips held by the selected meta-strips

```
bpy.ops.nla.move_down()
```

Move selected strips down a track if there's room

```
bpy.ops.nla.move_up()
```

Move selected strips up a track if there's room

```
bpy.ops.nla.mute_toggle()
```

Mute or un-mute selected strips

`bpy.ops.nla.properties()`

Toggle display properties panel

```
bpy.ops.nla.select_all_toggle(invert=False)
```

(De)Select all NI A-Strips

Parameters

```
bpy.ops.nla.select_border(gesture_mode=0,      xmin=0,      xmax=0,      ymin=0,      ymax=0,  
                           axis_range=False)
```

axis
Use box selection to grab NLA-Strips

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
 - **xmin** (*int in [-inf, inf], (optional)*) – X Min
 - **xmax** (*int in [-inf, inf], (optional)*) – X Max
 - **ymin** (*int in [-inf, inf], (optional)*) – Y Min
 - **ymax** (*int in [-inf, inf], (optional)*) – Y Max
 - **axis range** (*boolean, (optional)*) – Axis Range

```
bpy.ops.nla.select_leftright(mode='CHECK', extend=False)
```

Select strips to the left or the right of the current frame.

Parameters

- **mode** (*enum in ['CHECK', 'LEFT', 'RIGHT']*, *(optional)*) – Mode
- **extend** (*boolean, (optional)*) – Extend Select

bpy.ops.nla.snap(type='CFRA')

Move start of strips to specified time

Parameters type (*enum in ['CFRA', 'NEAREST_FRAME', 'NEAREST_SECOND', 'NEAREST_MARKER']*, *(optional)*) – Type

bpy.ops.nla.split()

Split selected strips at their midpoints

bpy.ops.nla.swap()

Swap order of selected strips within tracks

bpy.ops.nla.tracks_add(above_selected=False)

Add NLA-Tracks above/after the selected tracks

Parameters above_selected (*boolean, (optional)*) – Above Selected, Add a new NLA Track above every existing selected one.

bpy.ops.nla.transition_add()

Add a transition strip between two adjacent selected strips

bpy.ops.nla.tweakmode_enter()

Enter tweaking mode for the action referenced by the active strip

bpy.ops.nla.tweakmode_exit()

Exit tweaking mode for the action referenced by the active strip

Node Operators

bpy.ops.node.add_file(filepath="", filter_blender=False, filter_image=True, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, name="Image")

Add a file node to the current node editor

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

- **name** (*string, (optional)*) – Name, Datablock name to assign.

bpy.ops.node.backimage_move()
Move Node backdrop

bpy.ops.node.backimage_sample()
Undocumented (contribute)

bpy.ops.node.backimage_zoom(*factor=1.2*)
Undocumented (contribute)

Parameters **factor** (*float in [0, 10], (optional)*) – Factor

bpy.ops.node.delete()
Delete selected nodes

bpy.ops.node.duplicate()
Duplicate the nodes

bpy.ops.node.duplicate_move(*NODE_OT_duplicate=None, TRANSFORM_OT_translate=None*)
Undocumented (contribute)

Parameters

- **NODE_OT_duplicate** (*NODE_OT_duplicate, (optional)*) – Duplicate Nodes, Duplicate the nodes
- **TRANSFORM_OT_translate** (*TRANSFORM_OT_translate, (optional)*) – Translate, Translate selected items

bpy.ops.node.group_edit()
Edit node group

bpy.ops.node.group_make()
Make group from selected nodes

bpy.ops.node.group_socket_add(*in_out='IN', name=""*, *type='VALUE'*)
Add node group socket

Parameters

- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output
- **name** (*string, (optional)*) – Name, Group socket name
- **type** (*enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)*) – Type, Type of the group socket

bpy.ops.node.group_socket_move_down(*index=0, in_out='IN'*)
Move down node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

bpy.ops.node.group_socket_move_up(*index=0, in_out='IN'*)
Move up node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

bpy.ops.node.group_socket_remove(*index=0, in_out='IN'*)
Removed node group socket

Parameters

- **index** (*int in [0, inf], (optional)*) – Index
- **in_out** (*enum in ['IN', 'OUT'], (optional)*) – Socket Type, Input or Output

bpy.ops.node.**group_ungroup**()

Ungroup selected nodes

bpy.ops.node.**hide_socket_toggle**()

Toggle unused node socket display

bpy.ops.node.**hide_toggle**()

Toggle hiding of selected nodes

bpy.ops.node.**link**()

Undocumented ([contribute](#))

bpy.ops.node.**link_make**(*replace=False*)

Makes a link between selected output in input sockets

Parameters **replace** (*boolean, (optional)*) – Replace, Replace socket connections with the new links

bpy.ops.node.**link_viewer**()

Link to Viewer Node

bpy.ops.node.**links_cut**(*path=None, cursor=9*)

Undocumented ([contribute](#))

Parameters

- **path** (*bpy_prop_collection of OperatorMousePath, (optional)*) – path
- **cursor** (*int in [0, inf], (optional)*) – Cursor

bpy.ops.node.**mute_toggle**()

Toggle muting of the nodes

bpy.ops.node.**preview_toggle**()

Toggle preview display for selected nodes

bpy.ops.node.**properties**()

Toggles the properties panel display

bpy.ops.node.**read_fullsamplelayers**()

Undocumented ([contribute](#))

bpy.ops.node.**read_renderlayers**()

Undocumented ([contribute](#))

bpy.ops.node.**render_changed**()

Undocumented ([contribute](#))

bpy.ops.node.**resize**()

Undocumented ([contribute](#))

bpy.ops.node.**select**(*mouse_x=0, mouse_y=0, extend=False*)

Select node under cursor

Parameters

- **mouse_x** (*int in [-inf, inf], (optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf], (optional)*) – Mouse Y
- **extend** (*boolean, (optional)*) – Extend

bpy.ops.node.select_all()
(De)select all nodes

bpy.ops.node.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, tweak=False)
Use box selection to select nodes

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **tweak** (*boolean, (optional)*) – Tweak, Only activate when mouse is not over a node - useful for tweak gesture

bpy.ops.node.select_link_viewer(NODE_OT_select=None, NODE_OT_link_viewer=None)
Undocumented ([contribute](#))

Parameters

- **NODE_OT_select** (*NODE_OT_select, (optional)*) – Select, Select node under cursor
- **NODE_OT_link_viewer** (*NODE_OT_link_viewer, (optional)*) – Link to Viewer Node, Link to Viewer Node

bpy.ops.node.select_linked_from()
Select nodes linked from the selected ones

bpy.ops.node.select_linked_to()
Select nodes linked to the selected ones

bpy.ops.node.select_same_type()
Select all the same type

bpy.ops.node.select_same_type_next()
Select the next node of the same type.

bpy.ops.node.select_same_type_prev()
Select the prev node of the same type.

bpy.ops.node.show_cyclic_dependencies()
Sort the nodes and show the cyclic dependencies between the nodes

bpy.ops.node.view_all()
Resize view so you can see all nodes

bpy.ops.node.visibility_toggle(mouse_x=0, mouse_y=0)
Handle clicks on node header buttons

Parameters

- **mouse_x** (*int in [-inf, inf], (optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf], (optional)*) – Mouse Y

Object Operators

```
bpy.ops.object.add(type='EMPTY', view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Add an object to the scene

Parameters

- **type** (*enum in ['MESH', 'CURVE', 'SURFACE', 'META', 'FONT', 'ARMATURE', 'LATTICE', 'EMPTY', 'CAMERA', 'LAMP']*, *(optional)*) – Type
- **view_align** (*boolean*, *(optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean*, *(optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items*, *(optional)*) – Layer

```
bpy.ops.object.add_named(linked=False, name="Cube")
```

Add named object

Parameters

- **linked** (*boolean*, *(optional)*) – Linked, Duplicate object but not object data, linking to the original data
- **name** (*string*, *(optional)*) – Name, Object name to add

```
bpy.ops.object.add_named_cursor(name="Cube", VIEW3D_OT_cursor3d=None, OBJECT_OT_add_named=None)
```

Undocumented ([contribute](#))

Parameters

- **name** (*string*, *(optional)*) – Name, Object name to add.
- **VIEW3D_OT_cursor3d** (*VIEW3D_OT_cursor3d*, *(optional)*) – Set 3D Cursor, Set the location of the 3D cursor
- **OBJECT_OT_add_named** (*OBJECT_OT_add_named*, *(optional)*) – Add Named Object, Add named object

```
bpy.ops.object.align(align_mode='OPT_2', relative_to='OPT_4', align_axis=set())
```

Align Objects

Parameters

- **align_mode** (*enum in ['OPT_1', 'OPT_2', 'OPT_3']*, *(optional)*) – Align Mode:
- **relative_to** (*enum in ['OPT_1', 'OPT_2', 'OPT_3', 'OPT_4']*, *(optional)*) – Relative To:
- **align_axis** (*enum set in {'X', 'Y', 'Z'}*, *(optional)*) – Align, Align to axis

File [startup/bl_operators/object_align.py:272](#)

```
bpy.ops.object.armature_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0),  
    rotation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False,  
    False, False, False, False, False, False, False, False, False, False, False,  
    False, False, False, False))
```

Add an armature object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.object.bake_image()
```

Bake image textures of selected objects

```
bpy.ops.object.camera_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), ro-  
    tation=(0.0, 0.0, 0.0), layers=(False, False, False, False, False,  
    False, False, False, False, False, False, False, False, False, False, False,  
    False, False, False))
```

Add a camera object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.object.constraint_add(type='')
```

Add a constraint to the active object

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE',
 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION',
 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO',
 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO',
 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT',
 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

```
bpy.ops.object.constraint_add_with_targets(type='')
```

Add a constraint to the active object, with target (where applicable) set to the selected Objects/Bones

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE',
 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION',
 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO',
 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO',*

'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT',
'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)) – Type

bpy.ops.object.constraints_clear()

Clear all the constraints for the active Object only

bpy.ops.object.constraints_copy()

Copy constraints to other selected objects.

bpy.ops.object.convert(target='MESH', keep_original=False)

Convert selected objects to another type

Parameters

- **target** (enum in ['CURVE', 'MESH'], (optional)) – Target, Type of object to convert to
- **keep_original** (boolean, (optional)) – Keep Original, Keep original objects instead of replacing them

bpy.ops.object.delete()

Delete selected objects

bpy.ops.object.drop_named_material(name="Material")

Undocumented (contribute)

Parameters name (string, (optional)) – Name, Material name to assign.

bpy.ops.object.duplicate(linked=False, mode='TRANSLATION')

Duplicate selected objects

Parameters

- **linked** (boolean, (optional)) – Linked, Duplicate object but not object data, linking to the original data
- **mode** (enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TOSPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)) – Mode

bpy.ops.object.duplicate_move(OBJECT_OT_duplicate=None,
FORM_OT_translate=None)

TRANS-

Undocumented (contribute)

Parameters

- **OBJECT_OT_duplicate** (OBJECT_OT_duplicate, (optional)) – Duplicate Objects, Duplicate selected objects
- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

bpy.ops.object.duplicate_move_linked(OBJECT_OT_duplicate=None,
FORM_OT_translate=None)

TRANS-

Undocumented (contribute)

Parameters

- **OBJECT_OT_duplicate** (OBJECT_OT_duplicate, (optional)) – Duplicate Objects, Duplicate selected objects
- **TRANSFORM_OT_translate** (TRANSFORM_OT_translate, (optional)) – Translate, Translate selected items

```
bpy.ops.object.duplicates_make_real()  
    Make dupli objects attached to this object real  
  
bpy.ops.object.editmode_toggle()  
    Toggle object's editmode  
  
bpy.ops.object.effector_add(type='FORCE', view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))  
    Add an empty object with a physics effector to the scene
```

Parameters

- **type** (enum in ['FORCE', 'WIND', 'VORTEX', 'MAGNET', 'HARMONIC', 'CHARGE', 'LENNARDJ', 'TEXTURE', 'GUIDE', 'BOID', 'TURBULENCE', 'DRAG'], (optional)) – Type
- **view_align** (boolean, (optional)) – Align to View, Align the new object to the view
- **enter_editmode** (boolean, (optional)) – Enter Editmode, Enter editmode when adding this object
- **location** (float array of 3 items in [-inf, inf], (optional)) – Location, Location for the newly added object
- **rotation** (float array of 3 items in [-inf, inf], (optional)) – Rotation, Rotation for the newly added object
- **layers** (boolean array of 20 items, (optional)) – Layer

```
bpy.ops.object.explode_refresh(modifier="")  
    Refresh data in the Explode modifier
```

Parameters **modifier** (string, (optional)) – Modifier, Name of the modifier to edit

```
bpy.ops.object.forcefield_toggle()  
    Toggle object's force field
```

```
bpy.ops.object.game_property_clear()  
    Undocumented (contribute)
```

```
bpy.ops.object.game_property_copy(operation='COPY', property='')  
    Undocumented (contribute)
```

Parameters

- **operation** (enum in ['REPLACE', 'MERGE', 'COPY'], (optional)) – Operation
- **property** (enum in [], (optional)) – Property, Properties to copy

```
bpy.ops.object.game_property_new()  
    Create a new property available to the game engine
```

```
bpy.ops.object.game_property_remove(index=0)  
    Remove game property
```

Parameters **index** (int in [0, inf], (optional)) – Index, Property index to remove

```
bpy.ops.object.group_add()  
    Add an object to a new group
```

```
bpy.ops.object.group_instance_add(group='', view_align=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Add a dupligroup instance

Parameters

- **group** (*enum in [], (optional)*) – Group
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.object.group_link(group='')
```

Add an object to an existing group

Parameters **group** (*enum in [], (optional)*) – Group

```
bpy.ops.object.group_remove()
```

Undocumented ([contribute](#))

```
bpy.ops.object.hide_render_clear()
```

Reveal the render object by setting the hide render flag

```
bpy.ops.object.hide_render_clear_all()
```

Reveal all render objects by setting the hide render flag

File [startup/bl_operators/object.py:563](#)

```
bpy.ops.object.hide_render_set(unselected=False)
```

Hide the render object by setting the hide render flag

Parameters unselected (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

```
bpy.ops.object.hide_view_clear()
```

Reveal the object by setting the hide flag

```
bpy.ops.object.hide_view_set(unselected=False)
```

Hide the object by setting the hide flag

Parameters unselected (*boolean, (optional)*) – Unselected, Hide unselected rather than selected objects.

```
bpy.ops.object.hook_add_newob()
```

Hook selected vertices to the first selected Object

```
bpy.ops.object.hook_add_selob()
```

Hook selected vertices to the first selected Object

```
bpy.ops.object.hook_assign(modifier='')
```

Assign the selected vertices to a hook

Parameters modifier (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

```
bpy.ops.object.hook_recenter(modifier='')
```

Set hook center to cursor position

Parameters modifier (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

bpy.ops.object.hook_remove(modifier='')

Remove a hook from the active object

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to remove.

bpy.ops.object.hook_reset(modifier='')

Recalculate and clear offset transformation

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to assign to.

bpy.ops.object.hook_select(modifier='')

Selects effected vertices on mesh

Parameters **modifier** (*enum in [], (optional)*) – Modifier, Modifier number to remove.

bpy.ops.object.isolate_type_render()

Hide unselected render objects of same type as active by setting the hide render flag

File [startup/bl_operators/object.py:543](#)

bpy.ops.object.join()

Join selected objects into active object

bpy.ops.object.join_shapes()

Merge selected objects to shapes of active object

bpy.ops.object.join_uvs()

Copy UV Layout to objects with matching geometry

File [startup/bl_operators/object.py:465](#)

bpy.ops.object.lamp_add(type='POINT', view_align=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))

Add a lamp object to the scene

Parameters

- **type** (*enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA']*, *(optional)*) – Type
- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.object.location_clear()

Clear the object's location

bpy.ops.object.logic_bricks_copy()

Copy logic bricks to other selected objects.

bpy.ops.object.make_dupli_face()

Make linked objects into dupli-faces

File [startup/bl_operators/object.py:532](#)

bpy.ops.object.make_links_data(type='OBDATA')

Make links from the active object to other selected objects

Parameters `type` (*enum in ['OBDATA', 'MATERIAL', 'ANIMATION', 'DUPLIGROUP', 'MODIFIERS']*, *(optional)*) – Type

```
bpy.ops.object.make_links_scene(scene='')
```

Make linked data local to each object

Parameters `scene` (*enum in [], (optional)*) – Scene

`bpy.ops.object.make_local(type='SELECTED_OBJECTS')`
Make library linked datablocks local to this file

Parameters `type` (`enum in ['SELECTED_OBJECTS', 'SELECTED_OBJECTS_DATA', 'ALL']`, *(optional)*) – Type

```
bpy.ops.object.make_single_user(type='SELECTED_OBJECTS', object=False, obdata=False,  
material=False, texture=False, animation=False)
```

Make linked data local to each object

Parameters

- **type** (*enum in ['SELECTED_OBJECTS', 'ALL']*, *(optional)*) – Type
 - **object** (*boolean*, *(optional)*) – Object, Make single user objects
 - **obdata** (*boolean*, *(optional)*) – Object Data, Make single user object data
 - **material** (*boolean*, *(optional)*) – Materials, Make materials local to each datablock
 - **texture** (*boolean*, *(optional)*) – Textures, Make textures local to each material
 - **animation** (*boolean*, *(optional)*) – Object Animation, Make animation data local to each object

```
bpy.ops.object.material_slot_add()
```

Add a new material slot or duplicate the selected one

```
bpy.ops.object.material_slot_assign()
```

Assign the material in the selected material slot to the selected vertices

```
bpy.ops.object.material_slot_copy()
```

Copies materials to other selected objects

```
bpy.ops.object.material_slot_deselect()
```

Deselect vertices assigned to the selected material slot

```
bpy.ops.object.material_slot_remove()
```

Remove the selected material slot

```
bpy.ops.object.material_slot_select()
```

Select vertices assigned to the selected material slot

```
bpy.ops.object.meshdeform_bind(modifier="")
```

Bind mesh to cage in mesh deform modifier

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

Add an metaball object to the scene

Parameters

- **type** (*enum in ['BALL', 'CAPSULE', 'PLANE', 'ELLIPSOID', 'CUBE']*, *(optional)*) – Primitive

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

bpy.ops.object.mode_set (*mode='OBJECT'*, *toggle=False*)

Sets the object interaction mode

Parameters

- **mode** (*enum in ['OBJECT', 'EDIT', 'SCULPT', 'VERTEX_PAINT', 'WEIGHT_PAINT', 'TEXTURE_PAINT', 'PARTICLE_EDIT', 'POSE'], (optional)*) – Mode
- **toggle** (*boolean, (optional)*) – Toggle

bpy.ops.object.modifier_add (*type='SUBSURF'*)

Add a modifier to the active object

Parameters type (*enum in ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WARP', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE'], (optional)*) – Type

bpy.ops.object.modifier_apply (*apply_as='DATA'*, *modifier=""*)

Apply modifier and remove from the stack

Parameters

- **apply_as** (*enum in ['DATA', 'SHAPE'], (optional)*) – Apply as, How to apply the modifier to the geometry
- **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.modifier_convert (*modifier=""*)

Convert particles to a mesh object

Parameters modifier (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.modifier_copy (*modifier=""*)

Duplicate modifier at the same position in the stack

Parameters modifier (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.modifier_move_down (*modifier=""*)

Move modifier down in the stack

Parameters modifier (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.modifier_move_up (*modifier=""*)

Move modifier up in the stack

Parameters modifier (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.modifier_remove (*modifier=""*)

Remove a modifier from the active object

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

```
bpy.ops.object.move_to_layer(layers=(False, False, False, False, False, False, False, False,  
                               False, False, False, False, False, False, False, False, False, False,  
                               False))
```

Move the object to different layers

Parameters **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.object.multires_base_apply(modifier="")
```

Modify the base mesh to conform to the displaced mesh

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

```
bpy.ops.object.multires_external_pack()
```

Pack displacements from an external file

```
bpy.ops.object.multires_external_save(filepath="", check_existing=True,  
                                      filter_blender=False, filter_image=False, filter_movie=False,  
                                      filter_python=False, filter_font=False, filter_sound=False, filter_text=False,  
                                      filter_btx=True, filter_collada=False, filter_folder=True, filemode=9,  
                                      relative_path=False, modifier="")
```

Save displacements to an external file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

```
bpy.ops.object.multires_higher_levels_delete(modifier="")
```

Deletes the higher resolution mesh, potential loss of detail

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

```
bpy.ops.object.multires_reshape(modifier="")
```

Copy vertex coordinates from other object

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.multires_subdivide(*modifier=""*)
Add a new level of subdivision

Parameters **modifier** (*string, (optional)*) – Modifier, Name of the modifier to edit

bpy.ops.object.origin_clear()
Clear the object's origin

bpy.ops.object.origin_set(*type='GEOMETRY_ORIGIN', center='MEDIAN'*)
Set the object's origin, by either moving the data, or set to center of data, or use 3d cursor

Parameters

- **type** (*enum in ['GEOMETRY_ORIGIN', 'ORIGIN_GEOMETRY', 'ORIGIN_CURSOR'], (optional)*) – Type
- **center** (*enum in ['MEDIAN', 'BOUNDS'], (optional)*) – Center

bpy.ops.object.parent_clear(*type='CLEAR'*)
Clear the object's parenting

Parameters **type** (*enum in ['CLEAR', 'CLEAR_KEEP_TRANSFORM', 'CLEAR_INVERSE'], (optional)*) – Type

bpy.ops.object.parent_no_inverse_set()
Set the object's parenting without setting the inverse parent correction

bpy.ops.object.parent_set(*type='OBJECT'*)
Set the object's parenting

Parameters **type** (*enum in ['OBJECT', 'ARMATURE', 'ARMATURE_NAME', 'ARMATURE_AUTO', 'ARMATURE_ENVELOPE', 'BONE', 'CURVE', 'FOLLOW', 'PATH_CONST', 'LATTICE', 'VERTEX', 'TRIA'], (optional)*) – Type

bpy.ops.object.particle_system_add()
Add a particle system

bpy.ops.object.particle_system_remove()
Remove the selected particle system

bpy.ops.object.paths_calculate()
Calculate paths for the selected bones

bpy.ops.object.paths_clear()
Clear path caches for selected bones

bpy.ops.object.posemode_toggle()
Enables or disables posing/selecting bones

bpy.ops.object.proxy_make(*object="" type='DEFAULT'*)
Add empty object to become local replacement data of a library-linked object

Parameters

- **object** (*string, (optional)*) – Proxy Object, Name of lib-linked/grouped object to make a proxy for.
- **type** (*enum in ['DEFAULT'], (optional)*) – Type, Group object

bpy.ops.object.quick_explode(*style='EXPLODE', amount=100, frame_duration=50, frame_start=1, frame_end=10, velocity=1.0, fade=True'*)

Undocumented (contribute)

Parameters

- **style** (*enum in [‘EXplode’, ‘BLEND’], (optional)*) – Explode Style
- **amount** (*int in [2, 10000], (optional)*) – Amount of pieces
- **frame_duration** (*int in [1, 300000], (optional)*) – Duration
- **frame_start** (*int in [1, 300000], (optional)*) – Start Frame
- **frame_end** (*int in [1, 300000], (optional)*) – End Frame
- **velocity** (*float in [0, 300000], (optional)*) – Outwards Velocity
- **fade** (*boolean, (optional)*) – Fade, Fade the pieces over time.

File startup/bl_operators/object_quick_effects.py:131

```
bpy.ops.object.quick_fluid(style='BASIC', initial_velocity=(0.0, 0.0, 0.0), show_flows=False,  
                           start_baking=False)
```

Undocumented ([contribute](#))

Parameters

- **style** (*enum in [‘INFLOW’, ‘BASIC’], (optional)*) – Fluid Style
- **initial_velocity** (*float array of 3 items in [-100, 100], (optional)*) – Initial Velocity, Initial velocity of the fluid
- **show_flows** (*boolean, (optional)*) – Render Fluid Objects, Keep the fluid objects visible during rendering.
- **start_baking** (*boolean, (optional)*) – Start Fluid Bake, Start baking the fluid immediately after creating the domain object.

File startup/bl_operators/object_quick_effects.py:393

```
bpy.ops.object.quick_fur(density='MEDIUM', view_percentage=10, length=0.1)
```

Undocumented ([contribute](#))

Parameters

- **density** (*enum in [‘LIGHT’, ‘MEDIUM’, ‘HEAVY’], (optional)*) – Fur Density
- **view_percentage** (*int in [1, 100], (optional)*) – View %
- **length** (*float in [0.001, 100], (optional)*) – Length

File startup/bl_operators/object_quick_effects.py:62

```
bpy.ops.object.quick_smoke(style='STREAM', show_flows=False)
```

Undocumented ([contribute](#))

Parameters

- **style** (*enum in [‘STREAM’, ‘PUFF’, ‘FIRE’], (optional)*) – Smoke Style
- **show_flows** (*boolean, (optional)*) – Render Smoke Objects, Keep the smoke objects visible during rendering.

File startup/bl_operators/object_quick_effects.py:277

```
bpy.ops.object.randomize_transform(random_seed=0, use_delta=False, use_loc=True,  
                                   loc=(0.0, 0.0, 0.0), use_rot=True, rot=(0.0, 0.0, 0.0),  
                                   use_scale=True, scale_even=False, scale=(0.0, 0.0, 0.0))
```

Randomize objects loc/rot/scale

Parameters

- **random_seed** (*int in [0, 1000], (optional)*) – Random Seed, Seed value for the random generator
- **use_delta** (*boolean, (optional)*) – Transform Delta, Randomize delta transform values instead of regular transform
- **use_loc** (*boolean, (optional)*) – Randomize Location, Randomize the location values
- **loc** (*float array of 3 items in [-100, 100], (optional)*) – Location, Maximum distance the objects can spread over each axis
- **use_rot** (*boolean, (optional)*) – Randomize Rotation, Randomize the rotation values
- **rot** (*float array of 3 items in [-180, 180], (optional)*) – Rotation, Maximum rotation over each axis
- **use_scale** (*boolean, (optional)*) – Randomize Scale, Randomize the scale values
- **scale_even** (*boolean, (optional)*) – Scale Even, Use the same scale value for all axis
- **scale** (*float array of 3 items in [-100, 100], (optional)*) – Scale, Maximum scale randomization over each axis

File startup/bl_operators/object_randomize_transform.py:131

bpy.ops.object.rotation_clear()

Clear the object's rotation

bpy.ops.object.scale_clear()

Clear the object's scale

bpy.ops.object.select_all(action='TOGGLE')

Change selection of all visible objects in scene

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.object.select_by_layer(extend=False, layers=1)

Select all visible objects on a layer

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **layers** (*int in [1, 20], (optional)*) – Layer

bpy.ops.object.select_by_type(extend=False, type='MESH')

Select all visible objects that are of a type

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['MESH', 'CURVE', 'SURFACE', 'META', 'FONT', 'ARMATURE', 'LATTICE', 'EMPTY', 'CAMERA', 'LAMP'], (optional)*) – Type

bpy.ops.object.select_camera()

Select object matching a naming pattern

File startup/bl_operators/object.py:84

bpy.ops.object.select_grouped(extend=False, type='CHILDREN_RECURSIVE')

Select all visible objects grouped by various properties

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in [‘CHILDREN_RECURSIVE’, ‘CHILDREN’, ‘PARENT’, ‘SIBLINGS’, ‘TYPE’, ‘LAYER’, ‘GROUP’, ‘HOOK’, ‘PASS’, ‘COLOR’, ‘PROPERTIES’], (optional)*) – Type

bpy.ops.object.select_hierarchy(*direction=’PARENT’, extend=False*)

Select object relative to the active objects position in the hierarchy

Parameters

- **direction** (*enum in [‘PARENT’, ‘CHILD’], (optional)*) – Direction, Direction to select in the hierarchy
- **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

File startup/bl_operators/object.py:114

bpy.ops.object.select_inverse()

Invert selection of all visible objects

bpy.ops.object.select_linked(*extend=False, type=’OBDATA’*)

Select all visible objects that are linked

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in [‘OBDATA’, ‘MATERIAL’, ‘TEXTURE’, ‘DUPGROUP’, ‘PARTICLE’, ‘LIBRARY’, ‘LIBRARY_OBDATA’], (optional)*) – Type

bpy.ops.object.select_mirror(*extend=False*)

Select the Mirror objects of the selected object eg. L.sword -> R.sword

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.object.select_name(*name=””, extend=False*)

Select an object with this name

Parameters

- **name** (*string, (optional)*) – Name, Object name to select.
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.object.select_pattern(*pattern=”*”, case_sensitive=False, extend=True*)

Select object matching a naming pattern

Parameters

- **pattern** (*string, (optional)*) – Pattern, Name filter using ‘*’ and ‘?’ wildcard chars
- **case_sensitive** (*boolean, (optional)*) – Case Sensitive, Do a case sensitive compare
- **extend** (*boolean, (optional)*) – Extend, Extend the existing selection

File startup/bl_operators/object.py:35

bpy.ops.object.select_random(*percent=50.0, extend=False*)

Set select on random visible objects

Parameters

- **percent** (*float in [0, 100], (optional)*) – Percent, Percentage of objects to select randomly
- **extend** (*boolean, (optional)*) – Extend Selection, Extend selection instead of deselecting everything first.

bpy.ops.object.select_same_group(*group=""*)

Select object in the same group

Parameters **group** (*string, (optional)*) – Group, Name of the group to select.

bpy.ops.object.shade_flat()

Display faces ‘flat’

bpy.ops.object.shade_smooth()

Display faces ‘smooth’ (using vertex normals)

bpy.ops.object.shape_key_add(*from_mix=True*)

Add shape key to the object

Parameters **from_mix** (*boolean, (optional)*) – From Mix, Create the new shape key from the existing mix of keys.

bpy.ops.object.shape_key_clear()

Clear weights for all shape keys

bpy.ops.object.shape_key_mirror()

Undocumented (contribute)

bpy.ops.object.shape_key_move(*type='UP'*)

Undocumented (contribute)

Parameters **type** (*enum in ['UP', 'DOWN'], (optional)*) – Type

bpy.ops.object.shape_key_remove()

Remove shape key from the object

bpy.ops.object.shape_key_transfer(*mode='OFFSET', use_clamp=False*)

Copy another selected objects active shape to this one by applying the relative offsets

Parameters

- **mode** (*enum in ['OFFSET', 'RELATIVE_FACE', 'RELATIVE_EDGE'], (optional)*) – Transformation Mode, Method to apply relative shape positions to the new shape
- **use_clamp** (*boolean, (optional)*) – Clamp Offset, Clamp the transformation to the distance each vertex moves in the original shape.

File startup/bl_operators/object.py:391

bpy.ops.object.slow_parent_clear()

Clear the object’s slow parent

bpy.ops.object.slow_parent_set()

Set the object’s slow parent

bpy.ops.object.subdivision_set(*level=1, relative=False*)

Sets a Subdivision Surface Level (1-5)

Parameters

- **level** (*int in [-100, 100], (optional)*) – Level
- **relative** (*boolean, (optional)*) – Relative, Apply the subsurf level as an offset relative to the current level

File startup/bl_operators/object.py:173

```
bpy.ops.object.text_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Add a text object to the scene

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.object.track_clear(type='CLEAR')
```

Clear tracking constraint or flag from object

Parameters **type** (*enum in ['CLEAR', 'CLEAR_KEEP_TRANSFORM'], (optional)*) – Type

```
bpy.ops.object.track_set(type='DAMPTRACK')
```

Make the object track another object, either by constraint or old way or locked track

Parameters **type** (*enum in ['DAMPTRACK', 'TRACKTO', 'LOCKTRACK'], (optional)*) – Type

```
bpy.ops.object.transform_apply(location=False, rotation=False, scale=False)
```

Apply the object's transformation to its data

Parameters

- **location** (*boolean, (optional)*) – Location
- **rotation** (*boolean, (optional)*) – Rotation
- **scale** (*boolean, (optional)*) – Scale

```
bpy.ops.object.vertex_group_add()
```

Undocumented (contribute)

```
bpy.ops.object.vertex_group_assign(new=False)
```

Undocumented (contribute)

Parameters **new** (*boolean, (optional)*) – New, Assign vertex to new vertex group.

```
bpy.ops.object.vertex_group_blend()
```

Undocumented (contribute)

```
bpy.ops.object.vertex_group_clean(limit=0.01, all_groups=False, keep_single=False)
```

Remove Vertex Group assignments which aren't required

Parameters

- **limit** (*float in [0, 1], (optional)*) – Limit, Remove weights under this limit.
- **all_groups** (*boolean, (optional)*) – All Groups, Clean all vertex groups.
- **keep_single** (*boolean, (optional)*) – Keep Single, Keep verts assigned to at least one group when cleaning.

bpy.ops.object.vertex_group_copy()
Undocumented (contribute)

bpy.ops.object.vertex_group_copy_to_linked()
Copy Vertex Groups to all users of the same Geometry data

bpy.ops.object.vertex_group_copy_to_selected()
Copy Vertex Groups to other selected objects with matching indices

bpy.ops.object.vertex_group_deselect()
Undocumented (contribute)

bpy.ops.object.vertex_group_invert (*auto_assign=True, auto_remove=True*)
Undocumented (contribute)

Parameters

- **auto_assign** (*boolean, (optional)*) – Add Weights, Add verts from groups that have zero weight before inverting.
- **auto_remove** (*boolean, (optional)*) – Remove Weights, Remove verts from groups that have zero weight after inverting.

bpy.ops.object.vertex_group_levels (*offset=0.0, gain=1.0*)
Undocumented (contribute)

Parameters

- **offset** (*float in [-1, 1], (optional)*) – Offset, Value to add to weights.
- **gain** (*float in [0, inf], (optional)*) – Gain, Value to multiply weights by.

bpy.ops.object.vertex_group_mirror (*mirror_weights=True, flip_group_names=True*)
Mirror all vertex groups, flip weights and/or names, editing only selected vertices, flipping when both sides are selected otherwise copy from unselected

Parameters

- **mirror_weights** (*boolean, (optional)*) – Mirror Weights, Mirror weights.
- **flip_group_names** (*boolean, (optional)*) – Flip Groups, Flip vertex group names.

bpy.ops.object.vertex_group_move (*direction='UP'*)
Undocumented (contribute)

Parameters **direction** (*enum in ['UP', 'DOWN'], (optional)*) – Direction, Direction to move, UP or DOWN

bpy.ops.object.vertex_group_normalize()
Undocumented (contribute)

bpy.ops.object.vertex_group_normalize_all (*lock_active=True*)
Undocumented (contribute)

Parameters **lock_active** (*boolean, (optional)*) – Lock Active, Keep the values of the active group while normalizing others.

bpy.ops.object.vertex_group_remove (*all=False*)
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Remove from all vertex groups.

bpy.ops.object.vertex_group_remove_from (*all=False*)
Undocumented (contribute)

Parameters **all** (*boolean, (optional)*) – All, Remove from all vertex groups.

```
bpy.ops.object.vertex_group_select()  
    Undocumented (contribute)  
  
bpy.ops.object.vertex_group_set_active(group='')  
    Set the active vertex group  
  
        Parameters group (enum in [], (optional)) – Group, Vertex group to set as active.  
  
bpy.ops.object.vertex_group_sort()  
    Sorts vertex groups alphabetically  
  
bpy.ops.object.vertex_parent_set()  
    Parent selected objects to the selected vertices  
  
bpy.ops.object.visual_transform_apply()  
    Apply the object's visual transformation to its data
```

Outliner Operators

```
bpy.ops.outliner.data_operation(type='SELECT')  
    Undocumented (contribute)  
  
        Parameters type (enum in ['SELECT', 'DESELECT', 'HIDE', 'UNHIDE'], (optional)) – Data Operation  
  
bpy.ops.outliner.drivers_add_selected()  
    Add drivers to selected items  
  
bpy.ops.outliner.drivers_delete_selected()  
    Delete drivers assigned to selected items  
  
bpy.ops.outliner.expanded_toggle()  
    Expand/Collapse all items  
  
bpy.ops.outliner.group_operation(type='UNLINK')  
    Undocumented (contribute)  
  
        Parameters type (enum in ['UNLINK', 'LOCAL', 'LINK', 'TOGVIS', 'TOGSEL', 'TOGREN'], (optional)) – Group Operation  
  
bpy.ops.outliner.id_operation(type='UNLINK')  
    Undocumented (contribute)  
  
        Parameters type (enum in ['UNLINK', 'LOCAL'], (optional)) – ID data Operation  
  
bpy.ops.outliner.item_activate(extend=True)  
    Handle mouse clicks to activate/select items  
  
        Parameters extend (boolean, (optional)) – Extend, Extend selection for activation.  
  
bpy.ops.outliner.item_openclose(all=True)  
    Toggle whether item under cursor is enabled or closed  
  
        Parameters all (boolean, (optional)) – All, Close or open all items.  
  
bpy.ops.outliner.item_rename()  
    Rename item under cursor  
  
bpy.ops.outliner.keyingset_add_selected()  
    Add selected items (blue-grey rows) to active Keying Set  
  
bpy.ops.outliner.keyingset_remove_selected()  
    Remove selected items (blue-grey rows) from active Keying Set
```

```
bpy.ops.outliner.object_operation(type='SELECT')
Undocumented (contribute)

Parameters type (enum in ['SELECT', 'DESELECT', 'DELETE', 'TOGVIS', 'TOGSEL',
'TOGREN'], (optional)) – Object Operation

bpy.ops.outliner.operation()
Context menu for item operations

bpy.ops.outliner.renderability_toggle()
Toggle the renderability of selected items

bpy.ops.outliner.scroll_page(up=False)
Scroll page up or down

Parameters up (boolean, (optional)) – Up, Scroll up one page.

bpy.ops.outliner.selectability_toggle()
Toggle the selectability

bpy.ops.outliner.selected_toggle()
Toggle the Outliner selection of items

bpy.ops.outliner.show_active()
Adjust the view so that the active Object is shown centered

bpy.ops.outliner.show_hierarchy()
Open all object entries and close all others

bpy.ops.outliner.show_one_level(open=True)
Expand/collapse all entries by one level

Parameters open (boolean, (optional)) – Open, Expand all entries one level deep.

bpy.ops.outliner.visibility_toggle()
Toggle the visibility of selected items
```

Paint Operators

```
bpy.ops.paint.clone_cursor_set(location=(0.0, 0.0, 0.0))
Undocumented (contribute)

Parameters location (float array of 3 items in [-inf, inf], (optional)) – Location, Cursor location in
world space coordinates.

bpy.ops.paint.face_select_all(action='TOGGLE')
Change selection for all faces

Parameters action (enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)) – Ac-
tion, Selection action to execute

bpy.ops.paint.face_select_hide(unselected=False)
Hide selected faces

Parameters unselected (boolean, (optional)) – Unselected, Hide unselected rather than selected
objects.

bpy.ops.paint.face_select_inverse()
Invert selection of faces

bpy.ops.paint.face_select_linked()
Select linked faces
```

```
bpy.ops.paint.face_select_linked_pick(extend=False)
    Select linked faces

    Parameters extend (boolean, (optional)) – Extend, Extend the existing selection

bpy.ops.paint.face_select_reveal(unselected=False)
    Reveal hidden faces

    Parameters unselected (boolean, (optional)) – Unselected, Hide unselected rather than selected
        objects.

bpy.ops.paint.grab_clone(delta=(0.0, 0.0))
    Undocumented (contribute)

    Parameters delta (float array of 2 items in [-inf, inf], (optional)) – Delta, Delta offset of clone
        image in 0.0..1.0 coordinates.

bpy.ops.paint.image_from_view(filepath="")
    Make an image from the current 3D view for re-projection

    Parameters filepath (string, (optional)) – File Path, Name of the file

bpy.ops.paint.image_paint(stroke=None)
    Undocumented (contribute)

    Parameters stroke (bpy_prop_collection of OperatorStrokeElement, (optional)) –
        Stroke

bpy.ops.paint.project_image(image='')
    Project an edited render from the active camera back onto the object

    Parameters image (enum in [], (optional)) – Image

bpy.ops.paint.sample_color(location=(0, 0))
    Undocumented (contribute)

    Parameters location (int array of 2 items in [0, inf], (optional)) – Location, Cursor location in
        region coordinates.

bpy.ops.paint.texture_paint_toggle()
    Undocumented (contribute)

bpy.ops.paint.vertex_color_dirt(blur_strength=1.0, blur_iterations=1, clean_angle=180.0,
                               dirt_angle=0.0, dirt_only=False)
    Undocumented (contribute

    Parameters

        • blur_strength (float in [0.01, 1], (optional)) – Blur Strength, Blur strength per iteration

        • blur_iterations (int in [0, 40], (optional)) – Blur Iterations, Number times to blur the colors.
            (higher blurs more)

        • clean_angle (float in [0, 180], (optional)) – Highlight Angle, Less then 90 limits the angle
            used in the tonal range

        • dirt_angle (float in [0, 180], (optional)) – Dirt Angle, Less then 90 limits the angle used in
            the tonal range

        • dirt_only (boolean, (optional)) – Dirt Only, Dont calculate cleans for convex areas

File startup/bl_operators/vertexpaint_dirt.py:159

bpy.ops.paint.vertex_color_set()
    Undocumented (contribute)
```

bpy.ops.paint.vertex_paint(stroke=None)
Undocumented ([contribute](#))

Parameters **stroke** (bpy_prop_collection of OperatorStrokeElement, (optional)) – Stroke

bpy.ops.paint.vertex_paint_toggle()
Undocumented ([contribute](#))

bpy.ops.paint.weight_from_bones(type='AUTOMATIC')
Undocumented ([contribute](#))

Parameters **type** (enum in ['AUTOMATIC', 'ENVELOPES'], (optional)) – Type, Method to use for assigning weights.

bpy.ops.paint.weight_paint(stroke=None)
Undocumented ([contribute](#))

Parameters **stroke** (bpy_prop_collection of OperatorStrokeElement, (optional)) – Stroke

bpy.ops.paint.weight_paint_toggle()
Undocumented ([contribute](#))

bpy.ops.paint.weight_sample()
Undocumented ([contribute](#))

bpy.ops.paint.weight_sample_group(group='DEFAULT')
Undocumented ([contribute](#))

Parameters **group** (enum in ['DEFAULT'], (optional)) – Keying Set, The Keying Set to use

bpy.ops.paint.weight_set()
Undocumented ([contribute](#))

Particle Operators

bpy.ops.particle.brush_edit(stroke=None)
Undocumented ([contribute](#))

Parameters **stroke** (bpy_prop_collection of OperatorStrokeElement, (optional)) – Stroke

bpy.ops.particle.connect_hair(all=False)
Connect hair to the emitter mesh

Parameters **all** (boolean, (optional)) – All hair, Connect all hair systems to the emitter mesh

bpy.ops.particle.delete(type='PARTICLE')
Undocumented ([contribute](#))

Parameters **type** (enum in ['PARTICLE', 'KEY'], (optional)) – Type, Delete a full particle or only keys.

bpy.ops.particle.disconnect_hair(all=False)
Disconnect hair from the emitter mesh

Parameters **all** (boolean, (optional)) – All hair, Disconnect all hair systems from the emitter mesh

bpy.ops.particle.dupliob_copy()
Duplicate the current dupliobject

bpy.ops.particle.**dupliob_move_down()**
Move dupli object down in the list

bpy.ops.particle.**dupliob_move_up()**
Move dupli object up in the list

bpy.ops.particle.**dupliob_remove()**
Remove the selected dupliobject

bpy.ops.particle.**edited_clear()**
Undocumented (contribute)

bpy.ops.particle.**hide (unselected=False)**
Undocumented (contribute)

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

bpy.ops.particle.**mirror()**
Undocumented (contribute)

bpy.ops.particle.**new()**
Add new particle settings

bpy.ops.particle.**new_target()**
Add a new particle target

bpy.ops.particle.**particle_edit_toggle()**
Undocumented (contribute)

bpy.ops.particle.**rekey (keys=2)**
Undocumented (contribute)

Parameters **keys** (*int in [2, inf], (optional)*) – Number of Keys

bpy.ops.particle.**remove_doubles (threshold=0.0002)**
Undocumented (contribute)

Parameters **threshold** (*float in [0, inf], (optional)*) – Threshold, Threshold distance withing which particles are removed

bpy.ops.particle.**reveal()**
Undocumented (contribute)

bpy.ops.particle.**select_all (action='TOGGLE')**
Undocumented (contribute)

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.particle.**select_inverse()**
Undocumented (contribute)

bpy.ops.particle.**select_less()**
Undocumented (contribute)

bpy.ops.particle.**select_linked (deselect=False, location=(0, 0))**
Undocumented (contribute)

Parameters

- **deselect** (*boolean, (optional)*) – Deselect, Deselect linked keys rather than selecting them.
- **location** (*int array of 2 items in [0, inf], (optional)*) – Location

```
bpy.ops.particle.select_more()  
    Undocumented (contribute)  
  
bpy.ops.particle.select_roots()  
    Undocumented (contribute)  
  
bpy.ops.particle.select_tips()  
    Undocumented (contribute)  
  
bpy.ops.particle.subdivide()  
    Undocumented (contribute)  
  
bpy.ops.particle.target_move_down()  
    Move particle target down in the list  
  
bpy.ops.particle.target_move_up()  
    Move particle target up in the list  
  
bpy.ops.particle.target_remove()  
    Remove the selected particle target  
  
bpy.ops.particle.weight_set (factor=1.0)  
    Undocumented (contribute)
```

Parameters **factor** (*float in [0, 1], (optional)*) – Factor

Pose Operators

```
bpy.ops.pose.armature_apply()  
    Apply the current pose as the new rest pose  
  
bpy.ops.pose.armature_layers (layers=(False, False, False, False, False, False, False, False,  
                                False, False, False, False, False, False, False, False, False,  
                                False, False, False, False, False, False, False, False, False,  
                                False, False, False))  
    Change the visible armature layers
```

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers to make visible

```
bpy.ops.pose.autoside_names (axis='XAXIS')  
    Automatically renames the selected bones according to which side of the target axis they fall on
```

Parameters **axis** (*enum in ['XAXIS', 'YAXIS', 'ZAXIS'], (optional)*) – Axis, Axis tag names with.

```
bpy.ops.pose.bone_layers (layers=(False, False, False, False, False, False, False, False,  
                           False, False, False, False, False, False, False, False, False,  
                           False, False, False, False, False, False, False, False, False))  
    Change the layers that the selected bones belong to
```

Parameters **layers** (*boolean array of 32 items, (optional)*) – Layer, Armature layers that bone belongs to

```
bpy.ops.pose.breakdown (prev_frame=0, next_frame=0, percentage=0.5)  
    Create a suitable breakdown pose on the current frame
```

Parameters

- **prev_frame** (*int in [-300000, 300000], (optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000], (optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.

- **percentage** (*float in [0, 1], (optional)*) – Percentage, Weighting factor for the sliding operation

bpy.ops.pose.constraint_add(type='')

Add a constraint to the active bone

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

bpy.ops.pose.constraint_add_with_targets(type='')

Add a constraint to the active bone, with target (where applicable) set to the selected Objects/Bones

Parameters type (*enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], (optional)*) – Type

bpy.ops.pose.constraints_clear()

Clear all the constraints for the selected bones

bpy.ops.pose.constraints_copy()

Copy constraints to other selected bones.

bpy.ops.pose.copy()

Copies the current pose of the selected bones to copy/paste buffer

bpy.ops.pose.flip_names()

Flips (and corrects) the axis suffixes of the the names of selected bones

bpy.ops.pose.group_add()

Add a new bone group

bpy.ops.pose.group_assign(type=0)

Add selected bones to the chosen bone group

Parameters type (*int in [0, 10], (optional)*) – Bone Group Index

bpy.ops.pose.group_deselect()

Deselect bones of active Bone Group

bpy.ops.pose.group_remove()

Removes the active bone group

bpy.ops.pose.group_select()

Select bones in active Bone Group

bpy.ops.pose.group_unassign()

Remove selected bones from all bone groups

bpy.ops.pose.hide(unselected=False)

Tag selected bones to not be visible in Pose Mode

Parameters unselected (*boolean, (optional)*) – Unselected

bpy.ops.pose.ik_add(with_targets=True)

Add IK Constraint to the active Bone

Parameters with_targets (*boolean, (optional)*) – With Targets, Assign IK Constraint with targets derived from the select bones/objects

bpy.ops.pose.ik_clear()

Remove all IK Constraints from selected bones

bpy.ops.pose.loc_clear()

Reset locations of selected bones to their default values

bpy.ops.pose.paste (*flipped=False, selected_mask=False*)

Pastes the stored pose on to the current pose

Parameters

- **flipped** (*boolean, (optional)*) – Flipped on X-Axis, Paste the stored pose flipped on to current pose
- **selected_mask** (*boolean, (optional)*) – On Selected Only, Only paste the stored pose on to selected bones in the current pose

bpy.ops.pose.paths_calculate()

Calculate paths for the selected bones

bpy.ops.pose.paths_clear()

Clear path caches for selected bones

bpy.ops.pose.propagate (*mode='WHILE_HELD', end_frame=250.0*)

Copy selected aspects of the current pose to subsequent poses already keyframed

Parameters

- **mode** (*enum in ['WHILE_HELD', 'NEXT_KEY', 'LAST_KEY', 'BEFORE_FRAME', 'BEFORE_END', 'SELECTED_MARKERS']*, *(optional)*) – Terminate Mode, Method used to determine when to stop propagating pose to keyframes
- **end_frame** (*float in [1.17549e-38, inf]*, *(optional)*) – End Frame, Frame to stop propagating frames to (for ‘Before Frame’ mode)

bpy.ops.pose.push (*prev_frame=0, next_frame=0, percentage=0.5*)

Exaggerate the current pose

Parameters

- **prev_frame** (*int in [-300000, 300000]*, *(optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000]*, *(optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.
- **percentage** (*float in [0, 1]*, *(optional)*) – Percentage, Weighting factor for the sliding operation

bpy.ops.pose.quaternions_flip()

Flip quaternion values to achieve desired rotations, while maintaining the same orientations

bpy.ops.pose.relax (*prev_frame=0, next_frame=0, percentage=0.5*)

Make the current pose more similar to its surrounding ones

Parameters

- **prev_frame** (*int in [-300000, 300000]*, *(optional)*) – Previous Keyframe, Frame number of keyframe immediately before the current frame.
- **next_frame** (*int in [-300000, 300000]*, *(optional)*) – Next Keyframe, Frame number of keyframe immediately after the current frame.

- **percentage** (*float in [0, 1], (optional)*) – Percentage, Weighting factor for the sliding operation

bpy.ops.pose.**reveal**()

Unhide all bones that have been tagged to be hidden in Pose Mode

bpy.ops.pose.**rot_clear**()

Reset rotations of selected bones to their default values

bpy.ops.pose.**scale_clear**()

Reset scaling of selected bones to their default values

bpy.ops.pose.**select_all**(*action='TOGGLE'*)

Toggle selection status of all bones

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.pose.**select_constraint_target**()

Select bones used as targets for the currently selected bones

bpy.ops.pose.**select_flip_active**()

Activate the bone with a flipped name.

bpy.ops.pose.**select_grouped**(*extend=False, type='LAYER'*)

Select all visible bones grouped by similar properties

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.
- **type** (*enum in ['LAYER', 'GROUP'], (optional)*) – Type

bpy.ops.pose.**select_hierarchy**(*direction='PARENT', extend=False*)

Select immediate parent/children of selected bones

Parameters

- **direction** (*enum in ['PARENT', 'CHILD'], (optional)*) – Direction
- **extend** (*boolean, (optional)*) – Add to Selection

bpy.ops.pose.**select_inverse**()

Flip the selection status of bones (selected -> unselected, unselected -> selected)

bpy.ops.pose.**select_linked**(*extend=False*)

Select bones related to selected ones by parent/child relationships

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.pose.**select_parent**()

Select bones that are parents of the currently selected bones

bpy.ops.pose.**transforms_clear**()

Reset location, rotation, and scaling of selected bones to their default values

bpy.ops.pose.**visual_transform_apply**()

Apply final constrained position of pose bones to their transform.

Poselib Operators

bpy.ops.poselib.action_sanitize()

Make action suitable for use as a Pose Library

bpy.ops.poselib.apply_pose(pose_index=-1)

Apply specified Pose Library pose to the rig

Parameters **pose_index** (*int in [-2, inf], (optional)*) – Pose, Index of the pose to apply (-2 for no change to pose, -1 for poselib active pose)

bpy.ops.poselib.browse_interactive(pose_index=-1)

Interactively browse poses in 3D-View

Parameters **pose_index** (*int in [-2, inf], (optional)*) – Pose, Index of the pose to apply (-2 for no change to pose, -1 for poselib active pose)

bpy.ops.poselib.new()

Add New Pose Library to active Object

bpy.ops.poselib.pose_add(frame=1, name="Pose")

Add the current Pose to the active Pose Library

Parameters

- **frame** (*int in [0, inf], (optional)*) – Frame, Frame to store pose on
- **name** (*string, (optional)*) – Pose Name, Name of newly added Pose

bpy.ops.poselib.pose_remove(pose='DEFAULT')

Remove nth pose from the active Pose Library

Parameters **pose** (*enum in ['DEFAULT'], (optional)*) – Pose, The pose to remove

bpy.ops.poselib.pose_rename(name="RenamedPose", pose='')

Rename specified pose from the active Pose Library

Parameters

- **name** (*string, (optional)*) – New Pose Name, New name for pose
- **pose** (*enum in [], (optional)*) – Pose, The pose to rename

bpy.ops.poselib.unlink()

Remove Pose Library from active Object

Ptcache Operators

bpy.ops.ptcache.add()

Add new cache

bpy.ops.ptcache.bake(bake=False)

Bake physics

Parameters **bake** (*boolean, (optional)*) – Bake

bpy.ops.ptcache.bake_all(bake=True)

Bake all physics

Parameters **bake** (*boolean, (optional)*) – Bake

bpy.ops.ptcache.bake_from_cache()

Bake from cache

```
bpy.ops.ptcache.free_bake()  
    Free physics bake  
  
bpy.ops.ptcache.free_bake_all()  
    Undocumented (contribute)  
  
bpy.ops.ptcache.remove()  
    Delete current cache
```

Render Operators

```
bpy.ops.render.opengl (animation=False, write_still=False, view_context=True)  
    OpenGL render active viewport
```

Parameters

- **animation** (boolean, (optional)) – Animation, Render files from the animation range of this scene
- **write_still** (boolean, (optional)) – Write Image, Save rendered the image to the output path (used only when animation is disabled)
- **view_context** (boolean, (optional)) – View Context, Use the current 3D view for rendering, else use scene settings.

```
bpy.ops.render.play_rendered_anim()  
    Plays back rendered frames/movies using an external player.
```

File [startup/bl_operators/screen_play_rendered_anim.py:72](#)

```
bpy.ops.render.preset_add(name=""", remove_active=False)  
    Add a Render Preset
```

Parameters **name** (string, (optional)) – Name, Name of the preset, used to make the path name

File [startup/bl_operators/presets.py:42](#)

```
bpy.ops.render.render (animation=False, write_still=False, layer=""", scene="")  
    Render active scene
```

Parameters

- **animation** (boolean, (optional)) – Animation, Render files from the animation range of this scene
- **write_still** (boolean, (optional)) – Write Image, Save rendered the image to the output path (used only when animation is disabled)
- **layer** (string, (optional)) – Render Layer, Single render layer to re-render
- **scene** (string, (optional)) – Scene, Re-render single layer in this scene

```
bpy.ops.render.view_cancel()  
    Cancel show render view
```

```
bpy.ops.render.view_show()  
    Toggle show render view
```

Scene Operators

```
bpy.ops.scene.delete()  
    Delete active scene
```

```
bpy.ops.scene.new(type='NEW')
```

Add new scene by type

Parameters **type** (*enum in ['NEW', 'EMPTY', 'LINK_OBJECTS', 'LINK_OBJECT_DATA', 'FULL_COPY']*, *(optional)*) – Type

```
bpy.ops.scene.render_layer_add()
```

Add a render layer

```
bpy.ops.scene.render_layer_remove()
```

Remove the selected render layer

Screen Operators

```
bpy.ops.screen.actionzone(modifier=0)
```

Handle area action zones for mouse actions/gestures

Parameters **modifier** (*int in [0, 2]*, *(optional)*) – modifier, modifier state

```
bpy.ops.screen.animation_cancel(restore_frame=True)
```

Cancel animation, returning to the original frame

Parameters **restore_frame** (*boolean, (optional)*) – Restore Frame, Restore the frame when animation was initialized.

```
bpy.ops.screen.animation_play(reverse=False, sync=False)
```

Play animation

Parameters

- **reverse** (*boolean, (optional)*) – Play in Reverse, Animation is played backwards
- **sync** (*boolean, (optional)*) – Sync, Drop frames to maintain framerate

```
bpy.ops.screen.animation_step()
```

Step through animation by position

```
bpy.ops.screen.area_dupli()
```

Duplicate selected area into new window

```
bpy.ops.screen.area_join(min_x=-100, min_y=-100, max_x=-100, max_y=-100)
```

Join selected areas into new window

Parameters

- **min_x** (*int in [-inf, inf]*, *(optional)*) – X 1
- **min_y** (*int in [-inf, inf]*, *(optional)*) – Y 1
- **max_x** (*int in [-inf, inf]*, *(optional)*) – X 2
- **max_y** (*int in [-inf, inf]*, *(optional)*) – Y 2

```
bpy.ops.screen.area_move(x=0, y=0, delta=0)
```

Move selected area edges

Parameters

- **x** (*int in [-inf, inf]*, *(optional)*) – X
- **y** (*int in [-inf, inf]*, *(optional)*) – Y
- **delta** (*int in [-inf, inf]*, *(optional)*) – Delta

```
bpy.ops.screen.area_options()  
    Operations for splitting and merging  
  
bpy.ops.screen.area_split(direction='HORIZONTAL', factor=0.5, mouse_x=-100, mouse_y=-  
    100)  
    Split selected area into new windows
```

Parameters

- **direction** (*enum in ['HORIZONTAL', 'VERTICAL']*, *(optional)*) – Direction
- **factor** (*float in [0, 1]*, *(optional)*) – Factor
- **mouse_x** (*int in [-inf, inf]*, *(optional)*) – Mouse X
- **mouse_y** (*int in [-inf, inf]*, *(optional)*) – Mouse Y

```
bpy.ops.screen.area_swap()  
    Swap selected areas screen positions  
  
bpy.ops.screen.back_to_previous()  
    Revert back to the original screen layout, before fullscreen area overlay
```

```
bpy.ops.screen.delete()  
    Delete active screen
```

```
bpy.ops.screen.frame_jump(end=False)  
    Jump to first/last frame in frame range
```

Parameters **end** (*boolean, (optional)*) – Last Frame, Jump to the last frame of the frame range.

```
bpy.ops.screen.frame_offset(delta=0)  
    Undocumented (contribute)
```

Parameters **delta** (*int in [-inf, inf]*, *(optional)*) – Delta

```
bpy.ops.screen.header_flip()  
    Undocumented (contribute)
```

```
bpy.ops.screen.header_toolbox()  
    Display header region toolbox
```

```
bpy.ops.screen.keyframe_jump(next=True)  
    Jump to previous/next keyframe
```

Parameters **next** (*boolean, (optional)*) – Next Keyframe

```
bpy.ops.screen.new()  
    Add a new screen
```

```
bpy.ops.screen.redo_last()  
    Display menu for last action performed
```

```
bpy.ops.screen.region_flip()  
    Undocumented (contribute)
```

```
bpy.ops.screen.region_quadview()  
    Split selected area into camera, front, right & top views
```

```
bpy.ops.screen.region_scale()  
    Scale selected area
```

```
bpy.ops.screen.repeat_history(index=0)  
    Display menu for previous actions performed
```

Parameters **index** (*int in [0, inf]*, *(optional)*) – Index

bpy.ops.screen.**repeat_last**()

Repeat last action

bpy.ops.screen.**screen_full_area**()

Toggle display selected area as fullscreen

bpy.ops.screen.**screen_set**(*delta*=0)

Cycle through available screens

Parameters **delta** (*int in [-inf, inf], (optional)*) – Delta

bpy.ops.screen.**screencast**(*filepath=""*, *full=True*)

Undocumented ([contribute](#))

Parameters

- **filepath** (*string, (optional)*) – filepath
- **full** (*boolean, (optional)*) – Full Screen

bpy.ops.screen.**screenshot**(*filepath=""*, *check_existing=True*, *filter_blender=False*, *fil-*

ter_image=True, *filter_movie=False*, *filter_python=False*, *fil-*
ter_font=False, *filter_sound=False*, *filter_text=False*, *filter_btx=False*,
filter_collada=False, *filter_folder=True*, *filemode=9*, *full=True*)

Undocumented ([contribute](#))

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **full** (*boolean, (optional)*) – Full Screen

bpy.ops.screen.**spacedata_cleanup**()

Remove unused settings for invisible editors

bpy.ops.screen.**userpref_show**()

Show/hide user preferences

Script Operators

bpy.ops.script.execute_preset (filepath="", menu_idname="")
Executes a preset

Parameters

- **filepath** (*string, (optional)*) – Path, Path of the Python file to execute
- **menu_idname** (*string, (optional)*) – Menu ID Name, ID name of the menu this was called from

File startup/bl_operators/presets.py:139

bpy.ops.script.python_file_run (filepath="")
Run Python file

Parameters **filepath** (*string, (optional)*) – Path

bpy.ops.script.reload()
Reload Scripts

Sculpt Operators

bpy.ops.sculpt.brush_stroke (stroke=None, mode='NORMAL', ignore_background_click=False)
Undocumented (contribute)

Parameters

- **stroke** (bpy_prop_collection of OperatorStrokeElement, (optional)) – Stroke
- **mode** (*enum in ['NORMAL', 'INVERT', 'SMOOTH'], (optional)*) – Sculpt Stroke Mode, Action taken when a sculpt stroke is made
- **ignore_background_click** (*boolean, (optional)*) – Ignore Background Click, Clicks on the background do not start the stroke

bpy.ops.sculpt.sculptmode_toggle()
Undocumented (contribute)

bpy.ops.sculpt.set_persistent_base()
Undocumented (contribute)

Sequencer Operators

bpy.ops.sequencer.copy()
Undocumented (contribute)

bpy.ops.sequencer.crossfade_sounds()
Do crossfading volume animation of two selected sound strips.

File startup/bl_operators/sequencer.py:40

bpy.ops.sequencer.cut (frame=0, type='SOFT', side='BOTH')
Cut the selected strips

Parameters

- **frame** (*int in [-inf, inf], (optional)*) – Frame, Frame where selected strips will be cut

- **type** (*enum in ['SOFT', 'HARD']*, *(optional)*) – Type, The type of cut operation to perform on strips
- **side** (*enum in ['LEFT', 'RIGHT', 'BOTH']*, *(optional)*) – Side, The side that remains selected after cutting

bpy.ops.sequencer.cut_multicam(*camera=1*)

Cut multicam strip and select camera.

Parameters **camera** (*int in [1, 32]*, *(optional)*) – Camera

File [startup/bl_operators/sequencer.py:94](#)

bpy.ops.sequencer.deinterlace_selected_movies()

Deinterlace all selected movie sources.

File [startup/bl_operators/sequencer.py:129](#)

bpy.ops.sequencer.delete()

Erase selected strips from the sequencer

bpy.ops.sequencer.duplicate(*mode='TRANSLATION'*)

Duplicate the selected strips

Parameters **mode** (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TO_SPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE']*, *(optional)*) – Mode

bpy.ops.sequencer.effect_strip_add(*filepath=""*, *filter_blender=False*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=False*, *filemode=9*, *relative_path=False*, *frame_start=0*, *frame_end=0*, *channel=1*, *replace_sel=True*, *type='CROSS'*, *color=(0.0, 0.0, 0.0)*)

Add an effect to the sequencer, most are applied on top of existing strips

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **frame_end** (*int in [-inf, inf], (optional)*) – End Frame, End frame for the color strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **type** (*enum in ['CROSS', 'ADD', 'SUBTRACT', 'ALPHA_OVER', 'ALPHA_UNDER', 'GAMMA_CROSS', 'MULTIPLY', 'OVER_DROP', 'PLUGIN', 'WIPE', 'GLOW', 'TRANSFORM', 'COLOR', 'SPEED', 'MULTICAM', 'ADJUSTMENT'], (optional)*) – Type, Sequencer effect type
- **color** (*float array of 3 items in [0, 1], (optional)*) – Color, Initialize the strip with this color (only used when type='COLOR')

```
bpy.ops.sequencer.image_strip_add(directory="", filter_blender=False, filter_image=True, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, frame_start=0, frame_end=0, channel=1, replace_sel=True, files=None)
```

Add an image or image sequence to the sequencer

Parameters

- **directory** (*string, (optional)*) – Directory, Directory of the file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **frame_end** (*int in [-inf, inf], (optional)*) – End Frame, End frame for the color strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (*bpy_prop_collection of OperatorFileListElement, (optional)*) – Files

```
bpy.ops.sequencer.images_separate(length=1)
```

On image sequences strips, it return a strip for each image

Parameters **length** (*int in [1, 1000], (optional)*) – Length, Length of each frame

bpy.ops.sequencer.**lock**()
Lock the active strip so that it can't be transformed

bpy.ops.sequencer.**meta_make**()
Group selected strips into a metastrip

bpy.ops.sequencer.**meta_separate**()
Put the contents of a metastrip back in the sequencer

bpy.ops.sequencer.**meta_toggle**()
Toggle a metastrip (to edit enclosed strips)

bpy.ops.sequencer.**movie_strip_add**(filepath=""“, filter_blender=False, filter_image=False, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False, frame_start=0, channel=1, replace_sel=True, files=None, sound=True)

Add a movie strip to the sequencer

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (*bpy_prop_collection of OperatorFileListElement, (optional)*) – Files
- **sound** (*boolean, (optional)*) – Sound, Load sound with the movie

bpy.ops.sequencer.**mute**(unselected=False)
Mute selected strips

Parameters **unselected** (*boolean, (optional)*) – Unselected, Mute unselected rather than selected strips.

```
bpy.ops.sequencer.next_edit()  
    Move frame to next edit point  
  
bpy.ops.sequencer.paste()  
    Undocumented (contribute)  
  
bpy.ops.sequencer.previous_edit()  
    Move frame to previous edit point  
  
bpy.ops.sequencer.properties()  
    Open sequencer properties panel  
  
bpy.ops.sequencer.reassign_inputs()  
    Reassign the inputs for the effects strip  
  
bpy.ops.sequencer.refresh_all()  
    Refresh the sequencer editor  
  
bpy.ops.sequencer.reload()  
    Reload strips in the sequencer  
  
bpy.ops.sequencer.render_size()  
    Set render size and aspect from active sequence  
  
bpy.ops.sequencer.scene_strip_add(frame_start=0, channel=1, replace_sel=True, scene='')  
    Add a strip to the sequencer using a blender scene as a source
```

Parameters

- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **scene** (*enum in [], (optional)*) – Scene

```
bpy.ops.sequencer.select(extend=False, linked_handle=False, left_right=False,  
                        linked_time=False)  
Select a strip (last selected becomes the “active strip”)
```

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend the selection.
- **linked_handle** (*boolean, (optional)*) – Linked Handle, Select handles next to the active strip.
- **left_right** (*boolean, (optional)*) – Left/Right, select based on the frame side the cursor is on.
- **linked_time** (*boolean, (optional)*) – Linked Time, Select other strips at the same time.

```
bpy.ops.sequencer.select_active_side(side='BOTH')  
Select strips on the nominated side of the active strip
```

Parameters **side** (*enum in ['LEFT', 'RIGHT', 'BOTH'], (optional)*) – Side, The side of the handle that is selected

```
bpy.ops.sequencer.select_all_toggle()  
Select or deselect all strips
```

```
bpy.ops.sequencer.select_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)  
Enable border select mode
```

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.sequencer.**select_handles** (*side='BOTH'*)
Select manipulator handles on the sides of the selected strip

Parameters side (*enum in ['LEFT', 'RIGHT', 'BOTH'], (optional)*) – Side, The side of the handle that is selected

bpy.ops.sequencer.**select_inverse**()
Select unselected strips

bpy.ops.sequencer.**select_less**()
Shrink the current selection of adjacent selected strips

bpy.ops.sequencer.**select_linked**()
Select all strips adjacent to the current selection

bpy.ops.sequencer.**select_linked_pick** (*extend=False*)
Select a chain of linked strips nearest to the mouse pointer

Parameters extend (*boolean, (optional)*) – Extend, extend the selection

bpy.ops.sequencer.**select_more**()
Select more strips adjacent to the current selection

bpy.ops.sequencer.**snap** (*frame=0*)
Frame where selected strips will be snapped

Parameters frame (*int in [-inf, inf], (optional)*) – Frame, Frame where selected strips will be snapped

bpy.ops.sequencer.**sound_strip_add** (*filepath=""*, *filter_blender=False*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=True*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=9*, *relative_path=False*, *frame_start=0*, *channel=1*, *replace_sel=True*, *files=None*, *cache=False*)
Add a sound strip to the sequencer

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files

- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **frame_start** (*int in [-inf, inf], (optional)*) – Start Frame, Start frame of the sequence strip
- **channel** (*int in [1, 32], (optional)*) – Channel, Channel to place this strip into
- **replace_sel** (*boolean, (optional)*) – Replace Selection, replace the current selection
- **files** (*bpy_prop_collection of OperatorFileListElement, (optional)*) – Files
- **cache** (*boolean, (optional)*) – Cache, Cache the sound in memory.

`bpy.ops.sequencer.swap(side='RIGHT')`

Swap active strip with strip to the left

Parameters **side** (*enum in ['LEFT', 'RIGHT'], (optional)*) – Side, Side of the strip to swap

`bpy.ops.sequencer.swap_data()`

Swap 2 sequencer strips

`bpy.ops.sequencer.swap_inputs()`

Swap the first two inputs for the effects strip

`bpy.ops.sequencer.unlock()`

Unlock the active strip so that it can't be transformed

`bpy.ops.sequencer.unmute(unselected=False)`

Un-Mute unselected rather than selected strips

Parameters **unselected** (*boolean, (optional)*) – Unselected, UnMute unselected rather than selected strips.

`bpy.ops.sequencer.view_all()`

View all the strips in the sequencer

`bpy.ops.sequencer.view_all_preview()`

Zoom preview to fit in the area

`bpy.ops.sequencer.view_ghost_border(gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0)`

Enable border select mode

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

`bpy.ops.sequencer.view_selected()`

Zoom the sequencer on the selected strips

`bpy.ops.sequencer.view_toggle()`

Toggle between sequencer views (sequence, preview, both)

`bpy.ops.sequencer.view_zoom_ratio(ratio=1.0)`

Change zoom ratio of sequencer preview

Parameters **ratio** (*float in [0, inf], (optional)*) – Ratio, Zoom ratio, 1.0 is 1:1, higher is zoomed in, lower is zoomed out.

Sketch Operators

bpy.ops.sketch.**cancel_stroke**()
Undocumented ([contribute](#))

bpy.ops.sketch.**convert**()
Undocumented ([contribute](#))

bpy.ops.sketch.**delete**()
Undocumented ([contribute](#))

bpy.ops.sketch.**draw_preview**(*snap=False*)
Undocumented ([contribute](#))

Parameters **snap** (*boolean, (optional)*) – Snap

bpy.ops.sketch.**draw_stroke**(*snap=False*)
Undocumented ([contribute](#))

Parameters **snap** (*boolean, (optional)*) – Snap

bpy.ops.sketch.**finish_stroke**()
Undocumented ([contribute](#))

bpy.ops.sketch.**gesture**(*snap=False*)
Undocumented ([contribute](#))

Parameters **snap** (*boolean, (optional)*) – Snap

bpy.ops.sketch.**select**()
Undocumented ([contribute](#))

Sound Operators

bpy.ops.sound.**open**(*filepath=""*, *filter_blender=False*, *filter_image=False*, *filter_movie=True*, *filter_python=False*, *filter_font=False*, *filter_sound=True*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=9*, *relative_path=False*, *cache=False*)

Load a sound file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files

- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **cache** (*boolean, (optional)*) – Cache, Cache the sound in memory.

```
bpy.ops.sound.pack()  
    Pack the sound into the current blend file
```

```
bpy.ops.sound.unpack(method='USE_LOCAL', id="")  
    Unpack the sound to the samples filename
```

Parameters

- **method** (*enum in ['USE_LOCAL', 'WRITE_LOCAL', 'USE_ORIGINAL', 'WRITE_ORIGINAL'], (optional)*) – Method, How to unpack.
- **id** (*string, (optional)*) – Sound Name, Sound datablock name to unpack.

Surface Operators

```
bpy.ops.surface.primitive_nurbs_surface_circle_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurbs surface Circle

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.surface.primitive_nurbs_surface_curve_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurbs surface Curve

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enterEditMode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.surface.primitive_nurbs_surface_cylinder_add(view_align=False,           en-  
                                                    terEditMode=False,           loca-  
                                                    tion=(0.0, 0.0, 0.0),       ration=(0.0, 0.0, 0.0),       lay-  
                                                    layers=(False, False, False, False,  
                                                    False, False, False, False,  
                                                    False, False, False, False,  
                                                    False, False, False, False,  
                                                    False, False, False))
```

Construct a Nurbs surface Cylinder

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enterEditMode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.surface.primitive_nurbs_surface_sphere_add(view_align=False,           en-  
                                                    terEditMode=False,           loca-  
                                                    tion=(0.0, 0.0, 0.0),       rotation=(0.0,  
                                                    0.0, 0.0),       layers=(False, False,  
                                                    False, False, False, False,  
                                                    False, False, False, False,  
                                                    False, False, False, False,  
                                                    False, False, False))
```

Construct a Nurbs surface Sphere

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enterEditMode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.surface.primitive_nurbs_surface_surface_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurbs surface Patch

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

```
bpy.ops.surface.primitive_nurbs_surface_torus_add(view_align=False, enter_editmode=False, location=(0.0, 0.0, 0.0), rotation=(0.0, 0.0, 0.0), layers=(False, False, False))
```

Construct a Nurbs surface Torus

Parameters

- **view_align** (*boolean, (optional)*) – Align to View, Align the new object to the view
- **enter_editmode** (*boolean, (optional)*) – Enter Editmode, Enter editmode when adding this object
- **location** (*float array of 3 items in [-inf, inf], (optional)*) – Location, Location for the newly added object
- **rotation** (*float array of 3 items in [-inf, inf], (optional)*) – Rotation, Rotation for the newly added object
- **layers** (*boolean array of 20 items, (optional)*) – Layer

Text Operators

```
bpy.ops.text.comment()
```

Convert selected text to comment

```
bpy.ops.text.convert_whitespace(type='SPACES')
```

Convert whitespaces by type

Parameters **type** (*enum in ['SPACES', 'TABS'], (optional)*) – type, Type of whitespace to convert to.

bpy.ops.text.**copy**()
Copy selected text to clipboard

bpy.ops.text.**cursor_set**(x=0, y=0)
Set cursor position

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y

bpy.ops.text.**cut**()
Cut selected text to clipboard

bpy.ops.text.**delete**(type='NEXT_CHARACTER')
Delete text by cursor position

Parameters **type** (*enum in ['NEXT_CHARACTER', 'PREVIOUS_CHARACTER', 'NEXT_WORD', 'PREVIOUS_WORD'], (optional)*) – Type, Which part of the text to delete.

bpy.ops.text.**find**()
Find specified text

bpy.ops.text.**find_set_selected**()
Find specified text and set as selected

bpy.ops.text.**indent**()
Indent selected text

bpy.ops.text.**insert**(text="")
Insert text at cursor position

Parameters **text** (*string, (optional)*) – Text, Text to insert at the cursor position.

bpy.ops.text.**jump**(line=1)
Jump cursor to line

Parameters **line** (*int in [1, inf], (optional)*) – Line, Line number to jump to.

bpy.ops.text.**line_break**()
Insert line break at cursor position

bpy.ops.text.**line_number**()
The current line number

bpy.ops.text.**make_internal**()
Make active text file internal

bpy.ops.text.**mark_all**()
Mark all specified text

bpy.ops.text.**markers_clear**()
Clear all markers

bpy.ops.text.**move**(type='LINE_BEGIN')
Move cursor to position type

Parameters **type** (*enum in ['LINE_BEGIN', 'LINE_END', 'FILE_TOP', 'FILE_BOTTOM', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], (optional)*) – Type, Where to move cursor to.

bpy.ops.text.**move_select**(type='LINE_BEGIN')
Make selection from current cursor position to new cursor position type

Parameters **type** (*enum in* ['LINE_BEGIN', 'LINE_END', 'FILE_TOP', 'FILE_BOTTOM', 'PREVIOUS_CHARACTER', 'NEXT_CHARACTER', 'PREVIOUS_WORD', 'NEXT_WORD', 'PREVIOUS_LINE', 'NEXT_LINE', 'PREVIOUS_PAGE', 'NEXT_PAGE'], *(optional)*) – Type, Where to move cursor to, to make a selection.

bpy.ops.text.**new()**

Create a new text data block

bpy.ops.text.**next_marker()**

Move to next marker

bpy.ops.text.**open(filepath="“, filter_blender=False, filter_image=False, filter_movie=False, filter_python=True, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, internal=False)**

Open a new text data block

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **internal** (*boolean, (optional)*) – Make internal, Make text file internal after loading

bpy.ops.text.**overwrite_toggle()**

Toggle overwrite while typing

bpy.ops.text.**paste(selection=False)**

Paste text from clipboard

Parameters **selection** (*boolean, (optional)*) – Selection, Paste text selected elsewhere rather than copied, X11 only.

bpy.ops.text.**previous_marker()**

Move to previous marker

bpy.ops.text.**properties()**

Toggle text properties panel

bpy.ops.text.**refresh_pyconstraints()**

Refresh all pyconstraints

bpy.ops.text.**reload()**

Reload active text data block from its file

bpy.ops.text.replace()

Replace text with the specified text

bpy.ops.text.replace_set_selected()

Replace text with specified text and set as selected

bpy.ops.text.resolve_conflict(resolution='IGNORE')

When external text is out of sync, resolve the conflict

Parameters **resolution** (enum in ['IGNORE', 'RELOAD', 'SAVE', 'MAKE_INTERNAL'], (optional)) – Resolution, How to solve conflict due to different in internal and external text.

bpy.ops.text.run_script()

Run active script

bpy.ops.text.save()

Save active text data block

bpy.ops.text.save_as(filepath="", check_existing=True, filter_blender=False, filter_image=False, filter_movie=False, filter_python=True, filter_font=False, filter_sound=False, filter_text=True, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9)

Save active text file with options

Parameters

- **filepath** (string, (optional)) – File Path, Path to file
- **check_existing** (boolean, (optional)) – Check Existing, Check and warn on overwriting existing files
- **filter_blender** (boolean, (optional)) – Filter .blend files
- **filter_image** (boolean, (optional)) – Filter image files
- **filter_movie** (boolean, (optional)) – Filter movie files
- **filter_python** (boolean, (optional)) – Filter python files
- **filter_font** (boolean, (optional)) – Filter font files
- **filter_sound** (boolean, (optional)) – Filter sound files
- **filter_text** (boolean, (optional)) – Filter text files
- **filter_btx** (boolean, (optional)) – Filter btx files
- **filter_collada** (boolean, (optional)) – Filter COLLADA files
- **filter_folder** (boolean, (optional)) – Filter folders
- **filemode** (int in [1, 9], (optional)) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

bpy.ops.text.scroll(lines=1)

Scroll text screen

Parameters **lines** (int in [-inf, inf], (optional)) – Lines, Number of lines to scroll.

bpy.ops.text.scroll_bar(lines=1)

Scroll text screen

Parameters **lines** (int in [-inf, inf], (optional)) – Lines, Number of lines to scroll.

bpy.ops.text.select_all()

Select all text

```
bpy.ops.text.select_line()
```

Select text by line

```
bpy.ops.text.select_word()
```

Select word under cursor

```
bpy.ops.text.selection_set(select=False)
```

Set cursor selection

Parameters `select (boolean, (optional))` – Select, Set selection end rather than cursor.

```
bpy.ops.text.to_3d_object(split_lines=False)
```

Create 3d text object from active text data block

Parameters `split_lines (boolean, (optional))` – Split Lines, Create one object per line in the text.

```
bpy.ops.text.uncomment()
```

Convert selected comment to text

```
bpy.ops.text.unindent()
```

Unindent selected text

```
bpy.ops.text.unlink()
```

Unlink active text data block

Texture Operators

```
bpy.ops.texture.envmap_clear()
```

Discard the environment map and free it from memory

```
bpy.ops.texture.envmap_clear_all()
```

Discard all environment maps in the .blend file and free them from memory

```
bpy.ops.texture.envmap_save(filepath="", check_existing=True, filter_blender=False, filter_image=True, filter_movie=True, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=9, relative_path=False)
```

Save the current generated Environment map to an image file

Parameters

- `filepath (string, (optional))` – File Path, Path to file
- `check_existing (boolean, (optional))` – Check Existing, Check and warn on overwriting existing files
- `filter_blender (boolean, (optional))` – Filter .blend files
- `filter_image (boolean, (optional))` – Filter image files
- `filter_movie (boolean, (optional))` – Filter movie files
- `filter_python (boolean, (optional))` – Filter python files
- `filter_font (boolean, (optional))` – Filter font files
- `filter_sound (boolean, (optional))` – Filter sound files
- `filter_text (boolean, (optional))` – Filter text files
- `filter_btx (boolean, (optional))` – Filter btx files
- `filter_collada (boolean, (optional))` – Filter COLLADA files

- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file

bpy.ops.texture.new()

Add a new texture

bpy.ops.texture.slot_copy()

Copy the material texture settings and nodes

bpy.ops.texture.slot_move(*type='UP'*)

Move texture slots up and down

Parameters **type** (*enum in ['UP', 'DOWN'], (optional)*) – Type

bpy.ops.texture.slot_paste()

Copy the texture settings and nodes

Time Operators

bpy.ops.time.end_frame_set()

Set the end frame

bpy.ops.time.start_frame_set()

Set the start frame

bpy.ops.time.view_all()

Show the entire playable frame range

Transform Operators

bpy.ops.transform.create_orientation(*name=""*, *use=False*, *overwrite=False*)

Create transformation orientation from selection

Parameters

- **name** (*string, (optional)*) – Name, Text to insert at the cursor position.
- **use** (*boolean, (optional)*) – Use after creation, Select orientation after its creation
- **overwrite** (*boolean, (optional)*) – Overwrite previous, Overwrite previously created orientation with same name

bpy.ops.transform.delete_orientation()

Delete transformation orientation

bpy.ops.transform.edge_collapse(*value=0.0*, *snap=False*, *snap_target='CLOSEST'*,
snap_point=(0.0, 0.0, 0.0), *snap_align=False*, *snap_normal=(0.0, 0.0, 0.0)*, *release_confirm=False*)

Change the crease of edges

Parameters

- **value** (*float in [-1, 1], (optional)*) – Factor
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target

- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.edge_slide(value=0.0, mirror=False, snap=False, snap_target='CLOSEST',
                             snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0,
                             0.0, 0.0), release_confirm=False)
```

Slide an edge loop along a mesh

Parameters

- **value** (*float in [-1, 1], (optional)*) – Factor
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.mirror(constraint_axis=(False, False, False), constraint_orientation='',
                        proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, release_confirm=False)
```

Mirror selected vertices around one or more axes

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.push_pull(value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0,
                           snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)
```

Push/Pull selected items

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Distance
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.resize(value=(1.0, 1.0, 1.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), texture_space=False, release_confirm=False)
```

Resize selected items

Parameters

- **value** (*float array of 3 items in [-inf, inf], (optional)*) – Vector
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **texture_space** (*boolean, (optional)*) – Edit Object data texture space

- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.rotate(value=(0.0), axis=(0.0, 0.0, 0.0), constraint_axis=(False, False, False),  
constraint_orientation='', mirror=False, proportional='DISABLED',  
proportional_edit_falloff='SMOOTH', proportional_size=1.0,  
snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0),  
snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)
```

Rotate selected items

Parameters

- **value** (*float array of 1 items in [-inf, inf], (optional)*) – Angle
- **axis** (*float array of 3 items in [-inf, inf], (optional)*) – Axis, The axis around which the transformation occurs
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.select_orientation(orientation='')
```

Select transformation orientation

Parameters **orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation

```
bpy.ops.transform.seq_slide(value=(1.0, 1.0), snap=False, snap_target='CLOSEST',  
snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0,  
0.0, 0.0), release_confirm=False)
```

Slide a sequence strip in time

Parameters

- **value** (*float array of 2 items in [-inf, inf], (optional)*) – angle
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point

- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.shear(value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)
```

Shear selected items along the horizontal screen axis

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Offset
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.shrink_fatten(value=0.0, mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)
```

Shrink/fatten selected vertices along normals

Parameters

- **value** (*float in [-inf, inf], (optional)*) – Offset
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options

- **snap_target** (*enum in [‘CLOSEST’, ‘CENTER’, ‘MEDIAN’, ‘ACTIVE’]*, *(optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Point
- **snap_align** (*boolean*, *(optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Normal
- **release_confirm** (*boolean*, *(optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.snap_type (*type=‘INCREMENT’*)

Set the snap element type

Parameters **type** (*enum in [‘INCREMENT’, ‘VERTEX’, ‘EDGE’, ‘FACE’, ‘VOLUME’]*, *(optional)*)
– Type, Set the snap element type

bpy.ops.transform.tilt (*value=(0.0)*, *constraint_axis=(False, False, False)*, *constraint_orientation=‘‘*, *mirror=False*, *proportional=‘DISABLED’*, *proportional_edit_falloff=‘SMOOTH’*, *proportional_size=1.0*, *snap=False*, *snap_target=‘CLOSEST’*, *snap_point=(0.0, 0.0, 0.0)*, *snap_align=False*, *snap_normal=(0.0, 0.0, 0.0)*, *release_confirm=False*)

Tilt selected control vertices of 3d curve

Parameters

- **value** (*float array of 1 items in [-inf, inf]*, *(optional)*) – Angle
- **constraint_axis** (*boolean array of 3 items*, *(optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [‘‘’]*, *(optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean*, *(optional)*) – Mirror Editing
- **proportional** (*enum in [‘DISABLED’, ‘ENABLED’, ‘CONNECTED’]*, *(optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in [‘SMOOTH’, ‘SPHERE’, ‘ROOT’, ‘SHARP’, ‘LINEAR’, ‘CONSTANT’, ‘RANDOM’]*, *(optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf]*, *(optional)*) – Proportional Size
- **snap** (*boolean*, *(optional)*) – Use Snapping Options
- **snap_target** (*enum in [‘CLOSEST’, ‘CENTER’, ‘MEDIAN’, ‘ACTIVE’]*, *(optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Point
- **snap_align** (*boolean*, *(optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf]*, *(optional)*) – Normal
- **release_confirm** (*boolean*, *(optional)*) – Confirm on Release, Always confirm operation when releasing button

bpy.ops.transform.tosphere (*value=0.0*, *mirror=False*, *proportional=‘DISABLED’*, *proportional_edit_falloff=‘SMOOTH’*, *proportional_size=1.0*, *snap=False*, *snap_target=‘CLOSEST’*, *snap_point=(0.0, 0.0, 0.0)*, *snap_align=False*, *snap_normal=(0.0, 0.0, 0.0)*, *release_confirm=False*)

Move selected vertices outward in a spherical shape around mesh center

Parameters

- **value** (*float in [0, 1], (optional)*) – Factor
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.trackball(value=(1.0, 1.0), mirror=False, proportional='DISABLED',
                             proportional_edit_falloff='SMOOTH', proportional_size=1.0,
                             snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0,
                             0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0),
                             release_confirm=False)
```

Trackball style rotation of selected items

Parameters

- **value** (*float array of 2 items in [-inf, inf], (optional)*) – angle
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.transform(mode='TRANSLATION', value=(0.0, 0.0, 0.0, 0.0), axis=(0.0, 0.0, 0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), release_confirm=False)
```

Transform selected items by mode type

Parameters

- **mode** (*enum in ['INIT', 'DUMMY', 'TRANSLATION', 'ROTATION', 'RESIZE', 'TOSPHERE', 'SHEAR', 'WARP', 'SHRINKFATTEN', 'TILT', 'TRACKBALL', 'PUSHPULL', 'CREASE', 'MIRROR', 'BONE_SIZE', 'BONE_ENVELOPE', 'CURVE_SHRINKFATTEN', 'BONE_ROLL', 'TIME_TRANSLATE', 'TIME_SLIDE', 'TIME_SCALE', 'TIME_EXTEND', 'BAKE_TIME', 'BEVEL', 'BWEIGHT', 'ALIGN', 'EDGESLIDE', 'SEQSLIDE'], (optional)*) – Mode
- **value** (*float array of 4 items in [-inf, inf], (optional)*) – Values
- **axis** (*float array of 3 items in [-inf, inf], (optional)*) – Axis, The axis around which the transformation occurs
- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.translate(value=(0.0, 0.0, 0.0), constraint_axis=(False, False, False), constraint_orientation='', mirror=False, proportional='DISABLED', proportional_edit_falloff='SMOOTH', proportional_size=1.0, snap=False, snap_target='CLOSEST', snap_point=(0.0, 0.0, 0.0), snap_align=False, snap_normal=(0.0, 0.0, 0.0), texture_space=False, release_confirm=False)
```

Translate selected items

Parameters

- **value** (*float array of 3 items in [-inf, inf], (optional)*) – Vector

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **texture_space** (*boolean, (optional)*) – Edit Object data texture space
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.transform.warp(value=(0.0),      mirror=False,      proportional='DISABLED',      proportional_edit_falloff='SMOOTH',      proportional_size=1.0,      snap=False,      snap_target='CLOSEST',      snap_point=(0.0, 0.0, 0.0),      snap_align=False,      snap_normal=(0.0, 0.0, 0.0),      release_confirm=False)
```

Warp selected items around the cursor

Parameters

- **value** (*float array of 1 items in [-inf, inf], (optional)*) – Angle
- **mirror** (*boolean, (optional)*) – Mirror Editing
- **proportional** (*enum in ['DISABLED', 'ENABLED', 'CONNECTED'], (optional)*) – Proportional Editing
- **proportional_edit_falloff** (*enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], (optional)*) – Proportional Editing Falloff, Falloff type for proportional editing mode.
- **proportional_size** (*float in [1e-05, inf], (optional)*) – Proportional Size
- **snap** (*boolean, (optional)*) – Use Snapping Options
- **snap_target** (*enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], (optional)*) – Target
- **snap_point** (*float array of 3 items in [-inf, inf], (optional)*) – Point
- **snap_align** (*boolean, (optional)*) – Align with Point Normal
- **snap_normal** (*float array of 3 items in [-inf, inf], (optional)*) – Normal
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

Ui Operators

bpy.ops.ui.copy_data_path_button()

Copy the RNA data path for this property to the clipboard

bpy.ops.ui.copy_to_selected_button(*all=True*)

Copy property from this object to selected objects or bones

Parameters **all** (*boolean, (optional)*) – All, Reset to default values all elements of the array.

bpy.ops.ui.eyedropper()

Sample a color from the Blender Window to store in a property

bpy.ops.ui.reports_to_textblock()

Write the reports

bpy.ops.ui.reset_default_button(*all=True*)

Reset this property's value to its default value

Parameters **all** (*boolean, (optional)*) – All, Reset to default values all elements of the array.

bpy.ops.ui.reset_default_theme()

Reset to the default theme colors

Uv Operators

bpy.ops.uv.align(*axis='ALIGN_AUTO'*)

Align selected UV vertices to an axis

Parameters **axis** (*enum in ['ALIGN_AUTO', 'ALIGN_X', 'ALIGN_Y'], (optional)*) – Axis, Axis to align UV locations on.

bpy.ops.uv.average_islands_scale()

Undocumented (contribute)

bpy.ops.uv.circle_select(*x=0, y=0, radius=0, gesture_mode=0*)

Select UV vertices using circle selection

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y
- **radius** (*int in [-inf, inf], (optional)*) – Radius
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode

bpy.ops.uv(cube_size=*1.0*, correct_aspect=*True*, clip_to_bounds=*False*, scale_to_bounds=*False*)

Undocumented (contribute)

Parameters

- **cube_size** (*float in [0, inf], (optional)*) – Cube Size, Size of the cube to project on.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

bpy.ops.uv.cursor_set(*location*=(0.0, 0.0))

Set 2D cursor location

Parameters **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Cursor location in 0.0-1.0 coordinates.

bpy.ops.uv.cylinder_project(*direction*='VIEW_ON_EQUATOR', *align*='POLAR_ZX',
radius=1.0, *correct_aspect*=True, *clip_to_bounds*=False,
scale_to_bounds=False)

Undocumented ([contribute](#))

Parameters

- **direction** (*enum in ['VIEW_ON_EQUATOR', 'VIEW_ON_POLES', 'ALIGN_TO_OBJECT']*, *(optional)*) – Direction, Direction of the sphere or cylinder.
- **align** (*enum in ['POLAR_ZX', 'POLAR_ZY']*, *(optional)*) – Align, How to determine rotation around the pole.
- **radius** (*float in [0, inf]*, *(optional)*) – Radius, Radius of the sphere or cylinder.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

bpy.ops.uv.export_layout(*filepath*=“”, *check_existing*=True, *export_all*=False, *mode*='PNG',
size=(1024, 1024), *opacity*=0.25)

Export UV layout to file

Parameters

- **filepath** (*string, (optional)*) – File Path, File path used for exporting the SVG file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **export_all** (*boolean, (optional)*) – All UV's, Export all UVs in this mesh (not just the visible ones)
- **mode** (*enum in ['SVG', 'EPS', 'PNG']*, *(optional)*) – Format, File format to export the UV layout to
- **size** (*int array of 2 items in [8, 32768]*, *(optional)*) – Dimensions of the exported file
- **opacity** (*float in [0, 1]*, *(optional)*) – Fill Opacity

File [addons/io_mesh_uv_layout/_init__.py:132](#)

bpy.ops.uv.follow_active_quads(*mode*='LENGTH')

Follow UVs from active quads along continuous face loops

Parameters **mode** (*enum in ['EVEN', 'LENGTH']*, *(optional)*) – Edge Length Mode, Method to space UV edge loops

File [startup/bl_operators/uvcalc_follow_active.py:246](#)

bpy.ops.uv.hide(*unselected*=False)

Hide (un)selected UV vertices

Parameters **unselected** (*boolean, (optional)*) – Unselected, Hide unselected rather than selected.

```
bpy.ops.uv.lightmap_pack(PREF_CONTEXT='SEL_FACES',
                         PREF_NEW_UVLAYER=False,
                         PREF_IMG_PX_SIZE=512,
                         PREF_MARGIN_DIV=0.1)
                         PREF_PACK_IN_ONE=True,
                         PREF_APPLY_IMAGE=False,
                         PREF_BOX_DIV=12,
```

Follow UVs from active quads along continuous face loops

Parameters

- **PREF_CONTEXT** (*enum in ['SEL_FACES', 'ALL_FACES', 'ALL_OBJECTS']*, *(optional)*) – Selection
- **PREF_PACK_IN_ONE** (*boolean, (optional)*) – Share Tex Space, Objects Share texture space, map all objects into 1 uvmapping
- **PREF_NEW_UVLAYER** (*boolean, (optional)*) – New UV Layer, Create a new UV layer for every mesh packed
- **PREF_APPLY_IMAGE** (*boolean, (optional)*) – New Image, Assign new images for every mesh (only one if shared tex space enabled)
- **PREF_IMG_PX_SIZE** (*int in [64, 5000]*, *(optional)*) – Image Size, Width and Height for the new image
- **PREF_BOX_DIV** (*int in [1, 48]*, *(optional)*) – Pack Quality, Pre Packing before the complex boxpack
- **PREF_MARGIN_DIV** (*float in [0.001, 1]*, *(optional)*) – Margin, Size of the margin as a division of the UV

File `startup/bl_operators/uvcalc_lightmap.py:560`

```
bpy.ops.uv.minimize_stretch(fill_holes=True, blend=0.0, iterations=0)
Reduce UV stretching by relaxing angles
```

Parameters

- **fill_holes** (*boolean, (optional)*) – Fill Holes, Virtual fill holes in mesh before unwrapping, to better avoid overlaps and preserve symmetry.
- **blend** (*float in [0, 1]*, *(optional)*) – Blend, Blend factor between stretch minimized and original.
- **iterations** (*int in [0, inf]*, *(optional)*) – Iterations, Number of iterations to run, 0 is unlimited when run interactively.

```
bpy.ops.uv.pack_islands(margin=0.0)
```

Undocumented ([contribute](#))

Parameters **margin** (*float in [0, 1]*, *(optional)*) – Margin, Space between islands

```
bpy.ops.uv.pin(clear=False)
```

Set/clear selected UV vertices as anchored between multiple unwrap operations

Parameters **clear** (*boolean, (optional)*) – Clear, Clear pinning for the selection instead of setting it.

```
bpy.ops.uv.project_from_view(orthographic=False, correct_aspect=True, clip_to_bounds=False,
                             scale_to_bounds=False)
```

Undocumented ([contribute](#))

Parameters

- **orthographic** (*boolean, (optional)*) – Orthographic, Use orthographic projection.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.

- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

bpy.ops.uv.**reset**()

Undocumented ([contribute](#))

bpy.ops.uv.**reveal**()

Reveal all hidden UV vertices

bpy.ops.uv.**select** (*extend=False, location=(0.0, 0.0)*)

Select UV vertices

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

bpy.ops.uv.**select_all** (*action='TOGGLE'*)

Change selection of all UV vertices

Parameters **action** (*enum in ['TOGGLE', 'SELECT', 'DESELECT', 'INVERT'], (optional)*) – Action, Selection action to execute

bpy.ops.uv.**select_border** (*pinned=False, gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0*)

Select UV vertices using border selection

Parameters

- **pinned** (*boolean, (optional)*) – Pinned, Border select pinned UVs only.
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.uv.**select_linked** (*extend=False*)

Select all UV vertices linked to the active UV map

Parameters **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.

bpy.ops.uv.**select_linked_pick** (*extend=False, location=(0.0, 0.0)*)

Select all UV vertices linked under the mouse

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

bpy.ops.uv.**select_loop** (*extend=False, location=(0.0, 0.0)*)

Select a loop of connected UV vertices

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection rather than clearing the existing selection.
- **location** (*float array of 2 items in [-inf, inf], (optional)*) – Location, Mouse location in normalized coordinates, 0.0 to 1.0 is within the image bounds.

bpy.ops.uv.**select_pinned()**

Select all pinned UV vertices

bpy.ops.uv.**smart_project** (*angle_limit=66.0, island_margin=0.0, user_area_weight=0.0*)

This script projection unwraps the selected faces of a mesh. It operates on all selected mesh objects, and can be used unwrap selected faces, or all faces.

Parameters

- **angle_limit** (*float in [1, 89], (optional)*) – Angle Limit, lower for more projection groups, higher for less distortion
- **island_margin** (*float in [0, 1], (optional)*) – Island Margin, Margin to reduce bleed from adjacent islands
- **user_area_weight** (*float in [0, 1], (optional)*) – Area Weight, Weight projections vector by faces with larger areas

File startup/bl_operators/uvcalc_smart_project.py:1147

bpy.ops.uv.**snap_cursor** (*target='PIXELS'*)

Snap cursor to target type

Parameters **target** (*enum in ['PIXELS', 'SELECTED'], (optional)*) – Target, Target to snap the selected UV's to.

bpy.ops.uv.**snap_selected** (*target='PIXELS'*)

Snap selected UV vertices to target type

Parameters **target** (*enum in ['PIXELS', 'CURSOR', 'ADJACENT_UNSELECTED'], (optional)*) – Target, Target to snap the selected UV's to.

bpy.ops.uv.**sphere_project** (*direction='VIEW_ON_EQUATOR', align='POLAR_ZX', correct_aspect=True, clip_to_bounds=False, scale_to_bounds=False*)

Undocumented ([contribute](#))

Parameters

- **direction** (*enum in ['VIEW_ON_EQUATOR', 'VIEW_ON_POLES', 'ALIGN_TO_OBJECT'], (optional)*) – Direction, Direction of the sphere or cylinder.
- **align** (*enum in ['POLAR_ZX', 'POLAR_ZY'], (optional)*) – Align, How to determine rotation around the pole.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.
- **clip_to_bounds** (*boolean, (optional)*) – Clip to Bounds, Clip UV coordinates to bounds after unwrapping.
- **scale_to_bounds** (*boolean, (optional)*) – Scale to Bounds, Scale UV coordinates to bounds after unwrapping.

bpy.ops.uv.**stitch** (*use_limit=True, limit=0.01*)

Stitch selected UV vertices by proximity

Parameters

- **use_limit** (*boolean, (optional)*) – Use Limit, Stitch UVs within a specified limit distance.
- **limit** (*float in [0, inf], (optional)*) – Limit, Limit distance in normalized coordinates.

bpy.ops.uv.tile_set(tile=(0, 0))
Set UV image tile coordinates

Parameters **tile** (*int array of 2 items in [0, inf], (optional)*) – Tile, Tile coordinate.

bpy.ops.uv.unlink_selected()
Unlink selected UV vertices from active UV map

bpy.ops.uv.unwrap(method='ANGLE_BASED', fill_holes=True, correct_aspect=True)
Unwrap the mesh of the object being edited

Parameters

- **method** (*enum in ['ANGLE_BASED', 'CONFORMAL'], (optional)*) – Method, Unwrapping method. Angle Based usually gives better results than Conformal, while being somewhat slower.
- **fill_holes** (*boolean, (optional)*) – Fill Holes, Virtual fill holes in mesh before unwrapping, to better avoid overlaps and preserve symmetry.
- **correct_aspect** (*boolean, (optional)*) – Correct Aspect, Map UV's taking image aspect ratio into account.

bpy.ops.uv.weld()
Weld selected UV vertices together

View2D Operators

bpy.ops.view2d.pan(deltax=0, deltay=0)
Pan the view

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

bpy.ops.view2d.reset()
Reset the view

bpy.ops.view2d.scroll_down(deltax=0, deltay=0, page=False)
Scroll the view down

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y
- **page** (*boolean, (optional)*) – Page, Scroll down one page.

bpy.ops.view2d.scroll_left(deltax=0, deltay=0)
Scroll the view left

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

bpy.ops.view2d.**scroll_right** (*deltax=0, deltay=0*)
Scroll the view right

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y

bpy.ops.view2d.**scroll_up** (*deltax=0, deltay=0, page=False*)
Scroll the view up

Parameters

- **deltax** (*int in [-inf, inf], (optional)*) – Delta X
- **deltay** (*int in [-inf, inf], (optional)*) – Delta Y
- **page** (*boolean, (optional)*) – Page, Scroll up one page.

bpy.ops.view2d.**scroller_activate**()
Scroll view by mouse click and drag

bpy.ops.view2d.**zoom** (*deltax=0.0, deltay=0.0*)
Zoom in/out the view

Parameters

- **deltax** (*float in [-inf, inf], (optional)*) – Delta X
- **deltay** (*float in [-inf, inf], (optional)*) – Delta Y

bpy.ops.view2d.**zoom_border** (*gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0*)
Zoom in the view to the nearest item contained in the border

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.view2d.**zoom_in** (*zoomfacx=0.0, zoomfacy=0.0*)
Zoom in the view

Parameters

- **zoomfacx** (*float in [-inf, inf], (optional)*) – Zoom Factor X
- **zoomfacy** (*float in [-inf, inf], (optional)*) – Zoom Factor Y

bpy.ops.view2d.**zoom_out** (*zoomfacx=0.0, zoomfacy=0.0*)
Zoom out the view

Parameters

- **zoomfacx** (*float in [-inf, inf], (optional)*) – Zoom Factor X
- **zoomfacy** (*float in [-inf, inf], (optional)*) – Zoom Factor Y

View3D Operators

bpy.ops.view3d.**background_image_add**(*name*="Image", *filepath*="Path")
Add a new background image

Parameters

- **name** (*string, (optional)*) – Name, Image name to assign.
- **filepath** (*string, (optional)*) – Filepath, Path to image file

bpy.ops.view3d.**background_image_remove**(*index*=0)
Remove a background image from the 3D view

Parameters **index** (*int in [0, inf], (optional)*) – Index, Background image index to remove

bpy.ops.view3d.**camera_to_view**()
Set camera view to active view

bpy.ops.view3d.**clip_border**(*xmin*=0, *xmax*=0, *ymin*=0, *ymax*=0)
Set the view clipping border

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.view3d.**cursor3d**()
Set the location of the 3D cursor

bpy.ops.view3d.**dolly**(*delta*=0, *mx*=0, *my*=0)
Dolly in/out in the view

Parameters

- **delta** (*int in [-inf, inf], (optional)*) – Delta
- **mx** (*int in [0, inf], (optional)*) – Zoom Position X
- **my** (*int in [0, inf], (optional)*) – Zoom Position Y

bpy.ops.view3d.**edit_mesh_extrude_individual_move**()
Extrude individual elements and move

File startup/bl_ui/space_view3d.py:1554

bpy.ops.view3d.**edit_mesh_extrude_move_normal**()
Extrude and move along normals

File startup/bl_ui/space_view3d.py:1583

bpy.ops.view3d.**enable_manipulator**(*translate*=False, *rotate*=False, *scale*=False)
Enable the transform manipulator for use

Parameters

- **translate** (*boolean, (optional)*) – Translate, Enable the translate manipulator
- **rotate** (*boolean, (optional)*) – Rotate, Enable the rotate manipulator
- **scale** (*boolean, (optional)*) – Scale, Enable the scale manipulator

```
bpy.ops.view3d.fly()  
    Interactively fly around the scene  
  
bpy.ops.view3d.game_start()  
    Start game engine  
  
bpy.ops.view3d.layers (nr=1, extend=False, toggle=True)  
    Toggle layer(s) visibility
```

Parameters

- **nr** (*int in [0, 20], (optional)*) – Number, The layer number to set, zero for all layers
- **extend** (*boolean, (optional)*) – Extend, Add this layer to the current view layers
- **toggle** (*boolean, (optional)*) – Toggle, Toggle the layer

```
bpy.ops.view3d.localview()  
    Toggle display of selected object(s) separately and centered in view  
  
bpy.ops.view3d.manipulator (constraint_axis=(False, False, False), constraint_orientation=' ', release_confirm=False)  
    Manipulate selected item by axis
```

Parameters

- **constraint_axis** (*boolean array of 3 items, (optional)*) – Constraint Axis
- **constraint_orientation** (*enum in [], (optional)*) – Orientation, Transformation orientation
- **release_confirm** (*boolean, (optional)*) – Confirm on Release, Always confirm operation when releasing button

```
bpy.ops.view3d.move()  
    Move the view  
  
bpy.ops.view3d.object_as_camera()  
    Set the active object as the active camera for this view or scene  
  
bpy.ops.view3d.properties()  
    Toggles the properties panel display  
  
bpy.ops.view3d.render_border (xmin=0, xmax=0, ymin=0, ymax=0)  
    Set the boundaries of the border render and enables border render
```

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

```
bpy.ops.view3d.rotate()  
    Rotate the view  
  
bpy.ops.view3d.select (extend=False, center=False, enumerate=False)  
    Activate/select item(s)
```

Parameters

- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

- **center** (*boolean, (optional)*) – Center, Use the object center when selecting (object mode only).
- **enumerate** (*boolean, (optional)*) – Enumerate, List objects under the mouse (object mode only).

bpy.ops.view3d.**select_border**(*gesture_mode=0, xmin=0, xmax=0, ymin=0, ymax=0, extend=True*)
Select items using border selection

Parameters

- **gesture_mode** (*int in [-inf, inf], (optional)*) – Gesture Mode
- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min
- **ymax** (*int in [-inf, inf], (optional)*) – Y Max
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first

bpy.ops.view3d.**select_circle**(*x=0, y=0, radius=0, gesture_mode=0*)
Select items using circle selection

Parameters

- **x** (*int in [-inf, inf], (optional)*) – X
- **y** (*int in [-inf, inf], (optional)*) – Y
- **radius** (*int in [-inf, inf], (optional)*) – Radius
- **gesture_mode** (*int in [-inf, inf], (optional)*) – Event Type

bpy.ops.view3d.**select_lasso**(*path=None, deselect=False, extend=True*)
Select items using lasso selection

Parameters

- **path** (*bpy_prop_collection of OperatorMousePath, (optional)*) – Path
- **deselect** (*boolean, (optional)*) – Deselect, Deselect rather than select items.
- **extend** (*boolean, (optional)*) – Extend, Extend selection instead of deselecting everything first.

bpy.ops.view3d.**smoothview**()
The time to animate the change of view (in milliseconds)

bpy.ops.view3d.**snap_cursor_to_active**()
Snap cursor to active item

bpy.ops.view3d.**snap_cursor_to_center**()
Snap cursor to the Center

bpy.ops.view3d.**snap_cursor_to_grid**()
Snap cursor to nearest grid node

bpy.ops.view3d.**snap_cursor_to_selected**()
Snap cursor to center of selected item(s)

bpy.ops.view3d.**snap_selected_to_cursor**()
Snap selected item(s) to cursor

```
bpy.ops.view3d.snap_selected_to_grid()  
    Snap selected item(s) to nearest grid node
```

```
bpy.ops.view3d.toolshelf()  
    Toggles tool shelf display
```

```
bpy.ops.view3d.view_all(center=False)  
    View all objects in scene
```

Parameters **center** (*boolean, (optional)*) – Center

```
bpy.ops.view3d.view_center_camera()  
    Center the camera view
```

```
bpy.ops.view3d.view_center_cursor()  
    Centers the view so that the cursor is in the middle of the view
```

```
bpy.ops.view3d.view_orbit(type='ORBITLEFT')  
    Orbit the view
```

Parameters **type** (*enum in ['ORBITLEFT', 'ORBITRIGHT', 'ORBITUP', 'ORBITDOWN'], (optional)*) – Orbit, Direction of View Orbit

```
bpy.ops.view3d.view_pan(type='PANLEFT')  
    Pan the view
```

Parameters **type** (*enum in ['PANLEFT', 'PANRIGHT', 'PANUP', 'PANDOWN'], (optional)*) – Pan, Direction of View Pan

```
bpy.ops.view3d.view_persportho()  
    Switch the current view from perspective/orthographic
```

```
bpy.ops.view3d.view_selected()  
    Move the view to the selection center
```

```
bpy.ops.view3d.viewnumpad(type='FRONT', align_active=False)  
    Set the view
```

Parameters

- **type** (*enum in ['FRONT', 'BACK', 'LEFT', 'RIGHT', 'TOP', 'BOTTOM', 'CAMERA'], (optional)*) – View, The Type of view
- **align_active** (*boolean, (optional)*) – Align Active, Align to the active objects axis

```
bpy.ops.view3d.zoom(delta=0, mx=0, my=0)  
    Zoom in/out in the view
```

Parameters

- **delta** (*int in [-inf, inf], (optional)*) – Delta
- **mx** (*int in [0, inf], (optional)*) – Zoom Position X
- **my** (*int in [0, inf], (optional)*) – Zoom Position Y

```
bpy.ops.view3d.zoom_border(xmin=0, xmax=0, ymin=0, ymax=0)  
    Zoom in the view to the nearest object contained in the border
```

Parameters

- **xmin** (*int in [-inf, inf], (optional)*) – X Min
- **xmax** (*int in [-inf, inf], (optional)*) – X Max
- **ymin** (*int in [-inf, inf], (optional)*) – Y Min

- **ymax** (*int in [-inf, inf], (optional)*) – Y Max

bpy.ops.view3d.**zoom_camera_1_to_1**()
Match the camera to 1:1 to the render output

Wm Operators

bpy.ops.wm.**addon_disable**(*module=""*)
Disable an addon

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to disable

File startup/bl_ui/space_userpref.py:1058

bpy.ops.wm.**addon_enable**(*module=""*)
Enable an addon

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to enable

File startup/bl_ui/space_userpref.py:1037

bpy.ops.wm.**addon_expand**(*module=""*)
Display more information on this add-on

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to expand

File startup/bl_ui/space_userpref.py:1265

bpy.ops.wm.**addon_install**(*overwrite=True, target='DEFAULT', filepath="", filter_folder=True, filter_python=True, filter_glob="*.py;*.zip"*)
Install an addon

Parameters

- **overwrite** (*boolean, (optional)*) – Overwrite, Remove existing addons with the same ID
- **target** (*enum in ['DEFAULT', 'PREFS'], (optional)*) – Target Path
- **filepath** (*string, (optional)*) – File Path, File path to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_python** (*boolean, (optional)*) – Filter python

File startup/bl_ui/space_userpref.py:1092

bpy.ops.wm.**addon_remove**(*module=""*)
Disable an addon

Parameters **module** (*string, (optional)*) – Module, Module name of the addon to remove

File startup/bl_ui/space_userpref.py:1229

bpy.ops.wm.**appconfig_activate**(*filepath=""*)
Undocumented (contribute)

Parameters **filepath** (*string, (optional)*) – File Path

File startup/bl_operators/wm.py:965

bpy.ops.wm.**appconfig_default**()
Undocumented (contribute)

File startup/bl_operators/wm.py:946

```
bpy.ops.wm.call_menu(name=""")  
Undocumented (contribute)
```

Parameters `name` (*string, (optional)*) – Name, Name of the menu

```
bpy.ops.wm.context_collection_boolean_set(data_path_iter=""",  
                                            data_path_item=""",  
                                            type='TOGGLE')
```

Set boolean values for a collection of items

Parameters

- `data_path_iter` (*string, (optional)*) – The data path relative to the context, must point to an iterable.
- `data_path_item` (*string, (optional)*) – The data path from each iterable to the value (int or float)
- `type` (*enum in ['TOGGLE', 'ENABLE', 'DISABLE'], (optional)*) – Type

File `startup/bl_operators/wm.py:485`

```
bpy.ops.wm.context_cycle_array(data_path=""", reverse=False)
```

Set a context array value. Useful for cycling the active mesh edit mode.

Parameters

- `data_path` (*string, (optional)*) – Context Attributes, rna context string
- `reverse` (*boolean, (optional)*) – Reverse, Cycle backwards

File `startup/bl_operators/wm.py:370`

```
bpy.ops.wm.context_cycle_enum(data_path=""", reverse=False)  
Toggle a context value.
```

Parameters

- `data_path` (*string, (optional)*) – Context Attributes, rna context string
- `reverse` (*boolean, (optional)*) – Reverse, Cycle backwards

File `startup/bl_operators/wm.py:317`

```
bpy.ops.wm.context_cycle_int(data_path=""", reverse=False)  
Set a context value. Useful for cycling active material,
```

Parameters

- `data_path` (*string, (optional)*) – Context Attributes, rna context string
- `reverse` (*boolean, (optional)*) – Reverse, Cycle backwards

File `startup/bl_operators/wm.py:283`

```
bpy.ops.wm.context_menu_enum(data_path=""")  
Undocumented (contribute)
```

Parameters `data_path` (*string, (optional)*) – Context Attributes, rna context string

File `startup/bl_operators/wm.py:414`

```
bpy.ops.wm.context_modal_mouse(data_path_iter=""", data_path_item=""", input_scale=0.01, in-  
vert=False, initial_x=0)
```

Adjust arbitrary values with mouse input

Parameters

- **data_path_iter** (*string, (optional)*) – The data path relative to the context, must point to an iterable.
- **data_path_item** (*string, (optional)*) – The data path from each iterable to the value (int or float)
- **input_scale** (*float in [-inf, inf], (optional)*) – Scale the mouse movement by this value before applying the delta
- **invert** (*boolean, (optional)*) – Invert the mouse input

File `startup/bl_operators/wm.py:595`

`bpy.ops.wm.context_scale_int(data_path="", value=1.0, always_step=True)`
Scale an int context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*float in [-inf, inf], (optional)*) – Value, Assign value
- **always_step** (*boolean, (optional)*) – Always Step, Always adjust the value by a minimum of 1 when ‘value’ is not 1.0.

File `startup/bl_operators/wm.py:145`

`bpy.ops.wm.context_set_boolean(data_path="", value=True)`
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*boolean, (optional)*) – Value, Assignment value

File `startup/bl_operators/wm.py:67`

`bpy.ops.wm.context_set_enum(data_path="", value="")`
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assignment value (as a string)

File `startup/bl_operators/wm.py:67`

`bpy.ops.wm.context_set_float(data_path="", value=0.0, relative=False)`
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*float in [-inf, inf], (optional)*) – Value, Assignment value
- **relative** (*boolean, (optional)*) – Relative, Apply relative to the current value (delta)

File `startup/bl_operators/wm.py:67`

`bpy.ops.wm.context_set_id(data_path="", value="")`
Toggle a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string

- **value** (*string, (optional)*) – Value, Assign value

File startup/bl_operators/wm.py:431

bpy.ops.wm.context_set_int (data_path=""“, value=0, relative=False)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*int in [-inf, inf], (optional)*) – Value, Assign value
- **relative** (*boolean, (optional)*) – Relative, Apply relative to the current value (delta)

File startup/bl_operators/wm.py:67

bpy.ops.wm.context_set_string (data_path=""“, value=""“)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assign value

File startup/bl_operators/wm.py:67

bpy.ops.wm.context_set_value (data_path=""“, value=""“)
Set a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value** (*string, (optional)*) – Value, Assignment value (as a string)

File startup/bl_operators/wm.py:221

bpy.ops.wm.context_toggle (data_path=""“)
Toggle a context value.

Parameters **data_path** (*string, (optional)*) – Context Attributes, rna context string

File startup/bl_operators/wm.py:236

bpy.ops.wm.context_toggle_enum (data_path=""“, value_1=""“, value_2=""“)
Toggle a context value.

Parameters

- **data_path** (*string, (optional)*) – Context Attributes, rna context string
- **value_1** (*string, (optional)*) – Value, Toggle enum
- **value_2** (*string, (optional)*) – Value, Toggle enum

File startup/bl_operators/wm.py:260

bpy.ops.wm.copy_prev_settings ()
Copy settings from previous version

File startup/bl_operators/wm.py:993

bpy.ops.wm.debug_menu (debug_value=0)
Open a popup to set the debug level

Parameters **debug_value** (*int in [-10000, 10000], (optional)*) – Debug Value

bpy.ops.wm.doc_edit(doc_id="", doc_new="")

Load online reference docs

Parameters

- **doc_id** (*string, (optional)*) – Doc ID
- **doc_new** (*string, (optional)*) – Edit Description

File startup/bl_operators/wm.py:731

bpy.ops.wm.doc_view(doc_id="")

Load online reference docs

Parameters **doc_id** (*string, (optional)*) – Doc ID

File startup/bl_operators/wm.py:676

bpy.ops.wm.interaction_preset_add(name="", remove_active=False)

Add an Application Interaction Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File startup/bl_operators/presets.py:42

bpy.ops.wm.keyconfig_activate(filepath="")

Undocumented (contribute)

Parameters **filepath** (*string, (optional)*) – File Path

File startup/bl_operators/wm.py:937

bpy.ops.wm.keyconfig_export(filepath="keymap.py", filter_folder=True, filter_text=True, filter_python=True)

Export key configuration to a python script

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_text** (*boolean, (optional)*) – Filter text
- **filter_python** (*boolean, (optional)*) – Filter python

File startup/bl_ui/space_userpref_keymap.py:589

bpy.ops.wm.keyconfig_import(filepath="keymap.py", filter_folder=True, filter_text=True, filter_python=True, keep_original=True)

Import key configuration from a python script

Parameters

- **filepath** (*string, (optional)*) – File Path, Filepath to write file to
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filter_text** (*boolean, (optional)*) – Filter text
- **filter_python** (*boolean, (optional)*) – Filter python
- **keep_original** (*boolean, (optional)*) – Keep original, Keep original file after copying to configuration folder

File startup/bl_ui/space_userpref_keymap.py:546

bpy.ops.wm.keyconfig_preset_add(name="", remove_active=False)

Add a Keyconfig Preset

Parameters **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name

File startup/bl_operators/presets.py:42

bpy.ops.wm.keyconfig_remove()

Remove key config

File startup/bl_ui/space_userpref_keymap.py:773

bpy.ops.wm.keyconfig_test()

Test keyconfig for conflicts

File startup/bl_ui/space_userpref_keymap.py:513

bpy.ops.wm.keyitem_add()

Add key map item

File startup/bl_ui/space_userpref_keymap.py:725

bpy.ops.wm.keyitem_remove(*item_id=0*)

Remove key map item

Parameters **item_id** (*int in [-inf, inf], (optional)*) – Item Identifier, Identifier of the item to remove

File startup/bl_ui/space_userpref_keymap.py:755

bpy.ops.wm.keyitem_restore(*item_id=0*)

Restore key map item

Parameters **item_id** (*int in [-inf, inf], (optional)*) – Item Identifier, Identifier of the item to remove

File startup/bl_ui/space_userpref_keymap.py:710

bpy.ops.wm.keymap_edit()

Edit stored key map

File startup/bl_ui/space_userpref_keymap.py:672

bpy.ops.wm.keymap_restore(*all=False*)

Restore key map(s)

Parameters **all** (*boolean, (optional)*) – All Keymaps, Restore all keymaps to default

File startup/bl_ui/space_userpref_keymap.py:685

bpy.ops.wm.link_append(*filepath=""*, *directory=""*, *filename=""*, *filter_blender=True*, *filter_image=False*, *filter_movie=False*, *filter_python=False*, *filter_font=False*, *filter_sound=False*, *filter_text=False*, *filter_btx=False*, *filter_collada=False*, *filter_folder=True*, *filemode=1*, *relative_path=False*, *link=True*, *autoselect=True*, *active_layer=True*, *instance_groups=True*, *files=None*)

Link or Append from a Library .blend file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **directory** (*string, (optional)*) – Directory, Directory of the file
- **filename** (*string, (optional)*) – File Name, Name of the file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files

- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **relative_path** (*boolean, (optional)*) – Relative Path, Select the file relative to the blend file
- **link** (*boolean, (optional)*) – Link, Link the objects or datablocks rather than appending
- **autoselect** (*boolean, (optional)*) – Select, Select the linked objects
- **active_layer** (*boolean, (optional)*) – Active Layer, Put the linked objects on the active layer
- **instance_groups** (*boolean, (optional)*) – Instance Groups, Create instances for each group as a DupliGroup
- **files** (*bpy_prop_collection of OperatorFileListElement, (optional)*) – Files

```
bpy.ops.wm.memory_statistics()
```

Print memory statistics to the console

```
bpy.ops.wm.open_mainfile(filepath="", filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=True, filemode=8, load_ui=True, use_scripts=True)
```

Open a Blender file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **load_ui** (*boolean, (optional)*) – Load UI, Load user interface setup in the .blend file
- **use_scripts** (*boolean, (optional)*) – Trusted Source, Allow blend file execute scripts automatically, default available from system preferences

bpy.ops.wm.operator_preset_add(name=""", remove_active=False, operator="")
Add an Application Interaction Preset

Parameters

- **name** (*string, (optional)*) – Name, Name of the preset, used to make the path name
- **operator** (*string, (optional)*) – Operator

File startup/bl_operators/presets.py:42

bpy.ops.wm.path_open(filepath="")
Open a path in a file browser

Parameters **filepath** (*string, (optional)*) – File Path

File startup/bl_operators/wm.py:631

bpy.ops.wm.properties_add(data_path="")
Internal use (edit a property data_path)

Parameters **data_path** (*string, (optional)*) – Property Edit, Property data_path edit

File startup/bl_operators/wm.py:886

bpy.ops.wm.properties_context_change(context="")
Change the context tab in a Properties Window

Parameters **context** (*string, (optional)*) – Context

File startup/bl_operators/wm.py:912

bpy.ops.wm.properties_edit(data_path="", property="", value="", min=0.0, max=1.0, description="")
Internal use (edit a property data_path)

Parameters

- **data_path** (*string, (optional)*) – Property Edit, Property data_path edit
- **property** (*string, (optional)*) – Property Name, Property name edit
- **value** (*string, (optional)*) – Property Value, Property value edit
- **min** (*float in [-inf, inf], (optional)*) – Min
- **max** (*float in [-inf, inf], (optional)*) – Max
- **description** (*string, (optional)*) – Tip

File startup/bl_operators/wm.py:808

bpy.ops.wm.properties_remove(data_path="", property="")
Internal use (edit a property data_path)

Parameters

- **data_path** (*string, (optional)*) – Property Edit, Property data_path edit
- **property** (*string, (optional)*) – Property Name, Property name edit

File startup/bl_operators/wm.py:925

bpy.ops.wm.quit_blender()
Quit Blender

bpy.ops.wm.radial_control(data_path="", rotation_path="", color_path="", fill_color_path="", zoom_path="", image_id="")
Undocumented (contribute)

Parameters

- **data_path** (*string, (optional)*) – Data Path, Path of property to be set by the radial control.
- **rotation_path** (*string, (optional)*) – Rotation Path, Path of property used to rotate the texture display.
- **color_path** (*string, (optional)*) – Color Path, Path of property used to set the color of the control.
- **fill_color_path** (*string, (optional)*) – Fill Color Path, Path of property used to set the fill color of the control.
- **zoom_path** (*string, (optional)*) – Zoom Path, Path of property used to set the zoom level for the control.
- **image_id** (*string, (optional)*) – Image ID, Path of ID that is used to generate an image for the control.

bpy.ops.wm.read_factory_settings()

Load default file and user preferences

bpy.ops.wm.read_homefile()

Open the default file (doesn't save the current file)

bpy.ops.wm.recover_auto_save(filepath="", filter_blender=True, filter_image=False, filter_movie=False, filter_python=False, filter_font=False, filter_sound=False, filter_text=False, filter_btx=False, filter_collada=False, filter_folder=False, filemode=8)

Open an automatically saved file to recover it

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file

bpy.ops.wm.recover_last_session()

Open the last closed file ("quit.blend")

bpy.ops.wm.redraw_timer(type='DRAW', iterations=10)

Simple redraw timer to test the speed of updating the interface

Parameters

- **type** (*enum in [‘DRAW’, ‘DRAW_SWAP’, ‘DRAW_WIN’, ‘DRAW_WIN_SWAP’, ‘ANIM_STEP’, ‘ANIM_PLAY’, ‘UNDO’], (optional)*) – Type
- **iterations** (*int in [1, inf], (optional)*) – Iterations, Number of times to redraw

```
bpy.ops.wm.save_as_mainfile(filepath="", check_existing=True, filter.blender=True, filter.image=False, filter.movie=False, filter.python=False, filter.font=False, filter.sound=False, filter.text=False, filter.btx=False, filter.collada=False, filter.folder=True, filemode=8, compress=False, relative_remap=True, copy=False)
```

Save the current file in the desired location

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files
- **filter.blender** (*boolean, (optional)*) – Filter .blend files
- **filter.image** (*boolean, (optional)*) – Filter image files
- **filter.movie** (*boolean, (optional)*) – Filter movie files
- **filter.python** (*boolean, (optional)*) – Filter python files
- **filter.font** (*boolean, (optional)*) – Filter font files
- **filter.sound** (*boolean, (optional)*) – Filter sound files
- **filter.text** (*boolean, (optional)*) – Filter text files
- **filter.btx** (*boolean, (optional)*) – Filter btx files
- **filter.collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter.folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **compress** (*boolean, (optional)*) – Compress, Write compressed .blend file
- **relative_remap** (*boolean, (optional)*) – Remap Relative, Remap relative paths when saving in a different directory
- **copy** (*boolean, (optional)*) – Save Copy, Save a copy of the actual working state but does not make saved file active.

```
bpy.ops.wm.save_homefile()
```

Make the current file the default .blend file

```
bpy.ops.wm.save_mainfile(filepath="", check_existing=True, filter.blender=True, filter.image=False, filter.movie=False, filter.python=False, filter.font=False, filter.sound=False, filter.text=False, filter.btx=False, filter.collada=False, filter.folder=True, filemode=8, compress=False, relative_remap=False)
```

Save the current Blender file

Parameters

- **filepath** (*string, (optional)*) – File Path, Path to file
- **check_existing** (*boolean, (optional)*) – Check Existing, Check and warn on overwriting existing files

- **filter_blender** (*boolean, (optional)*) – Filter .blend files
- **filter_image** (*boolean, (optional)*) – Filter image files
- **filter_movie** (*boolean, (optional)*) – Filter movie files
- **filter_python** (*boolean, (optional)*) – Filter python files
- **filter_font** (*boolean, (optional)*) – Filter font files
- **filter_sound** (*boolean, (optional)*) – Filter sound files
- **filter_text** (*boolean, (optional)*) – Filter text files
- **filter_btx** (*boolean, (optional)*) – Filter btx files
- **filter_collada** (*boolean, (optional)*) – Filter COLLADA files
- **filter_folder** (*boolean, (optional)*) – Filter folders
- **filemode** (*int in [1, 9], (optional)*) – File Browser Mode, The setting for the file browser mode to load a .blend file, a library or a special file
- **compress** (*boolean, (optional)*) – Compress, Write compressed .blend file
- **relative_remap** (*boolean, (optional)*) – Remap Relative, Remap relative paths when saving in a different directory

bpy.ops.wm.**search_menu**()
Undocumented ([contribute](#))

bpy.ops.wm.**splash**()
Opens a blocking popup region with release info

bpy.ops.wm.**sysinfo**()
Generate System Info

File [startup/bl_operators/wm.py:982](#)

bpy.ops.wm.**url_open**(*url=""*)
Open a website in the Webbrowser

Parameters **url** (*string, (optional)*) – URL, URL to open

File [startup/bl_operators/wm.py:617](#)

bpy.ops.wm.**window_duplicate**()
Duplicate the current Blender window

bpy.ops.wm.**window_fullscreen_toggle**()
Toggle the current window fullscreen

World Operators

bpy.ops.world.**new**()
Add a new world

2.4 Types (bpy.types)

2.4.1 Action(ID)

base classes — `bpy_struct, ID`

class bpy.types.Action (ID)

A collection of F-Curves for animation

fcurves

The individual F-Curves that make up the Action

Type ActionFCurves bpy_prop_collection of FCurve, (readonly)

frame_range

The final frame range of all fcurves within this action

Type float array of 2 items in [-inf, inf], default (0.0, 0.0), (readonly)

groups

Convenient groupings of F-Curves

Type ActionGroups bpy_prop_collection of ActionGroup, (readonly)

id_root

Type of ID-block that action can be used on. DO NOT CHANGE UNLESS YOU KNOW WHAT YOU'RE DOING

Type enum in ['ACTION', 'ARMATURE', 'BRUSH', 'CAMERA', 'CURVE', 'FONT', 'GREASEPENCIL', 'GROUP', 'IMAGE', 'KEY', 'LAMP', 'LIBRARY', 'LATTICE', 'MATERIAL', 'META', 'MESH', 'NODETREE', 'OBJECT', 'PARTICLE', 'SCENE', 'SCREEN', 'SOUND', 'TEXT', 'TEXTURE', 'WORLD', 'WINDOWMANAGER'], default 'ACTION'

pose_markers

Markers specific to this Action, for labeling poses

Type ActionPoseMarkers bpy_prop_collection of TimelineMarker, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- ActionActuator.action
- ActionConstraint.action
- AnimData.action
- BlendData.actions
- BlendDataActions.new
- BlendDataActions.remove
- NlaStrip.action
- NlaStrips.new
- Object.pose_library
- ShapeActionActuator.action
- SpaceDopeSheetEditor.action

2.4.2 ActionActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.ActionActuator(Actuator)

Actuator to control the object movement

action

Type Action

frame_blend_in

Number of frames of motion blending

Type int in [0, 32767], default 0

frame_end

Type float in [-inf, inf], default 0.0

frame_property

Assign the action's current frame number to this property

Type string, default “”

frame_start

Type float in [-inf, inf], default 0.0

play_mode

Action playback type

Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'LOOPSTOP', 'LOOPEND', 'PROPERTY'], default 'PLAY'

priority

Execution priority - lower numbers will override actions with higher numbers. With 2 or more actions at once, the overriding channels must be lower in the stack

Type int in [0, 100], default 0

property

Use this property to define the Action position

Type string, default “”

use_continue_last_frame

Restore last frame when switching on/off, otherwise play from the start each time

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.3 ActionConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.ActionConstraint (Constraint)

Map an action to the transform axes of a bone

action

The constraining action

Type [Action](#)

frame_end

Last frame of the Action to use

Type int in [-300000, 300000], default 0

frame_start

First frame of the Action to use

Type int in [-300000, 300000], default 0

max

Maximum value for target channel range

Type float in [-1000, 1000], default 0.0

min

Minimum value for target channel range

Type float in [-1000, 1000], default 0.0

subtarget

Type string, default “”

target

Target Object

Type [Object](#)

transform_channel

Transformation channel from the target that is used to key the Action

Type enum in ['LOCATION_X', 'LOCATION_Y', 'LOCATION_Z', 'ROTATION_X', 'ROTATION_Y', 'ROTATION_Z', 'SCALE_X', 'SCALE_Y', 'SCALE_Z'], default 'ROTATION_X'

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`
- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.4 ActionFCurves(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ActionFCurves` (`bpy_struct`)

Collection of action fcurves

new (`data_path`, `index=0`, `action_group=""`)

Add a keyframe to the curve.

Parameters

- **data_path** (`string`) – Data Path, FCurve data path to use.
- **index** (`int in [0, inf], (optional)`) – Index, Array index.
- **action_group** (`string, (optional)`) – Action Group, Acton group to add this fcurve into.

Returns Newly created fcurve

Return type `FCurve`

remove (`fcurve`)

Remove action group.

Parameters `fcurve` (`FCurve`, (never None)) – FCurve to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`

- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Action.fcurves`

2.4.5 ActionGroup(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ActionGroup` (`bpy_struct`)
Groups of F-Curves

channels

F-Curves in this group

Type `bpy_prop_collection` of `FCurve`, (readonly)

custom_color

Index of custom color set

Type int in [-inf, inf], default 0

lock

Action Group is locked

Type boolean, default False

name

Type string, default “”

select

Action Group is selected

Type boolean, default False

show_expanded

Action Group is expanded

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Action.groups`
- `ActionGroups.new`
- `ActionGroups.remove`
- `FCurve.group`

2.4.6 ActionGroups(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ActionGroups (bpy_struct)`

Collection of action groups

new (`name`)

Add a keyframe to the curve.

Parameters `name` (`string`) – New name for the action group.

Returns Newly created action group

Return type `ActionGroup`

remove (`action_group`)

Remove action group.

Parameters `action_group` (`ActionGroup`, (never None)) – Action group to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Action.groups`

2.4.7 ActionPoseMarkers(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ActionPoseMarkers` (`bpy_struct`)
Collection of timeline markers

active

Active pose marker for this Action

Type `TimelineMarker`

active_index

Index of active pose marker

Type int in [-inf, inf], default 0

new (`name`)

Add a pose marker to the action.

Parameters `name` (string) – New name for the marker (not unique).

Returns Newly created marker

Return type `TimelineMarker`

remove (`marker`)

Remove a timeline marker.

Parameters `marker` (`TimelineMarker`, (never None)) – Timeline marker to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.pose_markers

2.4.8 Actuator(bpy_struct)

base class — bpy_struct

subclasses — ShapeActionActuator, VisibilityActuator, MessageActuator, RandomActuator, Filter2DActuator, GameActuator, CameraActuator, ArmatureActuator, SoundActuator, ParentActuator, SceneActuator, StateActuator, ActionActuator, ConstraintActuator, PropertyActuator, FCurveActuator, ObjectActuator, EditObjectActuator

class bpy.types.**Actuator**(*bpy_struct*)

Actuator to apply actions in the game engine

name

Type string, default “”

pin

Display when not linked to a visible states controller

Type boolean, default False

show_expanded

Set actuator expanded in the user interface

Type boolean, default False

type

Type enum in [‘ACTION’, ‘ARMATURE’, ‘CAMERA’, ‘CONSTRAINT’, ‘EDIT_OBJECT’, ‘FCURVE’, ‘FILTER_2D’, ‘GAME’, ‘MESSAGE’, ‘MOTION’, ‘PARENT’, ‘PROPERTY’, ‘RANDOM’, ‘SCENE’, ‘SHAPE_ACTION’, ‘SOUND’, ‘STATE’, ‘VISIBILITY’], default ‘MOTION’

link(*controller*)

Link the actuator to a controller.

Parameters **controller** (*Controller*) – Controller to link to.

unlink(*controller*)

Unlink the actuator from a controller.

Parameters **controller** (*Controller*) – Controller to unlink from.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Controller.link
- Controller.unlink
- GameObjectSettings.actuators

2.4.9 ActuatorSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.*ActuatorSensor* (*Sensor*)
Sensor to detect state modifications of actuators

actuator

Actuator name, actuator active state modifications will be detected

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level

- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.10 Addon(bpy_struct)

base class — bpy_struct

class bpy.types.**Addon** (*bpy_struct*)
Python addons to be loaded automatically

module
Module name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Addons.new`
- `Addons.remove`
- `UserPreferences.addons`

2.4.11 Addons(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.Addons` (`bpy_struct`)

Collection of add-ons

classmethod new()

Add a new addon

Returns Addon datablock.

Return type `Addon`

classmethod remove(addon)

Remove addon.

Parameters `addon` (`Addon`, (never None)) – Addon to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`

- `bpy_struct.values`

References

- `UserPreferences.addons`

2.4.12 AdjustmentSequence(Sequence)

base classes — `bpy_struct, Sequence`

```
class bpy.types.AdjustmentSequence (Sequence)
    Sequence strip to perform filter adjustments to layers below

    animation_offset_end
        Animation end offset (trim end)
        Type int in [0, inf], default 0

    animation_offset_start
        Animation start offset (trim start)
        Type int in [0, inf], default 0

    color_balance
        Type SequenceColorBalance, (readonly)

    color_multiply
        Type float in [0, 20], default 0.0

    color_saturation
        Type float in [0, 20], default 0.0

    crop
        Type SequenceCrop, (readonly)

    proxy
        Type SequenceProxy, (readonly)

    strobe
        Only display every nth frame
        Type float in [1, 30], default 0.0

    transform
        Type SequenceTransform, (readonly)

    use_color_balance
        (3-Way color correction) on input
        Type boolean, default False

    use_crop
        Crop image before processing
        Type boolean, default False

    use_deinterlace
        For video movies to remove fields
```

Type boolean, default False
use_flip_x
Flip on the X axis
Type boolean, default False
use_flip_y
Flip on the Y axis
Type boolean, default False
use_float
Convert input to float data
Type boolean, default False
use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False
use_proxy
Use a preview proxy for this strip
Type boolean, default False
use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False
use_proxy_custom_file
Use a custom file to read proxy data from
Type boolean, default False
use_reverse_frames
Reverse frame order
Type boolean, default False
use_translation
Translate image before processing
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`

- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.13 AlwaysSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.AlwaysSensor (Sensor)
Sensor to generate continuous pulses

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin

- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.14 AndController(Controller)

base classes — bpy_struct, Controller

class bpy.types.AndController(Controller)

Controller passing on events based on a logical AND operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.15 AnimData(bpy_struct)

base class — `bpy_struct`

class `bpy.types.AnimData(bpy_struct)`
Animation data for datablock

action
Active Action for this datablock

Type `Action`

action_blend_type
Method used for combining Active Action's result with result of NLA stack

Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULTPLY'], default 'REPLACE'

action_extrapolation
Action to take for gaps past the Active Action's range (when evaluating with NLA)

Type enum in ['NOTHING', 'HOLD', 'HOLD_FORWARD'], default 'HOLD'

action_influence
Amount the Active Action contributes to the result of the NLA stack

Type float in [0, 1], default 1.0

drivers
The Drivers/Expressions for this datablock

Type `AnimDataDrivers bpy_prop_collection of FCurve`, (readonly)

nla_tracks
NLA Tracks (i.e. Animation Layers)

Type `NlaTracks bpy_prop_collection of NlaTrack`, (readonly)

use_nla
NLA stack is evaluated when evaluating this block

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Armature.animation_data`
- `Camera.animation_data`
- `Curve.animation_data`
- `ID.animation_data_create`
- `Key.animation_data`
- `Lamp.animation_data`
- `Lattice.animation_data`
- `Material.animation_data`
- `Mesh.animation_data`
- `MetaBall.animation_data`
- `NodeTree.animation_data`
- `Object.animation_data`
- `ParticleSettings.animation_data`
- `Scene.animation_data`
- `Texture.animation_data`
- `World.animation_data`

2.4.16 AnimDataDrivers(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.AnimDataDrivers(bpy_struct)`

Collection of Driver F-Curves

from_existing (`src_driver=None`)

Add a new driver given an existing one

Parameters `src_driver` (`FCurve`, (optional)) – Existing Driver F-Curve to use as template for a new one

Returns New Driver F-Curve.

Return type `FCurve`

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- AnimData.drivers

2.4.17 AnimViz(bpy_struct)

base class — bpy_struct

class bpy.types.AnimViz (bpy_struct)

Settings for the visualisation of motion

motion_path

Motion Path settings for visualisation

Type AnimVizMotionPaths, (readonly, never None)

onion_skin_frames

Onion Skinning (ghosting) settings for visualisation

Type AnimVizOnionSkinning, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.animation_visualisation
- Pose.animation_visualisation

2.4.18 AnimVizMotionPaths(bpy_struct)

base class — bpy_struct

class bpy.types.AnimVizMotionPaths (bpy_struct)

Motion Path settings for animation visualisation

bake_location

When calculating Bone Paths, use Head or Tips

Type enum in ['HEADS', 'TAILS'], default 'TAILS'

frame_after

Number of frames to show after the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [1, 150000], default 0

frame_before

Number of frames to show before the current frame (only for 'Around Current Frame' Onion-skinning method)

Type int in [1, 150000], default 0

frame_end

End frame of range of paths to display/calculate (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_start

Starting frame of range of paths to display/calculate (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

frame_step

Number of frames between paths shown (not for 'On Keyframes' Onion-skinning method)

Type int in [1, 100], default 0

show_frame_numbers

Show frame numbers on Motion Paths

Type boolean, default False

show_keyframe_action_all

For bone motion paths, search whole Action for keyframes instead of in group with matching name only
(is slower)

Type boolean, default False

show_keyframe_highlight

Emphasize position of keyframes on Motion Paths

Type boolean, default False

show_keyframe_numbers

Show frame numbers of Keyframes on Motion Paths

Type boolean, default False

type

Type of range to show for Motion Paths

Type enum in ['CURRENT_FRAME', 'RANGE'], default 'RANGE'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- AnimViz.motion_path

2.4.19 AnimVizOnionSkinning(bpy_struct)

base class — `bpy_struct`

`class bpy.types.AnimVizOnionSkinning(bpy_struct)`

Onion Skinning settings for animation visualisation

`frame_after`

Number of frames to show after the current frame (only for ‘Around Current Frame’ Onion-skinning method)

Type int in [0, 30], default 0

`frame_before`

Number of frames to show before the current frame (only for ‘Around Current Frame’ Onion-skinning method)

Type int in [0, 30], default 0

`frame_end`

End frame of range of Ghosts to display (not for ‘Around Current Frame’ Onion-skinning method)

Type int in [-inf, inf], default 0

`frame_start`

Starting frame of range of Ghosts to display (not for ‘Around Current Frame’ Onion-skinning method)

Type int in [-inf, inf], default 0

`frame_step`

Number of frames between ghosts shown (not for ‘On Keyframes’ Onion-skinning method)

Type int in [1, 20], default 0

`show_only_selected`

For Pose-Mode drawing, only draw ghosts for selected bones

Type boolean, default False

`type`

Method used for determining what ghosts get drawn

Type enum in ['NONE', 'CURRENT_FRAME', 'RANGE', 'KEYS'], default ‘NONE’

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AnimViz.onion_skin_frames`

2.4.20 AnyType(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.AnyType` (`bpy_struct`)
RNA type used for pointers to any possible data

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `KeyingSetInfo.generate`
- `UILayout.context_pointer_set`
- `UILayout.prop`
- `UILayout.prop_enum`
- `UILayout.prop_menu_enum`
- `UILayout.prop_search`
- `UILayout.prop_search`

- `UILayout.props_enum`
- `UILayout.template_ID`
- `UILayout.template_ID_preview`
- `UILayout.template_any_ID`
- `UILayout.template_color_ramp`
- `UILayout.template_color_wheel`
- `UILayout.template_curve_mapping`
- `UILayout.template_histogram`
- `UILayout.template_image`
- `UILayout.template_layers`
- `UILayout.template_layers`
- `UILayout.template_list`
- `UILayout.template_list`
- `UILayout.template_path_builder`
- `UILayout.template_vectorscope`
- `UILayout.template_waveform`

2.4.21 Area(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.Area` (`bpy_struct`)

Area in a subdivided screen, containing an editor

height

Area height

Type `int` in [0, 32767], default 0, (readonly)

regions

Regions this area is subdivided in

Type `bpy_prop_collection` of `Region`, (readonly)

show_menus

Show menus in the header

Type boolean, default False

spaces

Spaces contained in this area, the first being the active space. NOTE: Useful for example to restore a previously used 3d view space in a certain area to get the old view orientation.

Type `AreaSpaces` `bpy_prop_collection` of `Space`, (readonly)

type

Space type

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY'

width

Area width

Type `int` in [0, 32767], default 0, (readonly)

```
tag_redraw()
tag_redraw

header_text_set (text="")
    Set the header text

Parameters text (string, (optional)) – Text, New string for the header, no argument clears the text.
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.area
- Screen.areas

2.4.22 AreaLamp(Lamp)

base classes — bpy_struct, ID, Lamp

```
class bpy.types.AreaLamp (Lamp)
    Directional area lamp

    gamma
        Light gamma correction value
        Type float in [-inf, inf], default 0.0

    shadow_adaptive_threshold
        Threshold for Adaptive Sampling (Raytraced shadows)
        Type float in [0, 1], default 0.0
```

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method

Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method

Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC', 'CONSTANT_JITTERED'], default 'CONSTANT_JITTERED'

shadow_ray_samples_x

Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_ray_samples_y

Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size

Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

shape

Shape of the area lamp

Type enum in ['SQUARE', 'RECTANGLE'], default 'SQUARE'

size

Size of the area of the area Lamp, X direction size for Rectangle shapes

Type float in [-inf, inf], default 0.0

size_y

Size of the area of the area Lamp in the Y direction for Rectangle shapes

Type float in [-inf, inf], default 0.0

use_dither

Use 2x2 dithering for sampling (Constant Jittered sampling)

Type boolean, default False

use_jitter

Use noise for sampling (Constant Jittered sampling)

Type boolean, default False

use_only_shadow

Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer

Causes only objects on the same layer to cast shadows

Type boolean, default False

use_umbra

Emphasize parts that are fully shadowed (Constant Jittered sampling)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.23 AreaSpaces(bpy_struct)

base class — `bpy_struct`

class bpy.types.AreaSpaces (bpy_struct)

Collection of spaces

active

Space currently being displayed in this area

Type `Space`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Area.spaces`

2.4.24 Armature(ID)

base classes — `bpy_struct, ID`

class bpy.types.Armature (ID)

Armature datablock containing a hierarchy of bones, usually used for rigging characters

animation_data

Animation data for this datablock

Type `AnimData`, (readonly)

bones

Type `ArmatureBones bpy_prop_collection of Bone`, (readonly)

draw_type

Type enum in ['OCTAHEDRAL', 'STICK', 'BBONE', 'ENVELOPE'], default 'OCTAHEDRAL'

edit_bones

Type ArmatureEditBones bpy_prop_collection of EditBone, (readonly)

ghost_frame_end

End frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

ghost_frame_start

Starting frame of range of Ghosts to display (not for 'Around Current Frame' Onion-skinning method)

Type int in [-inf, inf], default 0

ghost_size

Frame step for Ghosts (not for 'On Keyframes' Onion-skinning method)

Type int in [1, 20], default 0

ghost_step

Number of frame steps on either side of current frame to show as ghosts (only for 'Around Current Frame' Onion-skinning method)

Type int in [0, 30], default 0

ghost_type

Method of Onion-skinning for active Action

Type enum in ['CURRENT_FRAME', 'RANGE', 'KEYS'], default 'CURRENT_FRAME'

layers

Armature layer visibility

Type boolean array of 32 items, default (False, False, False)

layers_protected

Protected layers in Proxy Instances are restored to Proxy settings on file reload and undo

Type boolean array of 32 items, default (False, False, False)

pose_position

Show armature in binding pose or final posed state

Type enum in ['POSE', 'REST'], default 'POSE'

show_axes

Draw bone axes

Type boolean, default False

show_bone_custom_shapes

Draw bones with their custom shapes

Type boolean, default False

show_group_colors

Draw bone group colors

Type boolean, default False

show_names
Draw bone names

Type boolean, default False

show_only_ghost_selected

Type boolean, default False

use_auto_ik
Add temporal IK constraints while grabbing bones in Pose Mode

Type boolean, default False

use_deform_delay
Don't deform children when manipulating bones in Pose Mode

Type boolean, default False

use_deform_envelopes
Enable Bone Envelopes when defining deform

Type boolean, default False

use_deform_preserve_volume
Enable deform rotation with Quaternions

Type boolean, default False

use_deform_vertex_groups
Enable Vertex Groups when defining deform

Type boolean, default False

use_mirror_x
Apply changes to matching bone on opposite side of X-Axis

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.armatures
- BlendDataArmatures.new
- BlendDataArmatures.remove

2.4.25 ArmatureActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**ArmatureActuator** (Actuator)

Actuator to ..

bone

Bone on which the constraint is defined

Type string, default “”

constraint

Name of the constraint you want to control

Type string, default “”

mode

Type enum in ['RUN', 'ENABLE', 'DISABLE', 'SETTARGET', 'SETWEIGHT'], default 'RUN'

secondary_target

Set this object as the secondary target of the constraint (only IK polar target at the moment)

Type Object

target

Set this object as the target of the constraint

Type Object

weight

Set weight of this constraint

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

2.4.26 ArmatureBones(bpy_struct)

base class — bpy_struct

class bpy.types.**ArmatureBones** (*bpy_struct*)

Collection of armature bones

active

Armatures active bone

Type Bone

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Armature.bones`

2.4.27 ArmatureEditBones(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ArmatureEditBones` (`bpy_struct`)

Collection of armature edit bones

active

Armatures active edit bone

Type `EditBone`

new (`name`)

Add a new bone.

Parameters `name` (`string`) – New name for the bone

Returns Newly created edit bone

Return type `EditBone`

remove (`bone`)

Remove an existing bone from the armature

Parameters `bone` (`EditBone`, (never None)) – EditBone to remove

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.edit_bones

2.4.28 ArmatureModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ArmatureModifier (Modifier)
Armature deformation modifier

invert_vertex_group
Invert vertex group influence
Type boolean, default False

object
Armature object to deform with
Type Object

use_bone_envelopes
Binds Bone envelope to armature modifier
Type boolean, default False

use_deform_preserve_volume
Deform rotation interpolation with quaternions
Type boolean, default False

use_multi_modifier
Use same input as previous modifier, and mix results using overall vgroup
Type boolean, default False

use_vertex_groups
Binds vertex group to armature modifier
Type boolean, default False

vertex_group
Name of Vertex Group which determines influence of modifier per point
Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.29 ArmatureSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.ArmatureSensor (Sensor)

Sensor to detect values and changes in values of IK solver

bone

Identify the bone to check value from

Type string, default “”

constraint

Identify the bone constraint to check value from

Type string, default “”

test_type

Type of value and test

Type enum in ['STATECHG', 'LINERRORBELOW', 'LINERRORABOVE', 'ROTERROR-BELOW', 'ROTERRORABOVE'], default 'STATECHG'

value

Specify value to be used in comparison

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.30 ArrayModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ArrayModifier(*Modifier*)

Array duplication modifier

constant_offset_displace

Value for the distance between arrayed items

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

count

Number of duplicates to make

Type int in [1, inf], default 0

curve

Curve object to fit array length to

Type [Object](#)

end_cap

Mesh object to use as an end cap

Type [Object](#)

fit_length

Length to fit array within

Type float in [0, inf], default 0.0

fit_type

Array length calculation method

Type enum in ['FIXED_COUNT', 'FIT_LENGTH', 'FIT_CURVE'], default 'FIXED_COUNT'

merge_threshold

Limit below which to merge vertices

Type float in [0, inf], default 0.0

offset_object

Uses the location and rotation of another object to determine the distance and rotational change between arrayed items

Type [Object](#)

relative_offset_displace

The size of the geometry will determine the distance between arrayed items

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

start_cap

Mesh object to use as a start cap

Type [Object](#)

use_constant_offset

Add a constant offset

Type boolean, default False

use_merge_vertices

Merge vertices in adjacent duplicates

Type boolean, default False

use_merge_vertices_cap

Merge vertices in first and last duplicates

Type boolean, default False

use_object_offset

Add another object's transformation to the total offset

Type boolean, default False

use_relative_offset

Add an offset relative to the object's bounding box

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.31 BackgroundImage(bpy_struct)

base class — bpy_struct

class bpy.types.BackgroundImage (bpy_struct)

Image and settings for display in the 3d View background

image

Image displayed and edited in this space

Type Image

image_user

Parameters defining which layer, pass and frame of the image is displayed

Type ImageUser, (readonly, never None)

offset_x

Offsets image horizontally from the world origin

Type float in [-inf, inf], default 0.0

offset_y

Offsets image vertically from the world origin

Type float in [-inf, inf], default 0.0

opacity

Image opacity to blend the image against the background color

Type float in [0, 1], default 0.0

show_expanded

Show the expanded in the user interface

Type boolean, default False

size

Scaling factor for the background image

Type float in [0, inf], default 0.0

view_axis

The axis to display the image on

Type enum in ['LEFT', 'RIGHT', 'BACK', 'FRONT', 'BOTTOM', 'TOP', 'ALL', 'CAMERA'], default 'ALL'

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SpaceView3D.background_images`

2.4.32 BevelModifier(Modifier)

base classes — `bpy_struct, Modifier`

```
class bpy.types.BevelModifier(Modifier)
    Bevel modifier to make edges and vertices more rounded

    angle_limit
        Angle above which to bevel edges
        Type float in [0, 3.14159], default 0.0

    edge_weight_method
        What edge weight to use for weighting a vertex
        Type enum in ['AVERAGE', 'SHARPEST', 'LARGEST'], default 'AVERAGE'

    limit_method
        Type enum in ['NONE', 'ANGLE', 'WEIGHT'], default 'NONE'

    use_only_vertices
        Bevel verts/corners, not edges
        Type boolean, default False

    width
        Bevel value/amount
        Type float in [0, inf], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.33 BezierSplinePoint(bpy_struct)

base class — `bpy_struct`

class `bpy.types.BezierSplinePoint` (*bpy_struct*)

Bezier curve point with two handles

co

Coordinates of the control point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_left

Coordinates of the first handle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_left_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

handle_right

Coordinates of the second handle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_right_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

hide

Visibility status

Type boolean, default False

radius

Radius for bevelling

Type float in [0, inf], default 0.0

select_control_point

Control point selection status

Type boolean, default False

select_left_handle

Handle 1 selection status

Type boolean, default False

select_right_handle

Handle 2 selection status

Type boolean, default False

tilt

Tilt in 3D View

Type float in [-inf, inf], default 0.0

weight

Softbody goal weight

Type float in [0.01, 100], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.bezier_points

2.4.34 BlendData(bpy_struct)

base class — bpy_struct

class bpy.types.BlendData (bpy_struct)

Main data structure representing a .blend file and all its datablocks

actions

Action datablocks.

Type BlendDataActions bpy_prop_collection of Action, (readonly)

armatures

Armature datablocks.

Type BlendDataArmatures bpy_prop_collection of Armature, (readonly)

brushes

Brush datablocks.

Type BlendDataBrushes bpy_prop_collection of Brush, (readonly)

cameras

Camera datablocks.

Type BlendDataCameras bpy_prop_collection of Camera, (readonly)

curves

Curve datablocks.

Type BlendDataCurves bpy_prop_collection of [Curve](#), (readonly)

filepath
Path to the .blend file

Type string, default "", (readonly)

fonts
Vector font datablocks.

Type BlendDataFonts bpy_prop_collection of [VectorFont](#), (readonly)

grease_pencil
Grease Pencil datablocks.

Type BlendDataGreasePencils bpy_prop_collection of [GreasePencil](#), (readonly)

groups
Group datablocks.

Type BlendDataGroups bpy_prop_collection of [Group](#), (readonly)

images
Image datablocks.

Type BlendDataImages bpy_prop_collection of [Image](#), (readonly)

is_dirty
Have recent edits been saved to disk

Type boolean, default False, (readonly)

is_saved
Has the current session been saved to disk as a .blend file

Type boolean, default False, (readonly)

lamps
Lamp datablocks.

Type BlendDataLamps bpy_prop_collection of [Lamp](#), (readonly)

lattices
Lattice datablocks.

Type BlendDataLattices bpy_prop_collection of [Lattice](#), (readonly)

libraries
Library datablocks.

Type BlendDataLibraries bpy_prop_collection of [Library](#), (readonly)

materials
Material datablocks.

Type BlendDataMaterials bpy_prop_collection of [Material](#), (readonly)

meshes
Mesh datablocks.

Type BlendDataMeshes bpy_prop_collection of [Mesh](#), (readonly)

metaballs
Metaball datablocks.

Type BlendDataMetaBalls bpy_prop_collection of [MetaBall](#), (readonly)

node_groups

Node group datablocks.

Type `BlendDataNodeTrees bpy_prop_collection of NodeTree, (readonly)`

objects

Object datablocks.

Type `BlendDataObjects bpy_prop_collection of Object, (readonly)`

particles

Particle datablocks.

Type `BlendDataParticles bpy_prop_collection of ParticleSettings, (readonly)`

scenes

Scene datablocks.

Type `BlendDataScenes bpy_prop_collection of Scene, (readonly)`

screens

Screen datablocks.

Type `BlendDataScreens bpy_prop_collection of Screen, (readonly)`

scripts

Script datablocks (DEPRECATED).

Type `bpy_prop_collection of ID, (readonly)`

shape_keys

Shape Key datablocks.

Type `bpy_prop_collection of Key, (readonly)`

sounds

Sound datablocks.

Type `BlendDataSounds bpy_prop_collection of Sound, (readonly)`

texts

Text datablocks.

Type `BlendDataTexts bpy_prop_collection of Text, (readonly)`

textures

Texture datablocks.

Type `BlendDataTextures bpy_prop_collection of Texture, (readonly)`

window_managers

Window manager datablocks.

Type `BlendDataWindowManagers bpy_prop_collection of WindowManager, (readonly)`

worlds

World datablocks.

Type `BlendDataWorlds bpy_prop_collection of World, (readonly)`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Context.blend_data`

2.4.35 BlendDataActions(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataActions` (`bpy_struct`)

Collection of actions

new (`name`)

Add a new action to the main database

Parameters `name` (`string`) – New name for the datablock.

Returns New action datablock.

Return type `Action`

remove (`action`)

Remove a action from the current blendfile.

Parameters `action` (`Action`, (never None)) – Action to remove.

tag (`value`)

tag

Parameters `value` (`boolean`) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.actions

2.4.36 BlendDataArmatures(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataArmatures** (*bpy_struct*)

Collection of armatures

new (*name*)

Add a new armature to the main database

Parameters *name* (*string*) – New name for the datablock.

Returns New armature datablock.

Return type *Armature*

remove (*armature*)

Remove a armature from the current blendfile.

Parameters *armature* (*Armature*, (never None)) – Armature to remove.

tag (*value*)

tag

Parameters *value* (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.armatures

2.4.37 BlendDataBrushes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataBrushes** (*bpy_struct*)

Collection of brushes

new (*name*)

Add a new brush to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New brush datablock.

Return type **Brush**

remove (*brush*)

Remove a brush from the current blendfile.

Parameters **brush** (*Brush*, (never None)) – Brush to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.brushes

2.4.38 BlendDataCameras(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataCameras** (*bpy_struct*)
Collection of cameras

new (*name*)

Add a new camera to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New camera datablock.

Return type Camera

remove (*camera*)

Remove a camera from the current blendfile.

Parameters **camera** (Camera, (never None)) – Camera to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.cameras

2.4.39 BlendDataCurves(bpy_struct)

base class — bpy_struct

class bpy.types.BlendDataCurves (bpy_struct)

Collection of curves

new (name, type)

Add a new curve to the main database

Parameters

- **name** (string) – New name for the datablock.
- **type** (enum in ['CURVE', 'SURFACE', 'FONT']) – Type, The type of curve to add

Returns New curve datablock.

Return type Curve

remove (curve)

Remove a curve from the current blendfile.

Parameters curve (Curve, (never None)) – Curve to remove.

tag (value)

tag

Parameters value (boolean) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.curves

2.4.40 BlendDataFonts(bpy_struct)

base class — bpy_struct

class bpy.types.BlendDataFonts (*bpy_struct*)

Collection of fonts

load (*filepath*)

Load a new font into the main database

Parameters *filepath* (*string*) – path of the font to load.

Returns New font datablock.

Return type VectorFont

remove (*vfont*)

Remove a font from the current blendfile.

Parameters *vfont* (*VectorFont*, (never None)) – Font to remove.

tag (*value*)

tag

Parameters *value* (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.fonts

2.4.41 BlendDataGreasePencils(bpy_struct)

base class — bpy_struct

class bpy.types.BlendDataGreasePencils (bpy_struct)
Collection of grease pencils

tag (value)
tag

Parameters **value (boolean)** – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.grease_pencil

2.4.42 BlendDataGroups(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataGroups** (*bpy_struct*)

Collection of groups

new (*name*)

Add a new group to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New group datablock.

Return type [Group](#)

remove (*group*)

Remove a group from the current blendfile.

Parameters **group** ([Group](#), (never None)) – Group to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.groups`

2.4.43 BlendDataImages(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataImages` (`bpy_struct`)

Collection of images

new (`name, width, height, alpha=False, float_buffer=False`)

Add a new image to the main database

Parameters

- **name** (`string`) – New name for the datablock.
- **width** (`int in [1, inf]`) – Width of the image.
- **height** (`int in [1, inf]`) – Height of the image.
- **alpha** (`boolean, (optional)`) – Alpha, Use alpha channel
- **float_buffer** (`boolean, (optional)`) – Float Buffer, Create an image with floating point color

Returns New image datablock.

Return type `Image`

load (`filepath`)

Load a new image into the main database

Parameters `filepath` (`string`) – path of the file to load.

Returns New image datablock.

Return type `Image`

remove (`image`)

Remove an image from the current blendfile.

Parameters `image` (`Image`, (never None)) – Image to remove.

tag (`value`)

tag

Parameters `value` (`boolean`) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.images

2.4.44 BlendDataLamps(bpy_struct)

base class — bpy_struct

class bpy.types.BlendDataLamps (bpy_struct)

Collection of lamps

new (name, type)

Add a new lamp to the main database

Parameters

- **name** (string) – New name for the datablock.
- **type** (enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA']) – Type, The type of texture to add

Returns New lamp datablock.

Return type Lamp

remove (lamp)

Remove a lamp from the current blendfile.

Parameters lamp (Lamp, (never None)) – Lamp to remove.

tag (value)

tag

Parameters `value (boolean)` – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.lamps`

2.4.45 BlendDataLattices(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataLattices (bpy_struct)`

Collection of lattices

new (`name`)

Add a new lattice to the main database

Parameters `name (string)` – New name for the datablock.

Returns New lattices datablock.

Return type `Lattice`

remove (`lattice`)

Remove a lattice from the current blendfile.

Parameters `lattice (Lattice, (never None))` – Lattice to remove.

tag (`value`)

tag

Parameters `value (boolean)` – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.lattices

2.4.46 BlendDataLibraries(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataLibraries** (*bpy_struct*)

Collection of libraries

tag (*value*)
tag

Parameters **value** (*boolean*) – Value

load (*filepath*, *link=False*, *relative=False*)

Returns a context manager which exposes 2 library objects on entering. Each object has attributes matching bpy.data which are lists of strings to be linked.

Parameters

- **filepath** (*string*) – The path to a blend file.
- **link** (*bool*) – When False reference to the original file is lost.
- **relative** (*bool*) – When True the path is stored relative to the open blend file.

import bpy

```
filepath = "//link_library.blend"
```

```
# load a single scene we know the name of.
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.scenes = ["Scene"]

# load all meshes
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.meshes = data_from.meshes

# link all objects starting with 'A'
with bpy.data.libraries.load(filepath, link=True) as (data_from, data_to):
    data_to.objects = [name for name in data_from.objects if name.startswith("A")]

# append everything
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    for attr in dir(data_to):
        setattr(data_to, attr, getattr(data_from, attr))

# the 'data_to' variables lists are
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.scenes = ["Scene"]

# the loaded objects can be accessed from 'data_to' outside of the context
# since loading the data replaces the strings for the datablocks or None
# if the datablock could not be loaded.
with bpy.data.libraries.load(filepath) as (data_from, data_to):
    data_to.meshes = data_from.meshes
    # now operate directly on the loaded data
    for mesh in data_to.meshes:
        if mesh is not None:
            print(mesh.name)
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.libraries`

2.4.47 BlendDataMaterials(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataMaterials` (`bpy_struct`)

Collection of materials

new (`name`)

Add a new material to the main database

Parameters `name` (`string`) – New name for the datablock.

Returns New material datablock.

Return type `Material`

remove (`material`)

Remove a material from the current blendfile.

Parameters `material` (`Material`, (never None)) – Material to remove.

tag (`value`)

tag

Parameters `value` (`boolean`) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.materials

2.4.48 BlendDataMeshes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataMeshes** (*bpy_struct*)

Collection of meshes

new (*name*)

Add a new mesh to the main database

Parameters *name* (*string*) – New name for the datablock.

Returns New mesh datablock.

Return type Mesh

remove (*mesh*)

Remove a mesh from the current blendfile.

Parameters *mesh* (Mesh, (never None)) – Mesh to remove.

tag (*value*)

tag

Parameters *value* (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.meshes

2.4.49 BlendDataMetaBalls(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataMetaBalls** (*bpy_struct*)

Collection of metaballs

new (*name*)

Add a new metaball to the main database

Parameters **name** (*string*) – New name for the datablock.

Returns New metaball datablock.

Return type MetaBall

remove (*metaball*)

Remove a metaball from the current blendfile.

Parameters **metaball** (MetaBall, (never None)) – MetaBall to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.metaballs

2.4.50 BlendDataNodeTrees(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataNodeTrees** (*bpy_struct*)

Collection of node trees

new (*name*, *type*)

Add a new node tree to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in* [‘SHADER’, ‘COMPOSITE’, ‘TEXTURE’]) – Type, The type of node_group to add

Returns New node tree datablock.

Return type NodeTree

remove (*tree*)

Remove a node tree from the current blendfile.

Parameters **tree** (NodeTree, (never None)) – Node tree to remove.

tag (*value*)

tag

Parameters **value** (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- `bpy_struct.values`

References

- `BlendData.node_groups`

2.4.51 BlendDataObjects(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.BlendDataObjects (bpy_struct)`

Collection of objects

`new (name, object_data)`

Add a new object to the main database

Parameters

- `name (string)` – New name for the datablock.
- `object_data (ID)` – Object data or None for an empty object.

`Returns` New object datablock.

`Return type` `Object`

`remove (object)`

Remove a object from the current blendfile.

`Parameters` `object (Object, (never None))` – Object to remove.

`tag (value)`

tag

`Parameters` `value (boolean)` – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.objects

2.4.52 BlendDataParticles(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataParticles** (*bpy_struct*)

Collection of particle settings

new (*name*)

Add a new particle settings instance to the main database

Parameters *name* (*string*) – New name for the datablock.

Returns New particle settings datablock.

Return type ParticleSettings

remove (*particle*)

Remove a particle settings instance from the current blendfile.

Parameters *particle* (ParticleSettings, (never None)) – Particle Settings to remove.

tag (*value*)

tag

Parameters *value* (*boolean*) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.particles

2.4.53 BlendDataScenes(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataScenes** (*bpy_struct*)

Collection of scenes

new (*name*)

Add a new scene to the main database

Parameters *name* (*string*) – New name for the datablock.

Returns New scene datablock.

Return type Scene

remove (*scene*)

Remove a scene from the current blendfile.

Parameters *scene* (Scene, (never None)) – Scene to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.scenes

2.4.54 BlendDataScreens(bpy_struct)

base class — `bpy_struct`

class bpy.types.BlendDataScreens (bpy_struct)
Collection of screens

tag (value)
tag

Parameters `value (boolean)` – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.screens`

2.4.55 BlendDataSounds(bpy_struct)

base class — `bpy_struct`

class bpy.types.BlendDataSounds (bpy_struct)
Collection of sounds

tag (value)
tag

Parameters `value (boolean)` – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.sounds

2.4.56 BlendDataTexts(bpy_struct)

base class — bpy_struct

class bpy.types.**BlendDataTexts** (*bpy_struct*)

Collection of texts

new (*name*)

Add a new text to the main database

Parameters *name* (*string*) – New name for the datablock.

Returns New text datablock.

Return type *Text*

remove (*text*)

Remove a text from the current blendfile.

Parameters *text* (*Text*, (never None)) – Text to remove.

load (*filepath*)

Add a new text to the main database from a file

Parameters *filepath* (*string*) – path for the datablock.

Returns New text datablock.

Return type *Text*

tag (*value*)
tag

Parameters *value* (boolean) – Value

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlendData.texts

2.4.57 BlendDataTextures(bpy_struct)

base class — bpy_struct
class bpy.types.**BlendDataTextures** (*bpy_struct*)
Collection of groups
new (*name*, *type*)
Add a new texture to the main database

Parameters

- **name** (*string*) – New name for the datablock.
- **type** (*enum in* ['NONE', 'BLEND', 'CLOUDS', 'DISTORTED_NOISE', 'ENVIRONMENT_MAP', 'IMAGE', 'MAGIC', 'MARBLE', 'MUSGRAVE', 'NOISE', 'POINT_DENSITY', 'STUCCI', 'VORONOI', 'VOXEL_DATA', 'WOOD']) – Type, The type of texture to add

Returns New texture datablock.

Return type Texture

remove (*texture*)

Remove a texture from the current blendfile.

Parameters **texture** (`Texture`, (never None)) – Texture to remove.

tag (*value*)

tag

Parameters **value** (`boolean`) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.textures`

2.4.58 BlendDataWindowManagers(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataWindowManagers` (*bpy_struct*)

Collection of window managers

tag (*value*)

tag

Parameters **value** (`boolean`) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.window_managers`

2.4.59 BlendDataWorlds(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BlendDataWorlds` (`bpy_struct`)
Collection of worlds

new (`name`)

Add a new world to the main database

Parameters `name` (`string`) – New name for the datablock.

Returns New world datablock.

Return type `World`

remove (`world`)

Remove a world from the current blendfile.

Parameters `world` (`World`, (never None)) – World to remove.

tag (`value`)

tag

Parameters `value` (`boolean`) – Value

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BlendData.worlds`

2.4.60 BlendTexture(Texture)

base classes — `bpy_struct, ID, Texture`

class bpy.types.BlendTexture (Texture)

Procedural color blending texture

progression

Sets the style of the color blending

Type enum in ['LINEAR', 'QUADRATIC', 'EASING', 'DIAGONAL', 'SPHERICAL', 'QUADRATIC_SPHERE', 'RADIAL'], default 'LINEAR'

use_flip_axis

Flips the texture's X and Y axis

Type enum in ['HORIZONTAL', 'VERTICAL'], default 'HORIZONTAL'

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`

- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.61 BlenderRNA(bpy_struct)

base class — `bpy_struct`

class `bpy.types.BlenderRNA(bpy_struct)`
Blender RNA structure definitions

structs

Type `bpy_prop_collection of Struct, (readonly)`

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.62 BoidRule(bpy_struct)

base class — bpy_struct
subclasses — BoidRuleAvoidCollision, BoidRuleAverageSpeed, BoidRuleAvoid, BoidRuleFight, BoidRuleFollowLeader, BoidRuleGoal
class bpy.types.BoidRule (bpy_struct)

name

Boid rule name

Type string, default “”

type

Type enum in ['GOAL', 'AVOID', 'AVOID_COLLISION', 'SEPARATE', 'FLOCK', 'FOLLOW_LEADER', 'AVERAGE_SPEED', 'FIGHT'], default 'GOAL', (readonly)

use_in_air

Use rule when boid is flying

Type boolean, default False

use_on_land

Use rule when boid is on land

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BoidSettings.active_boid_state`
- `BoidState.active_boid_rule`
- `BoidState.rules`

2.4.63 BoidRuleAverageSpeed(BoidRule)

base classes — `bpy_struct, BoidRule`

`class bpy.types.BoidRuleAverageSpeed (BoidRule)`

level

How much velocity's z-component is kept constant

Type float in [0, 1], default 0.0

speed

Percentage of maximum speed

Type float in [0, 1], default 0.0

wander

How fast velocity's direction is randomized

Type float in [0, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `BoidRule.name`
- `BoidRule.use_in_air`
- `BoidRule.use_on_land`
- `BoidRule.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.64 BoidRuleAvoid(BoidRule)

base classes — `bpy_struct, BoidRule`

`class bpy.types.BoidRuleAvoid(BoidRule)`

`fear_factor`

Avoid object if danger from it is above this threshold

Type float in [0, 100], default 0.0

`object`

Object to avoid

Type `Object`

`use_predict`

Predict target movement

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `BoidRule.name`
- `BoidRule.use_in_air`
- `BoidRule.use_on_land`
- `BoidRule.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.65 BoidRuleAvoidCollision(BoidRule)

base classes — `bpy_struct, BoidRule`

`class bpy.types.BoidRuleAvoidCollision (BoidRule)`

`look_ahead`

Time to look ahead in seconds

Type float in [0, 100], default 0.0

`use_avoid`

Avoid collision with other boids

Type boolean, default False

`use_avoid_collision`

Avoid collision with deflector objects

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `BoidRule.name`
- `BoidRule.use_in_air`
- `BoidRule.use_on_land`
- `BoidRule.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.66 BoidRuleFight(BoidRule)

base classes — bpy_struct, BoidRule

class bpy.types.BoidRuleFight (*BoidRule*)

distance
Attack boids at max this distance
Type float in [0, 100], default 0.0

flee_distance
Flee to this distance
Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- BoidRule.name
- BoidRule.use_in_air
- BoidRule.use_on_land
- BoidRule.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.67 BoidRuleFollowLeader(BoidRule)

base classes — `bpy_struct`, `BoidRule`

class `bpy.types.BoidRuleFollowLeader` (`BoidRule`)

distance
Distance behind leader to follow
Type float in [0, 100], default 0.0

object
Follow this object instead of a boid
Type `Object`

queue_count
How many boids in a line
Type int in [0, 100], default 0

use_line
Follow leader in a line
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `BoidRule.name`
- `BoidRule.use_in_air`
- `BoidRule.use_on_land`
- `BoidRule.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.68 BoidRuleGoal(BoidRule)

base classes — `bpy_struct`, `BoidRule`

class `bpy.types.BoidRuleGoal` (`BoidRule`)

object
Goal object

Type `Object`

use_predict
Predict target movement

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `BoidRule.name`
- `BoidRule.use_in_air`
- `BoidRule.use_on_land`
- `BoidRule.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.69 BoidSettings(bpy_struct)

base class — `bpy_struct`

class `bpy.types.BoidSettings` (`bpy_struct`)

Settings for boid physics

accuracy
Accuracy of attack

Type float in [0, 1], default 0.0

active_boid_state
Type `BoidRule`, (readonly)

active_boid_state_index
Type int in [0, inf], default 0

aggression
Boid will fight this times stronger enemy
Type float in [0, 100], default 0.0

air_acc_max
Maximum acceleration in air (relative to maximum speed)
Type float in [0, 1], default 0.0

air_ave_max
Maximum angular velocity in air (relative to 180 degrees)
Type float in [0, 1], default 0.0

air_personal_space
Radius of boids personal space in air (% of particle size)
Type float in [0, 10], default 0.0

air_speed_max
Maximum speed in air
Type float in [0, 100], default 0.0

air_speed_min
Minimum speed in air (relative to maximum speed)
Type float in [0, 1], default 0.0

bank
Amount of rotation around velocity vector on turns
Type float in [0, 2], default 0.0

health
Initial boid health when born
Type float in [0, 100], default 0.0

height
Boid height relative to particle size
Type float in [0, 2], default 0.0

land_acc_max
Maximum acceleration on land (relative to maximum speed)
Type float in [0, 1], default 0.0

land_ave_max
Maximum angular velocity on land (relative to 180 degrees)
Type float in [0, 1], default 0.0

land_jump_speed
Maximum speed for jumping
Type float in [0, 100], default 0.0

land_personal_space

Radius of boids personal space on land (% of particle size)

Type float in [0, 10], default 0.0

land_smooth

How smoothly the boids land

Type float in [0, 10], default 0.0

land_speed_max

Maximum speed on land

Type float in [0, 100], default 0.0

land_stick_force

How strong a force must be to start effecting a boid on land

Type float in [0, 1000], default 0.0

pitch

Amount of rotation around side vector

Type float in [0, 2], default 0.0

range

The maximum distance from which a boid can attack

Type float in [0, 100], default 0.0

states

Type bpy_prop_collection of `BoidState`, (readonly)

strength

Maximum caused damage on attack per second

Type float in [0, 100], default 0.0

use_climb

Allow boids to climb goal objects

Type boolean, default False

use_flight

Allow boids to move in air

Type boolean, default False

use_land

Allow boids to move on land

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ParticleSettings.boids`

2.4.70 BoidState(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BoidState` (`bpy_struct`)

Boid state for boid physics

active_boid_rule

Type `BoidRule`, (readonly)

active_boid_rule_index

Type int in [0, inf], default 0

falloff

Type float in [0, 10], default 0.0

name

Boid state name

Type string, default “”

rule_fuzzy

Type float in [0, 1], default 0.0

rules

Type `bpy_prop_collection` of `BoidRule`, (readonly)

ruleset_type

How the rules in the list are evaluated

Type enum in ['FUZZY', 'RANDOM', 'AVERAGE'], default 'FUZZY'

volume

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BoidSettings.states

2.4.71 Bone(bpy_struct)

base class — bpy_struct

class bpy.types.Bone (bpy_struct)
Bone in an Armature datablock

bbone_in
Length of first Bezier Handle (for B-Bones only)
Type float in [0, 2], default 0.0

bbone_out
Length of second Bezier Handle (for B-Bones only)
Type float in [0, 2], default 0.0

bbone_segments
Number of subdivisions of bone (for B-Bones only)
Type int in [1, 32], default 0

bbone_x
B-Bone X size
Type float in [0, 1000], default 0.0

bbone_z
B-Bone Z size

Type float in [0, 1000], default 0.0

children
Bones which are children of this bone

Type bpy_prop_collection of Bone, (readonly)

envelope_distance
Bone deformation distance (for Envelope deform only)

Type float in [0, 1000], default 0.0

envelope_weight
Bone deformation weight (for Envelope deform only)

Type float in [0, 1000], default 0.0

head
Location of head end of the bone relative to its parent

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_local
Location of head end of the bone relative to armature

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_radius
Radius of head of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

hide
Bone is not visible when it is not in Edit Mode (i.e. in Object or Pose Modes)

Type boolean, default False

hide_select
Bone is able to be selected

Type boolean, default False

layers
Layers bone exists in

Type boolean array of 32 items, default (False, False, False)

matrix
3x3 bone matrix

Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_local
4x4 bone matrix relative to armature

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

name

Type string, default “”

parent
Parent bone (in same Armature)

Type `Bone`, (readonly)

select

Type boolean, default False

select_head

Type boolean, default False

select_tail

Type boolean, default False

show_wire

Bone is always drawn as Wireframe regardless of viewport draw mode. Useful for non-obstructive custom bone shapes

Type boolean, default False

tail

Location of tail end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_local

Location of tail end of the bone relative to armature

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_radius

Radius of tail of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

use_connect

When bone has a parent, bone's head is struck to the parent's tail

Type boolean, default False, (readonly)

use_cyclic_offset

When bone doesn't have a parent, it receives cyclic offset effects

Type boolean, default False

use_deform

Bone does not deform any geometry

Type boolean, default False

use_envelope_multiply

When deforming bone, multiply effects of Vertex Group weights with Envelope influence

Type boolean, default False

use_inherit_rotation

Bone inherits rotation or scale from parent bone

Type boolean, default False

use_inherit_scale

Bone inherits scaling from parent bone

Type boolean, default False

use_local_location

Bone location is set in local space

Type boolean, default False

basename

The name of this bone before any ‘.’ character (readonly)

center

The midpoint between the head and the tail. (readonly)

children

A list of all the bones children. (readonly)

children_recursive

a list of all children from this bone. (readonly)

children_recursive_basename

Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned. (readonly)

length

The distance from head to tail, when set the head is moved to fit the length.

parent_recursive

A list of parents, starting with the immediate parent (readonly)

vector

The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis

Vector pointing down the x-axis of the bone. (readonly)

y_axis

Vector pointing down the x-axis of the bone. (readonly)

z_axis

Vector pointing down the x-axis of the bone. (readonly)

evaluate_envelope (point)

Calculate bone envelope at given point.

Parameters *point* (*float array of 3 items in [-inf, inf]*) – Point, Position in 3d space to evaluate

Returns Factor, Envelope factor

Return type float in [-inf, inf]

parent_index (parent_test)

The same as ‘bone in other_bone.parent_recursive’ but saved generating a list.

translate (vec)

Utility function to add *vec* to the head and tail of this bone.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Armature.bones`
- `ArmatureBones.active`
- `Bone.children`
- `Bone.parent`
- `PoseBone.bone`

2.4.72 BoneGroup(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.BoneGroup` (`bpy_struct`)

Groups of Pose Channels (Bones)

color_set

Custom color set to use

Type enum in ['DEFAULT', 'THEME01', 'THEME02', 'THEME03', 'THEME04', 'THEME05', 'THEME06', 'THEME07', 'THEME08', 'THEME09', 'THEME10', 'THEME11', 'THEME12', 'THEME13', 'THEME14', 'THEME15', 'THEME16', 'THEME17', 'THEME18', 'THEME19', 'THEME20', 'CUSTOM'], default 'DEFAULT'

colors

Copy of the colors associated with the group's color set

Type `ThemeBoneColorSet`, (readonly, never None)

name

Type string, default ""

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BoneGroups.active
- Pose.bone_groups
- PoseBone.bone_group

2.4.73 BoneGroups(bpy_struct)

base class — bpy_struct

class bpy.types.BoneGroups (*bpy_struct*)

Collection of bone groups

active

Active bone group for this pose

Type BoneGroup

active_index

Active index in bone groups array

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Pose.bone_groups

2.4.74 BooleanModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.BooleanModifier (Modifier)
Boolean operations modifier

object
Mesh object to use for Boolean operation

Type Object

operation

Type enum in ['INTERSECT', 'UNION', 'DIFFERENCE'], default 'INTERSECT'

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.75 BooleanProperty(Property)

base classes — `bpy_struct, Property`

class bpy.types.BooleanProperty(*Property*)

RNA boolean definition

array_length

Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default

Default value for this number

Type boolean, default False, (readonly)

default_array

Default value for this array

Type boolean array of 3 items, default (False, False, False), (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Property.name`
- `Property.srna`
- `Property.description`
- `Property.is_enum_flag`
- `Property.is_hidden`
- `Property.identifier`
- `Property.is_never_none`
- `Property.is_readonly`
- `Property.is_registered`
- `Property.is_registered_optional`
- `Property.is_required`
- `Property.is_output`
- `Property.is_runtime`
- `Property.is_skip_save`
- `Property.subtype`
- `Property.type`
- `Property.unit`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.76 Brush(ID)

base classes — `bpy_struct, ID`

class bpy.types.Brush (ID)

Brush datablock for storing brush settings for painting and sculpting

auto_smooth_factor

Amount of smoothing to automatically apply to each stroke

Type float in [0, 1], default 0.0

blend

Brush blending mode

Type enum in ['MIX', 'ADD', 'SUB', 'MUL', 'LIGHTEN', 'DARKEN', 'ERASE_ALPHA', 'ADD_ALPHA'], default 'MIX'

clone_alpha

Opacity of clone image display

Type float in [0, 1], default 0.0

clone_image

Image for clone tool

Type Image

clone_offset

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

color

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

crease_pinch_factor

How much the crease brush pinches

Type float in [0, 1], default 0.666667

cursor_color_add

Color of cursor when adding

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor_color_subtract

Color of cursor when subtracting

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

curve

Editable falloff curve

Type `CurveMapping`, (readonly, never None)

direction

Type enum in ['ADD', 'SUBTRACT'], default 'ADD'

height

Affectable height of brush (layer height for layer tool, i.e.)

Type float in [0, 1], default 0.5

icon_filepath

File path to brush icon

Type string, default ""

image_tool

Type enum in ['DRAW', 'SOFTEN', 'SMEAR', 'CLONE'], default 'DRAW'

jitter

Jitter the position of the brush while painting

Type float in [0, 1], default 0.0

normal_weight

How much grab will pull vertexes out of surface during a grab

Type float in [0, 1], default 0.0

plane_offset

Adjusts plane on which the brush acts towards or away from the object surface

Type float in [-2, 2], default 0.0

plane_trim

If a vertex is further from offset plane than this then it is not affected

Type float in [0, 1], default 0.5

rate

Interval between paints for Airbrush

Type float in [0.0001, 10000], default 0.0

sculpt_plane

Type enum in ['AREA', 'VIEW', 'X', 'Y', 'Z'], default 'AREA'

sculpt_tool

Type enum in ['BLOB', 'CLAY', 'CREASE', 'DRAW', 'FILL', 'FLATTEN', 'GRAB', 'INFLATE', 'LAYER', 'NUUDGE', 'PINCH', 'ROTATE', 'SCRAPE', 'SMOOTH', 'SNAKE_HOOK', 'THUMB'], default 'BLOB'

size

Radius of the brush in pixels

Type int in [1, 2000], default 0

smooth_stroke_factor

Higher values give a smoother stroke

Type float in [0.5, 0.99], default 0.0

smooth_stroke_radius

Minimum distance from last point before stroke continues

Type int in [10, 200], default 0

spacing

Spacing between brush daubs as a percentage of brush diameter

Type int in [1, 1000], default 0

strength

How powerful the effect of the brush is when applied

Type float in [0, 10], default 0.5

stroke_method

Type enum in ['DOTS', 'DRAG_DOT', 'SPACE', 'ANCHORED', 'AIRBRUSH'], default 'DOTS'

texture

Type Texture

texture_angle_source_no_random

Type enum in ['USER', 'RAKE'], default 'USER'

texture_angle_source_random

Type enum in ['USER', 'RAKE', 'RANDOM'], default 'USER'

texture_overlay_alpha

Type int in [1, 100], default 0

texture_sample_bias

Value added to texture samples

Type float in [-1, 1], default 0.0

texture_slot

Type BrushTextureSlot, (readonly)

unprojected_radius

Radius of brush in Blender units

Type float in [0.001, inf], default 0.0

use_accumulate

Accumulate stroke dabs on top of each other

Type boolean, default False

use_adaptive_space

Space daubs according to surface orientation instead of screen space

Type boolean, default False

use_airbrush

Keep applying paint effect while holding mouse (spray)

Type boolean, default False

use_alpha

When this is disabled, lock alpha while painting

Type boolean, default False

use_anchor
Keep the brush anchored to the initial location

Type boolean, default False

use_custom_icon
Set the brush icon from an image file

Type boolean, default False

use_edge_to_edge
Drag anchor brush from edge-to-edge

Type boolean, default False

use_fixed_texture
Keep texture origin in fixed position

Type boolean, default False

use_fronface
Brush only affects vertexes that face the viewer

Type boolean, default False

use_inverse_smooth_pressure
Lighter pressure causes more smoothing to be applied

Type boolean, default False

use_locked_size
When locked brush stays same size relative to object; when unlocked brush size is given in pixels

Type boolean, default False

use_offset_pressure
Enable tablet pressure sensitivity for offset

Type boolean, default False

use_original_normal
When locked keep using normal of surface where stroke was initiated

Type boolean, default False

use_paint_image
Use this brush in texture paint mode

Type boolean, default False

use_paint_sculpt
Use this brush in sculpt mode

Type boolean, default False

use_paint_vertex
Use this brush in vertex paint mode

Type boolean, default False

use_paint_weight
Use this brush in weight paint mode

Type boolean, default False

use_persistent

Sculpts on a persistent layer of the mesh

Type boolean, default False

use_plane_trim

Enable Plane Trim

Type boolean, default False

use_pressure_jitter

Enable tablet pressure sensitivity for jitter

Type boolean, default False

use_pressure_size

Enable tablet pressure sensitivity for size

Type boolean, default False

use_pressure_spacing

Enable tablet pressure sensitivity for spacing

Type boolean, default False

use_pressure_strength

Enable tablet pressure sensitivity for strength

Type boolean, default False

use_rake

Rotate the brush texture to match the stroke direction

Type boolean, default False

use_random_rotation

Rotate the brush texture at random

Type boolean, default False

use_restore_mesh

Allows a single dot to be carefully positioned

Type boolean, default False

use_smooth_stroke

Brush lags behind mouse and follows a smoother path

Type boolean, default False

use_space

Limit brush application to the distance specified by spacing

Type boolean, default False

use_space_atten

Automatically adjusts strength to give consistent results for different spacings

Type boolean, default False

use_texture_overlay

Show texture in viewport

Type boolean, default False

use_wrap

Enable torus wrapping while painting

Type boolean, default False

vertex_tool

Type enum in ['MIX', 'ADD', 'SUB', 'MUL', 'BLUR', 'LIGHTEN', 'DARKEN'], default 'MIX'

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.brushes
- BlendDataBrushes.new
- BlendDataBrushes.remove
- Paint.brush

2.4.77 BrushTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

```
class bpy.types.BrushTextureSlot (TextureSlot)
    Texture slot for textures in a Brush datablock

    angle
        Defines brush texture rotation
        Type float in [0, 6.28319], default 0.0

    map_mode
        Type enum in ['FIXED', 'TILED', '3D'], default 'FIXED'
```

Inherited Properties

- `bpy_struct.id_data`
- `TextureSlot.name`
- `TextureSlot.blend_type`
- `TextureSlot.color`
- `TextureSlot.default_value`
- `TextureSlot.invert`
- `TextureSlot.offset`
- `TextureSlot.output_node`
- `TextureSlot.use_rgb_to_intensity`
- `TextureSlot.scale`
- `TextureSlot.use_stencil`
- `TextureSlot.texture`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Brush.texture_slot`

2.4.78 BuildModifier(Modifier)

base classes — `bpy_struct, Modifier`

```
class bpy.types.BuildModifier(Modifier)
    Build effect modifier

    frame_duration
        Specify the total time the build effect requires
        Type float in [1, 300000], default 0.0

    frame_start
        Specify the start frame of the effect
        Type float in [-300000, 300000], default 0.0

    seed
        Specify the seed for random if used
        Type int in [1, 300000], default 0

    use_random_order
        Randomize the faces or edges during build
        Type boolean, default False
```

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.79 Camera(ID)

base classes — `bpy_struct`, `ID`

class bpy.types.Camera (ID)

Camera datablock for storing camera settings

angle

Perspective Camera lens field of view in degrees

Type float in [0.00640536, 3.01675], default 0.0

animation_data

Animation data for this datablock

Type `AnimData`, (readonly)

clip_end

Camera far clipping distance

Type float in [1, inf], default 0.0

clip_start

Camera near clipping distance

Type float in [0.001, inf], default 0.0

dof_distance

Distance to the focus point for depth of field

Type float in [0, 5000], default 0.0

dof_object

Use this object to define the depth of field focal point

Type `Object`

draw_size

Apparent size of the Camera object in the 3D View

Type float in [0.01, 1000], default 0.0

lens

Perspective Camera lens value in millimeters

Type float in [1, 5000], default 0.0

lens_unit

Unit to edit lens in for the user interface

Type enum in ['MILLIMETERS', 'DEGREES'], default 'MILLIMETERS'

ortho_scale

Orthographic Camera scale (similar to zoom)

Type float in [0.01, 4000], default 0.0

passepourtout_alpha

Opacity (alpha) of the darkened overlay in Camera view

Type float in [0, 1], default 0.0

shift_x

Perspective Camera horizontal shift

Type float in [-10, 10], default 0.0

shift_y

Perspective Camera vertical shift

Type float in [-10, 10], default 0.0

show_guide

Draw overlay

Type enum set in {'CENTER', 'CENTER_DIAGONAL', 'THIRDS', 'GOLDEN', 'GOLDEN_TRIANGLE_A', 'GOLDEN_TRIANGLE_B', 'HARMONY_TRIANGLE_A', 'HARMONY_TRIANGLE_B'}, default {'CENTER'}

show_limits

Draw the clipping range and focus point on the camera

Type boolean, default False

show_mist

Draw a line from the Camera to indicate the mist area

Type boolean, default False

show_name

Show the active Camera's name in Camera view

Type boolean, default False

show_passepartout

Show a darkened overlay outside the image area in Camera view

Type boolean, default False

show_title_safe

Show indicators for the title safe zone in Camera view

Type boolean, default False

type

Camera types

Type enum in ['PERSP', 'ORTHO'], default 'PERSP'

use_panorama

Render the scene with a cylindrical camera for pseudo-fisheye lens effects

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.cameras
- BlendDataCameras.new
- BlendDataCameras.remove

2.4.80 CameraActuator(Actuator)

base classes — `bpy_struct, Actuator`

class `bpy.types.CameraActuator` (*Actuator*)
Actuator to ..

axis

Specify the axis the Camera will try to get behind

Type enum in ['X', 'Y'], default 'X'

damping

Specify the strength of the constraint that drive the camera behind the target

Type float in [0, 10], default 0.0

height

Type float in [-inf, inf], default 0.0

max

Type float in [-inf, inf], default 0.0

min

Type float in [-inf, inf], default 0.0

object

Look at this Object

Type `Object`

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.81 CastModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.CastModifier (Modifier)

Cast modifier to cast to other shapes

cast_type

Target object shape

Type enum in ['SPHERE', 'CYLINDER', 'CUBOID'], default 'SPHERE'

factor

Type float in [-inf, inf], default 0.0

object

Control object: if available, its location determines the center of the effect

Type Object

radius

Only deform vertices within this distance from the center of the effect (leave as 0 for infinite.)

Type float in [0, inf], default 0.0

size

Size of projection shape (leave as 0 for auto.)

Type float in [0, inf], default 0.0

use_radius_as_size

Use radius as size of projection shape (0 = auto)

Type boolean, default False

use_transform

Use object transform to control projection shape

Type boolean, default False

use_x

Type boolean, default False

use_y

Type boolean, default False

use_z

Type boolean, default False

vertex_group

Vertex group name

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- `bpy_struct.values`

2.4.82 ChannelDriverVariables(bpy_struct)

base class — `bpy_struct`

class `bpy.types.ChannelDriverVariables` (`bpy_struct`)

Collection of channel driver Variables

new()

Add a new variable for the driver.

Returns Newly created Driver Variable.

Return type `DriverVariable`

remove(variable)

Remove an existing variable from the driver.

Parameters `variable` (`DriverVariable`, (never None)) – Variable to remove from the driver.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Driver.variables`

2.4.83 ChildOfConstraint(Constraint)

base classes — `bpy_struct, Constraint`

```
class bpy.types.ChildOfConstraint (Constraint)
    Creates constraint-based parent-child relationship

    subtarget
        Type string, default ""

    target
        Target Object
        Type Object

    use_location_x
        Use X Location of Parent
        Type boolean, default False

    use_location_y
        Use Y Location of Parent
        Type boolean, default False

    use_location_z
        Use Z Location of Parent
        Type boolean, default False

    use_rotation_x
        Use X Rotation of Parent
        Type boolean, default False

    use_rotation_y
        Use Y Rotation of Parent
        Type boolean, default False

    use_rotation_z
        Use Z Rotation of Parent
        Type boolean, default False

    use_scale_x
        Use X Scale of Parent
        Type boolean, default False

    use_scale_y
        Use Y Scale of Parent
        Type boolean, default False

    use_scale_z
        Use Z Scale of Parent
        Type boolean, default False
```

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`

- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.84 ChildParticle(bpy_struct)

base class — bpy_struct
class bpy.types.ChildParticle(bpy_struct)
Child particle interpolated from simulated or edited particles

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.child_particles

2.4.85 ClampToConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.ClampToConstraint (*Constraint*)

Constrains an object's location to the nearest point along the target path

main_axis

Main axis of movement

Type enum in ['CLAMPTO_AUTO', 'CLAMPTO_X', 'CLAMPTO_Y', 'CLAMPTO_Z'], default 'CLAMPTO_AUTO'

target

Target Object

Type Object

use_cyclic

Treat curve as cyclic curve (no clamping to curve bounding box)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.86 ClothCollisionSettings(bpy_struct)

base class — `bpy_struct`

class bpy.types.ClothCollisionSettings (bpy_struct)

 Cloth simulation settings for self collision and collision with other objects

collision_quality

 How many collision iterations should be done. (higher is better quality but slower)

Type int in [1, 20], default 0

distance_min

 Minimum distance between collision objects before collision response takes in

Type float in [0.001, 1], default 0.0

distance_repel

 Maximum distance to apply repulsion force, must be greater than minimum distance

Type float in [0.001, 10], default 0.005

friction

 Friction force if a collision happened. (higher = less movement)

Type float in [0, 80], default 0.0

group

 Limit colliders to this Group

Type Group

repel_force

 Repulsion force to apply on cloth when close to colliding

Type float in [0, 20], default 1.0

self_collision_quality

 How many self collision iterations should be done. (higher is better quality but slower)

Type int in [1, 10], default 0

self_distance_min

 0.5 means no distance at all, 1.0 is maximum distance

Type float in [0.5, 1], default 0.0

self_friction

Friction/damping with self contact

Type float in [0, 80], default 0.0

use_collision

Enable collisions with other objects

Type boolean, default False

use_self_collision

Enable self collisions

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothModifier.collision_settings

2.4.87 ClothModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ClothModifier(*Modifier*)

Cloth simulation modifier

collision_settings

Type ClothCollisionSettings, (readonly, never None)

point_cache

Type `PointCache`, (readonly, never None)

settings

Type `ClothSettings`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ParticleSystem.cloth`

2.4.88 ClothSettings(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ClothSettings` (`bpy_struct`)

Cloth simulation settings for an object

air_damping

Air has normally some thickness which slows falling things down

Type float in [0, 10], default 0.0

bending_stiffness

Wrinkle coefficient. (higher = less smaller but more big wrinkles)

Type float in [0, 10000], default 0.0

bending_stiffness_max

Maximum bending stiffness value

Type float in [0, 10000], default 0.0

collider_friction

Type float in [0, 1], default 0.0

effector_weights

Type [EffectorWeights](#), (readonly)

goal_default

Default Goal (vertex target position) value, when no Vertex Group used

Type float in [0, 1], default 0.0

goal_friction

Goal (vertex target position) friction

Type float in [0, 50], default 0.0

goal_max

Goal maximum, vertex group weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_min

Goal minimum, vertex group weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_spring

Goal (vertex target position) spring stiffness

Type float in [0, 0.999], default 0.0

gravity

Gravity or external force vector

Type float array of 3 items in [-100, 100], default (0.0, 0.0, 0.0)

internal_friction

Type float in [0, 1], default 0.0

mass

Mass of cloth material

Type float in [0, 10], default 0.0

pin_stiffness

Pin (vertex target position) spring stiffness

Type float in [0, 50], default 0.0

pre_roll

Simulation starts on this frame

Type int in [0, 200], default 0

quality

Quality of the simulation in steps per frame. (higher is better quality but slower)

Type int in [4, 80], default 0

rest_shape_key

Shape key to use the rest spring lengths from

Type ShapeKey

spring_damping

Damping of cloth velocity. (higher = more smooth, less jiggling)

Type float in [0, 50], default 0.0

structural_stiffness

Overall stiffness of structure

Type float in [0, 10000], default 0.0

structural_stiffness_max

Maximum structural stiffness value

Type float in [0, 10000], default 0.0

use_pin_cloth

Enable pinning of cloth vertices to other objects/positions

Type boolean, default False

use_stiffness_scale

If enabled, stiffness can be scaled along a weight painted vertex group

Type boolean, default False

vertex_group_bending

Vertex group for fine control over bending stiffness

Type string, default “”

vertex_group_mass

Vertex Group for pinning of vertices

Type string, default “”

vertex_group_structural_stiffness

Vertex group for fine control over structural stiffness

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothModifier.settings

2.4.89 CloudsTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.CloudsTexture (*Texture*)

Procedural noise texture

cloud_type

Determines whether Noise returns grayscale or RGB values

Type enum in ['GREYSCALE', 'COLOR'], default 'GREYSCALE'

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_depth

Sets the depth of the cloud calculation

Type int in [0, 30], default 0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.90 CollectionProperty(Property)

base classes — `bpy_struct`, `Property`

class bpy.types.CollectionProperty(*Property*)
RNA collection property to define lists, arrays and mappings

fixed_type

Fixed pointer type, empty if variable type

Type `Struct`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Property.name`
- `Property.srna`
- `Property.description`
- `Property.is_enum_flag`
- `Property.is_hidden`
- `Property.identifier`
- `Property.is_never_none`
- `Property.is_readonly`
- `Property.is_registered`
- `Property.is_registered_optional`
- `Property.is_required`
- `Property.is_output`
- `Property.is_runtime`
- `Property.is_skip_save`
- `Property.subtype`
- `Property.type`
- `Property.unit`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.91 CollisionModifier(Modifier)

base classes — `bpy_struct`, `Modifier`

class `bpy.types.CollisionModifier` (*Modifier*)
Collision modifier defining modifier stack position used for collision
settings
Type `CollisionSettings`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.92 CollisionSensor(Sensor)

base classes — `bpy_struct`, `Sensor`

class `bpy.types.CollisionSensor` (*Sensor*)
Sensor to detect objects colliding with the current object, with more settings than the Touch sensor
material
Only look for Objects with this material (blank = all objects)
Type `string`, default “”

property

Only look for Objects with this property (blank = all objects)

Type string, default “”

use_material

Toggle collision on material or property

Type boolean, default False

use_pulse

Changes to the set of colliding objects generates pulse

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.93 CollisionSettings(bpy_struct)

base class — bpy_struct

```
class bpy.types.CollisionSettings (bpy_struct)
    Collision settings for object in physics simulation

    absorption
        How much of effector force gets lost during collision with this object (in percent)
        Type float in [0, 1], default 0.0

    damping
        Amount of damping during collision
        Type float in [0, 1], default 0.0

    damping_factor
        Amount of damping during particle collision
        Type float in [0, 1], default 0.0

    damping_random
        Random variation of damping
        Type float in [0, 1], default 0.0

    friction_factor
        Amount of friction during particle collision
        Type float in [0, 1], default 0.0

    friction_random
        Random variation of friction
        Type float in [0, 1], default 0.0

    permeability
        Chance that the particle will pass through the mesh
        Type float in [0, 1], default 0.0

    stickiness
        Amount of stickiness to surface collision
        Type float in [0, 10], default 0.0

    thickness_inner
        Inner face thickness
        Type float in [0.001, 1], default 0.0

    thickness_outer
        Outer face thickness
        Type float in [0.001, 1], default 0.0

    use
        Enable this objects as a collider for physics systems
        Type boolean, default False

    use_particle_kill
        Kill collided particles
        Type boolean, default False
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CollisionModifier.settings
- Object.collision

2.4.94 ColorRamp(bpy_struct)

base class — bpy_struct

class bpy.types.ColorRamp (bpy_struct)
Color ramp mapping a scalar value to a color

elements

Type ColorRampElements bpy_prop_collection of ColorRampElement, (read-only)

interpolation

Type enum in ['EASE', 'CARDINAL', 'LINEAR', 'B_SPLINE', 'CONSTANT'], default 'LINEAR'

evaluate (position)

Evaluate ColorRamp

Parameters position (*float in [0, 1]*) – Position, Evaluate ColorRamp at position

Returns Color, Color at given position

Return type float array of 4 items in [-inf, inf]

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `CompositorNodeValToRGB.color_ramp`
- `Material.diffuse_ramp`
- `Material.specular_ramp`
- `PointDensity.color_ramp`
- `ShaderNodeValToRGB.color_ramp`
- `Texture.color_ramp`
- `TextureNodeValToRGB.color_ramp`
- `UserPreferencesSystem.weight_color_range`

2.4.95 ColorRampElement(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ColorRampElement` (`bpy_struct`)
Element defining a color at a position in the color ramp

color
Set color of selected color stop

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

position
Set position of selected color stop

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ColorRamp.elements
- ColorRampElements.new
- ColorRampElements.remove

2.4.96 ColorRampElements(bpy_struct)

base class — bpy_struct

class bpy.types.ColorRampElements (bpy_struct)
Collection of Color Ramp Elements

new (position)

Add element to ColorRamp

Parameters position (float in [0, 1]) – Position, Position to add element

Returns New element.

Return type ColorRampElement

remove (element)

Delete element from ColorRamp

Parameters element (ColorRampElement, (never None)) – Element to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ColorRamp.elements`

2.4.97 ColorSequence(EffectSequence)

base classes — `bpy_struct, Sequence, EffectSequence`

class bpy.types.ColorSequence(EffectSequence)

Sequence strip creating an image filled with a single g

color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`
- `Sequence.frame_final_duration`
- `Sequence.frame_duration`
- `Sequence.lock`

- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.98 CompositorNode(Node)

base classes — `bpy_struct.Node`

subclasses — `CompositorNodeSepHSVA`, `CompositorNodeValToRGB`, `CompositorNodeSepYCCA`, `CompositorNodeSetAlpha`, `CompositorNodeCrop`, `CompositorNodeMath`, `CompositorNodeCurveRGB`, `CompositorNodeDilateErode`, `CompositorNodeGamma`, `CompositorNodeRotate`, `CompositorNodeLensdist`, `CompositorNodeLumaMatte`, `CompositorNodeTranslate`, `CompositorNodeCombYCCA`, `CompositorNodeBilateralblur`, `CompositorNodeZcombine`, `CompositorNodeFilter`, `CompositorNodePremulKey`, `CompositorNodeMixRGB`, `CompositorNodeTime`, `CompositorNodeValue`, `CompositorNodeHueCorrect`, `CompositorNodeNormal`, `CompositorNodeIDMask`, `CompositorNodeVecBlur`, `CompositorNodeRLayers`, `CompositorNodeComposite`, `CompositorNodeCombRGBA`, `CompositorNodeViewer`, `CompositorNodeCombHSVA`, `CompositorNodeOutputFile`, `CompositorNodeInvert`, `CompositorNodeFlip`, `CompositorNodeDistanceMatte`, `CompositorNodeRGBToBW`, `CompositorNodeCombYUVA`, `CompositorNodeBlur`, `CompositorNodeDefocus`, `CompositorNodeGlare`, `CompositorNodeDiffMatte`, `CompositorNodeImage`, `CompositorNodeDBlur`, `CompositorNodeMapView`, `CompositorNodeBrightContrast`, `CompositorNodeTexture`, `CompositorNodeLevels`, `CompositorNodeNormalize`, `CompositorNodeChannelMatte`, `CompositorNodeRGB`, `CompositorNodeColorSpill`, `CompositorNodeSepRGBA`, `CompositorNodeScale`, `CompositorNodeMapUV`, `CompositorNodeChromaMatte`, `CompositorNodeDisplace`, `CompositorNodeColorBalance`, `CompositorNodeTonemap`, `CompositorNodeAlphaOver`, `CompositorNodeColorMatte`, `CompositorNodeHueSat`, `CompositorNodeSepYUVA`, `CompositorNodeCurveVec`, `CompositorNodeSplitViewer`

class `bpy.types.CompositorNode` (`Node`)

type

Type enum in `['VIEWER', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RG-BTOBW', 'NORMAL', 'CURVE_VEC', 'CURVE_RGB', 'ALPHAOVER', 'BLUR', 'FILTER', 'MAP_VALUE', 'TIME', 'VECBLUR', 'SEPRGBA', 'SEPHSVA', 'SETALPHA', 'HUE_SAT', 'IMAGE', 'R_LAYERS', 'COMPOSITE', 'OUTPUT_FILE', 'TEXTURE', 'TRANSLATE', 'ZCOMBINE', 'COMBRGBA', 'DILATEERODE', 'ROTATE', 'SCALE', 'SEPYCCA', 'COMBYCCA', 'SEPYUVA', 'COMBYUVA', 'DIFF_MATTE', 'COLOR_SPILL', 'CHROMA_MATTE', 'CHANNEL_MATTE', 'FLIP', 'SPLITVIEWER', 'MAP_UV', 'ID_MASK', 'DEFOCUS', 'DISPLACE', 'COMBHNSVA', 'MATH', 'LUMA_MATTE', 'BRIGHTCONTRAST', 'GAMMA', 'INVERT', 'NORMALIZE', 'CROP', 'DBLUR', 'BILATERALBLUR', 'PREMULKEY', 'DISTANCE_MATTE', 'LEVELS', 'COLOR_MATTE', 'COLORBALANCE', 'HUECORRECT', 'GLARE', 'TONEMAP', 'LENSDIST', 'SCRIPT', 'GROUP'], default 'VIEWER', (readonly)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.99 CompositorNodeAlphaOver(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeAlphaOver (CompositorNode)`

`premul`

Mix Factor

Type float in [0, 1], default 0.0

`use premultiply`

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.100 CompositorNodeBilateralblur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeBilateralblur (CompositorNode)

iterations

Type int in [1, 128], default 0

sigma_color

Type float in [0.01, 3], default 0.0

sigma_space

Type float in [0.01, 30], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.101 CompositorNodeBlur(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeBlur (CompositorNode)`

`aspect_correction`

Type of aspect correction to use

Type enum in ['NONE', 'Y', 'X'], default 'NONE'

`factor`

Type float in [0, 2], default 0.0

`factor_x`

Type float in [0, 100], default 0.0

`factor_y`

Type float in [0, 100], default 0.0

`filter_type`

Type enum in ['FLAT', 'TENT', 'QUAD', 'CUBIC', 'GAUSS', 'FAST_GAUSS', 'CATROM', 'MITCH'], default 'FLAT'

`size_x`

Type int in [0, 2048], default 0

`size_y`

Type int in [0, 2048], default 0

`use_bokeh`

Uses circular filter (slower)

Type boolean, default False

`use_gamma_correction`

Applies filter on gamma corrected values

Type boolean, default False

`use_relative`

Use relative (percent) values to define blur radius

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`

- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.102 CompositorNodeBrightContrast(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeBrightContrast (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.103 CompositorNodeChannelMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeChannelMatte (CompositorNode)

color_space

Type enum in ['RGB', 'HSV', 'YUV', 'YCC'], default 'RGB'

limit_channel

Limit by this channels value

Type enum in ['R', 'G', 'B'], default 'R'

limit_max

Values higher than this setting are 100% opaque

Type float in [0, 1], default 0.0

limit_method

Algorithm to use to limit channel

Type enum in ['SINGLE', 'MAX'], default 'SINGLE'

limit_min

Values lower than this setting are 100% keyed

Type float in [0, 1], default 0.0

matte_channel

Channel used to determine matte

Type enum in ['R', 'G', 'B'], default 'R'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.104 CompositorNodeChromaMatte(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeChromaMatte (CompositorNode)`

`gain`

Alpha gain

Type float in [0, 1], default 0.0

`lift`

Alpha lift

Type float in [0, 1], default 0.0

`shadow_adjust`

Adjusts the brightness of any shadows captured

Type float in [0, 1], default 0.0

`threshold`

Tolerance below which colors will be considered as exact matches

Type float in [0, 30], default 0.0

`tolerance`

Tolerance for a color to be considered a keying color

Type float in [1, 80], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.105 CompositorNodeColorBalance(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeColorBalance (CompositorNode)`

`correction_method`

Type enum in `['LIFT_GAMMA_GAIN', 'OFFSET_POWER_SLOPE']`, default `'LIFT_GAMMA_GAIN'`

`gain`

Correction for Highlights

Type float array of 3 items in `[-inf, inf]`, default `(1.0, 1.0, 1.0)`

`gamma`

Correction for Midtones

Type float array of 3 items in `[-inf, inf]`, default `(1.0, 1.0, 1.0)`

`lift`

Correction for Shadows

Type float array of 3 items in `[-inf, inf]`, default `(1.0, 1.0, 1.0)`

`offset`

Correction for Shadows

Type float array of 3 items in `[-inf, inf]`, default `(0.0, 0.0, 0.0)`

`power`

Correction for Midtones

Type float array of 3 items in `[0, inf]`, default `(1.0, 1.0, 1.0)`

`slope`

Correction for Highlights

Type float array of 3 items in `[0, inf]`, default `(1.0, 1.0, 1.0)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.106 CompositorNodeColorMatte(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeColorMatte (CompositorNode)`

`color_hue`

Hue tolerance for colors to be considered a keying color

Type float in [0, 1], default 0.0

`color_saturation`

Saturation Tolerance for the color

Type float in [0, 1], default 0.0

`color_value`

Value Tolerance for the color

Type float in [0, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`

- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.107 CompositorNodeColorSpill(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeColorSpill (CompositorNode)`

`channel`

Type enum in ['R', 'G', 'B'], default 'R'

`limit_channel`

Type enum in ['R', 'G', 'B'], default 'R'

`limit_method`

Type enum in ['SIMPLE', 'AVERAGE'], default 'SIMPLE'

`ratio`

Scale limit by value

Type float in [0.5, 1.5], default 0.0

`unspill_blue`

Blue spillmap scale

Type float in [0, 1.5], default 0.0

`unspill_green`

Green spillmap scale

Type float in [0, 1.5], default 0.0

unspill_red

Red spillmap scale

Type float in [0, 1.5], default 0.0**use_unspill**

Compensate all channels (differently) by hand

Type boolean, default False**Inherited Properties**

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.108 CompositorNodeCombHSVAC(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode``class bpy.types.CompositorNodeCombHSVAC (CompositorNode)`**Inherited Properties**

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`

- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.109 CompositorNodeCombRGBA(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeCombRGBA (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.110 CompositorNodeCombYCCA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeCombYCCA (CompositorNode)

mode

Type enum in ['ITUBT601', 'ITUBT709', 'JFIF'], default 'ITUBT601'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.111 CompositorNodeCombYUVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeCombYUVA (CompositorNode)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.112 CompositorNodeComposite(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeComposite(CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.113 CompositorNodeCrop(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeCrop (*CompositorNode*)

max_x

Type int in [0, 10000], default 0

max_y

Type int in [0, 10000], default 0

min_x

Type int in [0, 10000], default 0

min_y

Type int in [0, 10000], default 0

rel_max_x

Type float in [0, 1], default 0.0

rel_max_y

Type float in [0, 1], default 0.0

rel_min_x

Type float in [0, 1], default 0.0

rel_min_y

Type float in [0, 1], default 0.0

relative

Use relative values to crop image

Type boolean, default False

use_crop_size

Whether to crop the size of the input image

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.114 CompositorNodeCurveRGB(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeCurveRGB (CompositorNode)`

`mapping`

Type `CurveMapping`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.115 CompositorNodeCurveVec(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeCurveVec (CompositorNode)`

`mapping`

Type `CurveMapping`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.116 CompositorNodeDBlur(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

```
class bpy.types.CompositorNodeDBlur (CompositorNode)
```

angle

Type float in [0, 360], default 0.0

center_x

Type float in [0, 1], default 0.0

center_y

Type float in [0, 1], default 0.0

distance

Type float in [-1, 1], default 0.0

iterations

Type int in [1, 32], default 0

spin

Type float in [-360, 360], default 0.0

use_wrap

Type boolean, default False

zoom

Type float in [0, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.117 CompositorNodeDefocus(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeDefocus (CompositorNode)

angle

Bokeh shape rotation offset in degrees

Type int in [0, 90], default 0

blur_max

blur limit, maximum CoC radius, 0=no limit

Type float in [0, 10000], default 0.0

bokeh

Type enum in ['OCTAGON', 'HEPTAGON', 'HEXAGON', 'PENTAGON', 'SQUARE', 'TRIANGLE', 'CIRCLE'], default 'CIRCLE'

f_stop

Amount of focal blur, 128=infinity=perfect focus, half the value doubles the blur radius

Type float in [0, 128], default 0.0

samples

Number of samples (16=grainy, higher=less noise)

Type int in [16, 256], default 0

threshold

CoC radius threshold, prevents background bleed on in-focus midground, 0=off

Type float in [0, 100], default 0.0

use_gamma_correction

Enable gamma correction before and after main process

Type boolean, default False

use_preview

Enable sampling mode, useful for preview when using low samplecounts

Type boolean, default False

use_zbuffer

Disable when using an image as input instead of actual z-buffer (auto enabled if node not image based, eg. time node)

Type boolean, default False

z_scale

Scales the Z input when not using a z-buffer, controls maximum blur designated by the color white or input value 1

Type float in [0, 1000], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.118 CompositorNodeDiffMatte(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeDiffMatte (CompositorNode)

falloff

Color distances below this additional threshold are partially keyed

Type float in [0, 1], default 0.0

tolerance

Color distances below this threshold are keyed

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.119 CompositorNodeDilateErode(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeDilateErode (*CompositorNode*)

distance

Distance to grow/shrink (number of iterations)

Type int in [-100, 100], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.120 CompositorNodeDisplace(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeDisplace(CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.121 CompositorNodeDistanceMatte(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeDistanceMatte (CompositorNode)`

falloff

Color distances below this additional threshold are partially keyed

Type float in [0, 1], default 0.0

tolerance

Color distances below this threshold are keyed

Type float in [0, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.122 CompositorNodeFilter(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

```
class bpy.types.CompositorNodeFilter(CompositorNode)

    filter_type

    Type enum in ['SOFTEN', 'SHARPEN', 'LAPLACE', 'SOBEL', 'PREWITT', 'KIRSCH',
                 'SHADOW'], default 'SOFTEN'
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.123 CompositorNodeFlip(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

```
class bpy.types.CompositorNodeFlip(CompositorNode)
```

axis

Type enum in ['X', 'Y', 'XY'], default 'X'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs

- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.124 CompositorNodeGamma(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeGamma (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.125 CompositorNodeGlare(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeGlare (CompositorNode)

angle_offset

Streak angle offset in degrees

Type int in [0, 180], default 0

color_modulation

Amount of Color Modulation, modulates colors of streaks and ghosts for a spectral dispersion effect

Type float in [0, 1], default 0.0

fade

Streak fade-out factor

Type float in [0.75, 1], default 0.0

glare_type

Type enum in ['GHOSTS', 'STREAKS', 'FOG_GLOW', 'SIMPLE_STAR'], default 'SIMPLE_STAR'

iterations

Type int in [2, 5], default 0

mix

-1 is original image only, 0 is exact 50/50 mix, 1 is processed image only

Type float in [-1, 1], default 0.0

quality

If not set to high quality, the effect will be applied to a low-res copy of the source image

Type enum in ['HIGH', 'MEDIUM', 'LOW'], default 'HIGH'

size

Glow/glare size (not actual size; relative to initial size of bright area of pixels)

Type int in [6, 9], default 0

streaks

Total number of streaks

Type int in [2, 16], default 0

threshold

The glare filter will only be applied to pixels brighter than this value

Type float in [0, 1000], default 0.0

use_rotate_45

Simple star filter: add 45 degree rotation offset

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.126 CompositorNodeHueCorrect(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeHueCorrect (*CompositorNode*)

mapping

Type CurveMapping, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location

- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.127 CompositorNodeHueSat(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeHueSat (CompositorNode)`

`color_hue`

Type float in [0, 1], default 0.0

`color_saturation`

Type float in [0, 2], default 0.0

`color_value`

Type float in [0, 2], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`

- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.128 CompositorNodeIDMask(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

class `bpy.types.CompositorNodeIDMask` (`CompositorNode`)

index

Pass index number to convert to alpha

Type int in [0, 10000], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.129 CompositorNodeImage(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeImage (CompositorNode)`

`frame_duration`

Sets the number of images of a movie to use

Type int in [0, 300000], default 0

`frame_offset`

Offsets the number of the frame to use in the animation

Type int in [-300000, 300000], default 0

`frame_start`

Sets the global starting frame of the movie/sequence, assuming first picture has a #1

Type int in [-300000, 300000], default 0

`image`

Type `Image`

`layer`

Type enum in ['PLACEHOLDER'], default 'PLACEHOLDER'

`use_auto_refresh`

Always refresh image on frame changes

Type boolean, default False

`use_cyclic`

Cycle the images in the movie

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.130 CompositorNodeInvert(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeInvert (*CompositorNode*)

invert_alpha

Type boolean, default False

invert_rgb

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.131 CompositorNodeLensdist(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeLensdist (*CompositorNode*)

use_fit

For positive distortion factor only: scale image such that black areas are not visible

Type boolean, default False

use_jitter

Enable/disable jittering; faster, but also noisier

Type boolean, default False

use_projector

Enable/disable projector mode. Effect is applied in horizontal direction only

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.132 CompositorNodeLevels(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeLevels (CompositorNode)`

`channel`

Type enum in ['COMBINED_RGB', 'RED', 'GREEN', 'BLUE', 'LUMINANCE'], default 'COMBINED_RGB'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.133 CompositorNodeLumaMatte(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeLumaMatte (CompositorNode)`

`limit_max`

Values higher than this setting are 100% opaque

Type float in [0, 1], default 0.0

`limit_min`

Values lower than this setting are 100% keyed

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.134 CompositorNodeMapUV(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeMapUV (*CompositorNode*)

alpha

Type int in [0, 100], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.135 CompositorNodeMapView(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeMapView (CompositorNode)`

max

Type float array of 1 items in [-1000, 1000], default (0.0)

min

Type float array of 1 items in [-1000, 1000], default (0.0)

offset

Type float array of 1 items in [-1000, 1000], default (0.0)

size

Type float array of 1 items in [-1000, 1000], default (0.0)

use_max

Type boolean, default False

use_min

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`

- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.136 CompositorNodeMath(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeMath (*CompositorNode*)

operation

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.137 CompositorNodeMixRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeMixRGB (*CompositorNode*)

blend_type

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

use_alpha

Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.138 CompositorNodeNormal(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeNormal (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.139 CompositorNodeNormalize(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeNormalize (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`

- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.140 CompositorNodeOutputFile(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class `bpy.types.CompositorNodeOutputFile` (*CompositorNode*)

`exr_codec`

Type enum in ['NONE', 'PXR24', 'ZIP', 'PIZ', 'RLE'], default 'NONE'

`filepath`

Output path for the image, same functionality as render output.

Type string, default “”

`frame_end`

Type int in [0, 300000], default 0

`frame_start`

Type int in [0, 300000], default 0

`image_type`

Type enum in ['TARGA', 'RAW_TARGA', 'PNG', 'BMP', 'JPEG', 'IRIS', 'RADIANCE_HDR', 'CINEON', 'DPX', 'OPENEXR'], default 'TARGA'

`quality`

Type int in [1, 100], default 0

`use_exr_half`

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.141 CompositorNodePremulKey(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodePremulKey (*CompositorNode*)

mapping

Conversion between premultiplied alpha and key alpha

Type enum in ['KEY_TO_PREMUL', 'PREMUL_TO_KEY'], default 'KEY_TO_PREMUL'

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.142 CompositorNodeRGB(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeRGB (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.143 CompositorNodeRGBToBW(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeRGBToBW (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.144 CompositorNodeRLayers(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeRLayers (CompositorNode)`

`layer`

Type enum in ['PLACEHOLDER'], default 'PLACEHOLDER'

`scene`

Type Scene

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.145 CompositorNodeRotate(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class `bpy.types.CompositorNodeRotate` (`CompositorNode`)

`filter_type`

Method to use to filter rotation

Type enum in ['NEAREST', 'BILINEAR', 'BICUBIC'], default 'NEAREST'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.146 CompositorNodeScale(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class `bpy.types.CompositorNodeScale (CompositorNode)`

space

Coordinate space to scale relative to

Type enum in ['RELATIVE', 'ABSOLUTE', 'SCENE_SIZE', 'RENDER_SIZE'], default 'RELATIVE'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.147 CompositorNodeSepHSVA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeSepHSVA (*CompositorNode*)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.148 CompositorNodeSepRGBA(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeSepRGBA (*CompositorNode*)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.149 CompositorNodeSepYCCA(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeSepYCCA (CompositorNode)`

`mode`

Type enum in ['ITUBT601', 'ITUBT709', 'JFIF'], default 'ITUBT601'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.150 CompositorNodeSepYUVA(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeSepYUVA (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.151 CompositorNodeSetAlpha(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeSetAlpha (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.152 CompositorNodeSplitViewer(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeSplitViewer (CompositorNode)`

`axis`

Type enum in ['X', 'Y'], default 'X'

`factor`

Type int in [0, 100], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.153 CompositorNodeTexture(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class `bpy.types.CompositorNodeTexture` (`CompositorNode`)

`node_output`

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

`texture`

Type `Texture`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`

- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.154 CompositorNodeTime(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class bpy.types.CompositorNodeTime (CompositorNode)

curve

Type `CurveMapping`, (readonly)

frame_end

Type int in [-32768, 32767], default 0

frame_start

Type int in [-32768, 32767], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.155 CompositorNodeTonemap(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeTonemap (CompositorNode)

adaptation

If 0, global; if 1, based on pixel intensity

Type float in [0, 1], default 0.0

contrast

Set to 0 to use estimate from input image

Type float in [0, 1], default 0.0

correction

If 0, same for all channels; if 1, each independent

Type float in [0, 1], default 0.0

gamma

If not used, set to 1

Type float in [0.001, 3], default 0.0

intensity

If less than zero, darkens image; otherwise, makes it brighter

Type float in [-8, 8], default 0.0

key

The value the average luminance is mapped to

Type float in [0, 1], default 0.0

offset

Normally always 1, but can be used as an extra control to alter the brightness curve

Type float in [0.001, 10], default 0.0

tonemap_type

Type enum in ['RD_PHOTORECEPTOR', 'RH_SIMPLE'], default 'RH_SIMPLE'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.156 CompositorNodeTranslate(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeTranslate(CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.157 CompositorNodeTree(NodeTree)

base classes — bpy_struct, ID, NodeTree

class bpy.types.CompositorNodeTree (NodeTree)
Node tree consisting of linked nodes used for compositing

nodes

Type CompositorNodes bpy_prop_collection of Node, (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- NodeTree.animation_data
- NodeTree.grease_pencil
- NodeTree.inputs
- NodeTree.links
- NodeTree.outputs
- NodeTree.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.158 CompositorNodeValToRGB(CompositorNode)

base classes — bpy_struct, Node, CompositorNode

class bpy.types.CompositorNodeValToRGB (CompositorNode)

color_ramp

Type ColorRamp, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- CompositorNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.159 CompositorNodeValue(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeValue (CompositorNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.160 CompositorNodeVecBlur(CompositorNode)

base classes — `bpy_struct`, `Node`, `CompositorNode`

`class bpy.types.CompositorNodeVecBlur (CompositorNode)`

factor

Scaling factor for motion vectors; actually ‘shutter speed’ in frames

Type float in [0, 2], default 0

samples

Type int in [1, 256], default 0

speed_max

Maximum speed, or zero for none

Type int in [0, 1024], default 0

speed_min

Minimum speed for a pixel to be blurred; used to separate background from foreground

Type int in [0, 1024], default 0

use_curved

Interpolate between frames in a Bezier curve, rather than linearly

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.161 CompositorNodeViewer(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

class bpy.types.CompositorNodeViewer(CompositorNode)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`

- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.162 CompositorNodeZcombine(CompositorNode)

base classes — `bpy_struct, Node, CompositorNode`

`class bpy.types.CompositorNodeZcombine (CompositorNode)`

`use_alpha`

Takes Alpha channel into account when doing the Z operation

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `CompositorNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.163 CompositorNodes(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.CompositorNodes` (`bpy_struct`)

Collection of Compositor Nodes

new (`type, group=None`)

Add a node to this node tree.

Parameters

- **type** (*enum in* ['VIEWER', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RG-BTOBW', 'NORMAL', 'CURVE_VEC', 'CURVE_RGB', 'ALPHAOVER', 'BLUR', 'FILTER', 'MAP_VALUE', 'TIME', 'VECBLUR', 'SEPRGBA', 'SEPHSVA', 'SETALPHA', 'HUE_SAT', 'IMAGE', 'R_LAYERS', 'COMPOSITE', 'OUTPUT_FILE', 'TEXTURE', 'TRANSLATE', 'ZCOMBINE', 'COMBRGBA', 'DILATEERODE', 'ROTATE', 'SCALE', 'SEPYCCA', 'COMBYCCA', 'SEPYUVA', 'COMBYUVA', 'DIFF_MATTE', 'COLOR_SPILL', 'CHROMA_MATTE', 'CHANNEL_MATTE', 'FLIP', 'SPLITVIEWER', 'MAP_UV', 'ID_MASK', 'DEFOCUS', 'DISPLACE', 'COMBHSVA', 'MATH', 'LUMA_MATTE', 'BRIGHTCONTRAST', 'GAMMA', 'INVERT', 'NORMALIZE', 'CROP', 'DBLUR', 'BILATERALBLUR', 'PREMULKEY', 'DISTANCE_MATTE', 'LEVELS', 'COLOR_MATTE', 'COLORBALANCE', 'HUECORRECT', 'GLARE', 'TONEMAP', 'LENSDIST', 'SCRIPT', 'GROUP']) – Type, Type of node to add
- **group** (`NodeTree`, (optional)) – The group tree

Returns New node.

Return type `Node`

remove (`node`)

remove a node from this node tree.

Parameters `node` (`Node`) – The node to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `CompositorNodeTree.nodes`

2.4.164 ConsoleLine(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ConsoleLine` (`bpy_struct`)

Input line for the interactive console

body

Text in the line

Type string, default “”

current_character

Type int in [-inf, inf], default 0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SpaceConsole.history`
- `SpaceConsole.scrollback`

2.4.165 Constraint(`bpy_struct`)

base class — `bpy_struct`

subclasses — `KinematicConstraint`, `CopyScaleConstraint`, `ShrinkwrapConstraint`, `FollowPathConstraint`, `LockedTrackConstraint`, `CopyTransformsConstraint`, `PythonConstraint`, `LimitDistanceConstraint`, `StretchToConstraint`, `PivotConstraint`, `ClampToConstraint`, `TransformConstraint`, `LimitRotationConstraint`, `LimitLocationConstraint`, `ChildOfConstraint`, `CopyRotationConstraint`, `DampedTrackConstraint`, `TrackToConstraint`, `SplineIKConstraint`, `MaintainVolumeConstraint`, `LimitScaleConstraint`, `RigidBodyJointConstraint`, `FloorConstraint`, `ActionConstraint`, `CopyLocationConstraint`

class `bpy.types.Constraint` (`bpy_struct`)

Constraint modifying the transformation of objects and bones

active
Constraint is the one being edited

Type boolean, default False

error_location
Amount of residual error in Blender space unit for constraints that work on position

Type float in [-inf, inf], default 0.0, (readonly)

error_rotation
Amount of residual error in radiant for constraints that work on orientation

Type float in [-inf, inf], default 0.0, (readonly)

influence
Amount of influence constraint will have on the final solution

Type float in [0, 1], default 0.0

is_proxy_local
Constraint was added in this proxy instance (i.e. did not belong to source Armature)

Type boolean, default False

is_valid
Constraint has valid settings and can be evaluated

Type boolean, default False, (readonly)

mute
Enable/Disable Constraint

Type boolean, default False

name
Constraint name
Type string, default “”

owner_space
Space that owner is evaluated in
Type enum in ['WORLD', 'POSE', 'LOCAL_WITH_PARENT', 'LOCAL'], default 'WORLD'

show_expanded
Constraint's panel is expanded in UI
Type boolean, default False

target_space
Space that target is evaluated in
Type enum in ['WORLD', 'POSE', 'LOCAL_WITH_PARENT', 'LOCAL'], default 'WORLD'

type
Type enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP'], default 'COPY_LOCATION', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.constraints`
- `ObjectConstraints.active`
- `ObjectConstraints.new`
- `ObjectConstraints.remove`
- `PoseBone.constraints`
- `PoseBoneConstraints.active`
- `PoseBoneConstraints.new`
- `PoseBoneConstraints.remove`
- `UILayout.template_constraint`

2.4.166 ConstraintActuator(*Actuator*)

base classes — `bpy_struct, Actuator`

class `bpy.types.ConstraintActuator` (*Actuator*)

Actuator to handle Constraints

angle_max

Maximum angle (in degree) allowed with target direction. No correction is done if angle with target direction is between min and max

Type float in [0, 180], default 0.0

angle_min

Minimum angle (in degree) to maintain with target direction. No correction is done if angle with target direction is between min and max

Type float in [0, 180], default 0.0

damping

Damping factor: time constant (in frame) of low pass filter

Type int in [-32768, 32767], default 0

damping_rotation

Use a different damping for orientation

Type int in [-32768, 32767], default 0

direction

Set the direction of the ray

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ', 'DIRNX', 'DIRNY', 'DIRNZ'], default 'NONE'

direction_axis

Select the axis to be aligned along the reference direction

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ', 'DIRNX', 'DIRNY', 'DIRNZ'], default 'NONE'

direction_axis_pos

Select the axis to be aligned along the reference direction

Type enum in ['NONE', 'DIRPX', 'DIRPY', 'DIRPZ'], default 'NONE'

distance

Keep this distance to target

Type float in [-inf, inf], default 0.0

fh_damping
Damping factor of the force field spring
Type float in [-inf, inf], default 0.0

fh_force
Spring force within the force field area
Type float in [-inf, inf], default 0.0

fh_height
Height of the force field area
Type float in [-inf, inf], default 0.0

limit
Type enum in ['NONE', 'LOCX', 'LOCY', 'LOCZ'], default 'NONE'

limit_max
Type float in [-inf, inf], default 0.0

limit_min
Type float in [-inf, inf], default 0.0

material
Ray detects only Objects with this material
Type string, default ""

mode
The type of the constraint
Type enum in ['LOC', 'DIST', 'ORI', 'FH'], default 'LOC'

property
Ray detect only Objects with this property
Type string, default ""

range
Set the maximum length of ray
Type float in [-inf, inf], default 0.0

rotation_max
Reference Direction
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

time
Maximum activation time in frame, 0 for unlimited
Type int in [-32768, 32767], default 0

use_fh_normal
Add a horizontal spring force on slopes
Type boolean, default False

use_fh_parallel_axis
Keep object axis parallel to normal
Type boolean, default False

use_force_distance

Force distance of object to point of impact of ray

Type boolean, default False

use_local

Set ray along object's axis or global axis

Type boolean, default False

use_material_detect

Detect material instead of property

Type boolean, default False

use_normal

Set object axis along (local axis) or parallel (global axis) to the normal at hit position

Type boolean, default False

use_persistent

Persistent actuator: stays active even if ray does not reach target

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.167 ConstraintTarget(bpy_struct)

base class — `bpy_struct`

class `bpy.types.ConstraintTarget` (*bpy_struct*)
Target object for multi-target constraints

subtarget
Type string, default “”

target
Target Object
Type `Object`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `PythonConstraint.targets`

2.4.168 Context(bpy_struct)

base class — `bpy_struct`

class `bpy.types.Context` (*bpy_struct*)
Current windowmanager and data context

area
Type `Area`, (readonly)

blend_data

Type `BlendData`, (readonly)

mode

Type enum in ['EDIT_MESH', 'EDIT_CURVE', 'EDIT_SURFACE', 'EDIT_TEXT', 'EDIT_ARMATURE', 'EDIT_METABALL', 'EDIT_LATTICE', 'POSE', 'SCULPT', 'PAINT_WEIGHT', 'PAINT_VERTEX', 'PAINT_TEXTURE', 'PARTICLE', 'OBJECT'], default 'EDIT_MESH', (readonly)

region

Type `Region`, (readonly)

region_data

Type `RegionView3D`, (readonly)

scene

Type `Scene`, (readonly)

screen

Type `Screen`, (readonly)

space_data

Type `Space`, (readonly)

tool_settings

Type `ToolSettings`, (readonly)

user_preferences

Type `UserPreferences`, (readonly)

window

Type `Window`, (readonly)

window_manager

Type `WindowManager`, (readonly)

static copy (self)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Header.draw
- KeyingSetInfo.generate
- KeyingSetInfo.iterator
- KeyingSetInfo.poll
- Macro.draw
- Macro.poll
- Menu.draw
- Menu.poll
- Operator.cancel
- Operator.check
- Operator.draw
- Operator.execute
- Operator.invoke
- Operator.modal
- Operator.poll
- Panel.draw
- Panel.draw_header
- Panel.poll

2.4.169 ControlFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.ControlFluidSettings(FluidSettings)

Fluid simulation settings for objects controlling the motion of fluid in the simulation

attraction_radius

Specifies the force field radius around the control object

Type float in [0, 10], default 0.0

attraction_strength

Force strength for directional attraction towards the control object

Type float in [-10, 10], default 0.0

end_time

Specifies time when the control particles are deactivated

Type float in [0, 100], default 0.0

quality

Specifies the quality which is used for object sampling. (higher = better but slower)

Type float in [5, 100], default 0.0

start_time

Specifies time when the control particles are activated

Type float in [0, 100], default 0.0

use

Object contributes to the fluid simulation

Type boolean, default False

use_reverse_frames

Reverse control object movement

Type boolean, default False

velocity_radius

Specifies the force field radius around the control object

Type float in [0, 10], default 0.0

velocity_strength

Force strength of how much of the control object's velocity is influencing the fluid velocity

Type float in [0, 10], default 0.0

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.170 Controller(bpy_struct)

base class — bpy_struct

subclasses — ExpressionController, XnorController, PythonController, AndController, NorController, OrController, XorController, NandController

class bpy.types.Controller(*bpy_struct*)

Game engine logic brick to process events, connecting sensors to actuators

name

Type string, default “”

show_expanded
Set controller expanded in the user interface

Type boolean, default False

states
Set Controller state index (1 to 30)

Type int in [1, 30], default 0

type

Type enum in ['LOGIC_AND', 'LOGIC_OR', 'LOGIC_NAND', 'LOGIC_NOR', 'LOGIC_XOR', 'LOGIC_XNOR', 'EXPRESSION', 'PYTHON'], default 'LOGIC_AND'

use_priority
Mark controller for execution before all non-marked controllers (good for startup scripts)

Type boolean, default False

link (*sensor=None, actuator=None*)
Link the controller with a sensor/actuator.

Parameters

- **sensor** ([Sensor](#), (optional)) – Sensor to link the controller to.
- **actuator** ([Actuator](#), (optional)) – Actuator to link the controller to.

unlink (*sensor=None, actuator=None*)
Unlink the controller from a sensor/actuator.

Parameters

- **sensor** ([Sensor](#), (optional)) – Sensor to unlink the controller from.
- **actuator** ([Actuator](#), (optional)) – Actuator to unlink the controller from.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)

- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Actuator.link`
- `Actuator.unlink`
- `GameObjectSettings.controllers`
- `Sensor.link`
- `Sensor.unlink`

2.4.171 CopyLocationConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.CopyLocationConstraint (Constraint)

Copies the location of the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

invert_x

Invert the X location

Type boolean, default False

invert_y

Invert the Y location

Type boolean, default False

invert_z

Invert the Z location

Type boolean, default False

subtarget

Type string, default “”

target

Target Object

Type `Object`

use_offset

Add original location into copied location

Type boolean, default False

use_x

Copy the target’s X location

Type boolean, default False

use_y

Copy the target’s Y location

Type boolean, default False

use_z

Copy the target's Z location

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.172 CopyRotationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.CopyRotationConstraint (*Constraint*)

Copies the rotation of the target

invert_x

Invert the X rotation

Type boolean, default False

invert_y

Invert the Y rotation

Type boolean, default False

invert_z

Invert the Z rotation

Type boolean, default False

subtarget

Type string, default “”

target

Target Object

Type Object

use_offset

Add original rotation into copied rotation

Type boolean, default False

use_x

Copy the target’s X rotation

Type boolean, default False

use_y

Copy the target’s Y rotation

Type boolean, default False

use_z

Copy the target’s Z rotation

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.173 CopyScaleConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.CopyScaleConstraint (Constraint)

Copies the scale of the target

subtarget

Type string, default “”

target

Target Object

Type Object

use_offset

Add original scale into copied scale

Type boolean, default False

use_x

Copy the target’s X scale

Type boolean, default False

use_y

Copy the target’s Y scale

Type boolean, default False

use_z

Copy the target’s Z scale

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local

- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.174 CopyTransformsConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.CopyTransformsConstraint (Constraint)

Copies all the transforms of the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

subtarget

Type string, default “”

target

Target Object

Type Object

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space

- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.175 Curve(ID)

base classes — bpy_struct, ID

subclasses — SurfaceCurve, TextCurve

class bpy.types.Curve (ID)

Curve datablock storing curves, splines and NURBS

animation_data

Animation data for this datablock

Type AnimData, (readonly)

bevel_depth

Bevel depth when not using a bevel object

Type float in [-inf, inf], default 0.0

bevel_object

Curve object name that defines the bevel shape

Type Object

bevel_resolution

Bevel resolution when depth is non-zero and no specific bevel object has been defined

Type int in [0, 32], default 0

dimensions

Select 2D or 3D curve type

Type enum in ['2D', '3D'], default '2D'

eval_time

Parametric position along the length of the curve that Objects ‘following’ it should be at. Position is evaluated by dividing by the ‘Path Length’ value

Type float in [-inf, inf], default 0.0

extrude

Amount of curve extrusion when not using a bevel object

Type float in [0, inf], default 0.0

materials

Type `IDMaterials bpy_prop_collection of Material`, (readonly)

offset

Offset the curve to adjust the width of a text

Type float in [-inf, inf], default 0.0

path_duration

The number of frames that are needed to traverse the path, defining the maximum value for the ‘Evaluation Time’ setting

Type int in [1, 300000], default 0

render_resolution_u

Surface resolution in U direction used while rendering. Zero skips this property

Type int in [0, 32767], default 0

render_resolution_v

Surface resolution in V direction used while rendering. Zero skips this property

Type int in [0, 32767], default 0

resolution_u

Surface resolution in U direction

Type int in [1, 32767], default 0

resolution_v

Surface resolution in V direction

Type int in [1, 32767], default 0

shape_keys

Type `Key`, (readonly)

show_handles

Display Bezier handles in editmode

Type boolean, default False

show_normal_face

Display 3D curve normals in editmode

Type boolean, default False

splines

Collection of splines in this curve data object

Type `CurveSplines bpy_prop_collection of Spline`, (readonly)

taper_object

Curve object name that defines the taper (width)

Type `Object`

texspace_location
Texture space location
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size
Texture space size
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

twist_mode
The type of tilt calculation for 3D Curves
Type enum in ['Z_UP', 'MINIMUM', 'TANGENT'], default 'Z_UP'

twist_smooth
Smoothing iteration for tangents
Type float in [-inf, inf], default 0.0

use_auto_texspace
Adjusts active object's texture space automatically when transforming object
Type boolean, default False

use_deform_bounds
Use the mesh bounds to clamp the deformation
Type boolean, default False

use_fill_back
Draw filled back for extruded/beveled curves
Type boolean, default False

use_fill_deform
Fill curve after applying shape keys and all modifiers
Type boolean, default False

use_fill_front
Draw filled front for extruded/beveled curves
Type boolean, default False

use_path
Enable the curve to become a translation path
Type boolean, default False

use_path_follow
Make curve path children to rotate along the path
Type boolean, default False

use_radius
Option for paths: apply the curve radius with path following it and deforming
Type boolean, default False

use_stretch
Option for curve-deform: makes deformed child to stretch along entire path
Type boolean, default False

use_time_offset

Children will use TimeOffs value as path distance offset

Type boolean, default False

use_uv_as_generated

Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.curves`
- `BlendDataCurves.new`
- `BlendDataCurves.remove`

2.4.176 CurveMap(bpy_struct)

base class — `bpy_struct`

```
class bpy.types.CurveMap(bpy_struct)
    Curve in a curve mapping

    extend
        Extrapolate the curve or extend it horizontally

        Type enum in ['HORIZONTAL', 'EXTRAPOLATED'], default 'HORIZONTAL', (readonly)

    points
        Type bpy_prop_collection of CurveMapPoint, (readonly)
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CurveMapping.curves

2.4.177 CurveMapPoint(bpy_struct)

base class — bpy_struct

```
class bpy.types.CurveMapPoint(bpy_struct)
    Point of a curve used for a curve mapping

    handle_type
        Curve interpolation at this point: Bezier or vector

        Type enum in ['AUTO', 'VECTOR'], default 'AUTO', (readonly)

    location
        X/Y coordinates of the curve point

        Type float array of 2 items in [-inf, inf], default (0.0, 0.0), (readonly)
```

select
Selection state of the curve point
Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CurveMap.points

2.4.178 CurveMapping(bpy_struct)

base class — bpy_struct

class bpy.types.CurveMapping (*bpy_struct*)

Curve mapping to map color, vector and scalar values to other values using a user defined curve

black_level

For RGB curves, the color that black is mapped to

Type float array of 3 items in [-1000, 1000], default (0.0, 0.0, 0.0)

clip_max_x

Type float in [-100, 100], default 0.0

clip_max_y

Type float in [-100, 100], default 0.0

clip_min_x

Type float in [-100, 100], default 0.0

clip_min_y

Type float in [-100, 100], default 0.0

curves

Type bpy_prop_collection of CurveMap, (readonly)

use_clip

Force the curve view to fit a defined boundary

Type boolean, default False

white_level

For RGB curves, the color that white is mapped to

Type float array of 3 items in [-1000, 1000], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Brush.curve
- CompositorNodeCurveRGB.mapping
- CompositorNodeCurveVec.mapping
- CompositorNodeHueCorrect.mapping
- CompositorNodeTime.curve
- ParticleBrush.curve
- PointDensity.falloff_curve
- PointLamp.falloff_curve
- ShaderNodeRGBCurve.mapping
- ShaderNodeVectorCurve.mapping
- SpaceImageEditor.curve
- SpotLamp.falloff_curve

- `TextureNodeCurveRGB.mapping`
- `TextureNodeCurveTime.curve`
- `WarpModifier.falloff_curve`

2.4.179 CurveModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.CurveModifier(Modifier)

Curve deformation modifier

deform_axis

The axis that the curve deforms along

Type enum in [‘POS_X’, ‘POS_Y’, ‘POS_Z’, ‘NEG_X’, ‘NEG_Y’, ‘NEG_Z’], default ‘POS_X’

object

Curve object to deform with

Type `Object`

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.180 CurveSplines(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.CurveSplines` (`bpy_struct`)

Collection of curve splines

active

Active curve spline

Type `Object`

new (`type`)

Add a new spline to the curve.

Parameters `type` (*enum in ['POLY', 'BEZIER', 'BSPLINE', 'CARDINAL', 'NURBS']*) – type for the new spline.

Returns The newly created spline.

Return type `Spline`

remove (`spline`)

Remove a spline from a curve.

Parameters `spline` (`Spline`, (never None)) – The spline to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Curve.splines`

2.4.181 DampedTrackConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.DampedTrackConstraint (Constraint)

Points toward target by taking the shortest rotation path

subtarget

Type `string, default “”`

target

Target Object

Type `Object`

track_axis

Axis that points to the target object

Type `enum in [‘TRACK_X’, ‘TRACK_Y’, ‘TRACK_Z’, ‘TRACK_NEGATIVE_X’, ‘TRACK_NEGATIVE_Y’, ‘TRACK_NEGATIVE_Z’], default ‘TRACK_X’`

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`
- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.182 DecimateModifier(Modifier)

base classes — bpy_struct, Modifier

```
class bpy.types.DecimateModifier (Modifier)
    Decimation modifier

    face_count
        The current number of faces in the decimated mesh
        Type int in [-inf, inf], default 0, (readonly)

    ratio
        Defines the ratio of triangles to reduce to
        Type float in [0, 1], default 0.0
```

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.183 DelaySensor(Sensor)

base classes — `bpy_struct`, `Sensor`

class `bpy.types.DelaySensor` (`Sensor`)

Sensor to send delayed events

delay

Delay in number of logic tics before the positive trigger (default 60 per second)

Type int in [0, 5000], default 0

duration

If >0, delay in number of logic tics before the negative trigger following the positive trigger

Type int in [0, 5000], default 0

use_repeat

Toggle repeat option. If selected, the sensor restarts after Delay+Dur logic tics

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sensor.name`
- `Sensor.show_expanded`
- `Sensor.frequency`
- `Sensor.invert`
- `Sensor.use_level`
- `Sensor.pin`
- `Sensor.use_pulse_false_level`
- `Sensor.use_pulse_true_level`
- `Sensor.use_tap`
- `Sensor.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Sensor.link`
- `Sensor.unlink`

2.4.184 DisplaceModifier(Modifier)

base classes — `bpy_struct`, `Modifier`

class bpy.types.DisplaceModifier (Modifier)
Displacement modifier

direction
Type enum in ['X', 'Y', 'Z', 'NORMAL', 'RGB_TO_XYZ'], default 'X'

mid_level
Material value that gives no displacement
Type float in [-inf, inf], default 0.0

strength
Amount to displace geometry
Type float in [-inf, inf], default 0.0

texture
Type `Texture`

texture_coords
Type enum in ['LOCAL', 'GLOBAL', 'OBJECT', 'UV'], default 'LOCAL'

texture_coords_object
Object to set the texture coordinates
Type `Object`

uv_layer
UV layer name
Type string, default ""

vertex_group
Name of Vertex Group which determines influence of modifier per point
Type string, default ""

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.185 DistortedNoiseTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.**DistortedNoiseTexture** (*Texture*)

Procedural distorted noise texture

distortion

Amount of distortion

Type float in [0, 10], default 0.0

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_distortion

Sets the noise basis for the distortion

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.186 DomainFluidSettings(FluidSettings)

base classes — `bpy_struct`, `FluidSettings`

class bpy.types.DomainFluidSettings (FluidSettings)

Fluid simulation settings for the domain of a fluid simulation

compressibility

Allowed compressibility due to gravitational force for standing fluid. (directly affects simulation step size)

Type float in [0.001, 0.1], default 0.0

end_time

Simulation time of the last blender frame (in seconds)

Type float in [0, 100], default 0.0

filepath

Directory (and/or filename prefix) to store baked fluid simulation files in

Type string, default “”

fluid_mesh_vertices

Vertices of the fluid mesh generated by simulation

Type `bpy_prop_collection` of `FluidMeshVertex`, (readonly)

generate_particles

Amount of particles to generate (0=off, 1=normal, >1=more)

Type float in [0, 10], default 0.0

gravity

Gravity in X, Y and Z direction

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

grid_levels

Number of coarsened grids to use (-1 for automatic)

Type int in [-1, 4], default 0

memory_estimate

Estimated amount of memory needed for baking the domain

Type string, default “”, (readonly)

partial_slip_factor

Amount of mixing between no- and free-slip, 0 is no slip and 1 is free slip

Type float in [0, 1], default 0.0

preview_resolution

Preview resolution in X,Y and Z direction

Type int in [1, 100], default 0

render_display_mode

How to display the mesh for rendering

Type enum in ['GEOMETRY', 'PREVIEW', 'FINAL'], default 'GEOMETRY'

resolution

Domain resolution in X,Y and Z direction

Type int in [1, 1024], default 0

simulation_scale

Size of the simulation domain in metres

Type float in [0.001, 10], default 0.0

slip_type

Type enum in ['NOSLIP', 'PARTIALSLIP', 'FREESLIP'], default 'NOSLIP'

start_time

Simulation time of the first blender frame (in seconds)

Type float in [0, 100], default 0.0

surface_noobs

Type boolean, default False

surface_smooth

Amount of surface smoothing. A value of 0 is off, 1 is normal smoothing and more than 1 is extra smoothing

Type float in [0, 5], default 0.0

surface_subdivisions

Number of isosurface subdivisions. This is necessary for the inclusion of particles into the surface generation. Warning - can lead to longer computation times!

Type int in [0, 5], default 0

tracer_particles

Number of tracer particles to generate

Type int in [0, 10000], default 0

use_reverse_frames

Reverse fluid frames

Type boolean, default False

use_speed_vectors

Generate speed vectors for vector blur

Type boolean, default False

use_time_override

Use a custom start and end time (in seconds) instead of the scene's timeline

Type boolean, default False

viewport_display_mode

How to display the mesh in the viewport

Type enum in ['GEOMETRY', 'PREVIEW', 'FINAL'], default 'GEOMETRY'

viscosity_base

Viscosity setting: value that is multiplied by 10 to the power of (exponent*-1)

Type float in [0, 10], default 0.0

viscosity_exponent

Negative exponent for the viscosity value (to simplify entering small values e.g. 5*10^-6.)

Type int in [0, 10], default 0

viscosity_preset

Set viscosity of the fluid to a preset value, or use manual input

Type enum in ['MANUAL', 'WATER', 'OIL', 'HONEY'], default 'MANUAL'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.187 DopeSheet(bpy_struct)

base class — bpy_struct

class bpy.types.DopeSheet (*bpy_struct*)

Settings for filtering the channels shown in Animation Editors

filter_fcurve_name

F-Curve live filtering string

Type string, default ""

filter_group

Group that included Object should be a member of

Type Group

show_armatures

Include visualization of Armature related Animation data

Type boolean, default False

show_cameras

Include visualization of Camera related Animation data

Type boolean, default False

show_curves

Include visualization of Curve related Animation data

Type boolean, default False

show_expanded_summary

Collapse summary when shown, so all other channels get hidden. (DopeSheet Editors Only)

Type boolean, default False

show_hidden

Include channels from objects/bone that aren't visible

Type boolean, default False

show_lamps

Include visualization of Lamp related Animation data

Type boolean, default False

show_lattices

Include visualization of Lattice related Animation data

Type boolean, default False

show_materials

Include visualization of Material related Animation data

Type boolean, default False

show_meshes

Include visualization of Mesh related Animation data

Type boolean, default False

show_metaballs

Include visualization of Metaball related Animation data

Type boolean, default False

show_missing_nla

Include Animation Data blocks with no NLA data. (NLA Editor only)

Type boolean, default False

show_nodes

Include visualization of Node related Animation data

Type boolean, default False

show_only_group_objects

Only include channels from Objects in the specified Group

Type boolean, default False

show_only_matching_fcurves

Only include F-Curves with names containing search text

Type boolean, default False

show_only_selected

Only include channels relating to selected objects and data

Type boolean, default False

show_particles

Include visualization of Particle related Animation data

Type boolean, default False

show_scenes

Include visualization of Scene related Animation data

Type boolean, default False

show_shapekeys
Include visualization of ShapeKey related Animation data

Type boolean, default False

show_summary
Display an additional ‘summary’ line. (DopeSheet Editors only)

Type boolean, default False

show_textures
Include visualization of Texture related Animation data

Type boolean, default False

show_transforms
Include visualization of Object-level Animation data (mostly Transforms)

Type boolean, default False

show_worlds
Include visualization of World related Animation data

Type boolean, default False

source
ID-Block representing source data, currently ID_SCE (for Dopesheet), and ID_SC (for Grease Pencil)

Type [ID](#), (readonly)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- SpaceDopeSheetEditor.dopesheet
- SpaceGraphEditor.dopesheet
- SpaceNLA.dopesheet

2.4.188 Driver([bpy_struct](#))

base class — [bpy_struct](#)

class bpy.types.Driver (bpy_struct)

Driver for the value of a setting based on an external value

expression

Expression to use for Scripted Expression

Type string, default “”

is_valid

Driver could not be evaluated in past, so should be skipped

Type boolean, default False

show_debug_info

Show intermediate values for the driver calculations to allow debugging of drivers

Type boolean, default False

type

Driver type

Type enum in [‘AVERAGE’, ‘SUM’, ‘SCRIPTED’, ‘MIN’, ‘MAX’], default ‘AVERAGE’

variables

Properties acting as inputs for this driver

Type [ChannelDriverVariables](#) bpy_prop_collection of [DriverVariable](#),
(readonly)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.driver

2.4.189 DriverTarget(bpy_struct)

base class — bpy_struct

class bpy.types.DriverTarget (*bpy_struct*)

Source of input values for driver variables

bone_target

Name of PoseBone to use as target

Type string, default “”

data_path

RNA Path (from ID-block) to property used

Type string, default “”

id

ID-block that the specific property used can be found from (id_type property must be set first)

Type ID

id_type

Type of ID-block that can be used

Type enum in [‘ACTION’, ‘ARMATURE’, ‘BRUSH’, ‘CAMERA’, ‘CURVE’, ‘FONT’, ‘GREASEPENCIL’, ‘GROUP’, ‘IMAGE’, ‘KEY’, ‘LAMP’, ‘LIBRARY’, ‘LATTICE’, ‘MATERIAL’, ‘META’, ‘MESH’, ‘NODETREE’, ‘OBJECT’, ‘PARTICLE’, ‘SCENE’, ‘SCREEN’, ‘SOUND’, ‘TEXT’, ‘TEXTURE’, ‘WORLD’, ‘WINDOWMANAGER’], default ‘OBJECT’

transform_type

Driver variable type

Type enum in [‘LOC_X’, ‘LOC_Y’, ‘LOC_Z’, ‘ROT_X’, ‘ROT_Y’, ‘ROT_Z’, ‘SCALE_X’, ‘SCALE_Y’, ‘SCALE_Z’], default ‘LOC_X’

use_local_space_transform

Use transforms in Local Space (as opposed to the worldspace default)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `DriverVariable.targets`

2.4.190 DriverVariable(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.DriverVariable(bpy_struct)`

Variable from some source/target for driver relationship

name

Name to use in scripted expressions/functions. (No spaces or dots are allowed. Also, must not start with a symbol or digit)

Type string, default “”

targets

Sources of input data for evaluating this variable

Type `bpy_prop_collection of DriverTarget`, (readonly)

type

Driver variable type

Type enum in ['SINGLE_PROP', 'TRANSFORMS', 'ROTATION_DIFF', 'LOC_DIFF'], default 'SINGLE_PROP'

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ChannelDriverVariables.new`
- `ChannelDriverVariables.remove`
- `Driver.variables`

2.4.191 DupliObject(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.DupliObject` (`bpy_struct`)

An object duplicate

matrix

Object duplicate transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_original

The original matrix of this object before it was duplicated

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

object

Object being duplicated

Type `Object`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.dupli_list`

2.4.192 EdgeSplitModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.EdgeSplitModifier (Modifier)
Edge splitting modifier to create sharp edges

split_angle
Angle above which to split edges
Type float in [0, 3.14159], default 0.0

use_edge_angle
Split edges with high angle between faces
Type boolean, default False

use_edge_sharp
Split edges that are marked as sharp
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`

- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.193 EditBone(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.EditBone` (`bpy_struct`)
Editmode bone in an Armature datablock

bbone_in
Length of first Bezier Handle (for B-Bones only)
Type float in [0, 2], default 0.0

bbone_out
Length of second Bezier Handle (for B-Bones only)
Type float in [0, 2], default 0.0

bbone_segments
Number of subdivisions of bone (for B-Bones only)
Type int in [1, 32], default 0

bbone_x
B-Bone X size
Type float in [0, 1000], default 0.0

bbone_z
B-Bone Z size
Type float in [0, 1000], default 0.0

envelope_distance
Bone deformation distance (for Envelope deform only)
Type float in [0, 1000], default 0.0

envelope_weight

Bone deformation weight (for Envelope deform only)

Type float in [0, 1000], default 0.0

head

Location of head end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

head_radius

Radius of head of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

hide

Bone is not visible when in Edit Mode

Type boolean, default False

hide_select

Bone is able to be selected

Type boolean, default False

layers

Layers bone exists in

Type boolean array of 32 items, default (False, False, False)

lock

Bone is not able to be transformed when in Edit Mode

Type boolean, default False

matrix

Read-only matrix calculated from the roll (armature space)

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

name

Type string, default “”

parent

Parent edit bone (in same Armature)

Type `EditBone`

roll

Bone rotation around head-tail axis

Type float in [-inf, inf], default 0.0

select

Type boolean, default False

select_head

Type boolean, default False

select_tail

Type boolean, default False

show_wire
Bone is always drawn as Wireframe regardless of viewport draw mode. Useful for non-obstructive custom bone shapes

Type boolean, default False

tail
Location of tail end of the bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tail_radius
Radius of tail of bone (for Envelope deform only)

Type float in [0, inf], default 0.0

use_connect
When bone has a parent, bone's head is struck to the parent's tail

Type boolean, default False

use_cyclic_offset
When bone doesn't have a parent, it receives cyclic offset effects

Type boolean, default False

use_deform
Bone does not deform any geometry

Type boolean, default False

use_envelope_multiply
When deforming bone, multiply effects of Vertex Group weights with Envelope influence

Type boolean, default False

use_inherit_rotation
Bone inherits rotation or scale from parent bone

Type boolean, default False

use_inherit_scale
Bone inherits scaling from parent bone

Type boolean, default False

use_local_location
Bone location is set in local space

Type boolean, default False

basename
The name of this bone before any '.' character (readonly)

center
The midpoint between the head and the tail. (readonly)

children
A list of all the bones children. (readonly)

children_recursive
a list of all children from this bone. (readonly)

children_recursive_basename

Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned. (readonly)

length

The distance from head to tail, when set the head is moved to fit the length.

parent_recursive

A list of parents, starting with the immediate parent (readonly)

vector

The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis

Vector pointing down the x-axis of the bone. (readonly)

y_axis

Vector pointing down the x-axis of the bone. (readonly)

z_axis

Vector pointing down the x-axis of the bone. (readonly)

align_roll (vector)

Align the bone to a localspace roll so the Z axis points in the direction of the vector given.

Parameters **vector** (*float array of 3 items in [-inf, inf]*) – Vector

align_orientation (other)

Align this bone to another by moving its tail and settings its roll the length of the other bone is not used.

parent_index (parent_test)

The same as ‘bone in other_bone.parent_recursive’ but saved generating a list.

transform (matrix, scale=True, roll=True)

Transform the the bones head, tail, roll and envelope (when the matrix has a scale component).

Parameters

- **matrix** (`Matrix`) – 3x3 or 4x4 transformation matrix.
- **scale** (`bool`) – Scale the bone envelope by the matrix.
- **roll** (`bool`) – Correct the roll to point in the same relative direction to the head and tail.

translate (vec)

Utility function to add `vec` to the head and tail of this bone.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Armature.edit_bones
- ArmatureEditBones.active
- ArmatureEditBones.new
- ArmatureEditBones.remove
- EditBone.parent

2.4.194 EditObjectActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types>EditObjectActuator(Actuator)
Actuator used to edit objects

angular_velocity

Angular velocity upon creation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dynamic_operation

Type enum in ['RESTOREDYN', 'SUSPENDDYN', 'ENABLERIGIDBODY', 'DISABLE-RIGIDBODY', 'SETMASS'], default 'RESTOREDYN'

linear_velocity

Velocity upon creation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mass

The mass of the object

Type float in [-inf, inf], default 0.0

mesh

Replace the existing, when left blank 'Phys' will remake the existing physics mesh

Type Mesh

mode

The mode of the actuator

Type enum in ['ADDOBJECT', 'ENDOBJECT', 'REPLACEMESH', 'TRACKTO', 'DYNAMICS'], default 'ADDOBJECT'

object

Add this Object and all its children (cant be on an visible layer)

Type `Object`

time
Duration the new Object lives or the track takes
Type int in [-inf, inf], default 0

track_object
Track to this Object
Type `Object`

use_3d_tracking
Enable 3D tracking
Type boolean, default False

use_local_angular_velocity
Apply the rotation locally
Type boolean, default False

use_local_linear_velocity
Apply the transformation locally
Type boolean, default False

use_replace_display_mesh
Replace the display mesh
Type boolean, default False

use_replace_physics_mesh
Replace the physics mesh (triangle bounds only - compound shapes not supported)
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

2.4.195 EffectSequence(Sequence)

base classes — bpy_struct, Sequence

subclasses — GlowSequence, PluginSequence, ColorSequence, TransformSequence, WipeSequence, SpeedControlSequence

class bpy.types.EffectSequence (Sequence)

Sequence strip applying an effect on the images created by other strips

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

proxy

Type SequenceProxy, (readonly)

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop

Crop image before processing

Type boolean, default False

use_deinterlace

For video movies to remove fields

Type boolean, default False

use_flip_x

Flip on the X axis

Type boolean, default False

use_flip_y
Flip on the Y axis
Type boolean, default False

use_float
Convert input to float data
Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False

use_proxy
Use a preview proxy for this strip
Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from
Type boolean, default False

use_reverse_frames
Reverse frame order
Type boolean, default False

use_translation
Translate image before processing
Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle

- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.196 EffectorWeights(bpy_struct)

base class — bpy_struct

class bpy.types.EffectorWeights (*bpy_struct*)
Effector weights for physics simulation

all
All effector's weight
Type float in [-200, 200], default 0.0

apply_to_hair_growing
Use force fields when growing hair
Type boolean, default False

boid
Boid effector weight
Type float in [-200, 200], default 0.0

charge
Charge effector weight
Type float in [-200, 200], default 0.0

curve_guide

Curve guide effector weight

Type float in [-200, 200], default 0.0

drag

Drag effector weight

Type float in [-200, 200], default 0.0

force

Force effector weight

Type float in [-200, 200], default 0.0

gravity

Global gravity weight

Type float in [-200, 200], default 0.0

group

Limit effectors to this Group

Type [Group](#)

harmonic

Harmonic effector weight

Type float in [-200, 200], default 0.0

lennardjones

Lennard-Jones effector weight

Type float in [-200, 200], default 0.0

magnetic

Magnetic effector weight

Type float in [-200, 200], default 0.0

texture

Texture effector weight

Type float in [-200, 200], default 0.0

turbulence

Turbulence effector weight

Type float in [-200, 200], default 0.0

vortex

Vortex effector weight

Type float in [-200, 200], default 0.0

wind

Wind effector weight

Type float in [-200, 200], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ClothSettings.effector_weights`
- `ParticleSettings.effector_weights`
- `SmokeDomainSettings.effector_weights`
- `SoftBodySettings.effector_weights`

2.4.197 `EnumProperty(Property)`

base classes — `bpy_struct, Property`

class `bpy.types.EnumProperty(Property)`

RNA enumeration property definition, to choose from a number of predefined options

default

Default value for this enum

Type enum in ['DUMMY'], default 'DUMMY', (readonly)

default_flag

Default value for this enum

Type enum set in { 'DUMMY' }, default set(), (readonly)

enum_items

Possible values for the property

Type `bpy_prop_collection of EnumPropertyItem`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Property.name`
- `Property.srna`
- `Property.description`

- `Property.is_enum_flag`
- `Property.is_hidden`
- `Property.identifier`
- `Property.is_never_none`
- `Property.is_READONLY`
- `Property.is_registered`
- `Property.is_registered_optional`
- `Property.is_REQUIRED`
- `Property.is_output`
- `Property.is_runtime`
- `Property.is_SKIP_SAVE`
- `Property.subtype`
- `Property.type`
- `Property.unit`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.198 `EnumPropertyItem(bpy_struct)`

base class — `bpy_struct`

class `bpy.types.EnumPropertyItem(bpy_struct)`

Definition of a choice in an RNA enum property

description

Description of the item's purpose

Type string, default "", (readonly)

identifier

Unique name used in the code and scripting

Type string, default "", (readonly)

name

Human readable name

Type string, default "", (readonly)

value

Value of the item

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EnumProperty.enum_items

2.4.199 EnvironmentMap(bpy_struct)

base class — bpy_struct

class bpy.types.EnvironmentMap (*bpy_struct*)

Environment map created by the renderer and cached for subsequent renders

clip_end

Objects further than this are not visible to map

Type float in [0.01, inf], default 0.0

clip_start

Objects nearer than this are not visible to map

Type float in [0.001, inf], default 0.0

depth

Number of times a map will be rendered recursively (mirror effects.)

Type int in [0, 5], default 0

layers_ignore

Hide objects on these layers when generating the Environment Map

Type boolean array of 20 items, default (False, False, False)

mapping

Type enum in ['CUBE', 'PLANE'], default 'CUBE'

resolution

Pixel resolution of the rendered environment map

Type int in [50, 4096], default 0

source

Type enum in ['STATIC', 'ANIMATED', 'IMAGE_FILE'], default 'STATIC'

viewpoint_object

Object to use as the environment map's viewpoint location

Type Object

zoom

Type float in [0.1, 5], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- EnvironmentMapTexture.environment_map

2.4.200 EnvironmentMapTexture(Texture)

base classes — `bpy_struct`, `ID`, `Texture`

class bpy.types.EnvironmentMapTexture (Texture)
Environment map texture

environment_map
Gets the environment map associated with this texture

Type `EnvironmentMap`, (readonly)

filter_eccentricity
Maximum eccentricity. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_probes
Maximum number of samples. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

filter_size
Multiplies the filter size used by MIP Map and Interpolation

Type float in [0.1, 50], default 0.0

filter_type
Texture filter to use for sampling image

Type enum in ['BOX', 'EWA', 'FELINE', 'AREA'], default 'BOX'

image
Source image file to read the environment map from

Type `Image`

image_user
Parameters defining which layer, pass and frame of the image is displayed

Type `ImageUser`, (readonly)

use_filter_size_min
Use Filter Size as a minimal filter value in pixels

Type boolean, default False

use_mipmap
Uses auto-generated MIP maps for the image

Type boolean, default False

use_mipmap_gauss
Uses Gauss filter to sample down MIP maps

Type boolean, default False

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.201 Event(*bpy_struct*)

base class — *bpy_struct*

class bpy.types.**Event** (*bpy_struct*)

Window Manager Event

alt

True when the Alt/Option key is held

Type boolean, default False, (readonly)

ascii

Single ASCII character for this event

Type string, default "", (readonly)

ctrl

True when the Ctrl key is held

Type boolean, default False, (readonly)

mouse_prev_x

The window relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_prev_y

The window relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_region_x

The region relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_region_y

The region relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_x

The window relative vertical location of the mouse

Type int in [-inf, inf], default 0, (readonly)

mouse_y

The window relative horizontal location of the mouse

Type int in [-inf, inf], default 0, (readonly)

oskey

True when the Cmd key is held

Type boolean, default False, (readonly)

shift

True when the Shift key is held

Type boolean, default False, (readonly)

type

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSEROTATE', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE', (readonly)

value

The type of event, only applies to some

Type enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK'], default 'NOTHING', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Operator.invoke`
- `Operator.modal`
- `WindowManager.invoke_confirm`
- `WindowManager.invoke_props_popup`

2.4.202 ExplodeModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.ExplodeModifier(*Modifier*)
Explosion effect modifier based on a particle system

particle_uv
UV Layer to change with particle age
Type string, default “”

protect
Clean vertex group edges
Type float in [0, 1], default 0.0

show_alive
Show mesh when particles are alive
Type boolean, default False

show_dead
Show mesh when particles are dead
Type boolean, default False

show_unborn
Show mesh when particles are unborn
Type boolean, default False

use_edge_cut
Cut face edges for nicer shrapnel
Type boolean, default False

use_size
Use particle size for the shrapnel
Type boolean, default False

vertex_group
Type string, default “”

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`

- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.203 ExpressionController(Controller)

base classes — `bpy_struct, Controller`

class bpy.types.ExpressionController(Controller)
Controller passing on events based on the evaluation of an expression
expression
Type string, default “”

Inherited Properties

- `bpy_struct.id_data`
- `Controller.name`
- `Controller.states`
- `Controller.show_expanded`
- `Controller.use_priority`
- `Controller.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.204 FCurve(bpy_struct)

base class — `bpy_struct`

class bpy.types.FCurve (*bpy_struct*)

F-Curve defining values of a period of time

array_index

Index to the specific property affected by F-Curve if applicable

Type int in [-inf, inf], default 0

color

Color of the F-Curve in the Graph Editor

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color_mode

Method used to determine color of F-Curve in Graph Editor

Type enum in ['AUTO_RAINBOW', 'AUTO_RGB', 'CUSTOM'], default 'AUTO_RAINBOW'

data_path

RNA Path to property affected by F-Curve

Type string, default ""

driver

Channel Driver (only set for Driver F-Curves)

Type `Driver`, (readonly)

extrapolation

Type enum in ['CONSTANT', 'LINEAR'], default 'CONSTANT'

group

Action Group that this F-Curve belongs to

Type `ActionGroup`

hide

F-Curve and its keyframes are hidden in the Graph Editor graphs

Type boolean, default False

is_valid

False when F-Curve could not be evaluated in past, so should be skipped when evaluating

Type boolean, default False

keyframe_points
User-editable keyframes

Type `FCurveKeyframePoints bpy_prop_collection of Keyframe`, (readonly)

lock
F-Curve's settings cannot be edited

Type boolean, default False

modifiers
Modifiers affecting the shape of the F-Curve

Type `FCurveModifiers bpy_prop_collection of FModifier`, (readonly)

mute
F-Curve is not evaluated

Type boolean, default False

samplesd_points
Sampled animation data

Type `bpy_prop_collection of FCurveSample`, (readonly)

select
F-Curve is selected for editing

Type boolean, default False

use_auto_handle_clamp
All auto-handles for F-Curve are clamped

Type boolean, default False

evaluate (frame)
Evaluate fcurve.

Parameters `frame (float in [-inf, inf])` – Frame, Evaluate fcurve at given frame

Returns Position, FCurve position

Return type float in [-inf, inf]

range ()
Get the time extents for F-Curve.

Returns Range, Min/Max values

Return type float array of 2 items in [-inf, inf]

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.fcurves
- ActionFCurves.new
- ActionFCurves.remove
- ActionGroup.channels
- AnimData.drivers
- AnimDataDrivers.from_existing
- AnimDataDrivers.from_existing
- NlaStrip.fcurves

2.4.205 FCurveActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.FCurveActuator (*Actuator*)

Actuator to animate the object

apply_to_children

Update F-Curve on all children Objects as well

Type boolean, default False

frame_end

Type float in [-inf, inf], default 0.0

frame_property

Assign the action's current frame number to this property

Type string, default “”

frame_start

Type float in [-inf, inf], default 0.0

play_type

Specify the way you want to play the animation

Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'STOP', 'END', 'PROP'], default 'PLAY'

property

Use this property to define the F-Curve position

Type string, default “”

use_additive

F-Curve is added to the current loc/rot/scale in global or local coordinate according to Local flag

Type boolean, default False

use_force

Apply F-Curve as a global or local force depending on the local option (dynamic objects only)

Type boolean, default False

use_local

Let the F-Curve act in local coordinates, used in Force and Add mode

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.206 FCurveKeyframePoints(bpy_struct)

base class — `bpy_struct`

class bpy.types.FCurveKeyframePoints (bpy_struct)

Collection of keyframe points

insert (frame, value, options=set())

Add a keyframe point to a F-Curve.

Parameters

- **frame** (*float in [-inf, inf]*) – X Value of this keyframe point
- **value** (*float in [-inf, inf]*) – Y Value of this keyframe point
- **options** (*enum set in {‘REPLACE’, ‘NEEDED’, ‘FAST’}, (optional)*) – Keyframe options.

Returns Newly created keyframe

Return type [Keyframe](#)

add (*count=1*)

Add a keyframe point to a F-Curve.

Parameters **count** (*int in [1, inf], (optional)*) – Number, Number of points to add to the spline

remove (*keyframe, fast=False*)

Remove keyframe from an fcurve.

Parameters

- **keyframe** ([Keyframe](#), (never None)) – Keyframe to remove.
- **fast** (*boolean, (optional)*) – Fast, Fast keyframe removal to avoid recalculating the curve each time

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [FCurve.keyframe_points](#)

2.4.207 FCurveModifiers([bpy_struct](#))

base class — [bpy_struct](#)

```
class bpy.types.FCurveModifiers (bpy_struct)
    Collection of F-Curve Modifiers

    active
        Active F-Curve Modifier

        Type FModifier

    new(type)
        Add a constraint to this object

        Parameters type (enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED']) – Constraint type to add.

        Returns New fmodifier.

        Return type FModifier

    remove(modifier)
        Remove a modifier from this fcurve.

        Parameters modifier (FModifier, (never None)) – Removed modifier.
```

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [FCurve.modifiers](#)

2.4.208 FCurveSample(bpy_struct)

base class — [bpy_struct](#)

```
class bpy.types.FCurveSample(bpy_struct)
    Sample point for F-Curve

    co
        Point coordinates
            Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

    select
        Selection status
            Type boolean, default False
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FCurve.sampled_points

2.4.209 FModifier(bpy_struct)

```
base class — bpy_struct

subclasses — FModifierCycles, FModifierPython, FModifierFunctionGenerator,
FModifierLimits, FModifierEnvelope, FModifierNoise, FModifierStepped,
FModifierGenerator

class bpy.types.FModifier(bpy_struct)
    Modifier for values of F-Curve

    active
        F-Curve Modifier is the one being edited
```

Type boolean, default False

is_valid

F-Curve Modifier has invalid settings and will not be evaluated

Type boolean, default False, (readonly)

mute

F-Curve Modifier will not be evaluated

Type boolean, default False

show_expanded

F-Curve Modifier's panel is expanded in UI

Type boolean, default False

type

F-Curve Modifier Type

Type enum in ['NULL', 'GENERATOR', 'FNGENERATOR', 'ENVELOPE', 'CYCLES', 'NOISE', 'FILTER', 'LIMITS', 'STEPPED'], default 'NULL', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `FCurve.modifiers`
- `FCurveModifiers.active`
- `FCurveModifiers.new`
- `FCurveModifiers.remove`
- `NlaStrip.modifiers`

2.4.210 FModifierCycles(FModifier)

base classes — `bpy_struct`, `FModifier`

`class bpy.types.FModifierCycles(FModifier)`

Repeats the values of the modified F-Curve

`cycles_after`

Maximum number of cycles to allow after last keyframe. (0 = infinite)

Type int in [-32768, 32767], default 0

`cycles_before`

Maximum number of cycles to allow before first keyframe. (0 = infinite)

Type int in [-32768, 32767], default 0

`mode_after`

Cycling mode to use after last keyframe

Type enum in ['NONE', 'REPEAT', 'REPEAT_OFFSET', 'MIRROR'], default 'NONE'

`mode_before`

Cycling mode to use before first keyframe

Type enum in ['NONE', 'REPEAT', 'REPEAT_OFFSET', 'MIRROR'], default 'NONE'

Inherited Properties

- `bpy_struct.id_data`
- `FModifier.active`
- `FModifier.is_valid`
- `FModifier.show_expanded`
- `FModifier.mute`
- `FModifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.211 FModifierEnvelope(FModifier)

base classes — `bpy_struct`, `FModifier`

class `bpy.types.FModifierEnvelope` (*FModifier*)

Scales the values of the modified F-Curve

control_points

Control points defining the shape of the envelope

Type `bpy_prop_collection` of `FModifierEnvelopeControlPoint`, (readonly)

default_max

Upper distance from Reference Value for 1:1 default influence

Type float in [-inf, inf], default 0.0

default_min

Lower distance from Reference Value for 1:1 default influence

Type float in [-inf, inf], default 0.0

reference_value

Value that envelope's influence is centered around / based on

Type float in [-inf, inf], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `FModifier.active`
- `FModifier.is_valid`
- `FModifier.show_expanded`
- `FModifier.mute`
- `FModifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.212 FModifierEnvelopeControlPoint(bpy_struct)

base class — `bpy_struct`

`class bpy.types.FModifierEnvelopeControlPoint (bpy_struct)`

Control point for envelope F-Modifier

`frame`

Frame this control-point occurs on

Type float in [-inf, inf], default 0.0

`max`

Upper bound of envelope at this control-point

Type float in [-inf, inf], default 0.0

`min`

Lower bound of envelope at this control-point

Type float in [-inf, inf], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `FModifierEnvelope.control_points`

2.4.213 FModifierFunctionGenerator(FModifier)

base classes — `bpy_struct, FModifier`

```
class bpy.types.FModifierFunctionGenerator(FModifier)
    Generates values using a Built-In Function

    amplitude
        Scale factor determining the maximum/minimum values
        Type float in [-inf, inf], default 0.0

    function_type
        Type of built-in function to use
        Type enum in ['SIN', 'COS', 'TAN', 'SQRT', 'LN', 'SINC'], default 'SIN'

    phase_multiplier
        Scale factor determining the 'speed' of the function
        Type float in [-inf, inf], default 0.0

    phase_offset
        Constant factor to offset time by for function
        Type float in [-inf, inf], default 0.0

    use_additive
        Values generated by this modifier are applied on top of the existing values instead of overwriting them
        Type boolean, default False

    value_offset
        Constant factor to offset values by
        Type float in [-inf, inf], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`
- `FModifier.active`
- `FModifier.is_valid`
- `FModifier.show_expanded`
- `FModifier.mute`
- `FModifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- bpy_struct.type_recast
- bpy_struct.values

2.4.214 FModifierGenerator(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.FModifierGenerator (FModifier)

Deterministically generates values for the modified F-Curve

coefficients

Coefficients for ‘x’ (starting from lowest power of x^0)

Type float array of 32 items in [-inf, inf], default (0.0, 0.0)

mode

Type of generator to use

Type enum in ['POLYNOMIAL', 'POLYNOMIAL_FACTORISED'], default 'POLYNOMIAL'

poly_order

The highest power of ‘x’ for this polynomial. (number of coefficients - 1)

Type int in [-inf, inf], default 0

use_additive

Values generated by this modifier are applied on top of the existing values instead of overwriting them

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.215 FModifierLimits(FModifier)

base classes — `bpy_struct`, `FModifier`

class bpy.types.FModifierLimits (*FModifier*)

Limits the time/value ranges of the modified F-Curve

max_x

Highest X value to allow

Type float in [-inf, inf], default 0.0

max_y

Highest Y value to allow

Type float in [-inf, inf], default 0.0

min_x

Lowest X value to allow

Type float in [-inf, inf], default 0.0

min_y

Lowest Y value to allow

Type float in [-inf, inf], default 0.0

use_max_x

Use the maximum X value

Type boolean, default False

use_max_y

Use the maximum Y value

Type boolean, default False

use_min_x

Use the minimum X value

Type boolean, default False

use_min_y

Use the minimum Y value

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.216 FModifierNoise(FModifier)

base classes — `bpy_struct, FModifier`

class bpy.types.FModifierNoise (FModifier)

Gives randomness to the modified F-Curve

blend_type

Method of modifying the existing F-Curve

Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULTIPLY'], default 'REPLACE'

depth

Amount of fine level detail present in the noise

Type int in [0, 32767], default 0

phase

A random seed for the noise effect

Type float in [-inf, inf], default 0.0

scale

Scaling (in time) of the noise

Type float in [-inf, inf], default 0.0

strength

Amplitude of the noise - the amount that it modifies the underlying curve

Type float in [-inf, inf], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `FModifier.active`
- `FModifier.is_valid`
- `FModifier.show_expanded`

- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.217 FModifierPython(FModifier)

base classes — bpy_struct, FModifier

class bpy.types.FModifierPython (FModifier)

Performs user-defined operation on the modified F-Curve

Inherited Properties

- bpy_struct.id_data
- FModifier.active
- FModifier.is_valid
- FModifier.show_expanded
- FModifier.mute
- FModifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert

- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.218 FModifierStepped(FModifier)

base classes — `bpy_struct, FModifier`

class bpy.types.FModifierStepped (FModifier)

Holds each interpolated value from the F-Curve for several frames without changing the timing

frame_end

Frame that modifier's influence ends (if applicable)

Type float in [-inf, inf], default 0.0

frame_offset

Reference number of frames before frames get held. Use to get hold for ‘1-3’ vs ‘5-7’ holding patterns

Type float in [-inf, inf], default 0.0

frame_start

Frame that modifier's influence starts (if applicable)

Type float in [-inf, inf], default 0.0

frame_step

Number of frames to hold each value

Type float in [-inf, inf], default 0.0

use_frame_end

Restrict modifier to only act before its ‘end’ frame

Type boolean, default False

use_frame_start

Restrict modifier to only act after its ‘start’ frame

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `FModifier.active`
- `FModifier.is_valid`
- `FModifier.show_expanded`
- `FModifier.mute`
- `FModifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.219 FieldSettings(bpy_struct)

base class — bpy_struct

class bpy.types.FieldSettings (bpy_struct)
Field settings for an object in physics simulation

apply_to_location
Effect particles' location
Type boolean, default False

apply_to_rotation
Effect particles' dynamic rotation
Type boolean, default False

distance_max
Maximum distance for the field to work
Type float in [0, 1000], default 0.0

distance_min
Minimum distance for the field's fall-off
Type float in [0, 1000], default 0.0

falloff_power
Falloff power (real gravitational falloff = 2)
Type float in [0, 10], default 0.0

falloff_type
Type enum in ['SPHERE', 'TUBE', 'CONE'], default 'SPHERE'

flow
Convert effector force into air flow velocity
Type float in [0, 10], default 0.0

guide_clump_amount
Amount of clumping
Type float in [-1, 1], default 0.0

guide_clump_shape
Shape of clumping
Type float in [-0.999, 0.999], default 0.0

guide_free

Guide-free time from particle life's end

Type float in [0, 0.99], default 0.0

guide_kink_amplitude

The amplitude of the offset

Type float in [0, 10], default 0.0

guide_kink_axis

Which axis to use for offset

Type enum in ['X', 'Y', 'Z'], default 'X'

guide_kink_frequency

The frequency of the offset (1/total length)

Type float in [0, 10], default 0.0

guide_kink_shape

Adjust the offset to the beginning/end

Type float in [-0.999, 0.999], default 0.0

guide_kink_type

Type of periodic offset on the curve

Type enum in ['NONE', 'CURL', 'RADIAL', 'WAVE', 'BRAID', 'ROTATION', 'ROLL'], default 'NONE'

guide_minimum

The distance from which particles are affected fully

Type float in [0, 1000], default 0.0

harmonic_damping

Damping of the harmonic force

Type float in [0, 10], default 0.0

inflow

Inwards component of the vortex force

Type float in [-10, 10], default 0.0

linear_drag

Drag component proportional to velocity

Type float in [-2, 2], default 0.0

noise

Amount of noise for the force strength

Type float in [0, 10], default 0.0

quadratic_drag

Drag component proportional to the square of velocity

Type float in [-2, 2], default 0.0

radial_falloff

Radial falloff power (real gravitational falloff = 2)

Type float in [0, 10], default 0.0

radial_max

Maximum radial distance for the field to work

Type float in [0, 1000], default 0.0

radial_min

Minimum radial distance for the field's fall-off

Type float in [0, 1000], default 0.0

rest_length

Rest length of the harmonic force

Type float in [0, 1000], default 0.0

seed

Seed of the noise

Type int in [1, 128], default 0

shape

Which direction is used to calculate the effector force

Type enum in ['POINT', 'PLANE', 'SURFACE', 'POINTS'], default 'POINT'

size

Size of the turbulence

Type float in [0, 10], default 0.0

strength

Strength of force field

Type float in [-1000, 1000], default 0.0

texture

Texture to use as force

Type Texture

texture_mode

How the texture effect is calculated (RGB & Curl need a RGB texture else Gradient will be used instead)

Type enum in ['RGB', 'GRADIENT', 'CURL'], default 'RGB'

texture_nabla

Defines size of derivative offset used for calculating gradient and curl

Type float in [0.0001, 1], default 0.0

type

Type of field

Type enum in ['NONE', 'FORCE', 'WIND', 'VORTEX', 'MAGNET', 'HARMONIC', 'CHARGE', 'LENNARDJ', 'TEXTURE', 'GUIDE', 'BOID', 'TURBULENCE', 'DRAG'], default 'NONE'

use_2d_force

Apply force only in 2d

Type boolean, default False

use_absorption

Force gets absorbed by collision objects

Type boolean, default False

use_global_coords

Use effector/global coordinates for turbulence

Type boolean, default False

use_guide_path_add

Based on distance/falloff it adds a portion of the entire path

Type boolean, default False

use_guide_path_weight

Use curve weights to influence the particle influence along the curve

Type boolean, default False

use_max_distance

Use a maximum distance for the field to work

Type boolean, default False

use_min_distance

Use a minimum distance for the field's fall-off

Type boolean, default False

use_multiple_springs

Every point is effected by multiple springs

Type boolean, default False

use_object_coords

Use object/global coordinates for texture

Type boolean, default False

use_radial_max

Use a maximum radial distance for the field to work

Type boolean, default False

use_radial_min

Use a minimum radial distance for the field's fall-off

Type boolean, default False

use_root_coords

Texture coordinates from root particle locations

Type boolean, default False

z_direction

Effect in full or only positive/negative Z direction

Type enum in ['BOTH', 'POSITIVE', 'NEGATIVE'], default 'BOTH'

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.field
- ParticleSettings.force_field_1
- ParticleSettings.force_field_2

2.4.220 FileSelectParams(bpy_struct)

base class — bpy_struct

class bpy.types.FileSelectParams (bpy_struct)
File Select Parameters

directory
Directory displayed in the file browser
Type string, default “”

display_type
Display mode for the file list
Type enum in ['FILE_SHORTDISPLAY', 'FILE_LONGDISPLAY', 'FILE_IMGDISPLAY'],
default 'FILE_SHORTDISPLAY'

filename
Active file in the file browser
Type string, default “”

filter_glob
Type string, default “”

show_hidden
Show hidden dot files
Type boolean, default False

sort_method
Type enum in ['FILE_SORT_ALPHA', 'FILE_SORT_EXTENSION', 'FILE_SORT_TIME',
'FILE_SORT_SIZE'], default 'FILE_SORT_ALPHA'

title
Title for the file browser
Type string, default "", (readonly)

use_filter
Enable filtering of files
Type boolean, default False

use_filter_blender
Show .blend files
Type boolean, default False

use_filter_folder
Show folders
Type boolean, default False

use_filter_font
Show font files
Type boolean, default False

use_filter_image
Show image files
Type boolean, default False

use_filter_movie
Show movie files
Type boolean, default False

use_filter_script
Show script files
Type boolean, default False

use_filter_sound
Show sound files
Type boolean, default False

use_filter_text
Show text files
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceFileBrowser.params

2.4.221 Filter2DActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.Filter2DActuator(Actuator)
Actuator to apply screen graphic effects

filter_pass
Set filter order
Type int in [0, 99], default 0

glsl_shader
Type Text

mode
Type enum in ['ENABLE', 'DISABLE', 'REMOVE', 'MOTIONBLUR', 'BLUR', 'SHARPEN', 'DILATION', 'EROSION', 'LAPLACIAN', 'SOBEL', 'PREWITT', 'GRAYSCALE', 'SEPIA', 'INVERT', 'CUSTOMFILTER'], default 'REMOVE'

motion_blur_factor
Set motion blur factor
Type float in [0, 1], default 0.0

use_motion_blur
Enable/Disable Motion Blur
Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.222 FloatProperty(Property)

base classes — `bpy_struct, Property`

class bpy.types.FloatProperty(*Property*)
RNA floating pointer number property definition

array_length

Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default

Default value for this number

Type float in [-inf, inf], default 0.0, (readonly)

default_array

Default value for this array

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

hard_max

Maximum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

hard_min

Minimum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

precision

Number of digits after the dot used by buttons

Type int in [0, inf], default 0, (readonly)

soft_max

Maximum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

soft_min

Minimum value used by buttons

Type float in [-inf, inf], default 0.0, (readonly)

step

Step size used by number buttons, for floats 1/100th of the step size

Type float in [0, inf], default 0.0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.is_runtime
- Property.is_skip_save
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.223 FloorConstraint(Constraint)

base classes — `bpy_struct`, `Constraint`

`class bpy.types.FloorConstraint(Constraint)`

Uses the target object for location limitation

floor_location

Location of target that object will not pass through

Type enum in ['FLOOR_X', 'FLOOR_Y', 'FLOOR_Z', 'FLOOR_NEGATIVE_X', 'FLOOR_NEGATIVE_Y', 'FLOOR_NEGATIVE_Z'], default 'FLOOR_X'

offset

Offset of floor from object origin

Type float in [0, 100], default 0.0

subtarget

Type string, default ""

target

Target Object

Type `Object`

use_rotation

Use the target's rotation to determine floor

Type boolean, default False

use_sticky

Immobilize object while constrained

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`
- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.224 FluidFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.FluidFluidSettings (FluidSettings)

Fluid simulation settings for the fluid in the simulation

initial_velocity

Initial velocity of fluid

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_INITIALIZATION

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.225 FluidMeshVertex(bpy_struct)

base class — bpy_struct

class bpy.types.**FluidMeshVertex** (*bpy_struct*)

Vertex of a simulated fluid mesh

velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- DomainFluidSettings.fluid_mesh_vertices

2.4.226 FluidSettings(bpy_struct)

base class — bpy_struct

```
subclasses — FluidFluidSettings, DomainFluidSettings, ControlFluidSettings,
InflowFluidSettings, ObstacleFluidSettings, ParticleFluidSettings,
OutflowFluidSettings

class bpy.types.FluidSettings (bpy_struct)
    Fluid simulation settings for an object taking part in the simulation

    type
        Type of participation in the fluid simulation
        Type enum in ['NONE', 'DOMAIN', 'FLUID', 'OBSTACLE', 'INFLOW', 'OUTFLOW',
        'PARTICLE', 'CONTROL'], default 'NONE'
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- FluidSimulationModifier.settings

2.4.227 FluidSimulationModifier(Modifier)

base classes — bpy_struct, Modifier

```
class bpy.types.FluidSimulationModifier (Modifier)
    Fluid simulation modifier

    settings
        Settings for how this object is used in the fluid simulation
        Type FluidSettings, (readonly, never None)
```

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.228 FollowPathConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.FollowPathConstraint (Constraint)

Locks motion to the target path

forward_axis

Axis that points forward along the path

Type enum in ['FORWARD_X', 'FORWARD_Y', 'FORWARD_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'FORWARD_X'

offset

Offset from the position corresponding to the time frame

Type float in [-300000, 300000], default 0.0

offset_factor

Percentage value defining target position along length of bone

Type float in [0, 1], default 0.0

target

Target Object

Type [Object](#)**up_axis**

Axis that points upward

Type enum in ['UP_X', 'UP_Y', 'UP_Z'], default 'UP_X'**use_curve_follow**

Object will follow the heading and banking of the curve

Type boolean, default False**use_curve_radius**

Objects scale by the curve radius

Type boolean, default False**use_fixed_location**

Object will stay locked to a single point somewhere along the length of the curve regardless of time

Type boolean, default False**Inherited Properties**

- [bpy_struct.id_data](#)
- [Constraint.name](#)
- [Constraint.active](#)
- [Constraint.mute](#)
- [Constraint.show_expanded](#)
- [Constraint.influence](#)
- [Constraint.error_location](#)
- [Constraint.owner_space](#)
- [Constraint.is_proxy_local](#)
- [Constraint.error_rotation](#)
- [Constraint.target_space](#)
- [Constraint.type](#)
- [Constraint.is_valid](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.229 Function(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.Function(bpy_struct)`

RNA function definition

description

Description of the Function's purpose

Type string, default "", (readonly)

identifier

Unique name used in the code and scripting

Type string, default "", (readonly)

is_registered

Function is registered as callback as part of type registration

Type boolean, default False, (readonly)

is_registered_optional

Function is optionally registered as callback part of type registration

Type boolean, default False, (readonly)

parameters

Parameters for the function

Type `bpy_prop_collection` of `Property`, (readonly)

use_self

Function does not pass its self as an argument (becomes a class method in python)

Type boolean, default False, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Struct.functions`

2.4.230 GPencilFrame(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.GPencilFrame` (`bpy_struct`)

Collection of related sketches on a particular frame

frame_number

The frame on which this sketch appears

Type int in [0, 300000], default 0

is_edited

Frame is being edited (painted on)

Type boolean, default False

select

Frame is selected for editing in the DopeSheet

Type boolean, default False

strokes

Freehand curves defining the sketch on this frame

Type `bpy_prop_collection` of `GPencilStroke`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `GPencilLayer.active_frame`
- `GPencilLayer.frames`

2.4.231 GPencilLayer(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.GPencilLayer` (`bpy_struct`)

Collection of related sketches

active_frame

Frame currently being displayed for this layer

Type `GPencilFrame`, (readonly)

alpha

Layer Opacity

Type float in [0.3, 1], default 0.0

color

Color for all strokes in this layer

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

frames

Sketches for this layer on different frames

Type `bpy_prop_collection` of `GPencilFrame`, (readonly)

ghost_range_max

Maximum number of frames on either side of the active frame to show (0 = show the ‘first’ available sketch on either side)

Type int in [0, 120], default 0

hide

Set layer Visibility

Type boolean, default False

info

Layer name

Type string, default “”

line_width

Thickness of strokes (in pixels)

Type int in [1, 10], default 0

lock

Protect layer from further editing and/or frame changes

Type boolean, default False

lock_frame

Lock current frame displayed by layer

Type boolean, default False

select

Layer is selected for editing in the DopeSheet

Type boolean, default False

show_points

Draw the points which make up the strokes (for debugging purposes)

Type boolean, default False

show_x_ray

Type boolean, default False

use_onion_skinning

Ghost frames on either side of frame

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GreasePencil.layers

2.4.232 GPencilStroke(bpy_struct)

base class — bpy_struct

```
class bpy.types.GPencilStroke(bpy_struct)
    Freehand curve defining part of a sketch

    points
        Stroke data points

    Type bpy_prop_collection of GPencilStrokePoint, (readonly)
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GPencilFrame.strokes

2.4.233 GPencilStrokePoint(bpy_struct)

base class — bpy_struct

```
class bpy.types.GPencilStrokePoint(bpy_struct)
    Data point for freehand stroke curve

    co
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    pressure
        Pressure of tablet at point when drawing it
        Type float in [0, 1], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `GPencilStroke.points`

2.4.234 GameActuator(Actuator)

base classes — `bpy_struct`, `Actuator`

`class bpy.types.GameActuator(Actuator)`

`filename`

Load this blend file, use the “//” prefix for a path relative to the current blend file

Type `string`, default “”

`mode`

Type `enum` in [‘START’, ‘RESTART’, ‘QUIT’, ‘SAVECFG’, ‘LOADCFG’], default ‘START’

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.235 GameBooleanProperty(GameProperty)

base classes — `bpy_struct, GameProperty`

class bpy.types.GameBooleanProperty (GameProperty)
Game engine user defined Boolean property

value
Property value

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `GameProperty.name`
- `GameProperty.show_debug`
- `GameProperty.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.236 GameFloatProperty(GameProperty)

base classes — `bpy_struct`, `GameProperty`

class bpy.types.GameFloatProperty (GameProperty)
Game engine user defined floating pointer number property

value
Property value

Type float in [-10000, 10000], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `GameProperty.name`
- `GameProperty.show_debug`
- `GameProperty.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.237 GameIntProperty(GameProperty)

base classes — `bpy_struct`, `GameProperty`

class bpy.types.GameIntProperty (GameProperty)
Game engine user defined integer number property

value

Property value

Type int in [-10000, 10000], default 0

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.238 GameObjectSettings(bpy_struct)

base class — bpy_struct

class bpy.types.GameObjectSettings (*bpy_struct*)

Game engine related settings for the object

actuators

Game engine actuators to act on events

Type bpy_prop_collection of Actuator, (readonly)

collision_bounds_type

Selects the collision type

Type enum in ['BOX', 'SPHERE', 'CYLINDER', 'CONE', 'CONVEX_HULL', 'TRIANGLE_MESH', 'CAPSULE'], default 'BOX'

collision_margin

Extra margin around object for collision detection, small amount required for stability

Type float in [0, 1], default 0.0

controllers

Game engine controllers to process events, connecting sensor to actuators

Type bpy_prop_collection of Controller, (readonly)

damping
General movement damping

Type float in [0, 1], default 0.0

form_factor
Form factor scales the inertia tensor

Type float in [0, 1], default 0.0

friction_coefficients
Relative friction coefficient in the in the X, Y and Z directions, when anisotropic friction is enabled

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

lock_location_x
Disable simulation of linear motion along the X axis

Type boolean, default False

lock_location_y
Disable simulation of linear motion along the Y axis

Type boolean, default False

lock_location_z
Disable simulation of linear motion along the Z axis

Type boolean, default False

lock_rotation_x
Disable simulation of angular motion along the X axis

Type boolean, default False

lock_rotation_y
Disable simulation of angular motion along the Y axis

Type boolean, default False

lock_rotation_z
Disable simulation of angular motion along the Z axis

Type boolean, default False

mass
Mass of the object

Type float in [0.01, 10000], default 0.0

physics_type
Selects the type of physical representation

Type enum in ['NO_COLLISION', 'STATIC', 'DYNAMIC', 'RIGID_BODY', 'SOFT_BODY', 'OCCLUDE', 'SENSOR'], default 'NO_COLLISION'

properties
Game engine properties

Type bpy_prop_collection of GameProperty, (readonly)

radius
Radius of bounding sphere and material physics

Type float in [0.01, 10], default 0.0

rotation_damping

General rotation damping

Type float in [0, 1], default 0.0

sensors

Game engine sensor to detect events

Type `bpy_prop_collection` of `Sensor`, (readonly)

show_actuators

Shows actuators for this object in the user interface

Type boolean, default False

show_controllers

Shows controllers for this object in the user interface

Type boolean, default False

show_debug_state

Print state debug info in the game engine

Type boolean, default False

show_sensors

Shows sensors for this object in the user interface

Type boolean, default False

show_state_panel

Show state panel

Type boolean, default False

soft_body

Settings for Bullet soft body simulation

Type `GameSoftBodySettings`, (readonly)

states_initial

Initial state when the game starts

Type boolean array of 30 items, default (False, False, False)

states_visible

State determining which controllers are displayed

Type boolean array of 30 items, default (False, False, False)

use_activity_culling

Disable simulation of angular motion along the Z axis

Type boolean, default False

use_actor

Object is detected by the Near and Radar sensor

Type boolean, default False

use_all_states

Set all state bits

Type boolean, default False

use_anisotropic_friction
Enable anisotropic friction

Type boolean, default False

use_collision_bounds
Specify a collision bounds type other than the default

Type boolean, default False

use_collision_compound
Add children to form a compound collision object

Type boolean, default False

use_ghost
Object does not reconstitute collisions, like a ghost

Type boolean, default False

use_material_physics_fh
React to force field physics settings in materials

Type boolean, default False

use_rotate_from_normal
Use face normal to rotate object, so that it points away from the surface

Type boolean, default False

use_sleep
Disable auto (de)activation in physics simulation

Type boolean, default False

used_states
States which are being used by controllers

Type boolean array of 30 items, default (False, False, False), (readonly)

velocity_max
Clamp velocity to this maximum speed

Type float in [0, 1000], default 0.0

velocity_min
Clamp velocity to this minimum speed (except when totally still)

Type float in [0, 1000], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.game

2.4.239 GameProperty(bpy_struct)

base class — bpy_struct
subclasses — GameStringProperty, GameIntProperty, GameBooleanProperty, GameFloatProperty, GameTimerProperty

class bpy.types.GameProperty(bpy_struct)
Game engine user defined object property

name
Available as GameObject attributes in the game engine's python API

Type string, default ""

show_debug
Print debug information for this property

Type boolean, default False

type
Type enum in ['BOOL', 'INT', 'FLOAT', 'STRING', 'TIMER'], default 'BOOL'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GameObjectSettings.properties

2.4.240 GameSoftBodySettings(bpy_struct)

base class — `bpy_struct`

class bpy.types.GameSoftBodySettings (bpy_struct)
Soft body simulation settings for an object in the game engine

cluster_iterations

Specify the number of cluster iterations

Type int in [1, 128], default 0

collision_margin

Collision margin for soft body. Small value makes the algorithm unstable

Type float in [0.01, 1], default 0.0

dynamic_friction

Dynamic Friction

Type float in [0, 1], default 0.0

linear_stiffness

Linear stiffness of the soft body links

Type float in [0, 1], default 0.0

location_iterations

Position solver iterations

Type int in [0, 10], default 0

shape_threshold

Shape matching threshold

Type float in [0, 1], default 0.0

use_bending_constraints

Enable bending constraints

Type boolean, default False

use_cluster_rigid_to_softbody

Enable cluster collision between soft and rigid body

Type boolean, default False

use_cluster_soft_to_softbody

Enable cluster collision between soft and soft body

Type boolean, default False

use_shape_match

Enable soft body shape matching goal

Type boolean, default False

weld_threshold

Welding threshold: distance between nearby vertices to be considered equal => set to 0.0 to disable welding test and speed up scene loading (ok if the mesh has no duplicates)

Type float in [0, 0.01], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GameObjectSettings.soft_body

2.4.241 GameStringProperty(GameProperty)

base classes — `bpy_struct`, `GameProperty`

class bpy.types.GameStringProperty (GameProperty)
Game engine user defined text string property

value

Property value

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.242 GameTimerProperty(GameProperty)

base classes — bpy_struct, GameProperty

class bpy.types.GameTimerProperty (GameProperty)
Game engine user defined timer property

value

Property value

Type float in [-10000, 10000], default 0.0

Inherited Properties

- bpy_struct.id_data
- GameProperty.name
- GameProperty.show_debug
- GameProperty.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.243 GlowSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.GlowSequence (*EffectSequence*)

Sequence strip creating a glow effect

blur_radius

Radius of glow effect

Type float in [0.5, 20], default 0.0

boost_factor

Brightness multiplier

Type float in [0, 10], default 0.0

clamp

rightness limit of intensity

Type float in [0, 1], default 0.0

quality

Accuracy of the blur effect

Type int in [1, 5], default 0

threshold

Minimum intensity to trigger a glow

Type float in [0, 1], default 0.0

use_only_boost

Show the glow buffer only

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel

- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Sequence.getStripElem`
- `Sequence.swap`

2.4.244 GreasePencil(*ID*)

base classes — `bpy_struct, ID`

class `bpy.types.GreasePencil` (*ID*)

Freehand annotation sketchbook

draw_mode

Type enum in [‘CURSOR’, ‘VIEW’, ‘SURFACE’, ‘STROKE’], default ‘VIEW’

layers

Type `GreasePencilLayers bpy_prop_collection of GPencilLayer`, (readonly)

use_stroke_endpoints

Only use the first and last parts of the stroke for snapping

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.grease_pencil
- GreasePencilLayers.active
- NodeTree.grease_pencil
- Object.grease_pencil
- Scene.grease_pencil
- SpaceImageEditor.grease_pencil

2.4.245 GreasePencilLayers(bpy_struct)

base class — bpy_struct

class bpy.types.GreasePencilLayers (*bpy_struct*)
Collection of grease pencil layers

active

Active grease pencil layer

Type GreasePencil

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- GreasePencil.layers

2.4.246 Group(ID)

base classes — bpy_struct, ID

class bpy.types.Group (*ID*)
Group of Object datablocks

dupli_offset

Offset from the origin to use when instancing as DupliGroup

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

layers

Layers visible when this groups is instanced as a dupli

Type boolean array of 20 items, default (False, False, False)

objects

A collection of this groups objects

Type GroupObjects bpy_prop_collection of Object, (readonly)

users_dupli_group

The dupli group this group is used in (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.groups`
- `BlendDataGroups.new`
- `BlendDataGroups.remove`
- `ClothCollisionSettings.group`
- `DopeSheet.filter_group`
- `EffectorWeights.group`
- `Material.light_group`
- `Object.dupli_group`
- `ParticleSettings.dupli_group`
- `RenderLayer.light_override`
- `SceneRenderLayer.light_override`
- `SmokeDomainSettings.collision_group`
- `SmokeDomainSettings.effector_group`
- `SmokeDomainSettings.fluid_group`

2.4.247 GroupInputs(bpy_struct)

base class — `bpy_struct`

class `bpy.types.GroupInputs` (`bpy_struct`)

Collection of group sockets

new (`name="Socket", type='VALUE'`)

Add a socket to the group tree.

Parameters

- `name` (*string, (optional)*) – Name, Name of the socket
- `type` (*enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)*) – Type, Type of socket

Returns New socket.

Return type `NodeSocket`

expose (`sock=None, add_link=True`)

Expose an internal socket in the group tree.

Parameters

- `sock` (`NodeSocket`, *(optional)*) – Socket, Internal node socket to expose
- `add_link` (*boolean, (optional)*) – Add Link, If TRUE, adds a link to the internal socket

Returns New socket.

Return type `NodeSocket`

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- NodeTree.inputs

2.4.248 GroupObjects(bpy_struct)

base class — bpy_struct

class bpy.types.**GroupObjects** (*bpy_struct*)

Collection of group objects

link (*object*)

Add this object to a group

Parameters **object** (*Object*, (never None)) – Object to add.

unlink (*object*)

Remove this object to a group

Parameters **object** (*Object*) – Object to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Group.objects

2.4.249 GroupOutputs(bpy_struct)

base class — `bpy_struct`

class `bpy.types.GroupOutputs` (`bpy_struct`)

Collection of group sockets

new (`name="Socket", type='VALUE'`)
Add a socket to the group tree.

Parameters

- **name** (`string, (optional)`) – Name, Name of the socket
- **type** (`enum in ['VALUE', 'VECTOR', 'RGBA'], (optional)`) – Type, Type of socket

Returns New socket.

Return type `NodeSocket`

expose (`sock=None, add_link=True`)
Expose an internal socket in the group tree.

Parameters

- **sock** (`NodeSocket, (optional)`) – Socket, Internal node socket to expose
- **add_link** (`boolean, (optional)`) – Add Link, If TRUE, adds a link to the internal socket

Returns New socket.

Return type `NodeSocket`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `NodeTree.outputs`

2.4.250 Header(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.Header(bpy_struct)`

Editor header containing UI elements.

bl_idname

If this is set, the header gets a custom ID, otherwise it takes the name of the class used to define the panel. For example, if the class name is “OBJECT_HT_hello”, and bl_idname is not set by the script, then bl_idname = “OBJECT_HT_hello”

Type string, default “”

bl_space_type

The space where the header is going to be used in.

Type enum in [‘EMPTY’, ‘VIEW_3D’, ‘GRAPH_EDITOR’, ‘OUTLINER’, ‘PROPERTIES’, ‘FILE_BROWSER’, ‘IMAGE_EDITOR’, ‘INFO’, ‘SEQUENCE_EDITOR’, ‘TEXT_EDITOR’, ‘AUDIO_WINDOW’, ‘DOPESHEET_EDITOR’, ‘NLA_EDITOR’, ‘SCRIPTS_WINDOW’, ‘TIMELINE’, ‘NODE_EDITOR’, ‘LOGIC_EDITOR’, ‘CONSOLE’, ‘USER_PREFERENCES’], default ‘EMPTY’

layout

Defines the structure of the header in the UI.

Type `UILayout`, (readonly)

draw(context)

Draw UI elements into the header UI layout.

classmethod **append** (*draw_func*)

Append a draw function to this menu, takes the same arguments as the menus draw function.

classmethod **prepend** (*draw_func*)

Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod **remove** (*draw_func*)

Remove a draw function that has been added to this menu

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.251 HemiLamp(Lamp)

base classes — `bpy_struct, ID, Lamp`

class `bpy.types.HemiLamp (Lamp)`

180 degree constant lamp

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Lamp.active_texture`
- `Lamp.active_texture_index`
- `Lamp.animation_data`
- `Lamp.color`
- `Lamp.use_diffuse`

- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.252 Histogram(bpy_struct)

base class — bpy_struct

class bpy.types.Histogram(*bpy_struct*)

Statistical view of the levels of color in an image

mode

Channels to display when drawing the histogram

Type enum in ['LUMA', 'RGB', 'R', 'G', 'B'], default 'LUMA'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scopes.histogram
- SpaceImageEditor.sample_histogram

2.4.253 HookModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.HookModifier (Modifier)

Hook modifier to modify the location of vertices

falloff

If not zero, the distance from the hook where influence ends

Type float in [0, inf], default 0.0

force

Relative force of the hook

Type float in [0, 1], default 0.0

object

Parent Object for hook, also recalculates and clears offset

Type Object

subtarget

Name of Parent Bone for hook (if applicable), also recalculates and clears offset

Type string, default “”

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline

- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.254 ID(bpy_struct)

base class — `bpy_struct`

subclasses — `Lattice`, `Library`, `Key`, `NodeTree`, `MetaBall`, `Text`, `Lamp`, `World`, `Brush`, `Object`, `Armature`, `Mesh`, `VectorFont`, `GreasePencil`, `Sound`, `ParticleSettings`, `Scene`, `.WindowManager`, `Texture`, `Curve`, `Action`, `Group`, `Screen`, `Material`, `Image`, `Camera`

class bpy.types.ID(bpy_struct)

Base type for datablocks, defining a unique name, linking from other libraries and garbage collection

library

Library file the datablock is linked from

Type `Library`, (readonly)

name

Unique datablock ID name

Type string, default “”

tag

Tools can use this to tag data, (initial state is undefined)

Type boolean, default False

use_fake_user

Saves this datablock even if it has no users

Type boolean, default False

users

Number of times this datablock is referenced

Type int in [0, 32767], default 0, (readonly)

copy()

Create a copy of this datablock (not supported for all datablocks).

Returns New copy of the ID.

Return type [ID](#)

user_clear()

Clears the user count of a datablock so its not saved, on reload the data will be removed.

animation_data_create()

Create animation data to this ID, note that not all ID types support this.

Returns New animation data or NULL.

Return type [AnimData](#)

animation_data_clear()

Clear animation on this this ID.

update_tag(*refresh*=*set()*)

Tag the id to update its display data.

Parameters **refresh** (enum set in {‘OBJECT’, ‘DATA’, ‘TIME’}, (optional)) – Type of updates to perform.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [BlendData.scripts](#)

- BlendDataObjects.new
- DopeSheet.source
- DriverTarget.id
- ID.copy
- Key.user
- KeyingSetPath.id
- KeyingSetPaths.add
- Object.data
- SpaceNodeEditor.id
- SpaceNodeEditor.id_from
- SpaceProperties.pin_id
- UILayout.template_path_builder
- UILayout.template_preview
- UILayout.template_preview

2.4.255 **IDMaterials(bpy_struct)**

base class — `bpy_struct`

class bpy.types.IDMaterials(bpy_struct)

Collection of materials

append(material)

Add a new material to the data block.

Parameters `material (Material)` – Material to add.

pop(index)

Remove a material from the data block.

Parameters `index (int in [0, inf])` – Index of material to remove.

Returns Material to remove.

Return type `Material`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Curve.materials`
- `Mesh.materials`
- `MetaBall.materials`

2.4.256 IKParam(`bpy_struct`)

base class — `bpy_struct`

subclasses — `Itasc`

class `bpy.types.IKParam(bpy_struct)`

Base type for IK solver parameters

ik_solver

IK solver for which these parameters are defined, 0 for Legacy, 1 for iTaSC

Type enum in ['LEGACY', 'ITASC'], default 'LEGACY', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Pose.ik_param`

2.4.257 Image(ID)

base classes — `bpy_struct, ID`

class bpy.types.Image (ID)

Image datablock referencing an external or packed image

bindcode

OpenGL bindcode

Type int in [0, inf], default 0, (readonly)

depth

Image bit depth

Type int in [0, inf], default 0, (readonly)

display_aspect

Display Aspect for this image, does not affect rendering

Type float array of 2 items in [0.1, 5000], default (0.0, 0.0)

field_order

Order of video fields. Select which lines are displayed first

Type enum in ['EVEN', 'ODD'], default 'EVEN'

file_format

Format used for re-saving this file

Type enum in ['BMP', 'IRIS', 'PNG', 'JPEG', 'TARGA', 'TARGA_RAW', 'AVI_JPEG', 'AVI_RAW', 'FRAMESERVER'], default 'TARGA'

filepath

Image/Movie file name

Type string, default ""

filepath_raw

Image/Movie file name (without data refreshing)

Type string, default ""

fps

Speed of the animation in frames per second

Type int in [1, 100], default 0

frame_end

End frame of an animated texture

Type int in [0, 128], default 0

frame_start

Start frame of an animated texture

Type int in [0, 128], default 0

generated_height

Generated image height

Type int in [1, 16384], default 0

generated_type

Generated image type

Type enum in ['BLANK', 'UV_GRID', 'COLOR_GRID'], default 'BLANK'

generated_width
Generated image width
Type int in [1, 16384], default 0

has_data
True if this image has data
Type boolean, default False, (readonly)

is_dirty
Image has changed and is not saved
Type boolean, default False, (readonly)

mapping
Mapping type to use for this image in the game engine
Type enum in ['UV', 'REFLECTION'], default 'UV'

packed_file
Type [PackedFile](#), (readonly)

pixels
Image pixels in floating point values
Type float in [-inf, inf], default 0.0

resolution
X/Y pixels per meter
Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

size
Width and height in pixels, zero when image data cant be loaded
Type int array of 2 items in [-inf, inf], default (0, 0), (readonly)

source
Where the image comes from
Type enum in ['FILE', 'SEQUENCE', 'MOVIE', 'GENERATED', 'VIEWER'], default 'FILE'

tiles_x
Degree of repetition in the X direction
Type int in [1, 16], default 0

tiles_y
Degree of repetition in the Y direction
Type int in [1, 16], default 0

type
How to generate the image
Type enum in ['IMAGE', 'MULTILAYER', 'UV_TEST', 'RENDER_RESULT', 'COMPOSITING'], default 'IMAGE', (readonly)

use_animation
Use as animated texture in the game engine
Type boolean, default False

use_clamp_x

Disable texture repeating horizontally

Type boolean, default False

use_clamp_y

Disable texture repeating vertically

Type boolean, default False

use_fields

Use fields of the image

Type boolean, default False

use_premultiply

Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_tiles

Use of tilemode for faces (default shift-LMB to pick the tile for selected faces)

Type boolean, default False

save_render (filepath, scene=None)

Save image to a specific path using a scenes render settings

Parameters

- **filepath** (*string*) – Save path.
- **scene** (*Scene*, (optional)) – Scene to take image parameters from

save ()

Save image to its source path

reload ()

Reload the image from its source path

update ()

Update the display image from the floating point buffer

gl_load (filter=9985, mag=9729)

Load the image into OpenGL graphics memory

Parameters

- **filter** (*int in [-inf, inf], (optional)*) – Filter, The texture minifying function
- **mag** (*int in [-inf, inf], (optional)*) – Magnification, The texture magnification function

Returns Error, OpenGL error value

Return type int in [-inf, inf]

gl_free ()

Free the image from OpenGL graphics memory

Inherited Properties

- *bpy_struct.id_data*
- *ID.name*
- *ID.use_fake_user*

- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BackgroundImage.image`
- `BlendData.images`
- `BlendDataImages.load`
- `BlendDataImages.new`
- `BlendDataImages.remove`
- `Brush.clone_image`
- `CompositorNodeImage.image`
- `EnvironmentMapTexture.image`
- `ImageTexture.image`
- `MeshTextureFace.image`
- `SpaceImageEditor.image`
- `TextureNodeImage.image`
- `UILayout.template_image_layers`
- `UVProjectModifier.image`
- `VoxelDataTexture.image`

2.4.258 ImagePaint(Paint)

base classes — `bpy_struct, Paint`

class `bpy.types.ImagePaint (Paint)`
Properties of image and texture painting mode

invert_stencil

Invert the stencil layer

Type boolean, default False

normal_angle

Paint most on faces pointing towards the view according to this angle

Type int in [0, 90], default 0

screen_grab_size

Size to capture the image for re-projecting

Type int array of 2 items in [512, 16384], default (0, 0)

seam_bleed

Extend paint beyond the faces UVs to reduce seams (in pixels, slower)

Type int in [0, 32767], default 0

use_backface_culling

Ignore faces pointing away from the view (faster)

Type boolean, default False

use_clone_layer

Use another UV layer as clone source, otherwise use 3D the cursor as the source

Type boolean, default False

use_normal_falloff

Paint most on faces pointing towards the view

Type boolean, default False

use_occlude

Only paint onto the faces directly under the brush (slower)

Type boolean, default False

use_projection

Use projection painting for improved consistency in the brush strokes

Type boolean, default False

use_stencil_layer

Set the mask layer from the UV layer buttons

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Paint.brush
- Paint.show_low_resolution
- Paint.show_brush
- Paint.show_brush_on_surface

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.image_paint

2.4.259 ImageSequence(Sequence)

base classes — `bpy_struct, Sequence`

class `bpy.types.ImageSequence (Sequence)`

Sequence strip to load one or more images

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type `SequenceColorBalance`, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type `SequenceCrop`, (readonly)

directory

Type string, default “”

elements

Type `bpy_prop_collection of SequenceElement`, (readonly)

proxy

Type `SequenceProxy`, (readonly)

strobe
Only display every nth frame
Type float in [1, 30], default 0.0

transform

Type `SequenceTransform`, (readonly)

use_color_balance
(3-Way color correction) on input
Type boolean, default False

use_crop
Crop image before processing
Type boolean, default False

use_deinterlace
For video movies to remove fields
Type boolean, default False

use_flip_x
Flip on the X axis
Type boolean, default False

use_flip_y
Flip on the Y axis
Type boolean, default False

use_float
Convert input to float data
Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False

use_proxy
Use a preview proxy for this strip
Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False

use_proxy_custom_file
Use a custom file to read proxy data from
Type boolean, default False

use_reverse_frames
Reverse frame order
Type boolean, default False

use_translation

Translate image before processing

Type boolean, default False**Inherited Properties**

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

- `Sequence.getStripElem`
- `Sequence.swap`

2.4.260 ImageTexture(Texture)

base classes — `bpy_struct, ID, Texture`

`class bpy.types.ImageTexture (Texture)`

`checker_distance`

Sets distance between checker tiles

Type float in [0, 0.99], default 0.0

`crop_max_x`

Sets maximum X value to crop the image

Type float in [-10, 10], default 0.0

`crop_max_y`

Sets maximum Y value to crop the image

Type float in [-10, 10], default 0.0

`crop_min_x`

Sets minimum X value to crop the image

Type float in [-10, 10], default 0.0

`crop_min_y`

Sets minimum Y value to crop the image

Type float in [-10, 10], default 0.0

`extension`

Sets how the image is extrapolated past its original bounds

Type enum in ['EXTEND', 'CLIP', 'CLIP_CUBE', 'REPEAT', 'CHECKER'], default 'EXTEND'

`filter_eccentricity`

Maximum eccentricity. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

`filter_probes`

Maximum number of samples. Higher gives less blur at distant/oblique angles, but is also slower

Type int in [1, 256], default 0

`filter_size`

Multiplies the filter size used by MIP Map and Interpolation

Type float in [0.1, 50], default 0.0

`filter_type`

Texture filter to use for sampling image

Type enum in ['BOX', 'EWA', 'FELINE', 'AREA'], default 'BOX'

`image`

Type `Image`

image_user

Parameters defining which layer, pass and frame of the image is displayed

Type `ImageUser`, (readonly)

invert_alpha

Inverts all the alpha values in the image

Type boolean, default False

repeat_x

Sets a repetition multiplier in the X direction

Type int in [1, 512], default 0

repeat_y

Sets a repetition multiplier in the Y direction

Type int in [1, 512], default 0

use_alpha

Uses the alpha channel information in the image

Type boolean, default False

use_calculate_alpha

Calculates an alpha channel based on RGB values in the image

Type boolean, default False

use_checker_even

Sets even checker tiles

Type boolean, default False

use_checker_odd

Sets odd checker tiles

Type boolean, default False

use_filter_size_min

Use Filter Size as a minimal filter value in pixels

Type boolean, default False

use_flip_axis

Flips the texture's X and Y axis

Type boolean, default False

use_interpolation

Interpolates pixels using selected filter

Type boolean, default False

use_mipmap

Uses auto-generated MIP maps for the image

Type boolean, default False

use_mipmap_gauss

Uses Gauss filter to sample down MIP maps

Type boolean, default False

use_mirror_x

Mirrors the image repetition on the X direction

Type boolean, default False

use_mirror_y

Mirrors the image repetition on the Y direction

Type boolean, default False

use_normal_map

Uses image RGB values for normal mapping

Type boolean, default False

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.261 ImageUser(bpy_struct)

base class — `bpy_struct`

`class bpy.types.ImageUser(bpy_struct)`

Parameters defining how an Image datablock is used by another datablock

fields_per_frame

The number of fields per rendered frame (2 fields is 1 image)

Type int in [1, 200], default 0

frame_duration

Sets the number of images of a movie to use

Type int in [0, 300000], default 0

frame_offset

Offsets the number of the frame to use in the animation

Type int in [-300000, 300000], default 0

frame_start

Sets the global starting frame of the movie/sequence, assuming first picture has a #1

Type int in [-300000, 300000], default 0

multilayer_layer

Layer in multilayer image

Type int in [0, 32767], default 0, (readonly)

multilayer_pass

Pass in multilayer image

Type int in [0, 32767], default 0, (readonly)

use_auto_refresh

Always refresh image on frame changes

Type boolean, default False

use_cyclic

Cycle the images in the movie

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BackgroundImage.image_user
- EnvironmentMapTexture.image_user
- ImageTexture.image_user
- SpaceImageEditor.image_user
- UILayout.template_image
- UILayout.template_image_layers
- VoxelDataTexture.image_user

2.4.262 InflowFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.InflowFluidSettings (FluidSettings)
Fluid simulation settings for objects adding fluids in the simulation

inflow_velocity
Initial velocity of fluid

Type float array of 3 items in [-1000.1, 1000.1], default (0.0, 0.0, 0.0)

use
Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh
Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False
use_local_coords
 Use local coordinates for inflow. (e.g. for rotating objects)
Type boolean, default False
volume_INITIALIZATION
 Volume initialization type
Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- bpy_struct.id_data
- FluidSettings.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.263 IntProperty(Property)

base classes — bpy_struct, Property

class bpy.types.**IntProperty** (*Property*)
 RNA integer number property definition

array_length
 Maximum length of the array, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

default
 Default value for this number

Type int in [-inf, inf], default 0, (readonly)

default_array
 Default value for this array

Type int array of 3 items in [-inf, inf], default (0, 0, 0), (readonly)

hard_max

Maximum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

hard_min

Minimum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

soft_max

Maximum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

soft_min

Minimum value used by buttons

Type int in [-inf, inf], default 0, (readonly)

step

Step size used by number buttons, for floats 1/100th of the step size

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data
- Property.name
- Property.srna
- Property.description
- Property.is_enum_flag
- Property.is_hidden
- Property.identifier
- Property.is_never_none
- Property.is_readonly
- Property.is_registered
- Property.is_registered_optional
- Property.is_required
- Property.is_output
- Property.is_runtime
- Property.is_skip_save
- Property.subtype
- Property.type
- Property.unit

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.264 Itasc(IKParam)

base classes — bpy_struct, IKParam

class bpy.types.Itasc (IKParam)

Parameters for the iTaSC IK solver

damping_epsilon

Singular value under which damping is progressively applied. Higher values=more stability, less reactivity.
Default=0.1

Type float in [0, 1], default 0.0

damping_max

Maximum damping coefficient when singular value is nearly 0. Higher values=more stability, less reactivity.
Default=0.5

Type float in [0, 1], default 0.0

feedback

Feedback coefficient for error correction. Average response time=1/feedback. Default=20

Type float in [0, 100], default 0.0

iterations

Maximum number of iterations for convergence in case of reiteration

Type int in [1, 1000], default 0

mode

Type enum in ['ANIMATION', 'SIMULATION'], default 'ANIMATION'

precision

Precision of convergence in case of reiteration

Type float in [0, 0.1], default 0.0

reiteration_method

Defines if the solver is allowed to reiterate (converges until precision is met) on none, first or all frames

Type enum in ['NEVER', 'INITIAL', 'ALWAYS'], default 'NEVER'

solver

Solving method selection: Automatic damping or manual damping

Type enum in ['SDLS', 'DLS'], default 'SDLS'

step_count

Divides the frame interval into this many steps

Type int in [1, 50], default 0

step_max

Higher bound for timestep in second in case of automatic substeps

Type float in [0, 1], default 0.0

step_min

Lower bound for timestep in second in case of automatic substeps

Type float in [0, 0.1], default 0.0

use_auto_step

Automatically determine the optimal number of steps for best performance/accuracy trade off

Type boolean, default False

velocity_max

Maximum joint velocity in rad/s. Default=50

Type float in [0, 100], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `IKParam.ik_solver`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.265 JoystickSensor(Sensor)

base classes — `bpy_struct`, `Sensor`

class bpy.types.JoystickSensor (Sensor)

Sensor to detect joystick events

axis_direction

The direction of the axis

Type enum in ['RIGHTAXIS', 'UPAXIS', 'LEFTAXIS', 'DOWNAXIS'], default 'RIGHTAXIS'

axis_number

Specify which axis pair to use, 1 is usually the main direction input

Type int in [1, 2], default 0

axis_threshold
Specify the precision of the axis

Type int in [0, 32768], default 0

button_number
Specify which button to use

Type int in [0, 18], default 0

event_type
The type of event this joystick sensor is triggered on

Type enum in ['BUTTON', 'AXIS', 'HAT', 'AXIS_SINGLE'], default 'BUTTON'

hat_direction
Specify hat direction

Type enum in ['UP', 'DOWN', 'LEFT', 'RIGHT', 'UPRIGHT', 'DOWNLEFT', 'UPLEFT', 'DOWNRIGHT'], default 'UP'

hat_number
Specify which hat to use

Type int in [1, 2], default 0

joystick_index
Specify which joystick to use

Type int in [0, 7], default 0

single_axis_number
Specify a single axis (verticle/horizontal/other) to detect

Type int in [1, 16], default 0

use_all_events
Triggered by all events on this joysticks current type (axis/button/hat)

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sensor.name`
- `Sensor.show_expanded`
- `Sensor.frequency`
- `Sensor.invert`
- `Sensor.use_level`
- `Sensor.pin`
- `Sensor.use_pulse_false_level`
- `Sensor.use_pulse_true_level`
- `Sensor.use_tap`
- `Sensor.type`

Inherited Functions

- `bpy_struct.as_pointer`

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.266 Key(ID)

base classes — bpy_struct, ID

class bpy.types.Key (ID)

Shape keys datablock containing different shapes of geometric datablocks

animation_data

Animation data for this datablock

Type AnimData, (readonly)

key_blocks

Shape keys

Type bpy_prop_collection of ShapeKey, (readonly)

reference_key

Type ShapeKey, (readonly, never None)

slurph

Creates a delay in amount of frames in applying keypositions, first vertex goes first

Type int in [-500, 500], default 0

use_relative

Makes shape keys relative

Type boolean, default False

user

Datablock using these shape keys

Type ID, (readonly, never None)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user

- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.shape_keys`
- `Curve.shape_keys`
- `Lattice.shape_keys`
- `Mesh.shape_keys`

2.4.267 KeyConfig(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.KeyConfig(bpy_struct)`

Input configuration, including keymaps

is_user_defined

Indicates that a keyconfig was defined by the user

Type boolean, default False, (readonly)

keymaps

Key maps configured as part of this configuration

Type `KeyMaps bpy_prop_collection of KeyMap, (readonly)`

name

Name of the key configuration

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyConfigurations.active
- KeyConfigurations.default
- KeyConfigurations.new
- KeyConfigurations.remove
- WindowManager.keyconfigs

2.4.268 KeyConfigurations(bpy_struct)

base class — bpy_struct

class bpy.types.KeyConfigurations (*bpy_struct*)
Collection of KeyConfigs

active

Active wm KeyConfig

Type KeyConfig

default

Type KeyConfig, (readonly)

new(*name*)

new

Parameters **name** (*string*) – Name

Returns Key Configuration, Added key configuration.

Return type `KeyConfig`

remove (`keyconfig`)

remove

Parameters `keyconfig` (`KeyConfig`) – Key Configuration, Removed key configuration.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `WindowManager.keyconfigs`

2.4.269 KeyMap(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.KeyMap` (`bpy_struct`)

Input configuration, including keymaps

is_modal

Indicates that a keymap is used for translate modal events for an operator

Type boolean, default False, (readonly)

is_user_defined

Keymap is defined by the user

Type boolean, default False

keymap_items

Items in the keymap, linking an operator to an input event

Type `KeyMapItems bpy_prop_collection` of `KeyMapItem`, (readonly)

name

Name of the key map

Type string, default "", (readonly)

region_type

Optional region type keymap is associated with

Type enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], default 'WINDOW', (readonly)

show_expanded_children

Children expanded in the user interface

Type boolean, default False

show_expanded_items

Expanded in the user interface

Type boolean, default False

space_type

Optional space type keymap is associated with

Type enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR', 'LOGIC_EDITOR', 'CONSOLE', 'USER_PREFERENCES'], default 'EMPTY', (readonly)

active()

active

Returns Key Map, Active key map.

Return type `KeyMap`

copy_to_user()

copy_to_user

Returns Key Map, User editable key map.

Return type `KeyMap`

restore_to_default()

restore_to_default

restore_item_to_default(item)

restore_item_to_default

Parameters item (`KeyMapItem`, (never None)) – Item

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyConfig.keymaps
- KeyMap.active
- KeyMap.copy_to_user
- KeyMaps.find
- KeyMaps.find_modal
- KeyMaps.new
- UserPreferencesInput.edited_keymaps

2.4.270 KeyMapItem(bpy_struct)

base class — `bpy_struct`

class `bpy.types.KeyMapItem` (`bpy_struct`)

Item in a Key Map

active

Activate or deactivate item

Type boolean, default False

alt

Alt key pressed

Type boolean, default False

any

Any modifier keys pressed

Type boolean, default False

ctrl

Control key pressed

Type boolean, default False

id

ID of the item

Type int in [-32768, 32767], default 0, (readonly)

idname

Identifier of operator to call on input event

Type string, default “”

is_user_defined

Is this keymap item user defined (doesn't just override a builtin item)

Type boolean, default False, (readonly)

key_modifier

Regular key pressed as a modifier

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'T', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

map_type

Type of event mapping

Type enum in ['KEYBOARD', 'TWEAK', 'MOUSE', 'TEXTINPUT', 'TIMER'], default 'KEYBOARD'

name

Name of operator to call on input event

Type string, default “”, (readonly)

oskey

Operating system key pressed

Type boolean, default False

properties

Properties to set when the operator is called

Type OperatorProperties, (readonly)

propvalue

The value this event translates to in a modal keymap

Type enum in ['NONE'], default 'NONE'

shift

Shift key pressed

Type boolean, default False

show_expanded

Show key map event and property details in the user interface

Type boolean, default False

type

Type of event

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'T', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

value

Type enum in ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK'], default 'NOTHING'

compare (item)

compare

Parameters item ([KeyMapItem](#)) – Item

Returns Comparison result

Return type boolean

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `KeyMap.keymap_items`
- `KeyMap.restore_item_to_default`
- `KeyMapItem.compare`
- `KeyMapItems.from_id`
- `KeyMapItems.new`
- `KeyMapItems.new_modal`
- `KeyMapItems.remove`

2.4.271 KeyMapItems(bpy_struct)

base class — `bpy_struct`

class bpy.types.KeyMapItems (bpy_struct)

Collection of keymap items

new (*idname*, *type*, *value*, *any=False*, *shift=False*, *ctrl=False*, *alt=False*, *oskey=False*,
key_modifier='NONE')
new

Parameters

- **`idname`** (*string*) – Operator Identifier
- **`type`** (*enum in* `['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRELESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX']`)

'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2']) – Type

- **value** (*enum in* ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK']) – Value
- **any** (*boolean, (optional)*) – Any
- **shift** (*boolean, (optional)*) – Shift
- **ctrl** (*boolean, (optional)*) – Ctrl
- **alt** (*boolean, (optional)*) – Alt
- **oskey** (*boolean, (optional)*) – OS Key
- **key_modifier** (*enum in* ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], *(optional)*) – Key Modifier

Returns Item, Added key map item.

Return type `KeyMapItem`

new_modal (*propvalue, type, value, any=False, shift=False, ctrl=False, alt=False, oskey=False, key_modifier='NONE'*)
`new_modal`

Parameters

- **propvalue** (*string*) – Property Value
- **type** (*enum in* ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], *(optional)*) – Key Modifier

'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2']) – Type

- **value** (*enum in* ['ANY', 'NOTHING', 'PRESS', 'RELEASE', 'CLICK', 'DOUBLE_CLICK']) – Value
- **any** (*boolean, (optional)*) – Any
- **shift** (*boolean, (optional)*) – Shift
- **ctrl** (*boolean, (optional)*) – Ctrl
- **alt** (*boolean, (optional)*) – Alt
- **oskey** (*boolean, (optional)*) – OS Key
- **key_modifier** (*enum in* ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'T', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], *(optional)*) – Key Modifier

Returns Item, Added key map item.

Return type [KeyMapItem](#)

remove (*item*)

remove

Parameters **item** ([KeyMapItem](#)) – Item

```
from_id(id)
from_id

Parameters id (int in [-inf, inf]) – id, ID of the item
Returns Item
Return type KeyMapItem
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyMap.keymap_items

2.4.272 KeyMaps(bpy_struct)

base class — bpy_struct

```
class bpy.types.KeyMaps(bpy_struct)
    Collection of keymaps

    new(name, space_type='EMPTY', region_type='WINDOW', modal=False)
        new
```

Parameters

- name (string) – Name
- space_type (enum in ['EMPTY', 'VIEW_3D', 'GRAPH_EDITOR', 'OUTLINER', 'PROPERTIES', 'FILE_BROWSER', 'IMAGE_EDITOR', 'INFO', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'AUDIO_WINDOW', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'SCRIPTS_WINDOW', 'TIMELINE', 'NODE_EDITOR',

‘LOGIC_EDITOR’, ‘CONSOLE’, ‘USER_PREFERENCES’], (optional)) – Space Type

- **region_type** (enum in [‘WINDOW’, ‘HEADER’, ‘CHANNELS’, ‘TEMPORARY’, ‘UI’, ‘TOOLS’, ‘TOOL_PROPS’, ‘PREVIEW’], (optional)) – Region Type
 - **modal** (boolean, optional) – Modal

Returns Key Map, Added key map.

Return type KeyMap

find(name, space_type=’EMPTY’, region_type=’WINDOW’)
find

Parameters

- **name** (string) – Name
- **space_type** (enum in [‘EMPTY’, ‘VIEW_3D’, ‘GRAPH_EDITOR’, ‘OUTLINER’, ‘PROPERTIES’, ‘FILE_BROWSER’, ‘IMAGE_EDITOR’, ‘INFO’, ‘SEQUENCE_EDITOR’, ‘TEXT_EDITOR’, ‘AUDIO_WINDOW’, ‘DOPESHEET_EDITOR’, ‘NLA_EDITOR’, ‘SCRIPTS_WINDOW’, ‘TIMELINE’, ‘NODE_EDITOR’, ‘LOGIC_EDITOR’, ‘CONSOLE’, ‘USER_PREFERENCES’], (optional)) – Space Type
- **region_type** (enum in [‘WINDOW’, ‘HEADER’, ‘CHANNELS’, ‘TEMPORARY’, ‘UI’, ‘TOOLS’, ‘TOOL_PROPS’, ‘PREVIEW’], (optional)) – Region Type

Returns Key Map, Corresponding key map.

Return type KeyMap

find_modal(name)
find_modal

Parameters name (string) – Operator Name

Returns Key Map, Corresponding key map.

Return type KeyMap

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `KeyConfig.keymaps`

2.4.273 KeyboardSensor(Sensor)

base classes — `bpy_struct, Sensor`

class bpy.types.KeyboardSensor (Sensor)
Sensor to detect keyboard events

key

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN', 'EIGHT', 'NINE', 'LEFT_CTRL', 'LEFT_ALT', 'LEFT_SHIFT', 'RIGHT_ALT', 'RIGHT_CTRL', 'RIGHT_SHIFT', 'OSKEY', 'GRLESS', 'ESC', 'TAB', 'RET', 'SPACE', 'LINE_FEED', 'BACK_SPACE', 'DEL', 'SEMI_COLON', 'PERIOD', 'COMMA', 'QUOTE', 'ACCENT_GRAVE', 'MINUS', 'SLASH', 'BACK_SLASH', 'EQUAL', 'LEFT_BRACKET', 'RIGHT_BRACKET', 'LEFT_ARROW', 'DOWN_ARROW', 'RIGHT_ARROW', 'UP_ARROW', 'NUMPAD_2', 'NUMPAD_4', 'NUMPAD_6', 'NUMPAD_8', 'NUMPAD_1', 'NUMPAD_3', 'NUMPAD_5', 'NUMPAD_7', 'NUMPAD_9', 'NUMPAD_PERIOD', 'NUMPAD_SLASH', 'NUMPAD_ASTERIX', 'NUMPAD_0', 'NUMPAD_MINUS', 'NUMPAD_ENTER', 'NUMPAD_PLUS', 'F1', 'F2', 'F3', 'F4', 'F5', 'F6', 'F7', 'F8', 'F9', 'F10', 'F11', 'F12', 'F13', 'F14', 'F15', 'F16', 'F17', 'F18', 'F19', 'PAUSE', 'INSERT', 'HOME', 'PAGE_UP', 'PAGE_DOWN', 'END', 'MEDIA_PLAY', 'MEDIA_STOP', 'MEDIA_FIRST', 'MEDIA_LAST', 'WINDOW_DEACTIVATE', 'TIMER', 'TIMER0', 'TIMER1', 'TIMER2'], default 'NONE'

log

Property that indicates whether to log keystrokes as a string

Type string, default ""

modifier_key_1

Modifier key code

Type enum in ['NONE', 'LEFTMOUSE', 'MIDDLEMOUSE', 'RIGHTMOUSE', 'BUTTON4MOUSE', 'BUTTON5MOUSE', 'ACTIONMOUSE', 'SELECTMOUSE', 'MOUSEMOVE', 'INBETWEEN_MOUSEMOVE', 'TRACKPADPAN', 'TRACKPADZOOM', 'MOUSERotate', 'WHEELUPMOUSE', 'WHEELEDOWNMOUSE', 'WHEELINMOUSE', 'WHEELOUTMOUSE', 'EVT_TWEAK_L', 'EVT_TWEAK_M', 'EVT_TWEAK_R', 'EVT_TWEAK_A', 'EVT_TWEAK_S', 'A', 'B', 'C', 'D', 'E', 'F', 'G', 'H', 'I', 'J', 'K', 'L', 'M', 'N', 'O', 'P', 'Q', 'R', 'S', 'T', 'U', 'V', 'W', 'X', 'Y', 'Z', 'ZERO', 'ONE', 'TWO', 'THREE', 'FOUR', 'FIVE', 'SIX', 'SEVEN',

‘EIGHT’, ‘NINE’, ‘LEFT_CTRL’, ‘LEFT_ALT’, ‘LEFT_SHIFT’, ‘RIGHT_ALT’, ‘RIGHT_CTRL’, ‘RIGHT_SHIFT’, ‘OSKEY’, ‘GRLESS’, ‘ESC’, ‘TAB’, ‘RET’, ‘SPACE’, ‘LINE_FEED’, ‘BACK_SPACE’, ‘DEL’, ‘SEMI_COLON’, ‘PERIOD’, ‘COMMA’, ‘QUOTE’, ‘ACCENT_GRAVE’, ‘MINUS’, ‘SLASH’, ‘BACK_SLASH’, ‘EQUAL’, ‘LEFT_BRACKET’, ‘RIGHT_BRACKET’, ‘LEFT_ARROW’, ‘DOWN_ARROW’, ‘RIGHT_ARROW’, ‘UP_ARROW’, ‘NUMPAD_2’, ‘NUMPAD_4’, ‘NUMPAD_6’, ‘NUMPAD_8’, ‘NUMPAD_1’, ‘NUMPAD_3’, ‘NUMPAD_5’, ‘NUMPAD_7’, ‘NUMPAD_9’, ‘NUMPAD_PERIOD’, ‘NUMPAD_SLASH’, ‘NUMPAD_ASTERIX’, ‘NUMPAD_0’, ‘NUMPAD_MINUS’, ‘NUMPAD_ENTER’, ‘NUMPAD_PLUS’, ‘F1’, ‘F2’, ‘F3’, ‘F4’, ‘F5’, ‘F6’, ‘F7’, ‘F8’, ‘F9’, ‘F10’, ‘F11’, ‘F12’, ‘F13’, ‘F14’, ‘F15’, ‘F16’, ‘F17’, ‘F18’, ‘F19’, ‘PAUSE’, ‘INSERT’, ‘HOME’, ‘PAGE_UP’, ‘PAGE_DOWN’, ‘END’, ‘MEDIA_PLAY’, ‘MEDIA_STOP’, ‘MEDIA_FIRST’, ‘MEDIA_LAST’, ‘WINDOW_DEACTIVATE’, ‘TIMER’, ‘TIMER0’, ‘TIMER1’, ‘TIMER2’], default ‘NONE’

modifier_key_2

Modifier key code

Type enum in [‘NONE’, ‘LEFTMOUSE’, ‘MIDDLEMOUSE’, ‘RIGHTMOUSE’, ‘BUTTON4MOUSE’, ‘BUTTON5MOUSE’, ‘ACTIONMOUSE’, ‘SELECTMOUSE’, ‘MOUSEMOVE’, ‘INBETWEEN_MOUSEMOVE’, ‘TRACKPADPAN’, ‘TRACKPADZOOM’, ‘MOUSERotate’, ‘WHEELUPMOUSE’, ‘WHEELEDOWNMOUSE’, ‘WHEELINMOUSE’, ‘WHEELOUTMOUSE’, ‘EVT_TWEAK_L’, ‘EVT_TWEAK_M’, ‘EVT_TWEAK_R’, ‘EVT_TWEAK_A’, ‘EVT_TWEAK_S’, ‘A’, ‘B’, ‘C’, ‘D’, ‘E’, ‘F’, ‘G’, ‘H’, ‘T’, ‘J’, ‘K’, ‘L’, ‘M’, ‘N’, ‘O’, ‘P’, ‘Q’, ‘R’, ‘S’, ‘T’, ‘U’, ‘V’, ‘W’, ‘X’, ‘Y’, ‘Z’, ‘ZERO’, ‘ONE’, ‘TWO’, ‘THREE’, ‘FOUR’, ‘FIVE’, ‘SIX’, ‘SEVEN’, ‘EIGHT’, ‘NINE’, ‘LEFT_CTRL’, ‘LEFT_ALT’, ‘LEFT_SHIFT’, ‘RIGHT_ALT’, ‘RIGHT_CTRL’, ‘RIGHT_SHIFT’, ‘OSKEY’, ‘GRLESS’, ‘ESC’, ‘TAB’, ‘RET’, ‘SPACE’, ‘LINE_FEED’, ‘BACK_SPACE’, ‘DEL’, ‘SEMI_COLON’, ‘PERIOD’, ‘COMMA’, ‘QUOTE’, ‘ACCENT_GRAVE’, ‘MINUS’, ‘SLASH’, ‘BACK_SLASH’, ‘EQUAL’, ‘LEFT_BRACKET’, ‘RIGHT_BRACKET’, ‘LEFT_ARROW’, ‘DOWN_ARROW’, ‘RIGHT_ARROW’, ‘UP_ARROW’, ‘NUMPAD_2’, ‘NUMPAD_4’, ‘NUMPAD_6’, ‘NUMPAD_8’, ‘NUMPAD_1’, ‘NUMPAD_3’, ‘NUMPAD_5’, ‘NUMPAD_7’, ‘NUMPAD_9’, ‘NUMPAD_PERIOD’, ‘NUMPAD_SLASH’, ‘NUMPAD_ASTERIX’, ‘NUMPAD_0’, ‘NUMPAD_MINUS’, ‘NUMPAD_ENTER’, ‘NUMPAD_PLUS’, ‘F1’, ‘F2’, ‘F3’, ‘F4’, ‘F5’, ‘F6’, ‘F7’, ‘F8’, ‘F9’, ‘F10’, ‘F11’, ‘F12’, ‘F13’, ‘F14’, ‘F15’, ‘F16’, ‘F17’, ‘F18’, ‘F19’, ‘PAUSE’, ‘INSERT’, ‘HOME’, ‘PAGE_UP’, ‘PAGE_DOWN’, ‘END’, ‘MEDIA_PLAY’, ‘MEDIA_STOP’, ‘MEDIA_FIRST’, ‘MEDIA_LAST’, ‘WINDOW_DEACTIVATE’, ‘TIMER’, ‘TIMER0’, ‘TIMER1’, ‘TIMER2’], default ‘NONE’

target

Property that receive the keystrokes in case a string is logged

Type string, default “”

use_all_keys

Trigger this sensor on any keystroke

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sensor.name`
- `Sensor.show_expanded`
- `Sensor.frequency`
- `Sensor.invert`

- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.274 Keyframe(bpy_struct)

base class — bpy_struct

class bpy.types.Keyframe(bpy_struct)
Bezier curve point with two handles defining a Keyframe on an F-Curve

co

Coordinates of the control point

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_left

Coordinates of the first handle

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_left_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

handle_right

Coordinates of the second handle

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

handle_right_type

Handle types

Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

interpolation

Interpolation method to use for segment of the curve from this Keyframe until the next Keyframe

Type enum in ['CONSTANT', 'LINEAR', 'BEZIER'], default 'CONSTANT'

select_control_point

Control point selection status

Type boolean, default False

select_left_handle

Handle 1 selection status

Type boolean, default False

select_right_handle

Handle 2 selection status

Type boolean, default False

type

The type of keyframe

Type enum in ['KEYFRAME', 'BREAKDOWN', 'EXTREME', 'JITTER'], default 'KEYFRAME'

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `FCurve.keyframe_points`
- `FCurveKeyframePoints.insert`
- `FCurveKeyframePoints.remove`

2.4.275 KeyingSet(bpy_struct)

base class — `bpy_struct`

class bpy.types.KeyingSet (bpy_struct)
Settings that should be keyframed together

bl_options

Keying set options

Type enum set in {‘INSERTKEY_NEEDED’, ‘INSERTKEY_VISUAL’, ‘INSERTKEY_XYZ_TO_RGB’}, default {‘INSERTKEY_NEEDED’}

is_path_absolute

Keying Set defines specific paths/settings to be keyframed (i.e. is not reliant on context info)

Type boolean, default False, (readonly)

name

Type string, default “”

paths

Keying Set Paths to define settings that get keyframed together

Type `KeyingSetPaths bpy_prop_collection of KeyingSetPath`, (readonly)

type_info

Callback function defines for built-in Keying Sets

Type `KeyingSetInfo`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- KeyingSetInfo.generate
- KeyingSetInfo.iterator
- KeyingSets.active
- KeyingSets.new
- KeyingSetsAll.active
- Scene.keying_sets
- Scene.keying_sets_all

2.4.276 KeyingSetInfo(bpy_struct)

base class — bpy_struct

class bpy.types.KeyingSetInfo (bpy_struct)
Callback function defines for builtin Keying Sets

bl_idname

Type string, default “”

bl_label

Type string, default “”

bl_options

Keying set options

Type enum set in {‘INSERTKEY_NEEDED’, ‘INSERTKEY_VISUAL’, ‘INSERTKEY_XYZ_TO_RGB’}, default {‘INSERTKEY_NEEDED’}

poll (context)

Test if Keying Set can be used or not

Return type boolean

iterator (context, ks)

Call generate() on the structs which have properties to be keyframed

generate (context, ks, data)

Add Paths to the Keying Set to keyframe the properties of the given data

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSet.type_info

2.4.277 KeyingSetPath(bpy_struct)

base class — bpy_struct

class bpy.types.KeyingSetPath (bpy_struct)

Path to a setting for use in a Keying Set

array_index

Index to the specific setting if applicable

Type int in [-inf, inf], default 0

bl_options

Keying set options

Type enum set in {'INSERTKEY_NEEDED', 'INSERTKEY_VISUAL', 'INSERTKEY_XYZ_TO_RGB'}, default {'INSERTKEY_NEEDED'}

data_path

Path to property setting

Type string, default “”

group

Name of Action Group to assign setting(s) for this path to

Type string, default “”

group_method

Method used to define which Group-name to use

Type enum in ['NAMED', 'NONE', 'KEYINGSET'], default 'NAMED'

id

ID-Block that keyframes for Keying Set should be added to (for Absolute Keying Sets only)

Type ID

id_type

Type of ID-block that can be used

Type enum in ['ACTION', 'ARMATURE', 'BRUSH', 'CAMERA', 'CURVE', 'FONT', 'GREASEPENCIL', 'GROUP', 'IMAGE', 'KEY', 'LAMP', 'LIBRARY', 'LATTICE', 'MATERIAL', 'META', 'MESH', 'NODETREE', 'OBJECT', 'PARTICLE', 'SCENE',

‘SCREEN’, ‘SOUND’, ‘TEXT’, ‘TEXTURE’, ‘WORLD’, ‘WINDOWMANAGER’], default ‘OBJECT’

use_entire_array

When an ‘array/vector’ type is chosen (Location, Rotation, Color, etc.), entire array is to be used

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- KeyingSet.paths
- KeyingSetPaths.active
- KeyingSetPaths.add
- KeyingSetPaths.remove

2.4.278 KeyingSetPaths(bpy_struct)

base class — bpy_struct

class bpy.types.KeyingSetPaths (bpy_struct)

Collection of keying set paths

active

Active Keying Set used to insert/delete keyframes

Type KeyingSetPath

active_index

Current Keying Set index

Type int in [-inf, inf], default 0

add (*target_id*, *data_path*, *index=-1*, *group_method='KEYINGSET'*, *group_name=""*)

Add a new path for the Keying Set.

Parameters

- **target_id** ([ID](#)) – Target ID, ID-Datablock for the destination.
- **data_path** ([string](#)) – Data-Path, RNA-Path to destination property.
- **index** (*int in [-1, inf], (optional)*) – Index, The index of the destination property (i.e. axis of Location/Rotation/etc.), or -1 for the entire array.
- **group_method** (*enum in ['NAMED', 'NONE', 'KEYINGSET'], (optional)*) – Grouping Method, Method used to define which Group-name to use.
- **group_name** (*string, (optional)*) – Group Name, Name of Action Group to assign destination to (only if grouping mode is to use this name).

Returns New Path, Path created and added to the Keying Set

Return type [KeyingSetPath](#)

remove (*path*)

Remove the given path from the Keying Set.

Parameters **path** ([KeyingSetPath](#), (never None)) – Path

clear()

Remove all the paths from the Keying Set.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [KeyingSet.paths](#)

2.4.279 KeyingSets(bpy_struct)

base class — `bpy_struct`

class `bpy.types.KeyingSets` (*bpy_struct*)
Scene keying sets

active
Active Keying Set used to insert/delete keyframes
Type `KeyingSet`

active_index
Current Keying Set index (negative for ‘builtin’ and positive for ‘absolute’)
Type int in [-inf, inf], default 0

new (*name="KeyingSet"*)
Add a new Keying Set to Scene.
Parameters `name` (string, (optional)) – Name, Name of Keying Set
Returns Newly created Keying Set.
Return type `KeyingSet`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.keying_sets`

2.4.280 KeyingSetsAll(bpy_struct)

base class — `bpy_struct`

class bpy.types.KeyingSetsAll (bpy_struct)
All available keying sets

active
Active Keying Set used to insert/delete keyframes
Type `KeyingSet`

active_index
Current Keying Set index (negative for ‘builtin’ and positive for ‘absolute’)
Type int in [-inf, inf], default 0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.keying_sets_all`

2.4.281 KinematicConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.KinematicConstraint (Constraint)
Inverse Kinematics

chain_count
How many bones are included in the IK effect - 0 uses all bones

Type int in [0, 255], default 0

distance
Radius of limiting sphere

Type float in [0, 100], default 0.0

ik_type

Type enum in ['COPY_POSE', 'DISTANCE'], default 'COPY_POSE'

iterations
Maximum number of solving iterations

Type int in [1, 10000], default 0

limit_mode
Distances in relation to sphere of influence to allow

Type enum in ['LIMITDIST_INSIDE', 'LIMITDIST_OUTSIDE', 'LIMITDIST_ONSURFACE'], default 'LIMITDIST_INSIDE'

lock_location_x
Constraint position along X axis

Type boolean, default False

lock_location_y
Constraint position along Y axis

Type boolean, default False

lock_location_z
Constraint position along Z axis

Type boolean, default False

lock_rotation_x
Constraint rotation along X axis

Type boolean, default False

lock_rotation_y
Constraint rotation along Y axis

Type boolean, default False

lock_rotation_z
Constraint rotation along Z axis

Type boolean, default False

orient_weight
For Tree-IK: Weight of orientation control for this target

Type float in [0.01, 1], default 0.0

pole_angle
Pole rotation offset

Type float in [-3.14159, 3.14159], default 0.0

pole_subtarget

Type string, default ""

pole_target

Object for pole rotation

Type [Object](#)

reference_axis

Constraint axis Lock options relative to Bone or Target reference

Type enum in ['BONE', 'TARGET'], default 'BONE'

subtarget

Type string, default ""

target

Target Object

Type [Object](#)

use_location

Chain follows position of target

Type boolean, default False

use_rotation

Chain follows rotation of target

Type boolean, default False

use_stretch

Enable IK Stretching

Type boolean, default False

use_tail

Include bone's tail as last element in chain

Type boolean, default False

use_target

Disable for targetless IK

Type boolean, default False

weight

For Tree-IK: Weight of position control for this target

Type float in [0.01, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`

- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.282 Lamp(ID)

base classes — `bpy_struct, ID`

subclasses — `SpotLamp, AreaLamp, HemiLamp, PointLamp, SunLamp`

class bpy.types.Lamp (ID)

Lamp datablock for lighting a scene

active_texture

Active texture slot being displayed

Type `Texture`

active_texture_index

Index of active texture slot

Type `int in [0, 17], default 0`

animation_data

Animation data for this datablock

Type `AnimData, (readonly)`

color

Light color

Type `float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)`

distance

Falloff distance - the light is at half the original intensity at this point

Type `float in [0, inf], default 0.0`

energy

Amount of light that the lamp emits

Type float in [-inf, inf], default 0.0

texture_slots

Texture slots defining the mapping and influence of textures

Type LampTextureSlots bpy_prop_collection of LampTextureSlot, (read-only)

type

Type of Lamp

Type enum in ['POINT', 'SUN', 'SPOT', 'HEMI', 'AREA'], default 'POINT'

use_diffuse

Lamp does diffuse shading

Type boolean, default False

use_negative

Lamp casts negative light

Type boolean, default False

use_own_layer

Illuminates objects only on the same layer the lamp is on

Type boolean, default False

use_specular

Lamp creates specular highlights

Type boolean, default False

Inherited Properties

- [bpy_struct.id_data](#)
- [ID.name](#)
- [ID.use_fake_user](#)
- [ID.library](#)
- [ID.tag](#)
- [ID.users](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.lamps`
- `BlendDataLamps.new`
- `BlendDataLamps.remove`

2.4.283 LampSkySettings(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.LampSkySettings (`bpy_struct`)

Sky related settings for a sun lamp

atmosphere_distance_factor

Multiplier to convert blender units to physical distance

Type float in [0, 500], default 0.0

atmosphere_extinction

Extinction scattering contribution factor

Type float in [0, 1], default 0.0

atmosphere_inscattering

Scatter contribution factor

Type float in [0, 1], default 0.0

atmosphere_turbidity

Sky turbidity

Type float in [1, 30], default 0.0

backscattered_light

Backscattered light

Type float in [-1, 1], default 0.0

horizon_brightness

Horizon brightness

Type float in [0, 20], default 0.0

sky_blend

Blend factor with sky

Type float in [0, 2], default 0.0

sky_blend_type

Blend mode for combining sun sky with world sky

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

sky_color_space

Color space to use for internal XYZ->RGB color conversion

Type enum in ['SMPTE', 'REC709', 'CIE'], default 'SMPTE'

sky_exposure

Strength of sky shading exponential exposure correction

Type float in [0, 20], default 0.0

spread

Horizon Spread

Type float in [0, 10], default 0.0

sun_brightness

Sun brightness

Type float in [0, 10], default 0.0

sun_intensity

Sun intensity

Type float in [0, 10], default 0.0

sun_size

Sun size

Type float in [0, 10], default 0.0

use_atmosphere

Apply sun effect on atmosphere

Type boolean, default False

use_sky

Apply sun effect on sky

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SunLamp.sky`

2.4.284 LampTextureSlot(TextureSlot)

base classes — `bpy_struct, TextureSlot`

class bpy.types.LampTextureSlot (TextureSlot)

Texture slot for textures in a Lamp datablock

color_factor

Amount texture affects color values

Type float in [-inf, inf], default 0.0

object

Object to use for mapping with Object texture coordinates

Type `Object`

shadow_factor

Amount texture affects shadow

Type float in [-inf, inf], default 0.0

texture_coords

Type enum in ['GLOBAL', 'VIEW', 'OBJECT'], default 'GLOBAL'

use_map_color

Lets the texture affect the basic color of the lamp

Type boolean, default False

use_map_shadow

Lets the texture affect the shadow color of the lamp

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `TextureSlot.name`
- `TextureSlot.blend_type`
- `TextureSlot.color`
- `TextureSlot.default_value`
- `TextureSlot.invert`
- `TextureSlot.offset`
- `TextureSlot.output_node`
- `TextureSlot.use_rgb_to_intensity`

- `TextureSlot.scale`
- `TextureSlot.use_stencil`
- `TextureSlot.texture`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Lamp.texture_slots`
- `LampTextureSlots.add`
- `LampTextureSlots.create`

2.4.285 LampTextureSlots(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.LampTextureSlots` (`bpy_struct`)
Collection of texture slots

classmethod add()
add

Returns The newly initialized mtex.

Return type `LampTextureSlot`

classmethod create(index)
create

Parameters `index (int in [0, inf])` – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type `LampTextureSlot`

classmethod clear(index)
clear

Parameters `index (int in [0, inf])` – Index, Slot index to clear.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Lamp.texture_slots

2.4.286 Lattice(ID)

base classes — bpy_struct, ID

```
class bpy.types.Lattice(ID)
    Lattice datablock defining a grid for deforming other objects

    animation_data
        Animation data for this datablock
            Type AnimData, (readonly)

    interpolation_type_u
        Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default
        'KEY_LINEAR'

    interpolation_type_v
        Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default
        'KEY_LINEAR'

    interpolation_type_w
        Type enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default
        'KEY_LINEAR'

    points
        Points of the lattice
```

Type bpy_prop_collection of LatticePoint, (readonly)

points_u

Points in U direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

points_v

Points in V direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

points_w

Points in W direction (can't be changed when there are shape keys)

Type int in [1, 64], default 0

shape_keys

Type Key, (readonly)

use_outside

Only draw, and take into account, the outer vertices

Type boolean, default False

vertex_group

Vertex group to apply the influence of the lattice

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.lattices`
- `BlendDataLattices.new`
- `BlendDataLattices.remove`

2.4.287 LatticeModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.LatticeModifier(*Modifier*)

Lattice deformation modifier

object

Lattice object to deform with

Type `Object`

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type `string, default “”`

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.288 LatticePoint(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.LatticePoint (bpy_struct)`

Point in the lattice grid

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

co_deform

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

groups

Weights for the vertex groups this point is member of

Type `bpy_prop_collection` of `VertexGroupElement`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Lattice.points`

2.4.289 Library(ID)

base classes — `bpy_struct, ID`

class bpy.types.Library (ID)

External .blend file from which data is linked

filepath

Path to the library .blend file

Type string, default “”

parent

Type `Library`, (readonly)

users_id

ID datablocks which use this library (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- BlendData.libraries
- ID.library
- Library.parent

2.4.290 LimitDistanceConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.LimitDistanceConstraint (Constraint)

Limits the distance from target object

distance

Radius of limiting sphere

Type float in [0, 100], default 0.0

limit_mode

Distances in relation to sphere of influence to allow

Type enum in ['LIMITDIST_INSIDE', 'LIMITDIST_OUTSIDE', 'LIMITDIST_ONSURFACE'], default 'LIMITDIST_INSIDE'

subtarget

Type string, default “”

target

Target Object

Type Object

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`
- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.291 LimitLocationConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.LimitLocationConstraint (Constraint)
Limits the location of the constrained object

max_x

Highest X value to allow

Type float in [-1000, 1000], default 0.0

max_y

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

max_z

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

min_x

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

min_y

Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

min_z

Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

use_max_x

Use the maximum X value

Type boolean, default False

use_max_y

Use the maximum Y value

Type boolean, default False

use_max_z

Use the maximum Z value

Type boolean, default False

use_min_x

Use the minimum X value

Type boolean, default False

use_min_y

Use the minimum Y value

Type boolean, default False

use_min_z

Use the minimum Z value

Type boolean, default False

use_transform_limit

Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.292 LimitRotationConstraint(Constraint)

base classes — `bpy_struct`, `Constraint`

`class bpy.types.LimitRotationConstraint (Constraint)`

Limits the rotation of the constrained object

`max_x`

Highest X value to allow

Type float in [-1000, 1000], default 0.0

`max_y`

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

`max_z`

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

`min_x`

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

`min_y`

Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

`min_z`

Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

`use_limit_x`

Use the minimum X value

Type boolean, default False

`use_limit_y`

Use the minimum Y value

Type boolean, default False

`use_limit_z`

Use the minimum Z value

Type boolean, default False

`use_transform_limit`

Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`

- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.293 LimitScaleConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**LimitScaleConstraint** (*Constraint*)

Limits the scaling of the constrained object

max_x

Highest X value to allow

Type float in [-1000, 1000], default 0.0

max_y

Highest Y value to allow

Type float in [-1000, 1000], default 0.0

max_z

Highest Z value to allow

Type float in [-1000, 1000], default 0.0

min_x

Lowest X value to allow

Type float in [-1000, 1000], default 0.0

min_y

Lowest Y value to allow

Type float in [-1000, 1000], default 0.0

min_z

Lowest Z value to allow

Type float in [-1000, 1000], default 0.0

use_max_x

Use the maximum X value

Type boolean, default False

use_max_y

Use the maximum Y value

Type boolean, default False

use_max_z

Use the maximum Z value

Type boolean, default False

use_min_x

Use the minimum X value

Type boolean, default False

use_min_y

Use the minimum Y value

Type boolean, default False

use_min_z

Use the minimum Z value

Type boolean, default False

use_transform_limit

Transforms are affected by this constraint as well

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.294 LockedTrackConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class bpy.types.LockedTrackConstraint (Constraint)

Points toward the target along the track axis, while locking the other axis

lock_axis

Axis that points upward

Type enum in ['LOCK_X', 'LOCK_Y', 'LOCK_Z'], default 'LOCK_X'

subtarget

Type string, default ""

target

Target Object

Type Object

track_axis

Axis that points to the target object

Type enum in ['TRACK_X', 'TRACK_Y', 'TRACK_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'TRACK_X'

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`

- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.295 Macro(bpy_struct)

base class — bpy_struct

class bpy.types.Macro (*bpy_struct*)

Storage of a macro operator being executed, or registered after execution

bl_description

Type string, default “”

bl_idname

Type string, default “”

bl_label

Type string, default “”

bl_options

Options for this operator type

Type enum set in {‘REGISTER’, ‘UNDO’, ‘BLOCKING’, ‘MACRO’, ‘GRAB_POINTER’, ‘PRESET’, ‘INTERNAL’}, default {‘REGISTER’}

name

Type string, default “”, (readonly)

properties

Type OperatorProperties, (readonly, never None)

report (*type, message*)
report

Parameters

- **type** (*enum set in {‘DEBUG’, ‘INFO’, ‘OPERATOR’, ‘WARNING’, ‘ERROR’, ‘ERROR_INVALID_INPUT’, ‘ERROR_INVALID_CONTEXT’, ‘ERROR_OUT_OF_MEMORY’}*) – Type
- **message** (*string*) – Report Message

classmethod poll (*context*)

Test if the operator can be called or not.

Return type

boolean

draw (*context*)

Draw function for the operator.

define (*opname*)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.296 MagicTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.MagicTexture (*Texture*)
Procedural noise texture

noise_depth

Sets the depth of the cloud calculation

Type int in [0, 30], default 0

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.297 MaintainVolumeConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.**MaintainVolumeConstraint** (*Constraint*)

Maintains a constant volume along a single scaling axis

free_axis

The free scaling axis of the object

Type enum in ['SAMEVOL_X', 'SAMEVOL_Y', 'SAMEVOL_Z'], default 'SAMEVOL_X'

volume

Volume of the bone at rest

Type float in [0.001, 100], default 0.0

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.298 MarbleTexture(Texture)

base classes — `bpy_struct`, `ID`, `Texture`

class bpy.types.MarbleTexture (Texture)

Procedural noise texture

marble_type

Type enum in ['SOFT', 'SHARP', 'SHARPER'], default 'SOFT'

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_basis_2

Type enum in ['SIN', 'SAW', 'TRI'], default 'SIN'

noise_depth

Sets the depth of the cloud calculation

Type int in [0, 30], default 0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`

- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.299 MaskModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.MaskModifier (Modifier)
Mask modifier to hide parts of the mesh

armature

Armature to use as source of bones to mask

Type [Object](#)

invert_vertex_group

Use vertices that are not part of region defined

Type boolean, default False

mode

Type enum in ['VERTEX_GROUP', 'ARMATURE'], default 'VERTEX_GROUP'

vertex_group

Vertex group name

Type string, default ""

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.300 Material(ID)

base classes — `bpy_struct, ID`

```
class bpy.types.Material(ID)
    Material datablock to defined the appearance of geometric objects for rendering

    active_node_material
        Active node material
        Type Material

    active_texture
        Active texture slot being displayed
        Type Texture

    active_texture_index
        Index of active texture slot
        Type int in [0, 17], default 0

    alpha
        Alpha transparency of the material
        Type float in [0, 1], default 0.0

    ambient
        Amount of global ambient color the material receives
        Type float in [0, 1], default 0.0

    animation_data
        Animation data for this datablock
        Type AnimData, (readonly)

    darkness
        Minnaert darkness
        Type float in [0, 2], default 0.0

    diffuse_color
        Diffuse color of the material
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    diffuse_fresnel
        Power of Fresnel
        Type float in [0, 5], default 0.0

    diffuse_fresnel_factor
        Blending factor of Fresnel
        Type float in [0, 5], default 0.0

    diffuse_intensity
        Amount of diffuse reflection
        Type float in [0, 1], default 0.0

    diffuse_ramp
        Color ramp used to affect diffuse shading
        Type ColorRamp, (readonly)

    diffuse_ramp_blend
        Blending method of the ramp and the diffuse color
```

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

diffuse_ramp_factor

Blending factor (also uses alpha in Colorband)

Type float in [0, 1], default 0.0

diffuse_ramp_input

Determines how the ramp maps on the surface

Type enum in ['SHADER', 'ENERGY', 'NORMAL', 'RESULT'], default 'SHADER'

diffuse_shader

Type enum in ['LAMBERT', 'OREN_NAYAR', 'TOON', 'MINNAERT', 'FRESNEL'], default 'LAMBERT'

diffuse_toon_size

Size of diffuse toon area

Type float in [0, 3.14], default 0.0

diffuse_toon_smooth

Smoothness of diffuse toon area

Type float in [0, 1], default 0.0

emit

Amount of light to emit

Type float in [0, inf], default 0.0

halo

Halo settings for the material

Type [MaterialHalo](#), (readonly, never None)

invert_z

Renders material's faces with an inverted Z buffer (scanline only)

Type boolean, default False

light_group

Limit lighting to lamps in this Group

Type [Group](#)

mirror_color

Mirror color of the material

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

node_tree

Node tree for node based materials

Type [NodeTree](#), (readonly)

offset_z

Gives faces an artificial offset in the Z buffer for Z transparency

Type float in [-inf, inf], default 0.0

physics

Game physics settings

Type `MaterialPhysics`, (readonly, never None)

preview_render_type
Type of preview render

Type enum in ['FLAT', 'SPHERE', 'CUBE', 'MONKEY', 'HAIR', 'SPHERE_A'], default 'FLAT'

raytrace_mirror
Raytraced reflection settings for the material

Type `MaterialRaytraceMirror`, (readonly, never None)

raytrace_transparency
Raytraced transparency settings for the material

Type `MaterialRaytraceTransparency`, (readonly, never None)

roughness
Oren-Nayar Roughness

Type float in [0, 3.14], default 0.0

shadow_buffer_bias
Factor to multiply shadow buffer bias with (0 is ignore.)

Type float in [0, 10], default 0.0

shadow_cast_alpha
Shadow casting alpha, in use for Irregular and Deep shadow buffer

Type float in [0.001, 1], default 0.0

shadow_only_type
How to draw shadows

Type enum in ['SHADOW_ONLY_OLD', 'SHADOW_ONLY_SHADED'], default 'SHADOW_ONLY_OLD' 'SHADOW_ONLY',

shadow_ray_bias
Shadow raytracing bias to prevent terminator problems on shadow boundary

Type float in [0, 0.25], default 0.0

specular_alpha
Alpha transparency for specular areas

Type float in [0, 1], default 0.0

specular_color
Specular color of the material

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

specular_hardness
How hard (sharp) the specular reflection is

Type int in [1, 511], default 0

specular_intensity
How intense (bright) the specular reflection is

Type float in [0, 1], default 0.0

specular_ior
Specular index of refraction

Type float in [1, 10], default 0.0

specular_ramp

Color ramp used to affect specular shading

Type [ColorRamp](#), (readonly)

specular_ramp_blend

Blending method of the ramp and the specular color

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

specular_ramp_factor

Blending factor (also uses alpha in Colorband)

Type float in [0, 1], default 0.0

specular_ramp_input

Determines how the ramp maps on the surface

Type enum in ['SHADER', 'ENERGY', 'NORMAL', 'RESULT'], default 'SHADER'

specular_shader

Type enum in ['COOKTORR', 'PHONG', 'BLINN', 'TOON', 'WARDISO'], default 'COOKTORR'

specular_slope

The standard deviation of surface slope

Type float in [0, 0.4], default 0.0

specular_toon_size

Size of specular toon area

Type float in [0, 1.53], default 0.0

specular_toon_smooth

Smoothness of specular toon area

Type float in [0, 1], default 0.0

strand

Strand settings for the material

Type [MaterialStrand](#), (readonly, never None)

subsurface_scattering

Subsurface scattering settings for the material

Type [MaterialSubsurfaceScattering](#), (readonly, never None)

texture_slots

Texture slots defining the mapping and influence of textures

Type [MaterialTextureSlots](#) bpy_prop_collection
of
[MaterialTextureSlot](#), (readonly)

translucency

Amount of diffuse shading on the back side

Type float in [0, 1], default 0.0

transparency_method

Method to use for rendering transparency

Type enum in ['MASK', 'Z_TRANSPARENCY', 'RAYTRACE'], default 'MASK'

type

Material type defining how the object is rendered

Type enum in ['SURFACE', 'WIRE', 'VOLUME', 'HALO'], default 'SURFACE'

use_cast_approximate

Allow this material to cast shadows when using approximate ambient occlusion.

Type boolean, default False

use_cast_buffer_shadows

Allow this material to cast shadows from shadow buffer lamps

Type boolean, default False

use_cast_shadows_only

Makes objects with this material appear invisible, only casting shadows (not rendered)

Type boolean, default False

use_cubic

Use cubic interpolation for diffuse values, for smoother transitions

Type boolean, default False

use_diffuse_ramp

Toggle diffuse ramp operations

Type boolean, default False

use_face_texture

Replaces the object's base color with color from face assigned image textures

Type boolean, default False

use_face_texture_alpha

Replaces the object's base alpha value with alpha from face assigned image textures

Type boolean, default False

use_full_oversampling

Force this material to render full shading/textures for all anti-aliasing samples

Type boolean, default False

use_light_group_exclusive

Material uses the light group exclusively - these lamps are excluded from other scene lighting

Type boolean, default False

use_mist

Use mist with this material (in world settings)

Type boolean, default False

use_nodes

Use shader nodes to render the material

Type boolean, default False

use_object_color

Modulate the result with a per-object color

Type boolean, default False

use_only_shadow
Renders shadows as the material's alpha value, making materials transparent except for shadowed areas

Type boolean, default False

use_ray_shadow_bias
Prevents raytraced shadow errors on surfaces with smooth shaded normals (terminator problem)

Type boolean, default False

use_raytrace
Include this material and geometry that uses it in ray tracing calculations

Type boolean, default False

use_shadeless
Makes this material insensitive to light or shadow

Type boolean, default False

use_shadows
Allows this material to receive shadows

Type boolean, default False

use_sky
Renders this material with zero alpha, with sky background in place (scanline only)

Type boolean, default False

use_specular_ramp
Toggle specular ramp operations

Type boolean, default False

use_tangent_shading
Use the material's tangent vector instead of the normal for shading - for anisotropic shading effects

Type boolean, default False

use_textures
Enable/Disable each texture

Type boolean array of 18 items, default (False, False, False)

use_transparency
Render material as transparent

Type boolean, default False

use_transparent_shadows
Allow this object to receive transparent shadows cast through other objects

Type boolean, default False

use_vertex_color_light
Add vertex colors as additional lighting

Type boolean, default False

use_vertex_color_paint
Replaces object base color with vertex colors (multiplies with 'texture face' face assigned textures)

Type boolean, default False

volume

Volume settings for the material

Type `MaterialVolume`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.materials`
- `BlendDataMaterials.new`
- `BlendDataMaterials.remove`
- `Curve.materials`
- `IDMaterials.append`
- `IDMaterials.pop`
- `Material.active_node_material`
- `MaterialSlot.material`
- `Mesh.materials`
- `MetaBall.materials`
- `Object.active_material`
- `RenderLayer.material_override`

- `SceneRenderLayer.material_override`
- `ShaderNodeExtendedMaterial.material`
- `ShaderNodeMaterial.material`
- `TouchSensor.material`

2.4.301 MaterialHalo(`bpy_struct`)

base class — `bpy_struct`

```
class bpy.types.MaterialHalo (bpy_struct)
    Halo particle effect settings for a Material datablock

    add
        Sets the strength of the add effect
        Type float in [0, 1], default 0.0

    flare_boost
        Gives the flare extra strength
        Type float in [0.1, 10], default 0.0

    flare_seed
        Specifies an offset in the flare seed table
        Type int in [0, 255], default 0

    flare_size
        Sets the factor by which the flare is larger than the halo
        Type float in [0.1, 25], default 0.0

    flare_subflare_count
        Sets the number of sub-flares
        Type int in [1, 32], default 0

    flare_subflare_size
        Sets the dimension of the sub-flares, dots and circles
        Type float in [0.1, 25], default 0.0

    hardness
        Sets the hardness of the halo
        Type int in [0, 127], default 0

    line_count
        Sets the number of star shaped lines rendered over the halo
        Type int in [0, 250], default 0

    ring_count
        Sets the number of rings rendered over the halo
        Type int in [0, 24], default 0

    seed
        Randomizes ring dimension and line location
        Type int in [0, 255], default 0

    size
        Sets the dimension of the halo
```

Type float in [0, 100], default 0.0

star_tip_count
Sets the number of points on the star shaped halo

Type int in [3, 50], default 0

use_extreme_alpha
Uses extreme alpha

Type boolean, default False

use_flare_mode
Renders halo as a lens flare

Type boolean, default False

use_lines
Renders star shaped lines over halo

Type boolean, default False

use_ring
Renders rings over halo

Type boolean, default False

use_shaded
Lets halo receive light and shadows from external objects

Type boolean, default False

use_soft
Softens the edges of halos at intersections with other geometry

Type boolean, default False

use_star
Renders halo as a star

Type boolean, default False

use_texture
Gives halo a texture

Type boolean, default False

use_vertex_normal
Uses the vertex normal to specify the dimension of the halo

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.halo

2.4.302 MaterialPhysics(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialPhysics** (bpy_struct)

Physics settings for a Material datablock

elasticity

Elasticity of collisions

Type float in [0, 1], default 0.0

fh_damping

Damping of the spring force, when inside the physics distance area

Type float in [0, 1], default 0.0

fh_distance

Distance of the physics area

Type float in [0, 20], default 0.0

fh_force

Upward spring force, when inside the physics distance area

Type float in [0, 1], default 0.0

friction

Coulomb friction coefficient, when inside the physics distance area

Type float in [0, 100], default 0.0

use_fh_normal

Align dynamic game objects along the surface normal, when inside the physics distance area

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Material.physics`

2.4.303 MaterialRaytraceMirror(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.MaterialRaytraceMirror(bpy_struct)`

Raytraced reflection settings for a Material datablock

`depth`

Maximum allowed number of light inter-reflections

Type int in [0, 32767], default 0

`distance`

Maximum distance of reflected rays. Reflections further than this range fade to sky color or material color

Type float in [0, 10000], default 0.0

`fade_to`

The color that rays with no intersection within the Max Distance take. Material color can be best for indoor scenes, sky color for outdoor

Type enum in ['FADE_TO_SKY', 'FADE_TO_MATERIAL'], default 'FADE_TO_SKY'

`fresnel`

Power of Fresnel for mirror reflection

Type float in [0, 5], default 0.0

`fresnel_factor`

Blending factor for Fresnel

Type float in [0, 5], default 0.0

`gloss_anisotropic`

The shape of the reflection, from 0.0 (circular) to 1.0 (fully stretched along the tangent)

Type float in [0, 1], default 0.0

gloss_factor

The shininess of the reflection. Values < 1.0 give diffuse, blurry reflections

Type float in [0, 1], default 0.0

gloss_samples

Number of cone samples averaged for blurry reflections

Type int in [0, 1024], default 0

gloss_threshold

Threshold for adaptive sampling. If a sample contributes less than this amount (as a percentage), sampling is stopped

Type float in [0, 1], default 0.0

reflect_factor

Sets the amount mirror reflection for raytrace

Type float in [0, 1], default 0.0

use

Enable raytraced reflections

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Material.raytrace_mirror`

2.4.304 MaterialRaytraceTransparency([bpy_struct](#))

base class — [bpy_struct](#)

class bpy.types.MaterialRaytraceTransparency ([bpy_struct](#))

Raytraced refraction settings for a Material datablock

depth

Maximum allowed number of light inter-refractions

Type int in [0, 32767], default 0

depth_max

Maximum depth for light to travel through the transparent material before becoming fully filtered (0.0 is disabled)

Type float in [0, 100], default 0.0

falloff

Falloff power for transmissivity filter effect (1.0 is linear)

Type float in [0.1, 10], default 0.0

filter

Amount to blend in the material's diffuse color in raytraced transparency (simulating absorption)

Type float in [0, 1], default 0.0

fresnel

Power of Fresnel for transparency (Ray or ZTransp)

Type float in [0, 5], default 0.0

fresnel_factor

Blending factor for Fresnel

Type float in [1, 5], default 0.0

gloss_factor

The clarity of the refraction. Values < 1.0 give diffuse, blurry refractions

Type float in [0, 1], default 0.0

gloss_samples

Number of cone samples averaged for blurry refractions

Type int in [0, 1024], default 0

gloss_threshold

Threshold for adaptive sampling. If a sample contributes less than this amount (as a percentage), sampling is stopped

Type float in [0, 1], default 0.0

ior

Sets angular index of refraction for raytraced refraction

Type float in [0.25, 4], default 0.0

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Material.raytrace_transparency`

2.4.305 MaterialSlot(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MaterialSlot` (`bpy_struct`)
Material slot in an object

link

Link material to object or the object's data

Type enum in ['OBJECT', 'DATA'], default 'DATA'

material

Material datablock used by this material slot

Type `Material`

name

Material slot name

Type string, default "", (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.material_slots

2.4.306 MaterialStrand(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MaterialStrand(bpy_struct)`

Strand settings for a Material datablock

blend_distance

Worldspace distance over which to blend in the surface normal

Type float in [0, 10], default 0.0

root_size

Start size of strands in pixels or Blender units

Type float in [0, inf], default 0.0

shape

Positive values make strands rounder, negative makes strands spiky

Type float in [-0.9, 0.9], default 0.0

size_min

Minimum size of strands in pixels

Type float in [0.001, 10], default 0.0

tip_size

End size of strands in pixels or Blender units

Type float in [0, inf], default 0.0

use_blender_units

Use Blender units for widths instead of pixels

Type boolean, default False

use_surface_diffuse

Make diffuse shading more similar to shading the surface

Type boolean, default False, (readonly)

use_tangent_shading

Uses direction of strands as normal for tangent-shading

Type boolean, default False

uv_layer

Name of UV layer to override

Type string, default “”

width_fade

Transparency along the width of the strand

Type float in [0, 2], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.strand

2.4.307 MaterialSubsurfaceScattering(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialSubsurfaceScattering** (*bpy_struct*)

Diffuse subsurface scattering settings for a Material datablock

back

Back scattering weight

Type float in [0, 10], default 0.0

color

Scattering color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

color_factor

Blend factor for SSS colors

Type float in [0, 1], default 0.0

error_threshold

Error tolerance (low values are slower and higher quality)

Type float in [-inf, inf], default 0.0

front

Front scattering weight

Type float in [0, 2], default 0.0

ior

Index of refraction (higher values are denser)

Type float in [-inf, inf], default 0.0

radius

Mean red/green/blue scattering path length

Type float array of 3 items in [0.001, inf], default (0.0, 0.0, 0.0)

scale

Object scale factor

Type float in [-inf, inf], default 0.0

texture_factor

Texture scattering blend factor

Type float in [0, 1], default 0.0

use

Enable diffuse subsurface scattering effects in a material

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.subsurface_scattering

2.4.308 MaterialTextureSlot(TextureSlot)

base classes — bpy_struct, TextureSlot

class bpy.types.MaterialTextureSlot (TextureSlot)

Texture slot for textures in a Material datablock

alpha_factor

Amount texture affects alpha

Type float in [-inf, inf], default 0.0

ambient_factor

Amount texture affects ambient

Type float in [-inf, inf], default 0.0

bump_method

Method to use for bump mapping

Type enum in ['BUMP_ORIGINAL', 'BUMP_COMPATIBLE', 'BUMP_DEFAULT', 'BUMP_BEST_QUALITY'], default 'BUMP_ORIGINAL'

bump_objectspace

Space to apply bump mapping in

Type enum in ['BUMP_VIEWSPACE', 'BUMP_OBJECTSPACE', 'BUMP_TEXTURESPACE'], default 'BUMP_VIEWSPACE'

density_factor

Amount texture affects density

Type float in [-inf, inf], default 0.0

diffuse_color_factor

Amount texture affects diffuse color

Type float in [-inf, inf], default 0.0

diffuse_factor

Amount texture affects diffuse reflectivity

Type float in [-inf, inf], default 0.0

displacement_factor

Amount texture displaces the surface

Type float in [-inf, inf], default 0.0

emission_color_factor

Amount texture affects emission color

Type float in [-inf, inf], default 0.0

emission_factor

Amount texture affects emission

Type float in [-inf, inf], default 0.0

emit_factor

Amount texture affects emission

Type float in [-inf, inf], default 0.0

hardness_factor

Amount texture affects hardness

Type float in [-inf, inf], default 0.0

mapping

Type enum in ['FLAT', 'CUBE', 'TUBE', 'SPHERE'], default 'FLAT'

mapping_x

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_y

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mapping_z

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

mirror_factor

Amount texture affects mirror color

Type float in [-inf, inf], default 0.0

normal_factor

Amount texture affects normal values

Type float in [-inf, inf], default 0.0

normal_map_space

Sets space of normal map image

Type enum in ['CAMERA', 'WORLD', 'OBJECT', 'TANGENT'], default 'CAMERA'

object

Object to use for mapping with Object texture coordinates

Type Object

raymir_factor

Amount texture affects ray mirror

Type float in [-inf, inf], default 0.0

reflection_color_factor

Amount texture affects color of out-scattered light

Type float in [-inf, inf], default 0.0

reflection_factor

Amount texture affects brightness of out-scattered light

Type float in [-inf, inf], default 0.0

scattering_factor
Amount texture affects scattering

Type float in [-inf, inf], default 0.0

specular_color_factor
Amount texture affects specular color

Type float in [-inf, inf], default 0.0

specular_factor
Amount texture affects specular reflectivity

Type float in [-inf, inf], default 0.0

texture_coords

Type enum in ['GLOBAL', 'OBJECT', 'UV', 'ORCO', 'STRAND', 'STICKY', 'WINDOW', 'NORMAL', 'REFLECTION', 'STRESS', 'TANGENT'], default 'GLOBAL'

translucency_factor
Amount texture affects translucency

Type float in [-inf, inf], default 0.0

transmission_color_factor
Amount texture affects result color after light has been scattered/absorbed

Type float in [-inf, inf], default 0.0

use
Enable this material texture slot

Type boolean, default False

use_from_dupli
Dupli's instanced from verts, faces or particles, inherit texture coordinate from their parent

Type boolean, default False

use_from_original
Dupli's derive their object coordinates from the original objects transformation

Type boolean, default False

use_map_alpha
Causes the texture to affect the alpha value

Type boolean, default False

use_map_ambient
Causes the texture to affect the value of ambient

Type boolean, default False

use_map_color_diffuse
Causes the texture to affect basic color of the material

Type boolean, default False

use_map_color_emission
Causes the texture to affect the color of emission

Type boolean, default False

use_map_color_reflection

Causes the texture to affect the color of scattered light

Type boolean, default False

use_map_color_spec

Causes the texture to affect the specularity color

Type boolean, default False

use_map_color_transmission

Causes the texture to affect the result color after other light has been scattered/absorbed

Type boolean, default False

use_map_density

Causes the texture to affect the volume's density

Type boolean, default False

use_map_diffuse

Causes the texture to affect the value of the materials diffuse reflectivity

Type boolean, default False

use_map_displacement

Let the texture displace the surface

Type boolean, default False

use_map_emission

Causes the texture to affect the volume's emission

Type boolean, default False

use_map_emit

Causes the texture to affect the emit value

Type boolean, default False

use_map_hardness

Causes the texture to affect the hardness value

Type boolean, default False

use_map_mirror

Causes the texture to affect the mirror color

Type boolean, default False

use_map_normal

Causes the texture to affect the rendered normal

Type boolean, default False

use_map_raymir

Causes the texture to affect the ray-mirror value

Type boolean, default False

use_map_reflect

Causes the texture to affect the reflected light's brightness

Type boolean, default False

use_map_scatter

Causes the texture to affect the volume's scattering

Type boolean, default False

use_map_specular

Causes the texture to affect the value of specular reflectivity

Type boolean, default False

use_map_translucency

Causes the texture to affect the translucency value

Type boolean, default False

use_map_warp

Let the texture warp texture coordinates of next channels

Type boolean, default False

uv_layer

UV layer to use for mapping with UV texture coordinates

Type string, default “”

warp_factor

Amount texture affects texture coordinates of next channels

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Material.texture_slots`
- `MaterialTextureSlots.add`
- `MaterialTextureSlots.create`

2.4.309 MaterialTextureSlots(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MaterialTextureSlots(bpy_struct)`

Collection of texture slots

classmethod `add()`

add

Returns The newly initialized mtex.

Return type `MaterialTextureSlot`

classmethod `create(index)`

create

Parameters `index (int in [0, inf])` – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type `MaterialTextureSlot`

classmethod `clear(index)`

clear

Parameters `index (int in [0, inf])` – Index, Slot index to clear.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.texture_slots

2.4.310 MaterialVolume(bpy_struct)

base class — bpy_struct

class bpy.types.**MaterialVolume** (*bpy_struct*)

Volume rendering settings for a Material datablock

asymmetry

Back scattering (-1.0) to Forward scattering (1.0) and the range in between

Type float in [-1, 1], default 0.0

cache_resolution

Resolution of the voxel grid, low resolutions are faster, high resolutions use more memory

Type int in [1, 1024], default 0

density

The base density of the volume

Type float in [0, 1], default 0.0

density_scale

Multiplier for the material's density

Type float in [0, inf], default 0.0

depth_threshold

Stop ray marching early if transmission drops below this luminance - higher values give speedups in dense volumes at the expense of accuracy

Type float in [0, 1], default 0.0

emission

Amount of light that gets emitted by the volume

Type float in [0, inf], default 0.0

emission_color

Color of emitted light

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

light_method

Method of shading, attenuating, and scattering light through the volume

Type enum in ['SHADELESS', 'SHADOWED', 'SHADED', 'MULTIPLE_SCATTERING', 'SHADED_PLUS_MULTIPLE_SCATTERING'], default 'SHADELESS'

ms_diffusion

Diffusion factor, the strength of the blurring effect

Type float in [0, inf], default 0.0

ms_intensity
Multiplier for multiple scattered light energy

Type float in [0, inf], default 0.0

ms_spread
Proportional distance over which the light is diffused

Type float in [0, inf], default 0.0

reflection
Multiplier to make out-scattered light brighter or darker (non-physically correct)

Type float in [0, inf], default 0.0

reflection_color
Color of light scattered out of the volume (does not affect transmission)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scattering
Amount of light that gets scattered out by the volume - the more out-scattering, the shallower the light will penetrate

Type float in [0, inf], default 0.0

step_method
Method of calculating the steps through the volume

Type enum in ['RANDOMIZED', 'CONSTANT'], default 'RANDOMIZED'

step_size
Distance between subsequent volume depth samples

Type float in [0, inf], default 0.0

transmission_color
Result color of the volume, after other light has been scattered/absorbed

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_external_shadows
Receive shadows from sources outside the volume (temporary)

Type boolean, default False

use_light_cache
Pre-calculate the shading information into a voxel grid, speeds up shading at slightly less accuracy

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Material.volume

2.4.311 Menu(bpy_struct)

Basic Menu Example

This script is a simple menu, menus differ from panels in that they must reference from a header, panel or another menu.

Notice the ‘CATEGORY_MT_name’ `Menu.bl_idname`, this is a naming convention for menus.

Note: Menu subclasses must be registered before referencing them from blender.

Note: Menu’s have their `Layout.operator_context` initialized as ‘EXEC_REGION_WIN’ rather than ‘INVOKE_DEFAULT’, so if the operator context needs to initialize inputs from the `Operator.invoke` function then this needs to be explicitly set.

```
import bpy

class BasicMenu(bpy.types.Menu):
    bl_idname = "OBJECT_MT_select_test"
    bl_label = "Select"

    def draw(self, context):
        layout = self.layout

        layout.operator("object.select_all", text="Select/Deselect All")
        layout.operator("object.select_inverse", text="Inverse")
        layout.operator("object.select_random", text="Random")

bpy.utils.register_class(BasicMenu)

# test call to display immediately.
bpy.ops.wm.call_menu(name="OBJECT_MT_select_test")
```

Submenus

This menu demonstrates some different functions.

```
import bpy

class SubMenu(bpy.types.Menu):
    bl_idname = "OBJECT_MT_select_submenu"
    bl_label = "Select"

    def draw(self, context):
        layout = self.layout

        layout.operator("object.select_all", text="Select/Deselect All")
        layout.operator("object.select_inverse", text="Inverse")
        layout.operator("object.select_random", text="Random")

        # access this operator as a submenu
        layout.operator_menu_enum("object.select_by_type", "type", text="Select All by Type...")

        layout.separator()

        # expand each operator option into this menu
        layout.operator_enum("object.lamp_add", "type")

        layout.separator()

        # use existing menu
        layout.menu("VIEW3D_MT_transform")

bpy.utils.register_class(SubMenu)

# test call to display immediately.
bpy.ops.wm.call_menu(name="OBJECT_MT_select_submenu")
```

Extending Menus

When creating menus for addons you can't reference menus in blenders default scripts.

Instead the addon can add menu items to existing menus.

The function menu_draw acts like Menu.draw

```
import bpy

def menu_draw(self, context):
    self.layout.operator("wm.save_homefile")

bpy.types.INFO_MT_file.append(menu_draw)

base class — bpy_struct
class bpy.types.Menu(bpy_struct)
    Editor menu containing buttons
```

bl_idname

If this is set, the menu gets a custom ID, otherwise it takes the name of the class used to define the panel. For example, if the class name is “OBJECT_MT_hello”, and bl_idname is not set by the script, then bl_idname = “OBJECT_MT_hello”

Type string, default “”

bl_label

The menu label

Type string, default “”

layout

Defines the structure of the menu in the UI.

TypeUILayout, (readonly)

classmethod poll (context)

If this method returns a non-null output, then the menu can be drawn.

Return type boolean

draw (context)

Draw UI elements into the menu UI layout.

classmethod append (draw_func)

Append a draw function to this menu, takes the same arguments as the menus draw function.

draw_preset (context)

Define these on the subclass

- preset_operator
- preset_subdir

path_menu (searchpaths, operator, props_default={})

classmethod prepend (draw_func)

Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove (draw_func)

Remove a draw function that has been added to this menu

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.312 Mesh(ID)

base classes — bpy_struct, ID

class bpy.types.Mesh (ID)

Mesh datablock defining geometric surfaces

animation_data

Animation data for this datablock

Type AnimData, (readonly)

auto_smooth_angle

Defines maximum angle between face normals that ‘Auto Smooth’ will operate on

Type float in [-inf, inf], default 0.0

edges

Edges of the mesh

Type MeshEdges bpy_prop_collection of MeshEdge, (readonly)

faces

Faces of the mesh

Type MeshFaces bpy_prop_collection of MeshFace, (readonly)

layers_float

Type bpy_prop_collection of MeshFloatPropertyLayer, (readonly)

layers_int

Type bpy_prop_collection of MeshIntPropertyLayer, (readonly)

layers_string

Type bpy_prop_collection of MeshStringPropertyLayer, (readonly)

materials

Type IDMaterials bpy_prop_collection of Material, (readonly)

shape_keys

Type Key, (readonly)

show_all_edges

Displays all edges for wireframe in all view modes in the 3D view

Type boolean, default False

show_double_sided

Render/display the mesh with double or single sided lighting

Type boolean, default False

show_edge_bevel_weight

Displays weights created for the Bevel modifier

Type boolean, default False

show_edge_creature

Displays creases created for subsurf weighting

Type boolean, default False

show_edge_seams

Displays UV unwrapping seams

Type boolean, default False

show_edge_sharp

Displays sharp edges, used with the EdgeSplit modifier

Type boolean, default False

show_edges

Displays selected edges using highlights in the 3D view and UV editor

Type boolean, default False

show_extra_edge_length

Displays selected edge lengths, Using global values when set in the transform panel

Type boolean, default False

show_extra_face_angle

Displays the angles in the selected edges in degrees, Using global values when set in the transform panel

Type boolean, default False

show_extra_face_area

Displays the area of selected faces, Using global values when set in the transform panel

Type boolean, default False

show_faces

Displays all faces as shades in the 3D view and UV editor

Type boolean, default False

show_normal_face

Displays face normals as lines

Type boolean, default False

show_normal_vertex

Displays vertex normals as lines

Type boolean, default False

sticky

Sticky texture coordinates

Type [bpy_prop_collection](#) of [MeshSticky](#), (readonly)

texco_mesh

Derive texture coordinates from another mesh

Type [Mesh](#)

texspace_location

Texture space location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size
Texture space size

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texture_mesh
Use another mesh for texture indices (vertex indices must be aligned)

Type [Mesh](#)

total_edge_sel
Selected edge count in editmode

Type int in [0, inf], default 0, (readonly)

total_face_sel
Selected face count in editmode

Type int in [0, inf], default 0, (readonly)

total_vert_sel
Selected vertex count in editmode

Type int in [0, inf], default 0, (readonly)

use_auto_smooth
Treats all set-smoothed faces with angles less than the specified angle as ‘smooth’ during render

Type boolean, default False

use_auto_tinspace
Adjusts active object’s texture space automatically when transforming object

Type boolean, default False

use_mirror_topology
Use topology based mirroring. For when both sides of mesh have matching, unique topology

Type boolean, default False

use_mirror_x
X Axis mirror editing

Type boolean, default False

use_paint_mask
Face selection masking for painting

Type boolean, default False

uv_texture_clone
UV texture to be used as cloning source

Type [MeshTextureFaceLayer](#)

uv_texture_clone_index
Clone UV texture index

Type int in [0, inf], default 0

uv_texture_stencil
UV texture to mask the painted area

Type [MeshTextureFaceLayer](#)

uv_texture_stencil_index

Mask UV texture index

Type int in [0, inf], default 0

uv_textures

Type UVTextures bpy_prop_collection of MeshTextureFaceLayer, (readonly)

vertex_colors

Type VertexColors bpy_prop_collection of MeshColorLayer, (readonly)

vertices

Vertices of the mesh

Type MeshVertices bpy_prop_collection of MeshVertex, (readonly)

edge_keys

(readonly)

transform (matrix)

Transform mesh vertices by a matrix.

Parameters **matrix** (float array of 16 items in [-inf, inf]) – Matrix.

calc_normals ()

Calculate vertex normals.

update (calc_edges=False)

update

Parameters **calc_edges** (boolean, (optional)) – Calculate Edges, Force recalculation of edges.

validate (verbose=False)

validate geometry, return True when the mesh has had invalid geometry corrected/removed.

Parameters **verbose** (boolean, (optional)) – Verbose, Output information about the errors found

Returns Result

Return type boolean

from_pydata (vertices, edges, faces)

Make a mesh from a list of verts/edges/faces Until we have a nicer way to make geometry, use this.

Parameters

- **vertices** (iterable object) – float triplets each representing (X, Y, Z) eg: [(0.0, 1.0, 0.5), ...].
- **edges** (iterable object) – int pairs, each pair contains two indices to the *vertices* argument. eg: [(1, 2), ...]
- **faces** (iterable object) – iterator of faces, each faces contains three or four indices to the *vertices* argument. eg: [(5, 6, 8, 9), (1, 2, 3), ...]

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.meshes`
- `BlendDataMeshes.new`
- `BlendDataMeshes.remove`
- `EditObjectActuator.mesh`
- `Mesh.texco_mesh`
- `Mesh.texture_mesh`
- `Object.to_mesh`

2.4.313 MeshColor(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MeshColor(bpy_struct)`
Vertex colors for a face in a Mesh

color1
Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color2
Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color3
Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

color4
Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshColorLayer.data

2.4.314 MeshColorLayer(bpy_struct)

base class — bpy_struct

class bpy.types.MeshColorLayer (bpy_struct)

Layer of vertex colors in a Mesh datablock

active

Sets the layer as active for display and editing

Type boolean, default False

active_render

Sets the layer as active for rendering

Type boolean, default False

data

Type bpy_prop_collection of MeshColor, (readonly)

name

Name of Vertex color layer

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertex_colors
- VertexColors.active
- VertexColors.new

2.4.315 MeshDeformModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.MeshDeformModifier (Modifier)
Mesh deformation modifier to deform with other meshes

invert_vertex_group
Invert vertex group influence

Type boolean, default False

is_bound
Whether geometry has been bound to control cage

Type boolean, default False, (readonly)

object
Mesh object to deform with

Type Object

precision
The grid size for binding

Type int in [2, 10], default 0

use_dynamic_bind

Recompute binding dynamically on top of other deformers (slower and more memory consuming.)

Type boolean, default False

vertex_group

Vertex group name

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.316 MeshEdge(bpy_struct)

base class — bpy_struct

class bpy.types.MeshEdge (bpy_struct)

Edge in a Mesh datablock

bevel_weight

Weight used by the Bevel modifier

Type float in [-inf, inf], default 0.0

crease

Weight used by the Subsurf modifier for creasing

Type float in [-inf, inf], default 0.0

hide

Type boolean, default False

index

Index number of the vertex

Type int in [0, inf], default 0, (readonly)

is_fgon

Fgon edge

Type boolean, default False

is_loose

Loose edge

Type boolean, default False

select

Type boolean, default False

use_edge_sharp

Sharp edge for the EdgeSplit modifier

Type boolean, default False

use_seam

Seam edge for UV unwrapping

Type boolean, default False

vertices

Vertex indices

Type int array of 2 items in [0, inf], default (0, 0)

key

(readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.edges

2.4.317 MeshEdges(bpy_struct)

base class — bpy_struct

class bpy.types.MeshEdges (bpy_struct)
Collection of mesh edges

add (count=0)
add

Parameters count (int in [0, inf], (optional)) – Count, Number of vertices to add.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.edges

2.4.318 MeshFace(bpy_struct)

base class — `bpy_struct`

class bpy.types.MeshFace (bpy_struct)
Face in a Mesh datablock

area

read only area of the face

Type float in [0, inf], default 0.0, (readonly)

hide

Type boolean, default False

index

Index number of the vertex

Type int in [0, inf], default 0, (readonly)

material_index

Type int in [0, 32767], default 0

normal

local space unit length normal vector for this face

Type float array of 3 items in [-1, 1], default (0.0, 0.0, 0.0), (readonly)

select

Type boolean, default False

use_smooth

Type boolean, default False

vertices

Vertex indices

Type int array of 4 items in [0, inf], default (0, 0, 0, 0)

vertices_raw

Fixed size vertex indices array

Type int array of 4 items in [0, inf], default (0, 0, 0, 0)

center

The midpoint of the face. (readonly)

edge_keys

(readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.faces

2.4.319 MeshFaces(bpy_struct)

base class — bpy_struct

class bpy.types.MeshFaces (*bpy_struct*)

Collection of mesh faces

active

The active face for this mesh

Type int in [-inf, inf], default 0

active_tface

Active Texture Face

Type MeshTextureFace, (readonly)

add(*count=0*)

add

Parameters **count** (int in [0, inf], (optional)) – Count, Number of vertices to add.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.faces

2.4.320 MeshFloatProperty(bpy_struct)

base class — bpy_struct

class bpy.types.MeshFloatProperty (bpy_struct)
User defined floating point number value in a float properties layer
value
Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshFloatPropertyLayer.data

2.4.321 MeshFloatPropertyLayer(bpy_struct)

base class — `bpy_struct`

`class bpy.types.MeshFloatPropertyLayer (bpy_struct)`

User defined layer of floating pointer number values

data

Type `bpy_prop_collection` of `MeshFloatProperty`, (readonly)

name

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Mesh.layers_float`

2.4.322 MeshIntProperty(bpy_struct)

base class — `bpy_struct`

`class bpy.types.MeshIntProperty (bpy_struct)`

User defined integer number value in an integer properties layer

value

Type int in [-inf, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MeshIntPropertyLayer.data

2.4.323 MeshIntPropertyLayer(bpy_struct)

base class — bpy_struct

class bpy.types.MeshIntPropertyLayer(bpy_struct)

User defined layer of integer number values

data

Type bpy_prop_collection of MeshIntProperty, (readonly)

name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.layers_int

2.4.324 MeshSticky(bpy_struct)

base class — bpy_struct

class bpy.types.MeshSticky (*bpy_struct*)
Stricky texture coordinate

co
Sticky texture coordinate location

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- `Mesh.sticky`

2.4.325 MeshStringProperty(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MeshStringProperty` (*bpy_struct*)
User defined string text value in a string properties layer
value
Type `string, default “”`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `MeshStringPropertyLayer.data`

2.4.326 MeshStringPropertyLayer(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MeshStringPropertyLayer` (*bpy_struct*)
User defined layer of string text values
data
Type `bpy_prop_collection of MeshStringProperty, (readonly)`

name

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.layers_string

2.4.327 MeshTextureFace(bpy_struct)

base class — bpy_struct

class bpy.types.MeshTextureFace (*bpy_struct*)

UV mapping, texturing and game engine data for a face

blend_type

Transparency blending mode

Type enum in [‘OPAQUE’, ‘ADD’, ‘ALPHA’, ‘CLIPALPHA’], default ‘OPAQUE’

hide

Make face invisible

Type boolean, default False

image

Type Image

pin_uv

Type boolean array of 4 items, default (False, False, False, False)

select_uv

Type boolean array of 4 items, default (False, False, False, False)

use_alpha_sort

Enable sorting of faces for correct alpha drawing (slow, use Clip Alpha instead when possible)

Type boolean, default False

use_billboard

Billboard with Z-axis constraint

Type boolean, default False

use_bitmap_text

Enable bitmap text on face

Type boolean, default False

use_blend_shared

Blend vertex colors across face when vertices are shared

Type boolean, default False

use_collision

Use face for collision and ray-sensor detection

Type boolean, default False

use_halo

Screen aligned billboard

Type boolean, default False

use_image

Render face with texture

Type boolean, default False

use_light

Use light for face

Type boolean, default False

use_object_color

Use ObColor instead of vertex colors

Type boolean, default False

use_shadow_cast

Face is used for shadow

Type boolean, default False

use_twoside

Render face two-sided

Type boolean, default False

uv

Type float array of 8 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

uv1

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv2

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv3

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv4

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

uv_raw

Fixed size UV coordinates array

Type float array of 8 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `MeshFaces.active_tface`
- `MeshTextureFaceLayer.data`

2.4.328 MeshTextureFaceLayer(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MeshTextureFaceLayer(bpy_struct)`

Layer of texture faces in a Mesh datablock

active

Sets the layer as active for display and editing

Type boolean, default False

active_clone

Sets the layer as active for cloning

Type boolean, default False

active_render

Sets the layer as active for rendering

Type boolean, default False

data

Type bpy_prop_collection of MeshTextureFace, (readonly)

name

Name of UV unwrapping layer

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.uv_texture_clone
- Mesh.uv_texture_stencil
- Mesh.uv_textures
- UVTextures.active
- UVTextures.new

2.4.329 MeshVertex(bpy_struct)

base class — bpy_struct

```
class bpy.types.MeshVertex (bpy_struct)
    Vertex in a Mesh datablock

    bevel_weight
        Weight used by the Bevel modifier ‘Only Vertices’ option
        Type float in [-inf, inf], default 0.0

    co
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    groups
        Weights for the vertex groups this vertex is member of
        Type bpy_prop_collection of VertexGroupElement, (readonly)

    hide
        Type boolean, default False

    index
        Index number of the vertex
        Type int in [0, inf], default 0, (readonly)

    normal
        Vertex Normal
        Type float array of 3 items in [-1, 1], default (0.0, 0.0, 0.0)

    select
        Type boolean, default False
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- `Mesh.vertices`

2.4.330 MeshVertices(bpy_struct)

base class — `bpy_struct`

class `bpy.types.MeshVertices(bpy_struct)`
Collection of mesh vertices

add (`count=0`)
add

Parameters `count` (`int in [0, inf], (optional)`) – Count, Number of vertices to add.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Mesh.vertices`

2.4.331 MessageActuator(Actuator)

base classes — `bpy_struct, Actuator`

class `bpy.types.MessageActuator(Actuator)`
Actuator to ..

body_message
Optional message body Text

Type string, default “”

body_property

The message body will be set by the Property Value

Type string, default “”

body_type

Toggle message type: either Text or aPropertyName

Type enum in ['TEXT', 'PROPERTY'], default 'TEXT'

subject

Optional message subject. This is what can be filtered on

Type string, default “”

to_property

Optional send message to objects with this name only, or empty to broadcast

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

2.4.332 MessageSensor(Sensor)

base classes — bpy_struct, Sensor

```
class bpy.types.MessageSensor (Sensor)
    Sensor to detect incoming messages

subject
    Optional subject filter: only accept messages with this subject, or empty for all

    Type string, default ""
```

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.333 MetaBall(ID)

base classes — `bpy_struct, ID`

```
class bpy.types.MetaBall (ID)
    Metaball datablock to defined blobby surfaces

animation_data
    Animation data for this datablock

    Type AnimData, (readonly)
```

elements

Meta elements

Type `MetaBallElements bpy_prop_collection of MetaElement`, (readonly)

materials

Type `IDMaterials bpy_prop_collection of Material`, (readonly)

render_resolution

Polygonization resolution in rendering

Type float in [0.05, 1], default 0.0

resolution

Polygonization resolution in the 3D viewport

Type float in [0.05, 1], default 0.0

texspace_location

Texture space location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texspace_size

Texture space size

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

threshold

Influence of meta elements

Type float in [0, 5], default 0.0

update_method

Metaball edit update behavior

Type enum in ['UPDATE_ALWAYS', 'HALFRES', 'FAST', 'NEVER'], default 'UPDATE_ALWAYS'

use_auto_tinspace

Adjusts active object's texture space automatically when transforming object

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.metaballs
- BlendDataMetaBalls.new
- BlendDataMetaBalls.remove

2.4.334 MetaBallElements(bpy_struct)

base class — bpy_struct

class bpy.types.MetaBallElements (*bpy_struct*)

Collection of metaball elements

active

Last selected element

Type MetaElement, (readonly)

new (*type*=’BALL’)

Add a new spline to the curve.

Parameters *type* (*enum in* [‘BALL’, ‘CAPSULE’, ‘PLANE’, ‘ELLIPSOID’, ‘CUBE’], (*optional*)) – type for the new meta-element.

Returns The newly created meta-element.

Return type MetaElement

remove (*element*)

Remove a spline from a curve.

Parameters *element* (MetaElement, (never None)) – The element to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `MetaBall.elements`

2.4.335 MetaElement(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MetaElement(bpy_struct)`
Blobby element in a MetaBall datablock

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

hide

Hide element

Type boolean, default False

radius

Type float in [0, inf], default 0.0

rotation

Normalized quaternion rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

size_x

Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

size_y

Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

size_z

Size of element, use of components depends on element type

Type float in [0, 20], default 0.0

stiffness

Stiffness defines how much of the element to fill

Type float in [0, 10], default 0.0

type

Metaball types

Type enum in ['BALL', 'CAPSULE', 'PLANE', 'ELLIPSOID', 'CUBE'], default 'BALL'

use_negative

Set metaball as negative one

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MetaBall.elements
- MetaBallElements.active
- MetaBallElements.new
- MetaBallElements.remove

2.4.336 MetaSequence(Sequence)

base classes — bpy_struct, Sequence

```
class bpy.types.MetaSequence(Sequence)
    Sequence strip to group other strips as a single sequence strip

    animation_offset_end
        Animation end offset (trim end)
        Type int in [0, inf], default 0

    animation_offset_start
        Animation start offset (trim start)
        Type int in [0, inf], default 0

    color_balance
        Type SequenceColorBalance, (readonly)

    color_multiply
        Type float in [0, 20], default 0.0

    color_saturation
        Type float in [0, 20], default 0.0

    crop
        Type SequenceCrop, (readonly)

    proxy
        Type SequenceProxy, (readonly)

    sequences
        Type bpy_prop_collection of Sequence, (readonly)

    strobe
        Only display every nth frame
        Type float in [1, 30], default 0.0

    transform
        Type SequenceTransform, (readonly)

    use_color_balance
        (3-Way color correction) on input
        Type boolean, default False

    use_crop
        Crop image before processing
        Type boolean, default False

    use_deinterlace
        For video movies to remove fields
        Type boolean, default False

    use_flip_x
        Flip on the X axis
        Type boolean, default False

    use_flip_y
        Flip on the Y axis
```

Type boolean, default False
use_float
Convert input to float data
Type boolean, default False
use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False
use_proxy
Use a preview proxy for this strip
Type boolean, default False
use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False
use_proxy_custom_file
Use a custom file to read proxy data from
Type boolean, default False
use_reverse_frames
Reverse frame order
Type boolean, default False
use_translation
Translate image before processing
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`
- `Sequence.frame_final_duration`
- `Sequence.frame_duration`
- `Sequence.lock`
- `Sequence.mute`
- `Sequence.select_right_handle`
- `Sequence.select`
- `Sequence.speed_factor`
- `Sequence.frame_start`

- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.337 MirrorModifier(Modifier)

base classes — bpy_struct, Modifier

```
class bpy.types.MirrorModifier (Modifier)
    Mirroring modifier

    merge_threshold
        Distance from axis within which mirrored vertices are merged
        Type float in [0, inf], default 0.0

    mirror_object
        Object to use as mirror
        Type Object

    use_clip
        Prevents vertices from going through the mirror during transform
        Type boolean, default False

    use_mirror_merge
        Merge vertices within the merge threshold
        Type boolean, default False

    use_mirror_u
        Mirror the U texture coordinate around the 0.5 point
```

Type boolean, default False

use_mirror_v
Mirror the V texture coordinate around the 0.5 point

Type boolean, default False

use_mirror_vertex_groups
Mirror vertex groups (e.g. .R->.L)

Type boolean, default False

use_x
Enable X axis mirror

Type boolean, default False

use_y
Enable Y axis mirror

Type boolean, default False

use_z
Enable Z axis mirror

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.338 Modifier(*bpy_struct*)

base class — *bpy_struct*
subclasses — FluidSimulationModifier, BevelModifier, SolidifyModifier, SmokeModifier, UVProjectModifier, DecimateModifier, ExplodeModifier, SmoothModifier, HookModifier, SoftBodyModifier, BooleanModifier, ArrayModifier, LatticeModifier, BuildModifier, ClothModifier, ParticleSystemModifier, SubsurfModifier, CurveModifier, ScrewModifier, MaskModifier, ShrinkwrapModifier, CollisionModifier, CastModifier, WaveModifier, ParticleInstanceModifier, SurfaceModifier, SimpleDeformModifier, DisplaceModifier, ArmatureModifier, MeshDeformModifier, WarpModifier, EdgeSplitModifier, MultiresModifier, MirrorModifier

class *bpy.types.Modifier* (*bpy_struct*)
Modifier affecting the geometry data of an object

name
Modifier name
Type string, default “”

show_expanded
Set modifier expanded in the user interface
Type boolean, default False

show_in_editmode
Use modifier while in the edit mode
Type boolean, default False

show_on_cage
Enable direct editing of modifier control cage
Type boolean, default False

show_render
Use modifier during rendering
Type boolean, default False

show_viewport
Realtime display of a modifier
Type boolean, default False

type
Type enum in ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WARP', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE'], default 'ARRAY', (readonly)

use_apply_on_spline
Apply this and all preceding deformation modifiers on splines' points rather than on filled curve/surface
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.modifiers`
- `ObjectModifiers.new`
- `ObjectModifiers.remove`
- `UILayout.template_modifier`

2.4.339 MotionPath(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.MotionPath(bpy_struct)`

Cache of the worldspace positions of an element over a frame range

frame_end

End frame of the stored range

Type int in [-inf, inf], default 0, (readonly)

frame_start

Starting frame of the stored range

Type int in [-inf, inf], default 0, (readonly)

is_modified

Path is being edited

Type boolean, default False

length

Number of frames cached

Type int in [-inf, inf], default 0, (readonly)

points

Cached positions per frame

Type bpy_prop_collection of MotionPathVert, (readonly)

use_bone_head

For PoseBone paths, use the bone head location when calculating this path

Type boolean, default False, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.motion_path
- PoseBone.motion_path

2.4.340 MotionPathVert(bpy_struct)

base class — bpy_struct

class bpy.types.MotionPathVert (bpy_struct)

Cached location on path

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

select

Path point is selected for editing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- MotionPath.points

2.4.341 MouseSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.MouseSensor (*Sensor*)

Sensor to detect mouse events

mouse_event

Specify the type of event this mouse sensor should trigger on

Type enum in ['LEFTCLICK', 'MIDDLECLICK', 'RIGHTCLICK', 'WHEELUP', 'WHEELDOWN', 'MOVEMENT', 'MOUSEOVER', 'MOUSEOVERANY'], default 'LEFTCLICK'

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap

- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.342 MovieSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.MovieSequence (Sequence)
Sequence strip to load a video

animation_offset_end
Animation end offset (trim end)
Type int in [0, inf], default 0

animation_offset_start
Animation start offset (trim start)
Type int in [0, inf], default 0

color_balance
Type SequenceColorBalance, (readonly)

color_multiply
Type float in [0, 20], default 0.0

color_saturation
Type float in [0, 20], default 0.0

crop
Type SequenceCrop, (readonly)

elements
Type bpy_prop_collection of SequenceElement, (readonly)

filepath
Type string, default ""

mpeg_preseek
For MPEG movies, preseek this many frames
Type int in [0, 50], default 0

proxy
Type SequenceProxy, (readonly)

strobe
Only display every nth frame
Type float in [1, 30], default 0.0

transform
Type SequenceTransform, (readonly)

use_color_balance
(3-Way color correction) on input
Type boolean, default False

use_crop
Crop image before processing
Type boolean, default False

use_deinterlace
For video movies to remove fields
Type boolean, default False

use_flip_x
Flip on the X axis
Type boolean, default False

use_flip_y
Flip on the Y axis
Type boolean, default False

use_float
Convert input to float data
Type boolean, default False

use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False

use_proxy
Use a preview proxy for this strip
Type boolean, default False

use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False

use_proxy_custom_file

Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames

Reverse frame order

Type boolean, default False

use_translation

Translate image before processing

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`
- `Sequence.frame_final_duration`
- `Sequence.frame_duration`
- `Sequence.lock`
- `Sequence.mute`
- `Sequence.select_right_handle`
- `Sequence.select`
- `Sequence.speed_factor`
- `Sequence.frame_start`
- `Sequence.frame_final_start`
- `Sequence.frame_offset_start`
- `Sequence.frame_still_start`
- `Sequence.type`
- `Sequence.use_default_fade`
- `Sequence.input_count`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.343 MulticamSequence(Sequence)

base classes — bpy_struct, Sequence

class bpy.types.MulticamSequence (Sequence)

Sequence strip to perform multicam editing: select channel from below

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

multicam_source

Type int in [0, 31], default 0

proxy

Type SequenceProxy, (readonly)

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop

Crop image before processing

Type boolean, default False

use_deinterlace

For video movies to remove fields

Type boolean, default False

use_flip_x

Flip on the X axis

Type boolean, default False

use_flip_y

Flip on the Y axis

Type boolean, default False

use_float

Convert input to float data

Type boolean, default False

use_premultiply

Convert RGB from key alpha to premultiplied alpha

Type boolean, default False

use_proxy

Use a preview proxy for this strip

Type boolean, default False

use_proxy_custom_directory

Use a custom directory to store data

Type boolean, default False

use_proxy_custom_file

Use a custom file to read proxy data from

Type boolean, default False

use_reverse_frames

Reverse frame order

Type boolean, default False

use_translation

Translate image before processing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader

- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.344 MultiresModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.MultiresModifier (Modifier)
Multiresolution mesh modifier

filepath

Path to external displacements file

Type string, default “”

is_external

Store multires displacements outside the .blend file, to save memory

Type boolean, default False, (readonly)

levels

Number of subdivisions to use in the viewport

Type int in [0, 255], default 0

render_levels

The subdivision level visible at render time

Type int in [0, 255], default 0

sculpt_levels

Number of subdivisions to use in sculpt mode

Type int in [0, 255], default 0

show_only_control_edges

Skip drawing/rendering of interior subdivided edges

Type boolean, default False

subdivision_type

Selects type of subdivision algorithm

Type enum in ['CATMULL_CLARK', 'SIMPLE'], default 'CATMULL_CLARK'

total_levels

Number of subdivisions for which displacements are stored

Type int in [0, 255], default 0, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.345 MusgraveTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.MusgraveTexture (*Texture*)

Procedural musgrave texture

dimension_max

Highest fractal dimension

Type float in [0.0001, 2], default 0.0

gain

The gain multiplier

Type float in [0, 6], default 0.0

lacunarity

Gap between successive frequencies

Type float in [0, 6], default 0.0

musgrave_type

Type enum in ['MULTIFRACTAL', 'RIDGED_MULTIFRACTAL', 'HYBRID_MULTIFRACTAL', 'FBM', 'HETERO_TERRAIN'], default 'MULTIFRACTAL'

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_intensity

Scales the intensity of the noise

Type float in [0, 10], default 0.0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

octaves

Number of frequencies used

Type float in [0, 8], default 0.0

offset

The fractal offset

Type float in [0, 6], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`

- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.346 NandController(Controller)

base classes — bpy_struct, Controller

class bpy.types.NandController (Controller)
Controller passing on events based on a logical NAND operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.347 NearSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.NearSensor (Sensor)
Sensor to detect nearby objects

distance

Trigger distance

Type float in [0, 10000], default 0.0

property

Only look for objects with this property (blank = all objects)

Type string, default “”

reset_distance

The distance where the sensor forgets the actor

Type float in [0, 10000], default 0.0

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.348 NlaStrip(bpy_struct)

base class — bpy_struct

```
class bpy.types.NlaStrip(bpy_struct)
    A container referencing an existing Action

    action
        Action referenced by this strip
        Type Action

    action_frame_end
        Type float in [-inf, inf], default 0.0

    action_frame_start
        Type float in [-inf, inf], default 0.0

    active
        NLA Strip is active
        Type boolean, default False, (readonly)

    blend_in
        Number of frames at start of strip to fade in influence
        Type float in [-inf, inf], default 0.0

    blend_out
        Type float in [-inf, inf], default 0.0

    blend_type
        Method used for combining strip's result with accumulated result
        Type enum in ['REPLACE', 'ADD', 'SUBTRACT', 'MULITPLY'], default 'REPLACE'

    extrapolation
        Action to take for gaps past the strip extents
        Type enum in ['NOTHING', 'HOLD', 'HOLD_FORWARD'], default 'HOLD'

    fcurves
        F-Curves for controlling the strip's influence and timing
        Type bpy_prop_collection of FCurve, (readonly)

    frame_end
        Type float in [-inf, inf], default 0.0

    frame_start
        Type float in [-inf, inf], default 0.0

    influence
        Amount the strip contributes to the current result
        Type float in [0, 1], default 0.0

    modifiers
        Modifiers affecting all the F-Curves in the referenced Action
        Type bpy_prop_collection of FModifier, (readonly)

    mute
        NLA Strip is not evaluated
        Type boolean, default False
```

name

Type string, default “”

repeat

Number of times to repeat the action range

Type float in [0.1, 1000], default 0.0

scale

Scaling factor for action

Type float in [0.0001, 1000], default 0.0

select

NLA Strip is selected

Type boolean, default False

strip_time

Frame of referenced Action to evaluate

Type float in [-inf, inf], default 0.0

strips

NLA Strips that this strip acts as a container for (if it is of type Meta)

Type bpy_prop_collection of NlaStrip, (readonly)

type

Type of NLA Strip

Type enum in ['CLIP', 'TRANSITION', 'META'], default 'CLIP', (readonly)

use_animated_influence

Influence setting is controlled by an F-Curve rather than automatically determined

Type boolean, default False

use_animated_time

Strip time is controlled by an F-Curve rather than automatically determined

Type boolean, default False

use_animated_time_cyclic

Cycle the animated time within the action start & end

Type boolean, default False

use_auto_blend

Number of frames for Blending In/Out is automatically determined from overlapping strips

Type boolean, default False

use_reverse

NLA Strip is played back in reverse order (only when timing is automatically determined)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `NlaStrip.strips`
- `NlaStrips.new`
- `NlaStrips.remove`
- `NlaTrack.strips`

2.4.349 NlaStrips(bpy_struct)

base class — `bpy_struct`

class `bpy.types.NlaStrips(bpy_struct)`

Collection of Nla Strips

new (*name, start, action*)

Add a new Action-Clip strip to the track

Parameters

- **name** (*string*) – Name for the NLA Strips.
- **start** (*int in [-inf, inf]*) – Start Frame, Start frame for this strip.
- **action** (`Action`, (never None)) – Action to assign to this strip.

Returns New NLA Strip.

Return type `NlaStrip`

remove (*strip*)

Remove a NLA Strip.

Parameters **strip** (`NlaStrip`, (never None)) – NLA Strip to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `NlaTrack.strips`

2.4.350 NlaTrack(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.NlaTrack(bpy_struct)`

A animation layer containing Actions referenced as NLA strips

active

NLA Track is active

Type boolean, default False, (readonly)

is_solo

NLA Track is evaluated itself (i.e. active Action and all other NLA Tracks in the same AnimData block are disabled)

Type boolean, default False, (readonly)

lock

NLA Track is locked

Type boolean, default False

mute

NLA Track is not evaluated

Type boolean, default False

name

Type string, default “”

select

NLA Track is selected

Type boolean, default False

strips

NLA Strips on this NLA-track

Type `NlaStrips bpy_prop_collection of NlaStrip, (readonly)`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AnimData.nla_tracks`
- `NlaTracks.active`
- `NlaTracks.new`
- `NlaTracks.new`
- `NlaTracks.remove`

2.4.351 NlaTracks(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.NlaTracks (bpy_struct)`

Collection of NLA Tracks

active

Active Object constraint

Type `NlaTrack`

new (`prev=None`)

Add a new NLA Track

Parameters `prev (NlaTrack, (optional))` – NLA Track to add the new one after.

Returns New NLA Track.

Return type `NlaTrack`

remove (`track`)

Remove a NLA Track.

Parameters `track` (`NlaTrack`, (never None)) – NLA Track to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AnimData.nla_tracks`

2.4.352 Node(`bpy_struct`)

base class — `bpy_struct`

subclasses — `TextureNode`, `ShaderNode`, `CompositorNode`, `NodeGroup`

class `bpy.types.Node` (`bpy_struct`)

Node in a node tree

inputs

Type `bpy_prop_collection` of `NodeSocket`, (readonly)

label

Optional custom node label

Type string, default “”

location

Type float array of 2 items in [-10000, 10000], default (0.0, 0.0)

name

Unique node identifier

Type string, default “”

outputs

Type bpy_prop_collection of NodeSocket, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- CompositorNodeTree.nodes
- CompositorNodes.new
- CompositorNodes.remove
- NodeLink.from_node
- NodeLink.to_node
- ShaderNodeTree.nodes
- ShaderNodes.new
- ShaderNodes.remove
- TextureNodeTree.nodes
- TextureNodes.new
- TextureNodes.remove

2.4.353 NodeGroup(Node)

base classes — bpy_struct, Node

```
class bpy.types.NodeGroup(Node)

    node_tree
        Type NodeTree
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.354 NodeLink(bpy_struct)

base class — bpy_struct

```
class bpy.types.NodeLink(bpy_struct)
    Link between nodes in a node tree

    from_node
        Type Node, (readonly)

    from_socket
        Type NodeSocket, (readonly)

    to_node
        Type Node, (readonly)

    to_socket
        Type NodeSocket, (readonly)
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `NodeLinks.new`
- `NodeLinks.remove`
- `NodeTree.links`

2.4.355 NodeLinks(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.NodeLinks(bpy_struct)`

Collection of Node Links

new (*input, output*)

Add a node link to this node tree.

Parameters

- `input` (`NodeSocket`) – The input socket.
- `output` (`NodeSocket`) – The output socket.

Returns New node link.

Return type `NodeLink`

remove (*link*)

remove a node link from the node tree.

Parameters `link` (`NodeLink`) – The node link to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `NodeTree.links`

2.4.356 NodeSocket(`bpy_struct`)

base class — `bpy_struct`

subclasses — `VectorNodeSocket`, `RGBANodeSocket`, `ValueNodeSocket`

class `bpy.types.NodeSocket` (`bpy_struct`)

Input or output socket of a node

name

Socket name

Type string, default “”

type

Node Socket type

Type enum in ['VALUE', 'VECTOR', 'RGBA'], default 'VALUE', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `GroupInputs.expose`
- `GroupInputs.expose`
- `GroupInputs.new`
- `GroupOutputs.expose`
- `GroupOutputs.expose`
- `GroupOutputs.new`
- `Node.inputs`
- `Node.outputs`
- `NodeLink.from_socket`
- `NodeLink.to_socket`
- `NodeLinks.new`
- `NodeLinks.new`
- `NodeTree.inputs`
- `NodeTree.outputs`

2.4.357 NodeTree(*ID*)

base classes — `bpy_struct, ID`

subclasses — `CompositorNodeTree, ShaderNodeTree, TextureNodeTree`

class `bpy.types.NodeTree (ID)`

Node tree consisting of linked nodes used for materials, textures and compositing

animation_data

Animation data for this datablock

Type `AnimData, (readonly)`

grease_pencil

Grease Pencil datablock

Type `GreasePencil`

inputs

Type GroupInputs bpy_prop_collection of NodeSocket, (readonly)

links

Type NodeLinks bpy_prop_collection of NodeLink, (readonly)

outputs

Type GroupOutputs bpy_prop_collection of NodeSocket, (readonly)

type

Node Tree type

Type enum in ['SHADER', 'COMPOSITE', 'TEXTURE'], default 'SHADER', (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.node_groups
- BlendDataNodeTrees.new
- BlendDataNodeTrees.remove

- CompositorNodes.new
- Material.node_tree
- NodeGroup.node_tree
- Scene.node_tree
- ShaderNodes.new
- SpaceNodeEditor.node_tree
- Texture.node_tree
- TextureNodes.new

2.4.358 NoiseTexture(Texture)

base classes — `bpy_struct`, `ID`, `Texture`

class bpy.types.NoiseTexture (Texture)

Procedural noise texture

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.359 NorController(Controller)

base classes — bpy_struct, Controller

class bpy.types.NorController(Controller)
Controller passing on events based on a logical NOR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast

- `bpy_struct.values`
- `Controller.link`
- `Controller.unlink`

2.4.360 Object(ID)

base classes — `bpy_struct, ID`

class bpy.types.Object (ID)

Object datablock defining an object in a scene

active_material

Active material being displayed

Type `Material`

active_material_index

Index of active material slot

Type int in [0, inf], default 0

active_shape_key

Current shape key

Type `ShapeKey`, (readonly)

active_shape_key_index

Current shape key index

Type int in [-32768, 32767], default 0

animation_data

Animation data for this datablock

Type `AnimData`, (readonly)

animation_visualisation

Animation data for this datablock

Type `AnimViz`, (readonly, never None)

bound_box

Objects bound box in object-space coordinates, all values are -1.0 when not available.

Type float array of 24 items in [-inf, inf], default (0.0, 0.0), (readonly)

collision

Settings for using the objects as a collider in physics simulation

Type `CollisionSettings`, (readonly)

color

Object color and alpha, used when faces have the ObColor mode enabled

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

constraints

Constraints affecting the transformation of the object

Type `ObjectConstraints bpy_prop_collection of Constraint`, (readonly)

data

Object data

Type `ID`

delta_location
Extra translation added to the location of the object
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

delta_rotation_euler
Extra rotation added to the rotation of the object (when using Euler rotations)
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

delta_rotation_quaternion
Extra rotation added to the rotation of the object (when using Quaternion rotations)
Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

delta_scale
Extra scaling added to the scale of the object
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dimensions
Absolute bounding box dimensions of the object
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

draw_bounds_type
Object boundary display type
Type enum in ['BOX', 'SPHERE', 'CYLINDER', 'CONE', 'POLYHEDRON', 'CAPSULE'], default 'BOX'

draw_type
Maximum draw type to display object with in viewport
Type enum in ['BOUNDS', 'WIRE', 'SOLID', 'TEXTURED'], default 'BOUNDS'

dupli_faces_scale
Scale the DupliFace objects
Type float in [0.001, 10000], default 0.0

dupli_frames_end
End frame for DupliFrames
Type int in [-300000, 300000], default 0

dupli_frames_off
Recurring frames to exclude from the Dupliframes
Type int in [0, 300000], default 0

dupli_frames_on
Number of frames to use between DupOff frames
Type int in [0, 300000], default 0

dupli_frames_start
Start frame for DupliFrames
Type int in [-300000, 300000], default 0

dupli_group
Instance an existing group
Type `Group`

dupli_list

Object duplis

Type `bpy_prop_collection` of `DupliObject`, (readonly)

dupli_type

If not None, object duplication method to use

Type enum in ['NONE', 'FRAMES', 'VERTS', 'FACES', 'GROUP'], default 'NONE'

empty_draw_size

Size of display for empties in the viewport

Type float in [0.0001, 1000], default 0.0

empty_draw_type

Viewport display style for empties

Type enum in ['PLAIN_AXES', 'ARROWS', 'SINGLE_ARROW', 'CIRCLE', 'CUBE', 'SPHERE', 'CONE', 'IMAGE'], default 'PLAIN_AXES'

empty_image_offset

Origin offset distance

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

field

Settings for using the objects as a field in physics simulation

Type `FieldSettings`, (readonly)

game

Game engine related settings for the object

Type `GameObjectSettings`, (readonly, never None)

grease_pencil

Grease Pencil datablock

Type `GreasePencil`

hide

Restrict visibility in the viewport

Type boolean, default False

hide_render

Restrict renderability

Type boolean, default False

hide_select

Restrict selection in the viewport

Type boolean, default False

is_duplicator

Type boolean, default False, (readonly)

layers

Layers the object is on

Type boolean array of 20 items, default (False, False, False)

location

Location of the object

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lock_location

Lock editing of location in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation

Lock editing of rotation in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation_w

Lock editing of ‘angle’ component of four-component rotations in the interface

Type boolean, default False

lock_rotations_4d

Lock editing of four component rotations by components (instead of as Eulers)

Type boolean, default False

lock_scale

Lock editing of scale in the interface

Type boolean array of 3 items, default (False, False, False)

material_slots

Material slots in the object

Type `bpy_prop_collection` of `MaterialSlot`, (readonly)

matrix_basis

Matrix access to location, rotation and scale (including deltas), before constraints and parenting are applied.

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_local

Parent relative transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_world

Worldspace transformation matrix

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

mode

Object interaction mode

Type enum in [‘OBJECT’, ‘EDIT’, ‘SCULPT’, ‘VERTEX_PAINT’, ‘WEIGHT_PAINT’, ‘TEXTURE_PAINT’, ‘PARTICLE_EDIT’, ‘POSE’], default ‘OBJECT’, (readonly)

modifiers

Modifiers affecting the geometric data of the object

Type `ObjectModifiers` `bpy_prop_collection` of `Modifier`, (readonly)

motion_path

Motion Path for this element

Type `MotionPath`, (readonly)

parent

Parent Object

Type `Object`

parent_bone

Name of parent bone in case of a bone parenting relation

Type string, default “”

parent_type

Type of parent relation

Type enum in ['OBJECT', 'CURVE', 'KEY', 'ARMATURE', 'LATTICE', 'VERTEX', 'VERTEX_3', 'BONE'], default 'OBJECT'

parent_vertices

Indices of vertices in cases of a vertex parenting relation

Type int array of 3 items in [0, inf], default (0, 0, 0)

particle_systems

Particle systems emitted from the object

Type `ParticleSystems bpy_prop_collection of ParticleSystem`, (readonly)

pass_index

Index # for the IndexOB render pass

Type int in [0, 32767], default 0

pose

Current pose for armatures

Type `Pose`, (readonly)

pose_library

Action used as a pose library for armatures

Type `Action`

proxy

Library object this proxy object controls

Type `Object`, (readonly)

proxy_group

Library group duplicator object this proxy object controls

Type `Object`, (readonly)

rotation_axis_angle

Angle of Rotation for Axis-Angle rotation representation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 1.0, 0.0)

rotation_euler

Rotation in Eulers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_mode

Type enum in ['QUATERNION', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX', 'AXIS_ANGLE'], default 'QUATERNION'

rotation_quaternion
Rotation in Quaternions

Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

scale
Scaling of the object

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

select
Object selection state

Type boolean, default False

show_axis
Displays the object's origin and axis

Type boolean, default False

show_bounds
Displays the object's bounds

Type boolean, default False

show_name
Displays the object's name

Type boolean, default False

show_only_shape_key
Always show the current Shape for this Object

Type boolean, default False

show_texture_space
Displays the object's texture space

Type boolean, default False

show_transparent
Displays material transparency in the object

Type boolean, default False

show_wire
Adds the object's wireframe over solid drawing

Type boolean, default False

show_x_ray
Makes the object draw in front of others

Type boolean, default False

soft_body
Settings for soft body simulation

Type `SoftBodySettings`, (readonly)

time_offset
Animation offset in frames for F-Curve and dupligrand instances

Type float in [-300000, 300000], default 0.0

track_axis

Axis that points in ‘forward’ direction (applies to DupliFrame when parent ‘Follow’ is enabled)

Type enum in [‘POS_X’, ‘POS_Y’, ‘POS_Z’, ‘NEG_X’, ‘NEG_Y’, ‘NEG_Z’], default ‘POS_X’

type

Type of Object

Type enum in [‘MESH’, ‘CURVE’, ‘SURFACE’, ‘META’, ‘FONT’, ‘ARMATURE’, ‘LATTICE’, ‘EMPTY’, ‘CAMERA’, ‘LAMP’], default ‘EMPTY’, (readonly)

up_axis

Axis that points in the upward direction (applies to DupliFrame when parent ‘Follow’ is enabled)

Type enum in [‘X’, ‘Y’, ‘Z’], default ‘X’

use_dupli_faces_scale

Scale dupli based on face size

Type boolean, default False

use_dupli_frames_speed

Set dupliframes to use the frame

Type boolean, default False

use_dupli_vertices_rotation

Rotate dupli according to vertex normal

Type boolean, default False

use_shape_key_edit_mode

Apply shape keys in edit mode (for Meshes only)

Type boolean, default False

use_slow_parent

Create a delay in the parent relationship

Type boolean, default False

use_time_offset_add_parent

Add the parents time offset value

Type boolean, default False

use_time_offset_edit

Use time offset when inserting keys and display time offset for F-Curve and action views

Type boolean, default False

use_time_offset_parent

Apply the time offset to this objects parent relationship

Type boolean, default False

use_time_offset_particle

Let the time offset work on the particle effect

Type boolean, default False

vertex_groups

Vertex groups of the object

Type `VertexGroups bpy_prop_collection of VertexGroup`, (readonly)

children

All the children of this object (readonly)

users_group

The groups this object is in (readonly)

users_scene

The scenes this object is in (readonly)

to_mesh (scene, apply_modifiers, settings)

Create a Mesh datablock with modifiers applied.

Parameters

- **scene** ([Scene](#), (never None)) – Scene within which to evaluate modifiers.
- **apply_modifiers** (*boolean*) – Apply modifiers.
- **settings** (*enum in ['PREVIEW', 'RENDER']*) – Modifier settings to apply.

Returns Mesh created from object, remove it if it is only used for export.

Return type [Mesh](#)

dupli_list_create (scene)

Create a list of dupli objects for this object, needs to be freed manually with `free_dupli_list` to restore the objects real matrix and layers.

Parameters **scene** ([Scene](#), (never None)) – Scene within which to evaluate duplis.

dupli_list_clear ()

Free the list of dupli objects.

find_armature ()

Find armature influencing this object as a parent or via a modifier.

Returns Armature object influencing this object or NULL.

Return type [Object](#)

shape_key_add (name="Key", from_mix=True)

Add shape key to an object.

Parameters

- **name** (*string, (optional)*) – Unique name for the new keylock.
- **from_mix** (*boolean, (optional)*) – Create new shape from existing mix of shapes.

Returns New shape keyblock.

Return type [ShapeKey](#)

ray_cast (start, end)

Cast a ray onto in object space.

Return (location, normal, index) *location*, The hit location of this ray cast, float array of 3 items in [-inf, inf]

normal, The face normal at the ray cast hit location, float array of 3 items in [-inf, inf]

index, The face index, -1 when no intersection is found., int in [-inf, inf]

is_visible (scene)

Determine if object is visible in a given scene.

Returns Object visibility.

Return type boolean

is_modified(*scene, settings*)

Determine if this object is modified from the base mesh data.

Parameters *settings* (*enum in [‘PREVIEW’, ‘RENDER’]*) – Modifier settings to apply.

Returns Object visibility.

Return type boolean

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- ActionConstraint.target
- ArmatureActuator.secondary_target
- ArmatureActuator.target
- ArmatureModifier.object
- ArrayModifier.curve
- ArrayModifier.end_cap
- ArrayModifier.offset_object

- `ArrayModifier.start_cap`
- `BlendData.objects`
- `BlendDataObjects.new`
- `BlendDataObjects.remove`
- `BoidRuleAvoid.object`
- `BoidRuleFollowLeader.object`
- `BoidRuleGoal.object`
- `BooleanModifier.object`
- `Camera.dof_object`
- `CameraActuator.object`
- `CastModifier.object`
- `ChildOfConstraint.target`
- `ClampToConstraint.target`
- `ConstraintTarget.target`
- `CopyLocationConstraint.target`
- `CopyRotationConstraint.target`
- `CopyScaleConstraint.target`
- `CopyTransformsConstraint.target`
- `Curve.bevel_object`
- `Curve.taper_object`
- `CurveModifier.object`
- `CurveSplines.active`
- `DampedTrackConstraint.target`
- `DisplaceModifier.texture_coords_object`
- `DupliObject.object`
- `EditObjectActuator.object`
- `EditObjectActuator.track_object`
- `EnvironmentMap.viewpoint_object`
- `FloorConstraint.target`
- `FollowPathConstraint.target`
- `Group.objects`
- `GroupObjects.link`
- `GroupObjects.unlink`
- `HookModifier.object`
- `KinematicConstraint.pole_target`
- `KinematicConstraint.target`
- `LampTextureSlot.object`
- `LatticeModifier.object`
- `LimitDistanceConstraint.target`
- `LockedTrackConstraint.target`
- `MaskModifier.armature`
- `MaterialTextureSlot.object`
- `MeshDeformModifier.object`
- `MirrorModifier.mirror_object`
- `Object.find_armature`
- `Object.parent`
- `Object.proxy`
- `Object.proxy_group`
- `ObjectActuator.reference_object`
- `ObjectBase.object`
- `ParentActuator.object`
- `ParticleEdit.object`
- `ParticleInstanceModifier.object`
- `ParticleSettings.billboard_object`

- ParticleSettings.dupli_object
- ParticleSettingsTextureSlot.object
- ParticleSystem.parent
- ParticleSystem.reactor_target_object
- ParticleTarget.object
- PivotConstraint.target
- PointDensity.object
- PoseBone.custom_shape
- PropertyActuator.object
- RigidBodyJointConstraint.child
- RigidBodyJointConstraint.target
- Scene.camera
- Scene.objects
- SceneActuator.camera
- SceneObjects.active
- SceneObjects.link
- SceneObjects.unlink
- SceneSequence.scene_camera
- ScrewModifier.object
- ShrinkwrapConstraint.target
- ShrinkwrapModifier.assistant_target
- ShrinkwrapModifier.target
- SimpleDeformModifier.origin
- SpaceView3D.camera
- SpaceView3D.lock_object
- SplineIKConstraint.target
- StretchToConstraint.target
- TextCurve.follow_curve
- TimelineMarker.camera
- ToolSettings.etch_template
- TrackToConstraint.target
- TransformConstraint.target
- UVProjector.object
- VoxelData.domain_object
- WarpModifier.object_from
- WarpModifier.object_to
- WarpModifier.texture_coords_object
- WaveModifier.start_position_object
- WaveModifier.texture_coords_object
- WorldTextureSlot.object

2.4.361 ObjectActuator(Actuator)

base classes — `bpy_struct, Actuator`

class `bpy.types.ObjectActuator` (`Actuator`)

Actuator to control the object movement

angular_velocity

Sets the angular velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

damping

Number of frames to reach the target velocity

Type int in [-32768, 32767], default 0

derivate_coefficient
Not required, high values can cause instability

Type float in [-inf, inf], default 0.0

force
Sets the force

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

force_max_x
Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_max_y
Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_max_z
Set the upper limit for force

Type float in [-inf, inf], default 0.0

force_min_x
Set the lower limit for force

Type float in [-inf, inf], default 0.0

force_min_y
Set the lower limit for force

Type float in [-inf, inf], default 0.0

force_min_z
Set the lower limit for force

Type float in [-inf, inf], default 0.0

integral_coefficient
Low value (0.01) for slow response, high value (0.5) for fast response

Type float in [-inf, inf], default 0.0

linear_velocity
Sets the linear velocity (in Servo mode it sets the target relative linear velocity, it will be achieved by automatic application of force. Null velocity is a valid target)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mode
Specify the motion system

Type enum in ['OBJECT_NORMAL', 'OBJECT_SERVO'], default 'OBJECT_NORMAL'

offset_location
Sets the location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

offset_rotation
Sets the rotation

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

proportional_coefficient

Typical value is 60x integral coefficient

Type float in [-inf, inf], default 0.0

reference_object

Reference object for velocity calculation, leave empty for world reference

Type Object

torque

Sets the torque

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_add_linear_velocity

Toggles between ADD and SET linV

Type boolean, default False

use_local_angular_velocity

Angular velocity is defined in local coordinates

Type boolean, default False

use_local_force

Force is defined in local coordinates

Type boolean, default False

use_local_linear_velocity

Velocity is defined in local coordinates

Type boolean, default False

use_local_location

Location is defined in local coordinates

Type boolean, default False

use_local_rotation

Rotation is defined in local coordinates

Type boolean, default False

use_local_torque

Torque is defined in local coordinates

Type boolean, default False

use_servo_limit_x

Set limit to force along the X axis

Type boolean, default False

use_servo_limit_y

Set limit to force along the Y axis

Type boolean, default False

use_servo_limit_z

Set limit to force along the Z axis

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.362 ObjectBase(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ObjectBase` (`bpy_struct`)

An object instance in a scene

layers

Layers the object base is on

Type boolean array of 20 items, default (False, False, False)

object

Object this base links to

Type `Object`, (readonly)

select

Object base selection state

Type boolean, default False

layers_from_view (`view`)

Sets the object layers from a 3D View (use when adding an object in local view).

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.object_bases
- SceneBases.active
- SceneObjects.link

2.4.363 ObjectConstraints(bpy_struct)

base class — bpy_struct

class bpy.types.ObjectConstraints (bpy_struct)
Collection of object constraints

active

Active Object constraint

Type Constraint

new (type)

Add a new constraint to this object

Parameters type (enum in ['COPY_LOCATION', 'COPY_ROTATION', 'COPY_SCALE', 'COPY_TRANSFORMS', 'LIMIT_DISTANCE', 'LIMIT_LOCATION', 'LIMIT_ROTATION', 'LIMIT_SCALE', 'MAINTAIN_VOLUME', 'TRANSFORM', 'CLAMP_TO', 'DAMPED_TRACK', 'IK', 'LOCKED_TRACK', 'SPLINE_IK', 'STRETCH_TO', 'TRACK_TO', 'ACTION', 'CHILD_OF', 'FLOOR', 'FOLLOW_PATH', 'PIVOT', 'RIGID_BODY_JOINT', 'SCRIPT', 'SHRINKWRAP']) – Constraint type to add.

Returns New constraint.

Return type Constraint

remove (constraint)

Remove a constraint from this object.

Parameters **constraint** ([Constraint](#), (never None)) – Removed constraint.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.constraints`

2.4.364 ObjectModifiers(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ObjectModifiers (bpy_struct)`

Collection of object modifiers

new (name, type)

Add a new modifier.

Parameters

- **name** (*string*) – New name for the bone.
- **type** (*enum in* ['ARRAY', 'BEVEL', 'BOOLEAN', 'BUILD', 'DECIMATE', 'EDGE_SPLIT', 'MASK', 'MIRROR', 'MULTIRES', 'SCREW', 'SOLIDIFY', 'SUBSURF', 'UV_PROJECT', 'ARMATURE', 'CAST', 'CURVE', 'DISPLACE', 'HOOK', 'LATTICE', 'MESH_DEFORM', 'SHRINKWRAP', 'SIMPLE_DEFORM', 'SMOOTH', 'WARP', 'WAVE', 'CLOTH', 'COLLISION', 'EXPLODE', 'FLUID_SIMULATION', 'PARTICLE_INSTANCE', 'PARTICLE_SYSTEM', 'SMOKE', 'SOFT_BODY', 'SURFACE']) – Modifier type to add.

Returns Newly created modifier.

Return type `Modifier`

remove (`modifier`)

Remove an existing modifier from the object.

Parameters `modifier` (`Modifier`, (never None)) – Modifier to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.modifiers`

2.4.365 `ObstacleFluidSettings(FluidSettings)`

base classes — `bpy_struct, FluidSettings`

class `bpy.types.ObstacleFluidSettings(FluidSettings)`

Fluid simulation settings for obstacles in the simulation

impact_factor

This is an unphysical value for moving objects - it controls the impact an obstacle has on the fluid, =0 behaves a bit like outflow (deleting fluid), =1 is default, while >1 results in high forces. Can be used to tweak total mass

Type float in [-2, 10], default 0.0

partial_slip_factor

Amount of mixing between no- and free-slip, 0 is no slip and 1 is free slip

Type float in [0, 1], default 0.0

slip_type

Type enum in ['NOSLIP', 'PARTIALSLIP', 'FREESLIP'], default 'NOSLIP'

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_INITIALIZATION

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- `bpy_struct.id_data`
- `FluidSettings.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.366 Operator(`bpy_struct`)

Basic Operator Example

This script shows simple operator which prints a message.

Since the operator only has an `Operator.execute` function it takes no user input.

Note: Operator subclasses must be registered before accessing them from blender.

```
import bpy

class HelloWorldOperator(bpy.types.Operator):
    bl_idname = "wm.hello_world"
    bl_label = "Minimal Operator"

    def execute(self, context):
        print("Hello World")
        return {'FINISHED'}

bpy.utils.register_class(SimpleOperator)

# test call to the newly defined operator
bpy.ops.wm.hello_world()
```

Invoke Function

`Operator.invoke` is used to initialize the operator from the context at the moment the operator is called. `invoke()` is typically used to assign properties which are then used by `execute()`. Some operators don't have an `execute()` function, removing the ability to be repeated from a script or macro.

This example shows how to define an operator which gets mouse input to execute a function and that this operator can be invoked or executed from the python api.

Also notice this operator defines its own properties, these are different to typical class properties because blender registers them with the operator, to use as arguments when called, saved for operator undo/redo and automatically added into the user interface.

```
import bpy

class SimpleMouseOperator(bpy.types.Operator):
    """ This operator shows the mouse location,
    this string is used for the tooltip and API docs
    """
    bl_idname = "wm.mouse_position"
    bl_label = "Invoke Mouse Operator"

    x = bpy.props.IntProperty()
    y = bpy.props.IntProperty()

    def execute(self, context):
        # rather than printing, use the report function,
        # this way the message appears in the header,
        self.report({'INFO'}, "Mouse coords are %d %d" % (self.x, self.y))
        return {'FINISHED'}

    def invoke(self, context, event):
        self.x = event.mouse_x
        self.y = event.mouse_y
        return self.execute(context)

bpy.utils.register_class(SimpleMouseOperator)

# Test call to the newly defined operator.
# Here we call the operator and invoke it, meaning that the settings are taken
```

```
# from the mouse.  
bpy.ops.wm.mouse_position('INVOKE_DEFAULT')  
  
# Another test call, this time call execute() directly with pre-defined settings.  
bpy.ops.wm.mouse_position('EXEC_DEFAULT', x=20, y=66)
```

Calling a File Selector

This example shows how an operator can use the file selector.

Notice the invoke function calls a window manager method and returns RUNNING_MODAL, this means the file selector stays open and the operator does not exit immediately after invoke finishes.

The file selector runs the operator, calling `Operator.execute` when the user confirms.

The `Operator.poll` function is optional, used to check if the operator can run.

```
import bpy
```

```
class ExportSomeData(bpy.types.Operator):  
    """Test exporter which just writes hello world"""  
    bl_idname = "export.some_data"  
    bl_label = "Export Some Data"  
  
    filepath = bpy.props.StringProperty(subtype="FILE_PATH")  
  
    @classmethod  
    def poll(cls, context):  
        return context.object is not None  
  
    def execute(self, context):  
        file = open(self.filepath, 'w')  
        file.write("Hello World " + context.object.name)  
        return {'FINISHED'}  
  
    def invoke(self, context, event):  
        context.window_manager.fileselect_add(self)  
        return {'RUNNING_MODAL'}  
  
    # Only needed if you want to add into a dynamic menu  
    def menu_func(self, context):  
        self.layout.operator_context = 'INVOKE_DEFAULT'  
        self.layout.operator(ExportSomeData.bl_idname, text="Text Export Operator")  
  
    # Register and add to the file selector  
    bpy.utils.register_class(ExportSomeData)  
    bpy.types.INFO_MT_file_export.append(menu_func)  
  
    # test call  
    bpy.ops.export.some_data('INVOKE_DEFAULT')
```

Dialog Box

This operator uses its `Operator.invoke` function to call a popup.

```
import bpy

class DialogOperator(bpy.types.Operator):
    bl_idname = "object.dialog_operator"
    bl_label = "Simple Dialog Operator"

    my_float = bpy.props.FloatProperty(name="Some Floating Point")
    my_bool = bpy.props.BoolProperty(name="Toggle Option")
    my_string = bpy.props.StringProperty(name="String Value")

    def execute(self, context):
        message = "Popup Values: %f, %d, '%s'" % \
            (self.my_float, self.my_bool, self.my_string)
        self.report({'INFO'}, message)
        return {'FINISHED'}

    def invoke(self, context, event):
        wm = context.window_manager
        return wm.invoke_props_dialog(self)

bpy.utils.register_class(DialogOperator)

# test call
bpy.ops.object.dialog_operator('INVOKE_DEFAULT')
```

Custom Drawing

By default operator properties use an automatic user interface layout. If you need more control you can create your own layout with a `Operator.draw` function.

This works like the `Panel` and `Menu` draw functions, its used for dialogs and file selectors.

```
import bpy

class CustomDrawOperator(bpy.types.Operator):
    bl_idname = "object.custom_draw"
    bl_label = "Simple Modal Operator"

    filepath = bpy.props.StringProperty(subtype="FILE_PATH")

    my_float = bpy.props.FloatProperty(name="Float")
    my_bool = bpy.props.BoolProperty(name="Toggle Option")
    my_string = bpy.props.StringProperty(name="String Value")

    def execute(self, context):
        print()
        return {'FINISHED'}

    def invoke(self, context, event):
        context.window_manager.fileselect_add(self)
        return {'RUNNING_MODAL'}

    def draw(self, context):
        layout = self.layout
```

```
col = layout.column()
col.label(text="Custom Interface!")

row = col.row()
row.prop(self, "my_float")
row.prop(self, "my_bool")

col.prop(self, "my_string")

bpy.utils.register_class(CustomDrawOperator)

# test call
bpy.ops.object.custom_draw('INVOKE_DEFAULT')
```

Modal Execution

This operator defines a `Operator.modal` function which runs, handling events until it returns {‘FINISHED’} or {‘CANCELLED’}.

Grab, Rotate, Scale and Fly-Mode are examples of modal operators. They are especially useful for interactive tools, your operator can have its own state where keys toggle options as the operator runs.

`Operator.invoke` is used to initialize the operator as being by returning {‘RUNNING_MODAL’}, initializing the modal loop.

Notice `__init__()` and `__del__()` are declared. For other operator types they are not useful but for modal operators they will be called before the `Operator.invoke` and after the operator finishes.

```
import bpy

class ModalOperator(bpy.types.Operator):
    bl_idname = "object.modal_operator"
    bl_label = "Simple Modal Operator"

    def __init__(self):
        print("Start")

    def __del__(self):
        print("End")

    def execute(self, context):
        context.object.location.x = self.value / 100.0

    def modal(self, context, event):
        if event.type == 'MOUSEMOVE': # Apply
            self.value = event.mouse_x
            self.execute(context)
        elif event.type == 'LEFTMOUSE': # Confirm
            return {'FINISHED'}
        elif event.type in ('RIGHTMOUSE', 'ESC'): # Cancel
            return {'CANCELLED'}

    return {'RUNNING_MODAL'}

def invoke(self, context, event):
    self.value = event.mouse_x
    self.execute(context)
```

```
print(context.window_manager.modal_handler_add(self))
return {'RUNNING_MODAL'}
```

bpy.utils.register_class(ModalOperator)

test call
bpy.ops.object.modal_operator('INVOKE_DEFAULT')

base class — `bpy_struct`

class bpy.types.Operator (`bpy_struct`)
Storage of an operator being executed, or registered after execution

bl_description
Type string, default “”

bl_idname
Type string, default “”

bl_label
Type string, default “”

bl_options
Options for this operator type
Type enum set in {‘REGISTER’, ‘UNDO’, ‘BLOCKING’, ‘MACRO’, ‘GRAB_POINTER’, ‘PRESET’, ‘INTERNAL’}, default {‘REGISTER’}

has_reports
Operator has a set of reports (warnings and errors) from last execution
Type boolean, default False, (readonly)

layout
Type `UILayout`, (readonly)

name
Type string, default “”, (readonly)

properties
Type `OperatorProperties`, (readonly, never None)

report (*type, message*)
report

Parameters

- **type** (enum set in {‘DEBUG’, ‘INFO’, ‘OPERATOR’, ‘WARNING’, ‘ERROR’, ‘ERROR_INVALID_INPUT’, ‘ERROR_INVALID_CONTEXT’, ‘ERROR_OUT_OF_MEMORY’}) – Type
- **message** (string) – Report Message

classmethod poll (*context*)
Test if the operator can be called or not.

Return type boolean

execute (*context*)

Execute the operator.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

check (*context*)

Check the operator settings.

Returns result

Return type boolean

invoke (*context, event*)

Invoke the operator.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

modal (*context, event*)

Modal operator function.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

draw (*context*)

Draw function for the operator.

cancel (*context*)

Called when the operator is cancelled.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

as_keywords (*ignore=()*)

Return a copy of the properties as a dictionary.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceFileBrowser.operator
- WindowManager.fileselect_add
- WindowManager.invoke_confirm
- WindowManager.invoke_popup
- WindowManager.invoke_props_dialog
- WindowManager.invoke_props_popup
- WindowManager.invoke_search_popup
- WindowManager.modal_handler_add
- WindowManager.operators

2.4.367 OperatorFileListElement(PropertyGroup)

base classes — bpy_struct, PropertyGroup

class bpy.types.OperatorFileListElement (*PropertyGroup*)

name

the name of a file or directory within a file list

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.368 OperatorMousePath(PropertyGroup)

base classes — `bpy_struct, PropertyGroup`

class bpy.types.OperatorMousePath (PropertyGroup)

Mouse path values for operators that record such paths

loc

Mouse location

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

time

Time of mouse location

Type float in [-inf, inf], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `PropertyGroup.name`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.369 OperatorProperties(bpy_struct)

base class — `bpy_struct`

class bpy.types.OperatorProperties (bpy_struct)

Input properties of an Operator

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `KeyMapItem.properties`
- `Macro.properties`
- `Operator.properties`
- `OperatorTypeMacro.properties`
- `UILayout.operator`

2.4.370 OperatorStrokeElement(PropertyGroup)

base classes — `bpy_struct, PropertyGroup`

`class bpy.types.OperatorStrokeElement (PropertyGroup)`

`is_start`

Type boolean, default False

`location`

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`mouse`

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

`pen_flip`

Type boolean, default False

`pressure`

Tablet pressure

Type float in [0, 1], default 0.0

time

Type float in [0, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- PropertyGroup.name

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.371 OperatorTypeMacro(bpy_struct)

base class — bpy_struct

class bpy.types.OperatorTypeMacro (*bpy_struct*)

Storage of a sub operator in a macro after it has been added

properties

Type OperatorProperties, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.372 OrController(Controller)

base classes — `bpy_struct, Controller`

class bpy.types.OrController(Controller)
Controller passing on events based on a logical OR operation

Inherited Properties

- `bpy_struct.id_data`
- `Controller.name`
- `Controller.states`
- `Controller.show_expanded`
- `Controller.use_priority`
- `Controller.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Controller.link`
- `Controller.unlink`

2.4.373 OutflowFluidSettings(FluidSettings)

base classes — `bpy_struct`, `FluidSettings`

class bpy.types.OutflowFluidSettings(FluidSettings)

Fluid simulation settings for objects removing fluids from the simulation

use

Object contributes to the fluid simulation

Type boolean, default False

use_animated_mesh

Export this mesh as an animated one. Slower, only use if really necessary (e.g. armatures or parented objects), animated pos/rot/scale IPOs do not require it

Type boolean, default False

volume_INITIALIZATION

Volume initialization type

Type enum in ['VOLUME', 'SHELL', 'BOTH'], default 'VOLUME'

Inherited Properties

- `bpy_struct.id_data`
- `FluidSettings.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.374 PackedFile(bpy_struct)

base class — `bpy_struct`

class bpy.types.PackedFile(bpy_struct)

External file packed into the .blend file

size

Size of packed file in bytes

Type int in [-inf, inf], default 0, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Image.packed_file
- Sound.packed_file
- VectorFont.packed_file

2.4.375 Paint(bpy_struct)

base class — bpy_struct

subclasses — VertexPaint, Sculpt, ImagePaint

class bpy.types.Paint (bpy_struct)

brush

Active Brush

Type Brush

show_brush

Type boolean, default False

show_brush_on_surface

Type boolean, default False

show_low_resolution

For multires, show low resolution while navigating the view

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.376 Panel(bpy_struct)

Basic Panel Example

This script is a simple panel which will draw into the object properties section.

Notice the ‘CATEGORY_PT_name’ Panel.bl_idname, this is a naming convention for panels.

Note: Panel subclasses must be registered for blender to use them.

```
import bpy

class HelloWorldPanel(bpy.types.Panel):
    bl_idname = "OBJECT_PT_hello_world"
    bl_label = "Hello World"
    bl_space_type = 'PROPERTIES'
    bl_region_type = 'WINDOW'
    bl_context = "object"

    def draw(self, context):
        self.layout.label(text="Hello World")

bpy.utils.register_class(HelloWorldPanel)
```

Simple Object Panel

This panel has a `Panel.poll` and `Panel.draw_header` function, even though the contents is basic this closely resemplies blenders panels.

```
import bpy

class ObjectSelectPanel(bpy.types.Panel):
    bl_idname = "OBJECT_PT_select"
    bl_label = "Select"
    bl_space_type = 'PROPERTIES'
    bl_region_type = 'WINDOW'
    bl_context = "object"
    bl_options = {'DEFAULT_CLOSED'}

    @classmethod
    def poll(cls, context):
        return (context.object is not None)

    def draw_header(self, context):
        layout = self.layout
        obj = context.object
        layout.prop(obj, "select", text="")

    def draw(self, context):
        layout = self.layout

        obj = context.object
        row = layout.row()
        row.prop(obj, "hide_select")
        row.prop(obj, "hide_render")

        box = layout.box()
        box.label("Selection Tools")
        box.operator("object.select_all")
        row = box.row()
        row.operator("object.select_inverse")
        row.operator("object.select_random")

bpy.utils.register_class(ObjectSelectPanel)
```

Mix-in Classes

A mix-in parent class can be used to share common properties and `Menu.poll` function.

```
import bpy

class View3DPanel():
    bl_space_type = 'VIEW_3D'
    bl_region_type = 'TOOLS'

    @classmethod
    def poll(cls, context):
        return (context.object is not None)
```

```
class PanelOne(View3DPanel, bpy.types.Panel):
    bl_idname = "VIEW3D_PT_test_1"
    bl_label = "Panel One"

    def draw(self, context):
        self.layout.label("Small Class")

class PanelTwo(View3DPanel, bpy.types.Panel):
    bl_idname = "VIEW3D_PT_test_2"
    bl_label = "Panel Two"

    def draw(self, context):
        self.layout.label("Also Small Class")

bpy.utils.register_class(PanelOne)
bpy.utils.register_class(PanelTwo)

base class — bpy\_struct

class bpy.types.Panel (bpy\_struct)
    Panel containing UI elements

bl_context
    The context in which the panel belongs to. (TODO: explain the possible combinations
    bl_context/bl_region_type/bl_space_type)

    Type string, default “”

bl_idname
    If this is set, the panel gets a custom ID, otherwise it takes the name of the class used to define the panel. For
    example, if the class name is “OBJECT_PT_hello”, and bl_idname is not set by the script, then bl_idname
    = “OBJECT_PT_hello”

    Type string, default “”

bl_label
    The panel label, shows up in the panel header at the right of the triangle used to collapse the panel.

    Type string, default “”

bl_options
    Options for this panel type

    Type enum set in {‘DEFAULT_CLOSED’, ‘HIDE_HEADER’}, default {‘DE-
        FAULT_CLOSED’}

bl_region_type
    The region where the panel is going to be used in.

    Type enum in [‘WINDOW’, ‘HEADER’, ‘CHANNELS’, ‘TEMPORARY’, ‘UI’, ‘TOOLS’,
        ‘TOOL_PROPS’, ‘PREVIEW’], default ‘WINDOW’

bl_space_type
    The space where the panel is going to be used in.

    Type enum in [‘EMPTY’, ‘VIEW_3D’, ‘GRAPH_EDITOR’, ‘OUTLINER’, ‘PROP-
        ERTIES’, ‘FILE_BROWSER’, ‘IMAGE_EDITOR’, ‘INFO’, ‘SEQUENCE_EDITOR’,
        ‘TEXT_EDITOR’, ‘AUDIO_WINDOW’, ‘DOPESHEET_EDITOR’, ‘NLA_EDITOR’,
```

‘SCRIPTS_WINDOW’, ‘TIMELINE’, ‘NODE_EDITOR’, ‘LOGIC_EDITOR’, ‘CONSOLE’, ‘USER_PREFERENCES’], default ‘EMPTY’

layout

Defines the structure of the panel in the UI.

Type `UILayout`, (readonly)

text

XXX todo

Type `string`, default “”

classmethod poll (context)

If this method returns a non-null output, then the panel can be drawn.

Return type `boolean`

draw (context)

Draw UI elements into the panel UI layout.

draw_header (context)

Draw UI elements into the panel’s header UI layout.

classmethod append (draw_func)

Append a draw function to this menu, takes the same arguments as the menus draw function.

classmethod prepend (draw_func)

Prepend a draw function to this menu, takes the same arguments as the menus draw function.

classmethod remove (draw_func)

Remove a draw function that has been added to this menu

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.377 ParentActuator(Actuator)

base classes — `bpy_struct`, `Actuator`
`class bpy.types.ParentActuator(Actuator)`

`mode`

Type enum in ['SETPARENT', 'REMOVEPARENT'], default 'SETPARENT'

`object`

Set this object as parent

Type `Object`

`use_compound`

Add this object shape to the parent shape (only if the parent shape is already compound)

Type boolean, default False

`use_ghost`

Make this object ghost while parented

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.378 Particle([bpy_struct](#))

base class — [bpy_struct](#)

class [bpy.types.Particle](#) (*bpy_struct*)

Particle in a particle system

alive_state

Type enum in ['DEAD', 'UNBORN', 'ALIVE', 'DYING'], default 'DEAD'

angular_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

birth_time

Type float in [-inf, inf], default 0.0

die_time

Type float in [-inf, inf], default 0.0

hair_keys

Type [bpy_prop_collection](#) of [ParticleHairKey](#), (readonly)

is_exist

Type boolean, default False, (readonly)

is_visible

Type boolean, default False, (readonly)

lifetime

Type float in [-inf, inf], default 0.0

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

particle_keys

Type [bpy_prop_collection](#) of [ParticleKey](#), (readonly)

prev_angular_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

prev_location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

prev_rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

prev_velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

size

Type float in [-inf, inf], default 0.0

velocity

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.particles

2.4.379 ParticleBrush(bpy_struct)

base class — bpy_struct

class bpy.types.ParticleBrush (*bpy_struct*)

Particle editing brush

count

Particle count

Type int in [1, 1000], default 0

curve

Type CurveMapping, (readonly)

length_mode

Type enum in ['GROW', 'SHRINK'], default 'GROW'

puff_mode

Type enum in ['ADD', 'SUB'], default 'ADD'

size

Radius of the brush in pixels

Type int in [1, 32767], default 0

steps

Brush steps

Type int in [1, 32767], default 0

strength

Brush strength

Type float in [0.001, 1], default 0.0

use_puff_volume

Apply puff to unselected end-points, (helps maintain hair volume when puffing root)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleEdit.brush

2.4.380 ParticleDupliWeight(bpy_struct)

base class — bpy_struct

class bpy.types.ParticleDupliWeight (*bpy_struct*)

Weight of a particle dupliobject in a group

count

The number of times this object is repeated with respect to other objects

Type int in [0, 32767], default 0

name

Particle dupliobject name

Type string, default "", (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ParticleSettings.active_dupliweight`
- `ParticleSettings.dupli_weights`

2.4.381 ParticleEdit(bpy_struct)

base class — `bpy_struct`

class `bpy.types.ParticleEdit(bpy_struct)`

Properties of particle editing mode

brush

Type `ParticleBrush`, (readonly)

default_key_count

How many keys to make new particles with

Type int in [2, 32767], default 0

draw_step

How many steps to draw the path with

Type int in [2, 10], default 0

emitter_distance

Distance to keep particles away from the emitter

Type float in [0, inf], default 0.0

fade_frames

How many frames to fade

Type int in [2, 100], default 0

is_editable

A valid edit mode exists

Type boolean, default False, (readonly)

is_hair

Editing hair

Type boolean, default False, (readonly)

object

The edited object

Type `Object`, (readonly)

select_mode

Particle select and display mode

Type enum in ['PATH', 'POINT', 'TIP'], default 'PATH'

show_particles

Draw actual particles

Type boolean, default False

tool

Type enum in ['NONE', 'COMB', 'SMOOTH', 'ADD', 'LENGTH', 'PUFF', 'CUT', 'WEIGHT'], default 'COMB'

type

Type enum in ['PARTICLES', 'SOFT_BODY', 'CLOTH'], default 'PARTICLES'

use_auto_velocity

Calculate point velocities automatically

Type boolean, default False

use_default_interpolate

Interpolate new particles from the existing ones

Type boolean, default False

use_emitter_deflect

Keep paths from intersecting the emitter

Type boolean, default False

use_fade_time

Fade paths and keys further away from current frame

Type boolean, default False

use_preserve_length

Keep path lengths constant

Type boolean, default False

use_preserve_root

Keep root keys unmodified

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.particle_edit

2.4.382 ParticleFluidSettings(FluidSettings)

base classes — bpy_struct, FluidSettings

class bpy.types.ParticleFluidSettings(FluidSettings)

Fluid simulation settings for objects storing fluid particles generated by the simulation

alpha_influence

Amount of particle alpha change, inverse of size influence: 0=off (all same alpha), 1=full. (large particles get lower alphas, smaller ones higher values)

Type float in [0, 2], default 0.0

filepath

Directory (and/or filename prefix) to store and load particles from

Type string, default “”

particle_influence
Amount of particle size scaling: 0=off (all same size), 1=full (range 0.2-2.0), >1=stronger

Type float in [0, 2], default 0.0

show_tracer
Show tracer particles

Type boolean, default False

use_drops
Show drop particles

Type boolean, default False

use_floats
Show floating foam particles

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `FluidSettings.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.383 ParticleHairKey(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.ParticleHairKey(`bpy_struct`)
Particle key for hair particle system

co
Location of the hair key in object space

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

co_hair_space

Location of the hair key in its internal coordinate system, relative to the emitting face

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

time

Relative time of key over hair length

Type float in [0, inf], default 0.0

weight

Weight for cloth simulation

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Particle.hair_keys

2.4.384 ParticleInstanceModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ParticleInstanceModifier (*Modifier*)

Particle system instancing modifier

axis

Pole axis for rotation

Type enum in ['X', 'Y', 'Z'], default 'X'

object

Object that has the particle system

Type [Object](#)

particle_system_index

Type int in [1, 10], default 0

position

Position along path

Type float in [0, 1], default 0.0

random_position

Randomize position along path

Type float in [0, 1], default 0.0

show_alive

Show instances when particles are alive

Type boolean, default False

show_dead

Show instances when particles are dead

Type boolean, default False

show_unborn

Show instances when particles are unborn

Type boolean, default False

use_children

Create instances from child particles

Type boolean, default False

use_normal

Create instances from normal particles

Type boolean, default False

use_path

Create instances along particle paths

Type boolean, default False

use_preserve_shape

Don't stretch the object

Type boolean, default False

use_size

Use particle size to scale the instances

Type boolean, default False

Inherited Properties

- [bpy_struct.id_data](#)
- [Modifier.name](#)
- [Modifier.use_apply_on_spline](#)

- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.385 ParticleKey(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ParticleKey` (`bpy_struct`)
Key location for a particle over time

angular_velocity
Key angular velocity
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

location
Key location
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation
Key rotation quaternion
Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

time
Time of key over the simulation
Type float in [0, inf], default 0.0

velocity
Key velocity
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Particle.particle_keys

2.4.386 ParticleSettings(ID)

base classes — bpy_struct, ID

class bpy.types.ParticleSettings (ID)

Particle settings, reusable by multiple particle systems

active_dupliweight

Type ParticleDupliWeight, (readonly)

active_dupliweight_index

Type int in [0, inf], default 0

active_texture

Active texture slot being displayed

Type Texture

active_texture_index

Index of active texture slot

Type int in [0, 17], default 0

adaptive_angle

How many degrees path has to curve to make another render segment

Type int in [0, 45], default 0

adaptive_pixel

How many pixels path has to cover to make another render segment

Type int in [0, 50], default 0

angular_velocity_factor

Angular velocity amount

Type float in [-200, 200], default 0.0

angular_velocity_mode

Particle angular velocity mode

Type enum in ['NONE', 'SPIN', 'RAND'], default 'NONE'

animation_data

Animation data for this datablock

Type `AnimData`, (readonly)

apply_effector_to_children

Apply effectors to children

Type boolean, default False

apply_guide_to_children

Type boolean, default False

billboard_align

In respect to what the billboards are aligned

Type enum in ['X', 'Y', 'Z', 'VIEW', 'VEL'], default 'X'

billboard_animation

How to animate billboard textures

Type enum in ['NONE', 'AGE', 'FRAME', 'ANGLE'], default 'NONE'

billboard_object

Billboards face this object (default is active camera)

Type `Object`

billboard_offset

Type float array of 2 items in [-100, 100], default (0.0, 0.0)

billboard_offset_split

How to offset billboard textures

Type enum in ['NONE', 'LINEAR', 'RANDOM'], default 'NONE'

billboard_size

Scale billboards relative to particle size

Type float array of 2 items in [0.001, 10], default (0.0, 0.0)

billboard_tilt

Tilt of the billboards

Type float in [-1, 1], default 0.0

billboard_tilt_random

Random tilt of the billboards

Type float in [0, 1], default 0.0

billboard_uv_split

Amount of rows/columns to split UV coordinates for billboards

Type int in [1, 100], default 0

billboard_velocity_head

Scale billboards by velocity

Type float in [0, 10], default 0.0

billboard_velocity_tail

Scale billboards by velocity

Type float in [0, 10], default 0.0

boids

Type `BoidSettings`, (readonly)

branch_threshold

Threshold of branching

Type float in [0, 1], default 0.0

brownian_factor

Specify the amount of Brownian motion

Type float in [0, 200], default 0.0

child_length

Length of child paths

Type float in [0, 1], default 0.0

child_length_threshold

Amount of particles left untouched by child path length

Type float in [0, 1], default 0.0

child_nbr

Amount of children/parent

Type int in [0, 100000], default 0

child_parting_factor

Create parting in the children based on parent strands

Type float in [0, 1], default 0.0

child_parting_max

Maximum root to tip angle (tip distance/root distance for long hair)

Type float in [0, 180], default 0.0

child_parting_min

Minimum root to tip angle (tip distance/root distance for long hair)

Type float in [0, 180], default 0.0

child_radius

Radius of children around parent

Type float in [0, 10], default 0.0

child_roundness

Roundness of children around parent

Type float in [0, 1], default 0.0

child_size
A multiplier for the child particle size

Type float in [0.001, 100000], default 0.0

child_size_random
Random variation to the size of the child particles

Type float in [0, 1], default 0.0

child_type
Create child particles

Type enum in ['NONE', 'SIMPLE', 'INTERPOLATED'], default 'NONE'

clump_factor
Amount of clumping

Type float in [-1, 1], default 0.0

clump_shape
Shape of clumping

Type float in [-0.999, 0.999], default 0.0

color_maximum
Maximum length of the particle color vector

Type float in [0.01, 100], default 0.0

count
Total number of particles

Type int in [0, 10000000], default 0

create_long_hair_children
Calculate children that suit long hair well

Type boolean, default False

damping
Specify the amount of damping

Type float in [0, 1], default 0.0

distribution
How to distribute particles on selected element

Type enum in ['NONE', 'RENDER', 'DOT', 'CIRC', 'CROSS', 'AXIS'], default 'NONE'

drag_factor
Specify the amount of air-drag

Type float in [0, 1], default 0.0

draw_color
Draw additional particle data as a color

Type enum in ['NONE', 'MATERIAL', 'VELOCITY', 'ACCELERATION'], default 'NONE'

draw_method
How particles are drawn in viewport

Type enum in ['NONE', 'RENDER', 'DOT', 'CIRC', 'CROSS', 'AXIS'], default 'NONE'

draw_percentage

Percentage of particles to display in 3D view

Type int in [0, 100], default 0

draw_size

Size of particles on viewport in pixels (0=default)

Type int in [0, 1000], default 0

draw_step

How many steps paths are drawn with (power of 2)

Type int in [0, 10], default 0

dupli_group

Show Objects in this Group in place of particles

Type Group

dupli_object

Show this Object in place of particles

Type Object

dupli_weights

Weights for all of the objects in the dupli group

Type bpy_prop_collection of ParticleDupliWeight, (readonly)

effect_hair

Hair stiffness for effectors

Type float in [0, 1], default 0.0

effector_amount

How many particles are effectors (0 is all particles)

Type int in [0, 10000], default 0

effector_weights

Type EffectorWeights, (readonly)

emit_from

Where to emit particles from

Type enum in ['VERT', 'FACE', 'VOLUME'], default 'VERT'

factor_random

Give the starting speed a random variation

Type float in [0, 200], default 0.0

fluid

Type SPHFluidSettings, (readonly)

force_field_1

Type FieldSettings, (readonly)

force_field_2

Type FieldSettings, (readonly)

frame_end

Frame # to stop emitting particles

Type float in [-300000, 300000], default 0.0

frame_start
Frame # to start emitting particles
Type float in [-300000, 300000], default 0.0

grid_random
Add random offset to the grid locations
Type float in [0, 1], default 0.0

grid_resolution
The resolution of the particle grid
Type int in [1, 250], default 0

hair_length
Length of the hair
Type float in [0, 1000], default 0.0

hair_step
Number of hair segments
Type int in [2, 50], default 0

hexagonal_grid
Create the grid in a hexagonal pattern
Type boolean, default False

integrator
Algorithm used to calculate physics. Fastest to most stable/accurate: Midpoint, Euler, Verlet, RK4 (Old)
Type enum in ['EULER', 'VERLET', 'MIDPOINT', 'RK4'], default 'EULER'

invert_grid
Invert what is considered object and what is not
Type boolean, default False

is_fluid
Particles were created by a fluid simulation
Type boolean, default False, (readonly)

jitter_factor
Amount of jitter applied to the sampling
Type float in [0, 2], default 0.0

keyed_loops
Number of times the keys are looped
Type int in [1, 10000], default 0

keys_step
Type int in [0, 32767], default 0

kink
Type of periodic offset on the path
Type enum in ['NO', 'CURL', 'RADIAL', 'WAVE', 'BRAID'], default 'NO'

kink_amplitude

The amplitude of the offset

Type float in [-100000, 100000], default 0.0

kink_amplitude_clump

How much clump effects kink amplitude

Type float in [0, 1], default 0.0

kink_axis

Which axis to use for offset

Type enum in ['X', 'Y', 'Z'], default 'X'

kink_flat

How flat the hairs are

Type float in [0, 1], default 0.0

kink_frequency

The frequency of the offset (1/total length)

Type float in [-100000, 100000], default 0.0

kink_shape

Adjust the offset to the beginning/end

Type float in [-0.999, 0.999], default 0.0

length_random

Give path length a random variation

Type float in [0, 1], default 0.0

lifetime

Specify the life span of the particles

Type float in [1, 300000], default 0.0

lifetime_random

Give the particle life a random variation

Type float in [0, 1], default 0.0

line_length_head

Length of the line's head

Type float in [0, 100000], default 0.0

line_length_tail

Length of the line's tail

Type float in [0, 100000], default 0.0

lock_billboard

Lock the billboards align axis

Type boolean, default False

lock_boids_to_surface

Constrain boids to a surface

Type boolean, default False

mass

Specify the mass of the particles

Type float in [0.001, 100000], default 0.0

material

Specify material used for the particles

Type int in [1, 32767], default 0

normal_factor

Let the surface normal give the particle a starting speed

Type float in [-1000, 1000], default 0.0

object_align_factor

Let the emitter object orientation give the particle a starting speed

Type float array of 3 items in [-200, 200], default (0.0, 0.0, 0.0)

object_factor

Let the object give the particle a starting speed

Type float in [-200, 200], default 0.0

particle_factor

Let the target particle give the particle a starting speed

Type float in [-200, 200], default 0.0

particle_size

The size of the particles

Type float in [0.001, 100000], default 0.0

path_end

End time of drawn path

Type float in [-inf, inf], default 0.0

path_start

Starting time of drawn path

Type float in [-inf, inf], default 0.0

phase_factor

Initial rotation phase

Type float in [-1, 1], default 0.0

phase_factor_random

Randomize rotation phase

Type float in [0, 1], default 0.0

physics_type

Particle physics type

Type enum in ['NO', 'NEWTON', 'KEYED', 'BOIDS', 'FLUID'], default 'NO'

react_event

The event of target particles to react on

Type enum in ['DEATH', 'COLLIDE', 'NEAR'], default 'DEATH'

reactor_factor

Let the vector away from the target particles location give the particle a starting speed

Type float in [-10, 10], default 0.0

regrow_hair

Regrow hair for each frame

Type boolean, default False

render_step

How many steps paths are rendered with (power of 2)

Type int in [0, 20], default 0

render_type

How particles are rendered

Type enum in ['NONE', 'HALO', 'LINE', 'PATH', 'OBJECT', 'GROUP', 'BILLBOARD'], default 'NONE'

rendered_child_count

Amount of children/parent for rendering

Type int in [0, 100000], default 0

rotation_factor_random

Randomize rotation

Type float in [0, 1], default 0.0

rotation_mode

Particles initial rotation

Type enum in ['NONE', 'NOR', 'VEL', 'GLOB_X', 'GLOB_Y', 'GLOB_Z', 'OB_X', 'OB_Y', 'OB_Z'], default 'NONE'

roughness_1

Amount of location dependent rough

Type float in [0, 100000], default 0.0

roughness_1_size

Size of location dependent rough

Type float in [0.01, 100000], default 0.0

roughness_2

Amount of random rough

Type float in [0, 100000], default 0.0

roughness_2_size

Size of random rough

Type float in [0.01, 100000], default 0.0

roughness_2_threshold

Amount of particles left untouched by random rough

Type float in [0, 1], default 0.0

roughness_end_shape

Shape of end point rough

Type float in [0, 10], default 0.0

roughness_endpoint

Amount of end point rough

Type float in [0, 100000], default 0.0

show_health
Draw boid health
Type boolean, default False

show_number
Show particle number
Type boolean, default False

show_size
Show particle size
Type boolean, default False

show_unborn
Show particles before they are emitted
Type boolean, default False

show_velocity
Show particle velocity
Type boolean, default False

simplify_rate
Speed of simplification
Type float in [0, 1], default 0.0

simplify_refsize
Reference size in pixels, after which simplification begins
Type int in [1, 32768], default 0

simplify_transition
Transition period for fading out strands
Type float in [0, 1], default 0.0

simplify_viewport
Speed of Simplification
Type float in [0, 0.999], default 0.0

size_random
Give the particle size a random variation
Type float in [0, 1], default 0.0

subframes
Subframes to simulate for improved stability and finer granularity simulations
Type int in [0, 1000], default 0

tangent_factor
Let the surface tangent give the particle a starting speed
Type float in [-1000, 1000], default 0.0

tangent_phase
Rotate the surface tangent
Type float in [-1, 1], default 0.0

texture_slots
Texture slots defining the mapping and influence of textures

Type `ParticleSettingsTextureSlots` `bpy_prop_collection` of
`ParticleSettingsTextureSlot`, (readonly)

time_tweak
A multiplier for physics timestep (1.0 means one frame = 1/25 seconds)
Type float in [0, 100], default 0.0

timestep
The simulation timestep per frame (in seconds)
Type float in [0.0001, 100], default 0.0

trail_count
Number of trail particles
Type int in [1, 100000], default 0

type
Particle Type
Type enum in ['EMITTER', 'HAIR'], default 'EMITTER'

use_absolute_path_time
Path timing is in absolute frames
Type boolean, default False

use_advanced_hair
Use full physics calculations for growing hair
Type boolean, default False

use_dead
Show particles after they have died
Type boolean, default False

use_die_on_collision
Particles die when they collide with a deflector object
Type boolean, default False

use_dynamic_rotation
Sets rotation to dynamic/constant
Type boolean, default False

use_emit_random
Emit in random order of elements
Type boolean, default False

use_even_distribution
Use even distribution from faces based on face areas or edge lengths
Type boolean, default False

use_global_dupli
Use object's global coordinates for duplication
Type boolean, default False

use_group_count
Use object multiple times in the same group
Type boolean, default False

use_group_pick_random
Pick objects from group randomly
Type boolean, default False

use_hair_bspline
Interpolate hair using B-Splines
Type boolean, default False

use_multiply_size_mass
Multiply mass by particle size
Type boolean, default False

use_parent_particles
Render parent particles
Type boolean, default False

use_react_multiple
React multiple times
Type boolean, default False

use_react_start_end
Give birth to unreacted particles eventually
Type boolean, default False

use_render_adaptive
Draw steps of the particle path
Type boolean, default False

use_render_emitter
Render emitter Object also
Type boolean, default False

use_self_effect
Particle effectors effect themselves
Type boolean, default False

use_simplify
Remove child strands as the object becomes smaller on the screen
Type boolean, default False

use_simplify_viewport
Type boolean, default False

use_size_deflect
Use particle's size in deflection
Type boolean, default False

use_strand_primitive
Use the strand primitive for rendering
Type boolean, default False

use_velocity_length
Multiply line length by particle speed

Type boolean, default False
use_whole_group
 Use whole group at once
 Type boolean, default False
userjit
 Emission locations / face (0 = automatic)
 Type int in [0, 1000], default 0
virtual_parents
 Relative amount of virtual parents
 Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.particles
- BlendDataParticles.new

- BlendDataParticles.remove
- ParticleSystem.settings

2.4.387 ParticleSettingsTextureSlot(TextureSlot)

base classes — `bpy_struct, TextureSlot`

`class bpy.types.ParticleSettingsTextureSlot (TextureSlot)`
Texture slot for textures in a Particle Settings datablock

`clump_factor`

Amount texture affects child clump

Type float in [-inf, inf], default 0.0

`damp_factor`

Amount texture affects particle damping

Type float in [-inf, inf], default 0.0

`density_factor`

Amount texture affects particle density

Type float in [-inf, inf], default 0.0

`field_factor`

Amount texture affects particle force fields

Type float in [-inf, inf], default 0.0

`gravity_factor`

Amount texture affects particle gravity

Type float in [-inf, inf], default 0.0

`kink_factor`

Amount texture affects child kink

Type float in [-inf, inf], default 0.0

`length_factor`

Amount texture affects child hair length

Type float in [-inf, inf], default 0.0

`life_factor`

Amount texture affects particle life time

Type float in [-inf, inf], default 0.0

`mapping`

Type enum in ['FLAT', 'CUBE', 'TUBE', 'SPHERE'], default 'FLAT'

`mapping_x`

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

`mapping_y`

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

`mapping_z`

Type enum in ['NONE', 'X', 'Y', 'Z'], default 'NONE'

object

Object to use for mapping with Object texture coordinates

Type [Object](#)

rough_factor

Amount texture affects child roughness

Type float in [-inf, inf], default 0.0

size_factor

Amount texture affects physical particle size

Type float in [-inf, inf], default 0.0

texture_coords

Texture coordinates used to map the texture onto the background

Type enum in ['GLOBAL', 'OBJECT', 'UV', 'ORCO', 'STRAND'], default 'GLOBAL'

time_factor

Amount texture affects particle emission time

Type float in [-inf, inf], default 0.0

use_map_clump

Affect the child clumping

Type boolean, default False

use_map_damp

Affect the particle velocity damping

Type boolean, default False

use_map_density

Affect the density of the particles

Type boolean, default False

use_map_field

Affect the particle force fields

Type boolean, default False

use_map_gravity

Affect the particle gravity

Type boolean, default False

use_map_kink

Affect the child kink

Type boolean, default False

use_map_length

Affect the child hair length

Type boolean, default False

use_map_life

Affect the life time of the particles

Type boolean, default False

use_map_rough

Affect the child rough

Type boolean, default False

use_map_size

Affect the particle size

Type boolean, default False

use_map_time

Affect the emission time of the particles

Type boolean, default False

use_map_velocity

Affect the particle initial velocity

Type boolean, default False

uv_layer

UV layer to use for mapping with UV texture coordinates

Type string, default “”

velocity_factor

Amount texture affects particle initial velocity

Type float in [-inf, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- TextureSlot.name
- TextureSlot.blend_type
- TextureSlot.color
- TextureSlot.default_value
- TextureSlot.invert
- TextureSlot.offset
- TextureSlot.output_node
- TextureSlot.use_rgb_to_intensity
- TextureSlot.scale
- TextureSlot.use_stencil
- TextureSlot.texture

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ParticleSettings.texture_slots`
- `ParticleSettingsTextureSlots.add`
- `ParticleSettingsTextureSlots.create`

2.4.388 ParticleSettingsTextureSlots(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ParticleSettingsTextureSlots` (`bpy_struct`)
Collection of texture slots

classmethod `add()`

add

Returns The newly initialized mtex.

Return type `ParticleSettingsTextureSlot`

classmethod `create(index)`

create

Parameters `index (int in [0, inf])` – Index, Slot index to initialize.

Returns The newly initialized mtex.

Return type `ParticleSettingsTextureSlot`

classmethod `clear(index)`

clear

Parameters `index (int in [0, inf])` – Index, Slot index to clear.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ParticleSettings.texture_slots`

2.4.389 ParticleSystem(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ParticleSystem(bpy_struct)`

Particle system in an object

active_particle_target

Type `ParticleTarget`, (readonly)

active_particle_target_index

Type int in [0, inf], default 0

billboard_normal_uv

UV Layer to control billboard normals

Type string, default “”

billboard_split_uv

UV Layer to control billboard splitting

Type string, default “”

billboard_time_index_uv

UV Layer to control billboard time index (X-Y)

Type string, default “”

child_particles

Child particles generated by the particle system

Type `bpy_prop_collection` of `ChildParticle`, (readonly)

child_seed

Offset in the random number table for child particles, to get a different randomized result

Type int in [0, inf], default 0

cloth

Cloth dynamics for hair

Type `ClothModifier`, (readonly, never None)

has_multiple_caches

Particle system has multiple point caches

Type boolean, default False, (readonly)

invert_vertex_group_clump

Negate the effect of the clump vertex group

Type boolean, default False

invert_vertex_group_density
Negate the effect of the density vertex group

Type boolean, default False

invert_vertex_group_field
Negate the effect of the field vertex group

Type boolean, default False

invert_vertex_group_kink
Negate the effect of the kink vertex group

Type boolean, default False

invert_vertex_group_length
Negate the effect of the length vertex group

Type boolean, default False

invert_vertex_group_rotation
Negate the effect of the rotation vertex group

Type boolean, default False

invert_vertex_group_roughness_1
Negate the effect of the roughness 1 vertex group

Type boolean, default False

invert_vertex_group_roughness_2
Negate the effect of the roughness 2 vertex group

Type boolean, default False

invert_vertex_group_roughness_end
Negate the effect of the roughness end vertex group

Type boolean, default False

invert_vertex_group_size
Negate the effect of the size vertex group

Type boolean, default False

invert_vertex_group_tangent
Negate the effect of the tangent vertex group

Type boolean, default False

invert_vertex_group_velocity
Negate the effect of the velocity vertex group

Type boolean, default False

is_editable
Particle system can be edited in particle mode

Type boolean, default False, (readonly)

is_edited
Particle system has been edited in particle mode

Type boolean, default False, (readonly)

is_global_hair
Hair keys are in global coordinate space
Type boolean, default False, (readonly)

name
Particle system name
Type string, default “”

parent
Use this object’s coordinate system instead of global coordinate system
Type Object

particles
Particles generated by the particle system
Type bpy_prop_collection of Particle, (readonly)

point_cache
Type PointCache, (readonly, never None)

reactor_target_object
For reactor systems, the object that has the target particle system (empty if same object)
Type Object

reactor_target_particle_system
For reactor systems, index of particle system on the target object
Type int in [1, 32767], default 0

seed
Offset in the random number table, to get a different randomized result
Type int in [0, inf], default 0

settings
Particle system settings
Type ParticleSettings, (never None)

targets
Target particle systems
Type bpy_prop_collection of ParticleTarget, (readonly)

use_hair_dynamics
Enable hair dynamics using cloth simulation
Type boolean, default False

use_keyed_timing
Use key times
Type boolean, default False

vertex_group_clump
Vertex group to control clump
Type string, default “”

vertex_group_density
Vertex group to control density

Type string, default “”

vertex_group_field
Vertex group to control field

Type string, default “”

vertex_group_kink
Vertex group to control kink

Type string, default “”

vertex_group_length
Vertex group to control length

Type string, default “”

vertex_group_rotation
Vertex group to control rotation

Type string, default “”

vertex_group_roughness_1
Vertex group to control roughness 1

Type string, default “”

vertex_group_roughness_2
Vertex group to control roughness 2

Type string, default “”

vertex_group_roughness_end
Vertex group to control roughness end

Type string, default “”

vertex_group_size
Vertex group to control size

Type string, default “”

vertex_group_tangent
Vertex group to control tangent

Type string, default “”

vertex_group_velocity
Vertex group to control velocity

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.particle_systems`
- `ParticleSystemModifier.particle_system`
- `ParticleSystems.active`
- `PointDensity.particle_system`
- `SmokeFlowSettings.particle_system`

2.4.390 ParticleSystemModifier(Modifier)

base classes — `bpy_struct, Modifier`

```
class bpy.types.ParticleSystemModifier(Modifier)
    Particle system simulation modifier

    particle_system
        Particle System that this modifier controls

    Type ParticleSystem, (readonly, never None)
```

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.391 ParticleSystems(bpy_struct)

base class — bpy_struct

class bpy.types.ParticleSystems (*bpy_struct*)

Collection of particle systems

active

Active particle system being displayed

Type ParticleSystem, (readonly)

active_index

Index of active particle system slot

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- [Object.particle_systems](#)

2.4.392 ParticleTarget(bpy_struct)

base class — `bpy_struct`

class `bpy.types.ParticleTarget(bpy_struct)`

Target particle system

alliance

Type enum in ['FRIEND', 'NEUTRAL', 'ENEMY'], default 'NEUTRAL'

duration

Type float in [0, 30000], default 0.0

is_valid

Keyed particles target is valid

Type boolean, default False

name

Particle target name

Type string, default "", (readonly)

object

The object that has the target particle system (empty if same object)

Type `Object`

system

The index of particle system on the target object

Type int in [1, inf], default 0

time

Type float in [0, 30000], default 0.0

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ParticleSystem.active_particle_target
- ParticleSystem.targets

2.4.393 PivotConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.PivotConstraint(Constraint)

Rotate around a different point

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

offset

Offset of pivot from target (when set), or from owner's location (when Fixed Position is off), or the absolute pivot point

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_range

Rotation range on which pivoting should occur

Type enum in ['ALWAYS_ACTIVE', 'NX', 'NY', 'NZ', 'X', 'Y', 'Z'], default 'NX'

subtarget

Type string, default ""

target

Target Object, defining the position of the pivot when defined

Type Object

use_relative_location

Offset will be an absolute point in space instead of relative to the target

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence

- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.394 PluginSequence(EffectSequence)

base classes — bpy_struct, Sequence, EffectSequence

class bpy.types.PluginSequence (EffectSequence)
Sequence strip applying an effect, loaded from an external plugin
filename
Type string, default "", (readonly)

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle

- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem

- `Sequence.swap`

2.4.395 `PluginTexture(Texture)`

base classes — `bpy_struct, ID, Texture`

class `bpy.types.PluginTexture(Texture)`

External plugin texture

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.396 PointCache(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.PointCache` (`bpy_struct`)

Point cache for physics simulations

compression

Compression method to be used

Type enum in ['NO', 'LIGHT', 'HEAVY'], default 'NO'

filepath

Cache file path

Type string, default “”

frame_end

Frame on which the simulation stops

Type int in [1, 300000], default 0

frame_start

Frame on which the simulation starts

Type int in [1, 300000], default 0

frame_step

Number of frames between cached frames

Type int in [1, 20], default 0

frames_skipped

Type boolean, default False, (readonly)

index

Index number of cache files

Type int in [-1, 100], default 0

info

Info on current cache status

Type string, default “”, (readonly)

is_baked

Type boolean, default False, (readonly)

is_baking

Type boolean, default False, (readonly)

is_outdated

Type boolean, default False, (readonly)

name

Cache name

Type string, default “”

point_caches

Point cache list

Type `PointCaches bpy_prop_collection of PointCache`, (readonly)

use_disk_cache

Save cache files to disk (.blend file must be saved first)

Type boolean, default False

use_external

Read cache from an external location

Type boolean, default False

use_library_path

Use this files path when library linked into another file.

Type boolean, default False

use_quick_cache

Update simulation with cache steps

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- ClothModifier.point_cache
- ParticleSystem.point_cache
- PointCache.point_caches
- SmokeDomainSettings.point_cache
- SoftBodyModifier.point_cache

2.4.397 PointCaches(bpy_struct)

base class — bpy_struct

class bpy.types.PointCaches (*bpy_struct*)

Collection of point caches

active_index

Type int in [0, inf], default 0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PointCache.point_caches

2.4.398 PointDensity(bpy_struct)

base class — bpy_struct

```
class bpy.types.PointDensity(bpy_struct)
    Point density settings

    color_ramp
        Type ColorRamp, (readonly)

    color_source
        Data to derive color results from
            Type enum in ['CONSTANT', 'PARTICLE_AGE', 'PARTICLE_SPEED', 'PARTICLE_VELOCITY'], default 'CONSTANT'

    falloff
        Method of attenuating density by distance from the point
            Type enum in ['STANDARD', 'SMOOTH', 'SOFT', 'CONSTANT', 'ROOT', 'PARTICLE_AGE', 'PARTICLE_VELOCITY'], default 'STANDARD'

    falloff_curve
        Type CurveMapping, (readonly)

    falloff_soft
        Softness of the 'soft' falloff option
            Type float in [0.01, inf], default 0.0

    falloff_speed_scale
        Multiplier to bring particle speed within an acceptable range
            Type float in [0.001, 100], default 0.0

    noise_basis
        Noise formula used for turbulence
            Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN',
                          'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4',
                          'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default
                          'BLENDER_ORIGINAL'

    object
        Object to take point data from
            Type Object

    particle_cache_space
        Co-ordinate system to cache particles in
            Type enum in ['OBJECT_LOCATION', 'OBJECT_SPACE', 'WORLD_SPACE'], default
                          'OBJECT_LOCATION'

    particle_system
        Particle System to render as points
            Type ParticleSystem

    point_source
        Point data to use as renderable point density
            Type enum in ['PARTICLE_SYSTEM', 'OBJECT'], default 'PARTICLE_SYSTEM'

    radius
        Radius from the shaded sample to look for points within
            Type float in [0.001, inf], default 0.0
```

speed_scale

Multiplier to bring particle speed within an acceptable range

Type float in [0.001, 100], default 0.0

turbulence_depth

Level of detail in the added turbulent noise

Type int in [0, 30], default 0

turbulence_influence

Method for driving added turbulent noise

Type enum in ['STATIC', 'PARTICLE_VELOCITY', 'PARTICLE_AGE', 'GLOBAL_TIME'], default 'STATIC'

turbulence_scale

Scale of the added turbulent noise

Type float in [0.01, inf], default 0.0

turbulence_strength

Type float in [0.01, inf], default 0.0

use_falloff_curve

Use a custom falloff curve

Type boolean, default False

use_turbulence

Add directed noise to the density at render-time

Type boolean, default False

vertex_cache_space

Co-ordinate system to cache vertices in

Type enum in ['OBJECT_LOCATION', 'OBJECT_SPACE', 'WORLD_SPACE'], default 'OBJECT_LOCATION'

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `PointDensityTexture.point_density`

2.4.399 PointDensityTexture(Texture)

base classes — `bpy_struct, ID, Texture`

class bpy.types.PointDensityTexture (Texture)

Settings for the Point Density texture

point_density

The point density settings associated with this texture

Type `PointDensity`, (readonly)

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `Texture.animation_data`
- `Texture.intensity`
- `Texture.color_ramp`
- `Texture.contrast`
- `Texture.factor_blue`
- `Texture.factor_green`
- `Texture.factor_red`
- `Texture.node_tree`
- `Texture.saturation`
- `Texture.use_preview_alpha`
- `Texture.type`
- `Texture.use_color_ramp`
- `Texture.use_nodes`
- `Texture.users_material`
- `Texture.users_object_modifier`
- `Texture.users_material`
- `Texture.users_object_modifier`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.400 PointLamp(Lamp)

base classes — `bpy_struct, ID, Lamp`

class bpy.types.PointLamp (Lamp)

Omnidirectional point lamp

falloff_curve

Custom Lamp Falloff Curve

Type `CurveMapping, (readonly)`

falloff_type

Intensity Decay with distance

Type `enum in ['CONSTANT', 'INVERSE_LINEAR', 'INVERSE_SQUARE', 'CUSTOM_CURVE', 'LINEAR_QUADRATIC_WEIGHTED'], default 'CONSTANT'`

linear_attenuation

Linear distance attenuation

Type `float in [0, 1], default 0.0`

quadratic_attenuation

Quadratic distance attenuation

Type `float in [0, 1], default 0.0`

shadow_adaptive_threshold

Threshold for Adaptive Sampling (Raytraced shadows)

Type `float in [0, 1], default 0.0`

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method

Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method

Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples

Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size

Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

use_only_shadow

Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer

Causes only objects on the same layer to cast shadows

Type boolean, default False

use_sphere

Sets light intensity to zero beyond lamp distance

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.401 PointerProperty(Property)

base classes — `bpy_struct, Property`

class bpy.types.PointerProperty(*Property*)
RNA pointer property to point to another RNA struct
fixed_type
Fixed pointer type, empty if variable type
Type `Struct`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Property.name`
- `Property.srna`
- `Property.description`
- `Property.is_enum_flag`
- `Property.is_hidden`
- `Property.identifier`
- `Property.is_never_none`
- `Property.is_readonly`
- `Property.is_registered`
- `Property.is_registered_optional`
- `Property.is_required`
- `Property.is_output`
- `Property.is_runtime`
- `Property.is_skip_save`

- `Property.subtype`
- `Property.type`
- `Property.unit`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.402 Pose(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.Pose (`bpy_struct`)

A collection of pose channels, including settings for animating bones

animation_visualisation

Animation data for this datablock

Type `AnimViz`, (readonly, never None)

bone_groups

Groups of the bones

Type `BoneGroups` `bpy_prop_collection` of `BoneGroup`, (readonly)

bones

Individual pose bones for the armature

Type `bpy_prop_collection` of `PoseBone`, (readonly)

ik_param

Parameters for IK solver

Type `IKParam`, (readonly)

ik_solver

Selection of IK solver for IK chain, current choice is 0 for Legacy, 1 for iTaSC

Type enum in ['LEGACY', 'ITASC'], default 'LEGACY'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.pose

2.4.403 PoseBone(bpy_struct)

base class — bpy_struct

class bpy.types.PoseBone (*bpy_struct*)
Channel defining pose data for a bone in a Pose

bone
Bone associated with this PoseBone

Type Bone, (readonly, never None)

bone_group
Bone Group this pose channel belongs to

Type BoneGroup

bone_group_index
Bone Group this pose channel belongs to (0=no group)

Type int in [-32768, 32767], default 0

child
Child of this pose bone

Type PoseBone, (readonly)

constraints
Constraints that act on this PoseChannel

Type `PoseBoneConstraints bpy_prop_collection of Constraint`, (readonly)

custom_shape
Object that defines custom draw type for this bone

Type `Object`

custom_shape_transform
Bone that defines the display transform of this custom shape

Type `PoseBone`

head
Location of head of the channel's bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

ik_linear_weight
Weight of scale constraint for IK

Type float in [0, 1], default 0.0

ik_max_x
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_max_y
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_max_z
Maximum angles for IK Limit

Type float in [0, 3.14159], default 0.0

ik_min_x
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_min_y
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_min_z
Minimum angles for IK Limit

Type float in [-3.14159, 0], default 0.0

ik_rotation_weight
Weight of rotation constraint for IK

Type float in [0, 1], default 0.0

ik_stiffness_x
IK stiffness around the X axis

Type float in [0, 0.99], default 0.0

ik_stiffness_y
IK stiffness around the Y axis

Type float in [0, 0.99], default 0.0

ik_stiffness_z

IK stiffness around the Z axis

Type float in [0, 0.99], default 0.0

ik_stretch

Allow scaling of the bone for IK

Type float in [0, 1], default 0.0

is_in_ik_chain

Is part of an IK chain

Type boolean, default False, (readonly)

location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lock_ik_x

Disallow movement around the X axis

Type boolean, default False

lock_ik_y

Disallow movement around the Y axis

Type boolean, default False

lock_ik_z

Disallow movement around the Z axis

Type boolean, default False

lock_location

Lock editing of location in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation

Lock editing of rotation in the interface

Type boolean array of 3 items, default (False, False, False)

lock_rotation_w

Lock editing of ‘angle’ component of four-component rotations in the interface

Type boolean, default False

lock_rotations_4d

Lock editing of four component rotations by components (instead of as Eulers)

Type boolean, default False

lock_scale

Lock editing of scale in the interface

Type boolean array of 3 items, default (False, False, False)

matrix

Final 4x4 matrix after constraints and drivers are applied (object space)

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

matrix_basis

Provides an alternative access to loc/scale/rotation relative to the parent and own rest bone.

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

matrix_channel

4x4 matrix, before constraints

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

motion_path

Motion Path for this element

Type [MotionPath](#), (readonly)

name

Type string, default “”

parent

Parent of this pose bone

Type [PoseBone](#), (readonly)

rotation_axis_angle

Angle of Rotation for Axis-Angle rotation representation

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 1.0, 0.0)

rotation_euler

Rotation in Eulers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation_mode

Type enum in ['QUATERNION', 'XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX', 'AXIS_ANGLE'], default 'QUATERNION'

rotation_quaternion

Rotation in Quaternions

Type float array of 4 items in [-inf, inf], default (1.0, 0.0, 0.0, 0.0)

scale

Type float array of 3 items in [-inf, inf], default (1.0, 1.0, 1.0)

tail

Location of tail of the channel's bone

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0), (readonly)

use_ik_limit_x

Limit movement around the X axis

Type boolean, default False

use_ik_limit_y

Limit movement around the Y axis

Type boolean, default False

use_ik_limit_z

Limit movement around the Z axis

Type boolean, default False

use_ik_linear_control

Apply channel size as IK constraint if stretching is enabled

Type boolean, default False

use_ik_rotation_control

Apply channel rotation as IK constraint

Type boolean, default False

basename

The name of this bone before any ‘.’ character (readonly)

center

The midpoint between the head and the tail. (readonly)

children

A list of all the bones children. (readonly)

children_recursive

a list of all children from this bone. (readonly)

children_recursive_basename

Returns a chain of children with the same base name as this bone Only direct chains are supported, forks caused by multiple children with matching basenames will terminate the function and not be returned. (readonly)

length

The distance from head to tail, when set the head is moved to fit the length.

parent_recursive

A list of parents, starting with the immediate parent (readonly)

vector

The direction this bone is pointing. Utility function for (tail - head) (readonly)

x_axis

Vector pointing down the x-axis of the bone. (readonly)

y_axis

Vector pointing down the x-axis of the bone. (readonly)

z_axis

Vector pointing down the x-axis of the bone. (readonly)

evaluate_envelope (point)

Calculate bone envelope at given point.

Parameters **point** (*float array of 3 items in [-inf, inf]*) – Point, Position in 3d space to evaluate

Returns Factor, Envelope factor

Return type float in [-inf, inf]

parent_index (parent_test)

The same as ‘bone in other_bone.parent_recursive’ but saved generating a list.

translate (vec)

Utility function to add *vec* to the head and tail of this bone.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Pose.bones`
- `PoseBone.child`
- `PoseBone.custom_shape_transform`
- `PoseBone.parent`

2.4.404 PoseBoneConstraints(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.PoseBoneConstraints` (`bpy_struct`)

Collection of pose bone constraints

active

Active PoseChannel constraint

Type `Constraint`

new (`type`)

Add a constraint to this object

Parameters `type` (enum in [`'COPY_LOCATION'`, `'COPY_ROTATION'`,
`'COPY_SCALE'`, `'COPY_TRANSFORMS'`, `'LIMIT_DISTANCE'`, `'LIMIT_LOCATION'`,
`'LIMIT_ROTATION'`, `'LIMIT_SCALE'`, `'MAINTAIN_VOLUME'`, `'TRANSFORM'`,
`'CLAMP_TO'`, `'DAMPED_TRACK'`, `'IK'`, `'LOCKED_TRACK'`, `'SPLINE_IK'`,
`'STRETCH_TO'`, `'TRACK_TO'`, `'ACTION'`, `'CHILD_OF'`, `'FLOOR'`, `'FOLLOW_PATH'`,
`'PIVOT'`, `'RIGID_BODY_JOINT'`, `'SCRIPT'`, `'SHRINKWRAP'`]) – Constraint type to add.

Returns New constraint.

Return type `Constraint`

remove (`constraint`)

Remove a constraint from this object.

Parameters `constraint` (`Constraint`, (never None)) – Removed constraint.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- PoseBone.constraints

2.4.405 Property(bpy_struct)

base class — bpy_struct
subclasses — PointerProperty, EnumProperty, IntProperty, CollectionProperty, BooleanProperty, FloatProperty, StringProperty

class bpy.types.Property(bpy_struct)
RNA property definition

description
Description of the property for tooltips

Type string, default "", (readonly)

identifier
Unique name used in the code and scripting

Type string, default "", (readonly)

is_enum_flag
True when multiple enums

Type boolean, default False, (readonly)

is_hidden
True when the property is hidden

Type boolean, default False, (readonly)

is_never_none

True when this value can't be set to None

Type boolean, default False, (readonly)

is_output

True when this property is an output value from an RNA function

Type boolean, default False, (readonly)

is_READONLY

Property is editable through RNA

Type boolean, default False, (readonly)

is_registered

Property is registered as part of type registration

Type boolean, default False, (readonly)

is_registered_optional

Property is optionally registered as part of type registration

Type boolean, default False, (readonly)

is_required

False when this property is an optional argument in an RNA function

Type boolean, default False, (readonly)

is_runtime

Property has been dynamically created at runtime

Type boolean, default False, (readonly)

is_skip_save

True when the property is not saved in presets

Type boolean, default False, (readonly)

name

Human readable name

Type string, default "", (readonly)

srna

Struct definition used for properties assigned to this item

Type Struct, (readonly)

subtype

Semantic interpretation of the property

Type enum in ['NONE', 'FILE_PATH', 'DIRECTORY_PATH', 'UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'COLOR', 'TRANSLATION', 'DIRECTION', 'MATRIX', 'EULER', 'QUATERNION', 'XYZ', 'COLOR_GAMMA', 'COORDINATES', 'LAYER', 'LAYER_MEMBERSHIP'], default 'NONE', (readonly)

type

Data type of the property

Type enum in ['BOOLEAN', 'INT', 'FLOAT', 'STRING', 'ENUM', 'POINTER', 'COLLECTION'], default 'BOOLEAN', (readonly)

unit

Type of units for this property

Type enum in ['NONE', 'LENGTH', 'AREA', 'VOLUME', 'ROTATION', 'TIME', 'VELOCITY', 'ACCELERATION'], default 'NONE', (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Function.parameters
- Struct.properties

2.4.406 PropertyActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.PropertyActuator(Actuator)

Actuator to handle properties

mode

Type enum in ['ASSIGN', 'ADD', 'COPY', 'TOGGLE'], default 'ASSIGN'

object

Copy from this Object

Type Object

object_property

Copy this property

Type string, default ""

property

The name of the property

Type string, default “”

value

The name of the property or the value to use (use “” around strings)

Type string, default “”

Inherited Properties

- [bpy_struct.id_data](#)
- [Actuator.name](#)
- [Actuator.show_expanded](#)
- [Actuator.pin](#)
- [Actuator.type](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [Actuator.link](#)
- [Actuator.unlink](#)

2.4.407 PropertyGroup(bpy_struct)

Custom Properties

PropertyGroups are the base class for dynamically defined sets of properties.

They can be used to extend existing blender data with your own types which can be animated, accessed from the user interface and from python.

Note: The values assigned to blender data are saved to disk but the class definitions are not, this means whenever you load blender the class needs to be registered too.

This is best done by creating an addon which loads on startup and registers your properties.

Note: PropertyGroups must be registered before assigning them to blender data.

See Also:

Property types used in class declarations are all in `bpy.props`

```
import bpy
```

```
class MyPropertyGroup(bpy.types.PropertyGroup):
    custom_1 = bpy.props.FloatProperty(name="My Float")
    custom_2 = bpy.props.IntProperty(name="My Int")

bpy.utils.register_class(MyPropertyGroup)

bpy.types.Object.my_prop_grp = bpy.props.PointerProperty(type=MyPropertyGroup)

# test this worked
bpy.data.objects[0].my_prop_grp.custom_1 = 22.0

base class — bpy_struct
subclasses — OperatorFileListElement, OperatorMousePath, OperatorStrokeElement
class bpy.types.PropertyGroup(bpy_struct)
    Group of ID properties

    name
        Unique name used in the code and scripting
        Type string, default ""


```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `PropertyGroupItem.collection`
- `PropertyGroupItem.group`
- `PropertyGroupItem.idp_array`

2.4.408 `PropertyGroupItem(bpy_struct)`

base class — `bpy_struct`

```
class bpy.types.PropertyGroupItem(bpy_struct)
    Property that stores arbitrary, user defined properties

    collection
        Type bpy_prop_collection of PropertyGroup, (readonly)

    double
        Type float in [-inf, inf], default 0.0

    double_array
        Type float array of 1 items in [-inf, inf], default (0.0)

    float
        Type float in [-inf, inf], default 0.0

    float_array
        Type float array of 1 items in [-inf, inf], default (0.0)

    group
        Type PropertyGroup, (readonly)

    idp_array
        Type bpy_prop_collection of PropertyGroup, (readonly)

    int
        Type int in [-inf, inf], default 0

    int_array
        Type int array of 1 items in [-inf, inf], default (0,)

    string
        Type string, default ""
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.409 PropertySensor(Sensor)

base classes — `bpy_struct, Sensor`

class bpy.types.PropertySensor (Sensor)

Sensor to detect values and changes in values of properties

evaluation_type

Type of property evaluation

Type enum in ['PROPEQUAL', 'PROPNEQUAL', 'PROPINTERVAL', 'PROPCHANGED'],
default 'PROPEQUAL'

property

Type string, default ""

value

Check for this value in types in Equal or Not Equal types

Type string, default ""

value_max

Specify maximum value in Interval type

Type string, default ""

value_min

Specify minimum value in Interval type

Type string, default ""

Inherited Properties

- `bpy_struct.id_data`
- `Sensor.name`
- `Sensor.show_expanded`
- `Sensor.frequency`

- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.410 PythonConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.PythonConstraint (*Constraint*)
Uses Python script for constraint evaluation

has_script_error
The linked Python script has thrown an error
Type boolean, default False, (readonly)

target_count
Usually only 1-3 are needed
Type int in [-inf, inf], default 0

targets
Target Objects
Type bpy_prop_collection of ConstraintTarget, (readonly)

text
The text object that contains the Python script
Type Text

use_targets

Use the targets indicated in the constraint panel

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.411 PythonController(Controller)

base classes — bpy_struct, Controller

class bpy.types.PythonController(*Controller*)
Controller executing a python script

mode

Python script type (textblock or module - faster)

Type enum in ['SCRIPT', 'MODULE'], default 'SCRIPT'

module

Module name and function to run e.g. “someModule.main”. Internal texts and external python files can be used

Type string, default “”

text

Text datablock with the python script

Type Text

use_debug

Continuously reload the module from disk for editing external modules without restarting

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.412 RGBANodeSocket(NodeSocket)

base classes — bpy_struct, NodeSocket

class bpy.types.RGBANodeSocket (*NodeSocket*)

Input or output socket of a node

default_value

Default value of the socket when no link is attached

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`
- `NodeSocket.name`
- `NodeSocket.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.413 RadarSensor(Sensor)

base classes — `bpy_struct, Sensor`

class bpy.types.RadarSensor (Sensor)

Sensor to detect objects in a cone shaped radar emanating from the current object

angle

Opening angle of the radar cone (in degrees)

Type float in [0, 179.9], default 0.0

axis

Specify along which axis the radar cone is cast

Type enum in ['XAXIS', 'YAXIS', 'ZAXIS', 'NEGXAXIS', 'NEYGYAXIS', 'NEGZAXIS'], default 'XAXIS'

distance

Depth of the radar cone

Type float in [0, 10000], default 0.0

property

Only look for Objects with this property (blank = all objects)

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.414 RandomActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.**RandomActuator** (Actuator)
Actuator to ..

chance

Pick a number between 0 and 1. Success if you stay below this value

Type float in [0, 1], default 0.0

distribution

Choose the type of distribution

Type enum in ['BOOL_CONSTANT', 'BOOL_UNIFORM', 'BOOL_BERNOULLI',
'INT_CONSTANT', 'INT_UNIFORM', 'INT_POISSON', 'FLOAT_CONSTANT',
'FLOAT_UNIFORM', 'FLOAT_NORMAL', 'FLOAT_NEGATIVE_EXPONENTIAL'],
default 'BOOL_CONSTANT'

float_max

Choose a number from a range. Upper boundary of the range

Type float in [-1000, 1000], default 0.0

float_mean

A normal distribution. Mean of the distribution

Type float in [-1000, 1000], default 0.0

float_min

Choose a number from a range. Lower boundary of the range

Type float in [-1000, 1000], default 0.0

float_value

Always return this number

Type float in [0, 1], default 0.0

half_life_time

Negative exponential dropoff

Type float in [-1000, 1000], default 0.0

int_max

Choose a number from a range. Upper boundary of the range

Type int in [-1000, 1000], default 0

int_mean

Expected mean value of the distribution

Type float in [0.01, 100], default 0.0

int_min

Choose a number from a range. Lower boundary of the range

Type int in [-1000, 1000], default 0

int_value

Always return this number

Type int in [-inf, inf], default 0

property

Assign the random value to this property

Type string, default “”

seed

Initial seed of the random generator. Use Python for more freedom (choose 0 for not random)

Type int in [0, 300000], default 0

standard_derivation

A normal distribution. Standard deviation of the distribution

Type float in [-1000, 1000], default 0.0

use_always_true

Always false or always true

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.415 RandomSensor(Sensor)

base classes — `bpy_struct, Sensor`

class bpy.types.RandomSensor (Sensor)

Sensor to send random events

seed

Initial seed of the generator. (Choose 0 for not random)

Type int in [0, 1000], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Sensor.name`
- `Sensor.show_expanded`
- `Sensor.frequency`
- `Sensor.invert`
- `Sensor.use_level`
- `Sensor.pin`
- `Sensor.use_pulse_false_level`
- `Sensor.use_pulse_true_level`

- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.416 RaySensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.RaySensor (Sensor)

Sensor to detect intersections with a ray emanating from the current object

axis

Specify along which axis the ray is cast

Type enum in ['XAXIS', 'YAXIS', 'ZAXIS', 'NEGXAXIS', 'NEYAXIS', 'NEGZAXIS'],
default 'YAXIS'

material

Only look for Objects with this material (blank = all objects)

Type string, default “”

property

Only look for Objects with this property (blank = all objects)

Type string, default “”

range

Sense objects no farther than this distance

Type float in [0.01, 10000], default 0.0

ray_type

Toggle collision on material or property

Type enum in ['PROPERTY', 'MATERIAL'], default 'PROPERTY'

use_x_ray

Toggle X-Ray option (see through objects that don't have the property)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap
- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.417 Region(bpy_struct)

base class — bpy_struct

class bpy.types.Region(*bpy_struct*)
Region in a subdivided screen area

height

Region height

Type int in [0, 32767], default 0, (readonly)

id

Unique ID for this region

Type int in [-32768, 32767], default 0, (readonly)

type

Type of this region

Type enum in ['WINDOW', 'HEADER', 'CHANNELS', 'TEMPORARY', 'UI', 'TOOLS', 'TOOL_PROPS', 'PREVIEW'], default 'WINDOW', (readonly)

width

Region width

Type int in [0, 32767], default 0, (readonly)

tag_redraw()

tag_redraw

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Area.regions
- Context.region

2.4.418 RegionView3D(bpy_struct)

base class — bpy_struct

class bpy.types.RegionView3D (*bpy_struct*)

3D View region data

is_perspective

Type boolean, default False

lock_rotation

Lock view rotation in side views

Type boolean, default False

perspective_matrix

Current perspective matrix of the 3D region

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0), (readonly)

show_sync_view

Sync view position between side views

Type boolean, default False

use_box_clip

Clip objects based on what's visible in other side views

Type boolean, default False

view_distance

Distance to the view location

Type float in [0, inf], default 0.0

view_location

View pivot location

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_matrix

Current view matrix of the 3D region

Type float array of 16 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

view_perspective

View Perspective

Type enum in ['PERSP', 'ORTHO', 'CAMERA'], default 'ORTHO'

view_rotation

Rotation in quaternions (keep normalized)

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.region_data
- SpaceView3D.region_3d
- SpaceView3D.region_quadview

2.4.419 RenderEngine(bpy_struct)

Simple Render Engine

```
import bpy

class CustomRenderEngine(bpy.types.RenderEngine):
    # These three members are used by blender to set up the
    # RenderEngine; define its internal name, visible name and capabilities.
    bl_idname = 'custom_renderer'
    bl_label = 'Flat Color Renderer'
    bl_use_preview = True

    # This is the only method called by blender, in this example
    # we use it to detect preview rendering and call the implementation
    # in another method.
    def render(self, scene):
        scale = scene.render.resolution_percentage / 100.0
        self.size_x = int(scene.render.resolution_x * scale)
        self.size_y = int(scene.render.resolution_y * scale)

        if scene.name == 'preview':
            self.render_preview(scene)
        else:
            self.render_scene(scene)

    # In this example, we fill the preview renders with a flat green color.
    def render_preview(self, scene):
        pixel_count = self.size_x * self.size_y

        # The framebuffer is defined as a list of pixels, each pixel
        # itself being a list of R,G,B,A values
        green_rect = [[0.0, 1.0, 0.0, 1.0]] * pixel_count

        # Here we write the pixel values to the RenderResult
        result = self.begin_result(0, 0, self.size_x, self.size_y)
        layer = result.layers[0]
        layer.rect = green_rect
        self.end_result(result)
```

```
# In this example, we fill the full renders with a flat blue color.
def render_scene(self, scene):
    pixel_count = self.size_x * self.size_y

    # The framebuffer is defined as a list of pixels, each pixel
    # itself being a list of R,G,B,A values
    blue_rect = [[0.0, 0.0, 1.0, 1.0]] * pixel_count

    # Here we write the pixel values to the RenderResult
    result = self.begin_result(0, 0, self.size_x, self.size_y)
    layer = result.layers[0]
    layer.rect = blue_rect
    self.end_result(result)

# Register the RenderEngine
bpy.utils.register_class(CustomRenderEngine)

# RenderEngines also need to tell UI Panels that they are compatible
# Otherwise most of the UI will be empty when the engine is selected.
# In this example, we need to see the main render image button and
# the material preview panel.
import properties_render
properties_render.RENDER_PT_render.COMPAT_ENGINES.add('custom_renderer')
del properties_render

import properties_material
properties_material.MATERIAL_PT_preview.COMPAT_ENGINES.add('custom_renderer')
del properties_material

base class — bpy_struct

class bpy.types.RenderEngine(bpy_struct)
    Render engine

    bl_idname
        Type string, default ""

    bl_label
        Type string, default ""

    bl_use_postprocess
        Type boolean, default False

    bl_use_preview
        Type boolean, default False

    render(scene=None)
        Render scene into an image.
```

begin_result (x, y, w, h)
begin_result

Parameters

- **x** (int in [0, inf]) – X
- **y** (int in [0, inf]) – Y

- **w** (*int in [0, inf]*) – Width
- **h** (*int in [0, inf]*) – Height

Returns Result

Return type RenderResult

update_result (*result*)
update_result

Parameters **result** (RenderResult) – Result

end_result (*result*)
end_result

Parameters **result** (RenderResult) – Result

test_break ()
test_break

Returns Break

Return type boolean

update_stats (*stats, info*)
update_stats

Parameters

- **stats** (*string*) – Stats
- **info** (*string*) – Info

report (*type, message*)
report

Parameters

- **type** (*enum set in {‘DEBUG’, ‘INFO’, ‘OPERATOR’, ‘WARNING’, ‘ERROR’, ‘ERROR_INVALID_INPUT’, ‘ERROR_INVALID_CONTEXT’, ‘ERROR_OUT_OF_MEMORY’}*) – Type
- **message** (*string*) – Report Message

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.420 RenderLayer(bpy_struct)

base class — bpy_struct

class bpy.types.RenderLayer (bpy_struct)

exclude_ambient_occlusion

Exclude AO pass from combined

Type boolean, default False, (readonly)

exclude_emit

Exclude emission pass from combined

Type boolean, default False, (readonly)

exclude_environment

Exclude environment pass from combined

Type boolean, default False, (readonly)

exclude_indirect

Exclude indirect pass from combined

Type boolean, default False, (readonly)

exclude_reflection

Exclude raytraced reflection pass from combined

Type boolean, default False, (readonly)

exclude_refraction

Exclude raytraced refraction pass from combined

Type boolean, default False, (readonly)

exclude_shadow

Exclude shadow pass from combined

Type boolean, default False, (readonly)

exclude_specular

Exclude specular pass from combined

Type boolean, default False, (readonly)

invert_zmask

For Zmask, only render what is behind solid z values instead of in front

Type boolean, default False, (readonly)

layers

Scene layers included in this render layer

Type boolean array of 20 items, default (False, False, False), (readonly)

layers_zmask

Zmask scene layers

Type boolean array of 20 items, default (False, False, False), (readonly)

light_override

Group to override all other lights in this render layer

Type [Group](#), (readonly)

material_override

Material to override all other materials in this render layer

Type [Material](#), (readonly)

name

Render layer name

Type string, default "", (readonly)

passes

Type [bpy_prop_collection](#) of [RenderPass](#), (readonly)

rect

Type float in [-inf, inf], default 0.0

use

Disable or enable the render layer

Type boolean, default False, (readonly)

use_all_z

Fill in Z values for solid faces in invisible layers, for masking

Type boolean, default False, (readonly)

use_edge_enhance

Render Edge-enhance in this Layer (only works for Solid faces)

Type boolean, default False, (readonly)

use_halo

Render Halos in this Layer (on top of Solid)

Type boolean, default False, (readonly)

use_pass_ambient_occlusion

Deliver AO pass

Type boolean, default False, (readonly)

use_pass_color

Deliver shade-less color pass

Type boolean, default False, (readonly)

use_pass_combined

Deliver full combined RGBA buffer

Type boolean, default False, (readonly)

use_pass_diffuse

Deliver diffuse pass

Type boolean, default False, (readonly)

use_pass_emit
Deliver emission pass

Type boolean, default False, (readonly)

use_pass_environment
Deliver environment lighting pass

Type boolean, default False, (readonly)

use_pass_indirect
Deliver indirect lighting pass

Type boolean, default False, (readonly)

use_pass_mist
Deliver mist factor pass (0.0-1.0)

Type boolean, default False, (readonly)

use_pass_normal
Deliver normal pass

Type boolean, default False, (readonly)

use_pass_object_index
Deliver object index pass

Type boolean, default False, (readonly)

use_pass_reflection
Deliver raytraced reflection pass

Type boolean, default False, (readonly)

use_pass_refraction
Deliver raytraced refraction pass

Type boolean, default False, (readonly)

use_pass_shadow
Deliver shadow pass

Type boolean, default False, (readonly)

use_pass_specular
Deliver specular pass

Type boolean, default False, (readonly)

use_pass_uv
Deliver texture UV pass

Type boolean, default False, (readonly)

use_pass_vector
Deliver speed vector pass

Type boolean, default False, (readonly)

use_pass_z
Deliver Z values pass

Type boolean, default False, (readonly)

use_sky

Render Sky in this Layer

Type boolean, default False, (readonly)

use_solid

Render Solid faces in this Layer

Type boolean, default False, (readonly)

use_strand

Render Strands in this Layer

Type boolean, default False, (readonly)

use_zmask

Only render what's in front of the solid z values

Type boolean, default False, (readonly)

use_ztransp

Render Z-Transparent faces in this Layer (On top of Solid and Halos)

Type boolean, default False, (readonly)

load_from_file (*filename, x=0, y=0*)

Copies the pixels of this renderlayer from an image file.

Parameters

- **filename** (*string*) – Filename, Filename to load into this render tile, must be no smaller than the renderlayer
- **x** (*int in [0, inf], (optional)*) – Offset X, Offset the position to copy from if the image is larger than the render layer
- **y** (*int in [0, inf], (optional)*) – Offset Y, Offset the position to copy from if the image is larger than the render layer

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `RenderResult.layers`

2.4.421 RenderLayers(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.RenderLayers (bpy_struct)`

Collection of render layers

active

Active Render Layer

Type `SceneRenderLayer`

active_index

Active index in render layer array

Type int in [-32768, 32767], default 0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `RenderSettings.layers`

2.4.422 RenderPass(bpy_struct)

base class — `bpy_struct`

`class bpy.types.RenderPass (bpy_struct)`

`channel_id`

Type string, default "", (readonly)

`channels`

Type int in [-inf, inf], default 0, (readonly)

`name`

Type string, default "", (readonly)

`rect`

Type float in [-inf, inf], default 0.0

`type`

Type enum in ['COMBINED', 'Z', 'COLOR', 'DIFFUSE', 'SPECULAR', 'SHADOW', 'AO', 'REFLECTION', 'NORMAL', 'VECTOR', 'REFRACTION', 'OBJECT_INDEX', 'UV', 'MIST', 'EMIT', 'ENVIRONMENT'], default 'COMBINED', (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `RenderLayer.passes`

2.4.423 RenderResult(bpy_struct)

base class — `bpy_struct`

class `bpy.types.RenderResult(bpy_struct)`

Result of rendering, including all layers and passes

layers

Type `bpy_prop_collection of RenderLayer, (readonly)`

resolution_x

Type int in [-inf, inf], default 0, (readonly)

resolution_y

Type int in [-inf, inf], default 0, (readonly)

load_from_file (`filename`)

Copies the pixels of this render result from an image file.

Parameters `filename (string)` – File Name, Filename to load into this render tile, must be no smaller than the render result

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `RenderEngine.begin_result`
- `RenderEngine.end_result`
- `RenderEngine.update_result`

2.4.424 RenderSettings(bpy_struct)

base class — `bpy_struct`

class bpy.types.RenderSettings (bpy_struct)

Rendering settings for a Scene datablock

alpha_mode

Representation of alpha information in the RGBA pixels

Type enum in ['SKY', 'PREMUL', 'STRAIGHT'], default 'SKY'

antialiasing_samples

Amount of anti-aliasing samples per pixel

Type enum in ['5', '8', '11', '16'], default '5'

bake_aa_mode

Type enum in ['5', '8', '11', '16'], default '5'

bake_bias

Bias towards faces further away from the object (in blender units)

Type float in [0, 1000], default 0.0

bake_distance

Maximum distance from active object to other object (in blender units)

Type float in [0, 1000], default 0.0

bake_margin

Amount of pixels to extend the baked result with, as post process filter

Type int in [0, 32], default 0

bake_normal_space

Choose normal space for baking

Type enum in ['CAMERA', 'WORLD', 'OBJECT', 'TANGENT'], default 'CAMERA'

bake_quad_split

Choose the method used to split a quad into 2 triangles for baking

Type enum in ['AUTO', 'FIXED', 'FIXED_ALT'], default 'AUTO'

bake_type

Choose shading information to bake into the image

Type enum in ['FULL', 'AO', 'SHADOW', 'NORMALS', 'TEXTURE', 'DISPLACEMENT', 'EMIT', 'ALPHA', 'MIRROR_INTENSITY', 'MIRROR_COLOR', 'SPEC_INTENSITY', 'SPEC_COLOR'], default 'FULL'

border_max_x

Sets maximum X value for the render border

Type float in [0, 1], default 0.0

border_max_y

Sets maximum Y value for the render border

Type float in [0, 1], default 0.0

border_min_x

Sets minimum X value to for the render border

Type float in [0, 1], default 0.0

border_min_y
Sets minimum Y value for the render border

Type float in [0, 1], default 0.0

cineon_black
Log conversion reference blackpoint

Type int in [0, 1024], default 0

cineon_gamma
Log conversion gamma

Type float in [0, 10], default 0.0

cineon_white
Log conversion reference whitepoint

Type int in [0, 1024], default 0

color_mode
Choose BW for saving greyscale images, RGB for saving red, green and blue channels, AND RGBA for saving red, green, blue + alpha channels

Type enum in ['BW', 'RGB', 'RGBA'], default 'BW'

display_mode
Select where rendered images will be displayed

Type enum in ['SCREEN', 'AREA', 'WINDOW', 'NONE'], default 'SCREEN'

dither_intensity
Amount of dithering noise added to the rendered image to break up banding

Type float in [0, 2], default 0.0

edge_color
Edge color

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_threshold
Threshold for drawing outlines on geometry edges

Type int in [0, 255], default 0

engine
Engine to use for rendering

Type enum in ['BLENDER_RENDER'], default 'BLENDER_RENDER'

field_order
Order of video fields. Select which lines get rendered first, to create smooth motion for TV output

Type enum in ['EVEN_FIRST', 'ODD_FIRST'], default 'EVEN_FIRST'

file_extension
The file extension used for saving renders

Type string, default "", (readonly)

file_format
File format to save the rendered images as

Type enum in ['BMP', 'IRIS', 'PNG', 'JPEG', 'TARGA', 'TARGA_RAW', 'AVI_JPEG', 'AVI_RAW', 'FRAMESERVER'], default 'TARGA'

file_quality
Quality of JPEG images, AVI Jpeg and SGI movies, Compression for PNG's
Type int in [0, 100], default 0

filepath
Directory/name to save animations, # characters defines the position and length of frame numbers
Type string, default ""

filter_size
Pixel width over which the reconstruction filter combines samples
Type float in [0.5, 1.5], default 0.0

fps
Framerate, expressed in frames per second
Type int in [1, 120], default 0

fps_base
Framerate base
Type float in [0.1, 120], default 0.0

frame_map_new
Specify how many frames the Map Old will last
Type int in [1, 900], default 0

frame_map_old
Specify old mapping value in frames
Type int in [1, 900], default 0

has_multiple_engines
More than one rendering engine is available
Type boolean, default False, (readonly)

is_movie_format
When true the format is a movie
Type boolean, default False, (readonly)

layers
Type RenderLayers bpy_prop_collection of SceneRenderLayer, (readonly)

motion_blur_samples
Number of scene samples to take with motion blur
Type int in [1, 32], default 0

motion_blur_shutter
Time taken in frames between shutter open and close
Type float in [0.01, 10], default 0.0

octree_resolution
Resolution of raytrace accelerator. Use higher resolutions for larger scenes
Type enum in ['64', '128', '256', '512'], default '64'

parts_x

Number of horizontal tiles to use while rendering

Type int in [1, 512], default 0

parts_y

Number of vertical tiles to use while rendering

Type int in [1, 512], default 0

pixel_aspect_x

Horizontal aspect ratio - for anamorphic or non-square pixel output

Type float in [1, 200], default 0.0

pixel_aspect_y

Vertical aspect ratio - for anamorphic or non-square pixel output

Type float in [1, 200], default 0.0

pixel_filter_type

Reconstruction filter used for combining anti-aliasing samples

Type enum in ['BOX', 'TENT', 'QUADRATIC', 'CUBIC', 'CATMULLROM', 'GAUSSIAN', 'MITCHELL'], default 'BOX'

raytrace_method

Type of raytrace accelerator structure

Type enum in ['AUTO', 'OCTREE', 'BLIBVH', 'VBVH', 'SIMD_SVBVH', 'SIMD_QBVH'], default 'AUTO'

resolution_percentage

Percentage scale for render resolution

Type int in [1, 32767], default 0

resolution_x

Number of horizontal pixels in the rendered image

Type int in [4, 10000], default 0

resolution_y

Number of vertical pixels in the rendered image

Type int in [4, 10000], default 0

sequencer_g1_preview

Method to draw in the sequencer view

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

sequencer_g1_render

Method to draw in the sequencer view

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

simplify_ao_sss

Global approximate AA and SSS quality factor

Type float in [0, 1], default 0.0

simplify_child_particles

Global child particles percentage

Type float in [0, 1], default 0.0

simplify_shadow_samples
Global maximum shadow samples

Type int in [0, 32767], default 0

simplify_subdivision
Global maximum subdivision level

Type int in [0, 32767], default 0

stamp_background
Color to use behind stamp text

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

stamp_font_size
Size of the font used when rendering stamp text

Type int in [8, 64], default 0

stamp_foreground
Color to use for stamp text

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

stamp_note_text
Custom text to appear in the stamp note

Type string, default “”

threads
Number of CPU threads to use simultaneously while rendering (for multi-core/CPU systems)

Type int in [1, 64], default 0

threads_mode
Determine the amount of render threads used

Type enum in ['AUTO', 'FIXED'], default 'AUTO'

use_antialiasing
Render and combine multiple samples per pixel to prevent jagged edges

Type boolean, default False

use_bake_antialiasing
Enables Anti-aliasing

Type boolean, default False

use_bake_clear
Clear Images before baking

Type boolean, default False

use_bake_lores_mesh
Calculate heights against unsubdivided low resolution mesh

Type boolean, default False

use_bake_multires
Bake directly from multires object

Type boolean, default False

use_bake_normalize

With displacement normalize to the distance, with ambient occlusion normalize without using material settings

Type boolean, default False

use_bake_selected_to_active

Bake shading on the surface of selected objects to the active object

Type boolean, default False

use_border

Render a user-defined border region, within the frame size. Note, this disables save_buffers and full_sample

Type boolean, default False

use_cineon_log

Convert to logarithmic color space

Type boolean, default False

use_color_management

Use linear workflow - gamma corrected imaging pipeline

Type boolean, default False

use_compositing

Process the render result through the compositing pipeline, if compositing nodes are enabled

Type boolean, default False

use_crop_to_border

Crop the rendered frame to the defined border size

Type boolean, default False

use_edge_enhance

Create a toon outline around the edges of geometry

Type boolean, default False

use_envmaps

Calculate environment maps while rendering

Type boolean, default False

use_fields

Render image to two fields per frame, for interlaced TV output

Type boolean, default False

use_fields_still

Disable the time difference between fields

Type boolean, default False

use_file_extension

Add the file format extensions to the rendered file name (eg: filename + .jpg)

Type boolean, default False

use_free_image_textures

Free all image texture from memory after render, to save memory before compositing

Type boolean, default False

use_free_unused_nodes

Free Nodes that are not used while compositing, to save memory

Type boolean, default False

use_full_sample

Save for every anti-aliasing sample the entire RenderLayer results. This solves anti-aliasing issues with compositing

Type boolean, default False

use_game_engine

Current rendering engine is a game engine

Type boolean, default False, (readonly)

use_instances

Instance support leads to effective memory reduction when using duplicates

Type boolean, default False

use_local_coords

Vertex coordinates are stored locally on each primitive. Increases memory usage, but may have impact on speed

Type boolean, default False

use_motion_blur

Use multi-sampled 3D scene motion blur

Type boolean, default False

use_overwrite

Overwrite existing files while rendering

Type boolean, default False

use_placeholder

Create empty placeholder files while rendering frames (similar to Unix ‘touch’)

Type boolean, default False

use_radiosity

Calculate radiosity in a pre-process before rendering

Type boolean, default False

use_raytrace

Pre-calculate the raytrace accelerator and render raytracing effects

Type boolean, default False

use_save_buffers

Save tiles for all RenderLayers and SceneNodes to files in the temp directory (saves memory, required for Full Sample)

Type boolean, default False

use_sequencer

Process the render (and composited) result through the video sequence editor pipeline, if sequencer strips exist

Type boolean, default False

use_sequencer_gl_preview

Type boolean, default False

use_sequencer_gl_render

Type boolean, default False

use_shadows

Calculate shadows while rendering

Type boolean, default False

use_simplify

Enable simplification of scene for quicker preview renders

Type boolean, default False

use_simplify_triangulate

Disables non-planer quads being triangulated

Type boolean, default False

use_single_layer

Only render the active layer

Type boolean, default False

use_sss

Calculate sub-surface scattering in materials rendering

Type boolean, default False

use_stamp

Render the stamp info text in the rendered image

Type boolean, default False

use_stamp_camera

Include the name of the active camera in image metadata

Type boolean, default False

use_stamp_date

Include the current date in image metadata

Type boolean, default False

use_stamp_filename

Include the filename of the .blend file in image metadata

Type boolean, default False

use_stamp_frame

Include the frame number in image metadata

Type boolean, default False

use_stamp_lens

Include the name of the active cameras lens in image metadata

Type boolean, default False

use_stamp_marker

Include the name of the last marker in image metadata

Type boolean, default False

use_stamp_note

Include a custom note in image metadata

Type boolean, default False

use_stamp_render_time

Include the render time in the stamp image

Type boolean, default False

use_stamp_scene

Include the name of the active scene in image metadata

Type boolean, default False

use_stamp_sequencer_strip

Include the name of the foreground sequence strip in image metadata

Type boolean, default False

use_stamp_time

Include the render frame as HH:MM:SS.FF in image metadata

Type boolean, default False

use_textures

Use textures to affect material properties

Type boolean, default False

use_tiff_16bit

Save TIFF with 16 bits per channel

Type boolean, default False

frame_path (frame=-2147483648)

Return the absolute path to the filename to be written for a given frame.

Parameters **frame** (*int in [-inf, inf], (optional)*) – Frame number to use, if unset the current frame will be used.

Returns File Path, the resulting filepath from the scenes render settings.

Return type string

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.render

2.4.425 RigidBodyJointConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.RigidBodyJointConstraint (*Constraint*)

For use with the Game Engine

axis_x

Rotate pivot on X axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

axis_y

Rotate pivot on Y axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

axis_z

Rotate pivot on Z axis in degrees

Type float in [-6.28319, 6.28319], default 0.0

child

Child object

Type Object

limit_angle_max_x

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_max_y

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_max_z

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_x

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_y

Type float in [-6.28319, 6.28319], default 0.0

limit_angle_min_z

Type float in [-6.28319, 6.28319], default 0.0

limit_max_x

Type float in [-inf, inf], default 0.0

limit_max_y

Type float in [-inf, inf], default 0.0

limit_max_z

Type float in [-inf, inf], default 0.0

limit_min_x

Type float in [-inf, inf], default 0.0

limit_min_y

Type float in [-inf, inf], default 0.0

limit_min_z

Type float in [-inf, inf], default 0.0

pivot_type

Type enum in ['BALL', 'HINGE', 'CONE_TWIST', 'GENERIC_6_DOF'], default 'BALL'

pivot_x

Offset pivot on X

Type float in [-1000, 1000], default 0.0

pivot_y

Offset pivot on Y

Type float in [-1000, 1000], default 0.0

pivot_z

Offset pivot on Z

Type float in [-1000, 1000], default 0.0

show_pivot

Display the pivot point and rotation in 3D view

Type boolean, default False

target

Target Object

Type [Object](#)

use_angular_limit_x

Use minimum/maximum x angular limit

Type boolean, default False

use_angular_limit_y

Use minimum/maximum y angular limit

Type boolean, default False

use_angular_limit_z

Use minimum/maximum z angular limit

Type boolean, default False

use_limit_x

Use minimum/maximum x limit

Type boolean, default False

use_limit_y

Use minimum/maximum y limit

Type boolean, default False

use_limit_z

Use minimum/maximum z limit

Type boolean, default False

use_linked_collision

Disable collision between linked bodies

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.426 SPHFluidSettings(bpy_struct)

base class — `bpy_struct`

class bpy.types.SPHFluidSettings (bpy_struct)

Settings for particle fluids physics

buoyancy

Artificial buoyancy force in negative gravity direction based on pressure differences inside the fluid

Type float in [0, 10], default 0.0

factor_density

Density is calculated as a factor of default density (depends on particle size)

Type boolean, default False

factor_radius

Interaction radius is a factor of 4 * particle size

Type boolean, default False

factor_repulsion

Repulsion is a factor of stiffness

Type boolean, default False

factor_rest_length

Spring rest length is a factor of 2 * particle size

Type boolean, default False

factor_stiff_viscosity

Stiff viscosity is a factor of normal viscosity

Type boolean, default False

fluid_radius

Fluid interaction radius

Type float in [0, 20], default 0.0

linear_viscosity

Linear viscosity

Type float in [0, 100], default 0.0

plasticity

How much the spring rest length can change after the elastic limit is crossed

Type float in [0, 100], default 0.0

repulsion

How strongly the fluid tries to keep from clustering (factor of stiffness)

Type float in [0, 100], default 0.0

rest_density

Fluid rest density

Type float in [0, 100], default 0.0

rest_length

Spring rest length (factor of particle radius)

Type float in [0, 2], default 0.0

spring_force

Spring force

Type float in [0, 100], default 0.0

spring_frames

Create springs for this number of frames since particles birth (0 is always)

Type int in [0, 100], default 0

stiff_viscosity

Creates viscosity for expanding fluid)

Type float in [0, 100], default 0.0

stiffness

How incompressible the fluid is

Type float in [0, 100], default 0.0

use_initial_rest_length

Use the initial length as spring rest length instead of 2 * particle size

Type boolean, default False

use_viscoelastic_springs

Use viscoelastic springs instead of Hooke's springs

Type boolean, default False

yield_ratio

How much the spring has to be stretched/compressed in order to change it's rest length

Type float in [0, 1], default 0.0

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- `ParticleSettings.fluid`

2.4.427 Scene(ID)

base classes — `bpy_struct, ID`

class bpy.types.Scene (ID)

Scene consisting objects and defining time and render related settings

animation_data

Animation data for this datablock

Type `AnimData`, (readonly)

audio_distance_model

Distance model for distance attenuation calculation

Type `enum` in ['NONE', 'INVERSE', 'INVERSE_CLAMPED', 'LINEAR', 'LINEAR_CLAMPED', 'EXPONENT', 'EXPONENT_CLAMPED'], default 'NONE'

audio_doppler_factor

Pitch factor for Doppler effect calculation

Type `float` in [0, inf], default 0.0

audio_doppler_speed

Speed of sound for Doppler effect calculation

Type `float` in [0.01, inf], default 0.0

background_set

Background set scene

Type `Scene`

camera

Active camera used for rendering the scene

Type `Object`

cursor_location

3D cursor location

Type `float array of 3 items` in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Current Frame

Type `int` in [-300000, 300000], default 0

frame_end

Final frame of the playback/rendering range

Type `int` in [0, 300000], default 0

frame_preview_end

Alternative end frame for UI playback

Type `int` in [-inf, inf], default 0

frame_preview_start

Alternative start frame for UI playback

Type int in [-inf, inf], default 0

frame_start
First frame of the playback/rendering range

Type int in [0, 300000], default 0

frame_step
Number of frames to skip forward while rendering/playing back each frame

Type int in [0, 300000], default 0

frame_subframe

Type float in [-inf, inf], default 0.0, (readonly)

game_settings

Type SceneGameData, (readonly, never None)

gravity
Constant acceleration in a given direction

Type float array of 3 items in [-200, 200], default (0.0, 0.0, 0.0)

grease_pencil
Grease Pencil datablock

Type GreasePencil

is_nla_tweakmode
Indicates whether there is any action referenced by NLA being edited. Strictly read-only

Type boolean, default False, (readonly)

keying_sets
Absolute Keying Sets for this Scene

Type KeyingSets bpy_prop_collection of KeyingSet, (readonly)

keying_sets_all
All Keying Sets available for use (Builtins and Absolute Keying Sets for this Scene)

Type KeyingSetsAll bpy_prop_collection of KeyingSet, (readonly)

layers
Layers visible when rendering the scene

Type boolean array of 20 items, default (False, False, False)

node_tree
Compositing node tree

Type NodeTree, (readonly)

object_bases

Type SceneBases bpy_prop_collection of ObjectBase, (readonly)

objects

Type SceneObjects bpy_prop_collection of Object, (readonly)

orientations

Type bpy_prop_collection of TransformOrientation, (readonly)

render

Type `RenderSettings`, (readonly, never None)

sequence_editor

Type `SequenceEditor`, (readonly)

sync_mode

How to sync playback

Type enum in ['NONE', 'FRAME_DROP', 'AUDIO_SYNC'], default 'NONE'

timeline_markers

Markers used in all timelines for the current scene

Type `TimelineMarkers bpy_prop_collection of TimelineMarker`, (readonly)

tool_settings

Type `ToolSettings`, (readonly, never None)

unit_settings

Unit editing settings

Type `UnitSettings`, (readonly, never None)

use_audio

Play back of audio from Sequence Editor will be muted

Type boolean, default False

use_audio_scrub

Play audio from Sequence Editor while scrubbing

Type boolean, default False

use_audio_sync

Play back and sync with audio clock, dropping frames if frame display is too slow

Type boolean, default False

use_frame_drop

Play back dropping frames if frame display is too slow

Type boolean, default False

use_gravity

Use global gravity for all dynamics

Type boolean, default False

use_nodes

Enable the compositing node tree

Type boolean, default False

use_preview_range

Use an alternative start/end frame for UI playback, rather than the scene start/end frame

Type boolean, default False

use_stamp_note

User define note for the render stamping

Type string, default ""

world

World used for rendering the scene

Type [World](#)

statistics()

statistics

Returns Statistics

Return type string

frame_set(frame, subframe=0.0)

Set scene frame updating all objects immediately.

Parameters

- **frame** (*int in [-300000, 300000]*) – Frame number to set.
- **subframe** (*float in [0, 1], (optional)*) – Sub-frame time, between 0.0 and 1.0

update()

Update data tagged to be updated from previous access to data or operators.

Inherited Properties

- [bpy_struct.id_data](#)
- [ID.name](#)
- [ID.use_fake_user](#)
- [ID.library](#)
- [ID.tag](#)
- [ID.users](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [ID.copy](#)
- [ID.user_clear](#)
- [ID.animation_data_create](#)
- [ID.animation_data_clear](#)
- [ID.update_tag](#)

References

- BlendData.scenes
- BlendDataScenes.new
- BlendDataScenes.remove
- CompositorNodeRLayers.scene
- Context.scene
- Image.save_render
- Object.dupli_list_create
- Object.is_modified
- Object.is_visible
- Object.to_mesh
- RenderEngine.render
- Scene.background_set
- SceneActuator.scene
- SceneSequence.scene
- Screen.scene

2.4.428 SceneActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.SceneActuator (Actuator)
Actuator to ..

camera

Set this Camera. Leave empty to refer to self object

Type Object

mode

Type enum in ['RESTART', 'SET', 'CAMERA', 'ADDFRONT', 'ADDBACK', 'REMOVE', 'SUSPEND', 'RESUME'], default 'RESTART'

scene

Set the Scene to be added/removed/paused/resumed

Type Scene

Inherited Properties

- bpy_struct.id_data
- Actuator.name
- Actuator.show_expanded
- Actuator.pin
- Actuator.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Actuator.link
- Actuator.unlink

2.4.429 SceneBases(bpy_struct)

base class — bpy_struct

class bpy.types.SceneBases (*bpy_struct*)
Collection of scene bases
active
Active object base in the scene
Type ObjectBase

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- `Scene.object_bases`

2.4.430 `SceneGameData(bpy_struct)`

base class — `bpy_struct`

class `bpy.types.SceneGameData(bpy_struct)`

Game data for a Scene datablock

activity_culling_box_radius

Radius of the activity bubble, in Manhattan length. Objects outside the box are activity-culled

Type float in [0, 1000], default 0.0

depth

Displays bit depth of full screen display

Type int in [8, 32], default 0

dome_angle

Field of View of the Dome - it only works in mode Fisheye and Truncated

Type int in [-32768, 32767], default 0

dome_buffer_resolution

Buffer Resolution - decrease it to increase speed

Type float in [-inf, inf], default 0.0

dome_mode

Dome physical configurations

Type enum in ['FISHEYE', 'TRUNCATED_FRONT', 'TRUNCATED_REAR', 'ENVMAP', 'PANORAM_SPH'], default 'FISHEYE'

dome_tesselation

Tessellation level - check the generated mesh in wireframe mode

Type int in [-32768, 32767], default 0

dome_text

Custom Warp Mesh data file

Type `Text`

dome_tilt

Camera rotation in horizontal axis

Type int in [-32768, 32767], default 0

fps

The nominal number of game frames per second. Physics fixed timestep = 1/fps, independently of actual frame rate

Type int in [1, 250], default 0

frame_color

Set color of the bars

Type float array of 3 items in [0, 1], default (0.0, 0.0, 0.0)

frame_type

Select the type of Framing you want

Type enum in ['LETTERBOX', 'EXTEND', 'SCALE'], default 'LETTERBOX'

frequency

Displays clock frequency of fullscreen display

Type int in [4, 2000], default 0

logic_step_max

Sets the maximum number of logic frame per game frame if graphics slows down the game, higher value allows better synchronization with physics

Type int in [1, 5], default 0

material_mode

Material mode to use for rendering

Type enum in ['TEXTURE_FACE', 'MULTITEXTURE', 'GLSL'], default 'TEXTURE_FACE'

occlusion_culling_resolution

The size of the occlusion buffer in pixel, use higher value for better precision (slower)

Type int in [128, 1024], default 0

physics_engine

Physics engine used for physics simulation in the game engine

Type enum in ['NONE', 'BULLET'], default 'NONE'

physics_gravity

Gravitational constant used for physics simulation in the game engine

Type float in [0, 10000], default 0.0

physics_step_max

Sets the maximum number of physics step per game frame if graphics slows down the game, higher value allows physics to keep up with realtime

Type int in [1, 5], default 0

physics_step_sub

Sets the number of simulation substep per physic timestep, higher value give better physics precision

Type int in [1, 5], default 0

resolution_x

Number of horizontal pixels in the screen

Type int in [4, 10000], default 0

resolution_y

Number of vertical pixels in the screen

Type int in [4, 10000], default 0

show_debug_properties

Show properties marked for debugging while the game runs

Type boolean, default False

show_framerate_profile

Show framerate and profiling information while the game runs

Type boolean, default False

show_fullscreen
Starts player in a new fullscreen display

Type boolean, default False

show_mouse
Start player with a visible mouse cursor

Type boolean, default False

show_physics_visualization
Show a visualization of physics bounds and interactions

Type boolean, default False

stereo

Type enum in ['NONE', 'STEREO', 'DOME'], default 'NONE'

stereo_eye_separation
Set the distance between the eyes - the camera focal length/30 should be fine

Type float in [0.01, 5], default 0.0

stereo_mode
Stereographic techniques

Type enum in ['QUADBUFFERED', 'ABOVEBELOW', 'INTERLACED', 'ANAGLYPH', 'SIDEBYSIDE', 'VINTERLACE'], default 'QUADBUFFERED'

use_activity_culling
Activity culling is enabled

Type boolean, default False

use_animation_record
Record animation to fcurves

Type boolean, default False

use_auto_start
Automatically start game at load time

Type boolean, default False

use_deprecation_warnings
Print warnings when using deprecated features in the python API

Type boolean, default False

use_display_lists
Use display lists to speed up rendering by keeping geometry on the GPU

Type boolean, default False

use_frame_rate
Respect the frame rate rather than rendering as many frames as possible

Type boolean, default False

use_gsls_color_management
Use color management for GLSL rendering

Type boolean, default False

use_gsls_extra_textures
Use extra textures like normal or specular maps for GLSL rendering
Type boolean, default False

use_gsls_lights
Use lights for GLSL rendering
Type boolean, default False

use_gsls_nodes
Use nodes for GLSL rendering
Type boolean, default False

use_gsls_ramps
Use ramps for GLSL rendering
Type boolean, default False

use_gsls_shaders
Use shaders for GLSL rendering
Type boolean, default False

use_gsls_shadows
Use shadows for GLSL rendering
Type boolean, default False

use_occlusion_culling
Use optimized Bullet DBVT tree for view frustum and occlusion culling
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.game_settings`

2.4.431 SceneObjects(bpy_struct)

base class — `bpy_struct`

class bpy.types.SceneObjects (bpy_struct)
Collection of scene objects

active

Active object for this scene

Type `Object`

link (object)

Link object to scene, run `scene.update()` after.

Parameters `object (Object, (never None))` – Object to add to scene.

Returns The newly created base.

Return type `ObjectBase`

unlink (object)

Unlink object from scene.

Parameters `object (Object, (never None))` – Object to remove from scene.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.objects`

2.4.432 SceneRenderLayer(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.SceneRenderLayer` (`bpy_struct`)
 Render layer

exclude_ambient_occlusion

Exclude AO pass from combined

Type boolean, default False

exclude_emit

Exclude emission pass from combined

Type boolean, default False

exclude_environment

Exclude environment pass from combined

Type boolean, default False

exclude_indirect

Exclude indirect pass from combined

Type boolean, default False

exclude_reflection

Exclude raytraced reflection pass from combined

Type boolean, default False

exclude_refraction

Exclude raytraced refraction pass from combined

Type boolean, default False

exclude_shadow

Exclude shadow pass from combined

Type boolean, default False

exclude_specular

Exclude specular pass from combined

Type boolean, default False

invert_zmask

For Zmask, only render what is behind solid z values instead of in front

Type boolean, default False

layers

Scene layers included in this render layer

Type boolean array of 20 items, default (False, False, False)

layers_zmask

Zmask scene layers

Type boolean array of 20 items, default (False, False, False)

light_override

Group to override all other lights in this render layer

Type Group

material_override

Material to override all other materials in this render layer

Type Material

name

Render layer name

Type string, default “”

use

Disable or enable the render layer

Type boolean, default False

use_all_z

Fill in Z values for solid faces in invisible layers, for masking

Type boolean, default False

use_edge_enhance

Render Edge-enhance in this Layer (only works for Solid faces)

Type boolean, default False

use_halo

Render Halos in this Layer (on top of Solid)

Type boolean, default False

use_pass_ambient_occlusion

Deliver AO pass

Type boolean, default False

use_pass_color

Deliver shade-less color pass

Type boolean, default False

use_pass_combined

Deliver full combined RGBA buffer

Type boolean, default False

use_pass_diffuse

Deliver diffuse pass

Type boolean, default False

use_pass_emit

Deliver emission pass

Type boolean, default False

use_pass_environment

Deliver environment lighting pass

Type boolean, default False

use_pass_indirect
Deliver indirect lighting pass
Type boolean, default False

use_pass_mist
Deliver mist factor pass (0.0-1.0)
Type boolean, default False

use_pass_normal
Deliver normal pass
Type boolean, default False

use_pass_object_index
Deliver object index pass
Type boolean, default False

use_pass_reflection
Deliver raytraced reflection pass
Type boolean, default False

use_pass_refraction
Deliver raytraced refraction pass
Type boolean, default False

use_pass_shadow
Deliver shadow pass
Type boolean, default False

use_pass_specular
Deliver specular pass
Type boolean, default False

use_pass_uv
Deliver texture UV pass
Type boolean, default False

use_pass_vector
Deliver speed vector pass
Type boolean, default False

use_pass_z
Deliver Z values pass
Type boolean, default False

use_sky
Render Sky in this Layer
Type boolean, default False

use_solid
Render Solid faces in this Layer
Type boolean, default False

use_strand
Render Strands in this Layer

Type boolean, default False

use_zmask

Only render what's in front of the solid z values

Type boolean, default False

use_ztransp

Render Z-Transparent faces in this Layer (On top of Solid and Halos)

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- RenderLayers.active
- RenderSettings.layers

2.4.433 SceneSequence(Sequence)

base classes — `bpy_struct`, `Sequence`

class bpy.types.SceneSequence (Sequence)

Sequence strip to used the rendered image of a scene

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

color_balance

Type SequenceColorBalance, (readonly)

color_multiply

Type float in [0, 20], default 0.0

color_saturation

Type float in [0, 20], default 0.0

crop

Type SequenceCrop, (readonly)

proxy

Type SequenceProxy, (readonly)

scene

Scene that this sequence uses

Type Scene

scene_camera

Override the scenes active camera

Type Object

strobe

Only display every nth frame

Type float in [1, 30], default 0.0

transform

Type SequenceTransform, (readonly)

use_color_balance

(3-Way color correction) on input

Type boolean, default False

use_crop

Crop image before processing

Type boolean, default False

use_deinterlace

For video movies to remove fields

Type boolean, default False

use_flip_x

Flip on the X axis

Type boolean, default False

use_flip_y

Flip on the Y axis

Type boolean, default False

use_float

Convert input to float data

Type boolean, default False
use_premultiply
Convert RGB from key alpha to premultiplied alpha
Type boolean, default False
use_proxy
Use a preview proxy for this strip
Type boolean, default False
use_proxy_custom_directory
Use a custom directory to store data
Type boolean, default False
use_proxy_custom_file
Use a custom file to read proxy data from
Type boolean, default False
use_reverse_frames
Reverse frame order
Type boolean, default False
use_translation
Translate image before processing
Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type

- Sequence.use_default_fade
- Sequence.input_count

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.434 Scopes(bpy_struct)

base class — bpy_struct

class bpy.types.Scopes (*bpy_struct*)
Scopes for statistical view of an image

accuracy

Proportion of original image source pixel lines to sample

Type float in [0, 100], default 0.0

histogram

Histogram for viewing image statistics

Type Histogram, (readonly)

use_full_resolution

Sample every pixel of the image

Type boolean, default False

vectorscope_alpha

Opacity of the points

Type float in [0, 1], default 0.0

waveform_alpha

Opacity of the points

Type float in [0, 1], default 0.0

waveform_mode

Type enum in ['LUMA', 'RGB', 'YCBCR601', 'YCBCR709', 'YCBQRJPG'], default 'LUMA'

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceImageEditor.scopes

2.4.435 Screen(ID)

base classes — bpy_struct, ID

class bpy.types.Screen (*ID*)

Screen datablock, defining the layout of areas in a window

areas

Areas the screen is subdivided into

Type bpy_prop_collection of Area, (readonly)

is_animation_playing

Animation playback is active

Type boolean, default False, (readonly)

scene

Active scene to be edited in the screen

Type Scene, (never None)

show_fullscreen

An area is maximised, filling this screen

Type boolean, default False, (readonly)

use_play_3d_editors

Type boolean, default False

use_play_animation_editors

Type boolean, default False

use_play_image_editors

Type boolean, default False

use_play_node_editors

Type boolean, default False

use_play_properties_editors

Type boolean, default False

use_play_sequence_editors

Type boolean, default False

use_play_top_left_3d_editor

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`

- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.screens
- Context.screen
- Window.screen

2.4.436 ScrewModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ScrewModifier (*Modifier*)
Revolve edges

angle

Angle of revolution

Type float in [-inf, inf], default 0.0

axis

Screw axis

Type enum in ['X', 'Y', 'Z'], default 'X'

iterations

Number of times to apply the screw operation

Type int in [1, 10000], default 0

object

Object to define the screw axis

Type Object

render_steps

Number of steps in the revolution

Type int in [2, 10000], default 0

screw_offset

Offset the revolution along its axis

Type float in [-inf, inf], default 0.0

steps

Number of steps in the revolution

Type int in [2, 10000], default 0

use_normal_calculate

Calculate the order of edges (needed for meshes, but not curves)

Type boolean, default False

use_normal_flip

Flip normals of lathed faces

Type boolean, default False

use_object_screw_offset

Use the distance between the objects to make a screw

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.437 Sculpt(Paint)

base classes — bpy_struct, Paint

class bpy.types.Sculpt (*Paint*)

lock_x

Disallow changes to the X axis of vertices

Type boolean, default False

lock_y

Disallow changes to the Y axis of vertices

Type boolean, default False

lock_z

Disallow changes to the Z axis of vertices

Type boolean, default False

radial_symmetry

Number of times to copy strokes across the surface

Type int array of 3 items in [1, 64], default (1, 1, 1)

use_deform_only

Use only deformation modifiers (temporary disable all constructive modifiers except multi-resolution)

Type boolean, default False

use_symmetry_feather

Reduce the strength of the brush where it overlaps symmetrical daubs

Type boolean, default False

use_symmetry_x

Mirror brush across the X axis

Type boolean, default False

use_symmetry_y

Mirror brush across the Y axis

Type boolean, default False

use_symmetry_z

Mirror brush across the Z axis

Type boolean, default False

use_threaded

Take advantage of multiple CPU cores to improve sculpting performance

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Paint.brush`
- `Paint.show_low_resolution`
- `Paint.show_brush`
- `Paint.show_brush_on_surface`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.sculpt

2.4.438 Sensor(bpy_struct)

base class — bpy_struct
subclasses — RaySensor, PropertySensor, MessageSensor, TouchSensor, KeyboardSensor, CollisionSensor, RadarSensor, DelaySensor, RandomSensor, AlwaysSensor, ActuatorSensor, JoystickSensor, MouseSensor, ArmatureSensor, NearSensor

class bpy.types.Sensor(bpy_struct)
Game engine logic brick to detect events

frequency
Delay between repeated pulses(in logic tics, 0=no delay)
Type int in [0, 10000], default 0

invert
Invert the level(output) of this sensor
Type boolean, default False

name
Sensor name
Type string, default “”

pin
Display when not linked to a visible states controller
Type boolean, default False

show_expanded
Set sensor expanded in the user interface
Type boolean, default False

type
Type enum in ['ACTUATOR', 'ALWAYS', 'ARMATURE', 'COLLISION', 'DELAY', 'JOYSTICK', 'KEYBOARD', 'MESSAGE', 'MOUSE', 'NEAR', 'PROPERTY', 'RADAR', 'RANDOM', 'RAY', 'TOUCH'], default 'ALWAYS'

use_level
Level detector, trigger controllers of new states(only applicable upon logic state transition)
Type boolean, default False

use_pulse_false_level
Activate FALSE level triggering (pulse mode)
Type boolean, default False

use_pulse_true_level

Activate TRUE level triggering (pulse mode)

Type boolean, default False

use_tap

Trigger controllers only for an instant, even while the sensor remains true

Type boolean, default False

link(controller)

Link the sensor to a controller.

Parameters **controller** ([Controller](#)) – Controller to link to.

unlink(controller)

Unlink the sensor from a controller.

Parameters **controller** ([Controller](#)) – Controller to unlink from.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [Controller.link](#)
- [Controller.unlink](#)
- [GameObjectSettings.sensors](#)

2.4.439 Sequence([bpy_struct](#))

base class — [bpy_struct](#)

subclasses — [MulticamSequence](#), [ImageSequence](#), [SceneSequence](#), [AdjustmentSequence](#), [MetaSequence](#), [SoundSequence](#), [MovieSequence](#), [EffectSequence](#)

```
class bpy.types.Sequence (bpy_struct)
    Sequence strip in the sequence editor

    blend_alpha
        Type float in [0, 1], default 0.0

    blend_type
        Type enum in ['REPLACE', 'CROSS', 'ADD', 'SUBTRACT', 'ALPHA_OVER', 'ALPHA_UNDER', 'GAMMA_CROSS', 'MULTIPLY', 'OVER_DROP'], default 'REPLACE'

    channel
        Y position of the sequence strip
        Type int in [0, 31], default 0

    effect_fader
        Type float in [0, 1], default 0.0

    frame_duration
        The length of the contents of this strip before the handles are applied
        Type int in [1, 300000], default 0, (readonly)

    frame_final_duration
        The length of the contents of this strip before the handles are applied
        Type int in [1, 300000], default 0

    frame_final_end
        End frame displayed in the sequence editor after offsets are applied
        Type int in [-inf, inf], default 0

    frame_final_start
        Start frame displayed in the sequence editor after offsets are applied, setting this is equivalent to moving
        the handle, not the actual start frame
        Type int in [-inf, inf], default 0

    frame_offset_end
        Type int in [-inf, inf], default 0, (readonly)

    frame_offset_start
        Type int in [-inf, inf], default 0, (readonly)

    frame_start
        Type int in [-inf, inf], default 0

    frame_still_end
        Type int in [0, 300000], default 0, (readonly)

    frame_still_start
        Type int in [0, 300000], default 0, (readonly)

    input_1
        First input for the effect strip
        Type Sequence, (readonly)
```

input_2
Second input for the effect strip
Type Sequence, (readonly)

input_3
Third input for the effect strip
Type Sequence, (readonly)

input_count

Type int in [0, inf], default 0, (readonly)

lock
Lock strip so that it can't be transformed
Type boolean, default False

mute

Type boolean, default False

name

Type string, default “”

select

Type boolean, default False

select_left_handle

Type boolean, default False

select_right_handle

Type boolean, default False

speed_factor
Multiply the current speed of the sequence with this number or remap current frame to this frame
Type float in [-inf, inf], default 0.0

type

Type enum in ['IMAGE', 'META', 'SCENE', 'MOVIE', 'SOUND', 'CROSS', 'ADD', 'SUBTRACT', 'ALPHA_OVER', 'ALPHA_UNDER', 'GAMMA_CROSS', 'MULTIPLY', 'OVER_DROP', 'PLUGIN', 'WIPE', 'GLOW', 'TRANSFORM', 'COLOR', 'SPEED', 'MULTICAM', 'ADJUSTMENT'], default 'IMAGE', (readonly)

use_default_fade
Fade effect using the built-in default (usually make transition as long as effect strip)
Type boolean, default False

getStripElem(frame)
Return the strip element from a given frame or None.

Parameters **frame** (int in [-300000, 300000]) – Frame, The frame to get the strip element from

Returns strip element of the current frame

Return type SequenceElement

swap(other)
swap

Parameters other ([Sequence](#), (never None)) – Other

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `MetaSequence.sequences`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.swap`
- `SequenceEditor.active_strip`
- `SequenceEditor.meta_stack`
- `SequenceEditor.sequences`
- `SequenceEditor.sequences_all`

2.4.440 SequenceColorBalance(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.SequenceColorBalance(bpy_struct)`

Color balance parameters for a sequence strip

gain

Color balance gain (highlights)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

gamma

Color balance gamma (midtones)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

invert_gain
 Type boolean, default False
invert_gamma
 Type boolean, default False
invert_lift
 Type boolean, default False
lift
 Color balance lift (shadows)
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AdjustmentSequence.color_balance`
- `EffectSequence.color_balance`
- `ImageSequence.color_balance`
- `MetaSequence.color_balance`
- `MovieSequence.color_balance`
- `MulticamSequence.color_balance`
- `SceneSequence.color_balance`

2.4.441 SequenceCrop(`bpy_struct`)

base class — `bpy_struct`

```
class bpy.types.SequenceCrop(bpy_struct)
    Cropping parameters for a sequence strip
```

max_x

Type int in [0, inf], default 0

max_y

Type int in [0, inf], default 0

min_x

Type int in [0, inf], default 0

min_y

Type int in [0, inf], default 0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AdjustmentSequence.crop`
- `EffectSequence.crop`
- `ImageSequence.crop`
- `MetaSequence.crop`
- `MovieSequence.crop`
- `MulticamSequence.crop`
- `SceneSequence.crop`

2.4.442 SequenceEditor(bpy_struct)

base class — `bpy_struct`

class bpy.types.SequenceEditor(bpy_struct)
Sequence editing data for a Scene datablock

active_strip
Type `Sequence`

meta_stack
Meta strip stack, last is currently edited meta strip
Type `bpy_prop_collection` of `Sequence`, (readonly)

overlay_frame
Sequencers active strip
Type int in [-inf, inf], default 0

overlay_lock
Type boolean, default False

sequences
Type `bpy_prop_collection` of `Sequence`, (readonly)

sequences_all
Type `bpy_prop_collection` of `Sequence`, (readonly)

show_overlay
Partial overlay on top of the sequencer
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.sequence_editor`

2.4.443 SequenceElement(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.SequenceElement(bpy_struct)`

Sequence strip data for a single frame

filename

Type string, default “”

orig_height

Original image height

Type int in [-inf, inf], default 0, (readonly)

orig_width

Original image width

Type int in [-inf, inf], default 0, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ImageSequence.elements`
- `MovieSequence.elements`
- `Sequence.getStripElem`

2.4.444 SequenceProxy(bpy_struct)

base class — `bpy_struct`

`class bpy.types.SequenceProxy(bpy_struct)`

Proxy parameters for a sequence strip

directory

Location to store the proxy files

Type string, default “”

filepath

Location of custom proxy file

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AdjustmentSequence.proxy`
- `EffectSequence.proxy`
- `ImageSequence.proxy`
- `MetaSequence.proxy`
- `MovieSequence.proxy`
- `MulticamSequence.proxy`
- `SceneSequence.proxy`

2.4.445 SequenceTransform(bpy_struct)

base class — `bpy_struct`

```
class bpy.types.SequenceTransform(bpy_struct)
    Transform parameters for a sequence strip

    offset_x
        Type int in [-inf, inf], default 0

    offset_y
        Type int in [-inf, inf], default 0
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `AdjustmentSequence.transform`
- `EffectSequence.transform`
- `ImageSequence.transform`
- `MetaSequence.transform`
- `MovieSequence.transform`
- `MulticamSequence.transform`
- `SceneSequence.transform`

2.4.446 ShaderNode(Node)

base classes — `bpy_struct, Node`

subclasses — `ShaderNodeHueSaturation, ShaderNodeVectorMath, ShaderNodeRGB, ShaderNodeCameraData, ShaderNodeSeparateRGB, ShaderNodeMath, ShaderNodeRGBOBW, ShaderNodeRGBCurve, ShaderNodeInvert, ShaderNodeExtendedMaterial, ShaderNodeMaterial, ShaderNodeValue, ShaderNodeMixRGB, ShaderNodeVectorCurve,`

ShaderNodeCombineRGB, ShaderNodeOutput, ShaderNodeValToRGB, ShaderNodeGeometry, ShaderNodeTexture, ShaderNodeMapping, ShaderNodeSqueeze, ShaderNodeNormal

```
class bpy.types.ShaderNode(Node)
    Material shader node

    type
        Type enum in ['OUTPUT', 'MATERIAL', 'RGB', 'VALUE', 'MIX_RGB', 'VAL-
        TORGB', 'RGBOBW', 'TEXTURE', 'NORMAL', 'GEOMETRY', 'MAPPING',
        'CURVE_VEC', 'CURVE_RGB', 'CAMERA', 'MATH', 'VECT_MATH', 'SQUEEZE',
        'MATERIAL_EXT', 'INVERT', 'SEPRGB', 'COMBRGB', 'HUE_SAT', 'SCRIPT',
        'GROUP'], default 'OUTPUT', (readonly)
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.447 ShaderNodeCameraData(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

```
class bpy.types.ShaderNodeCameraData(ShaderNode)
```

Inherited Properties

- bpy_struct.id_data
- Node.name

- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.448 ShaderNodeCombineRGB(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeCombineRGB (ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.449 ShaderNodeExtendedMaterial(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.ShaderNodeExtendedMaterial (ShaderNode)

invert_normal

Material Node uses inverted normal

Type boolean, default False

material

Type Material

use_diffuse

Material Node outputs Diffuse

Type boolean, default False

use_specular

Material Node outputs Specular

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.450 ShaderNodeGeometry(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.ShaderNodeGeometry (*ShaderNode*)

color_layer

Type string, default “”

uv_layer

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.451 ShaderNodeHueSaturation(ShaderNode)

base classes — `bpy_struct`, `Node`, `ShaderNode`

`class bpy.types.ShaderNodeHueSaturation(ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.452 ShaderNodeInvert(ShaderNode)

base classes — `bpy_struct`, `Node`, `ShaderNode`

`class bpy.types.ShaderNodeInvert(ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.453 ShaderNodeMapping(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeMapping (ShaderNode)`

`location`

Location offset for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`max`

Maximum value to clamp coordinate to

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`min`

Minimum value to clamp coordinate to

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`rotation`

Rotation offset for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`scale`

Scale adjustment for the input coordinate

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

`use_max`

Clamp the output coordinate to a maximum value

Type boolean, default False

`use_min`

Clamp the output coordinate to a minimum value

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.454 ShaderNodeMaterial(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

class bpy.types.ShaderNodeMaterial (ShaderNode)

`invert_normal`

Material Node uses inverted normal

Type boolean, default False

`material`

Type Material

`use_diffuse`

Material Node outputs Diffuse

Type boolean, default False

`use_specular`

Material Node outputs Specular

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.455 ShaderNodeMath(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeMath (ShaderNode)`

`operation`

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.456 ShaderNodeMixRGB(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeMixRGB (ShaderNode)`

`blend_type`

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

`use_alpha`

Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.457 ShaderNodeNormal(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeNormal (ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.458 ShaderNodeOutput(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

```
class bpy.types.ShaderNodeOutput (ShaderNode)
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.459 ShaderNodeRGB(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

```
class bpy.types.ShaderNodeRGB (ShaderNode)
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer

- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.460 ShaderNodeRGBCurve(ShaderNode)

base classes — `bpy_struct`, `Node`, `ShaderNode`

class `bpy.types.ShaderNodeRGBCurve` (`ShaderNode`)

mapping

Type `CurveMapping`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.461 ShaderNodeRGBToBW(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeRGBToBW (ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.462 ShaderNodeSeparateRGB(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeSeparateRGB (ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`

- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.463 `ShaderNodeSqueeze(ShaderNode)`

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeSqueeze (ShaderNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.464 ShaderNodeTexture(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.ShaderNodeTexture (*ShaderNode*)

node_output

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

texture

Type Texture

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.465 ShaderNodeTree(NodeTree)

base classes — `bpy_struct`, `ID`, `NodeTree`

class bpy.types.ShaderNodeTree (NodeTree)

Node tree consisting of linked nodes used for materials

nodes

Type `ShaderNodes bpy_prop_collection of Node`, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `NodeTree.animation_data`
- `NodeTree.grease_pencil`
- `NodeTree.inputs`
- `NodeTree.links`
- `NodeTree.outputs`
- `NodeTree.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.466 ShaderNodeValToRGB(ShaderNode)

base classes — `bpy_struct`, `Node`, `ShaderNode`

```
class bpy.types.ShaderNodeValToRGB (ShaderNode)

    color_ramp
    Type ColorRamp, (readonly)
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.467 ShaderNodeValue(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

```
class bpy.types.ShaderNodeValue (ShaderNode)
```

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.468 ShaderNodeVectorCurve(ShaderNode)

base classes — `bpy_struct, Node, ShaderNode`

`class bpy.types.ShaderNodeVectorCurve (ShaderNode)`

`mapping`

Type `CurveMapping, (readonly)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `ShaderNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.469 ShaderNodeVectorMath(ShaderNode)

base classes — bpy_struct, Node, ShaderNode

class bpy.types.ShaderNodeVectorMath(*ShaderNode*)

operation

Type enum in [‘ADD’, ‘SUBTRACT’, ‘AVERAGE’, ‘DOT_PRODUCT’, ‘CROSS_PRODUCT’, ‘NORMALIZE’], default ‘ADD’

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- ShaderNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.470 ShaderNodes(bpy_struct)

base class — bpy_struct

class bpy.types.ShaderNodes (bpy_struct)

Collection of Shader Nodes

new (type, group=None)

Add a node to this node tree.

Parameters

- **type** (*enum in ['OUTPUT', 'MATERIAL', 'RGB', 'VALUE', 'MIX_RGB', 'VALTORGB', 'RGBTOBW', 'TEXTURE', 'NORMAL', 'GEOMETRY', 'MAPPING', 'CURVE_VEC', 'CURVE_RGB', 'CAMERA', 'MATH', 'VECT_MATH', 'SQUEEZE', 'MATERIAL_EXT', 'INVERT', 'SEPRGB', 'COMBRGB', 'HUE_SAT', 'SCRIPT', 'GROUP']*) – Type, Type of node to add
- **group** ([NodeTree](#), (optional)) – The group tree

Returns New node.

Return type [Node](#)

remove (node)

remove a node from this node tree.

Parameters **node** ([Node](#)) – The node to remove.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [ShaderNodeTree.nodes](#)

2.4.471 ShapeActionActuator(**Actuator**)

base classes — `bpy_struct`, `Actuator`

class bpy.types.ShapeActionActuator(Actuator)
Actuator to control shape key animations

action
Type `Action`

frame_blend_in
Number of frames of motion blending
Type int in [0, 32767], default 0

frame_end
Type float in [-inf, inf], default 0.0

frame_property
Assign the action's current frame number to this property
Type string, default “”

frame_start
Type float in [-inf, inf], default 0.0

mode
Action playback type
Type enum in ['PLAY', 'PINGPONG', 'FLIPPER', 'LOOPSTOP', 'LOOPEND', 'PROPERTY'], default 'PLAY'

priority
Execution priority - lower numbers will override actions with higher numbers. With 2 or more actions at once, the overriding channels must be lower in the stack
Type int in [0, 100], default 0

property
Use this property to define the Action position
Type string, default “”

use_continue_last_frame
Restore last frame when switching on/off, otherwise play from the start each time
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.472 ShapeKey(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ShapeKey (bpy_struct)`

Shape key in a shape keys datablock

data

Type `bpy_prop_collection of UnknownType, (readonly)`

frame

Frame for absolute keys

Type `float in [-inf, inf], default 0.0, (readonly)`

interpolation

Interpolation type

Type `enum in ['KEY_LINEAR', 'KEY_CARDINAL', 'KEY_BSPLINE'], default 'KEY_LINEAR'`

mute

Mute this shape key

Type `boolean, default False`

name

Name of Shape Key

Type `string, default ""`

relative_key

Shape used as a relative key

Type `ShapeKey`

slider_max

Maximum for slider

Type float in [-10, 10], default 1.0

slider_min

Minimum for slider

Type float in [-10, 10], default 0.0

value

Value of shape key at the current frame

Type float in [0, 1], default 0.0

vertex_group

Vertex weight group, to blend with basis shape

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ClothSettings.rest_shape_key
- Key.key_blocks
- Key.reference_key
- Object.active_shape_key
- Object.shape_key_add
- ShapeKey.relative_key

2.4.473 ShapeKeyBezierPoint(bpy_struct)

base class — bpy_struct

```
class bpy.types.ShapeKeyBezierPoint (bpy_struct)
    Point in a shape key for Bezier curves

    co
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    handle_left
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    handle_right
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.474 ShapeKeyCurvePoint(bpy_struct)

base class — bpy_struct

```
class bpy.types.ShapeKeyCurvePoint (bpy_struct)
    Point in a shape key for curves

    co
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    tilt
        Type float in [-inf, inf], default 0.0
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.475 ShapeKeyPoint(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ShapeKeyPoint` (`bpy_struct`)

Point in a shape key

co

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.476 ShrinkwrapConstraint(Constraint)

base classes — `bpy_struct`, `Constraint`

`class bpy.types.ShrinkwrapConstraint(Constraint)`

Creates constraint-based shrinkwrap relationship

`distance`

Distance to Target

Type float in [0, 100], default 0.0

`shrinkwrap_type`

Selects type of shrinkwrap algorithm for target position

Type enum in ['NEAREST_SURFACE', 'PROJECT', 'NEAREST_VERTEX'], default 'NEAREST_SURFACE'

`target`

Target Object

Type `Object`

`use_x`

Projection over X Axis

Type boolean, default False

`use_y`

Projection over Y Axis

Type boolean, default False

`use_z`

Projection over Z Axis

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Constraint.name`
- `Constraint.active`
- `Constraint.mute`
- `Constraint.show_expanded`
- `Constraint.influence`
- `Constraint.error_location`
- `Constraint.owner_space`
- `Constraint.is_proxy_local`
- `Constraint.error_rotation`
- `Constraint.target_space`
- `Constraint.type`
- `Constraint.is_valid`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.477 ShrinkwrapModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.ShrinkwrapModifier (Modifier)

Shrink wrapping modifier to shrink wrap and object to a target

auxiliary_target

Additional mesh target to shrink to

Type Object

cull_face

Stop vertices from projecting to a the face on the target when facing towards/away

Type enum in ['OFF', 'FRONT', 'BACK'], default 'OFF'

offset

Distance to keep from the target

Type float in [-inf, inf], default 0.0

subsurf_levels

Number of subdivisions that must be performed before extracting vertices' positions and normals

Type int in [0, 6], default 0

target

Mesh target to shrink to

Type Object

use_keep_above_surface

Type boolean, default False

use_negative_direction

Allow vertices to move in the negative direction of axis

Type boolean, default False

use_positive_direction

Allow vertices to move in the positive direction of axis

Type boolean, default False

use_project_x

Type boolean, default False

use_project_y

Type boolean, default False

use_project_z

Type boolean, default False

vertex_group

Vertex group name

Type string, default “”

wrap_method

Type enum in ['NEAREST_SURFACEPOINT', 'PROJECT', 'NEAREST_VERTEX'], default 'NEAREST_SURFACEPOINT'

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.478 SimpleDeformModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.SimpleDeformModifier(*Modifier*)

Simple deformation modifier to apply effects such as twisting and bending

deform_method

Type enum in ['TWIST', 'BEND', 'TAPER', 'STRETCH'], default 'TWIST'

factor

Amount to deform object

Type float in [-inf, inf], default 0.0

limits

Lower/Upper limits for deform

Type float array of 2 items in [0, 1], default (0.0, 0.0)

lock_x

Do not allow tapering along the X axis

Type boolean, default False

lock_y

Do not allow tapering along the Y axis

Type boolean, default False

origin

Origin of modifier space coordinates

Type Object

use_relative

Sets the origin of deform space to be relative to the object

Type boolean, default False

vertex_group

Vertex group name

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`

- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.479 `SmokeCollSettings(bpy_struct)`

base class — `bpy_struct`

class `bpy.types.SmokeCollSettings (bpy_struct)`
Smoke collision settings

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SmokeModifier.coll_settings`

2.4.480 `SmokeDomainSettings(bpy_struct)`

base class — `bpy_struct`

class `bpy.types.SmokeDomainSettings (bpy_struct)`
Smoke domain settings

alpha

How much density effects smoke motion, higher value results in faster rising smoke

Type float in [-5, 5], default 0.0

amplify

Enhance the resolution of smoke by this factor using noise

Type int in [1, 10], default 0

beta

How much heat effects smoke motion, higher value results in faster rising smoke

Type float in [-5, 5], default 0.0

collision_extents

Selects which domain border will be treated as collision object.

Type enum in ['BORDEROPEN', 'BORDERVERTICAL', 'BORDERCLOSED'], default 'BORDEROPEN'

collision_group

Limit collisions to this group

Type Group

dissolve_speed

Dissolve Speed

Type int in [1, 10000], default 0

effector_group

Limit effectors to this group

Type Group

effector_weights

Type EffectorWeights, (readonly)

fluid_group

Limit fluid objects to this group

Type Group

noise_type

Noise method which is used for creating the high resolution

Type enum in ['NOISEWAVE'], default 'NOISEWAVE'

point_cache

Type PointCache, (readonly, never None)

point_cache_compress_type

Compression method to be used

Type enum in ['CACHELIGHT', 'CACHEHEAVY'], default 'CACHELIGHT'

resolution_max

Maximal resolution used in the fluid domain

Type int in [24, 512], default 0

show_high_resolution

Show high resolution (using amplification)

Type boolean, default False

smooth_emitter

Smoothens emitted smoke to avoid blockiness.

Type boolean, default False

strength

Strength of noise

Type float in [0, 10], default 0.0

time_scale

Adjust simulation speed.

Type float in [0.2, 1.5], default 0.0

use_dissolve_smoke

Enable smoke to disappear over time

Type boolean, default False

use_dissolve_smoke_log

Using 1/x

Type boolean, default False

use_high_resolution

Enable high resolution (using amplification)

Type boolean, default False

vorticity

Amount of turbulence/rotation in fluid.

Type float in [0.01, 4], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SmokeModifier.domain_settings`

2.4.481 `SmokeFlowSettings(bpy_struct)`

base class — `bpy_struct`

```
class bpy.types.SmokeFlowSettings(bpy_struct)
    Smoke flow settings

    density
        Type float in [0.001, 1], default 0.0

    initial_velocity
        Smoke inherits it's velocity from the emitter particle
        Type boolean, default False

    particle_system
        Particle systems emitted from the object
        Type ParticleSystem

    temperature
        Temperature difference to ambient temperature
        Type float in [-10, 10], default 0.0

    use_absolute
        Only allows given density value in emitter area.
        Type boolean, default False

    use_outflow
        Deletes smoke from simulation
        Type boolean, default False

    velocity_factor
        Multiplier to adjust velocity passed to smoke
        Type float in [-2, 2], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`

- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `SmokeModifier.flow_settings`

2.4.482 `SmokeModifier(Modifier)`

base classes — `bpy_struct, Modifier`

class `bpy.types.SmokeModifier(Modifier)`

 Smoke simulation modifier

`coll_settings`

Type `SmokeCollSettings`, (readonly)

`domain_settings`

Type `SmokeDomainSettings`, (readonly)

`flow_settings`

Type `SmokeFlowSettings`, (readonly)

`smoke_type`

Type enum in ['NONE', 'DOMAIN', 'FLOW', 'COLLISION'], default 'NONE'

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.483 SmoothModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.SmoothModifier (Modifier)
Smoothing effect modifier

factor

Strength of modifier effect

Type float in [-inf, inf], default 0.0

iterations

Type int in [-32768, 32767], default 0

use_x

Smooth object along X axis

Type boolean, default False

use_y

Smooth object along Y axis

Type boolean, default False

use_z

Smooth object along Z axis

Type boolean, default False

vertex_group

Name of Vertex Group which determines influence of modifier per point

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render

- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.484 SoftBodyModifier(Modifier)

base classes — `bpy_struct, Modifier`

```
class bpy.types.SoftBodyModifier (Modifier)
    Soft body simulation modifier

    point_cache
        Type PointCache, (readonly, never None)

    settings
        Type SoftBodySettings, (readonly, never None)
```

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.485 SoftBodySettings(bpy_struct)

base class — bpy_struct

class bpy.types.SoftBodySettings (*bpy_struct*)

Soft body simulation settings for an object

aero

Make edges ‘sail’

Type int in [0, 30000], default 0

aerodynamics_type

Method of calculating aerodynamic interaction

Type enum in ['SIMPLE', 'LIFT_FORCE'], default 'SIMPLE'

ball_damp

Blending to inelastic collision

Type float in [0.001, 1], default 0.0

ball_size

Absolute ball size or factor if not manual adjusted

Type float in [-10, 10], default 0.0

ball_stiff

Ball inflating pressure

Type float in [0.001, 100], default 0.0

bend

Bending Stiffness

Type float in [0, 10], default 0.0

choke

‘Viscosity’ inside collision target

Type int in [0, 100], default 0

collision_type

Choose Collision Type

Type enum in ['MANUAL', 'AVERAGE', 'MINIMAL', 'MAXIMAL', 'MINMAX'], default 'MANUAL'

damping

Edge spring friction

Type float in [0, 50], default 0.0

effector_weights

Type [EffectorWeights](#), (readonly)

error_threshold

The Runge-Kutta ODE solver error limit, low value gives more precision, high values speed

Type float in [0.001, 10], default 0.0

friction

General media friction for point movements

Type float in [0, 50], default 0.0

fuzzy

Fuzziness while on collision, high values make collision handling faster but less stable

Type int in [1, 100], default 0

goal_default

Default Goal (vertex target position) value, when no Vertex Group used

Type float in [0, 1], default 0.0

goal_friction

Goal (vertex target position) friction

Type float in [0, 50], default 0.0

goal_max

Goal maximum, vertex weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_min

Goal minimum, vertex weights are scaled to match this range

Type float in [0, 1], default 0.0

goal_spring

Goal (vertex target position) spring stiffness

Type float in [0, 0.999], default 0.0

gravity

Apply gravitation to point movement

Type float in [-10, 10], default 0.0

location_mass_center

Location of Center of mass

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

mass

General Mass value

Type float in [0, 50000], default 0.0

plastic

Permanent deform

Type int in [0, 100], default 0

pull
Edge spring stiffness when longer than rest length
Type float in [0, 0.999], default 0.0

push
Edge spring stiffness when shorter than rest length
Type float in [0, 0.999], default 0.0

rotation_estimate
Estimated rotation matrix
Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

scale_estimate
Estimated scale matrix
Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)

shear
Shear Stiffness
Type float in [0, 1], default 0.0

speed
Tweak timing for physics to control frequency and speed
Type float in [0.01, 100], default 0.0

spring_length
Alter spring length to shrink/blow up (unit %) 0 to disable
Type int in [0, 200], default 0

step_max
Maximal # solver steps/frame
Type int in [0, 30000], default 0

step_min
Minimal # solver steps/frame
Type int in [0, 30000], default 0

use_auto_step
Use velocities for automagic step sizes
Type boolean, default False

use_diagnose
Turn on SB diagnose console prints
Type boolean, default False

use_edge_collision
Edges collide too
Type boolean, default False

use_edges
Use Edges as springs
Type boolean, default False

```
use_estimate_matrix
    estimate matrix .. split to COM , ROT ,SCALE
        Type boolean, default False

use_face_collision
    Faces collide too, can be very slow
        Type boolean, default False

use_goal
    Define forces for vertices to stick to animated position
        Type boolean, default False

use_self_collision
    Enable naive vertex ball self collision
        Type boolean, default False

use_stiff_quads
    Adds diagonal springs on 4-gons
        Type boolean, default False

vertex_group_goal
    Control point weight values
        Type string, default “”

vertex_group_mass
    Control point mass values
        Type string, default “”

vertex_group_spring
    Control point spring strength values
        Type string, default “”
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.soft_body`
- `SoftBodyModifier.settings`

2.4.486 SolidifyModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.SolidifyModifier (Modifier)

Create a solid skin by extruding, compensating for sharp angles

edge_creature_inner

Assign a crease to inner edges

Type float in [0, 1], default 0.0

edge_creature_outer

Assign a crease to outer edges

Type float in [0, 1], default 0.0

edge_creature_rim

Assign a crease to the edges making up the rim

Type float in [0, 1], default 0.0

invert_vertex_group

Invert the vertex group influence

Type boolean, default False

material_offset

Offset material index of generated faces

Type int in [-32768, 32767], default 0

material_offset_rim

Offset material index of generated rim faces

Type int in [-32768, 32767], default 0

offset

Offset the thickness from the center

Type float in [-inf, inf], default 0.0

thickness

Thickness of the shell

Type float in [-inf, inf], default 0.0

use_even_offset

Maintain thickness by adjusting for sharp corners (slow, disable when not needed)

Type boolean, default False

use_quality_normals

Calculate normals which result in more even thickness (slow, disable when not needed)

Type boolean, default False

use_rim

Create edge loops between the inner and outer surfaces on face edges (slow, disable when not needed)

Type boolean, default False

vertex_group

Vertex group name

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.487 Sound(ID)

base classes — bpy_struct, ID

class bpy.types.Sound(*ID*)

Sound datablock referencing an external or packed sound file

filepath

Sound sample file used by this Sound datablock

Type string, default “”

packed_file

Type [PackedFile](#), (readonly)

use_memory_cache

The sound file is decoded and loaded into RAM

Type boolean, default False

Inherited Properties

- [bpy_struct.id_data](#)
- [ID.name](#)
- [ID.use_fake_user](#)
- [ID.library](#)
- [ID.tag](#)
- [ID.users](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)
- [ID.copy](#)
- [ID.user_clear](#)
- [ID.animation_data_create](#)
- [ID.animation_data_clear](#)
- [ID.update_tag](#)

References

- [BlendData.sounds](#)
- [SoundActuator.sound](#)
- [SoundSequence.sound](#)

2.4.488 SoundActuator(Actuator)

base classes — [bpy_struct](#), [Actuator](#)

```
class bpy.types.SoundActuator(Actuator)
    Sound file

    cone_inner_angle_3d
        The angle of the inner cone
        Type float in [-inf, inf], default 0.0

    cone_outer_angle_3d
        The angle of the outer cone
        Type float in [-inf, inf], default 0.0

    cone_outer_gain_3d
        The gain outside the outer cone. The gain in the outer cone will be interpolated between this value and the normal gain in the inner cone
        Type float in [-inf, inf], default 0.0

    distance_3d_max
        The maximum distance at which you can hear the sound
        Type float in [-inf, inf], default 0.0

    distance_3d_reference
        The distance where the sound has a gain of 1.0
        Type float in [-inf, inf], default 0.0

    gain_3d_max
        The maximum gain of the sound, no matter how near it is
        Type float in [-inf, inf], default 0.0

    gain_3d_min
        The minimum gain of the sound, no matter how far it is away
        Type float in [-inf, inf], default 0.0

    mode
        Type enum in ['PLAYSTOP', 'PLAYEND', 'LOOPSTOP', 'LOOPEND', 'LOOPBIDIRECTIONAL', 'LOOPBIDIRECTIONALSTOP'], default 'PLAYSTOP'

    pitch
        Sets the pitch of the sound
        Type float in [-inf, inf], default 0.0

    rolloff_factor_3d
        The influence factor on volume depending on distance
        Type float in [-inf, inf], default 0.0

    sound
        Type Sound

    use_sound_3d
        Enable/Disable 3D Sound
        Type boolean, default False

    volume
        Sets the initial volume of the sound
        Type float in [0, 2], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`
- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.489 SoundSequence(Sequence)

base classes — `bpy_struct`, `Sequence`

class bpy.types.SoundSequence (Sequence)

Sequence strip defining a sound to be played over a period of time

animation_offset_end

Animation end offset (trim end)

Type int in [0, inf], default 0

animation_offset_start

Animation start offset (trim start)

Type int in [0, inf], default 0

attenuation

Attenuation in decibel

Type float in [-100, 40], default 0.0

filepath

Type string, default “”

sound

Sound datablock used by this sequence

Type `Sound`, (readonly)

volume

Playback volume of the sound

Type float in [0, 100], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`
- `Sequence.frame_final_duration`
- `Sequence.frame_duration`
- `Sequence.lock`
- `Sequence.mute`
- `Sequence.select_right_handle`
- `Sequence.select`
- `Sequence.speed_factor`
- `Sequence.frame_start`
- `Sequence.frame_final_start`
- `Sequence.frame_offset_start`
- `Sequence.frame_still_start`
- `Sequence.type`
- `Sequence.use_default_fade`
- `Sequence.input_count`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Sequence.getStripElem`
- `Sequence.swap`

2.4.490 Space(`bpy_struct`)

base class — `bpy_struct`

subclasses — `SpaceUserPreferences`, `SpaceOutliner`, `SpaceImageEditor`,
`SpaceSequenceEditor`, `SpaceProperties`, `SpaceGraphEditor`, `SpaceLogicEditor`,
`SpaceInfo`, `SpaceConsole`, `SpaceNodeEditor`, `SpaceView3D`, `SpaceDopeSheetEditor`,
`SpaceTextEditor`, `SpaceFileBrowser`, `SpaceNLA`, `SpaceTimeline`

class `bpy.types.Space` (`bpy_struct`)

Space data for a screen area

type

Space data type

Type enum in [‘EMPTY’, ‘VIEW_3D’, ‘GRAPH_EDITOR’, ‘OUTLINER’, ‘PROPERTIES’, ‘FILE_BROWSER’, ‘IMAGE_EDITOR’, ‘INFO’, ‘SEQUENCE_EDITOR’, ‘TEXT_EDITOR’, ‘AUDIO_WINDOW’, ‘DOPESHEET_EDITOR’, ‘NLA_EDITOR’, ‘SCRIPTS_WINDOW’, ‘TIMELINE’, ‘NODE_EDITOR’, ‘LOGIC_EDITOR’, ‘CONSOLE’, ‘USER_PREFERENCES’], default ‘EMPTY’, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Area.spaces`

- `AreaSpaces.active`
- `Context.space_data`

2.4.491 SpaceConsole(Space)

base classes — `bpy_struct`, `Space`

class `bpy.types.SpaceConsole` (*Space*)

Interactive python console

font_size

Font size to use for displaying the text

Type int in [8, 32], default 0

history

Command history

Type `bpy_prop_collection` of `ConsoleLine`, (readonly)

language

Command line prompt language

Type string, default “”

prompt

Command line prompt

Type string, default “”

scrollback

Command output

Type `bpy_prop_collection` of `ConsoleLine`, (readonly)

select_end

Type int in [0, inf], default 0

select_start

Type int in [0, inf], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.492 SpaceDopeSheetEditor(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceDopeSheetEditor (Space)

DopeSheet space data

action

Action displayed and edited in this space

Type Action

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

dopesheet

Settings for filtering animation data

Type DopeSheet, (readonly)

mode

Editing context being displayed

Type enum in ['DOPESHEET', 'ACTION', 'SHAPEKEY', 'GPENCIL'], default 'ACTION'

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_pose_markers

Show markers belonging to the active action instead of Scene markers (Action and Shape Key Editors only)

Type boolean, default False

show_seconds

Show timing in seconds not frames

Type boolean, default False, (readonly)

show_sliders

Show sliders beside F-Curve channels

Type boolean, default False

use_auto_merge_keyframes

Automatically merge nearby keyframes

Type boolean, default False

use_marker_sync

Sync Markers with keyframe edits

Type boolean, default False

use_realtime_update

When transforming keyframes, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.493 SpaceFileBrowser(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceFileBrowser(Space)

File browser space data

operator

Type Operator, (readonly)

params

Parameters and Settings for the Filebrowser

Type FileSelectParams, (readonly)

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.494 SpaceGraphEditor(Space)

base classes — `bpy_struct, Space`

class bpy.types.SpaceGraphEditor (Space)

Graph Editor space data

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

cursor_position_y

Graph Editor 2D-Value cursor - Y-Value component

Type float in [-inf, inf], default 0.0

dopesheet

Settings for filtering animation data

Type `DopeSheet`, (readonly)

has_ghost_curves

Graph Editor instance has some ghost curves stored

Type boolean, default False

mode

Editing context being displayed

Type enum in ['FCURVES', 'DRIVERS'], default 'FCURVES'

pivot_point

Pivot center for rotation/scaling

Type enum in ['BOUNDING_BOX_CENTER', 'CURSOR', 'INDIVIDUAL_ORIGINS'], default 'BOUNDING_BOX_CENTER'

show_cursor

Show 2D cursor

Type boolean, default False

show_frame_indicator
Show frame number beside the current frame indicator line

Type boolean, default False

show_handles
Show handles of Bezier control points

Type boolean, default False

show_seconds
Show timing in seconds not frames

Type boolean, default False, (readonly)

show_sliders
Show sliders beside F-Curve channels

Type boolean, default False

use_auto_merge_keyframes
Automatically merge nearby keyframes

Type boolean, default False

use_fancy_drawing
Draw F-Curves using Anti-Aliasing and other fancy effects. Disable for better performance

Type boolean, default False

use_only_selected_curves_handles
Only keyframes of selected F-Curves are visible and editable

Type boolean, default False

use_only_selected_keyframe_handles
Only show and edit handles of selected keyframes

Type boolean, default False

use_realtime_update
When transforming keyframes, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.495 SpaceImageEditor(Space)

base classes — `bpy_struct`, `Space`

class bpy.types.SpaceImageEditor (Space)

 Image and UV editor space data

curve

 Color curve mapping to use for displaying the image

Type `CurveMapping`, (readonly)

draw_channels

 Channels of the image to draw

Type enum in ['COLOR', 'COLOR_ALPHA', 'ALPHA', 'Z_BUFFER'], default 'COLOR'

grease_pencil

 Grease pencil data for this space

Type `GreasePencil`

image

 Image displayed and edited in this space

Type `Image`

image_user

 Parameters defining which layer, pass and frame of the image is displayed

Type `ImageUser`, (readonly, never None)

sample_histogram

 Sampled colors along line

Type `Histogram`, (readonly)

scopes

 Scopes to visualize image statistics.

Type `Scopes`, (readonly)

show_paint

 Show paint related properties

Type boolean, default False, (readonly)

show_render

 Show render related properties

Type boolean, default False, (readonly)

show_repeat

Draw the image repeated outside of the main view

Type boolean, default False

show_uvedit

Show UV editing related properties

Type boolean, default False, (readonly)

use_grease_pencil

Display and edit the grease pencil freehand annotations overlay

Type boolean, default False

use_image_paint

Enable image painting mode

Type boolean, default False

use_image_pin

Display current image regardless of object selection

Type boolean, default False

use_realtime_update

Update other affected window spaces automatically to reflect changes during interactive operations such as transform

Type boolean, default False

uv_editor

UV editor settings

Type SpaceUVEditor, (readonly, never None)

zoom

Zoom factor

Type float array of 2 items in [-inf, inf], default (0.0, 0.0), (readonly)

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.496 SpaceInfo(Space)

base classes — `bpy_struct`, `Space`

```
class bpy.types.SpaceInfo(Space)
    Info space data

    show_report_debug
        Display debug reporting info
            Type boolean, default False

    show_report_error
        Display error text
            Type boolean, default False

    show_report_info
        Display general information
            Type boolean, default False

    show_report_operator
        Display the operator log
            Type boolean, default False

    show_report_warning
        Display warnings
            Type boolean, default False
```

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.497 SpaceLogicEditor(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceLogicEditor(Space)

Logic editor space data

show_actuators_active_object

Show actuators of active object

Type boolean, default False

show_actuators_active_states

Show only actuators connected to active states

Type boolean, default False

show_actuators_linked_controller

Show linked objects to the actuator

Type boolean, default False

show_actuators_selected_objects

Show actuators of all selected objects

Type boolean, default False

show_controllers_active_object

Show controllers of active object

Type boolean, default False

show_controllers_linked_controller

Show linked objects to sensor/actuator

Type boolean, default False

show_controllers_selected_objects

Show controllers of all selected objects

Type boolean, default False

show_sensors_active_object

Show sensors of active object

Type boolean, default False

show_sensors_active_states

Show only sensors connected to active states

Type boolean, default False

show_sensors_linked_controller

Show linked objects to the controller

Type boolean, default False

show_sensors_selected_objects

Show sensors of all selected objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.498 SpaceNLA(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceNLA(Space)

NLA editor space data

auto_snap

Automatic time snapping settings for transformations

Type enum in ['NONE', 'STEP', 'FRAME', 'MARKER'], default 'NONE'

dopesheet

Settings for filtering animation data

Type DopeSheet, (readonly)

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_seconds

Show timing in seconds not frames

Type boolean, default False, (readonly)

show_strip_curves

Show influence curves on strips

Type boolean, default False

use_realtime_update

When transforming strips, changes to the animation data are flushed to other views

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.499 SpaceNodeEditor(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceNodeEditor(Space)

Node editor space data

backdrop_channels

Channels of the image to draw

Type enum in ['COLOR', 'COLOR_ALPHA', 'ALPHA'], default 'COLOR'

backdrop_x

Backdrop X offset

Type float in [-inf, inf], default 0.0

backdrop_y

Backdrop Y offset

Type float in [-inf, inf], default 0.0

backdrop_zoom

Backdrop zoom factor

Type float in [0.01, inf], default 1.0

id

Datablock whose nodes are being edited

Type ID, (readonly)

id_from

Datablock from which the edited datablock is linked

Type `ID`, (readonly)

node_tree

Node tree being displayed and edited

Type `NodeTree`, (readonly)

show_backdrop

Use active Viewer Node output as backdrop for compositing nodes

Type boolean, default False

texture_type

Type of data to take texture from

Type enum in ['OBJECT', 'WORLD', 'BRUSH'], default 'OBJECT'

tree_type

Node tree type to display and edit

Type enum in ['MATERIAL', 'TEXTURE', 'COMPOSITING'], default 'MATERIAL'

use_auto_render

Re-render and composite changed layer on 3D edits

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.500 SpaceOutliner(Space)

base classes — `bpy_struct`, `Space`

```
class bpy.types.SpaceOutliner (Space)
    Outliner space data

    display_mode
        Type enum in ['ALL_SCENES', 'CURRENT_SCENE', 'VISIBLE_LAYERS', 'SELECTED', 'ACTIVE', 'SAME_TYPES', 'GROUPS', 'LIBRARIES', 'SEQUENCE', 'DATABLOCKS', 'USER_PREFERENCES', 'KEYMAPS'], default 'ALL_SCENES'

    filter_text
        Live search filtering string
        Type string, default ""

    show_restrict_columns
        Show column
        Type boolean, default False

    use_filter_case_sensitive
        Only use case sensitive matches of search string
        Type boolean, default False

    use_filter_complete
        Only use complete matches of search string
        Type boolean, default False
```

Inherited Properties

- [bpy_struct.id_data](#)
- [Space.type](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

2.4.501 SpaceProperties(Space)

base classes — `bpy_struct`, `Space`

class bpy.types.SpaceProperties (Space)

Properties space data

align

Arrangement of the panels

Type enum in ['HORIZONTAL', 'VERTICAL'], default 'HORIZONTAL'

context

Type of active data to display and edit

Type enum in ['SCENE', 'RENDER', 'WORLD', 'OBJECT', 'CONSTRAINT', 'MODIFIER', 'DATA', 'BONE', 'BONE_CONSTRAINT', 'MATERIAL', 'TEXTURE', 'PARTICLES', 'PHYSICS'], default 'RENDER'

pin_id

Type ID

texture_context

Type of texture data to display and edit

Type enum in ['MATERIAL'], default 'MATERIAL'

use_pin_id

Use the pinned context

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.502 SpaceSequenceEditor(Space)

base classes — `bpy_struct`, `Space`

class bpy.types.SpaceSequenceEditor (Space)

Sequence editor space data

display_channel

The channel number shown in the image preview. 0 is the result of all strips combined

Type int in [-5, 32], default 0

display_mode

The view mode to use for displaying sequencer output

Type enum in ['IMAGE', 'WAVEFORM', 'VECTOR_SCOPE', 'HISTOGRAM'], default 'IMAGE'

draw_overexposed

Show overexposed areas with zebra stripes

Type int in [0, 110], default 0

grease_pencil

Grease pencil data for this space

Type `UnknownType`, (readonly)

offset_x

Offsets image horizontally from the view center

Type float in [-inf, inf], default 0.0

offset_y

Offsets image horizontally from the view center

Type float in [-inf, inf], default 0.0

proxy_render_size

Draw preview using full resolution or different proxy resolutions

Type enum in ['NONE', 'SCENE', 'PROXY_25', 'PROXY_50', 'PROXY_75', 'FULL'], default 'SCENE'

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_frames

Draw frames rather than seconds

Type boolean, default False

show_safe_margin

Draw title safe margins in preview

Type boolean, default False

show_separate_color

Separate color channels in preview

Type boolean, default False

use_grease_pencil

Display and edit the grease pencil freehand annotations overlay

Type boolean, default False

use_marker_sync

Transform markers as well as strips

Type boolean, default False

view_type

The type of the Sequencer view (sequencer, preview or both)

Type enum in ['SEQUENCER', 'PREVIEW', 'SEQUENCER_PREVIEW'], default 'SEQUENCER'

zoom

Display zoom level

Type float in [-inf, inf], default 0.0

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.503 SpaceTextEditor(Space)

base classes — `bpy_struct`, `Space`

class bpy.types.SpaceTextEditor(Space)

Text editor space data

find_text

Text to search for with the find tool

Type string, default ""

font_size

Font size to use for displaying the text

Type int in [8, 32], default 0

margin_column
Column number to show right margin at

Type int in [0, 1024], default 0

replace_text
Text to replace selected text with using the replace tool

Type string, default ""

show_line_highlight
Highlight the current line

Type boolean, default False

show_line_numbers
Show line numbers next to the text

Type boolean, default False

show_margin
Show right margin

Type boolean, default False

show_syntax_highlight
Syntax highlight for scripting

Type boolean, default False

show_word_wrap
Wrap words if there is not enough horizontal space

Type boolean, default False

tab_width
Number of spaces to display tabs with

Type int in [2, 8], default 0

text
Text displayed and edited in this space

Type Text

use_find_all
Search in all text datablocks, instead of only the active one

Type boolean, default False

use_find_wrap
Search again from the start of the file when reaching the end

Type boolean, default False

use_live_edit
Run python while editing

Type boolean, default False

use_match_case
Search string is sensitive to uppercase and lowercase letters

Type boolean, default False

use_overwrite

Overwrite characters when typing rather than inserting them

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.504 SpaceTimeline(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceTimeline (Space)

Timeline editor space data

cache_cloth

Show the active object's cloth point cache

Type boolean, default False

cache_particles

Show the active object's particle point cache

Type boolean, default False

cache_smoke

Show the active object's smoke cache

Type boolean, default False

cache_softbody

Show the active object's softbody point cache

Type boolean, default False

show_cache

Show the status of cached frames in the timeline

Type boolean, default False

show_frame_indicator

Show frame number beside the current frame indicator line

Type boolean, default False

show_only_selected

Show keyframes for active Object and/or its selected channels only

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.505 SpaceUVEditor(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.SpaceUVEditor(bpy_struct)`

UV editor data for the image editor space

cursor_location

2D cursor location for this view

Type float array of 2 items in [-inf, inf], default (0.0, 0.0)

draw_stretch_type

Type of stretch to draw

Type enum in ['ANGLE', 'AREA'], default 'ANGLE'

edge_draw_type

Draw type for drawing UV edges

Type enum in ['OUTLINE', 'DASH', 'BLACK', 'WHITE'], default 'OUTLINE'

lock_bounds

Constraint to stay within the image bounds while editing

Type boolean, default False

pivot_point

Rotation/Scaling Pivot

Type enum in ['CENTER', 'MEDIAN', 'CURSOR'], default 'CENTER'

show_faces

Draw faces over the image

Type boolean, default False

show_modified_edges

Draw edges after modifiers are applied

Type boolean, default False

show_normalized_coords

Display UV coordinates from 0.0 to 1.0 rather than in pixels

Type boolean, default False

show_other_objects

Draw other selected objects that share the same image

Type boolean, default False

show_smooth_edges

Draw UV edges anti-aliased

Type boolean, default False

show_stretch

Draw faces colored according to the difference in shape between UVs and their 3D coordinates (blue for low distortion, red for high distortion)

Type boolean, default False

sticky_select_mode

Automatically select also UVs sharing the same vertex as the ones being selected

Type enum in ['DISABLED', 'SHARED_LOCATION', 'SHARED_VERTEX'], default 'SHARED_LOCATION'

use_live_unwrap

Continuously unwrap the selected UV island while transforming pinned vertices

Type boolean, default False

use_snap_to_pixels

Snap UVs to pixel locations while editing

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- SpaceImageEditor.uv_editor

2.4.506 SpaceUserPreferences(Space)

base classes — bpy_struct, Space

class bpy.types.SpaceUserPreferences (Space)
User preferences space data

filter_text
Search term for filtering in the UI

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Space.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.507 SpaceView3D(Space)

base classes — `bpy_struct`, `Space`

class bpy.types.SpaceView3D (Space)
3D View space data

background_images

List of background images

Type `bpy_prop_collection` of `BackgroundImage`, (readonly)

camera

Active camera used in this view (when unlocked from the scene's active camera)

Type `Object`

clip_end

3D View far clipping distance

Type float in [1, inf], default 0.0

clip_start

3D View near clipping distance

Type float in [0.001, inf], default 0.0

current_orientation

Current Transformation orientation

Type `TransformOrientation`, (readonly)

cursor_location

3D cursor location for this view (dependent on local view setting)

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid_lines

The number of grid lines to display in perspective view

Type int in [0, 1024], default 0

grid_scale

The distance between 3D View grid lines

Type float in [0, inf], default 0.0

grid_subdivisions

The number of subdivisions between grid lines

Type int in [1, 1024], default 0

layers

Layers visible in this 3D View

Type boolean array of 20 items, default (False, False, False)

layers_used

Layers that contain something

Type boolean array of 20 items, default (False, False, False), (readonly)

lens

Lens angle (mm) in perspective view

Type float in [1, 250], default 0.0

local_view

Display an isolated sub-set of objects, apart from the scene visibility

Type SpaceView3D, (readonly)

lock_bone

3D View center is locked to this bone's position

Type string, default “”

lock_camera

Enable view navigation within the camera view

Type boolean, default False

lock_camera_and_layers

Use the scene's active camera and layers in this view, rather than local layers

Type boolean, default False

lock_cursor

3D View center is locked to the cursor's position

Type boolean, default False

lock_object

3D View center is locked to this object's position

Type Object

pivot_point

Pivot center for rotation/scaling

Type enum in ['BOUNDING_BOX_CENTER', 'CURSOR', 'INDIVIDUAL_ORIGINS', 'MEDIAN_POINT', 'ACTIVE_ELEMENT'], default 'BOUNDING_BOX_CENTER'

region_3d

3D region in this space, in case of quad view the camera region

Type RegionView3D, (readonly)

region_quadview

3D region that defines the quad view settings

Type RegionView3D, (readonly)

show_all_objects_origin

Show the object origin center dot for all (selected and unselected) objects

Type boolean, default False

show_axis_x
Show the X axis line in perspective view

Type boolean, default False

show_axis_y
Show the Y axis line in perspective view

Type boolean, default False

show_axis_z
Show the Z axis line in perspective view

Type boolean, default False

show_background_images
Display reference images behind objects in the 3D View

Type boolean, default False

show_floor
Show the ground plane grid in perspective view

Type boolean, default False

show_manipulator
Use a 3D manipulator widget for controlling transforms

Type boolean, default False

show_only_render
Display only objects which will be rendered

Type boolean, default False

show_outline_selected
Show an outline highlight around selected objects in non-wireframe views

Type boolean, default False

show_relationship_lines
Show dashed lines indicating parent or constraint relationships

Type boolean, default False

show_textured_solid
Display face-assigned textures in solid view

Type boolean, default False

transform_orientation
Transformation orientation

Type enum in ['GLOBAL', 'LOCAL', 'GIMBAL', 'NORMAL', 'VIEW', 'CUSTOM'], default 'GLOBAL'

use_manipulator_rotate
Use the manipulator for rotation transformations

Type boolean, default False

use_manipulator_scale
Use the manipulator for scale transformations

Type boolean, default False

use_manipulator_translate

Use the manipulator for movement transformations

Type boolean, default False

use_occlude_geometry

Limit selection to visible (clipped with depth buffer)

Type boolean, default False

use_pivot_point_align

Manipulate object centers only

Type boolean, default False

viewport_shade

Method to display/shade objects in the 3D View

Type enum in ['BOUNDBOX', 'WIREFRAME', 'SOLID', 'TEXTURED'], default 'BOUNDBOX'

Inherited Properties

- `bpy_struct.id_data`
- `Space.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ObjectBase.layers_from_view`
- `SpaceView3D.local_view`

2.4.508 SpeedControlSequence(EffectSequence)

base classes — `bpy_struct`, `Sequence`, `EffectSequence`

```
class bpy.types.SpeedControlSequence(EffectSequence)
    Sequence strip to control the speed of other strips

    multiply_speed
        Multiply the resulting speed after the speed factor
        Type float in [0, inf], default 0.0

    scale_to_length
        Scale values from 0.0 to 1.0 to target sequence length
        Type boolean, default False

    use_as_speed
        Interpret the value as speed instead of a frame number
        Type boolean, default False

    use_frame_blend
        Blend two frames into the target for a smoother result
        Type boolean, default False
```

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames

- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.509 Spline(bpy_struct)

base class — `bpy_struct`

class `bpy.types.Spline(bpy_struct)`

Element of a curve, either Nurbs, Bezier or Polyline or a character with text objects

bezier_points

Collection of points for Bezier curves only

Type `SplineBezierPoints` `bpy_prop_collection` of `BezierSplinePoint`,
(readonly)

character_index

Location of this character in the text data (only for text curves)

Type int in [0, inf], default 0, (readonly)

hide
Hide this curve in editmode
Type boolean, default False

material_index
Type int in [0, 32767], default 0

order_u
Nurbs order in the U direction (For splines and surfaces), Higher values let points influence a greater area
Type int in [2, 6], default 0

order_v
Nurbs order in the V direction (For surfaces only), Higher values let points influence a greater area
Type int in [2, 6], default 0

point_count_u
Total number points for the curve or surface in the U direction
Type int in [0, 32767], default 0, (readonly)

point_count_v
Total number points for the surface on the V direction
Type int in [0, 32767], default 0, (readonly)

points
Collection of points that make up this poly or nurbs spline
Type SplinePoints bpy_prop_collection of SplinePoint, (readonly)

radius_interpolation
The type of radius interpolation for Bezier curves
Type enum in ['LINEAR', 'CARDINAL', 'BSPLINE', 'EASE'], default 'LINEAR'

resolution_u
Curve or Surface subdivisions per segment
Type int in [1, 32767], default 0

resolution_v
Surface subdivisions per segment
Type int in [1, 32767], default 0

tilt_interpolation
The type of tilt interpolation for 3D, Bezier curves
Type enum in ['LINEAR', 'CARDINAL', 'BSPLINE', 'EASE'], default 'LINEAR'

type
The interpolation type for this curve element
Type enum in ['POLY', 'BEZIER', 'BSPLINE', 'CARDINAL', 'NURBS'], default 'POLY'

use_bezier_u
Make this nurbs curve or surface act like a Bezier spline in the U direction (Order U must be 3 or 4, Cyclic U must be disabled)
Type boolean, default False

use_bezier_v

Make this nurbs surface act like a Bezier spline in the V direction (Order V must be 3 or 4, Cyclic V must be disabled)

Type boolean, default False

use_cyclic_u

Make this curve or surface a closed loop in the U direction

Type boolean, default False

use_cyclic_v

Make this surface a closed loop in the V direction

Type boolean, default False

use_endpoint_u

Make this nurbs curve or surface meet the endpoints in the U direction (Cyclic U must be disabled)

Type boolean, default False

use_endpoint_v

Make this nurbs surface meet the endpoints in the V direction (Cyclic V must be disabled)

Type boolean, default False

use_smooth

Smooth the normals of the surface or beveled curve

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Curve.splines

- `CurveSplines.new`
- `CurveSplines.remove`

2.4.510 SplineBezierPoints(bpy_struct)

base class — `bpy_struct`

class `bpy.types.SplineBezierPoints` (*bpy_struct*)

Collection of spline bezirt points

add (*count=1*)

Add a number of points to this spline.

Parameters `count` (*int in [-inf, inf], (optional)*) – Number, Number of points to add to the spline

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Spline.bezier_points`

2.4.511 SplineIKConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class `bpy.types.SplineIKConstraint` (*Constraint*)

Align ‘n’ bones along a curve

chain_count

How many bones are included in the chain

Type int in [1, 255], default 0

joint_bindings

(EXPERIENCED USERS ONLY) The relative positions of the joints along the chain as percentages

Type float array of 32 items in [0, 1], default (0.0, 0.0)

target

Curve that controls this relationship

Type Object

use_chain_offset

Offset the entire chain relative to the root joint

Type boolean, default False

use_curve_radius

Average radius of the endpoints is used to tweak the X and Z Scaling of the bones, on top of XZ Scale mode

Type boolean, default False

use_even_divisions

Ignore the relative lengths of the bones when fitting to the curve

Type boolean, default False

use_y_stretch

Stretch the Y axis of the bones to fit the curve

Type boolean, default False

xz_scale_mode

Method used for determining the scaling of the X and Z axes of the bones

Type enum in ['NONE', 'BONE_ORIGINAL', 'VOLUME_PRESERVE'], default 'NONE'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.512 SplinePoint(bpy_struct)

base class — `bpy_struct`

class `bpy.types.SplinePoint` (`bpy_struct`)
Spline point without handles

co
Point coordinates
Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

hide
Visibility status
Type boolean, default False

radius
Radius for bevelling
Type float in [0, inf], default 0.0

select
Selection status
Type boolean, default False

tilt
Tilt in 3D View
Type float in [-inf, inf], default 0.0

weight
Nurbs weight
Type float in [-inf, inf], default 0.0

weight_softbody
Softbody goal weight
Type float in [0.01, 100], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Spline.points`

2.4.513 SplinePoints(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.SplinePoints(bpy_struct)`
Collection of spline points

add (`count=1`)

Add a number of points to this spline.

Parameters `count` (`int in [1, inf], (optional)`) – Number, Number of points to add to the spline

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`

- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Spline.points

2.4.514 SpotLamp(Lamp)

base classes — bpy_struct, ID, Lamp

class bpy.types.SpotLamp (Lamp)

Directional cone lamp

compression_threshold

Deep shadow map compression threshold

Type float in [0, 1], default 0.0

falloff_curve

Custom Lamp Falloff Curve

Type CurveMapping, (readonly)

falloff_type

Intensity Decay with distance

Type enum in ['CONSTANT', 'INVERSE_LINEAR', 'INVERSE_SQUARE', 'CUSTOM_CURVE', 'LINEAR_QUADRATIC_WEIGHTED'], default 'CONSTANT'

halo_intensity

Brightness of the spotlight's halo cone

Type float in [-inf, inf], default 0.0

halo_step

Volumetric halo sampling frequency

Type int in [0, 12], default 0

linear_attenuation

Linear distance attenuation

Type float in [0, 1], default 0.0

quadratic_attenuation

Quadratic distance attenuation

Type float in [0, 1], default 0.0

shadow_adaptive_threshold

Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_buffer_bias

Shadow buffer sampling bias

Type float in [0.001, 5], default 0.0

shadow_buffer_clip_end

Shadow map clip end beyond which objects will not generate shadows

Type float in [0, 9999], default 0.0

shadow_buffer_clip_start

Shadow map clip start: objects closer will not generate shadows

Type float in [0, 9999], default 0.0

shadow_buffer_samples

Number of shadow buffer samples

Type int in [1, 16], default 0

shadow_buffer_size

Resolution of the shadow buffer, higher values give crisper shadows but use more memory

Type int in [512, 10240], default 0

shadow_buffer_soft

Size of shadow buffer sampling area

Type float in [0, 100], default 0.0

shadow_buffer_type

Type of shadow buffer

Type enum in ['REGULAR', 'HALFWAY', 'IRREGULAR', 'DEEP'], default 'REGULAR'

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_filter_type

Type of shadow filter (Buffer Shadows)

Type enum in ['BOX', 'TENT', 'GAUSS'], default 'BOX'

shadow_method

Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'BUFFER_SHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method

Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples

Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_sample_buffers

Number of shadow buffers to render for better AA, this increases memory usage

Type enum in ['BUFFERS_1', 'BUFFERS_4', 'BUFFERS_9'], default 'BUFFERS_1'

shadow_soft_size

Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

show_cone

Draw transparent cone in 3D view to visualize which objects are contained in it

Type boolean, default False

spot_blend

The softness of the spotlight edge

Type float in [0, 1], default 0.0

spot_size

Angle of the spotlight beam in degrees

Type float in [0.0174533, 3.14159], default 0.0

use_auto_clip_end

Automatic calculation of clipping-end, based on visible vertices

Type boolean, default False

use_auto_clip_start

Automatic calculation of clipping-start, based on visible vertices

Type boolean, default False

use_halo

Renders spotlight with a volumetric halo

Type boolean, default False

use_only_shadow

Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer

Causes only objects on the same layer to cast shadows

Type boolean, default False

use_sphere

Sets light intensity to zero beyond lamp distance

Type boolean, default False

use_square

Casts a square spot light shape

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color

- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.515 StateActuator(Actuator)

base classes — bpy_struct, Actuator

class bpy.types.StateActuator(Actuator)

Actuator to handle states

operation

Select the bit operation on object state mask

Type enum in ['SET', 'ADD', 'REMOVE', 'CHANGE'], default 'SET'

states

Type boolean array of 30 items, default (False, False, False)

Inherited Properties

- bpy_struct.id_data

- `Actuator.name`
- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.516 StretchToConstraint(Constraint)

base classes — `bpy_struct, Constraint`

class `bpy.types.StretchToConstraint (Constraint)`

Stretches to meet the target object

bulge

Factor between volume variation and stretching

Type float in [0, 100], default 0.0

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

keep_axis

Axis to maintain during stretch

Type enum in ['PLANE_X', 'PLANE_Z'], default 'PLANE_X'

rest_length

Length at rest position

Type float in [0, 100], default 0.0

subtarget

Type string, default ""

target

Target Object

Type Object

volume

Maintain the object's volume as it stretches

Type enum in ['VOLUME_XZX', 'VOLUME_X', 'VOLUME_Z', 'NO_VOLUME'], default 'VOLUME_XZX'

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.517 StringProperty(Property)

base classes — bpy_struct, Property

class bpy.types.StringProperty(*Property*)
RNA text string property definition

default

string default value

Type string, default "", (readonly)

length_max

Maximum length of the string, 0 means unlimited

Type int in [0, inf], default 0, (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Property.name`
- `Property.srna`
- `Property.description`
- `Property.is_enum_flag`
- `Property.is_hidden`
- `Property.identifier`
- `Property.is_never_none`
- `Property.is_readonly`
- `Property.is_registered`
- `Property.is_registered_optional`
- `Property.is_required`
- `Property.is_output`
- `Property.is_runtime`
- `Property.is_skip_save`
- `Property.subtype`
- `Property.type`
- `Property.unit`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Struct.name_property`

2.4.518 Struct(bpy_struct)

base class — `bpy_struct`

class `bpy.types.Struct` (`bpy_struct`)

RNA structure definition

base

Struct definition this is derived from

Type `Struct`, (readonly)

description

Description of the Struct's purpose

Type `string`, default “”, (readonly)

functions

Type `bpy_prop_collection` of `Function`, (readonly)

identifier

Unique name used in the code and scripting

Type `string`, default “”, (readonly)

name

Human readable name

Type `string`, default “”, (readonly)

name_property

Property that gives the name of the struct

Type `StringProperty`, (readonly)

nested

Struct in which this struct is always nested, and to which it logically belongs

Type `Struct`, (readonly)

properties

Properties in the struct

Type `bpy_prop_collection` of `Property`, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`

- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- BlenderRNA.structs
- CollectionProperty.fixed_type
- PointerProperty.fixed_type
- Property.srna
- Struct.base
- Struct.nested

2.4.519 StucciTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.StucciTexture (Texture)
Procedural noise texture

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN',
'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4',
'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default
'BLENDER_ORIGINAL'

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

stucci_type

Type enum in ['PLASTIC', 'WALL_IN', 'WALL_OUT'], default 'PLASTIC'

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.520 SubsurfModifier(Modifier)

base classes — `bpy_struct`, `Modifier`

class bpy.types.SubsurfModifier(*Modifier*)
Subdivision surface modifier

levels
Number of subdivisions to perform
Type int in [0, 32767], default 0

render_levels
Number of subdivisions to perform when rendering
Type int in [0, 32767], default 0

show_only_control_edges
Skip drawing/rendering of interior subdivided edges
Type boolean, default False

subdivision_type
Selects type of subdivision algorithm
Type enum in ['CATMULL_CLARK', 'SIMPLE'], default 'CATMULL_CLARK'

use_subsurf_uv
Use subsurf to subdivide UVs
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Modifier.name`
- `Modifier.use_apply_on_spline`
- `Modifier.show_in_editmode`
- `Modifier.show_expanded`
- `Modifier.show_on_cage`
- `Modifier.show_viewport`
- `Modifier.show_render`
- `Modifier.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.521 SunLamp(Lamp)

base classes — `bpy_struct`, `ID`, `Lamp`

class bpy.types.SunLamp (Lamp)

Constant direction parallel ray lamp

shadow_adaptive_threshold

Threshold for Adaptive Sampling (Raytraced shadows)

Type float in [0, 1], default 0.0

shadow_color

Color of shadows cast by the lamp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadow_method

Method to compute lamp shadow with

Type enum in ['NOSHADOW', 'RAY_SHADOW'], default 'NOSHADOW'

shadow_ray_sample_method

Method for generating shadow samples: Adaptive QMC is fastest, Constant QMC is less noisy but slower

Type enum in ['ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'ADAPTIVE_QMC'

shadow_ray_samples

Amount of samples taken extra (samples x samples)

Type int in [1, 64], default 0

shadow_soft_size

Light size for ray shadow sampling (Raytraced shadows)

Type float in [-inf, inf], default 0.0

sky

Sky related settings for sun lamps

Type `LampSkySettings`, (readonly, never None)

use_only_shadow

Causes light to cast shadows only without illuminating objects

Type boolean, default False

use_shadow_layer

Causes only objects on the same layer to cast shadows

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`

- ID.library
- ID.tag
- ID.users
- Lamp.active_texture
- Lamp.active_texture_index
- Lamp.animation_data
- Lamp.color
- Lamp.use_diffuse
- Lamp.distance
- Lamp.energy
- Lamp.use_own_layer
- Lamp.use_negative
- Lamp.use_specular
- Lamp.texture_slots
- Lamp.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.522 SurfaceCurve(Curve)

base classes — bpy_struct, ID, Curve

class bpy.types.SurfaceCurve (*Curve*)
Curve datablock used for storing surfaces

use_uv_as_generated
Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Curve.animation_data
- Curve.use_auto_texspace
- Curve.use_fill_back
- Curve.bevel_depth
- Curve.bevel_object
- Curve.bevel_resolution
- Curve.use_deform_bounds
- Curve.dimensions
- Curve.show_handles
- Curve.show_normal_face
- Curve.eval_time
- Curve.extrude
- Curve.use_fill_deform
- Curve.use_path_follow
- Curve.use_fill_front
- Curve.materials
- Curve.offset
- Curve.use_time_offset
- Curve.use_path
- Curve.path_duration
- Curve.use_radius
- Curve.render_resolution_u
- Curve.render_resolution_v
- Curve.resolution_u
- Curve.resolution_v
- Curve.shape_keys
- Curve.splines
- Curve.use_stretch
- Curve.taper_object
- Curve.texspace_location
- Curve.texspace_size
- Curve.twist_mode
- Curve.twist_smooth
- Curve.use_uv_as_generated

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set

- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.523 SurfaceModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.SurfaceModifier(*Modifier*)
Surface modifier defining modifier stack position used for surface fields

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.524 TexMapping(bpy_struct)

base class — [bpy_struct](#)

class bpy.types.TexMapping (bpy_struct)
Mapping settings

location
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

max
Maximum value for clipping
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

min
Minimum value for clipping
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

rotation
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scale
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

use_max
Whether to use maximum clipping value
Type boolean, default False

use_min
Whether to use minimum clipping value
Type boolean, default False

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)

- `bpy_struct.values`

2.4.525 Text(ID)

base classes — `bpy_struct, ID`

class bpy.types.Text (ID)

Text datablock referencing an external or packed text file

current_character

Index of current character in current line, and also start index of character in selection if one exists

Type int in [0, inf], default 0, (readonly)

current_line

Current line, and start line of selection if one exists

Type `TextLine`, (readonly, never None)

filepath

Filename of the text file

Type string, default “”

is_dirty

Text file has been edited since last save

Type boolean, default False, (readonly)

is_in_memory

Text file is in memory, without a corresponding file on disk

Type boolean, default False, (readonly)

is_modified

Text file on disk is different than the one in memory

Type boolean, default False, (readonly)

lines

Lines of text

Type `bpy_prop_collection` of `TextLine`, (readonly)

markers

Text markers highlighting part of the text

Type `bpy_prop_collection` of `TextMarker`, (readonly)

select_end_character

Index of character after end of selection in the selection end line

Type int in [0, inf], default 0, (readonly)

select_end_line

End line of selection

Type `TextLine`, (readonly, never None)

use_module

Register this text as a module on loading, Text name must end with “.py”

Type boolean, default False

use_tabs_as_spaces

Automatically converts all new tabs into spaces

Type boolean, default False

users_logic

Logic bricks that use this text (readonly)

clear()

clear the text block.

write(*text*)

write text at the cursor location and advance to the end of the text block.

Parameters *text* (*string*) – New text for this datablock.

static as_string(*self*)

Return the text as a string.

from_string(*string*)

Replace text with this string.

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.texts
- BlendDataTexts.load
- BlendDataTexts.new
- BlendDataTexts.remove
- Filter2DActuator.gsl_shader
- PythonConstraint.text
- PythonController.text
- SceneGameData.dome_text
- SpaceTextEditor.text

2.4.526 TextBox(bpy_struct)

base class — `bpy_struct`

```
class bpy.types.TextBox(bpy_struct)
    Text bounding box for layout

    height
        Type float in [0, 50], default 0.0

    width
        Type float in [0, 50], default 0.0

    x
        Type float in [-50, 50], default 0.0

    y
        Type float in [-50, 50], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `TextCurve.text_boxes`

2.4.527 TextCharacterFormat(`bpy_struct`)

base class — `bpy_struct`

```
class bpy.types.TextCharacterFormat (bpy_struct)
    Text character formatting settings

    use_bold
        Type boolean, default False

    use_italic
        Type boolean, default False

    use_small_caps
        Type boolean, default False

    use_underline
        Type boolean, default False
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `TextCurve.body_format`
- `TextCurve.edit_format`

2.4.528 `TextCurve(Curve)`

base classes — `bpy_struct`, `ID`, `Curve`

class `bpy.types.TextCurve(Curve)`

Curve datablock used for storing text

active_textbox

Type int in [-inf, inf], default 0

align

Text align from the object center

Type enum in ['LEFT', 'CENTER', 'RIGHT', 'JUSTIFY', 'FLUSH'], default 'LEFT'

body

contents of this text object

Type string, default ""

body_format

Stores the style of each character

Type `bpy_prop_collection` of `TextCharacterFormat`, (readonly)

edit_format

Editing settings character formatting

Type `TextCharacterFormat`, (readonly)

family

Use Blender Objects as font characters. Give font objects a common name followed by the character it represents, eg. familya, familyb etc, and turn on Verts Duplication

Type string, default ""

follow_curve

Curve deforming text object

Type `Object`

font

Type `VectorFont`

font_bold

Type `VectorFont`

font_bold_italic

Type `VectorFont`

font_italic

Type `VectorFont`

offset_x

Horizontal offset from the object origin

Type float in [-50, 50], default 0.0

offset_y
Vertical offset from the object origin

Type float in [-50, 50], default 0.0

shear
Italic angle of the characters

Type float in [-1, 1], default 0.0

size

Type float in [0.0001, 10000], default 0.0

small_caps_scale
Scale of small capitals

Type float in [-inf, inf], default 0.0

space_character

Type float in [0, 10], default 0.0

space_line

Type float in [0, 10], default 0.0

space_word

Type float in [0, 10], default 0.0

text_boxes

Type bpy_prop_collection of TextBox, (readonly)

underline_height

Type float in [-0.2, 0.8], default 0.0

underline_position
Vertical position of underline

Type float in [-0.2, 0.8], default 0.0

use_fast_edit
Don't fill polygons while editing

Type boolean, default False

use_uv_as_generated
Uses the UV values as Generated textured coordinates

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Curve.animation_data

- `Curve.use_auto_texspace`
- `Curve.use_fill_back`
- `Curve.bevel_depth`
- `Curve.bevel_object`
- `Curve.bevel_resolution`
- `Curve.use_deform_bounds`
- `Curve.dimensions`
- `Curve.show_handles`
- `Curve.show_normal_face`
- `Curve.eval_time`
- `Curve.extrude`
- `Curve.use_fill_deform`
- `Curve.use_path_follow`
- `Curve.use_fill_front`
- `Curve.materials`
- `Curve.offset`
- `Curve.use_time_offset`
- `Curve.use_path`
- `Curve.path_duration`
- `Curve.use_radius`
- `Curve.render_resolution_u`
- `Curve.render_resolution_v`
- `Curve.resolution_u`
- `Curve.resolution_v`
- `Curve.shape_keys`
- `Curve.splines`
- `Curve.use_stretch`
- `Curve.taper_object`
- `Curve.texspace_location`
- `Curve.texspace_size`
- `Curve.twist_mode`
- `Curve.twist_smooth`
- `Curve.use_uv_as_generated`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`

- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.529 TextLine(bpy_struct)

base class — bpy_struct

class bpy.types.TextLine (*bpy_struct*)
Line of text in a Text datablock

body

Text in the line

Type string, default “”

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Text.current_line
- Text.lines
- Text.select_end_line

2.4.530 TextMarker(bpy_struct)

base class — bpy_struct

class bpy.types.TextMarker (*bpy_struct*)
Marker highlighting a portion of text in a Text datablock

character_index_end

Start position of the marker in the line

Type int in [0, inf], default 0, (readonly)

character_index_start

Start position of the marker in the line

Type int in [0, inf], default 0, (readonly)

color

Color to display the marker with

Type float array of 4 items in [0, 1], default (0.0, 0.0, 0.0, 0.0)

group

Type int in [0, 65535], default 0, (readonly)

is_temporary

Marker is temporary

Type boolean, default False, (readonly)

line

Line in which the marker is located

Type int in [0, inf], default 0, (readonly)

use_edit_all

Edit all markers of the same group as one

Type boolean, default False, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- `Text.markers`

2.4.531 Texture(ID)

base classes — `bpy_struct, ID`

subclasses — `ImageTexture, MarbleTexture, EnvironmentMapTexture, PointDensityTexture, VoxelDataTexture, BlendTexture, MusgraveTexture, StucciTexture, VoronoiTexture, MagicTexture, PluginTexture, WoodTexture, CloudsTexture, DistortedNoiseTexture, NoiseTexture`

class bpy.types.Texture(ID)

Texture datablock used by materials, lamps, worlds and brushes

animation_data

Animation data for this datablock

Type `AnimData, (readonly)`

color_ramp

Type `ColorRamp, (readonly)`

contrast

Adjusts the contrast of the texture

Type float in [0.01, 5], default 0.0

factor_blue

Type float in [0, 2], default 0.0

factor_green

Type float in [0, 2], default 0.0

factor_red

Type float in [0, 2], default 0.0

intensity

Adjusts the brightness of the texture

Type float in [0, 2], default 0.0

node_tree

Node tree for node-based textures

Type `NodeTree, (readonly)`

saturation

Adjusts the saturation of colors in the texture

Type float in [0, 2], default 0.0

type

Type enum in ['NONE', 'BLEND', 'CLOUDS', 'DISTORTED_NOISE', 'ENVIRONMENT_MAP', 'IMAGE', 'MAGIC', 'MARBLE', 'MUSGRAVE', 'NOISE', 'POINT_DENSITY', 'STUCCI', 'VORONOI', 'VOXEL_DATA', 'WOOD'], default 'NONE'

use_color_ramp
Toggle color ramp operations

Type boolean, default False

use_nodes
Make this a node-based texture

Type boolean, default False

use_preview_alpha
Show Alpha in Preview Render

Type boolean, default False

users_material
Materials that use this texture (readonly)

users_object_modifier
Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

References

- BlendData.textures
- BlendDataTextures.new
- BlendDataTextures.remove
- Brush.texture
- CompositorNodeTexture.texture
- DisplaceModifier.texture
- FieldSettings.texture
- Lamp.active_texture
- Material.active_texture
- ParticleSettings.active_texture
- ShaderNodeTexture.texture
- TextureNodeTexture.texture
- TextureSlot.texture
- WarpModifier.texture
- WaveModifier.texture
- World.active_texture

2.4.532 TextureNode(Node)

base classes — `bpy_struct, Node`

subclasses — `TextureNodeScale, TextureNodeRGBToBW, TextureNodeTranslate, TextureNodeTexture, TextureNodeCompose, TextureNodeValToNor, TextureNodeDecompose, TextureNodeHueSaturation, TextureNodeImage, TextureNodeBricks, TextureNodeCurveTime, TextureNodeInvert, TextureNodeCurveRGB, TextureNodeDistance, TextureNodeRotate, TextureNodeMixRGB, TextureNodeChecker, TextureNodeOutput, TextureNodeCoordinates, TextureNodeValToRGB, TextureNodeMath, TextureNodeViewer`

`class bpy.types.TextureNode (Node)`

`type`

Type enum in ['OUTPUT', 'CHECKER', 'TEXTURE', 'BRICKS', 'MATH', 'MIX_RGB', 'RGBTOBW', 'VALTORGB', 'IMAGE', 'CURVE_RGB', 'INVERT', 'HUE_SAT', 'CURVE_TIME', 'ROTATE', 'VIEWER', 'TRANSLATE', 'COORD', 'DISTANCE', 'COMPOSE', 'DECOMPOSE', 'VALTONOR', 'SCALE', 'SCRIPT', 'GROUP'], default 'OUTPUT', (readonly)

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`

Inherited Functions

- `bpy_struct.as_pointer`

- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.533 TextureNodeBricks(*TextureNode*)

base classes — `bpy_struct`, `Node`, `TextureNode`

class `bpy.types.TextureNodeBricks` (*TextureNode*)

offset

Type float in [0, 1], default 0.0

offset_frequency

Offset every N rows

Type int in [2, 99], default 0

squash

Type float in [0, 99], default 0.0

squash_frequency

Squash every N rows

Type int in [2, 99], default 0

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`

- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.534 TextureNodeChecker(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeChecker (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.535 TextureNodeCompose(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeCompose (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.536 TextureNodeCoordinates(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeCoordinates (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.537 TextureNodeCurveRGB(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeCurveRGB (TextureNode)`

`mapping`

Type `CurveMapping, (readonly)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.538 TextureNodeCurveTime(TextureNode)

base classes — bpy_struct, Node, TextureNode

```
class bpy.types.TextureNodeCurveTime (TextureNode)
```

curve

Type CurveMapping, (readonly)

frame_end

Type int in [-32768, 32767], default 0

frame_start

Type int in [-32768, 32767], default 0

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.539 TextureNodeDecompose(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeDecompose (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.540 TextureNodeDistance(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeDistance (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.541 TextureNodeHueSaturation(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeHueSaturation (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.542 TextureNodeImage(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeImage (TextureNode)`

image

Type `Image`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.543 TextureNodeInvert(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeInvert (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.544 TextureNodeMath(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeMath (TextureNode)`

`operation`

Type enum in ['ADD', 'SUBTRACT', 'MULTIPLY', 'DIVIDE', 'SINE', 'COSINE', 'TANGENT', 'ARCSINE', 'ARCCOSINE', 'ARCTANGENT', 'POWER', 'LOGARITHM', 'MINIMUM', 'MAXIMUM', 'ROUND', 'LESS_THAN', 'GREATER_THAN'], default 'ADD'

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.545 TextureNodeMixRGB(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeMixRGB (TextureNode)`

`blend_type`

Type enum in ['MIX', 'ADD', 'MULTIPLY', 'SUBTRACT', 'SCREEN', 'DIVIDE', 'DIFFERENCE', 'DARKEN', 'LIGHTEN', 'OVERLAY', 'DODGE', 'BURN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

`use_alpha`

Include alpha of second input in this operation

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.546 TextureNodeOutput(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeOutput (TextureNode)`

`filepath`

Type string, default “”

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.547 TextureNodeRGBToBW(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeRGBToBW (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.548 TextureNodeRotate(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeRotate (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.549 TextureNodeScale(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeScale (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.550 TextureNodeTexture(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeTexture (TextureNode)`

`node_output`

For node-based textures, which output node to use

Type int in [-32768, 32767], default 0

`texture`

Type Texture

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.551 TextureNodeTranslate(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeTranslate (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.552 TextureNodeTree(NodeTree)

base classes — `bpy_struct, ID, NodeTree`

class `bpy.types.TextureNodeTree (NodeTree)`

Node tree consisting of linked nodes used for textures

nodes

Type `TextureNodes bpy_prop_collection of Node, (readonly)`

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`
- `NodeTree.animation_data`
- `NodeTree.grease_pencil`
- `NodeTree.inputs`
- `NodeTree.links`

- `NodeTree.outputs`
- `NodeTree.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.553 TextureNodeValToNor(TextureNode)

base classes — `bpy_struct, Node, TextureNode`

`class bpy.types.TextureNodeValToNor (TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.554 TextureNodeValToRGB(TextureNode)

base classes — bpy_struct, Node, TextureNode

class bpy.types.TextreeNodeValToRGB (TextureNode)

color_ramp

Type ColorRamp, (readonly)

Inherited Properties

- bpy_struct.id_data
- Node.name
- Node.inputs
- Node.label
- Node.location
- Node.outputs
- TextureNode.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.555 TextureNodeViewer(TextureNode)

base classes — `bpy_struct`, `Node`, `TextureNode`

`class bpy.types.TextureNodeViewer(TextureNode)`

Inherited Properties

- `bpy_struct.id_data`
- `Node.name`
- `Node.inputs`
- `Node.label`
- `Node.location`
- `Node.outputs`
- `TextureNode.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.556 TextureNodes(bpy_struct)

base class — `bpy_struct`

`class bpy.types.TextureNodes(bpy_struct)`

Collection of Texture Nodes

`new(type, group=None)`

Add a node to this node tree.

Parameters

- `type` (`enum in ['OUTPUT', 'CHECKER', 'TEXTURE', 'BRICKS', 'MATH', 'MIX_RGB', 'RGBTOBW', 'VALTORGB', 'IMAGE', 'CURVE_RGB', 'INVERT', 'HUE_SAT', 'CURVE_TIME', 'ROTATE', 'VIEWER', 'TRANSLATE', 'COORD', 'DISTANCE', 'COMPOSE', 'DECOMPOSE', 'VALTONOR', 'SCALE', 'SCRIPT', 'GROUP']`) – Type, Type of node to add
- `group` (`NodeTree`, (optional)) – The group tree

Returns New node.

Return type [Node](#)

remove (*node*)

remove a node from this node tree.

Parameters **node** ([Node](#)) – The node to remove.

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [TextureNodeTree.nodes](#)

2.4.557 TextureSlot([bpy_struct](#))

base class — [bpy_struct](#)

subclasses — [ParticleSettingsTextureSlot](#), [MaterialTextureSlot](#), [LampTextureSlot](#), [BrushTextureSlot](#), [WorldTextureSlot](#)

class [bpy.types.TextureSlot](#) (*bpy_struct*)

Texture slot defining the mapping and influence of a texture

blend_type

The mode used to apply the texture

Type enum in ['MIX', 'ADD', 'SUBTRACT', 'MULTIPLY', 'SCREEN', 'OVERLAY', 'DIFFERENCE', 'DIVIDE', 'DARKEN', 'LIGHTEN', 'HUE', 'SATURATION', 'VALUE', 'COLOR', 'SOFT_LIGHT', 'LINEAR_LIGHT'], default 'MIX'

color

The default color for textures that don't return RGB or when RGB to intensity is enabled

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

default_value

Value to use for Ref, Spec, Amb, Emit, Alpha, RayMir, TransLu and Hard

Type float in [-inf, inf], default 0.0

invert

Inverts the values of the texture to reverse its effect

Type boolean, default False

name

Texture slot name

Type string, default "", (readonly)

offset

Fine tunes texture mapping X, Y and Z locations

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

output_node

Which output node to use, for node-based textures

Type enum in ['DUMMY'], default 'DUMMY'

scale

Sets scaling for the texture's X, Y and Z sizes

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

texture

Texture datablock used by this texture slot

Type [Texture](#)

use_rgb_to_intensity

Converts texture RGB values to intensity (gray) values

Type boolean, default False

use_stencil

Use this texture as a blending value on the next texture

Type boolean, default False

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UILayout.template_preview

2.4.558 Theme(bpy_struct)

base class — `bpy_struct`

class `bpy.types.Theme` (`bpy_struct`)

Theme settings defining draw style and colors in the user interface

bone_color_sets

Type `bpy_prop_collection` of `ThemeBoneColorSet`, (readonly, never None)

console

Type `ThemeConsole`, (readonly, never None)

dopesheet_editor

Type `ThemeDopeSheet`, (readonly, never None)

file_browser

Type `ThemeFileBrowser`, (readonly, never None)

graph_editor

Type `ThemeGraphEditor`, (readonly, never None)

image_editor

Type `ThemeImageEditor`, (readonly, never None)

info

Type `ThemeInfo`, (readonly, never None)

logic_editor

Type `ThemeLogicEditor`, (readonly, never None)

name

Name of the theme

Type string, default “”

nla_editor

Type `ThemeNLAEditor`, (readonly, never None)

node_editor

Type ThemeNodeEditor, (readonly, never None)

outliner

Type ThemeOutliner, (readonly, never None)

properties

Type ThemeProperties, (readonly, never None)

sequence_editor

Type ThemeSequenceEditor, (readonly, never None)

text_editor

Type ThemeTextEditor, (readonly, never None)

theme_area

Type enum in ['USER_INTERFACE', 'BONE_COLOR_SETS', 'VIEW_3D', 'TIMELINE', 'GRAPH_EDITOR', 'DOPESHEET_EDITOR', 'NLA_EDITOR', 'IMAGE_EDITOR', 'SEQUENCE_EDITOR', 'TEXT_EDITOR', 'NODE_EDITOR', 'LOGIC_EDITOR', 'PROPERTIES', 'OUTLINER', 'USER_PREFERENCES', 'INFO', 'FILE_BROWSER', 'CONSOLE'], default 'USER_INTERFACE'

timeline

Type ThemeTimeline, (readonly, never None)

user_interface

Type ThemeUserInterface, (readonly, never None)

user_preferences

Type ThemeUserPreferences, (readonly, never None)

view_3d

Type ThemeView3D, (readonly, never None)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys

- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `UserPreferences.themes`

2.4.559 ThemeAudioWindow(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.ThemeAudioWindow(bpy_struct)`

Theme settings for the Audio Window

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

window_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.560 ThemeBoneColorSet(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.ThemeBoneColorSet(bpy_struct)`

Theme settings for bone color sets

active

Color used for active bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

normal

Color used for the surface of bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

select

Color used for selected bones

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

show_colored_constraints

Allow the use of colors indicating constraints/keyed status

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `BoneGroup.colors`
- `Theme.bone_color_sets`

2.4.561 ThemeConsole(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.ThemeConsole (`bpy_struct`)

Theme settings for the Console

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_error

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_info

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_input

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_output

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`

- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.console`

2.4.562 ThemeDopeSheet(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ThemeDopeSheet` (`bpy_struct`)

Theme settings for the DopeSheet

active_channels_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channel_group

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_channel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_subchannel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

long_key

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

long_key_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

value_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.dopesheet_editor`

2.4.563 ThemeFileBrowser(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.ThemeFileBrowser (`bpy_struct`)
Theme settings for the File Browser

active_file
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

active_file_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scroll_handle
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scrollbar
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_file
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

tiles
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`

- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.file_browser`

2.4.564 `ThemeFontStyle(bpy_struct)`

base class — `bpy_struct`

class bpy.types.ThemeFontStyle (bpy_struct)

Theme settings for Font

font_kerning_style

Which style to use for font kerning

Type enum in ['UNFITTED', 'DEFAULT'], default 'UNFITTED'

points

Type int in [6, 48], default 0

shadow

Shadow size in pixels (0, 3 and 5 supported)

Type int in [0, 5], default 0

shadow_offset_x

Shadow offset in pixels

Type int in [-10, 10], default 0

shadow_offset_y

Shadow offset in pixels

Type int in [-10, 10], default 0

shadowalpha

Type float in [0, 1], default 0.0

shadowcolor

Shadow color in grey value

Type float in [0, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`

- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `ThemeStyle.panel_title`
- `ThemeStyle.widget`
- `ThemeStyle.widget_label`

2.4.565 ThemeGraphEditor(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ThemeGraphEditor(bpy_struct)`
Theme settings for the graph editor

active_channels_group
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channel_group
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

channels_region
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_channel
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

dopesheet_subchannel
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_align
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_auto
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_free
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_align
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_auto
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_free
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_vect
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vect
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex_select
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vertex_size
 Type int in [0, 255], default 0

header
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lastsel_point
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_select
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_size
Type int in [1, 10], default 0

window_sliders
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`

- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.graph_editor

2.4.566 ThemelImageEditor(bpy_struct)

base class — `bpy_struct`

class bpy.types.ThemelImageEditor (*bpy_struct*)

Theme settings for the Image Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

editmesh_active

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face_dot

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face_select

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

facedot_size

Type int in [1, 10], default 0

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

```
header_text_hi
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
scope_back
  Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)
text
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
text_hi
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
title
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
vertex
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
vertex_select
  Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
vertex_size
  Type int in [1, 10], default 0
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.image_editor`

2.4.567 ThemeInfo(bpy_struct)

base class — `bpy_struct`

class bpy.types.ThemeInfo (bpy_struct)
Theme settings for Info

back
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- [Theme.info](#)

2.4.568 ThemeLogicEditor(bpy_struct)

base class — bpy_struct

class bpy.types.ThemeLogicEditor (*bpy_struct*)
Theme settings for the Logic Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.logic_editor

2.4.569 ThemeNLAEditor(bpy_struct)

base class — bpy_struct

class bpy.types.ThemeNLAEditor (*bpy_struct*)

Theme settings for the NLA Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bars

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bars_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

strips

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

strips_selected

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

view_sliders

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.nla_editor`

2.4.570 ThemeNodeEditor(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.ThemeNodeEditor (`bpy_struct`)
Theme settings for the Node Editor

back
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

converter_node
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

group_node
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

in_out_node
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

list_title
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nodeBackdrop
 Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

operator_node
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

wire
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

wire_select
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.node_editor`

2.4.571 ThemeOutliner(`bpy_struct`)

base class — `bpy_struct`

`class bpy.types.ThemeOutliner(bpy_struct)`

Theme settings for the Outliner

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.outliner`

2.4.572 ThemeProperties(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.ThemeProperties (`bpy_struct`)

Theme settings for the Properties

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

panel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)

- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.properties`

2.4.573 ThemeSequenceEditor(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ThemeSequenceEditor(bpy_struct)`

Theme settings for the Sequence Editor

audio_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

draw_action

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

effect_strip

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

image_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

keyframe
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

meta_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

movie_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

plugin_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scene_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

transition_strip
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

window_sliders
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.sequence_editor`

2.4.574 `ThemeStyle(bpy_struct)`

base class — `bpy_struct`

class `bpy.types.ThemeStyle(bpy_struct)`

Theme settings for style sets

panel_title

Type `ThemeFontStyle`, (readonly, never None)

widget

Type `ThemeFontStyle`, (readonly, never None)

widget_label

Type `ThemeFontStyle`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `UserPreferences.ui_styles`

2.4.575 ThemeTextEditor(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ThemeTextEditor(bpy_struct)`

Theme settings for the Text Editor

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

cursor

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

line_numbers_background

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

scroll_bar

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

selected_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_builtin

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_comment

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_numbers

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_special

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

syntax_string

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.text_editor`

2.4.576 ThemeTimeline(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.ThemeTimeline(bpy_struct)`

Theme settings for the Timeline

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.timeline

2.4.577 ThemeUserInterface(bpy_struct)

base class — bpy_struct

```
class bpy.types.ThemeUserInterface(bpy_struct)
    Theme settings for user interface elements

    icon_file
        Type string, default ""

    wcol_box
        Type ThemeWidgetColors, (readonly, never None)

    wcol_list_item
        Type ThemeWidgetColors, (readonly, never None)

    wcol_menu
        Type ThemeWidgetColors, (readonly, never None)

    wcol_menu_back
        Type ThemeWidgetColors, (readonly, never None)

    wcol_menu_item
        Type ThemeWidgetColors, (readonly, never None)

    wcol_num
        Type ThemeWidgetColors, (readonly, never None)

    wcol_numslider
        Type ThemeWidgetColors, (readonly, never None)

    wcol_option
        Type ThemeWidgetColors, (readonly, never None)

    wcol_progress
        Type ThemeWidgetColors, (readonly, never None)

    wcol_pulldown
        Type ThemeWidgetColors, (readonly, never None)
```

wcol_radio

Type `ThemeWidgetColors`, (readonly, never None)

wcol_regular

Type `ThemeWidgetColors`, (readonly, never None)

wcol_scroll

Type `ThemeWidgetColors`, (readonly, never None)

wcol_state

Type `ThemeWidgetStateColors`, (readonly, never None)

wcol_text

Type `ThemeWidgetColors`, (readonly, never None)

wcol_toggle

Type `ThemeWidgetColors`, (readonly, never None)

wcol_tool

Type `ThemeWidgetColors`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Theme.user_interface`

2.4.578 ThemeUserPreferences(bpy_struct)

base class — [bpy_struct](#)

class bpy.types.ThemeUserPreferences (bpy_struct)

Theme settings for the User Preferences

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Theme.user_preferences

2.4.579 ThemeView3D(bpy_struct)

base class — bpy_struct

class bpy.types.ThemeView3D (*bpy_struct*)
Theme settings for the 3D View

act_spline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

back

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bone_pose

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

bone_solid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_text_hi

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

button_title

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_creature

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_facesel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_seam

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_select

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

edge_sharp

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

editmesh_active

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

extra_edge_len

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

extra_face_angle

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

extra_face_area

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

face_dot

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

face_select

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

facedot_size

Type int in [1, 10], default 0

frame_current

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

grid

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_align

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_auto

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_free

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_sel_vect
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

handle_vect
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

header_text_hi
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

lamp
 Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

lastsel_point
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

normal
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_sel_uline
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_sel_vline
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_uline
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

nurb_vline
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_active
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_grouped
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_grouped_active
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

object_selected
 Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

outline_width
 Type int in [1, 5], default 0

panel
 Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

text
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_hi
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

title
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

transform
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_normal
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_select
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

vertex_size
Type int in [1, 10], default 0

wire
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- [Theme.view_3d](#)

2.4.580 ThemeWidgetColors(bpy_struct)

base class — `bpy_struct`

class `bpy.types.ThemeWidgetColors` (`bpy_struct`)

Theme settings for widget color sets

inner

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

inner_sel

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

item

Type float array of 4 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0)

outline

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

shadedown

Type int in [-100, 100], default 0

shadetop

Type int in [-100, 100], default 0

show_shaded

Type boolean, default False

text

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

text_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ThemeUserInterface.wcol_box
- ThemeUserInterface.wcol_list_item
- ThemeUserInterface.wcol_menu
- ThemeUserInterface.wcol_menu_back
- ThemeUserInterface.wcol_menu_item
- ThemeUserInterface.wcol_num
- ThemeUserInterface.wcol_numslider
- ThemeUserInterface.wcol_option
- ThemeUserInterface.wcol_progress
- ThemeUserInterface.wcol_pulldown
- ThemeUserInterface.wcol_radio
- ThemeUserInterface.wcol_regular
- ThemeUserInterface.wcol_scroll
- ThemeUserInterface.wcol_text
- ThemeUserInterface.wcol_toggle
- ThemeUserInterface.wcol_tool

2.4.581 ThemeWidgetStateColors(bpy_struct)

base class — bpy_struct

```
class bpy.types.ThemeWidgetStateColors(bpy_struct)
    Theme settings for widget state colors

    blend
        Type float in [0, 1], default 0.0

    inner_anim
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    inner_anim_sel
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    inner_driven
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    inner_driven_sel
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    inner_key
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)
```

inner_key_sel

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ThemeUserInterface.wcol_state

2.4.582 TimelineMarker(bpy_struct)

base class — bpy_struct

class bpy.types.TimelineMarker (*bpy_struct*)

Marker for noting points in the timeline

camera

Camera this timeline sets to active

Type Object

frame

The frame on which the timeline marker appears

Type int in [-inf, inf], default 0

name

Type string, default “”

select

Marker selection state

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Action.pose_markers
- ActionPoseMarkers.active
- ActionPoseMarkers.new
- ActionPoseMarkers.remove
- Scene.timeline_markers
- TimelineMarkers.new
- TimelineMarkers.remove

2.4.583 TimelineMarkers(bpy_struct)

base class — bpy_struct

class bpy.types.TimelineMarkers (*bpy_struct*)
Collection of timeline markers

new (*name*)

Add a keyframe to the curve.

Parameters *name* (*string*) – New name for the marker (not unique).

Returns Newly created timeline marker

Return type TimelineMarker

remove (*marker*)

Remove a timeline marker.

Parameters `marker` (`TimelineMarker`, (never None)) – Timeline marker to remove.

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.timeline_markers`

2.4.584 Timer(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.Timer(bpy_struct)`
Window event timer

time_delta
Time since last step in seconds
Type float in [-inf, inf], default 0.0, (readonly)

time_duration
Time since last step in seconds
Type float in [-inf, inf], default 0.0, (readonly)

time_step
Type float in [-inf, inf], default 0.0, (readonly)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `WindowManager.event_timer_add`
- `WindowManager.event_timer_remove`

2.4.585 ToolSettings(bpy_struct)

base class — `bpy_struct`

`class bpy.types.ToolSettings (bpy_struct)`

`auto_keying_mode`

Mode of automatic keyframe insertion for Objects and Bones

Type enum in ['ADD_REPLACE_KEYS', 'REPLACE_KEYS'], default 'REPLACE_KEYS'
'ADD_REPLACE_KEYS'

`edge_path_live_unwrap`

Changing edges seam re-calculates UV unwrap

Type boolean, default False

`edge_path_mode`

The edge flag to tag when selecting the shortest path

Type enum in ['SELECT', 'SEAM', 'SHARP', 'CREASE', 'BEVEL'], default 'SELECT'

`etch_adaptive_limit`

Number of bones in the subdivided stroke

Type float in [1e-05, 1], default 0.0

`etch_convert_mode`

Method used to convert stroke to bones

Type enum in ['FIXED', 'LENGTH', 'ADAPTIVE', 'RETARGET'], default 'FIXED'

etch_length_limit
Number of bones in the subdivided stroke
Type float in [1e-05, 100000], default 0.0

etch_number
DOC BROKEN
Type string, default “”

etch_roll_mode
Method used to adjust the roll of bones when retargeting
Type enum in ['NONE', 'VIEW', 'JOINT'], default 'NONE'

etch_side
DOC BROKEN
Type string, default “”

etch_subdivision_number
Number of bones in the subdivided stroke
Type int in [1, 255], default 0

etch_template
Template armature that will be retargeted to the stroke
Type Object

image_paint
Type ImagePaint, (readonly)

mesh_select_mode
Which mesh elements selection works on
Type boolean array of 3 items, default (False, False, False)

normal_size
Display size for normals in the 3D view
Type float in [1e-05, 1000], default 0.0

particle_edit
Type ParticleEdit, (readonly)

proportional_edit
Proportional Editing mode, allows transforms with distance fall-off
Type enum in ['DISABLED', 'ENABLED', 'CONNECTED'], default 'DISABLED'

proportional_edit_falloff
Falloff type for proportional editing mode
Type enum in ['SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT', 'RANDOM'], default 'SMOOTH'

proportional_size
Display size for proportional editing circle
Type float in [1e-05, 5000], default 0.0

sculpt
Type Sculpt, (readonly)

sculpt_paint_use_unified_size

Instead of per brush radius, the radius is shared across brushes

Type boolean, default False

sculpt_paint_use_unified_strength

Instead of per brush strength, the strength is shared across brushes

Type boolean, default False

show_uv_local_view

Draw only faces with the currently displayed image assigned

Type boolean, default False

snap_element

Type of element to snap to

Type enum in ['INCREMENT', 'VERTEX', 'EDGE', 'FACE', 'VOLUME'], default 'INCREMENT'

snap_target

Which part to snap onto the target

Type enum in ['CLOSEST', 'CENTER', 'MEDIAN', 'ACTIVE'], default 'CLOSEST'

use_auto_normalize

Ensure all bone-deforming vertex groups add up to 1.0 while weight painting

Type boolean, default False

use_bone_sketching

DOC BROKEN

Type boolean, default False

use_etch_autoname

DOC BROKEN

Type boolean, default False

use_etch_overdraw

DOC BROKEN

Type boolean, default False

use_etch_quick

DOC BROKEN

Type boolean, default False

use_grease_pencil_sessions

Allow drawing multiple strokes at a time with Grease Pencil

Type boolean, default False

use_keyframe_insert_auto

Automatic keyframe insertion for Objects and Bones

Type boolean, default False

use_keyframe_insert_keyingset

Automatic keyframe insertion using active Keying Set only

Type boolean, default False

use_mesh_automerge

Automatically merge vertices moved to the same location

Type boolean, default False

use_proportional_edit_objects

Proportional editing object mode

Type boolean, default False

use_record_with_nla

Add a new NLA Track + Strip for every loop/pass made over the animation to allow non-destructive tweaking

Type boolean, default False

use_snap

Snap during transform

Type boolean, default False

use_snap_align_rotation

Align rotation with the snapping target

Type boolean, default False

use_snap_peel_object

Consider objects as whole when finding volume center

Type boolean, default False

use_snap_project

Project individual elements on the surface of other objects

Type boolean, default False

use_snap_project_self

Project into its self (editmode)

Type boolean, default False

use_uv_select_sync

Keep UV and edit mode mesh selection in sync

Type boolean, default False

uv_select_mode

UV selection and display mode

Type enum in ['VERTEX', 'EDGE', 'FACE', 'ISLAND'], default 'VERTEX'

vertex_group_weight

Weight to assign in vertex groups

Type float in [0, 1], default 0.0

vertex_paint

Type `VertexPaint`, (readonly)

weight_paint

Type `VertexPaint`, (readonly)

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Context.tool_settings
- Scene.tool_settings

2.4.586 TouchSensor(Sensor)

base classes — bpy_struct, Sensor

class bpy.types.TouchSensor (Sensor)

Sensor to detect objects colliding with the current object

material

Only look for objects with this material (blank = all objects)

Type Material

Inherited Properties

- bpy_struct.id_data
- Sensor.name
- Sensor.show_expanded
- Sensor.frequency
- Sensor.invert
- Sensor.use_level
- Sensor.pin
- Sensor.use_pulse_false_level
- Sensor.use_pulse_true_level
- Sensor.use_tap

- Sensor.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sensor.link
- Sensor.unlink

2.4.587 TrackToConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.TrackToConstraint (Constraint)

Aims the constrained object toward the target

head_tail

Target along length of bone: Head=0, Tail=1

Type float in [0, 1], default 0.0

subtarget

Type string, default “”

target

Target Object

Type Object

track_axis

Axis that points to the target object

Type enum in ['TRACK_X', 'TRACK_Y', 'TRACK_Z', 'TRACK_NEGATIVE_X', 'TRACK_NEGATIVE_Y', 'TRACK_NEGATIVE_Z'], default 'TRACK_X'

up_axis

Axis that points upward

Type enum in ['UP_X', 'UP_Y', 'UP_Z'], default 'UP_X'

use_target_z

Target's Z axis, not World Z axis, will constrain the Up direction

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.588 TransformConstraint(Constraint)

base classes — bpy_struct, Constraint

class bpy.types.TransformConstraint (Constraint)

Maps transformations of the target to the object

from_max_x

Top range of X axis source motion

Type float in [-inf, inf], default 0.0

from_max_y

Top range of Y axis source motion

Type float in [-inf, inf], default 0.0

from_max_z

Top range of Z axis source motion

Type float in [-inf, inf], default 0.0

from_min_x
Bottom range of X axis source motion

Type float in [-inf, inf], default 0.0

from_min_y
Bottom range of Y axis source motion

Type float in [-inf, inf], default 0.0

from_min_z
Bottom range of Z axis source motion

Type float in [-inf, inf], default 0.0

map_from
The transformation type to use from the target

Type enum in ['LOCATION', 'ROTATION', 'SCALE'], default 'LOCATION'

map_to
The transformation type to affect of the constrained object

Type enum in ['LOCATION', 'ROTATION', 'SCALE'], default 'LOCATION'

map_to_x_from
The source axis constrained object's X axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

map_to_y_from
The source axis constrained object's Y axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

map_to_z_from
The source axis constrained object's Z axis uses

Type enum in ['X', 'Y', 'Z'], default 'X'

subtarget

Type string, default ""

target
Target Object

Type `Object`

to_max_x
Top range of X axis destination motion

Type float in [-inf, inf], default 0.0

to_max_y
Top range of Y axis destination motion

Type float in [-inf, inf], default 0.0

to_max_z
Top range of Z axis destination motion

Type float in [-inf, inf], default 0.0

to_min_x

Bottom range of X axis destination motion

Type float in [-inf, inf], default 0.0

to_min_y

Bottom range of Y axis destination motion

Type float in [-inf, inf], default 0.0

to_min_z

Bottom range of Z axis destination motion

Type float in [-inf, inf], default 0.0

use_motion_extrapolate

Extrapolate ranges

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Constraint.name
- Constraint.active
- Constraint.mute
- Constraint.show_expanded
- Constraint.influence
- Constraint.error_location
- Constraint.owner_space
- Constraint.is_proxy_local
- Constraint.error_rotation
- Constraint.target_space
- Constraint.type
- Constraint.is_valid

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.589 TransformOrientation(`bpy_struct`)

base class — `bpy_struct`

```
class bpy.types.TransformOrientation(bpy_struct)
    matrix
        Type float array of 9 items in [-inf, inf], default (0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0, 0.0)
    name
        Type string, default “”
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Scene.orientations`
- `SpaceView3D.current_orientation`

2.4.590 TransformSequence(`EffectSequence`)

base classes — `bpy_struct, Sequence, EffectSequence`

```
class bpy.types.TransformSequence(EffectSequence)
    Sequence strip applying affine transformations to other strips
    interpolation
        Type enum in ['NONE', 'BILINEAR', 'BICUBIC'], default ‘NONE’
    rotation_start
```

Type float in [-360, 360], default 0.0

scale_start_x

Type float in [0, inf], default 0.0

scale_start_y

Type float in [0, inf], default 0.0

translate_start_x

Type float in [-inf, inf], default 0.0

translate_start_y

Type float in [-inf, inf], default 0.0

translation_unit

Type enum in ['PIXELS', 'PERCENT'], default 'PIXELS'

use_uniform_scale

Scale uniformly, preserving aspect ratio

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`
- `Sequence.name`
- `Sequence.blend_type`
- `Sequence.blend_alpha`
- `Sequence.channel`
- `Sequence.effect_fader`
- `Sequence.frame_final_end`
- `Sequence.frame_offset_end`
- `Sequence.frame_still_end`
- `Sequence.input_1`
- `Sequence.input_2`
- `Sequence.input_3`
- `Sequence.select_left_handle`
- `Sequence.frame_final_duration`
- `Sequence.frame_duration`
- `Sequence.lock`
- `Sequence.mute`
- `Sequence.select_right_handle`
- `Sequence.select`
- `Sequence.speed_factor`
- `Sequence.frame_start`
- `Sequence.frame_final_start`
- `Sequence.frame_offset_start`
- `Sequence.frame_still_start`
- `Sequence.type`
- `Sequence.use_default_fade`
- `Sequence.input_count`
- `EffectSequence.color_balance`
- `EffectSequence.use_float`
- `EffectSequence.crop`

- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x
- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.591 UILayout(bpy_struct)

base class — bpy_struct

class bpy.types.**UILayout** (*bpy_struct*)
User interface layout in a panel or header

active

Type boolean, default False

alert

Type boolean, default False

alignment

Type enum in ['EXPAND', 'LEFT', 'CENTER', 'RIGHT'], default 'EXPAND'

enabled

When false, this (sub)layout is greyed out.

Type boolean, default False

operator_context

Type enum in ['INVOKE_DEFAULT', 'INVOKE_REGION_WIN', 'INVOKE_REGION_CHANNELS', 'INVOKE_REGION_PREVIEW', 'INVOKE_AREA', 'INVOKE_SCREEN', 'EXEC_DEFAULT', 'EXEC_REGION_WIN', 'EXEC_REGION_CHANNELS', 'EXEC_REGION_PREVIEW', 'EXEC_AREA', 'EXEC_SCREEN'], default 'INVOKE_DEFAULT'

scale_x

Scale factor along the X for items in this (sub)layout.

Type float in [0, inf], default 0.0

scale_y

Scale factor along the Y for items in this (sub)layout.

Type float in [0, inf], default 0.0

row (*align=False*)

Sub-layout. Items placed in this sublayout are placed next to each other in a row.

Parameters *align* (boolean, *(optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type [UILayout](#)

column (*align=False*)

Sub-layout. Items placed in this sublayout are placed under each other in a column.

Parameters *align* (boolean, *(optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type [UILayout](#)

column_flow (*columns=0, align=False*)

column_flow

Parameters

- **columns** (int in [0, inf], *(optional)*) – Number of columns, 0 is automatic.
- **align** (boolean, *(optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type [UILayout](#)

box ()

Sublayout. Items placed in this sublayout are placed under each other in a column and are surrounded by a box.

Returns Sub-layout to put items in.

Return type [UILayout](#)

split (*percentage=0.0, align=False*)

split

Parameters

- **percentage** (*float in [0, 1], (optional)*) – Percentage of width to split at.
 - **align** (*boolean, (optional)*) – Align buttons to each other.

Returns Sub-layout to put items in.

Return type `UILayout`

prop(*data*, *property*, *text*=“”, *icon*=‘NONE’, *expand*=*False*, *slider*=*False*, *toggle*=*False*, *icon_only*=*False*, *event*=*False*, *full_event*=*False*, *emboss*=*True*, *index*=-1)
Item. Exposes an RNA item and places it into the layout.

Parameters

'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEEP_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE', 'MATSHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR',

'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSHCREASE', 'BRUSH_DARKEN',
'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE',
'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY',
'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW',
'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK',
'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB',
'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT',
'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC',
'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

- **expand** (boolean, (optional)) – Expand button to show more detail.
- **slider** (boolean, (optional)) – Use slider widget for numeric values.
- **toggle** (boolean, (optional)) – Use toggle widget for boolean values.
- **icon_only** (boolean, (optional)) – Draw only icons in buttons, no text.
- **event** (boolean, (optional)) – Use button to input key events.
- **full_event** (boolean, (optional)) – Use button to input full events including modifiers.
- **emboss** (boolean, (optional)) – Draw the button itself, just the icon/text.
- **index** (int in [-2, inf], (optional)) – The index of this button, when set a single member of an array can be accessed, when set to -1 all array members are used.

props_enum (data, property)
props_enum

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (string) – Identifier of property in data.

prop_menu_enum (data, property, text=""“, icon='NONE')
prop_menu_enum

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (string) – Identifier of property in data.
- **text** (string, (optional)) – Override automatic text of the item.
- **icon** (enum in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST',

'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS', 'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY', 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE', 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP', 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH', 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE', 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY', 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME', 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE', 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE',

'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON',
 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH',
 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON',
 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE',
 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE',
 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEELED_OBJECT',
 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIP-
 DOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL',
 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE',
 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON',
 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN',
 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTAL-
 PHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORT-
 DISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FIL-
 TER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER',
 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT',
 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MAT-
 PLANE', 'MATSHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED',
 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORD-
 WRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUM-
 BERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW',
 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM',
 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IM-
 AGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR',
 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSHCREASE', 'BRUSH_DARKEN',
 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE',
 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY',
 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW',
 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK',
 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB',
 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'ED-
 ITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DIS-
 CLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC',
 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

prop_enum (*data*, *property*, *value*, *text*= "", *icon*='NONE')
prop_enum

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **value** (*string*) – Enum property value.
- **text** (*string*, (optional)) – Override automatic text of the item.
- **icon** (*enum in* ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT', 'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOT']) – Icon, Override automatic icon of the item

`SUP`, `DOTSDOWN`, `LINK`, `INLINK`, `PLUGIN`, `HELP`, `GHOST_ENABLED`, `COLOR`, `LINKED`, `UNLINKED`, `HAND`, `ZOOM_ALL`, `ZOOM_SELECTED`, `ZOOM_PREVIOUS`, `ZOOM_IN`, `ZOOM_OUT`, `RENDER_REGION`, `BORDER_RECT`, `BORDER_LASSO`, `FREEZE`, `STYLUS_PRESSURE`, `GHOST_DISABLED`, `NEW`, `FILE_TICK`, `QUIT`, `URL`, `RECOVER_LAST`, `FULLSCREEN_ENTER`, `FULLSCREEN_EXIT`, `BLANK1`, `LAMP`, `MATERIAL`, `TEXTURE`, `ANIM`, `WORLD`, `SCENE`, `EDIT`, `GAME`, `RADIO`, `SCRIPT`, `PARTICLES`, `PHYSICS`, `SPEAKER`, `TEXTURE_SHADED`, `VIEW3D`, `IPO`, `OOPS`, `BUTS`, `FILESEL`, `IMAGE_COL`, `INFO`, `SEQUENCE`, `TEXT`, `IMASEL`, `SOUND`, `ACTION`, `NLA`, `SCRIPTWIN`, `TIME`, `NODETREE`, `LOGIC`, `CONSOLE`, `PREFERENCES`, `ASSET_MANAGER`, `OBJECT_DATAMODE`, `EDITMODE_HLT`, `FACESEL_HLT`, `VPAINT_HLT`, `TPAINT_HLT`, `WPAINT_HLT`, `SCULPTMODE_HLT`, `POSE_HLT`, `PARTICLEMODE`, `LIGHTPAINT`, `SCENE_DATA`, `RENDERLAYERS`, `WORLD_DATA`, `OBJECT_DATA`, `MESH_DATA`, `CURVE_DATA`, `META_DATA`, `LATTICE_DATA`, `LAMP_DATA`, `MATERIAL_DATA`, `TEXTURE_DATA`, `ANIM_DATA`, `CAMERA_DATA`, `PARTICLE_DATA`, `LIBRARY_DATA_DIRECT`, `GROUP`, `ARMATURE_DATA`, `POSE_DATA`, `BONE_DATA`, `CONSTRAINT`, `SHAPEKEY_DATA`, `CONSTRAINT_BONE`, `PACKAGE`, `UGLYPACKAGE`, `BRUSH_DATA`, `IMAGE_DATA`, `FILE`, `FCURVE`, `FONT_DATA`, `RENDER_RESULT`, `SURFACE_DATA`, `EMPTY_DATA`, `SETTINGS`, `RENDER_ANIMATION`, `RENDER_STILL`, `BOIDS`, `STRANDS`, `LIBRARY_DATA_INDIRECT`, `GREASEPENCIL`, `GROUP_BONE`, `GROUP_VERTEX`, `GROUP_VCOL`, `GROUP_UVS`, `RNA`, `RNA_ADD`, `OUTLINER_OB_EMPTY`, `OUTLINER_OB_MESH`, `OUTLINER_OB_CURVE`, `OUTLINER_OB_LATTICE`, `OUTLINER_OB_META`, `OUTLINER_OB_LAMP`, `OUTLINER_OB_CAMERA`, `OUTLINER_OB_ARMATURE`, `OUTLINER_OB_FONT`, `OUTLINER_OB_SURFACE`, `RESTRICT_VIEW_OFF`, `RESTRICT_VIEW_ON`, `RESTRICT_SELECT_OFF`, `RESTRICT_SELECT_ON`, `RESTRICT_RENDER_OFF`, `RESTRICT_RENDER_ON`, `OUTLINER_DATA_EMPTY`, `OUTLINER_DATA_MESH`, `OUTLINER_DATA_CURVE`, `OUTLINER_DATA_LATTICE`, `OUTLINER_DATA_META`, `OUTLINER_DATA_LAMP`, `OUTLINER_DATA_CAMERA`, `OUTLINER_DATA_ARMATURE`, `OUTLINER_DATA_FONT`, `OUTLINER_DATA_SURFACE`, `OUTLINER_DATA_POSE`, `MESH_PLANE`, `MESH_CUBE`, `MESH_CIRCLE`, `MESH_UVSPHERE`, `MESH_ICOSPHERE`, `MESH_GRID`, `MESH_MONKEY`, `MESH_CYLINDER`, `MESH_TORUS`, `MESH_CONE`, `LAMP_POINT`, `LAMP_SUN`, `LAMP_SPOT`, `LAMP_HEMI`, `LAMP_AREA`, `META_PLANE`, `META_CUBE`, `META BALL`, `META_ELLIPSOID`, `META_CAPSULE`, `SURFACE_NCURVE`, `SURFACE_NCIRCLE`, `SURFACE_NSURFACE`, `SURFACE_NCYLINDER`, `SURFACE_NSHERE`, `SURFACE_NTorus`, `CURVE_BEZCURVE`, `CURVE_BEZCIRCLE`, `CURVE_NCURVE`, `CURVE_NCIRCLE`, `CURVE_PATH`, `FORCE_FORCE`, `FORCE_WIND`, `FORCE_VORTEX`, `FORCE_MAGNETIC`, `FORCE_HARMONIC`, `FORCE_CHARGE`, `FORCE LENNARDJONES`, `FORCE_TEXTURE`, `FORCE_CURVE`, `FORCE_BOID`, `FORCE_TURBULENCE`, `FORCE_DRAG`, `MODIFIER`, `MOD_WAVE`, `MOD_BUILD`, `MOD_DECIM`, `MOD_MIRROR`, `MOD_SOFT`, `MOD_SUBSURF`, `HOOK`, `MOD_PHYSICS`, `MOD_PARTICLES`, `MOD_BOOLEAN`, `MOD_EDGESPLIT`, `MOD_ARRAY`, `MOD_UVPROJECT`, `MOD_DISPLACE`, `MOD_CURVE`, `MOD_LATTICE`, `CONSTRAINT_DATA`, `MOD_ARMATURE`, `MOD_SHRINKWRAP`, `MOD_CAST`, `MOD_MESHDEFORM`, `MOD_BEVEL`, `MOD_SMOOTH`, `MOD_SIMPLEDEFORM`, `MOD_MASK`, `MOD_CLOTH`, `MOD_EXPLODE`, `MOD_FLUIDSIM`, `MOD_MULTIRES`, `MOD_SMOKE`, `MOD_SOLIDIFY`, `MOD SCREW`, `REC`, `PLAY`, `FF`, `REW`, `PAUSE`, `PREV_KEYFRAME`, `NEXT_KEYFRAME`, `PLAY_AUDIO`, `PLAY_REVERSE`, `PREVIEW_RANGE`,

'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER', 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF', 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR', 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN', 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE', 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON', 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH', 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON', 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE', 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE', 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEELED_OBJECT', 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN', 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL', 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE', 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON', 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN', 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA', 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY', 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER', 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER', 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT', 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATERIAL_PLANE', 'MATS_SPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED', 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON', 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON', 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW', 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM', 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH', 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR', 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSHCREASE', 'BRUSH_DARKEN', 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE', 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY', 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW', 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK', 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB', 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT', 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC', 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

prop_search (*data*, *property*, *search_data*, *search_property*, *text*=“”, *icon*=’NONE’)
prop_search

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **search_data** ([AnyType](#), (never None)) – Data from which to take collection to search in.
- **search_property** (*string*) – Identifier of search collection property.
- **text** (*string*, (optional)) – Override automatic text of the item.
- **icon** (*enum in* [’NONE’, ‘QUESTION’, ‘ERROR’, ‘CANCEL’, ‘TRIA_RIGHT’, ‘TRIA_DOWN’, ‘TRIA_LEFT’, ‘TRIA_UP’, ‘ARROW_LEFTRIGHT’, ‘PLUS’, ‘DISCLOSURE_TRI_DOWN’, ‘DISCLOSURE_TRI_RIGHT’, ‘RADIOBUT_OFF’, ‘RA-

`DIOBUT_ON`, `'MENU_PANEL'`, `'BLENDER'`, `'DOT'`, `'X'`, `'GO_LEFT'`, `'PLUG'`,
`'UI'`, `'NODE'`, `'NODE_SEL'`, `'FULLSCREEN'`, `'SPLITSCREEN'`, `'RIGHTAR-`
`'ROW_THIN'`, `'BORDERMOVE'`, `'VIEWZOOM'`, `'ZOOMIN'`, `'ZOOMOUT'`,
`'PANEL_CLOSE'`, `'COPY_ID'`, `'EYEDROPPER'`, `'LINK_AREA'`, `'AUTO'`, `'CHECK-`
`'BOX_DEHLT'`, `'CHECKBOX_HLT'`, `'UNLOCKED'`, `'LOCKED'`, `'UNPINNED'`,
`'PINNED'`, `'SCREEN_BACK'`, `'RIGHTARROW'`, `'DOWNNARROW_HLT'`, `'DOT-`
`'SUP'`, `'DOTSDOWN'`, `'LINK'`, `'INLINK'`, `'PLUGIN'`, `'HELP'`, `'GHOST_ENABLED'`,
`'COLOR'`, `'LINKED'`, `'UNLINKED'`, `'HAND'`, `'ZOOM_ALL'`, `'ZOOM_SELECTED'`,
`'ZOOM_PREVIOUS'`, `'ZOOM_IN'`, `'ZOOM_OUT'`, `'RENDER_REGION'`,
`'BORDER_RECT'`, `'BORDER_LASSO'`, `'FREEZE'`, `'STYLUS_PRESSURE'`,
`'GHOST_DISABLED'`, `'NEW'`, `'FILE_TICK'`, `'QUIT'`, `'URL'`, `'RECOVER_LAST'`,
`'FULLSCREEN_ENTER'`, `'FULLSCREEN_EXIT'`, `'BLANK1'`, `'LAMP'`, `'MA-`
`'TERIAL'`, `'TEXTURE'`, `'ANIM'`, `'WORLD'`, `'SCENE'`, `'EDIT'`, `'GAME'`, `'RA-`
`'DIO'`, `'SCRIPT'`, `'PARTICLES'`, `'PHYSICS'`, `'SPEAKER'`, `'TEXTURE_SHADED'`,
`'VIEW3D'`, `'IPO'`, `'OOPS'`, `'BUTS'`, `'FILESEL'`, `'IMAGE_COL'`, `'INFO'`, `'SE-`
`'QUENCE'`, `'TEXT'`, `'IMASEL'`, `'SOUND'`, `'ACTION'`, `'NLA'`, `'SCRIPTWIN'`, `'TIME'`,
`'NODETREE'`, `'LOGIC'`, `'CONSOLE'`, `'PREFERENCES'`, `'ASSET_MANAGER'`,
`'OBJECT_DATAMODE'`, `'EDITMODE_HLT'`, `'FACESEL_HLT'`, `'VPAINT_HLT'`,
`'TPAINT_HLT'`, `'WPAINT_HLT'`, `'SCULPTMODE_HLT'`, `'POSE_HLT'`, `'PARTI-`
`'CLEMODE'`, `'LIGHTPAINT'`, `'SCENE_DATA'`, `'RENDERLAYERS'`, `'WORLD_DATA'`,
`'OBJECT_DATA'`, `'MESH_DATA'`, `'CURVE_DATA'`, `'META_DATA'`, `'LATTICE_DATA'`,
`'LAMP_DATA'`, `'MATERIAL_DATA'`, `'TEXTURE_DATA'`, `'ANIM_DATA'`, `'CAM-`
`'ERA_DATA'`, `'PARTICLE_DATA'`, `'LIBRARY_DATA_DIRECT'`, `'GROUP'`, `'ARMA-`
`'TURE_DATA'`, `'POSE_DATA'`, `'BONE_DATA'`, `'CONSTRAINT'`, `'SHAPEKEY_DATA'`,
`'CONSTRAINT_BONE'`, `'PACKAGE'`, `'UGLYPACKAGE'`, `'BRUSH_DATA'`, `'IM-`
`'AGE_DATA'`, `'FILE'`, `'FCURVE'`, `'FONT_DATA'`, `'RENDER_RESULT'`, `'SUR-`
`'FACE_DATA'`, `'EMPTY_DATA'`, `'SETTINGS'`, `'RENDER_ANIMATION'`, `'REN-`
`'DER_STILL'`, `'BOIDS'`, `'STRANDS'`, `'LIBRARY_DATA_INDIRECT'`, `'GREASEPEN-`
`'CIL'`, `'GROUP_BONE'`, `'GROUP_VERTEX'`, `'GROUP_VCOL'`, `'GROUP_UVS'`,
`'RNA'`, `'RNA_ADD'`, `'OUTLINER_OB_EMPTY'`, `'OUTLINER_OB_MESH'`, `'OUT-`
`'LINER_OB_CURVE'`, `'OUTLINER_OB_LATTICE'`, `'OUTLINER_OB_META'`, `'OUT-`
`'LINER_OB_LAMP'`, `'OUTLINER_OB_CAMERA'`, `'OUTLINER_OB_ARMATURE'`,
`'OUTLINER_OB_FONT'`, `'OUTLINER_OB_SURFACE'`, `'RESTRICT_VIEW_OFF'`,
`'RESTRICT_VIEW_ON'`, `'RESTRICT_SELECT_OFF'`, `'RESTRICT_SELECT_ON'`, `'RE-`
`'STRICT_RENDER_OFF'`, `'RESTRICT_RENDER_ON'`, `'OUTLINER_DATA_EMPTY'`,
`'OUTLINER_DATA_MESH'`, `'OUTLINER_DATA_CURVE'`, `'OUT-`
`'LINER_DATA_LATTICE'`, `'OUTLINER_DATA_META'`, `'OUTLINER_DATA_LAMP'`,
`'OUTLINER_DATA_CAMERA'`, `'OUTLINER_DATA_ARMATURE'`, `'OUT-`
`'LINER_DATA_FONT'`, `'OUTLINER_DATA_SURFACE'`, `'OUTLINER_DATA_POSE'`,
`'MESH_PLANE'`, `'MESH_CUBE'`, `'MESH_CIRCLE'`, `'MESH_UVSHERE'`,
`'MESH_ICOSPHERE'`, `'MESH_GRID'`, `'MESH_MONKEY'`, `'MESH_CYLINDER'`,
`'MESH_TORUS'`, `'MESH_CONE'`, `'LAMP_POINT'`, `'LAMP_SUN'`, `'LAMP_SPOT'`,
`'LAMP_HEMI'`, `'LAMP_AREA'`, `'META_PLANE'`, `'META_CUBE'`, `'META_BALL'`,
`'META_ELLIPSOID'`, `'META_CAPSULE'`, `'SURFACE_NCURVE'`, `'SUR-`
`'FACE_NCIRCLE'`, `'SURFACE_NSURFACE'`, `'SURFACE_NCYLINDER'`,
`'SURFACE_NSPHERE'`, `'SURFACE_NTORUS'`, `'CURVE_BEZCURVE'`,
`'CURVE_BEZCIRCLE'`, `'CURVE_NCURVE'`, `'CURVE_NCIRCLE'`, `'CURVE_PATH'`,
`'FORCE_FORCE'`, `'FORCE_WIND'`, `'FORCE_VORTEX'`, `'FORCE_MAGNETIC'`,
`'FORCE_HARMONIC'`, `'FORCE_CHARGE'`, `'FORCE_LENNARDJONES'`,
`'FORCE_TEXTURE'`, `'FORCE_CURVE'`, `'FORCE_BOID'`, `'FORCE_TURBULENCE'`,
`'FORCE_DRAG'`, `'MODIFIER'`, `'MOD_WAVE'`, `'MOD_BUILD'`, `'MOD_DECIM'`,
`'MOD_MIRROR'`, `'MOD_SOFT'`, `'MOD_SUBSURF'`, `'HOOK'`, `'MOD_PHYSICS'`,
`'MOD_PARTICLES'`, `'MOD_BOOLEAN'`, `'MOD_EDGESPLIT'`, `'MOD_ARRAY'`,
`'MOD_UVPROJECT'`, `'MOD_DISPLACE'`, `'MOD_CURVE'`, `'MOD_LATTICE'`,

'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP',
 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH',
 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE',
 'MOD_FLUIDSIM', 'MOD_MULTRES', 'MOD_SMOKE', 'MOD_SOLIDIFY',
 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME',
 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE',
 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER',
 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF',
 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR',
 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN',
 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE',
 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON',
 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH',
 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON',
 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE',
 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE',
 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEELED_OBJECT',
 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN',
 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESSEL',
 'UV_FACESSEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE',
 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON',
 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN',
 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA',
 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY',
 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER',
 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER',
 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT',
 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE',
 'MATSHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED',
 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON',
 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON',
 'SCRIPTPLUGINS', 'SEQSEQUENCER', 'SEQ_PREVIEW',
 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM',
 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH',
 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR',
 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSHCREASE', 'BRUSH_DARKEN',
 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE',
 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY',
 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW',
 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK',
 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB',
 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT',
 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC',
 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

operator (*operator*, *text*="" , *icon*='NONE', *emboss*=True)

Item. Places a button into the layout to call an Operator.

Parameters

- **operator** (*string*) – Identifier of the operator.
- **text** (*string*, (optional)) – Override automatic text of the item.
- **icon** (*enum* in ['NONE', 'QUESTION', 'ERROR', 'CANCEL', 'TRIA_RIGHT',

'TRIA_DOWN', 'TRIA_LEFT', 'TRIA_UP', 'ARROW_LEFTRIGHT', 'PLUS', 'DISCLOSURE_TRI_DOWN', 'DISCLOSURE_TRI_RIGHT', 'RADIOBUT_OFF', 'RADIOBUT_ON', 'MENU_PANEL', 'BLENDER', 'DOT', 'X', 'GO_LEFT', 'PLUG', 'UI', 'NODE', 'NODE_SEL', 'FULLSCREEN', 'SPLITSCREEN', 'RIGHTARROW_THIN', 'BORDERMOVE', 'VIEWZOOM', 'ZOOMIN', 'ZOOMOUT', 'PANEL_CLOSE', 'COPY_ID', 'EYEDROPPER', 'LINK_AREA', 'AUTO', 'CHECKBOX_DEHLT', 'CHECKBOX_HLT', 'UNLOCKED', 'LOCKED', 'UNPINNED', 'PINNED', 'SCREEN_BACK', 'RIGHTARROW', 'DOWNARROW_HLT', 'DOTSUP', 'DOTSDOWN', 'LINK', 'INLINK', 'PLUGIN', 'HELP', 'GHOST_ENABLED', 'COLOR', 'LINKED', 'UNLINKED', 'HAND', 'ZOOM_ALL', 'ZOOM_SELECTED', 'ZOOM_PREVIOUS', 'ZOOM_IN', 'ZOOM_OUT', 'RENDER_REGION', 'BORDER_RECT', 'BORDER_LASSO', 'FREEZE', 'STYLUS_PRESSURE', 'GHOST_DISABLED', 'NEW', 'FILE_TICK', 'QUIT', 'URL', 'RECOVER_LAST', 'FULLSCREEN_ENTER', 'FULLSCREEN_EXIT', 'BLANK1', 'LAMP', 'MATERIAL', 'TEXTURE', 'ANIM', 'WORLD', 'SCENE', 'EDIT', 'GAME', 'RADIO', 'SCRIPT', 'PARTICLES', 'PHYSICS', 'SPEAKER', 'TEXTURE_SHADED', 'VIEW3D', 'IPO', 'OOPS', 'BUTS', 'FILESEL', 'IMAGE_COL', 'INFO', 'SEQUENCE', 'TEXT', 'IMASEL', 'SOUND', 'ACTION', 'NLA', 'SCRIPTWIN', 'TIME', 'NODETREE', 'LOGIC', 'CONSOLE', 'PREFERENCES', 'ASSET_MANAGER', 'OBJECT_DATAMODE', 'EDITMODE_HLT', 'FACESEL_HLT', 'VPAINT_HLT', 'TPAINT_HLT', 'WPAINT_HLT', 'SCULPTMODE_HLT', 'POSE_HLT', 'PARTICLEMODE', 'LIGHTPAINT', 'SCENE_DATA', 'RENDERLAYERS', 'WORLD_DATA', 'OBJECT_DATA', 'MESH_DATA', 'CURVE_DATA', 'META_DATA', 'LATTICE_DATA', 'LAMP_DATA', 'MATERIAL_DATA', 'TEXTURE_DATA', 'ANIM_DATA', 'CAMERA_DATA', 'PARTICLE_DATA', 'LIBRARY_DATA_DIRECT', 'GROUP', 'ARMATURE_DATA', 'POSE_DATA', 'BONE_DATA', 'CONSTRAINT', 'SHAPEKEY_DATA', 'CONSTRAINT_BONE', 'PACKAGE', 'UGLYPACKAGE', 'BRUSH_DATA', 'IMAGE_DATA', 'FILE', 'FCURVE', 'FONT_DATA', 'RENDER_RESULT', 'SURFACE_DATA', 'EMPTY_DATA', 'SETTINGS', 'RENDER_ANIMATION', 'RENDER_STILL', 'BOIDS', 'STRANDS', 'LIBRARY_DATA_INDIRECT', 'GREASEPENCIL', 'GROUP_BONE', 'GROUP_VERTEX', 'GROUP_VCOL', 'GROUP_UVS', 'RNA', 'RNA_ADD', 'OUTLINER_OB_EMPTY', 'OUTLINER_OB_MESH', 'OUTLINER_OB_CURVE', 'OUTLINER_OB_LATTICE', 'OUTLINER_OB_META', 'OUTLINER_OB_LAMP', 'OUTLINER_OB_CAMERA', 'OUTLINER_OB_ARMATURE', 'OUTLINER_OB_FONT', 'OUTLINER_OB_SURFACE', 'RESTRICT_VIEW_OFF', 'RESTRICT_VIEW_ON', 'RESTRICT_SELECT_OFF', 'RESTRICT_SELECT_ON', 'RESTRICT_RENDER_OFF', 'RESTRICT_RENDER_ON', 'OUTLINER_DATA_EMPTY', 'OUTLINER_DATA_MESH', 'OUTLINER_DATA_CURVE', 'OUTLINER_DATA_LATTICE', 'OUTLINER_DATA_META', 'OUTLINER_DATA_LAMP', 'OUTLINER_DATA_CAMERA', 'OUTLINER_DATA_ARMATURE', 'OUTLINER_DATA_FONT', 'OUTLINER_DATA_SURFACE', 'OUTLINER_DATA_POSE', 'MESH_PLANE', 'MESH_CUBE', 'MESH_CIRCLE', 'MESH_UVSPHERE', 'MESH_ICOSPHERE', 'MESH_GRID', 'MESH_MONKEY', 'MESH_CYLINDER', 'MESH_TORUS', 'MESH_CONE', 'LAMP_POINT', 'LAMP_SUN', 'LAMP_SPOT', 'LAMP_HEMI', 'LAMP_AREA', 'META_PLANE', 'META_CUBE', 'META_BALL', 'META_ELLIPSOID', 'META_CAPSULE', 'SURFACE_NCURVE', 'SURFACE_NCIRCLE', 'SURFACE_NSURFACE', 'SURFACE_NCYLINDER', 'SURFACE_NSPHERE', 'SURFACE_NTORUS', 'CURVE_BEZCURVE', 'CURVE_BEZCIRCLE', 'CURVE_NCURVE', 'CURVE_NCIRCLE', 'CURVE_PATH', 'FORCE_FORCE', 'FORCE_WIND', 'FORCE_VORTEX', 'FORCE_MAGNETIC', 'FORCE_HARMONIC', 'FORCE_CHARGE', 'FORCE_LENNARDJONES', 'FORCE_TEXTURE', 'FORCE_CURVE', 'FORCE_BOID', 'FORCE_TURBULENCE', 'FORCE_DRAG', 'MODIFIER', 'MOD_WAVE', 'MOD_BUILD', 'MOD_DECIM', 'MOD_MIRROR', 'MOD_SOFT', 'MOD_SUBSURF', 'HOOK', 'MOD_PHYSICS',

'MOD_PARTICLES', 'MOD_BOOLEAN', 'MOD_EDGESPLIT', 'MOD_ARRAY',
 'MOD_UVPROJECT', 'MOD_DISPLACE', 'MOD_CURVE', 'MOD_LATTICE',
 'CONSTRAINT_DATA', 'MOD_ARMATURE', 'MOD_SHRINKWRAP',
 'MOD_CAST', 'MOD_MESHDEFORM', 'MOD_BEVEL', 'MOD_SMOOTH',
 'MOD_SIMPLEDEFORM', 'MOD_MASK', 'MOD_CLOTH', 'MOD_EXPLODE',
 'MOD_FLUIDSIM', 'MOD_MULTIRES', 'MOD_SMOKE', 'MOD_SOLIDIFY',
 'MOD_SCREW', 'REC', 'PLAY', 'FF', 'REW', 'PAUSE', 'PREV_KEYFRAME',
 'NEXT_KEYFRAME', 'PLAY_AUDIO', 'PLAY_REVERSE', 'PREVIEW_RANGE',
 'PMARKER_ACT', 'PMARKER_SEL', 'PMARKER', 'MARKER_HLT', 'MARKER',
 'SPACE2', 'SPACE3', 'KEY_DEHLT', 'KEY_HLT', 'MUTE_IPO_OFF',
 'MUTE_IPO_ON', 'VERTEXSEL', 'EDGESEL', 'FACESEL', 'ROTATE', 'CURSOR',
 'ROTATECOLLECTION', 'ROTATECENTER', 'ROTACTIVE', 'ALIGN',
 'SMOOTHCURVE', 'SPHERECURVE', 'ROOTCURVE', 'SHARPCURVE',
 'LINCURVE', 'NOCURVE', 'RNDCURVE', 'PROP_OFF', 'PROP_ON',
 'PROP_CON', 'PARTICLE_POINT', 'PARTICLE_TIP', 'PARTICLE_PATH',
 'MAN_TRANS', 'MAN_ROT', 'MAN_SCALE', 'MANIPUL', 'SNAP_OFF', 'SNAP_ON',
 'SNAP_NORMAL', 'SNAP_INCREMENT', 'SNAP_VERTEX', 'SNAP_EDGE',
 'SNAP_FACE', 'SNAP_VOLUME', 'STICKY_UVS_LOC', 'STICKY_UVS_DISABLE',
 'STICKY_UVS_VERT', 'CLIPUV_DEHLT', 'CLIPUV_HLT', 'SNAP_PEELED_OBJECT',
 'GRID', 'PASTEDOWN', 'COPYDOWN', 'PASTEFLIPUP', 'PASTEFLIPDOWN',
 'SNAP_SURFACE', 'RETOPO', 'UV_VERTEXSEL', 'UV_EDGESEL',
 'UV_FACESEL', 'UV_ISLANDSEL', 'UV_SYNC_SELECT', 'BBOX', 'WIRE',
 'SOLID', 'SMOOTH', 'POTATO', 'ORTHO', 'LOCKVIEW_OFF', 'LOCKVIEW_ON',
 'AXIS_SIDE', 'AXIS_FRONT', 'AXIS_TOP', 'NDOF_DOM', 'NDOF_TURN',
 'NDOF_FLY', 'NDOF_TRANS', 'LAYER_USED', 'LAYER_ACTIVE', 'SORTALPHA',
 'SORTBYEXT', 'SORTTIME', 'SORTSIZE', 'LONGDISPLAY', 'SHORTDISPLAY',
 'GHOST', 'IMGDISPLAY', 'BOOKMARKS', 'FONTPREVIEW', 'FILTER',
 'NEWFOLDER', 'FILE_PARENT', 'FILE_REFRESH', 'FILE_FOLDER',
 'FILE_BLANK', 'FILE_BLEND', 'FILE_IMAGE', 'FILE_MOVIE', 'FILE_SCRIPT',
 'FILE_SOUND', 'FILE_FONT', 'BACK', 'FORWARD', 'DISK_DRIVE', 'MATPLANE',
 'MATS_SPHERE', 'MATCUBE', 'MONKEY', 'HAIR', 'ALIASED',
 'ANTIALIASED', 'MAT_SPHERE_SKY', 'WORDWRAP_OFF', 'WORDWRAP_ON',
 'SYNTAX_OFF', 'SYNTAX_ON', 'LINENUMBERS_OFF', 'LINENUMBERS_ON',
 'SCRIPTPLUGINS', 'SEQ_SEQUENCER', 'SEQ_PREVIEW',
 'SEQ_LUMA_WAVEFORM', 'SEQ_CHROMA_SCOPE', 'SEQ_HISTOGRAM',
 'SEQ_SPLITVIEW', 'IMAGE_RGB', 'IMAGE_RGB_ALPHA', 'IMAGE_ALPHA', 'IMAGE_ZDEPTH',
 'IMAGEFILE', 'BRUSH_ADD', 'BRUSH_BLOB', 'BRUSH_BLUR',
 'BRUSH_CLAY', 'BRUSH_CLONE', 'BRUSHCREASE', 'BRUSH_DARKEN',
 'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE',
 'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY',
 'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW',
 'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK',
 'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB',
 'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT',
 'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC',
 'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC', 'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

- **emboss** (boolean, (optional)) – Draw the button itself, just the icon/text.

Returns Operator properties to fill in, return when ‘properties’ is set to true.

Return type `OperatorProperties`

operator_enum (*operator, property*)

`operator_enum`

Parameters

- **operator** (*string*) – Identifier of the operator.
- **property** (*string*) – Identifier of property in operator.

operator_menu_enum (*operator*, *property*, *text*=“”, *icon*=’NONE’)
operator_menu_enum

Parameters

- **operator** (*string*) – Identifier of the operator.
- **property** (*string*) – Identifier of property in operator.
- **text** (*string, (optional)*) – Override automatic text of the item.
- **icon** (*enum in [’NONE’, ’QUESTION’, ’ERROR’, ’CANCEL’, ’TRIA_RIGHT’, ’TRIA_DOWN’, ’TRIA_LEFT’, ’TRIA_UP’, ’ARROW_LEFTRIGHT’, ’PLUS’, ’DISCLOSURE_TRI_DOWN’, ’DISCLOSURE_TRI_RIGHT’, ’RADIOBUT_OFF’, ’RADIOBUT_ON’, ’MENU_PANEL’, ’BLENDER’, ’DOT’, ’X’, ’GO_LEFT’, ’PLUG’, ’UI’, ’NODE’, ’NODE_SEL’, ’FULLSCREEN’, ’SPLITSCREEN’, ’RIGHTARROW_THIN’, ’BORDERMOVE’, ’VIEWZOOM’, ’ZOMMIN’, ’ZOOMOUT’, ’PANEL_CLOSE’, ’COPY_ID’, ’EYEDROPPER’, ’LINK_AREA’, ’AUTO’, ’CHECKBOX_DEHLT’, ’CHECKBOX_HLT’, ’UNLOCKED’, ’LOCKED’, ’UNPINNED’, ’PINNED’, ’SCREEN_BACK’, ’RIGHTARROW’, ’DOWNARROW_HLT’, ’DOTSUP’, ’DOTSDOWN’, ’LINK’, ’INLINK’, ’PLUGIN’, ’HELP’, ’GHOST_ENABLED’, ’COLOR’, ’LINKED’, ’UNLINKED’, ’HAND’, ’ZOOM_ALL’, ’ZOOM_SELECTED’, ’ZOOM_PREVIOUS’, ’ZOOM_IN’, ’ZOOM_OUT’, ’RENDER_REGION’, ’BORDER_RECT’, ’BORDER_LASSO’, ’FREEZE’, ’STYLUS_PRESSURE’, ’GHOST_DISABLED’, ’NEW’, ’FILE_TICK’, ’QUIT’, ’URL’, ’RECOVER_LAST’, ’FULLSCREEN_ENTER’, ’FULLSCREEN_EXIT’, ’BLANKI’, ’LAMP’, ’MATERIAL’, ’TEXTURE’, ’ANIM’, ’WORLD’, ’SCENE’, ’EDIT’, ’GAME’, ’RADIO’, ’SCRIPT’, ’PARTICLES’, ’PHYSICS’, ’SPEAKER’, ’TEXTURE_SHADED’, ’VIEW3D’, ’IPO’, ’OOPS’, ’BUTS’, ’FILESEL’, ’IMAGE_COL’, ’INFO’, ’SEQUENCE’, ’TEXT’, ’IMASEL’, ’SOUND’, ’ACTION’, ’NLA’, ’SCRIPTWIN’, ’TIME’, ’NODETREE’, ’LOGIC’, ’CONSOLE’, ’PREFERENCES’, ’ASSET_MANAGER’, ’OBJECT_DATAMODE’, ’EDITMODE_HLT’, ’FACESEL_HLT’, ’VPAINT_HLT’, ’TPAINT_HLT’, ’WPAINT_HLT’, ’SCULPTMODE_HLT’, ’POSE_HLT’, ’PARTICLEMODE’, ’LIGHTPAINT’, ’SCENE_DATA’, ’RENDERLAYERS’, ’WORLD_DATA’, ’OBJECT_DATA’, ’MESH_DATA’, ’CURVE_DATA’, ’META_DATA’, ’LATTICE_DATA’, ’LAMP_DATA’, ’MATERIAL_DATA’, ’TEXTURE_DATA’, ’ANIM_DATA’, ’CAMERA_DATA’, ’PARTICLE_DATA’, ’LIBRARY_DATA_DIRECT’, ’GROUP’, ’ARMATURE_DATA’, ’POSE_DATA’, ’BONE_DATA’, ’CONSTRAINT’, ’SHAPEKEY_DATA’, ’CONSTRAINT_BONE’, ’PACKAGE’, ’UGLYPACKAGE’, ’BRUSH_DATA’, ’IMAGE_DATA’, ’FILE’, ’FCURVE’, ’FONT_DATA’, ’RENDER_RESULT’, ’SURFACE_DATA’, ’EMPTY_DATA’, ’SETTINGS’, ’RENDER_ANIMATION’, ’RENDER_STILL’, ’BOIDS’, ’STRANDS’, ’LIBRARY_DATA_INDIRECT’, ’GREASEPENCIL’, ’GROUP_BONE’, ’GROUP_VERTEX’, ’GROUP_VCOL’, ’GROUP_UVS’, ’RNA’, ’RNA_ADD’, ’OUTLINER_OB_EMPTY’, ’OUTLINER_OB_MESH’, ’OUTLINER_OB_CURVE’, ’OUTLINER_OB_LATTICE’, ’OUTLINER_OB_META’, ’OUTLINER_OB_LAMP’, ’OUTLINER_OB_CAMERA’, ’OUTLINER_OB_ARMATURE’, ’OUTLINER_OB_FONT’, ’OUTLINER_OB_SURFACE’, ’RESTRICT_VIEW_OFF’, ’RESTRICT_VIEW_ON’, ’RESTRICT_SELECT_OFF’, ’RESTRICT_SELECT_ON’, ’RESTRICT_RENDER_OFF’, ’RESTRICT_RENDER_ON’, ’OUTLINER_DATA_EMPTY’, ’OUTLINER_DATA_MESH’, ’OUTLINER_DATA_CURVE’, ’OUTLINER_DATA_LATTICE’, ’OUTLINER_DATA_META’, ’OUTLINER_DATA_LAMP’, ’OUTLINER_DATA_CAMERA’, ’OUTLINER_DATA_ARMATURE’, ’OUTLINER_DATA’)*

`LINER_DATA_FONT`, `OUTLINER_DATA_SURFACE`, `OUTLINER_DATA_POSE`,
`MESH_PLANE`, `MESH_CUBE`, `MESH_CIRCLE`, `MESH_UVSHERE`,
`MESH_ICOSPHERE`, `MESH_GRID`, `MESH_MONKEY`, `MESH_CYLINDER`,
`MESH_TORUS`, `MESH_CONE`, `LAMP_POINT`, `LAMP_SUN`, `LAMP_SPOT`,
`LAMP_HEMI`, `LAMP_AREA`, `META_PLANE`, `META_CUBE`, `META_BALL`,
`META_ELLIPSOID`, `META_CAPSULE`, `SURFACE_NCURVE`, `SURFACE_NCIRCLE`,
`SURFACE_NSURFACE`, `SURFACE_NTORUS`, `CURVE_BEZCURVE`,
`CURVE_BEZCIRCLE`, `CURVE_NCURVE`, `CURVE_NCIRCLE`, `CURVE_PATH`,
`FORCE_FORCE`, `FORCE_WIND`, `FORCE_VORTEX`, `FORCE_MAGNETIC`,
`FORCE_HARMONIC`, `FORCE_CHARGE`, `FORCE_LENNARDJONES`,
`FORCE_TEXTURE`, `FORCE_CURVE`, `FORCE_BOID`, `FORCE_TURBULENCE`,
`FORCE_DRAG`, `MODIFIER`, `MOD_WAVE`, `MOD_BUILD`, `MOD_DECIM`,
`MOD_MIRROR`, `MOD_SOFT`, `MOD_SUBSURF`, `HOOK`, `MOD_PHYSICS`,
`MOD_PARTICLES`, `MOD_BOOLEAN`, `MOD_EDGESPLIT`, `MOD_ARRAY`,
`MOD_UVPROJECT`, `MOD_DISPLACE`, `MOD_CURVE`, `MOD_LATTICE`,
`CONSTRAINT_DATA`, `MOD_ARMATURE`, `MOD_SHRINKWRAP`,
`MOD_CAST`, `MOD_MESHDEFORM`, `MOD_BEVEL`, `MOD_SMOOTH`,
`MOD_SIMPLEDEFORM`, `MOD_MASK`, `MOD_CLOTH`, `MOD_EXPLODE`,
`MOD_FLUIDSIM`, `MOD_MULTRES`, `MOD_SMOKE`, `MOD_SOLIDIFY`,
`MOD_SCREW`, `REC`, `PLAY`, `FF`, `REW`, `PAUSE`, `PREV_KEYFRAME`,
`NEXT_KEYFRAME`, `PLAY_AUDIO`, `PLAY_REVERSE`, `PREVIEW_RANGE`,
`PMARKER_ACT`, `PMARKER_SEL`, `PMARKER`, `MARKER_HLT`, `MARKER`,
`SPACE2`, `SPACE3`, `KEY_DEHLT`, `KEY_HLT`, `MUTE_IPO_OFF`,
`MUTE_IPO_ON`, `VERTEXSEL`, `EDGESEL`, `FACESEL`, `ROTATE`, `CURSOR`,
`ROTATECOLLECTION`, `ROTATECENTER`, `ROTACTIVE`, `ALIGN`,
`SMOOTHCURVE`, `SPHERECURVE`, `ROOTCURVE`, `SHARPCURVE`,
`LINCURVE`, `NOCURVE`, `RNDCURVE`, `PROP_OFF`, `PROP_ON`,
`PROP_CON`, `PARTICLE_POINT`, `PARTICLE_TIP`, `PARTICLE_PATH`,
`MAN_TRANS`, `MAN_ROT`, `MAN_SCALE`, `MANIPUL`, `SNAP_OFF`, `SNAP_ON`,
`SNAP_NORMAL`, `SNAP_INCREMENT`, `SNAP_VERTEX`, `SNAP_EDGE`,
`SNAP_FACE`, `SNAP_VOLUME`, `STICKY_UVS_LOC`, `STICKY_UVS_DISABLE`,
`STICKY_UVS_VERT`, `CLIPUV_DEHLT`, `CLIPUV_HLT`, `SNAP_PEELED_OBJECT`,
`GRID`, `PASTEDOWN`, `COPYDOWN`, `PASTEFILIPUP`, `PASTEFILIPDOWN`,
`SNAP_SURFACE`, `RETOPO`, `UV_VERTEXSEL`, `UV_EDGESEL`,
`UV_FACESEL`, `UV_ISLANDSEL`, `UV_SYNC_SELECT`, `BBOX`, `WIRE`,
`SOLID`, `SMOOTH`, `POTATO`, `ORTHO`, `LOCKVIEW_OFF`, `LOCKVIEW_ON`,
`AXIS_SIDE`, `AXIS_FRONT`, `AXIS_TOP`, `NDOF_DOM`, `NDOF_TURN`,
`NDOF_FLY`, `NDOF_TRANS`, `LAYER_USED`, `LAYER_ACTIVE`, `SORTALPHA`,
`SORTBYEXT`, `SORTTIME`, `SORTSIZE`, `LONGDISPLAY`, `SHORTDISPLAY`,
`GHOST`, `IMGDISPLAY`, `BOOKMARKS`, `FONTPREVIEW`, `FILTER`,
`NEWFOLDER`, `FILE_PARENT`, `FILE_REFRESH`, `FILE_FOLDER`,
`FILE_BLANK`, `FILE_BLEND`, `FILE_IMAGE`, `FILE_MOVIE`, `FILE_SCRIPT`,
`FILE_SOUND`, `FILE_FONT`, `BACK`, `FORWARD`, `DISK_DRIVE`, `MATPLANE`,
`MATSPHERE`, `MATCUBE`, `MONKEY`, `HAIR`, `ALIASED`,
`ANTIALIASED`, `MAT_SPHERE_SKY`, `WORDWRAP_OFF`, `WORDWRAP_ON`,
`SYNTAX_OFF`, `SYNTAX_ON`, `LINENUMBERS_OFF`, `LINENUMBERS_ON`,
`SCRIPTPLUGINS`, `SEQ_SEQUENCER`, `SEQ_PREVIEW`,
`SEQ_LUMA_WAVEFORM`, `SEQ_CHROMA_SCOPE`, `SEQ_HISTOGRAM`,
`SEQ_SPLITVIEW`, `IMAGE_RGB`, `IMAGE_RGB_ALPHA`, `IMAGE_ALPHA`, `IMAGE_ZDEPTH`,
`IMAGEFILE`, `BRUSH_ADD`, `BRUSH_BLOB`, `BRUSH_BLUR`,
`BRUSH_CLAY`, `BRUSH_CLONE`, `BRUSHCREASE`, `BRUSH_DARKEN`,
`BRUSH_FILL`, `BRUSH_FLATTEN`, `BRUSH_GRAB`, `BRUSH_INFLATE`,
`BRUSH_LAYER`, `BRUSH_LIGHTEN`, `BRUSH_MIX`, `BRUSH_MULTIPLY`,

‘BRUSH_NUDGE’, ‘BRUSH_PINCH’, ‘BRUSH_SCRAPE’, ‘BRUSH_SCULPT_DRAW’,
‘BRUSH_SMEAR’, ‘BRUSH_SMOOTH’, ‘BRUSH_SNAKE_HOOK’,
‘BRUSH_SOFTEN’, ‘BRUSH_SUBTRACT’, ‘BRUSH_TEXDRAW’, ‘BRUSH_THUMB’,
‘BRUSH_ROTATE’, ‘BRUSH_VERTEXDRAW’, ‘VIEW3D_VEC’, ‘EDIT_VEC’, ‘ED-
ITMODE_DEHLT’, ‘EDITMODE_HLT’, ‘DISCLOSURE_TRI_RIGHT_VEC’, ‘DIS-
CLOSURE_TRI_DOWN_VEC’, ‘MOVE_UP_VEC’, ‘MOVE_DOWN_VEC’, ‘X_VEC’,
‘SMALL_TRI_RIGHT_VEC’], (optional)) – Icon, Override automatic icon of the item

label (*text*=““, *icon*='NONE')

Item. Display text in the layout.

Parameters

- **text** (*string*, (optional)) – Override automatic text of the item.
- **icon** (*enum* in [‘NONE’, ‘QUESTION’, ‘ERROR’, ‘CANCEL’, ‘TRIA_RIGHT’, ‘TRIA_DOWN’, ‘TRIA_LEFT’, ‘TRIA_UP’, ‘ARROW_LEFTRIGHT’, ‘PLUS’, ‘DISCLOSURE_TRI_DOWN’, ‘DISCLOSURE_TRI_RIGHT’, ‘RADIOBUT_OFF’, ‘RADIOBUT_ON’, ‘MENU_PANEL’, ‘BLENDER’, ‘DOT’, ‘X’, ‘GO_LEFT’, ‘PLUG’, ‘UI’, ‘NODE’, ‘NODE_SEL’, ‘FULLSCREEN’, ‘SPLITSCREEN’, ‘RIGHTARROW_THIN’, ‘BORDERMOVE’, ‘VIEWZOOM’, ‘ZOMMIN’, ‘ZOOMOUT’, ‘PANEL_CLOSE’, ‘COPY_ID’, ‘EYEDROPPER’, ‘LINK_AREA’, ‘AUTO’, ‘CHECKBOX_DEHLT’, ‘CHECKBOX_HLT’, ‘UNLOCKED’, ‘LOCKED’, ‘UNPINNED’, ‘PINNED’, ‘SCREEN_BACK’, ‘RIGHTARROW’, ‘DOWNARROW_HLT’, ‘DOTSUP’, ‘DOTSDOWN’, ‘LINK’, ‘INLINK’, ‘PLUGIN’, ‘HELP’, ‘GHOST_ENABLED’, ‘COLOR’, ‘LINKED’, ‘UNLINKED’, ‘HAND’, ‘ZOOM_ALL’, ‘ZOOM_SELECTED’, ‘ZOOM_PREVIOUS’, ‘ZOOM_IN’, ‘ZOOM_OUT’, ‘RENDER_REGION’, ‘BORDER_RECT’, ‘BORDER_LASSO’, ‘FREEZE’, ‘STYLUS_PRESSURE’, ‘GHOST_DISABLED’, ‘NEW’, ‘FILE_TICK’, ‘QUIT’, ‘URL’, ‘RECOVER_LAST’, ‘FULLSCREEN_ENTER’, ‘FULLSCREEN_EXIT’, ‘BLANKI’, ‘LAMP’, ‘MATERIAL’, ‘TEXTURE’, ‘ANIM’, ‘WORLD’, ‘SCENE’, ‘EDIT’, ‘GAME’, ‘RADIO’, ‘SCRIPT’, ‘PARTICLES’, ‘PHYSICS’, ‘SPEAKER’, ‘TEXTURE_SHADED’, ‘VIEW3D’, ‘IPO’, ‘OOPS’, ‘BUTS’, ‘FILESEL’, ‘IMAGE_COL’, ‘INFO’, ‘SEQUENCE’, ‘TEXT’, ‘IMASEL’, ‘SOUND’, ‘ACTION’, ‘NLA’, ‘SCRIPTWIN’, ‘TIME’, ‘NODETREE’, ‘LOGIC’, ‘CONSOLE’, ‘PREFERENCES’, ‘ASSET_MANAGER’, ‘OBJECT_DATAMODE’, ‘EDITMODE_HLT’, ‘FACESEL_HLT’, ‘VPAINT_HLT’, ‘TPAINT_HLT’, ‘WPAINT_HLT’, ‘SCULPTMODE_HLT’, ‘POSE_HLT’, ‘PARTICLEMODE’, ‘LIGHTPAINT’, ‘SCENE_DATA’, ‘RENDERLAYERS’, ‘WORLD_DATA’, ‘OBJECT_DATA’, ‘MESH_DATA’, ‘CURVE_DATA’, ‘META_DATA’, ‘LATTICE_DATA’, ‘LAMP_DATA’, ‘MATERIAL_DATA’, ‘TEXTURE_DATA’, ‘ANIM_DATA’, ‘CAMERA_DATA’, ‘PARTICLE_DATA’, ‘LIBRARY_DATA_DIRECT’, ‘GROUP’, ‘ARMATURE_DATA’, ‘POSE_DATA’, ‘BONE_DATA’, ‘CONSTRAINT’, ‘SHAPEKEY_DATA’, ‘CONSTRAINT_BONE’, ‘PACKAGE’, ‘UGLYPACKAGE’, ‘BRUSH_DATA’, ‘IMAGE_DATA’, ‘FILE’, ‘FCURVE’, ‘FONT_DATA’, ‘RENDER_RESULT’, ‘SURFACE_DATA’, ‘EMPTY_DATA’, ‘SETTINGS’, ‘RENDER_ANIMATION’, ‘RENDER_STILL’, ‘BOIDS’, ‘STRANDS’, ‘LIBRARY_DATA_INDIRECT’, ‘GREASEPENCIL’, ‘GROUP_BONE’, ‘GROUP_VERTEX’, ‘GROUP_VCOL’, ‘GROUP_UVS’, ‘RNA’, ‘RNA_ADD’, ‘OUTLINER_OB_EMPTY’, ‘OUTLINER_OB_MESH’, ‘OUTLINER_OB_CURVE’, ‘OUTLINER_OB_LATTICE’, ‘OUTLINER_OB_META’, ‘OUTLINER_OB_LAMP’, ‘OUTLINER_OB_CAMERA’, ‘OUTLINER_OB_ARMATURE’, ‘OUTLINER_OB_FONT’, ‘OUTLINER_OB_SURFACE’, ‘RESTRICT_VIEW_OFF’, ‘RESTRICT_VIEW_ON’, ‘RESTRICT_SELECT_OFF’, ‘RESTRICT_SELECT_ON’, ‘RESTRICT_RENDER_OFF’, ‘RESTRICT_RENDER_ON’, ‘OUTLINER_DATA_EMPTY’, ‘OUTLINER_DATA_MESH’, ‘OUTLINER_DATA_CURVE’, ‘OUTLINER_DATA_LATTICE’, ‘OUTLINER_DATA_META’, ‘OUTLINER_DATA_LAMP’, ‘OUTLINER_DATA_CAMERA’, ‘OUTLINER_DATA_ARMATURE’, ‘OUT-

LINER_DATA_FONT, ‘*OUTLINER_DATA_SURFACE*’, ‘*OUTLINER_DATA_POSE*’, ‘*MESH_PLANE*’, ‘*MESH_CUBE*’, ‘*MESH_CIRCLE*’, ‘*MESH_UVSPHERE*’, ‘*MESH_ICOSPHERE*’, ‘*MESH_GRID*’, ‘*MESH_MONKEY*’, ‘*MESH_CYLINDER*’, ‘*MESH_TORUS*’, ‘*MESH_CONE*’, ‘*LAMP_POINT*’, ‘*LAMP_SUN*’, ‘*LAMP_SPOT*’, ‘*LAMP_HEMI*’, ‘*LAMP_AREA*’, ‘*META_PLANE*’, ‘*META_CUBE*’, ‘*META_BALL*’, ‘*META_ELLIPSOID*’, ‘*META_CAPSULE*’, ‘*SURFACE_NCURVE*’, ‘*SURFACE_NCIRCLE*’, ‘*SURFACE_NSURFACE*’, ‘*SURFACE_NCYLINDER*’, ‘*SURFACE_NSHERE*’, ‘*SURFACE_NTORUS*’, ‘*CURVE_BEZCURVE*’, ‘*CURVE_BEZCIRCLE*’, ‘*CURVE_NCURVE*’, ‘*CURVE_NCIRCLE*’, ‘*CURVE_PATH*’, ‘*FORCE_FORCE*’, ‘*FORCE_WIND*’, ‘*FORCE_VORTEX*’, ‘*FORCE_MAGNETIC*’, ‘*FORCE_HARMONIC*’, ‘*FORCE_CHARGE*’, ‘*FORCE_LENNARDJONES*’, ‘*FORCE_TEXTURE*’, ‘*FORCE_CURVE*’, ‘*FORCE_BOID*’, ‘*FORCE_TURBULENCE*’, ‘*FORCE_DRAG*’, ‘*MODIFIER*’, ‘*MOD_WAVE*’, ‘*MOD_BUILD*’, ‘*MOD_DECIM*’, ‘*MOD_MIRROR*’, ‘*MOD_SOFT*’, ‘*MOD_SUBSURF*’, ‘*HOOK*’, ‘*MOD_PHYSICS*’, ‘*MOD_PARTICLES*’, ‘*MOD_BOOLEAN*’, ‘*MOD_EDGESPLIT*’, ‘*MOD_ARRAY*’, ‘*MOD_UVPROJECT*’, ‘*MOD_DISPLACE*’, ‘*MOD_CURVE*’, ‘*MOD_LATTICE*’, ‘*CONSTRAINT_DATA*’, ‘*MOD_ARMATURE*’, ‘*MOD_SHRINKWRAP*’, ‘*MOD_CAST*’, ‘*MOD_MESHDEFORM*’, ‘*MOD_BEVEL*’, ‘*MOD_SMOOTH*’, ‘*MOD_SIMPLEDEFORM*’, ‘*MOD_MASK*’, ‘*MOD_CLOTH*’, ‘*MOD_EXPLODE*’, ‘*MOD_FLUIDSIM*’, ‘*MOD_MULTRES*’, ‘*MOD_SMOKE*’, ‘*MOD_SOLIDIFY*’, ‘*MOD_SCREW*’, ‘*REC*’, ‘*PLAY*’, ‘*FF*’, ‘*REW*’, ‘*PAUSE*’, ‘*PREV_KEYFRAME*’, ‘*NEXT_KEYFRAME*’, ‘*PLAY_AUDIO*’, ‘*PLAY_REVERSE*’, ‘*PREVIEW_RANGE*’, ‘*PMARKER_ACT*’, ‘*PMARKER_SEL*’, ‘*PMARKER*’, ‘*MARKER_HLT*’, ‘*MARKER*’, ‘*SPACE2*’, ‘*SPACE3*’, ‘*KEY_DEHLT*’, ‘*KEY_HLT*’, ‘*MUTE_IPO_OFF*’, ‘*MUTE_IPO_ON*’, ‘*VERTEXSEL*’, ‘*EDGESEL*’, ‘*FACESEL*’, ‘*ROTATE*’, ‘*CURSOR*’, ‘*ROTATECOLLECTION*’, ‘*ROTATECENTER*’, ‘*ROTACTIVE*’, ‘*ALIGN*’, ‘*SMOOTHCURVE*’, ‘*SPHERECURVE*’, ‘*ROOTCURVE*’, ‘*SHARPCURVE*’, ‘*LINCURVE*’, ‘*NOCURVE*’, ‘*RNDCURVE*’, ‘*PROP_OFF*’, ‘*PROP_ON*’, ‘*PROP_CON*’, ‘*PARTICLE_POINT*’, ‘*PARTICLE_TIP*’, ‘*PARTICLE_PATH*’, ‘*MAN_TRANS*’, ‘*MAN_ROT*’, ‘*MAN_SCALE*’, ‘*MANIPUL*’, ‘*SNAP_OFF*’, ‘*SNAP_ON*’, ‘*SNAP_NORMAL*’, ‘*SNAP_INCREMENT*’, ‘*SNAP_VERTEX*’, ‘*SNAP_EDGE*’, ‘*SNAP_FACE*’, ‘*SNAP_VOLUME*’, ‘*STICKY_UVS_LOC*’, ‘*STICKY_UVS_DISABLE*’, ‘*STICKY_UVS_VERT*’, ‘*CLIPUV_DEHLT*’, ‘*CLIPUV_HLT*’, ‘*SNAP_PEELED_OBJECT*’, ‘*GRID*’, ‘*PASTEDOWN*’, ‘*COPYDOWN*’, ‘*PASTEFLIPUP*’, ‘*PASTEFLIPDOWN*’, ‘*SNAP_SURFACE*’, ‘*RETOPO*’, ‘*UV_VERTEXSEL*’, ‘*UV_EDGESEL*’, ‘*UV_FACESEL*’, ‘*UV_ISLANDSEL*’, ‘*UV_SYNC_SELECT*’, ‘*BBOX*’, ‘*WIRE*’, ‘*SOLID*’, ‘*SMOOTH*’, ‘*POTATO*’, ‘*ORTHO*’, ‘*LOCKVIEW_OFF*’, ‘*LOCKVIEW_ON*’, ‘*AXIS_SIDE*’, ‘*AXIS_FRONT*’, ‘*AXIS_TOP*’, ‘*NDOF_DOM*’, ‘*NDOF_TURN*’, ‘*NDOF_FLY*’, ‘*NDOF_TRANS*’, ‘*LAYER_USED*’, ‘*LAYER_ACTIVE*’, ‘*SORTALPHA*’, ‘*SORTBYEXT*’, ‘*SORTTIME*’, ‘*SORTSIZE*’, ‘*LONGDISPLAY*’, ‘*SHORTDISPLAY*’, ‘*GHOST*’, ‘*IMGDISPLAY*’, ‘*BOOKMARKS*’, ‘*FONTPREVIEW*’, ‘*FILTER*’, ‘*NEWFOLDER*’, ‘*FILE_PARENT*’, ‘*FILE_REFRESH*’, ‘*FILE_FOLDER*’, ‘*FILE_BLANK*’, ‘*FILE_BLEND*’, ‘*FILE_IMAGE*’, ‘*FILE_MOVIE*’, ‘*FILE_SCRIPT*’, ‘*FILE_SOUND*’, ‘*FILE_FONT*’, ‘*BACK*’, ‘*FORWARD*’, ‘*DISK_DRIVE*’, ‘*MAT_PLANE*’, ‘*MATSPHERE*’, ‘*MATCUBE*’, ‘*MONKEY*’, ‘*HAIR*’, ‘*ALIASED*’, ‘*ANTIALIASED*’, ‘*MAT_SPHERE_SKY*’, ‘*WORDWRAP_OFF*’, ‘*WORDWRAP_ON*’, ‘*SYNTAX_OFF*’, ‘*SYNTAX_ON*’, ‘*LINENUMBERS_OFF*’, ‘*LINENUMBERS_ON*’, ‘*SCRIPTPLUGINS*’, ‘*SEQ_SEQUENCER*’, ‘*SEQ_PREVIEW*’, ‘*SEQ_LUMA_WAVEFORM*’, ‘*SEQ_CHROMA_SCOPE*’, ‘*SEQ_HISTOGRAM*’, ‘*SEQ_SPLITVIEW*’, ‘*IMAGE_RGB*’, ‘*IMAGE_RGB_ALPHA*’, ‘*IMAGE_ALPHA*’, ‘*IMAGE_ZDEPTH*’, ‘*IMAGEFILE*’, ‘*BRUSH_ADD*’, ‘*BRUSH_BLOB*’, ‘*BRUSH_BLUR*’, ‘*BRUSH_CLAY*’, ‘*BRUSH_CLONE*’, ‘*BRUSHCREASE*’, ‘*BRUSH_DARKEN*’, ‘*BRUSH_FILL*’, ‘*BRUSH_FLATTEN*’, ‘*BRUSH_GRAB*’, ‘*BRUSH_INFLATE*’, ‘*BRUSH_LAYER*’, ‘*BRUSH_LIGHTEN*’, ‘*BRUSH_MIX*’, ‘*BRUSH_MULTIPLY*,

‘BRUSH_NUDGE’, ‘BRUSH_PINCH’, ‘BRUSH_SCRAPE’, ‘BRUSH_SCULPT_DRAW’,
‘BRUSH_SMEAR’, ‘BRUSH_SMOOTH’, ‘BRUSH_SNAKE_HOOK’,
‘BRUSH_SOFTEN’, ‘BRUSH_SUBTRACT’, ‘BRUSH_TEXDRAW’, ‘BRUSH_THUMB’,
‘BRUSH_ROTATE’, ‘BRUSH_VERTEXDRAW’, ‘VIEW3D_VEC’, ‘EDIT_VEC’, ‘EDITMODE_DEHLT’,
‘EDITMODE_HLT’, ‘DISCLOSURE_TRI_RIGHT_VEC’, ‘DISCLOSURE_TRI_DOWN_VEC’,
‘MOVE_UP_VEC’, ‘MOVE_DOWN_VEC’, ‘X_VEC’,
‘SMALL_TRI_RIGHT_VEC’], (optional)) – Icon, Override automatic icon of the item

menu (*menu, text=""*, *icon='NONE'*)
menu

Parameters

`LINER_DATA_LATTICE`, `OUTLINER_DATA_META`, `OUTLINER_DATA_LAMP`,
`OUTLINER_DATA_CAMERA`, `OUTLINER_DATA_ARMATURE`, `OUTLINER_DATA_FONT`, `OUTLINER_DATA_SURFACE`, `OUTLINER_DATA_POSE`,
`MESH_PLANE`, `MESH_CUBE`, `MESH_CIRCLE`, `MESH_UVSPHERE`,
`MESH_ICOSPHERE`, `MESH_GRID`, `MESH_MONKEY`, `MESH_CYLINDER`,
`MESH_TORUS`, `MESH_CONE`, `LAMP_POINT`, `LAMP_SUN`, `LAMP_SPOT`,
`LAMP_HEMI`, `LAMP_AREA`, `META_PLANE`, `META_CUBE`, `META_BALL`,
`META_ELLIPSOID`, `META_CAPSULE`, `SURFACE_NCURVE`, `SURFACE_NCIRCLE`,
`SURFACE_NSURFACE`, `SURFACE_NCYLINDER`, `SURFACE_NSPHERE`,
`SURFACE_NTORUS`, `CURVE_BEZCURVE`, `CURVE_BEZCIRCLE`, `CURVE_NCURVE`, `CURVE_NCIRCLE`, `CURVE_PATH`,
`FORCE_FORCE`, `FORCE_WIND`, `FORCE_VORTEX`, `FORCE_MAGNETIC`,
`FORCE_HARMONIC`, `FORCE_CHARGE`, `FORCE_LENNARDJONES`,
`FORCE_TEXTURE`, `FORCE_CURVE`, `FORCE_BOID`, `FORCE_TURBULENCE`,
`FORCE_DRAG`, `MODIFIER`, `MOD_WAVE`, `MOD_BUILD`, `MOD_DECIM`,
`MOD_MIRROR`, `MOD_SOFT`, `MOD_SUBSURF`, `HOOK`, `MOD_PHYSICS`,
`MOD_PARTICLES`, `MOD_BOOLEAN`, `MOD_EDGESPLIT`, `MOD_ARRAY`,
`MOD_UVPROJECT`, `MOD_DISPLACE`, `MOD_CURVE`, `MOD_LATTICE`,
`CONSTRAINT_DATA`, `MOD_ARMATURE`, `MOD_SHRINKWRAP`,
`MOD_CAST`, `MOD_MESHDEFORM`, `MOD_BEVEL`, `MOD_SMOOTH`,
`MOD_SIMPLEDEFORM`, `MOD_MASK`, `MOD_CLOTH`, `MOD_EXPLODE`,
`MOD_FLUIDSIM`, `MOD_MULTIRES`, `MOD_SMOKE`, `MOD_SOLIDIFY`,
`MOD_SCREW`, `REC`, `PLAY`, `FF`, `REW`, `PAUSE`, `PREV_KEYFRAME`,
`NEXT_KEYFRAME`, `PLAY_AUDIO`, `PLAY_REVERSE`, `PREVIEW_RANGE`,
`PMARKER_ACT`, `PMARKER_SEL`, `PMARKER`, `MARKER_HLT`, `MARKER`,
`SPACE2`, `SPACE3`, `KEY_DEHLT`, `KEY_HLT`, `MUTE_IPO_OFF`,
`MUTE_IPO_ON`, `VERTEXSEL`, `EDGESEL`, `FACESEL`, `ROTATE`, `CURSOR`,
`ROTATECOLLECTION`, `ROTATECENTER`, `ROTACTIVE`, `ALIGN`,
`SMOOTHCURVE`, `SPHERERECURVE`, `ROOTCURVE`, `SHARPCURVE`,
`LINCURVE`, `NOCURVE`, `RNDcurve`, `PROP_OFF`, `PROP_ON`,
`PROP_CON`, `PARTICLE_POINT`, `PARTICLE_TIP`, `PARTICLE_PATH`,
`MAN_TRANS`, `MAN_ROT`, `MAN_SCALE`, `MANIPUL`, `SNAP_OFF`, `SNAP_ON`,
`SNAP_NORMAL`, `SNAP_INCREMENT`, `SNAP_VERTEX`, `SNAP_EDGE`,
`SNAP_FACE`, `SNAP_VOLUME`, `STICKY_UVS_LOC`, `STICKY_UVS_DISABLE`,
`STICKY_UVS_VERT`, `CLIPUV_DEHLT`, `CLIPUV_HLT`, `SNAP_PEELE_OBJECT`,
`GRID`, `PASTEDOWN`, `COPYDOWN`, `PASTEFLIPUP`, `PASTEFLIPDOWN`,
`SNAP_SURFACE`, `RETOPO`, `UV_VERTEXSEL`, `UV_EDGESEL`,
`UV_FACESEL`, `UV_ISLANDSEL`, `UV_SYNC_SELECT`, `BBOX`, `WIRE`,
`SOLID`, `SMOOTH`, `POTATO`, `ORTHO`, `LOCKVIEW_OFF`, `LOCKVIEW_ON`,
`AXIS_SIDE`, `AXIS_FRONT`, `AXIS_TOP`, `NDOF_DOM`, `NDOF_TURN`,
`NDOF_FLY`, `NDOF_TRANS`, `LAYER_USED`, `LAYER_ACTIVE`, `SORTALPHA`,
`SORTBYEXT`, `SORTTIME`, `SORTSIZE`, `LONGDISPLAY`, `SHORTDISPLAY`,
`HOST`, `IMGDISPLAY`, `BOOKMARKS`, `FONTPREVIEW`, `FILTER`,
`NEWFOLDER`, `FILE_PARENT`, `FILE_REFRESH`, `FILE_FOLDER`,
`FILE_BLANK`, `FILE_BLEND`, `FILE_IMAGE`, `FILE_MOVIE`, `FILE_SCRIPT`,
`FILE_SOUND`, `FILE_FONT`, `BACK`, `FORWARD`, `DISK_DRIVE`, `MATPLANE`,
`MATSPHERE`, `MATCUBE`, `MONKEY`, `HAIR`, `ALIASED`,
`ANTIALIASED`, `MAT_SPHERE_SKY`, `WORDWRAP_OFF`, `WORDWRAP_ON`,
`SYNTAX_OFF`, `SYNTAX_ON`, `LINENUMBERS_OFF`, `LINENUMBERS_ON`,
`SCRIPTPLUGINS`, `SEQ_SEQUENCER`, `SEQ_PREVIEW`,
`SEQ_LUMA_WAVEFORM`, `SEQ_CHROMA_SCOPE`, `SEQ_HISTOGRAM`,
`SEQ_SPLITVIEW`, `IMAGE_RGB`, `IMAGE_RGB_ALPHA`, `IMAGE_ALPHA`, `IMAGE_ZDEPTH`,
`IMAGEFILE`, `BRUSH_ADD`, `BRUSH_BLOB`, `BRUSH_BLUR`,
`BRUSH_CLAY`, `BRUSH_CLONE`, `BRUSHCREASE`, `BRUSH_DARKEN`,

'BRUSH_FILL', 'BRUSH_FLATTEN', 'BRUSH_GRAB', 'BRUSH_INFLATE',
'BRUSH_LAYER', 'BRUSH_LIGHTEN', 'BRUSH_MIX', 'BRUSH_MULTIPLY',
'BRUSH_NUDGE', 'BRUSH_PINCH', 'BRUSH_SCRAPE', 'BRUSH_SCULPT_DRAW',
'BRUSH_SMEAR', 'BRUSH_SMOOTH', 'BRUSH_SNAKE_HOOK',
'BRUSH_SOFTEN', 'BRUSH_SUBTRACT', 'BRUSH_TEXDRAW', 'BRUSH_THUMB',
'BRUSH_ROTATE', 'BRUSH_VERTEXDRAW', 'VIEW3D_VEC', 'EDIT_VEC', 'EDITMODE_DEHLT',
'EDITMODE_HLT', 'DISCLOSURE_TRI_RIGHT_VEC', 'DISCLOSURE_TRI_DOWN_VEC',
'MOVE_UP_VEC', 'MOVE_DOWN_VEC', 'X_VEC',
'SMALL_TRI_RIGHT_VEC'], (optional)) – Icon, Override automatic icon of the item

separator()

Item. Inserts empty space into the layout between items.

context_pointer_set (name, data)

context_pointer_set

Parameters

- **name** (string) – Name, Name of entry in the context.
- **data** (AnyType) – Pointer to put in context.

template_header (menus=True)

template_header

Parameters **menus** (boolean, (optional)) – The header has menus, and should show menu expander.

template_ID (data, property, new=""“, open=""“, unlink=""“)

template_ID

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (string) – Identifier of property in data.
- **new** (string, (optional)) – Operator identifier to create a new ID block.
- **open** (string, (optional)) – Operator identifier to open a file for creating a new ID block.
- **unlink** (string, (optional)) – Operator identifier to unlink the ID block.

template_ID_preview (data, property, new=""“, open=""“, unlink=""“, rows=0, cols=0)

template_ID_preview

Parameters

- **data** (AnyType, (never None)) – Data from which to take property.
- **property** (string) – Identifier of property in data.
- **new** (string, (optional)) – Operator identifier to create a new ID block.
- **open** (string, (optional)) – Operator identifier to open a file for creating a new ID block.
- **unlink** (string, (optional)) – Operator identifier to unlink the ID block.
- **rows** (int in [0, inf], (optional)) – Number of thumbnail preview rows to display
- **cols** (int in [0, inf], (optional)) – Number of thumbnail preview columns to display

template_any_ID (data, property, type_property, text=""“)

template_any_ID

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **type_property** (*string*) – Identifier of property in data giving the type of the ID-blocks to use.
- **text** (*string, (optional)*) – Custom label to display in UI.

template_path_builder (*data, property, root, text=""*)
template_path_builder

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **root** ([ID](#)) – ID-block from which path is evaluated from.
- **text** (*string, (optional)*) – Custom label to display in UI.

template_modifier (*data*)
Layout . Generates the UI layout for modifiers.

Parameters **data** ([Modifier](#), (never None)) – Modifier data.

Returns Sub-layout to put items in.

Return type [UILayout](#)

template_constraint (*data*)
Layout . Generates the UI layout for constraints.

Parameters **data** ([Constraint](#), (never None)) – Constraint data.

Returns Sub-layout to put items in.

Return type [UILayout](#)

template_preview (*id, show_buttons=True, parent=None, slot=None*)
Item. A preview window for materials, textures, lamps, etc.

Parameters

- **id** ([ID](#)) – ID datablock.
- **show_buttons** (*boolean, (optional)*) – Show preview buttons?
- **parent** ([ID, \(optional\)](#)) – ID datablock.
- **slot** ([TextureSlot, \(optional\)](#)) – Texture slot.

template_curve_mapping (*data, property, type='NONE', levels=False, brush=False*)
Item. A curve mapping widget used for e.g falloff curves for lamps.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **type** (*enum in ['NONE', 'VECTOR', 'COLOR'], (optional)*) – Type, Type of curves to display.
- **levels** (*boolean, (optional)*) – Show black/white levels.
- **brush** (*boolean, (optional)*) – Show brush options.

template_color_ramp (*data, property, expand=False*)

Item. A color ramp widget.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **expand** (*boolean, (optional)*) – Expand button to show more detail.

template_histogram (*data, property*)

Item. A histogramm widget to analyze imaga data.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_waveform (*data, property*)

Item. A waveform widget to analyze imaga data.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_vectorscope (*data, property*)

Item. A vectorscope widget to analyze imaga data.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.

template_layers (*data, property, used_layers_data, used_layers_property, active_layer*)

template_layers

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **used_layers_data** ([AnyType](#)) – Data from which to take property.
- **used_layers_property** (*string*) – Identifier of property in data.
- **active_layer** (*int in [0, inf]*) – Active Layer

template_color_wheel (*data, property, value_slider=False, lock=False, lock_luminosity=False, cubic=True*)

Item. A color wheel widget to pick colors.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **value_slider** (*boolean, (optional)*) – Display the value slider to the right of the color wheel
- **lock** (*boolean, (optional)*) – Lock the color wheel display to value 1.0 regardless of actual color
- **lock_luminosity** (*boolean, (optional)*) – Keep the color at its original vector length

- **cubic** (*boolean, (optional)*) – Cubic saturation for picking values close to white

template_image_layers (*image, image_user*)
template_image_layers

template_image (*data, property, image_user, compact=False*)

Item(s). User interface for selecting images and their source paths.

Parameters

- **data** ([AnyType](#), (never None)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **compact** (*boolean, (optional)*) – Use more compact layout.

template_list (*data, property, active_data, active_property, rows=5, maxrows=5, type='DEFAULT'*)

Item. A list widget to display data. e.g. vertexgroups.

Parameters

- **data** ([AnyType](#)) – Data from which to take property.
- **property** (*string*) – Identifier of property in data.
- **active_data** ([AnyType](#), (never None)) – Data from which to take property for the active element.
- **active_property** (*string*) – Identifier of property in data, for the active element.
- **rows** (*int in [0, inf], (optional)*) – Number of rows to display.
- **maxrows** (*int in [0, inf], (optional)*) – Maximum number of rows to display.
- **type** (*enum in ['DEFAULT', 'COMPACT', 'ICONS'], (optional)*) – Type, Type of list to use.

template_running_jobs ()
template_running_jobs

template_operator_search ()
template_operator_search

template_header_3D ()
template_header_3D

template_edit_mode_selection ()
template_edit_mode_selection

template_reports_banner ()
template_reports_banner

introspect ()
introspect

Returns Descr, DESCRIPTOR

Return type string

Inherited Properties

- **bpy_struct.id_data**

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Header.layout`
- `Menu.layout`
- `Operator.layout`
- `Panel.layout`
- `UILayout.box`
- `UILayout.column`
- `UILayout.column_flow`
- `UILayout.row`
- `UILayout.split`
- `UILayout.template_constraint`
- `UILayout.template_modifier`

2.4.592 UVProjectModifier(Modifier)

base classes — `bpy_struct, Modifier`

class bpy.types.UVProjectModifier (Modifier)
UV projection modifier to sets UVs from a projector

aspect_x

Type float in [1, inf], default 0.0

aspect_y

Type float in [1, inf], default 0.0

image

Type Image

projector_count

Number of projectors to use

Type int in [1, 10], default 0

projectors

Type bpy_prop_collection of UVProjector, (readonly)

scale_x

Type float in [0, inf], default 0.0

scale_y

Type float in [0, inf], default 0.0

use_image_override

Override faces' current images with the given image

Type boolean, default False

uv_layer

UV layer name

Type string, default “”

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.593 UVProjector(bpy_struct)

base class — bpy_struct

```
class bpy.types.UVProjector(bpy_struct)
    UV projector used by the UV project modifier

    object
        Object to use as projector transform

    Type Object
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UVProjectModifier.projectors

2.4.594 UVTextures(bpy_struct)

base class — bpy_struct

```
class bpy.types.UVTextures(bpy_struct)
    Collection of uv textures

    active
        Active UV texture
        Type MeshTextureFaceLayer

    active_index
        Active UV texture index
        Type int in [0, inf], default 0

    new(name="UVTex")
        Add a UV texture layer to Mesh.
```

Parameters `name` (*string, (optional)*) – UV Texture name.

Returns The newly created layer.

Return type `MeshTextureFaceLayer`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Mesh.uv_textures`

2.4.595 UnitSettings(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.UnitSettings` (`bpy_struct`)

`scale_length`

Scale to use when converting between blender units and dimensions

Type float in [1e-05, 100000], default 0.0

`system`

The unit system to use for button display

Type enum in ['NONE', 'METRIC', 'IMPERIAL'], default 'NONE'

`system_rotation`

Unit to use for displaying/editing rotation values

Type enum in ['DEGREES', 'RADIAN'], default 'DEGREES'

use_separate

Display units in pairs

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Scene.unit_settings

2.4.596 UnknownType(bpy_struct)

base class — bpy_struct

class bpy.types.UnknownType (bpy_struct)

Stub RNA type used for pointers to unknown or internal data

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ShapeKey.data
- SpaceSequenceEditor.grease_pencil

2.4.597 UserPreferences(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferences** (*bpy_struct*)
Global user preferences

active_section
Active section of the user preferences shown in the user interface
Type enum in ['INTERFACE', 'EDITING', 'INPUT', 'ADDONS', 'THEMES', 'FILES', 'SYSTEM'], default 'INTERFACE'

addons
Type Addons bpy_prop_collection of Addon, (readonly)

edit
Settings for interacting with Blender data
Type UserPreferencesEdit, (readonly, never None)

filepaths
Default paths for external files
Type UserPreferencesFilePaths, (readonly, never None)

inputs
Settings for input devices
Type UserPreferencesInput, (readonly, never None)

system
Graphics driver and operating system settings
Type UserPreferencesSystem, (readonly, never None)

themes
Type bpy_prop_collection of Theme, (readonly)

ui_styles
Type bpy_prop_collection of ThemeStyle, (readonly)

view

Preferences related to viewing data

Type `UserPreferencesView`, (readonly, never None)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Context.user_preferences`

2.4.598 UserPreferencesEdit(bpy_struct)

base class — `bpy_struct`

`class bpy.types.UserPreferencesEdit (bpy_struct)`

Settings for interacting with Blender data

auto_keying_mode

Mode of automatic keyframe insertion for Objects and Bones

Type enum in [‘ADD_REPLACE_KEYS’, ‘REPLACE_KEYS’], default
‘ADD_REPLACE_KEYS’

grease_pencil_eraser_radius

Radius of eraser ‘brush’

Type int in [0, 100], default 0

grease_pencil_euclidean_distance

Distance moved by mouse when drawing stroke (in pixels) to include

Type int in [0, 100], default 0

grease_pencil_manhattan_distance
Pixels moved by mouse per axis when drawing stroke
Type int in [0, 100], default 0

keyframe_new_handle_type
Type enum in ['FREE', 'AUTO', 'VECTOR', 'ALIGNED'], default 'FREE'

keyframe_new_interpolation_type
Type enum in ['CONSTANT', 'LINEAR', 'BEZIER'], default 'CONSTANT'

material_link
Toggle whether the material is linked to object data or the object block
Type enum in ['OBDATA', 'OBJECT'], default 'OBDATA'

object_align
When adding objects from a 3D View menu, either align them to that view's direction or the world coordinates
Type enum in ['WORLD', 'VIEW'], default 'WORLD'

sculpt_paint_overlay_color
Color of texture overlay
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

undo_memory_limit
Maximum memory usage in megabytes (0 means unlimited)
Type int in [0, 32767], default 0

undo_steps
Number of undo steps available (smaller values conserve memory)
Type int in [0, 64], default 0

use_auto_keying
Automatic keyframe insertion for Objects and Bones
Type boolean, default False

use_drag_immediately
Moving things with a mouse drag confirms when releasing the button
Type boolean, default False

use_duplicate_action
Causes actions to be duplicated with the object
Type boolean, default False

use_duplicate_armature
Causes armature data to be duplicated with the object
Type boolean, default False

use_duplicate_curve
Causes curve data to be duplicated with the object
Type boolean, default False

use_duplicate_fcurve
Causes F-curve data to be duplicated with the object

Type boolean, default False

use_duplicate_lamp
Causes lamp data to be duplicated with the object

Type boolean, default False

use_duplicate_material
Causes material data to be duplicated with the object

Type boolean, default False

use_duplicate_mesh
Causes mesh data to be duplicated with the object

Type boolean, default False

use_duplicate_metaball
Causes metaball data to be duplicated with the object

Type boolean, default False

use_duplicate_particle
Causes particle systems to be duplicated with the object

Type boolean, default False

use_duplicate_surface
Causes surface data to be duplicated with the object

Type boolean, default False

use_duplicate_text
Causes text data to be duplicated with the object

Type boolean, default False

use_duplicate_texture
Causes texture data to be duplicated with the object

Type boolean, default False

use_enter_edit_mode
Enter Edit Mode automatically after adding a new object

Type boolean, default False

use_global_undo
Global undo works by keeping a full copy of the file itself in memory, so takes extra memory

Type boolean, default False

use_grease_pencil_simplify_stroke
Simplify the final stroke

Type boolean, default False

use_grease_pencil_smooth_stroke
Smooth the final stroke

Type boolean, default False

use_insertkey_xyz_to_rgb
Color for newly added transformation F-Curves (Location, Rotation, Scale) and also Color is based on the transform axis

Type boolean, default False

use_keyframe_insert_available
Automatic keyframe insertion in available curves
Type boolean, default False

use_keyframe_insert_needed
Keyframe insertion only when keyframe needed
Type boolean, default False

use_negative_frames
Current frame number can be manually set to a negative value
Type boolean, default False

use_visual_keying
Use Visual keying automatically for constrained objects
Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `UserPreferences.edit`

2.4.599 UserPreferencesFilePaths(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.UserPreferencesFilePaths` (`bpy_struct`)
Default paths for external files

animation_player

Path to a custom animation/frame sequence player

Type string, default “”

animation_player_preset

Preset configs for external animation players

Type enum in ['BLENDER24', 'DJV', 'FRAMECYCLER', 'RV', 'MPLAYER', 'CUSTOM'], default 'BLENDER24'

auto_save_time

The time (in minutes) to wait between automatic temporary saves

Type int in [1, 60], default 0

font_directory

The default directory to search for loading fonts

Type string, default “”

hide_recent_locations

Hide recent locations in the file selector

Type boolean, default False

image_editor

Path to an image editor

Type string, default “”

recent_files

Maximum number of recently opened files to remember

Type int in [0, 30], default 0

render_output_directory

The default directory for rendering output, for new scenes

Type string, default “”

save_version

The number of old versions to maintain in the current directory, when manually saving

Type int in [0, 32], default 0

script_directory

Alternate script path, matching the default layout with subdirs: startup, addons & modules (requires restart)

Type string, default “”

sequence_plugin_directory

The default directory to search for sequence plugins

Type string, default “”

show_hidden_files_datablocks

Hide files/datablocks that start with a dot(.)^{*}

Type boolean, default False

show_thumbnails

Open in thumbnail view for images and movies

Type boolean, default False

sound_directory

The default directory to search for sounds

Type string, default “”

temporary_directory

The directory for storing temporary save files

Type string, default “”

texture_directory

The default directory to search for textures

Type string, default “”

texture_plugin_directory

The default directory to search for texture plugins

Type string, default “”

use_auto_save_temporary_files

Automatic saving of temporary files in temp directory, uses process ID

Type boolean, default False

use_file_compression

Enable file compression when saving .blend files

Type boolean, default False

use_filter_files

Display only files with extensions in the image select window

Type boolean, default False

use_load_ui

Load user interface setup when loading .blend files

Type boolean, default False

use_relative_paths

Default relative path option for the file selector

Type boolean, default False

use_save_preview_images

Enables automatic saving of preview images in the .blend file

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get

- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- UserPreferences.filepaths

2.4.600 UserPreferencesInput(bpy_struct)

base class — bpy_struct

class bpy.types.**UserPreferencesInput** (bpy_struct)

Settings for input devices

active_keyconfig

The name of the active key configuration

Type string, default “”

drag_threshold

Amount of pixels you have to drag before dragging UI items happens

Type int in [3, 40], default 0

edited_keymaps

Type bpy_prop_collection of KeyMap, (readonly)

invert_mouse_zoom

Invert the axis of mouse movement for zooming

Type boolean, default False

invert_zoom_wheel

Swap the Mouse Wheel zoom direction

Type boolean, default False

mouse_double_click_time

The time (in ms) for a double click

Type int in [1, 1000], default 0

ndof_pan_speed

The overall panning speed of an NDOF device, as percent of standard

Type int in [0, 200], default 0

ndof_rotate_speed

The overall rotation speed of an NDOF device, as percent of standard

Type int in [0, 200], default 0

select_mouse

The mouse button used for selection

Type enum in ['LEFT', 'RIGHT'], default 'RIGHT'

use_emulate_numpad

Causes the 1 to 0 keys to act as the numpad (useful for laptops)

Type boolean, default False

use_mouse_continuous

Allow moving the mouse outside the view on some manipulations (transform, ui control drag)

Type boolean, default False

use_mouse_emulate_3_button

Emulates Middle Mouse with Alt+Left Mouse (doesn't work with Left Mouse Select option)

Type boolean, default False

use_mouse_mmb_paste

In text window, paste with middle mouse button instead of panning

Type boolean, default False

view_rotate_method

Rotation style in the viewport

Type enum in ['TURNTABLE', 'TRACKBALL'], default 'TURNTABLE'

view_zoom_axis

Axis of mouse movement to zoom in or out on

Type enum in ['VERTICAL', 'HORIZONTAL'], default 'VERTICAL'

view_zoom_method

Which style to use for viewport scaling

Type enum in ['CONTINUE', 'DOLLY', 'SCALE'], default 'CONTINUE'

wheel_scroll_lines

The number of lines scrolled at a time with the mouse wheel

Type int in [0, 32], default 0

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)

- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `UserPreferences.inputs`

2.4.601 UserPreferencesSystem(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.UserPreferencesSystem(`bpy_struct`)

Graphics driver and operating system settings

anisotropic_filter

The quality of the anisotropic filtering (values greater than 1.0 enable anisotropic filtering)

Type enum in ['FILTER_0', 'FILTER_2', 'FILTER_4', 'FILTER_8', 'FILTER_16'], default 'FILTER_0'

audio_channels

Sets the audio channel count

Type enum in ['MONO', 'STEREO', 'SURROUND4', 'SURROUND51', 'SURROUND71'], default 'MONO'

audio_device

Sets the audio output device

Type enum in ['NONE'], default 'NONE'

audio_mixing_buffer

Sets the number of samples used by the audio mixing buffer

Type enum in ['SAMPLES_256', 'SAMPLES_512', 'SAMPLES_1024', 'SAMPLES_2048', 'SAMPLES_4096', 'SAMPLES_8192', 'SAMPLES_16384', 'SAMPLES_32768'], default 'SAMPLES_256'

audio_sample_format

Sets the audio sample format

Type enum in ['U8', 'S16', 'S24', 'S32', 'FLOAT', 'DOUBLE'], default 'U8'

audio_sample_rate

Sets the audio sample rate

Type enum in ['RATE_44100', 'RATE_48000', 'RATE_96000', 'RATE_192000'], default 'RATE_44100'

author

Name that will be used in exported files when format supports such feature

Type string, default ""

color_picker_type

Different styles of displaying the color picker widget

Type enum in ['CIRCLE', 'SQUARE_SV', 'SQUARE_HS', 'SQUARE_HV'], default 'CIRCLE'

dpi

Font size and resolution for display

Type int in [48, 128], default 0

frame_server_port

Frameserver Port for Frameserver Rendering

Type int in [0, 32727], default 0

gl_clip_alpha

Clip alpha below this threshold in the 3D textured view

Type float in [0, 1], default 0.0

gl_texture_limit

Limit the texture size to save graphics memory

Type enum in ['CLAMP_OFF', 'CLAMP_8192', 'CLAMP_4096', 'CLAMP_2048', 'CLAMP_1024', 'CLAMP_512', 'CLAMP_256', 'CLAMP_128'], default 'CLAMP_OFF'

language

Language use for translation

Type enum in ['ENGLISH', 'JAPANESE', 'DUTCH', 'ITALIAN', 'GERMAN', 'FINNISH', 'SWEDISH', 'FRENCH', 'SPANISH', 'CATALAN', 'CZECH', 'BRAZILIAN_PORTUGUESE', 'SIMPLIFIED_CHINESE', 'RUSSIAN', 'CROATIAN', 'SERBIAN', 'UKRAINIAN', 'POLISH', 'ROMANIAN', 'ARABIC', 'BULGARIAN', 'GREEK', 'KOREAN'], default 'ENGLISH'

memory_cache_limit

Memory cache limit in sequencer (megabytes)

Type int in [0, 16384], default 0

prefetch_frames

Number of frames to render ahead during playback

Type int in [0, 500], default 0

screencast_fps

Frame rate for the screencast to be played back

Type int in [10, 50], default 0

screencast_wait_time

Time in milliseconds between each frame recorded for screencast

Type int in [50, 1000], default 0

scrollback

Maximum number of lines to store for the console buffer

Type int in [32, 32768], default 0

solid_lights

Lights user to display objects in solid draw mode

Type bpy_prop_collection of UserSolidLight, (readonly)

texture_collection_rate

Number of seconds between each run of the GL texture garbage collector

Type int in [1, 3600], default 0

texture_time_out
Time since last access of a GL texture in seconds after which it is freed. (Set to 0 to keep textures allocated.)

Type int in [0, 3600], default 0

use_antialiasing
Use anti-aliasing for the 3D view (may impact redraw performance)

Type boolean, default False

use_international_fonts
Use international fonts

Type boolean, default False

use_mipmaps
Scale textures for the 3D View (looks nicer but uses more memory and slows image reloading)

Type boolean, default False

use_preview_images
Enables automatic saving of preview images in the .blend file (Windows only)

Type boolean, default False

use_scripts_auto_execute
Allow any .blend file to run scripts automatically (unsafe with blend files from an untrusted source)

Type boolean, default False

use_tabs_as_spaces
Automatically converts all new tabs into spaces for new and loaded text files

Type boolean, default False

use_text_antialiasing
Draw user interface text anti-aliased

Type boolean, default False

use_textured_fonts
Use textures for drawing international fonts

Type boolean, default False

use_translate_buttons
Translate button labels

Type boolean, default False

use_translate_toolbox
Translate toolbox menu

Type boolean, default False

use_translate_tooltips
Translate Tooltips

Type boolean, default False

use_vertex_buffer_objects
Use Vertex Buffer Objects (or Vertex Arrays, if unsupported) for viewport rendering

Type boolean, default False

use_weight_color_range

Enable color range used for weight visualization in weight painting mode

Type boolean, default False

weight_color_range

Color range used for weight visualization in weight painting mode

Type [ColorRamp](#), (readonly, never None)

window_draw_method

Drawing method used by the window manager

Type enum in ['AUTOMATIC', 'TRIPLE_BUFFER', 'OVERLAP', 'OVERLAP_FLIP', 'FULL'], default 'TRIPLE_BUFFER'

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [UserPreferences.system](#)

2.4.602 UserPreferencesView(bpy_struct)

base class — [bpy_struct](#)

class [bpy.types.UserPreferencesView](#)([bpy_struct](#))

Preferences related to viewing data

manipulator_handle_size

Size of widget handles as percentage of widget radius

Type int in [2, 40], default 25

manipulator_hotspot

Pixel distance around the handles to accept mouse clicks

Type int in [4, 40], default 14

manipulator_size

Diameter of widget, in 10 pixel units

Type int in [2, 40], default 15

mini_axis_brightness

The brightness of the icon

Type int in [0, 10], default 0

mini_axis_size

The axis icon's size

Type int in [10, 64], default 0

object_origin_size

Diameter in Pixels for Object/Lamp origin display

Type int in [4, 10], default 0

open_left_mouse_delay

Time in 1/10 seconds to hold the Left Mouse Button before opening the toolbox

Type int in [1, 40], default 0

open_right_mouse_delay

Time in 1/10 seconds to hold the Right Mouse Button before opening the toolbox

Type int in [1, 40], default 0

open_sublevel_delay

Time delay in 1/10 seconds before automatically opening sub level menus

Type int in [1, 40], default 0

open_toplevel_delay

Time delay in 1/10 seconds before automatically opening top level menus

Type int in [1, 40], default 0

rotation_angle

The rotation step for numerical pad keys (2 4 6 8)

Type int in [0, 90], default 0

show_column_layout

Use a column layout for toolbox

Type boolean, default False

show_large_cursors

Use large mouse cursors when available

Type boolean, default False

show_manipulator

Use 3D transform manipulator

Type boolean, default False

show_mini_axis

Show a small rotating 3D axis in the bottom left corner of the 3D View

Type boolean, default False

show_object_info
Display objects name and frame number in 3D view

Type boolean, default False

show_playback_fps
Show the frames per second screen refresh rate, while animation is played back

Type boolean, default False

show_splash
Display splash screen on startup

Type boolean, default False

show_tooltips
Display tooltips

Type boolean, default False

show_tooltips_python
Show Python references in tooltips

Type boolean, default False

show_view_name
Show the name of the view's direction in each 3D View

Type boolean, default False

smooth_view
The time to animate the view in milliseconds, zero to disable

Type int in [0, 1000], default 0

timecode_style
Format of Time Codes displayed when not displaying timing in terms of frames

Type enum in ['MINIMAL', 'SMPTE', 'SMPTE_COMPACT', 'MILLISECONDS', 'SECONDS_ONLY'], default 'MINIMAL'

use_auto_perspective
Automatically switch between orthographic and perspective when changing from top/front/side views

Type boolean, default False

use_camera_lock_parent
When the camera is locked to the view and in fly mode, transform the parent rather than the camera

Type boolean, default False

use_directional_menus
Otherwise menus, etc will always be top to bottom, left to right, no matter opening direction

Type boolean, default False

use_global_pivot
Lock the same rotation/scaling pivot in all 3D Views

Type boolean, default False

use_global_scene
Forces the current Scene to be displayed in all Screens

Type boolean, default False

use_mouse_auto_depth

Use the depth under the mouse to improve view pan/rotate/zoom functionality

Type boolean, default False

use_mouse_over_open

Open menu buttons and pulldowns automatically when the mouse is hovering

Type boolean, default False

use_rotate_around_active

Use selection as the pivot point

Type boolean, default False

use_zoom_to_mouse

Zoom in towards the mouse pointer's position in the 3D view, rather than the 2D window center

Type boolean, default False

view2d_grid_spacing_min

Minimum number of pixels between each gridline in 2D Viewports

Type int in [1, 500], default 0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `UserPreferences.view`

2.4.603 UserSolidLight(bpy_struct)

base class — `bpy_struct`

```
class bpy.types.UserSolidLight(bpy_struct)
    Light used for OpenGL lighting in solid draw mode

    diffuse_color
        The diffuse color of the OpenGL light
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    direction
        The direction that the OpenGL light is shining
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    specular_color
        The color of the lights specular highlight
        Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

    use
        Enable this OpenGL light in solid draw mode
        Type boolean, default False
```

Inherited Properties

- [bpy_struct.id_data](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

References

- [UserPreferencesSystem.solid_lights](#)

2.4.604 ValueNodeSocket(NodeSocket)

base classes — [bpy_struct](#), [NodeSocket](#)

```
class bpy.types.ValueNodeSocket (NodeSocket)
    Input or output socket of a node

    default_value
        Default value of the socket when no link is attached
        Type float array of 1 items in [-inf, inf], default (0.0)
```

Inherited Properties

- bpy_struct.id_data
- NodeSocket.name
- NodeSocket.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

2.4.605 VectorFont(ID)

base classes — bpy_struct, ID

```
class bpy.types.VectorFont (ID)
    Vector font for Text objects

    filepath
        Type string, default "", (readonly)

    packed_file
        Type PackedFile, (readonly)
```

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library

- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.fonts`
- `BlendDataFonts.load`
- `BlendDataFonts.remove`
- `TextCurve.font`
- `TextCurve.font_bold`
- `TextCurve.font_bold_italic`
- `TextCurve.font_italic`

2.4.606 VectorNodeSocket(NodeSocket)

base classes — `bpy_struct, NodeSocket`

class bpy.types.VectorNodeSocket (NodeSocket)

Input or output socket of a node

default_value

Default value of the socket when no link is attached

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

Inherited Properties

- `bpy_struct.id_data`

- `NodeSocket.name`
- `NodeSocket.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.607 VertexColors(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.VertexColors (bpy_struct)`

Collection of vertex colors

active

Active vertex color layer

Type `MeshColorLayer`

active_index

Active vertex color index

Type int in [0, inf], default 0

new (`name="Col"`)

Add a vertex color layer to Mesh.

Parameters `name` (`string, (optional)`) – Vertex color name.

Returns The newly created layer.

Return type `MeshColorLayer`

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`

- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Mesh.vertex_colors

2.4.608 VertexGroup(bpy_struct)

base class — bpy_struct

class bpy.types.VertexGroup (*bpy_struct*)

Group of vertices, used for armature deform and other purposes

index

Index number of the vertex group

Type int in [0, inf], default 0, (readonly)

name

Vertex group name

Type string, default “”

add (*index, weight, type*)

Add vertices to the group.

Parameters

- **index** (int array of 1 items in [-inf, inf]) – Index List.
- **weight** (float in [0, 1]) – Vertex weight.
- **type** (enum in ['REPLACE', 'ADD', 'SUBTRACT']) – Vertex assign mode.

remove (*index*)

Remove a vertex from the group.

Parameters **index** (int array of 1 items in [-inf, inf]) – Index List.

weight (*index*)

Get a vertex weight from the group.

Parameters **index** (int in [0, inf]) – Index, The index of the vertex.

Returns Vertex weight.

Return type float in [0, 1]

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `Object.vertex_groups`
- `VertexGroups.active`
- `VertexGroups.new`
- `VertexGroups.remove`

2.4.609 VertexGroupElement(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.VertexGroupElement` (`bpy_struct`)

Weight value of a vertex in a vertex group

group

Type int in [0, inf], default 0, (readonly)

weight

Vertex Weight

Type float in [0, 1], default 0.0

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `LatticePoint.groups`
- `MeshVertex.groups`

2.4.610 VertexGroups(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.VertexGroups (`bpy_struct`)
Collection of vertex groups

active

Vertex groups of the object

Type `VertexGroup`, (readonly)

active_index

Active index in vertex group array

Type int in [-32768, 32767], default 0

new (name="Group")

Add vertex group to object.

Parameters `name` (string, (optional)) – Vertex group name.

Returns New vertex group.

Return type `VertexGroup`

remove (group)

Delete vertex group from object.

Parameters `group` (`VertexGroup`, (never None)) – Vertex group to remove.

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- Object.vertex_groups

2.4.611 VertexPaint(Paint)

base classes — bpy_struct, Paint

class bpy.types.VertexPaint (Paint)

Properties of vertex and weight paint mode

use_all_faces

Paint on all faces inside brush

Type boolean, default False

use_normal

Applies the vertex normal before painting

Type boolean, default False

use_spray

Keep applying paint effect while holding mouse

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Paint.brush

- Paint.show_low_resolution
- Paint.show_brush
- Paint.show_brush_on_surface

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- ToolSettings.vertex_paint
- ToolSettings.weight_paint

2.4.612 VisibilityActuator(Actuator)

base classes — `bpy_struct, Actuator`

class bpy.types.VisibilityActuator(Actuator)

Actuator to set visibility and occlusion of the object

apply_to_children

Set all the children of this object to the same visibility/occlusion recursively

Type boolean, default False

use_occlusion

Set the object to occlude objects behind it. Initialized from the object type in physics button

Type boolean, default False

use_visible

Set the objects visible. Initialized from the object render restriction toggle in physics button

Type boolean, default False

Inherited Properties

- bpy_struct.id_data
- Actuator.name

- `Actuator.show_expanded`
- `Actuator.pin`
- `Actuator.type`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `Actuator.link`
- `Actuator.unlink`

2.4.613 VoronoiTexture(Texture)

base classes — `bpy_struct, ID, Texture`

class `bpy.types.VoronoiTexture (Texture)`

Procedural voronoi texture

color_mode

Type enum in ['INTENSITY', 'POSITION', 'POSITION_OUTLINE', 'POSITION_OUTLINE_INTENSITY'], default 'INTENSITY'

distance_metric

Type enum in ['DISTANCE', 'DISTANCE_SQUARED', 'MANHATTAN', 'CHEBYCHEV', 'MINKOVSKY_HALF', 'MINKOVSKY_FOUR', 'MINKOVSKY'], default 'DISTANCE'

minkovsky_exponent

Minkovsky exponent

Type float in [0.01, 10], default 0.0

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_intensity

Scales the intensity of the noise

Type float in [0.01, 10], default 0.0

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

weight_1

Voronoi feature weight 1

Type float in [-2, 2], default 0.0

weight_2

Voronoi feature weight 2

Type float in [-2, 2], default 0.0

weight_3

Voronoi feature weight 3

Type float in [-2, 2], default 0.0

weight_4

Voronoi feature weight 4

Type float in [-2, 2], default 0.0

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

2.4.614 VoxelData(bpy_struct)

base class — `bpy_struct`

class bpy.types.VoxelData(bpy_struct)
Voxel data settings

domain_object
Object used as the smoke simulation domain
Type `Object`

extension
Sets how the texture is extrapolated past its original bounds
Type enum in ['EXTEND', 'CLIP', 'REPEAT'], default 'EXTEND'

file_format
Format of the source data set to render
Type enum in ['BLENDER_VOXEL', 'RAW_8BIT', 'IMAGE_SEQUENCE', 'SMOKE'], default 'BLENDER_VOXEL'

filepath
The external source data file to use
Type string, default ""

intensity
Multiplier for intensity values
Type float in [0.01, inf], default 0.0

interpolation
Method to interpolate/smooth values between voxel cells

Type enum in ['NEREASTNEIGHBOR', 'TRILINEAR', 'QUADRATIC', 'TRICUBIC_CATROM', 'TRICUBIC_BSPLINE'], default 'NEREASTNEIGHBOR'

resolution

Resolution of the voxel grid

Type int array of 3 items in [1, 100000], default (0, 0, 0)

smoke_data_type

Simulation value to be used as a texture

Type enum in ['SMOKEDENSITY', 'SMOKEHEAT', 'SMOKEVEL'], default 'SMOKEDENSITY'

still_frame

The frame number to always use

Type int in [-300000, 300000], default 0

use_still_frame

Always render a still frame from the voxel data sequence

Type boolean, default False

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `VoxelDataTexture.voxel_data`

2.4.615 VoxelDataTexture(Texture)

base classes — `bpy_struct, ID, Texture`

```
class bpy.types.VoxelDataTexture (Texture)
    Settings for the Voxel Data texture

    image
        Type Image

    image_user
        Parameters defining which layer, pass and frame of the image is displayed
        Type ImageUser, (readonly)

    voxel_data
        The voxel data associated with this texture
        Type VoxelData, (readonly)

    users_material
        Materials that use this texture (readonly)

    users_object_modifier
        Object modifiers that use this texture (readonly)
```

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove

- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.616 WarpModifier(Modifier)

base classes — bpy_struct, Modifier

class bpy.types.WarpModifier (*Modifier*)

Warp modifier

falloff_curve

Custom Lamp Falloff Curve

Type CurveMapping, (readonly)

falloff_radius

Radius to apply

Type float in [0, inf], default 0.0

falloff_type

Type enum in ['NONE', 'CURVE', 'SMOOTH', 'SPHERE', 'ROOT', 'SHARP', 'LINEAR', 'CONSTANT'], default 'NONE'

object_from

Object to transform from

Type Object

object_to

Object to transform to

Type Object

strength

Type float in [-inf, inf], default 0.0

texture

Type Texture

texture_coords

Type enum in ['LOCAL', 'GLOBAL', 'OBJECT', 'UV'], default 'LOCAL'

texture_coords_object

Object to set the texture coordinates

Type [Object](#)

use_volume_preserve

Preserve volume when rotations are used

Type boolean, default False

uv_layer

UV layer name

Type string, default “”

vertex_group

Vertex group name for modulating the deform

Type string, default “”

Inherited Properties

- [bpy_struct.id_data](#)
- [Modifier.name](#)
- [Modifier.use_apply_on_spline](#)
- [Modifier.show_in_editmode](#)
- [Modifier.show_expanded](#)
- [Modifier.show_on_cage](#)
- [Modifier.show_viewport](#)
- [Modifier.show_render](#)
- [Modifier.type](#)

Inherited Functions

- [bpy_struct.as_pointer](#)
- [bpy_struct.callback_add](#)
- [bpy_struct.callback_remove](#)
- [bpy_struct.driver_add](#)
- [bpy_struct.driver_remove](#)
- [bpy_struct.get](#)
- [bpy_struct.is_property_hidden](#)
- [bpy_struct.is_property_set](#)
- [bpy_struct.items](#)
- [bpy_struct.keyframe_delete](#)
- [bpy_struct.keyframe_insert](#)
- [bpy_struct.keys](#)
- [bpy_struct.path_from_id](#)
- [bpy_struct.path_resolve](#)
- [bpy_struct.type_recast](#)
- [bpy_struct.values](#)

2.4.617 WaveModifier(Modifier)

base classes — [bpy_struct](#), [Modifier](#)

```
class bpy.types.WaveModifier(Modifier)
    Wave effect modifier

    damping_time
        Number of frames in which the waves damps out after it dies
        Type float in [-300000, 300000], default 0.0

    falloff_radius
        Distance after which it fades out
        Type float in [0, inf], default 0.0

    height
        Height of the wave
        Type float in [-inf, inf], default 0.0

    lifetime
        Lifetime of the wave in frames, zero means infinite
        Type float in [-300000, 300000], default 0.0

    narrowness
        Distance between the top and the base of a wave, the higher the value, the more narrow the wave
        Type float in [0, inf], default 0.0

    speed
        Speed of the wave, towards the starting point when negative
        Type float in [-inf, inf], default 0.0

    start_position_object
        Object which defines the wave center
        Type Object

    start_position_x
        X coordinate of the start position
        Type float in [-inf, inf], default 0.0

    start_position_y
        Z coordinate of the start position
        Type float in [-inf, inf], default 0.0

    texture
        Texture for modulating the wave
        Type Texture

    texture_coords
        Texture coordinates used for modulating input
        Type enum in ['LOCAL', 'GLOBAL', 'OBJECT', 'MAP_UV'], default 'LOCAL'

    texture_coords_object
        Type Object

    time_offset
        Either the starting frame (for positive speed) or ending frame (for negative speed.)
        Type float in [-300000, 300000], default 0.0
```

use_cyclic

Cyclic wave effect

Type boolean, default False

use_normal

Displace along normals

Type boolean, default False

use_normal_x

Enable displacement along the X normal

Type boolean, default False

use_normal_y

Enable displacement along the Y normal

Type boolean, default False

use_normal_z

Enable displacement along the Z normal

Type boolean, default False

use_x

X axis motion

Type boolean, default False

use_y

Y axis motion

Type boolean, default False

uv_layer

UV layer name

Type string, default “”

vertex_group

Vertex group name for modulating the wave

Type string, default “”

width

Distance between the waves

Type float in [0, inf], default 0.0

Inherited Properties

- bpy_struct.id_data
- Modifier.name
- Modifier.use_apply_on_spline
- Modifier.show_in_editmode
- Modifier.show_expanded
- Modifier.show_on_cage
- Modifier.show_viewport
- Modifier.show_render
- Modifier.type

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

2.4.618 Window(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.Window` (`bpy_struct`)
Open window
screen
Active screen showing in the window
Type `Screen`, (never None)

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`

- `bpy_struct.values`

References

- `Context.window`
- `WindowManager.event_timer_add`
- `WindowManager.windows`

2.4.619 WindowManager(ID)

base classes — `bpy_struct, ID`

class bpy.types.WindowManager (ID)

Window manager datablock defining open windows and other user interface data

addon_filter

Filter add-ons by category

Type enum in [], default “”

addon_search

Search within the selected filter

Type string, default “”

addon_support

Display support level

Type enum set in {‘OFFICIAL’, ‘COMMUNITY’}, default {‘OFFICIAL’, ‘COMMUNITY’}

clipboard

Type string, default “”

keyconfigs

Registered key configurations

Type KeyConfigurations bpy_prop_collection of `KeyConfig`, (readonly)

operators

Operator registry

Type bpy_prop_collection of `Operator`, (readonly)

windows

Open windows

Type bpy_prop_collection of `Window`, (readonly)

classmethod fileselect_add(operator)

Show up the file selector.

Parameters `operator (Operator)` – Operator to call.

classmethod modal_handler_add(operator)

modal_handler_add

Parameters `operator (Operator)` – Operator to call.

Return type boolean

event_timer_add(time_step, window=None)

event_timer_add

Parameters

- **time_step** (*float in [0, inf]*) – Time Step, Interval in seconds between timer events
- **window** ([Window](#), (optional)) – Window to attach the timer to or None.

Return type [Timer](#)

event_timer_remove (*timer*)
event_timer_remove

classmethod invoke_props_popup (*operator, event*)

Operator popup invoke.

Parameters

- **operator** ([Operator](#)) – Operator to call.
- **event** ([Event](#)) – Event.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

classmethod invoke_props_dialog (*operator, width=300, height=20*)

Operator dialog (non-autoexec popup) invoke.

Parameters

- **operator** ([Operator](#)) – Operator to call.
- **width** (*int in [0, inf], (optional)*) – Width of the popup.
- **height** (*int in [0, inf], (optional)*) – Height of the popup.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

classmethod invoke_search_popup (*operator*)

invoke_search_popup

Parameters **operator** ([Operator](#)) – Operator to call.

classmethod invoke_popup (*operator, width=300, height=20*)

Operator popup invoke.

Parameters

- **operator** ([Operator](#)) – Operator to call.
- **width** (*int in [0, inf], (optional)*) – Width of the popup.
- **height** (*int in [0, inf], (optional)*) – Height of the popup.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

classmethod invoke_confirm (*operator, event*)

Operator confirmation.

Parameters

- **operator** ([Operator](#)) – Operator to call.
- **event** ([Event](#)) – Event.

Returns result

Return type enum set in {‘RUNNING_MODAL’, ‘CANCELLED’, ‘FINISHED’, ‘PASS_THROUGH’}

Inherited Properties

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.window_managers`
- `Context.window_manager`

2.4.620 WipeSequence(EffectSequence)

base classes — `bpy_struct`, `Sequence`, `EffectSequence`

```
class bpy.types.WipeSequence(EffectSequence)
    Sequence strip creating a wipe transition

    angle
        Edge angle
        Type float in [-1.5708, 1.5708], default 0.0

    blur_width
        Width of the blur edge, in percentage relative to the image size
        Type float in [0, 1], default 0.0

    direction
        Wipe direction
        Type enum in ['OUT', 'IN'], default 'OUT'

    transition_type
        Type enum in ['SINGLE', 'DOUBLE', 'IRIS', 'CLOCK'], default 'SINGLE'
```

Inherited Properties

- bpy_struct.id_data
- Sequence.name
- Sequence.blend_type
- Sequence.blend_alpha
- Sequence.channel
- Sequence.effect_fader
- Sequence.frame_final_end
- Sequence.frame_offset_end
- Sequence.frame_still_end
- Sequence.input_1
- Sequence.input_2
- Sequence.input_3
- Sequence.select_left_handle
- Sequence.frame_final_duration
- Sequence.frame_duration
- Sequence.lock
- Sequence.mute
- Sequence.select_right_handle
- Sequence.select
- Sequence.speed_factor
- Sequence.frame_start
- Sequence.frame_final_start
- Sequence.frame_offset_start
- Sequence.frame_still_start
- Sequence.type
- Sequence.use_default_fade
- Sequence.input_count
- EffectSequence.color_balance
- EffectSequence.use_float
- EffectSequence.crop
- EffectSequence.use_deinterlace
- EffectSequence.use_reverse_frames
- EffectSequence.use_flip_x

- EffectSequence.use_flip_y
- EffectSequence.color_multiply
- EffectSequence.use_premultiply
- EffectSequence.proxy
- EffectSequence.use_proxy_custom_directory
- EffectSequence.use_proxy_custom_file
- EffectSequence.color_saturation
- EffectSequence.strobe
- EffectSequence.transform
- EffectSequence.use_color_balance
- EffectSequence.use_crop
- EffectSequence.use_proxy
- EffectSequence.use_translation

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Sequence.getStripElem
- Sequence.swap

2.4.621 WoodTexture(Texture)

base classes — bpy_struct, ID, Texture

class bpy.types.WoodTexture (*Texture*)
Procedural noise texture

nabla

Size of derivative offset used for calculating normal

Type float in [0.001, 0.1], default 0.0

noise_basis

Sets the noise basis used for turbulence

Type enum in ['BLENDER_ORIGINAL', 'ORIGINAL_PERLIN', 'IMPROVED_PERLIN', 'VORONOI_F1', 'VORONOI_F2', 'VORONOI_F3', 'VORONOI_F4', 'VORONOI_F2_F1', 'VORONOI_CRACKLE', 'CELL_NOISE'], default 'BLENDER_ORIGINAL'

noise_basis_2

Type enum in ['SIN', 'SAW', 'TRI'], default 'SIN'

noise_scale

Sets scaling for noise input

Type float in [0.0001, inf], default 0.0

noise_type

Type enum in ['SOFT_NOISE', 'HARD_NOISE'], default 'SOFT_NOISE'

turbulence

Sets the turbulence of the bandnoise and ringnoise types

Type float in [0.0001, inf], default 0.0

wood_type

Type enum in ['BANDS', 'RINGS', 'BANDNOISE', 'RINGNOISE'], default 'BANDS'

users_material

Materials that use this texture (readonly)

users_object_modifier

Object modifiers that use this texture (readonly)

Inherited Properties

- bpy_struct.id_data
- ID.name
- ID.use_fake_user
- ID.library
- ID.tag
- ID.users
- Texture.animation_data
- Texture.intensity
- Texture.color_ramp
- Texture.contrast
- Texture.factor_blue
- Texture.factor_green
- Texture.factor_red
- Texture.node_tree
- Texture.saturation
- Texture.use_preview_alpha
- Texture.type
- Texture.use_color_ramp
- Texture.use_nodes
- Texture.users_material
- Texture.users_object_modifier
- Texture.users_material
- Texture.users_object_modifier

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add

- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- ID.copy
- ID.user_clear
- ID.animation_data_create
- ID.animation_data_clear
- ID.update_tag

2.4.622 World(ID)

base classes — `bpy_struct, ID`

class bpy.types.World(ID)
World datablock describing the environment and ambient lighting of a scene

active_texture
Active texture slot being displayed
Type `Texture`

active_texture_index
Index of active texture slot
Type int in [0, 17], default 0

ambient_color
Ambient color of the world
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

animation_data
Animation data for this datablock
Type `AnimData`, (readonly)

color_range
The color range that will be mapped to 0-1
Type float in [0.2, 5], default 0.0

exposure
Amount of exponential color correction for light
Type float in [0, 1], default 0.0

horizon_color
Color at the horizon
Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)

light_settings

World lighting settings

Type `WorldLighting`, (readonly, never None)**mist_settings**

World mist settings

Type `WorldMistSettings`, (readonly, never None)**star_settings**

World stars settings

Type `WorldStarsSettings`, (readonly, never None)**texture_slots**

Texture slots defining the mapping and influence of textures

Type `WorldTextureSlots bpy_prop_collection` of `WorldTextureSlot`, (read-only)**use_sky_blend**

Render background with natural progression from horizon to zenith

Type boolean, default False**use_sky_paper**

Flatten blend or texture coordinates

Type boolean, default False**use_sky_real**

Render background with a real horizon, relative to the camera angle

Type boolean, default False**zenith_color**

Color at the zenith

Type float array of 3 items in [-inf, inf], default (0.0, 0.0, 0.0)**Inherited Properties**

- `bpy_struct.id_data`
- `ID.name`
- `ID.use_fake_user`
- `ID.library`
- `ID.tag`
- `ID.users`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`

- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`
- `ID.copy`
- `ID.user_clear`
- `ID.animation_data_create`
- `ID.animation_data_clear`
- `ID.update_tag`

References

- `BlendData.worlds`
- `BlendDataWorlds.new`
- `BlendDataWorlds.remove`
- `Scene.world`

2.4.623 WorldLighting(`bpy_struct`)

base class — `bpy_struct`

class bpy.types.WorldLighting (`bpy_struct`)

Lighting for a World datablock

adapt_to_speed

Use the speed vector pass to reduce AO samples in fast moving pixels. Higher values result in more aggressive sample reduction. Requires Vec pass enabled (for Raytrace Adaptive QMC)

Type float in [0, 1], default 0.0

ao_blend_type

Defines how AO mixes with material shading

Type enum in ['MULTIPLY', 'ADD'], default 'ADD'

ao_factor

Factor for ambient occlusion blending

Type float in [0, inf], default 0.0

bias

Bias (in radians) to prevent smoothed faces from showing banding (for Raytrace Constant Jittered)

Type float in [0, 0.5], default 0.0

correction

Ad-hoc correction for over-occlusion due to the approximation

Type float in [0, 1], default 0.0

distance

Length of rays, defines how far away other faces give occlusion effect

Type float in [-inf, inf], default 0.0

environment_color

Defines where the color of the environment light comes from

Type enum in ['PLAIN', 'SKY_COLOR', 'SKY_TEXTURE'], default 'PLAIN'

environment_energy

Defines the strength of environment light

Type float in [-inf, inf], default 0.0

error_threshold

Low values are slower and higher quality

Type float in [0.0001, 10], default 0.0

falloff_strength

Attenuation falloff strength, the higher, the less influence distant objects have

Type float in [-inf, inf], default 0.0

gather_method

Type enum in ['RAYTRACE', 'APPROXIMATE'], default 'RAYTRACE'

indirect_bounces

Number of indirect diffuse light bounces

Type int in [1, 32767], default 0

indirect_factor

Factor for how much surrounding objects contribute to light

Type float in [0, inf], default 0.0

passes

Number of preprocessing passes to reduce overocclusion

Type int in [0, 10], default 0

sample_method

Method for generating shadow samples (for Raytrace)

Type enum in ['CONSTANT_JITTERED', 'ADAPTIVE_QMC', 'CONSTANT_QMC'], default 'CONSTANT_JITTERED'

samples

Amount of ray samples. Higher values give smoother results and longer rendering times

Type int in [1, 32], default 0

threshold

Samples below this threshold will be considered fully shadowed/unshadowed and skipped (for Raytrace Adaptive QMC)

Type float in [0, 1], default 0.0

use_ambient_occlusion

Use Ambient Occlusion to add shadowing based on distance between objects

Type boolean, default False

use_cache

Cache AO results in pixels and interpolate over neighbouring pixels for speedup

Type boolean, default False

use_environment_light

Add light coming from the environment

Type boolean, default False

use_falloff

Distance will be used to attenuate shadows

Type boolean, default False

use_indirect_light

Add indirect light bouncing of surrounding objects

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.light_settings

2.4.624 WorldMistSettings(bpy_struct)

base class — bpy_struct

class bpy.types.**WorldMistSettings** (*bpy_struct*)

Mist settings for a World data-block

depth

The distance over which the mist effect fades in

Type float in [0, inf], default 0.0

falloff

Type of transition used to fade mist

Type enum in ['QUADRATIC', 'LINEAR', 'INVERSE_QUADRATIC'], default 'QUADRATIC'

height

Control how much mist density decreases with height

Type float in [0, 100], default 0.0

intensity

Intensity of the mist effect

Type float in [0, 1], default 0.0

start

Starting distance of the mist, measured from the camera

Type float in [0, inf], default 0.0

use_mist

Occlude objects with the environment color as they are further away

Type boolean, default False

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.mist_settings

2.4.625 WorldStarsSettings(bpy_struct)

base class — `bpy_struct`

```
class bpy.types.WorldStarsSettings (bpy_struct)
    Stars setting for a World data-block

    average_separation
        Average distance between any two stars
        Type float in [2, 1000], default 0.0

    color_random
        Randomize star colors
        Type float in [0, 1], default 0.0

    distance_min
        Minimum distance to the camera for stars
        Type float in [0, 1000], default 0.0

    size
        Average screen dimension of stars
        Type float in [0, 10], default 0.0

    use_stars
        Enable starfield generation
        Type boolean, default False
```

Inherited Properties

- `bpy_struct.id_data`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `World.star_settings`

2.4.626 WorldTextureSlot(TextureSlot)

base classes — `bpy_struct, TextureSlot`

```
class bpy.types.WorldTextureSlot (TextureSlot)
    Texture slot for textures in a World datablock

    blend_factor
        Amount texture affects color progression of the background
        Type float in [-inf, inf], default 0.0

    horizon_factor
        Amount texture affects color of the horizon
        Type float in [-inf, inf], default 0.0

    object
        Object to use for mapping with Object texture coordinates
        Type Object

    texture_coords
        Texture coordinates used to map the texture onto the background
        Type enum in ['VIEW', 'GLOBAL', 'ANGMAP', 'SPHERE', 'TUBE', 'OBJECT'], default
            'VIEW'

    use_map_blend
        Affect the color progression of the background
        Type boolean, default False

    use_map_horizon
        Affect the color of the horizon
        Type boolean, default False

    use_map_zenith_down
        Affect the color of the zenith below
        Type boolean, default False

    use_map_zenith_up
        Affect the color of the zenith above
        Type boolean, default False

    zenith_down_factor
        Amount texture affects color of the zenith below
        Type float in [-inf, inf], default 0.0

    zenith_up_factor
        Amount texture affects color of the zenith above
        Type float in [-inf, inf], default 0.0
```

Inherited Properties

- `bpy_struct.id_data`
- `TextureSlot.name`
- `TextureSlot.blend_type`
- `TextureSlot.color`
- `TextureSlot.default_value`
- `TextureSlot.invert`
- `TextureSlot.offset`
- `TextureSlot.output_node`
- `TextureSlot.use_rgb_to_intensity`
- `TextureSlot.scale`
- `TextureSlot.use_stencil`
- `TextureSlot.texture`

Inherited Functions

- `bpy_struct.as_pointer`
- `bpy_struct.callback_add`
- `bpy_struct.callback_remove`
- `bpy_struct.driver_add`
- `bpy_struct.driver_remove`
- `bpy_struct.get`
- `bpy_struct.is_property_hidden`
- `bpy_struct.is_property_set`
- `bpy_struct.items`
- `bpy_struct.keyframe_delete`
- `bpy_struct.keyframe_insert`
- `bpy_struct.keys`
- `bpy_struct.path_from_id`
- `bpy_struct.path_resolve`
- `bpy_struct.type_recast`
- `bpy_struct.values`

References

- `World.texture_slots`
- `WorldTextureSlots.add`
- `WorldTextureSlots.create`

2.4.627 WorldTextureSlots(`bpy_struct`)

base class — `bpy_struct`

class `bpy.types.WorldTextureSlots` (`bpy_struct`)

Collection of texture slots

classmethod `add()`

add

Returns The newly initialized mtex.

Return type `WorldTextureSlot`

```
classmethod create(index)
    create

    Parameters index (int in [0, inf]) – Index, Slot index to initialize.

    Returns The newly initialized mtex.

    Return type WorldTextureSlot

classmethod clear(index)
    clear

    Parameters index (int in [0, inf]) – Index, Slot index to clear.
```

Inherited Properties

- bpy_struct.id_data

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values

References

- World.texture_slots

2.4.628 XnorController(Controller)

base classes — bpy_struct, Controller

```
class bpy.types.XnorController(Controller)
    Controller passing on events based on a logical XNOR operation
```

Inherited Properties

- bpy_struct.id_data
- Controller.name

- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden
- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.629 XorController(Controller)

base classes — bpy_struct, Controller

class bpy.types.XorController(Controller)

Controller passing on events based on a logical XOR operation

Inherited Properties

- bpy_struct.id_data
- Controller.name
- Controller.states
- Controller.show_expanded
- Controller.use_priority
- Controller.type

Inherited Functions

- bpy_struct.as_pointer
- bpy_struct.callback_add
- bpy_struct.callback_remove
- bpy_struct.driver_add
- bpy_struct.driver_remove
- bpy_struct.get
- bpy_struct.is_property_hidden

- bpy_struct.is_property_set
- bpy_struct.items
- bpy_struct.keyframe_delete
- bpy_struct.keyframe_insert
- bpy_struct.keys
- bpy_struct.path_from_id
- bpy_struct.path_resolve
- bpy_struct.type_recast
- bpy_struct.values
- Controller.link
- Controller.unlink

2.4.630 bpy_prop_collection

class bpy.types.bpy_prop_collection
built-in class used for all collections.

Note: Note that bpy.types.bpy_prop_collection is not actually available from within blender, it only exists for the purpose of documentation.

foreach_get (attr, seq)

This is a function to give fast access to attributes within a collection.

```
collection.foreach_get(someseq, attr)

# Python equivalent
for i in range(len(seq)): someseq[i]= getattr(collection, attr)
```

foreach_set (attr, seq)

This is a function to give fast access to attributes within a collection.

```
collection.foreach_set(seq, attr)

# Python equivalent
for i in range(len(seq)): setattr(collection[i], attr, seq[i])
```

get (key, default=None)

Returns the value of the item assigned to key or default when not found (matches pythons dictionary function of the same name).

Parameters

- **key** (string) – The identifier for the collection member.
- **default** (*Undefined*) – Optional argument for the value to return if *key* is not found.

items ()

Return the identifiers of collection members (matching pythons dict.items() functionality).

Returns (key, value) pairs for each member of this collection.

Return type list of tuples

keys ()

Return the identifiers of collection members (matching pythons dict.keys() functionality).

Returns the identifiers for each member of this collection.

Return type list of strings

values()

Return the values of collection (matching pythons dict.values() functionality).

Returns the members of this collection.

Return type list

2.4.631 bpy_struct

subclasses — ActionFCurves, ActionGroup, ActionGroups, ActionPoseMarkers, Actuator, Addon, Addons, AnimData, AnimDataDrivers, AnimViz, AnimVizMotionPaths, AnimVizOnionSkinning, AnyType, Area, AreaSpaces, ArmatureBones, ArmatureEditBones, BackgroundImage, BezierSplinePoint, BlendData, BlendDataActions, BlendDataArmatures, BlendDataBrushes, BlendDataCameras, BlendDataCurves, BlendDataFonts, BlendDataGreasePencils, BlendDataGroups, BlendDataImages, BlendDataLamps, BlendDataLattices, BlendDataLibraries, BlendDataMaterials, BlendDataMeshes, BlendDataMetaBalls, BlendDataNodeTrees, BlendDataObjects, BlendDataParticles, BlendDataScenes, BlendDataScreens, BlendDataSounds, BlendDataTexts, BlendDataTextures, BlendDataWindowManagers, BlendDataWorlds, BlenderRNA, BoidRule, BoidSettings, BoidState, Bone, BoneGroup, BoneGroups, ChannelDriverVariables, ChildParticle, ClothCollisionSettings, ClothSettings, CollisionSettings, ColorRamp, ColorRampElement, ColorRampElements, CompositorNodes, ConsoleLine, Constraint, ConstraintTarget, Context, Controller, CurveMap, CurveMapPoint, CurveMapping, CurveSplines, DopeSheet, Driver, DriverTarget, DriverVariable, DupliObject, EditBone, EffectorWeights, EnumPropertyItem, EnvironmentMap, Event, FCurve, FCurveKeyframePoints, FCurveModifiers, FCurveSample, FModifier, FModifierEnvelopeControlPoint, FieldSettings, FileSelectParams, FluidMeshVertex, FluidSettings, Function, GPencilFrame, GPencilLayer, GPencilStroke, GPencilStrokePoint, GameObjectSettings, GameProperty, GameSoftBodySettings, GreasePencilLayers, GroupInputs, GroupObjects, GroupOutputs, Header, Histogram, ID, IDMaterials, IKParam, ImageUser, KeyConfig, KeyConfigurations, KeyMap, KeyMapItem, KeyMapItems, KeyMaps, Keyframe, KeyingSet, KeyingSetInfo, KeyingSetPath, KeyingSetPaths, KeyingSets, KeyingSetsAll, LampSkySettings, LampTextureSlots, LatticePoint, Macro, MaterialHalo, MaterialPhysics, MaterialRaytraceMirror, MaterialRaytraceTransparency, MaterialSlot, MaterialStrand, MaterialSubsurfaceScattering, MaterialTextureSlots, MaterialVolume, Menu, MeshColor, MeshColorLayer, MeshEdge, MeshEdges, MeshFace, MeshFaces, MeshFloatProperty, MeshFloatPropertyLayer, MeshIntProperty, MeshIntPropertyLayer, MeshSticky, MeshStringProperty, MeshStringPropertyLayer, MeshTextureFace, MeshTextureFaceLayer, MeshVertex, MeshVertices, MetaBallElements, MetaElement, Modifier, MotionPath, MotionPathVert, NlaStrip, NlaStrips, NlaTrack, NlaTracks, Node, NodeLink, NodeLinks, NodeSocket, ObjectBase, ObjectConstraints, ObjectModifiers, Operator, OperatorProperties, OperatorTypeMacro, PackedFile, Paint, Panel, Particle, ParticleBrush, ParticleDupliWeight, ParticleEdit, ParticleHairKey, ParticleKey, ParticleSettingsTextureSlots, ParticleSystem, ParticleSystems, ParticleTarget, PointCache, PointCaches, PointDensity, Pose, PoseBone, PoseBoneConstraints, Property, PropertyGroup, PropertyGroupItem, Region, RegionView3D, RenderEngine, RenderLayer, RenderLayers, RenderPass, RenderResult, RenderSettings, SPHFluidSettings, SceneBases, SceneGameData, SceneObjects, SceneRenderLayer, Scopes, Sensor, Sequence, SequenceColorBalance, SequenceCrop, SequenceEditor, SequenceElement, SequenceProxy, SequenceTransform, ShaderNodes, ShapeKey, ShapeKeyBezierPoint, ShapeKeyCurvePoint, ShapeKeyPoint, SmokeCollSettings, SmokeDomainSettings, SmokeFlowSettings, SoftBodySettings, Space, SpaceUVEditor, Spline, SplineBezierPoints, SplinePoint, SplinePoints,

Struct, TexMapping, TextBox, TextCharacterFormat, TextLine, TextMarker,
TextureNodes, TextureSlot, Theme, ThemeAudioWindow, ThemeBoneColorSet,
ThemeConsole, ThemeDopeSheet, ThemeFileBrowser, ThemeFontStyle, ThemeGraphEditor,
ThemeImageEditor, ThemeInfo, ThemeLogicEditor, ThemeNLAEditor, ThemeNodeEditor,
ThemeOutliner, ThemeProperties, ThemeSequenceEditor, ThemeStyle, ThemeTextEditor,
ThemeTimeline, ThemeUserInterface, ThemeUserPreferences, ThemeView3D,
ThemeWidgetColors, ThemeWidgetStateColors, TimelineMarker, TimelineMarkers, Timer,
ToolSettings, TransformOrientation, UILayout, UVProjector, UVTextures, UnitSettings,
UnknownType, UserPreferences, UserPreferencesEdit, UserPreferencesFilePaths,
UserPreferencesInput, UserPreferencesSystem, UserPreferencesView, UserSolidLight,
VertexColors, VertexGroup, VertexGroupElement, VertexGroups, VoxelData, Window,
WorldLighting, WorldMistSettings, WorldStarsSettings, WorldTextureSlots

class bpy.types.bpy_struct

built-in base class for all classes in bpy.types.

Note: Note that bpy.types.bpy_struct is not actually available from within blender, it only exists for the purpose of documentation.

as_pointer()

Returns the memory address which holds a pointer to blenders internal data

Returns int (memory address).

Return type int

Note: This is intended only for advanced script writers who need to pass blender data to their own C/Python modules.

Undocumented ([contribute](#))

Undocumented ([contribute](#))

driver_add(path, index=-1)

Adds driver(s) to the given property

Parameters

- **path** (string) – path to the property to drive, analogous to the fcurve's data path.
- **index** (int) – array index of the property drive. Defaults to -1 for all indices or a single channel if the property is not an array.

Returns The driver(s) added.

Return type FCurve or list if index is -1 with an array property.

driver_remove(path, index=-1)

Remove driver(s) from the given property

Parameters

- **path** (string) – path to the property to drive, analogous to the fcurve's data path.
- **index** (int) – array index of the property drive. Defaults to -1 for all indices or a single channel if the property is not an array.

Returns Success of driver removal.

Return type boolean

get (key, default=None)

Returns the value of the custom property assigned to key or default when not found (matches pythons dictionary function of the same name).

Parameters

- **key** (*string*) – The key assosiated with the custom property.
 - **default** (*Undefined*) – Optional argument for the value to return if *key* is not found.
-

Note: Only [ID](#), [Bone](#) and [PoseBone](#) classes support custom properties.

is_property_hidden (property)

Check if a property is hidden.

Returns True when the property is hidden.

Return type boolean

is_property_set (property)

Check if a property is set, use for testing operator properties.

Returns True when the property has been set.

Return type boolean

items ()

Returns the items of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property key, value pairs.

Return type list of key, value tuples

Note: Only [ID](#), [Bone](#) and [PoseBone](#) classes support custom properties.

keyframe_delete (data_path, index=-1, frame=bpy.context.scene.frame_current, group="")

Remove a keyframe from this properties fcurve.

Parameters

- **data_path** (*string*) – path to the property to remove a key, analogous to the fcurve's data path.
- **index** (*int*) – array index of the property to remove a key. Defaults to -1 removing all indices or a single channel if the property is not an array.
- **frame** (*float*) – The frame on which the keyframe is deleted, defaulting to the current frame.
- **group** (*str*) – The name of the group the F-Curve should be added to if it doesn't exist yet.

Returns Success of keyframe deletion.

Return type boolean

keyframe_insert (data_path, index=-1, frame=bpy.context.scene.frame_current, group="")

Insert a keyframe on the property given, adding fcurves and animation data when necessary.

Parameters

- **data_path** (*string*) – path to the property to key, analogous to the fcurve's data path.

- **index** (*int*) – array index of the property to key. Defaults to -1 which will key all indices or a single channel if the property is not an array.
- **frame** (*float*) – The frame on which the keyframe is inserted, defaulting to the current frame.
- **group** (*str*) – The name of the group the F-Curve should be added to if it doesn't exist yet.

Returns Success of keyframe insertion.

Return type boolean

This is the most simple example of inserting a keyframe from python.

```
import bpy

obj = bpy.context.object

# set the keyframe at frame 1
obj.location = 3.0, 4.0, 10.0
obj.keyframe_insert(data_path="location", frame=1)
```

Note that when keying data paths which contain nested properties this must be done from the [ID](#) subclass, in this case the [Armature](#) rather then the bone.

```
import bpy
from bpy.props import PointerProperty


# define a nested property
class MyPropGroup(bpy.types.PropertyGroup):
    nested = bpy.props.FloatProperty(name="Nested", default=0.0)

# register it so its available for all bones
bpy.utils.register_class(MyPropGroup)
bpy.types.Bone.my_prop = PointerProperty(type=MyPropGroup,
                                         name="MyProp")

# get a bone
obj = bpy.data.objects["Armature"]
arm = obj.data

# set the keyframe at frame 1
arm.bones["Bone"].my_prop_group.nested = 10
arm.keyframe_insert(data_path='bones["Bone"].my_prop.nested',
                     frame=1,
                     group="Nested Group")
```

keys()

Returns the keys of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property keys.

Return type list of strings

Note: Only [ID](#), [Bone](#) and [PoseBone](#) classes support custom properties.

path_from_id(*property*=““)

Returns the data path from the ID to this object (string).

Parameters `property` (*string*) – Optional property name which can be used if the path is to a property of this object.

Returns The path from `bpy_struct.id_data` to this struct and property (when given).

Return type str

`path_resolve` (*path*, *coerce=True*)

Returns the property from the path, raise an exception when not found.

Parameters

- `path` (*string*) – path which this property resolves.
- `coerce` (*boolean*) – optional argument, when True, the property will be converted into its python representation.

`type_recast` ()

Return a new instance, this is needed because types such as textures can be changed at runtime.

Returns a new instance of this object with the type initialized again.

Return type subclass of `bpy_struct`

`values` ()

Returns the values of this objects custom properties (matches pythons dictionary function of the same name).

Returns custom property values.

Return type list

Note: Only `ID`, `Bone` and `PoseBone` classes support custom properties.

`id_data`

The `ID` object this datablock is from or None, (not available for all data types)

2.5 Utilities (`bpy.utils`)

This module contains utility functions specific to blender but not assosiated with blenders internal data.

`bpy.utils.blend_paths` (*absolute=False*)

Returns a list of paths to external files referenced by the loaded .blend file.

Parameters `absolute` (*boolean*) – When true the paths returned are made absolute.

Returns path list.

Return type list of strings

`bpy.utils.keyconfig_set` (*filepath*)

`bpy.utils.load_scripts` (*reload_scripts=False*, *refresh_scripts=False*)

Load scripts and run each modules register function.

Parameters

- `reload_scripts` (*bool*) – Causes all scripts to have their unregister method called before loading.
- `refresh_scripts` (*bool*) – only load scripts which are not already loaded as modules.

bpy.utils.modules_from_path(*path*, *loaded_modules*)

Load all modules in a path and return them as a list.

Parameters

- **path** (*string*) – this path is scanned for scripts and packages.
- **loaded_modules** (*set*) – already loaded module names, files matching these names will be ignored.

Returns all loaded modules.

Return type

bpy.utils.preset_find(*name*, *preset_path*, *display_name=False*)

bpy.utils.preset_paths(*subdir*)

Returns a list of paths for a specific preset.

bpy.utils.refresh_script_paths()

Run this after creating new script paths to update sys.path

bpy.utils.register_class(*cls*)

Register a subclass of a blender type in (Panel, Menu, Header, Operator, KeyingSetInfo, RenderEngine).

If the class has a *register* class method it will be called before registration.

Note: ValueError exception is raised if the class is not a subclass of a registerable blender class.

bpy.utils.register_module(*module*, *verbose=False*)

bpy.utils.resource_path(*type*, *major=2*, *minor=57*)

Return the base path for storing system files.

Parameters

- **type** (*string*) – string in ['USER', 'LOCAL', 'SYSTEM'].
- **major** (*int*) – major version, defaults to current.
- **minor** (*string*) – minor version, defaults to current.

Returns the resource path (not necessarily existing).

Return type

bpy.utils.script_paths(*subdir=None*, *user_pref=True*, *all=False*)

Returns a list of valid script paths.

Parameters

- **subdir** (*string*) – Optional subdir.
- **user_pref** (*bool*) – Include the user preference script path.
- **all** (*bool*) – Include local, user and system paths rather just the paths blender uses.

Returns script paths.

Return type

bpy.utils.smpte_from_frame(*frame*, *fps=None*, *fps_base=None*)

Returns an SMPTE formatted string from the frame: "HH:MM:SS:FF".

If *fps* and *fps_base* are not given the current scene is used.

`bpy.utils.smpte_from_seconds(time, fps=None)`
Returns an SMPTE formatted string from the time in seconds: “HH:MM:SS:FF”.

If the `fps` is not given the current scene is used.

`bpy.utils.unregister_class(cls)`
Unload the python class from blender.

If the class has an `unregister` class method it will be called before unregistering.

`bpy.utils.unregister_module(module, verbose=False)`

`bpy.utils.user_resource(type, path='', create=False)`
Return a user resource path (normally from the users home directory).

Parameters

- `type (string)` – Resource type in [‘DATAFILES’, ‘CONFIG’, ‘SCRIPTS’, ‘AUTOSAVE’].
- `subdir (string)` – Optional subdirectory.
- `create (boolean)` – Treat the path as a directory and create it if its not existing.

Returns a path.

Return type string

`bpy.utils.user_script_path()`

2.6 Path Utilities (bpy.path)

This module has a similar scope to os.path, containing utility functions for dealing with paths in Blender.

`bpy.path.abspath(path, start=None)`
Returns the absolute path relative to the current blend file using the “//” prefix.

Parameters `start (string)` – Relative to this path, when not set the current filename is used.

`bpy.path.clean_name(name, replace='_')`
Returns a name with characters replaced that may cause problems under various circumstances, such as writing to a file. All characters besides A-Z/a-z, 0-9 are replaced with “_” or the replace argument if defined.

`bpy.path.display_name(name)`
Creates a display string from name to be used menus and the user interface. Capitalize the first letter in all lowercase names, mixed case names are kept as is. Intended for use with filenames and module names.

`bpy.path.display_name_from_filepath(name)`
Returns the path stripped of directort and extension, ensured to be utf8 compatible.

`bpy.path.ensure_ext(filepath, ext, case_sensitive=False)`
Return the path with the extension added its its not alredy set.

Parameters

- `ext (string)` – The extension to check for.
- `case_sensitive (bool)` – Check for matching case when comparing extensions.

`bpy.path.is_subdir(path, directory)`
Returns true if `path` in a subdirectory of `directory`. Both paths must be absolute.

`bpy.path.module_names(path, recursive=False)`
Return a list of modules which can be imported from `path`.

Parameters

- **path** (*string*) – a directory to scan.
- **recursive** (*bool*) – Also return submodule names for packages.

Returns a list of string pairs (module_name, module_file).

Return type list

`bpy.path.relpwd(path, start=None)`

Returns the path relative to the current blend file using the “//” prefix.

Parameters `start` (*string*) – Relative to this path, when not set the current filename is used.

`bpy.path.resolve_ncase(path)`

Resolve a case insensitive path on a case sensitive system, returning a string with the path if found else return the original path.

2.7 Application Data (bpy.app)

This module contains application values that remain unchanged during runtime.

`bpy.app.debug`

Boolean, set when blender is running in debug mode (started with -d)

`bpy.app.debug_value`

Int, number which can be set to non-zero values for testing purposes.

`bpy.app.driver_namespace`

Dictionary for drivers namespace, editable in-place, reset on file load (read-only)

`bpy.app.tempdir`

String, the temp directory used by blender (read-only)

`bpy.app.background`

Boolean, True when blender is running without a user interface (started with -b)

`bpy.app.binary_path`

The location of blenders executable, useful for utilities that spawn new instances

`bpy.app.build_cflags`

C compiler flags

`bpy.app.build_cxxflags`

C++ compiler flags

`bpy.app.build_date`

The date this blender instance was built

`bpy.app.build_linkflags`

Binary linking flags

`bpy.app.build_platform`

The platform this blender instance was built for

`bpy.app.build_revision`

The subversion revision this blender instance was built with

`bpy.app.build_system`

Build system used

bpy.app.build_time

The time this blender instance was built

bpy.app.build_type

The type of build (Release, Debug)

bpy.app.handlers

Application handler callbacks

bpy.app.version

The Blender version as a tuple of 3 numbers. eg. (2, 50, 11)

bpy.app.version_char

The Blender version character (for minor releases)

bpy.app.version_cycle

The release status of this build alpha/beta/rc/release

bpy.app.version_string

The Blender version formatted as a string

T.count(value) -> integer – return number of occurrences of value

T.index(value, [start, [stop]]) -> integer – return first index of value. Raises ValueError if the value is not present.

2.8 Property Definitions (bpy.props)

This module defines properties to extend blenders internal data, the result of these functions is used to assign properties to classes registered with blender and can't be used directly.

2.8.1 Assigning to Existing Classes

Custom properties can be added to any subclass of an ID, Bone and PoseBone.

These properties can be animated, accessed by the user interface and python like blenders existing properties.

```
import bpy
```

```
# Assign a custom property to an existing type.  
bpy.types.Material.custom_float = bpy.props.FloatProperty(name="Test Prob")  
  
# Test the property is there.  
bpy.data.materials[0].custom_float = 5.0
```

2.8.2 Operator Example

A common use of custom properties is for python based Operator classes.

```
import bpy
```

```
class DialogOperator(bpy.types.Operator):  
    bl_idname = "object.dialog_operator"  
    bl_label = "Property Example"  
  
    my_float = bpy.props.FloatProperty(name="Some Floating Point")
```

```
my_bool = bpy.props.BoolProperty(name="Toggle Option")
my_string = bpy.props.StringProperty(name="String Value")

def execute(self, context):
    print("Dialog Runs")
    return {'FINISHED'}

def invoke(self, context, event):
    wm = context.window_manager
    return wm.invoke_props_dialog(self)

bpy.utils.register_class(DialogOperator)

# test call
bpy.ops.object.dialog_operator('INVOKE_DEFAULT')
```

2.8.3 PropertyGroup Example

PropertyGroups can be used for collecting custom settings into one value to avoid many individual settings mixed in together.

```
import bpy

class MaterialSettings(bpy.types.PropertyGroup):
    my_int = bpy.props.IntProperty()
    my_float = bpy.props.FloatProperty()
    my_string = bpy.props.StringProperty()

bpy.utils.register_class(MaterialSettings)

bpy.types.Material.my_settings = \
    bpy.props.PointerProperty(type=MaterialSettings)

# test the new settings work
material = bpy.data.materials[0]

material.my_settings.my_int = 5
material.my_settings.my_float = 3.0
material.my_settings.my_string = "Foo"
```

2.8.4 Collection Example

Custom properties can be added to any subclass of an ID, Bone and PoseBone.

```
import bpy

# Assign a collection
class SceneSettingItem(bpy.types.PropertyGroup):
    name = bpy.props.StringProperty(name="Test Prop", default="Unknown")
    value = bpy.props.IntProperty(name="Test Prop", default=22)

bpy.utils.register_class(SceneSettingItem)
```

```
bpy.types.Scene.my_settings = \
    bpy.props.CollectionProperty(type=SceneSettingItem)

# Assume an armature object selected
print("Adding 3 values!")

my_item = bpy.context.scene.my_settings.add()
my_item.name = "Spam"
my_item.value = 1000

my_item = bpy.context.scene.my_settings.add()
my_item.name = "Eggs"
my_item.value = 30

for my_item in bpy.context.scene.my_settings:
    print(my_item.name, my_item.value)
```

2.8.5 Update Example

It can be useful to perform an action when a property is changed and can be used to update other properties or synchronize with external data.

All properties define update functions except for CollectionProperty.

```
import bpy

def update_func(self, context):
    print("my test function", self)

bpy.types.Scene.testprop = bpy.props.FloatProperty(update=update_func)

bpy.context.scene.testprop = 11.0

# >>> my test function <bpy_struct, Scene("Scene")>

bpy.props.BoolProperty(name="", description="", default=False, options={'ANIMATABLE'}, subtype='NONE', update=None)
>Returns a new boolean property definition.
```

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in ['HIDDEN', 'SKIP_SAVE', 'ANIMATABLE'].
- **subtype** (*string*) – Enumerator in ['UNSIGNED', 'PERCENTAGE', 'FACTOR', 'ANGLE', 'TIME', 'DISTANCE', 'NONE'].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.BoolVectorProperty(name="", description="", default=(False, False, False),
                             options={'ANIMATABLE'}, subtype='NONE', size=3, update=None)
>Returns a new vector boolean property definition.
```

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*sequence*) – sequence of booleans the length of *size*.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘COLOR’, ‘TRANSLATION’, ‘DIRECTION’, ‘VELOCITY’, ‘ACCELERATION’, ‘MATRIX’, ‘EULER’, ‘QUATERNION’, ‘AXISANGLE’, ‘XYZ’, ‘COLOR_GAMMA’, ‘LAYER’, ‘NONE’].
- **size** (*int*) – Vector dimensions in [1, and 32].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.CollectionProperty(items, type=""", description=""", default=""", options={'ANIMTABLE'})
```

Returns a new collection property definition.

Parameters

- **type** (*class*) – A subclass of `bpy.types.PropertyGroup`.
- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].

```
bpy.props.EnumProperty(items, name=""", description=""", default=""", options={'ANIMTABLE'}, update=None)
```

Returns a new enumerator property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*string or set*) – The default value for this enum, A string when *ENUM_FLAG* is disabled otherwise a set which may only contain string identifiers used in *items*.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’, ‘ENUM_FLAG’].
- **items** (*sequence of string triplets or a function*) – sequence of enum items formatted: [(identifier, name, description), ...] where the identifier is used for python access and other values are used for the interface. For dynamic values a callback can be passed which returns a list in the same format as the static list. This function must take 2 arguments (self, context)
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.FloatProperty(name=""", description=""", default=0.0, min=sys.float_info.min, max=sys.float_info.max, soft_min=sys.float_info.min, soft_max=sys.float_info.max, step=3, precision=2, options={'ANIMTABLE'}, subtype='NONE', unit='NONE', update=None)
```

Returns a new float property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.

- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘UNSIGNED’, ‘PERCENTAGE’, ‘FACTOR’, ‘ANGLE’, ‘TIME’, ‘DISTANCE’, ‘NONE’].
- **unit** (*string*) – Enumerator in [‘NONE’, ‘LENGTH’, ‘AREA’, ‘VOLUME’, ‘ROTATION’, ‘TIME’, ‘VELOCITY’, ‘ACCELERATION’].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.FloatVectorProperty(name="", description="", default=(0.0, 0.0, 0.0),
                               min=sys.float_info.min, max=sys.float_info.max,
                               soft_min=sys.float_info.min, soft_max=sys.float_info.max,
                               step=3, precision=2, options={'ANIMTABLE'}, subtype='NONE', size=3, update=None)
```

Returns a new vector float property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **default** (*sequence*) – sequence of floats the length of *size*.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘COLOR’, ‘TRANSLATION’, ‘DIRECTION’, ‘VELOCITY’, ‘ACCELERATION’, ‘MATRIX’, ‘EULER’, ‘QUATERNION’, ‘AXISANGLE’, ‘XYZ’, ‘COLOR_GAMMA’, ‘LAYER’, ‘NONE’].
- **size** (*int*) – Vector dimensions in [1, and 32].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.IntProperty(name="", description="", default=0, min=-sys.maxint, max=sys.maxint,
                      soft_min=-sys.maxint, soft_max=sys.maxint, step=1, options={'ANIMTABLE'}, subtype='NONE', update=None)
```

Returns a new int property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘UNSIGNED’, ‘PERCENTAGE’, ‘FACTOR’, ‘ANGLE’, ‘TIME’, ‘DISTANCE’, ‘NONE’].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

```
bpy.props.IntVectorProperty(name="", description="", default=(0, 0, 0), min=-sys.maxint,
                            max=sys.maxint, soft_min=-sys.maxint, soft_max=sys.maxint, options={'ANIMTABLE'}, subtype='NONE', size=3, update=None)
```

Returns a new vector int property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.

- **default** (*sequence*) – sequence of ints the length of *size*.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘COLOR’, ‘TRANSLATION’, ‘DIRECTION’, ‘VELOCITY’, ‘ACCELERATION’, ‘MATRIX’, ‘EULER’, ‘QUATERNION’, ‘AXISANGLE’, ‘XYZ’, ‘COLOR_GAMMA’, ‘LAYER’, ‘NONE’].
- **size** (*int*) – Vector dimensions in [1, and 32].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

bpy.props.**PointerProperty** (*type*=““, *description*=““, *options*={‘ANIMTABLE’}, *update*=None)

Returns a new pointer property definition.

Parameters

- **type** (*class*) – A subclass of bpy.types.PropertyGroup.
- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

bpy.props.**RemoveProperty** (*attr*)

Removes a dynamically defined property.

Parameters *attr* (*string*) – Property name.

bpy.props.**StringProperty** (*name*=““, *description*=““, *default*=““, *maxlen*=0, *options*={‘ANIMTABLE’}, *subtype*=‘NONE’, *update*=None)

Returns a new string property definition.

Parameters

- **name** (*string*) – Name used in the user interface.
- **description** (*string*) – Text used for the tooltip and api documentation.
- **options** (*set*) – Enumerator in [‘HIDDEN’, ‘SKIP_SAVE’, ‘ANIMTABLE’].
- **subtype** (*string*) – Enumerator in [‘FILE_PATH’, ‘DIR_PATH’, ‘FILENAME’, ‘NONE’].
- **update** (*function*) – function to be called when this value is modified, This function must take 2 values (self, context) and return None.

STANDALONE MODULES

3.1 Math Types & Utilities (mathutils)

This module provides access to matrices, eulers, quaternions and vectors.

```
import mathutils
from math import radians

vec = mathutils.Vector((1.0, 2.0, 3.0))

mat_rot = mathutils.Matrix.Rotation(radians(90.0), 4, 'X')
mat_trans = mathutils.Matrix.Translation(vec)

mat = mat_trans * mat_rot
mat.invert()

mat3 = mat.to_3x3()
quat1 = mat.to_quaternion()
quat2 = mat3.to_quaternion()

quat_diff = quat1.rotation_difference(quat2)

print(quat_diff.angle)
```

class mathutils.Color

This object gives access to Colors in Blender.

copy()

Returns a copy of this color.

Returns A copy of the color.

Return type Color

Note: use this to get a copy of a wrapped color with no reference to the original data.

b

Blue color channel.

Type float

g

Green color channel.

Type float

h
HSV Hue component in [0, 1].

Type float

hsv
HSV Values in [0, 1].

Type float triplet

is_wrapped
True when this object wraps external data (readonly).

Type boolean

owner
The item this is wrapping or None (readonly).

r
Red color channel.

Type float

s
HSV Saturation component in [0, 1].

Type float

v
HSV Value component in [0, 1].

Type float

class `mathutils.Euler`

This object gives access to Eulers in Blender.

```
import mathutils

# todo

copy()
    Returns a copy of this euler.

Returns A copy of the euler.

Return type Euler
```

Note: use this to get a copy of a wrapped euler with no reference to the original data.

make_compatible (`other`)
Make this euler compatible with another, so interpolating between them works as intended.

Note: the rotation order is not taken into account for this function.

rotate (`other`)
Rotates the euler a by another mathutils value.

Parameters `other` (`Euler, Quaternion or Matrix`) – rotation component of mathutils value

rotate_axis(axis, angle)

Rotates the euler a certain amount and returning a unique euler rotation (no 720 degree pitches).

Parameters

- **axis** (*string*) – single character in [‘X’, ‘Y’, ‘Z’].
- **angle** (*float*) – angle in radians.

to_matrix()

Return a matrix representation of the euler.

Returns A 3x3 roation matrix representation of the euler.

Return type `Matrix`

to_quaternion()

Return a quaternion representation of the euler.

Returns Quaternion representation of the euler.

Return type `Quaternion`

zero()

Set all values to zero.

is_wrapped

True when this object wraps external data (readonly).

Type boolean

order

Euler rotation order.

Type string in [‘XYZ’, ‘XZY’, ‘YXZ’, ‘YZX’, ‘ZXY’, ‘ZYX’]

owner

The item this is wrapping or None (readonly).

x

Euler X axis in radians.

Type float

y

Euler Y axis in radians.

Type float

z

Euler Z axis in radians.

Type float

class `mathutils.Matrix`

This object gives access to Matrices in Blender.

```
import mathutils
```

```
# todo
```

classmethod OrthoProjection(axis, size)

Create a matrix to represent an orthographic projection.

Parameters

- **axis** (string or [Vector](#)) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix. Or a vector for an arbitrary axis
- **size** (*int*) – The size of the projection matrix to construct [2, 4].

Returns A new projection matrix.

Return type [Matrix](#)

classmethod Rotation (*angle, size, axis*)

Create a matrix representing a rotation.

Parameters

- **angle** (*float*) – The angle of rotation desired, in radians.
- **size** (*int*) – The size of the rotation matrix to construct [2, 4].
- **axis** (string or [Vector](#)) – a string in ['X', 'Y', 'Z'] or a 3D Vector Object (optional when size is 2).

Returns A new rotation matrix.

Return type [Matrix](#)

classmethod Scale (*factor, size, axis*)

Create a matrix representing a scaling.

Parameters

- **factor** (*float*) – The factor of scaling to apply.
- **size** (*int*) – The size of the scale matrix to construct [2, 4].
- **axis** ([Vector](#)) – Direction to influence scale. (optional).

Returns A new scale matrix.

Return type [Matrix](#)

classmethod Shear (*plane, size, factor*)

Create a matrix to represent an shear transformation.

Parameters

- **plane** (string) – Can be any of the following: ['X', 'Y', 'XY', 'XZ', 'YZ'], where a single axis is for a 2D matrix only.
- **size** (*int*) – The size of the shear matrix to construct [2, 4].
- **factor** (*float or float pair*) – The factor of shear to apply. For a 3 or 4 *size* matrix pass a pair of floats corrasponding with the *plane* axis.

Returns A new shear matrix.

Return type [Matrix](#)

classmethod Translation (*vector*)

Create a matrix representing a translation.

Parameters **vector** ([Vector](#)) – The translation vector.

Returns An identity matrix with a translation.

Return type [Matrix](#)

copy()

Returns a copy of this matrix.

Returns an instance of itself

Return type `Matrix`

decompose()

Return the location, rotation and scale components of this matrix.

Returns loc, rot, scale triple.

Return type (`Vector`, `Quaternion`, `Vector`)

determinant()

Return the determinant of a matrix.

Returns Return a the determinant of a matrix.

Return type float

See Also:

<<http://en.wikipedia.org/wiki/Determinant>>

identity()

Set the matrix to the identity matrix.

Note: An object with zero location and rotation, a scale of one, will have an identity matrix.

See Also:

<http://en.wikipedia.org/wiki/Identity_matrix>

invert()

Set the matrix to its inverse.

Note: ValueError exception is raised.

See Also:

<http://en.wikipedia.org/wiki/Inverse_matrix>

inverted()

Return an inverted copy of the matrix.

Returns the inverted matrix.

Return type `Matrix`

Note: ValueError exception is raised.

lerp(other, factor)

Returns the interpolation of two matrices.

Parameters

- **other** (`Matrix`) – value to interpolate with.
- **factor** (`float`) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type `Matrix`

resize_4x4()

Resize the matrix to 4x4.

rotate(*other*)

Rotates the matrix a by another mathutils value.

Parameters *other* ([Euler](#), [Quaternion](#) or [Matrix](#)) – rotation component of mathutils value

Note: If any of the columns are not unit length this may not have desired results.

to_3x3()

Return a 3x3 copy of this matrix.

Returns a new matrix.

Return type [Matrix](#)

to_4x4()

Return a 4x4 copy of this matrix.

Returns a new matrix.

Return type [Matrix](#)

to_euler(*order*, *euler_compat*)

Return an Euler representation of the rotation matrix (3x3 or 4x4 matrix only).

Parameters

- **order** (*string*) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- **euler_compat** ([Euler](#)) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

Returns Euler representation of the matrix.

Return type [Euler](#)

to_quaternion()

Return a quaternion representation of the rotation matrix.

Returns Quaternion representation of the rotation matrix.

Return type [Quaternion](#)

to_scale()

Return a the scale part of a 3x3 or 4x4 matrix.

Returns Return a the scale of a matrix.

Return type [Vector](#)

Note: This method does not return negative a scale on any axis because it is not possible to obtain this data from the matrix alone.

to_translation()

Return a the translation part of a 4 row matrix.

Returns Return a the translation of a matrix.

Return type `Vector`

transpose()
Set the matrix to its transpose.

See Also:
[<http://en.wikipedia.org/wiki/Transpose>](http://en.wikipedia.org/wiki/Transpose)

transposed()
Return a new, transposed matrix.

Returns a transposed matrix

Return type `Matrix`

zero()
Set all the matrix values to zero.

Returns an instance of itself

Return type `Matrix`

col_size
The column size of the matrix (readonly).

Type int

is_negative
True if this matrix results in a negative scale, 3x3 and 4x4 only, (readonly).

Type bool

is_orthogonal
True if this matrix is orthogonal, 3x3 and 4x4 only, (readonly).

Type bool

is_wrapped
True when this object wraps external data (readonly).

Type boolean

median_scale
The average scale applied to each axis (readonly).

Type float

owner
The item this is wrapping or None (readonly).

row_size
The row size of the matrix (readonly).

Type int

class `mathutils.Quaternion`
This object gives access to Quaternions in Blender.

```
import mathutils

# todo
```

conjugate()
Set the quaternion to its conjugate (negate x, y, z).

conjugated()

Return a new conjugated quaternion.

Returns a new quaternion.

Return type [Quaternion](#)

copy()

Returns a copy of this quaternion.

Returns A copy of the quaternion.

Return type [Quaternion](#)

Note: use this to get a copy of a wrapped quaternion with no reference to the original data.

cross (other)

Return the cross product of this quaternion and another.

Parameters **other** ([Quaternion](#)) – The other quaternion to perform the cross product with.

Returns The cross product.

Return type [Quaternion](#)

dot (other)

Return the dot product of this quaternion and another.

Parameters **other** ([Quaternion](#)) – The other quaternion to perform the dot product with.

Returns The dot product.

Return type [Quaternion](#)

identity()

Set the quaternion to an identity quaternion.

Returns an instance of itself.

Return type [Quaternion](#)

invert()

Set the quaternion to its inverse.

inverted()

Return a new, inverted quaternion.

Returns the inverted value.

Return type [Quaternion](#)

negate()

Set the quaternion to its negative.

Returns an instance of itself.

Return type [Quaternion](#)

normalize()

Normalize the quaternion.

normalized()

Return a new normalized quaternion.

Returns a normalized copy.

Return type `Quaternion`

rotate (*other*)

Rotates the quaternion *a* by another mathutils value.

Parameters `other` (`Euler`, `Quaternion` or `Matrix`) – rotation component of mathutils value

difference (*other*)

Returns a quaternion representing the rotational difference.

Parameters `other` (`Quaternion`) – second quaternion.

Returns the rotational difference between the two quat rotations.

Return type `Quaternion`

slerp (*other*, *factor*)

Returns the interpolation of two quaternions.

Parameters

- `other` (`Quaternion`) – value to interpolate with.
- `factor` (`float`) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type `Quaternion`

to_euler (*order*, *euler_compat*)

Return Euler representation of the quaternion.

Parameters

- `order` (`string`) – Optional rotation order argument in ['XYZ', 'XZY', 'YXZ', 'YZX', 'ZXY', 'ZYX'].
- `euler_compat` (`Euler`) – Optional euler argument the new euler will be made compatible with (no axis flipping between them). Useful for converting a series of matrices to animation curves.

Returns Euler representation of the quaternion.

Return type `Euler`

to_matrix ()

Return a matrix representation of the quaternion.

Returns A 3x3 rotation matrix representation of the quaternion.

Return type `Matrix`

angle

angle of the quaternion.

Type `float`

axis

quaternion axis as a vector.

Type `Vector`

is_wrapped

True when this object wraps external data (readonly).

Type `boolean`

magnitude

Size of the quaternion (readonly).

Type float

owner

The item this is wrapping or None (readonly).

w

Quaternion W value.

Type float

x

Quaternion X axis.

Type float

y

Quaternion Y axis.

Type float

z

Quaternion Z axis.

Type float

class mathutils.Vector

This object gives access to Vectors in Blender.

```
import mathutils
```

```
# zero length vector
```

```
vec = mathutils.Vector((0, 0, 1))
```

```
# unit length vector
```

```
vec_a = vec.copy().normalize()
```

```
vec_b = mathutils.Vector((0, 1, 2))
```

```
vec2d = mathutils.Vector((1, 2))
```

```
vec3d = mathutils.Vector((1, 0, 0))
```

```
vec4d = vec_a.to_4d()
```

```
# other mathutuls types
```

```
quat = mathutils.Quaternion()
```

```
matrix = mathutils.Matrix()
```

```
# Comparison operators can be done on Vector classes:
```

```
# greater and less then test vector length.
```

```
vec_a > vec_b
```

```
vec_a >= vec_b
```

```
vec_a < vec_b
```

```
vec_a <= vec_b
```

```
# ==, != test vector values e.g. 1,2,3 != 3,2,1 even if they are the same length
```

```
vec_a == vec_b
```

```
vec_a != vec_b
```

```
# Math can be performed on Vector classes
vec_a + vec_b
vec_a - vec_b
vec_a * vec_b
vec_a * 10.0
vec_a * matrix
vec_a * vec_b
vec_a * quat
-vec_a

# You can access a vector object like a sequence
x = vec_a[0]
len(vec)
vec_a[:] = vec_b
vec2d[:] = vec3d[:2]

# Vectors support 'swizzle' operations
# See http://en.wikipedia.org/wiki/Swizzling_(computer_graphics)
vec.xyz = vec.zyx
vec.xy = vec4d.zw
vec.xyz = vec4d.wzz
vec4d.wxyz = vec.yxyx
```

angle (other, fallback)

Return the angle between two vectors.

Parameters

- **other** ([Vector](#)) – another vector to compare the angle with
- **fallback** (*any*) – return this value when the angle cant be calculated (zero length vector)

Returns angle in radians or fallback when given

Return type float

Note: Zero length vectors raise an `AttributeError`.

copy ()

Returns a copy of this vector.

Returns A copy of the vector.

Return type [Vector](#)

Note: use this to get a copy of a wrapped vector with no reference to the original data.

cross (other)

Return the cross product of this vector and another.

Parameters **other** ([Vector](#)) – The other vector to perform the cross product with.

Returns The cross product.

Return type [Vector](#)

Note: both vectors must be 3D

dot (*other*)

Return the dot product of this vector and another.

Parameters **other** ([Vector](#)) – The other vector to perform the dot product with.

Returns The dot product.

Return type [Vector](#)

lerp (*other, factor*)

Returns the interpolation of two vectors.

Parameters

- **other** ([Vector](#)) – value to interpolate with.
- **factor** ([float](#)) – The interpolation value in [0.0, 1.0].

Returns The interpolated rotation.

Return type [Vector](#)

negate ()

Set all values to their negative.

Returns an instance of itself

Return type [Vector](#)

normalize ()

Normalize the vector, making the length of the vector always 1.0.

Warning: Normalizing a vector where all values are zero results in all axis having a nan value (not a number).

Note: Normalize works for vectors of all sizes, however 4D Vectors w axis is left untouched.

normalized ()

Return a new, normalized vector.

Returns a normalized copy of the vector

Return type [Vector](#)

project (*other*)

Return the projection of this vector onto the *other*.

Parameters **other** ([Vector](#)) – second vector.

Returns the parallel projection vector

Return type [Vector](#)

reflect (*mirror*)

Return the reflection vector from the *mirror* argument.

Parameters **mirror** ([Vector](#)) – This vector could be a normal from the reflecting surface.

Returns The reflected vector matching the size of this vector.

Return type [Vector](#)

resize_2d()

Resize the vector to 2D (x, y).

Returns an instance of itself

Return type [Vector](#)

resize_3d()

Resize the vector to 3D (x, y, z).

Returns an instance of itself

Return type [Vector](#)

resize_4d()

Resize the vector to 4D (x, y, z, w).

Returns an instance of itself

Return type [Vector](#)

rotate(*other*)

Return vector by a rotation value.

Parameters *other* ([Euler](#), [Quaternion](#) or [Matrix](#)) – rotation component of `mathutils` value

difference(*other*)

Returns a quaternion representing the rotational difference between this vector and another.

Parameters *other* ([Vector](#)) – second vector.

Returns the rotational difference between the two vectors.

Return type [Quaternion](#)

Note: 2D vectors raise an `AttributeError`.

to_2d()

Return a 2d copy of the vector.

Returns a new vector

Return type [Vector](#)

to_3d()

Return a 3d copy of the vector.

Returns a new vector

Return type [Vector](#)

to_4d()

Return a 4d copy of the vector.

Returns a new vector

Return type [Vector](#)

to_track_quat(*track, up*)

Return a quaternion rotation from the vector and the track and up axis.

Parameters

- **track** (*string*) – Track axis in ['X', 'Y', 'Z', '-X', '-Y', '-Z'].

- **up** (*string*) – Up axis in [‘X’, ‘Y’, ‘Z’].

Returns rotation from the vector and the track and up axis.

Return type [Quaternion](#)

to_tuple (*precision=-1*)

Return this vector as a tuple with.

Parameters **precision** (*int*) – The number to round the value to in [-1, 21].

Returns the values of the vector rounded by *precision*

Return type tuple

zero ()

Set all values to zero.

is_wrapped

True when this object wraps external data (readonly).

Type boolean

length

Vector Length.

Type float

magnitude

Vector Length.

Type float

owner

The item this is wrapping or None (readonly).

w

Vector W axis (4D Vectors only).

Type float

ww

Undocumented ([contribute](#))

www

Undocumented ([contribute](#))

wwww

Undocumented ([contribute](#))

wwwx

Undocumented ([contribute](#))

wwwy

Undocumented ([contribute](#))

wwwz

Undocumented ([contribute](#))

wwx

Undocumented ([contribute](#))

wwyw

Undocumented ([contribute](#))

wwxx
Undocumented ([contribute](#))

wwxy
Undocumented ([contribute](#))

wwxz
Undocumented ([contribute](#))

wwy
Undocumented ([contribute](#))

wwyw
Undocumented ([contribute](#))

wwyx
Undocumented ([contribute](#))

wwyy
Undocumented ([contribute](#))

wwyz
Undocumented ([contribute](#))

wwz
Undocumented ([contribute](#))

wwzw
Undocumented ([contribute](#))

wwzx
Undocumented ([contribute](#))

wwzy
Undocumented ([contribute](#))

wwzz
Undocumented ([contribute](#))

wx
Undocumented ([contribute](#))

wxw
Undocumented ([contribute](#))

wxww
Undocumented ([contribute](#))

wxwx
Undocumented ([contribute](#))

wxwy
Undocumented ([contribute](#))

wxwz
Undocumented ([contribute](#))

wxx
Undocumented ([contribute](#))

wxxx
Undocumented ([contribute](#))

wxxx

Undocumented ([contribute](#))

wxxy

Undocumented ([contribute](#))

wxxz

Undocumented ([contribute](#))

wxy

Undocumented ([contribute](#))

wxyw

Undocumented ([contribute](#))

wxyx

Undocumented ([contribute](#))

wxyy

Undocumented ([contribute](#))

wxyz

Undocumented ([contribute](#))

wxz

Undocumented ([contribute](#))

wxzw

Undocumented ([contribute](#))

wxzx

Undocumented ([contribute](#))

wxzy

Undocumented ([contribute](#))

wxzz

Undocumented ([contribute](#))

wy

Undocumented ([contribute](#))

wyw

Undocumented ([contribute](#))

wyww

Undocumented ([contribute](#))

wywz

Undocumented ([contribute](#))

wyx

Undocumented ([contribute](#))

wyxw

Undocumented ([contribute](#))

wyxx
Undocumented ([contribute](#))

wyxy
Undocumented ([contribute](#))

wyxz
Undocumented ([contribute](#))

wyy
Undocumented ([contribute](#))

wyyw
Undocumented ([contribute](#))

wyyx
Undocumented ([contribute](#))

wyyy
Undocumented ([contribute](#))

wyyz
Undocumented ([contribute](#))

wyz
Undocumented ([contribute](#))

wyzw
Undocumented ([contribute](#))

wyzz
Undocumented ([contribute](#))

wyzy
Undocumented ([contribute](#))

wyzz
Undocumented ([contribute](#))

wz
Undocumented ([contribute](#))

wzw
Undocumented ([contribute](#))

wzww
Undocumented ([contribute](#))

wzwx
Undocumented ([contribute](#))

wzwy
Undocumented ([contribute](#))

wzwz
Undocumented ([contribute](#))

wzx
Undocumented ([contribute](#))

wzxw
Undocumented ([contribute](#))

wzxx

Undocumented ([contribute](#))

wzxy

Undocumented ([contribute](#))

wzxz

Undocumented ([contribute](#))

wzy

Undocumented ([contribute](#))

wzyw

Undocumented ([contribute](#))

wzyx

Undocumented ([contribute](#))

wzyy

Undocumented ([contribute](#))

wzyz

Undocumented ([contribute](#))

wzz

Undocumented ([contribute](#))

wzzw

Undocumented ([contribute](#))

wzzx

Undocumented ([contribute](#))

wzyy

Undocumented ([contribute](#))

wzzz

Undocumented ([contribute](#))

x

Vector X axis.

Type float

xw

Undocumented ([contribute](#))

xww

Undocumented ([contribute](#))

xwww

Undocumented ([contribute](#))

xwwx

Undocumented ([contribute](#))

xwwy

Undocumented ([contribute](#))

xwwz

Undocumented ([contribute](#))

xwx

Undocumented ([contribute](#))

xwxw
Undocumented ([contribute](#))

xwxz
Undocumented ([contribute](#))

xwxy
Undocumented ([contribute](#))

xwxz
Undocumented ([contribute](#))

xwy
Undocumented ([contribute](#))

xwyw
Undocumented ([contribute](#))

xwyx
Undocumented ([contribute](#))

xwyy
Undocumented ([contribute](#))

xwyz
Undocumented ([contribute](#))

xwz
Undocumented ([contribute](#))

xwzw
Undocumented ([contribute](#))

xwzx
Undocumented ([contribute](#))

xwzy
Undocumented ([contribute](#))

xwzz
Undocumented ([contribute](#))

xx
Undocumented ([contribute](#))

xxw
Undocumented ([contribute](#))

xxww
Undocumented ([contribute](#))

xxwx
Undocumented ([contribute](#))

xxwy
Undocumented ([contribute](#))

xxwz
Undocumented ([contribute](#))

xxx
Undocumented ([contribute](#))

xxxxw
Undocumented ([contribute](#))

xxxxx
Undocumented ([contribute](#))

xxxxy
Undocumented ([contribute](#))

xxxxz
Undocumented ([contribute](#))

xxxy
Undocumented ([contribute](#))

xxyw
Undocumented ([contribute](#))

xxyx
Undocumented ([contribute](#))

xxyy
Undocumented ([contribute](#))

xxyz
Undocumented ([contribute](#))

xxz
Undocumented ([contribute](#))

xxzw
Undocumented ([contribute](#))

xxzx
Undocumented ([contribute](#))

xxzy
Undocumented ([contribute](#))

xxzz
Undocumented ([contribute](#))

xy
Undocumented ([contribute](#))

xyw
Undocumented ([contribute](#))

xyww
Undocumented ([contribute](#))

xywx
Undocumented ([contribute](#))

xywy
Undocumented ([contribute](#))

xywz
Undocumented ([contribute](#))

xyx
Undocumented ([contribute](#))

xyxw
Undocumented ([contribute](#))

xyxx
Undocumented ([contribute](#))

xyxy
Undocumented ([contribute](#))

xyxz
Undocumented ([contribute](#))

xyy
Undocumented ([contribute](#))

xyyw
Undocumented ([contribute](#))

xyyx
Undocumented ([contribute](#))

xyyy
Undocumented ([contribute](#))

xyyz
Undocumented ([contribute](#))

xyz
Undocumented ([contribute](#))

xyzw
Undocumented ([contribute](#))

xyzx
Undocumented ([contribute](#))

xyzy
Undocumented ([contribute](#))

xyzz
Undocumented ([contribute](#))

xz
Undocumented ([contribute](#))

xzw
Undocumented ([contribute](#))

xzww
Undocumented ([contribute](#))

xzwx
Undocumented ([contribute](#))

xzwy
Undocumented ([contribute](#))

xz wz
Undocumented ([contribute](#))

xzx
Undocumented ([contribute](#))

xzxw

Undocumented ([contribute](#))

xzxx

Undocumented ([contribute](#))

xzxy

Undocumented ([contribute](#))

xzxz

Undocumented ([contribute](#))

xzy

Undocumented ([contribute](#))

xzyw

Undocumented ([contribute](#))

xzyx

Undocumented ([contribute](#))

xzyy

Undocumented ([contribute](#))

xzyz

Undocumented ([contribute](#))

xzz

Undocumented ([contribute](#))

xzzw

Undocumented ([contribute](#))

xzxx

Undocumented ([contribute](#))

xzzy

Undocumented ([contribute](#))

xzzz

Undocumented ([contribute](#))

y

Vector Y axis.

Type float

yw

Undocumented ([contribute](#))

yww

Undocumented ([contribute](#))

ywww

Undocumented ([contribute](#))

ywwx

Undocumented ([contribute](#))

ywwy

Undocumented ([contribute](#))

ywwz

Undocumented ([contribute](#))

ywx
Undocumented ([contribute](#))

ywxw
Undocumented ([contribute](#))

ywxz
Undocumented ([contribute](#))

ywxy
Undocumented ([contribute](#))

ywxz
Undocumented ([contribute](#))

ywy
Undocumented ([contribute](#))

ywyw
Undocumented ([contribute](#))

ywyx
Undocumented ([contribute](#))

ywyy
Undocumented ([contribute](#))

ywyz
Undocumented ([contribute](#))

ywz
Undocumented ([contribute](#))

ywzw
Undocumented ([contribute](#))

ywzx
Undocumented ([contribute](#))

ywzy
Undocumented ([contribute](#))

ywzz
Undocumented ([contribute](#))

yx
Undocumented ([contribute](#))

yxw
Undocumented ([contribute](#))

yxww
Undocumented ([contribute](#))

yxwx
Undocumented ([contribute](#))

yxwy
Undocumented ([contribute](#))

yxwz
Undocumented ([contribute](#))

yxx
Undocumented ([contribute](#))

yxxxw
Undocumented ([contribute](#))

yxxxx
Undocumented ([contribute](#))

yxxxy
Undocumented ([contribute](#))

yxxxz
Undocumented ([contribute](#))

yxy
Undocumented ([contribute](#))

yxyw
Undocumented ([contribute](#))

yxyx
Undocumented ([contribute](#))

yxyy
Undocumented ([contribute](#))

yxyz
Undocumented ([contribute](#))

yxz
Undocumented ([contribute](#))

yxzw
Undocumented ([contribute](#))

yxzx
Undocumented ([contribute](#))

yxzy
Undocumented ([contribute](#))

yxzz
Undocumented ([contribute](#))

yy
Undocumented ([contribute](#))

yyw
Undocumented ([contribute](#))

yyww
Undocumented ([contribute](#))

yywx
Undocumented ([contribute](#))

yywy
Undocumented ([contribute](#))

yywz
Undocumented ([contribute](#))

yyx
Undocumented ([contribute](#))

yyxw
Undocumented ([contribute](#))

yyxx
Undocumented ([contribute](#))

yyxy
Undocumented ([contribute](#))

yyxz
Undocumented ([contribute](#))

yyy
Undocumented ([contribute](#))

yyyw
Undocumented ([contribute](#))

yyyx
Undocumented ([contribute](#))

yyyy
Undocumented ([contribute](#))

yyyz
Undocumented ([contribute](#))

yyz
Undocumented ([contribute](#))

yyzw
Undocumented ([contribute](#))

yyzx
Undocumented ([contribute](#))

yyzy
Undocumented ([contribute](#))

yyzz
Undocumented ([contribute](#))

yz
Undocumented ([contribute](#))

yzw
Undocumented ([contribute](#))

yzww
Undocumented ([contribute](#))

yzwx
Undocumented ([contribute](#))

yzwy
Undocumented ([contribute](#))

yzwz
Undocumented ([contribute](#))

yzx
Undocumented ([contribute](#))

yzxw
Undocumented ([contribute](#))

yzxx
Undocumented ([contribute](#))

yzxy
Undocumented ([contribute](#))

yzxz
Undocumented ([contribute](#))

yzy
Undocumented ([contribute](#))

yzyw
Undocumented ([contribute](#))

yzyx
Undocumented ([contribute](#))

yzyy
Undocumented ([contribute](#))

yzyz
Undocumented ([contribute](#))

yzz
Undocumented ([contribute](#))

yzzw
Undocumented ([contribute](#))

yzzx
Undocumented ([contribute](#))

yzzy
Undocumented ([contribute](#))

yzzz
Undocumented ([contribute](#))

z
Vector Z axis (3D Vectors only).

Type float

zw
Undocumented ([contribute](#))

zww
Undocumented ([contribute](#))

zwww
Undocumented ([contribute](#))

zwx
Undocumented ([contribute](#))

zwy
Undocumented ([contribute](#))

zwwz
Undocumented ([contribute](#))

zwx
Undocumented ([contribute](#))

zwxw
Undocumented ([contribute](#))

zwxx
Undocumented ([contribute](#))

zwxy
Undocumented ([contribute](#))

zwxz
Undocumented ([contribute](#))

zwy
Undocumented ([contribute](#))

zwyw
Undocumented ([contribute](#))

zwyx
Undocumented ([contribute](#))

zwyy
Undocumented ([contribute](#))

zwyz
Undocumented ([contribute](#))

zwz
Undocumented ([contribute](#))

zwzw
Undocumented ([contribute](#))

zwzx
Undocumented ([contribute](#))

zwzy
Undocumented ([contribute](#))

zwzz
Undocumented ([contribute](#))

zx
Undocumented ([contribute](#))

zxw
Undocumented ([contribute](#))

zxww
Undocumented ([contribute](#))

zxwx
Undocumented ([contribute](#))

zxwy
Undocumented ([contribute](#))

zxwz

Undocumented ([contribute](#))

zxx

Undocumented ([contribute](#))

zxxw

Undocumented ([contribute](#))

xxxx

Undocumented ([contribute](#))

zxxxy

Undocumented ([contribute](#))

zxxxz

Undocumented ([contribute](#))

zxy

Undocumented ([contribute](#))

zxyw

Undocumented ([contribute](#))

zxyx

Undocumented ([contribute](#))

zxyy

Undocumented ([contribute](#))

zxyz

Undocumented ([contribute](#))

zxz

Undocumented ([contribute](#))

zxzw

Undocumented ([contribute](#))

zxzx

Undocumented ([contribute](#))

zxzy

Undocumented ([contribute](#))

zxzz

Undocumented ([contribute](#))

zy

Undocumented ([contribute](#))

zyw

Undocumented ([contribute](#))

zyww

Undocumented ([contribute](#))

zywx

Undocumented ([contribute](#))

zywy

Undocumented ([contribute](#))

zywz
Undocumented ([contribute](#))

zyx
Undocumented ([contribute](#))

zyxw
Undocumented ([contribute](#))

zyxx
Undocumented ([contribute](#))

zyxy
Undocumented ([contribute](#))

zyxz
Undocumented ([contribute](#))

zyy
Undocumented ([contribute](#))

zyyw
Undocumented ([contribute](#))

zyyx
Undocumented ([contribute](#))

zyyy
Undocumented ([contribute](#))

zyyz
Undocumented ([contribute](#))

zyz
Undocumented ([contribute](#))

zyzw
Undocumented ([contribute](#))

zyzx
Undocumented ([contribute](#))

zyzy
Undocumented ([contribute](#))

zyzz
Undocumented ([contribute](#))

zz
Undocumented ([contribute](#))

zzw
Undocumented ([contribute](#))

zzww
Undocumented ([contribute](#))

zzwx
Undocumented ([contribute](#))

zzwy
Undocumented ([contribute](#))

zzwz

Undocumented ([contribute](#))

zzx

Undocumented ([contribute](#))

zzxw

Undocumented ([contribute](#))

zzxx

Undocumented ([contribute](#))

zzxy

Undocumented ([contribute](#))

zzxz

Undocumented ([contribute](#))

zzy

Undocumented ([contribute](#))

zzyw

Undocumented ([contribute](#))

zzyx

Undocumented ([contribute](#))

zzyy

Undocumented ([contribute](#))

zzyz

Undocumented ([contribute](#))

zzz

Undocumented ([contribute](#))

zzzw

Undocumented ([contribute](#))

zzzx

Undocumented ([contribute](#))

zzzy

Undocumented ([contribute](#))

zzzz

Undocumented ([contribute](#))

3.2 Geometry Utilities (mathutils.geometry)

The Blender geometry module

`mathutils.geometry.area_tri(v1, v2, v3)`

Returns the area size of the 2D or 3D triangle defined.

Parameters

- `v1 (mathutils.Vector)` – Point1
- `v2 (mathutils.Vector)` – Point2
- `v3 (mathutils.Vector)` – Point3

Return type float

```
mathutils.geometry.barycentric_transform(point, tri_a1, tri_a2, tri_a3, tri_b1, tri_b2,  
                                         tri_b3)
```

Return a transformed point, the transformation is defined by 2 triangles.

Parameters

- **point** (`mathutils.Vector`) – The point to transform.
- **tri_a1** (`mathutils.Vector`) – source triangle vertex.
- **tri_a2** (`mathutils.Vector`) – source triangle vertex.
- **tri_a3** (`mathutils.Vector`) – source triangle vertex.
- **tri_a1** – target triangle vertex.
- **tri_a2** – target triangle vertex.
- **tri_a3** – target triangle vertex.

Returns The transformed point

Return type `mathutils.Vector`'s`

```
mathutils.geometry.box_pack_2d(boxes)
```

Returns the normal of the 3D tri or quad.

Parameters **boxes** (*list*) – list of boxes, each box is a list where the first 4 items are [x, y, width, height, ...] other items are ignored.

Returns the width and height of the packed bounding box

Return type tuple, pair of floats

```
mathutils.geometry.interpolate_bezier(knot1, handle1, handle2, knot2, resolution)
```

Interpolate a bezier spline segment.

Parameters

- **knot1** (`mathutils.Vector`) – First bezier spline point.
- **handle1** (`mathutils.Vector`) – First bezier spline handle.
- **handle2** (`mathutils.Vector`) – Second bezier spline handle.
- **knot2** (`mathutils.Vector`) – Second bezier spline point.
- **resolution** (*int*) – Number of points to return.

Returns The interpolated points

Return type list of `mathutils.Vector`'s`

```
mathutils.geometry.intersect_line_line(v1, v2, v3, v4)
```

Returns a tuple with the points on each line respectively closest to the other.

Parameters

- **v1** (`mathutils.Vector`) – First point of the first line
- **v2** (`mathutils.Vector`) – Second point of the first line
- **v3** (`mathutils.Vector`) – First point of the second line
- **v4** (`mathutils.Vector`) – Second point of the second line

Return type tuple of `mathutils.Vector`'s`

`mathutils.geometry.intersect_line_line_2d(lineA_p1, lineA_p2, lineB_p1, lineB_p2)`

Takes 2 lines (as 4 vectors) and returns a vector for their point of intersection or None.

Parameters

- `lineA_p1` (`mathutils.Vector`) – First point of the first line
- `lineA_p2` (`mathutils.Vector`) – Second point of the first line
- `lineB_p1` (`mathutils.Vector`) – First point of the second line
- `lineB_p2` (`mathutils.Vector`) – Second point of the second line

Returns The point of intersection or None when not found

Return type `mathutils.Vector` or None

`mathutils.geometry.intersect_line_plane(line_a, line_b, plane_co, plane_no, no_flip=False)`

Takes 2 lines (as 4 vectors) and returns a vector for their point of intersection or None.

Parameters

- `line_a` (`mathutils.Vector`) – First point of the first line
- `line_b` (`mathutils.Vector`) – Second point of the first line
- `plane_co` (`mathutils.Vector`) – A point on the plane
- `plane_no` (`mathutils.Vector`) – The direction the plane is facing
- `no_flip` (:boolean) – Always return an intersection on the directon defined bt line_a -> line_b

Returns The point of intersection or None when not found

Return type `mathutils.Vector` or None

`mathutils.geometry.intersect_line_sphere(line_a, line_b, sphere_co, sphere_radius, clip=True)`

Takes a lines (as 2 vectors), a sphere as a point and a radius and returns the intersection

Parameters

- `line_a` (`mathutils.Vector`) – First point of the first line
- `line_b` (`mathutils.Vector`) – Second point of the first line
- `sphere_co` (`mathutils.Vector`) – The center of the sphere
- `sphere_radius` (`sphere_radius`) – Radius of the sphere

Returns The intersection points as a pair of vectors or None when there is no intersection

Return type A tuple pair containing `mathutils.Vector` or None

`mathutils.geometry.intersect_line_sphere_2d(line_a, line_b, sphere_co, sphere_radius, clip=True)`

Takes a lines (as 2 vectors), a sphere as a point and a radius and returns the intersection

Parameters

- `line_a` (`mathutils.Vector`) – First point of the first line
- `line_b` (`mathutils.Vector`) – Second point of the first line
- `sphere_co` (`mathutils.Vector`) – The center of the sphere
- `sphere_radius` (`sphere_radius`) – Radius of the sphere

Returns The intersection points as a pair of vectors or None when there is no intersection

Return type A tuple pair containing `mathutils.Vector` or None

`mathutils.geometry.intersect_point_line(pt, line_p1, line_p2)`

Takes a point and a line and returns a tuple with the closest point on the line and its distance from the first point of the line as a percentage of the length of the line.

Parameters

- `pt` (`mathutils.Vector`) – Point
- `line_p1` (`mathutils.Vector`) – First point of the line
- `line_p2` – Second point of the line

Return type (`mathutils.Vector`, float)

`mathutils.geometry.intersect_point_quad_2d(pt, quad_p1, quad_p2, quad_p3, quad_p4)`

Takes 5 vectors (using only the x and y coordinates): one is the point and the next 4 define the quad, only the x and y are used from the vectors. Returns 1 if the point is within the quad, otherwise 0.

Parameters

- `pt` – Point
- `quad_p1` (`mathutils.Vector`) – First point of the quad
- `quad_p2` (`mathutils.Vector`) – Second point of the quad
- `quad_p3` (`mathutils.Vector`) – Third point of the quad
- `quad_p4` (`mathutils.Vector`) – Forth point of the quad

Return type int

`mathutils.geometry.intersect_point_tri_2d(pt, tri_p1, tri_p2, tri_p3)`

Takes 4 vectors (using only the x and y coordinates): one is the point and the next 3 define the triangle. Returns 1 if the point is within the triangle, otherwise 0.

Parameters

- `pt` – Point
- `tri_p1` (`mathutils.Vector`) – First point of the triangle
- `tri_p2` (`mathutils.Vector`) – Second point of the triangle
- `tri_p3` (`mathutils.Vector`) – Third point of the triangle

Return type int

`mathutils.geometry.intersect_ray_tri(v1, v2, v3, ray, orig, clip=True)`

Returns the intersection between a ray and a triangle, if possible, returns None otherwise.

Parameters

- `v1` (`mathutils.Vector`) – Point1
- `v2` (`mathutils.Vector`) – Point2
- `v3` (`mathutils.Vector`) – Point3
- `ray` (`mathutils.Vector`) – Direction of the projection
- `orig` (`mathutils.Vector`) – Origin
- `clip` (boolean) – When False, don't restrict the intersection to the area of the triangle, use the infinite plane defined by the triangle.

Returns The point of intersection or None if no intersection is found

Return type `mathutils.Vector` or `None`

`mathutils.geometry.normal(v1, v2, v3, v4=None)`

Returns the normal of the 3D tri or quad.

Parameters

- `v1` (`mathutils.Vector`) – Point1
- `v2` (`mathutils.Vector`) – Point2
- `v3` (`mathutils.Vector`) – Point3
- `v4` (`mathutils.Vector`) – Point4 (optional)

Return type `mathutils.Vector`

`mathutils.geometry.tesselate_polygon(veclist_list)`

Takes a list of polylines (each point a vector) and returns the point indices for a polyline filled with triangles.

Parameters `veclist_list` – list of polylines

Return type list

3.3 bgl module (OpenGL wrapper)

This module wraps OpenGL constants and functions, making them available from within Blender Python.

The complete list can be retrieved from the module itself, by listing its contents: `dir(bgl)`. A simple search on the net can point to more than enough material to teach OpenGL programming, from books to many collections of tutorials.

The “red book”: “*OpenGL Programming Guide: The Official Guide to Learning OpenGL*” and the online NeHe tutorials are two of the best resources.

..note:: You can use the `Image` type to load and set textures. See `Image.gl_load` and `Image.gl_load`, for example. OpenGL.org NeHe GameDev

glAccum(op, value) :

Operate on the accumulation buffer.

See Also:

[OpenGL Docs](#)

Parameters

- `op` (*Enumerated constant*) – The accumulation buffer operation.
- `value` (*float*) – a value used in the accumulation buffer operation.

glAlphaFunc(func, ref) :

Specify the alpha test function.

See Also:

[OpenGL Docs](#)

Parameters

- `func` (*Enumerated constant*) – Specifies the alpha comparison function.
- `ref` (*float*) – The reference value that incoming alpha values are compared to. Clamped between 0 and 1.

glAreTexturesResident(n, textures, residences) :

Determine if textures are loaded in texture memory

See Also:

[OpenGL Docs](#)

Parameters

- **n** (*int*) – Specifies the number of textures to be queried.
- **textures** (*Buffer object* I{type GL_INT}) – Specifies an array containing the names of the textures to be queried
- **residences** (*Buffer object* I{type GL_INT}(boolean)) – An array in which the texture residence status is returned. The residence status of a texture named by an element of textures is returned in the corresponding element of residences.

glBegin(mode) :

Delimit the vertices of a primitive or a group of like primitives

See Also:

[OpenGL Docs](#)

Parameters mode (*Enumerated constant*) – Specifies the primitive that will be created from vertices between glBegin and glEnd.

glBindTexture(target, texture) :

Bind a named texture to a texturing target

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the target to which the texture is bound.
- **texture** (*unsigned int*) – Specifies the name of a texture.

glBitmap(width, height, xorig, yorig, xmove, ymove, bitmap) :

Draw a bitmap

See Also:

[OpenGL Docs](#)

Parameters

- **height** (*width*,) – Specify the pixel width and height of the bitmap image.
- **yorig** (*xorig*,) – Specify the location of the origin in the bitmap image. The origin is measured from the lower left corner of the bitmap, with right and up being the positive axes.
- **ymove** (*xmove*,) – Specify the x and y offsets to be added to the current raster position after the bitmap is drawn.
- **bitmap** (*Buffer object* I{type GL_BYTE}) – Specifies the address of the bitmap image.

glBlendFunc(sfactor, dfactor) :

Specify pixel arithmetic

See Also:

[OpenGL Docs](#)

Parameters

- **sfactor** (*Enumerated constant*) – Specifies how the red, green, blue, and alpha source blending factors are computed.
- **dfactor** (*Enumerated constant*) – Specifies how the red, green, blue, and alpha destination blending factors are computed.

glCallList(list):

Execute a display list

See Also:

[OpenGL Docs](#)

Parameters **list** (*unsigned int*) – Specifies the integer name of the display list to be executed.

glCallLists(n, type, lists):

Execute a list of display lists

See Also:

[OpenGL Docs](#)

Parameters

- **n** (*int*) – Specifies the number of display lists to be executed.
- **type** (*Enumerated constant*) – Specifies the type of values in lists.
- **lists** (*Buffer object*) – Specifies the address of an array of name offsets in the display list. The pointer type is void because the offsets can be bytes, shorts, ints, or floats, depending on the value of type.

glClear(mask):

Clear buffers to preset values

See Also:

[OpenGL Docs](#)

Parameters **mask** (*Enumerated constant(s)*) – Bitwise OR of masks that indicate the buffers to be cleared.

glClearAccum(red, green, blue, alpha):

Specify clear values for the accumulation buffer

See Also:

[OpenGL Docs](#)

Parameters **green, blue, alpha** (*red,*) – Specify the red, green, blue, and alpha values used when the accumulation buffer is cleared. The initial values are all 0.

glClearColor(red, green, blue, alpha):

Specify clear values for the color buffers

See Also:

[OpenGL Docs](#)

Parameters `green, blue, alpha` (*red,*) – Specify the red, green, blue, and alpha values used when the color buffers are cleared. The initial values are all 0.

glClearDepth (*depth*) :

Specify the clear value for the depth buffer

See Also:

[OpenGL Docs](#)

Parameters `depth` (*int*) – Specifies the depth value used when the depth buffer is cleared. The initial value is 1.

glClearIndex (*c*) :

Specify the clear value for the color index buffers

See Also:

[OpenGL Docs](#)

Parameters `c` (*float*) – Specifies the index used when the color index buffers are cleared. The initial value is 0.

glClearStencil (*s*) :

Specify the clear value for the stencil buffer

See Also:

[OpenGL Docs](#)

Parameters `s` (*int*) – Specifies the index used when the stencil buffer is cleared. The initial value is 0.

glClipPlane (*plane, equation*) :

Specify a plane against which all geometry is clipped

See Also:

[OpenGL Docs](#)

Parameters

- `plane` (*Enumerated constant*) – Specifies which clipping plane is being positioned.
- `equation` (`Buffer` object I{type GL_FLOAT}(double)) – Specifies the address of an array of four double-precision floating-point values. These values are interpreted as a plane equation.

glColor (*red, green, blue, alpha*) :

B{`glColor3b, glColor3d, glColor3f, glColor3i, glColor3s, glColor3ub, glColor3ui, glColor3us, glColor4b, glColor4d, glColor4f, glColor4i, glColor4s, glColor4ub, glColor4ui, glColor4us, glColor3bv, glColor3dv, glColor3fv, glColor3iv, glColor3sv, glColor3ubv, glColor3uiv, glColor3usv, glColor4bv, glColor4dv, glColor4fv, glColor4iv, glColor4sv, glColor4ubv, glColor4uiv, glColor4usv`}

Set a new color.

See Also:

[OpenGL Docs](#)

Parameters

- `green, blue` (*red,*) – Specify new red, green, and blue values for the current color.

- **alpha** – Specifies a new alpha value for the current color. Included only in the four-argument glColor4 commands. (With ‘4’ colors only)

glColorMask(red, green, blue, alpha):

Enable and disable writing of frame buffer color components

See Also:

[OpenGL Docs](#)

Parameters **green, blue, alpha (red,)** – Specify whether red, green, blue, and alpha can or cannot be written into the frame buffer. The initial values are all GL_TRUE, indicating that the color components can be written.

glColorMaterial(face, mode):

Cause a material color to track the current color

See Also:

[OpenGL Docs](#)

Parameters

- **face (Enumerated constant)** – Specifies whether front, back, or both front and back material parameters should track the current color.
- **mode (Enumerated constant)** – Specifies which of several material parameters track the current color.

glCopyPixels(x, y, width, height, type):

Copy pixels in the frame buffer

See Also:

[OpenGL Docs](#)

Parameters

- **y (x,)** – Specify the window coordinates of the lower left corner of the rectangular region of pixels to be copied.
- **width,height** – Specify the dimensions of the rectangular region of pixels to be copied. Both must be non-negative.
- **type (Enumerated constant)** – Specifies whether color values, depth values, or stencil values are to be copied.

def glCopyTexImage2D(target, level, internalformat, x, y, width, height, border):

Copy pixels into a 2D texture image

See Also:

[OpenGL Docs](#)

Parameters

- **target (Enumerated constant)** – Specifies the target texture.
- **level (int)** – Specifies the level-of-detail number. Level 0 is the base image level. Level n is the nth mipmap reduction image.
- **internalformat (int)** – Specifies the number of color components in the texture.

- **y** (*x*) – Specify the window coordinates of the first pixel that is copied from the frame buffer. This location is the lower left corner of a rectangular block of pixels.
- **width** (*int*) – Specifies the width of the texture image. Must be $2n+2(\text{border})$ for some integer n. All implementations support texture images that are at least 64 texels wide.
- **height** (*int*) – Specifies the height of the texture image. Must be $2m+2(\text{border})$ for some integer m. All implementations support texture images that are at least 64 texels high.
- **border** (*int*) – Specifies the width of the border. Must be either 0 or 1.

glCullFace (mode) :

Specify whether front- or back-facing facets can be culled

See Also:

[OpenGL Docs](#)

Parameters mode (*Enumerated constant*) – Specifies whether front- or back-facing facets are candidates for culling.

glDeleteLists (list, range) :

Delete a contiguous group of display lists

See Also:

[OpenGL Docs](#)

Parameters

- **list** (*unsigned int*) – Specifies the integer name of the first display list to delete
- **range** (*int*) – Specifies the number of display lists to delete

glDeleteTextures (n, textures) :

Delete named textures

See Also:

[OpenGL Docs](#)

Parameters

- **n** (*int*) – Specifies the number of textures to be deleted
- **textures** (*Buffer I{GL_INT}*) – Specifies an array of textures to be deleted

glDepthFunc (func) :

Specify the value used for depth buffer comparisons

See Also:

[OpenGL Docs](#)

Parameters func (*Enumerated constant*) – Specifies the depth comparison function.

glDepthMask (flag) :

Enable or disable writing into the depth buffer

See Also:

[OpenGL Docs](#)

Parameters `flag` (*int (boolean)*) – Specifies whether the depth buffer is enabled for writing. If flag is GL_FALSE, depth buffer writing is disabled. Otherwise, it is enabled. Initially, depth buffer writing is enabled.

glDepthRange (zNear, zFar) :

Specify mapping of depth values from normalized device coordinates to window coordinates

See Also:

[OpenGL Docs](#)

Parameters

- `zNear` (*int*) – Specifies the mapping of the near clipping plane to window coordinates. The initial value is 0.
- `zFar` (*int*) – Specifies the mapping of the far clipping plane to window coordinates. The initial value is 1.

glDisable (cap) :

Disable server-side GL capabilities

See Also:

[OpenGL Docs](#)

Parameters `cap` (*Enumerated constant*) – Specifies a symbolic constant indicating a GL capability.

glDrawBuffer (mode) :

Specify which color buffers are to be drawn into

See Also:

[OpenGL Docs](#)

Parameters `mode` (*Enumerated constant*) – Specifies up to four color buffers to be drawn into.

glDrawPixels (width, height, format, type, pixels) :

Write a block of pixels to the frame buffer

See Also:

[OpenGL Docs](#)

Parameters

- `height` (*width*,) – Specify the dimensions of the pixel rectangle to be written into the frame buffer.
- `format` (*Enumerated constant*) – Specifies the format of the pixel data.
- `type` (*Enumerated constant*) – Specifies the data type for pixels.
- `pixels` (*Buffer object*) – Specifies a pointer to the pixel data.

glEdgeFlag (flag) :

B{glEdgeFlag, glEdgeFlagv}

Flag edges as either boundary or non-boundary

See Also:

[OpenGL Docs](#)

Parameters `flag` (*Depends on function prototype*) – Specifies the current edge flag value. The initial value is GL_TRUE.

glEnable (cap) :

Enable server-side GL capabilities

See Also:

[OpenGL Docs](#)

Parameters `cap` (*Enumerated constant*) – Specifies a symbolic constant indicating a GL capability.

glEnd () :

Delimit the vertices of a primitive or group of like primitives

See Also:

[OpenGL Docs](#)

glEndList () :

Create or replace a display list

See Also:

[OpenGL Docs](#)

glEvalCoord (u, v) :

B{glEvalCoord1d, glEvalCoord1f, glEvalCoord2d, glEvalCoord2f, glEvalCoord1dv, glEvalCoord1fv, glEvalCoord2dv, glEvalCoord2fv}

Evaluate enabled one- and two-dimensional maps

See Also:

[OpenGL Docs](#)

Parameters

- `u` (*Depends on function prototype.*) – Specifies a value that is the domain coordinate u to the basis function defined in a previous glMap1 or glMap2 command. If the function prototype ends in ‘v’ then u specifies a pointer to an array containing either one or two domain coordinates. The first coordinate is u. The second coordinate is v, which is present only in glEvalCoord2 versions.
- `v` (*Depends on function prototype. (only with ‘2’ prototypes)*) – Specifies a value that is the domain coordinate v to the basis function defined in a previous glMap2 command. This argument is not present in a glEvalCoord1 command.

glEvalMesh (mode, i1, i2) :

B{glEvalMesh1 or glEvalMesh2}

Compute a one- or two-dimensional grid of points or lines

See Also:

[OpenGL Docs](#)

Parameters

- `mode` (*Enumerated constant*) – In glEvalMesh1, specifies whether to compute a one-dimensional mesh of points or lines.
- `i2 (i1,)` – Specify the first and last integer values for the grid domain variable i.

glEvalPoint (i, j) :
B{glEvalPoint1 and glEvalPoint2}

Generate and evaluate a single point in a mesh

See Also:

[OpenGL Docs](#)

Parameters

- **i** (*int*) – Specifies the integer value for grid domain variable i.
- **j** (*int (only with ‘2’ prototypes)*) – Specifies the integer value for grid domain variable j (glEvalPoint2 only).

glFeedbackBuffer (size, type, buffer) :

Controls feedback mode

See Also:

[OpenGL Docs](#)

Parameters

- **size** (*int*) – Specifies the maximum number of values that can be written into buffer.
- **type** (*Enumerated constant*) – Specifies a symbolic constant that describes the information that will be returned for each vertex.
- **buffer** (*Buffer object* I{GL_FLOAT}) – Returns the feedback data.

glFinish () :

Block until all GL execution is complete

See Also:

[OpenGL Docs](#)

glFlush () :

Force Execution of GL commands in finite time

See Also:

[OpenGL Docs](#)

glFog (pname, param) :
B{glFogf, glFogi, glFogfv, glFogiv}

Specify fog parameters

See Also:

[OpenGL Docs](#)

Parameters

- **pname** (*Enumerated constant*) – Specifies a single-valued fog parameter. If the function prototype ends in ‘v’ specifies a fog parameter.
- **param** (*Depends on function prototype.*) – Specifies the value or values to be assigned to pname. GL_FOG_COLOR requires an array of four values. All other parameters accept an array containing only a single value.

glFrontFace (mode) :

Define front- and back-facing polygons

See Also:

[OpenGL Docs](#)

Parameters mode (*Enumerated constant*) – Specifies the orientation of front-facing polygons.

glFrustum(left, right, bottom, top, zNear, zFar) :

Multiply the current matrix by a perspective matrix

See Also:

[OpenGL Docs](#)

Parameters

- **right** (*left*,) – Specify the coordinates for the left and right vertical clipping planes.
- **bottom** (*top*,) – Specify the coordinates for the bottom and top horizontal clipping planes.
- **zFar** (*zNear*,) – Specify the distances to the near and far depth clipping planes. Both distances must be positive.

glGenLists (range) :

Generate a contiguous set of empty display lists

See Also:

[OpenGL Docs](#)

Parameters range (*int*) – Specifies the number of contiguous empty display lists to be generated.

glGenTextures (n, textures) :

Generate texture names

See Also:

[OpenGL Docs](#)

Parameters

- **n** (*int*) – Specifies the number of textures name to be generated.
- **textures** (*Buffer object I{type GL_INT}*) – Specifies an array in which the generated textures names are stored.

glGet (pname, param) :

B{glGetBooleanv, glGetfloatv, glGetFloatv, glGetIntegerv}

Return the value or values of a selected parameter

See Also:

[OpenGL Docs](#)

Parameters

- **pname** (*Enumerated constant*) – Specifies the parameter value to be returned.
- **param** (*Depends on function prototype.*) – Returns the value or values of the specified parameter.

glGetClipPlane (plane, equation) :

Return the coefficients of the specified clipping plane

See Also:

[OpenGL Docs](#)

Parameters

- **plane** (*Enumerated constant*) – Specifies a clipping plane. The number of clipping planes depends on the implementation, but at least six clipping planes are supported. They are identified by symbolic names of the form GL_CLIP_PLANE*i* where $0 < i < \text{GL_MAX_CLIP_PLANES}$.
- **equation** (*Buffer object* I{type GL_FLOAT}) – Returns four float (double)-precision values that are the coefficients of the plane equation of plane in eye coordinates. The initial value is (0, 0, 0, 0).

glGetError () :

Return error information

See Also:

[OpenGL Docs](#)

glGetLight (light, pname, params) :

B{glGetLightfv and glGetLightiv}

Return light source parameter values

See Also:

[OpenGL Docs](#)

Parameters

- **light** (*Enumerated constant*) – Specifies a light source. The number of possible lights depends on the implementation, but at least eight lights are supported. They are identified by symbolic names of the form GL_LIGHT*i* where $0 < i < \text{GL_MAX_LIGHTS}$.
- **pname** (*Enumerated constant*) – Specifies a light source parameter for light.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetMap (target, query, v) :

B{glGetMapdv, glGetMapfv, glGetMapiv}

Return evaluator parameters

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the symbolic name of a map.
- **query** (*Enumerated constant*) – Specifies which parameter to return.
- **v** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetMaterial (face, pname, params) :

B{glGetMaterialfv, glGetMaterialiv}

Return material parameters

See Also:

[OpenGL Docs](#)

Parameters

- **face** (*Enumerated constant*) – Specifies which of the two materials is being queried. representing the front and back materials, respectively.
- **pname** (*Enumerated constant*) – Specifies the material parameter to return.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetPixelMap (map, values) :

B{glGetPixelMapfv, glGetPixelMapuiv, glGetPixelMapusv}

Return the specified pixel map

See Also:

[OpenGL Docs](#)

Parameters

- **map** (*Enumerated constant*) – Specifies the name of the pixel map to return.
- **values** (*Buffer object*. Depends on function prototype.) – Returns the pixel map contents.

glGetPolygonStipple (mask) :

Return the polygon stipple pattern

See Also:

[OpenGL Docs](#)

Parameters **mask** (*Buffer object* I{type GL_BYTE}) – Returns the stipple pattern. The initial value is all 1's.

glGetString (name) :

Return a string describing the current GL connection

See Also:

[OpenGL Docs](#)

Parameters **name** (*Enumerated constant*) – Specifies a symbolic constant.

glGetTexEnv (target, pname, params) :

B{glGetTexEnvfv, glGetTexEnviv}

Return texture environment parameters

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies a texture environment. Must be GL_TEXTURE_ENV.
- **pname** (*Enumerated constant*) – Specifies the symbolic name of a texture environment parameter.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetTexGen (coord, pname, params) :
B{glGetTexGendv, glGetTexGenfv, glGetTexGeniv}

Return texture coordinate generation parameters

See Also:

[OpenGL Docs](#)

Parameters

- **coord** (*Enumerated constant*) – Specifies a texture coordinate.
- **pname** (*Enumerated constant*) – Specifies the symbolic name of the value(s) to be returned.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetTexImage(target, level, format, type, pixels) :

Return a texture image

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies which texture is to be obtained.
- **level** (*int*) – Specifies the level-of-detail number of the desired image. Level 0 is the base image level. Level n is the nth mipmap reduction image.
- **format** (*Enumerated constant*) – Specifies a pixel format for the returned data.
- **type** (*Enumerated constant*) – Specifies a pixel type for the returned data.
- **pixels** (*Buffer object*.) – Returns the texture image. Should be a pointer to an array of the type specified by type

glGetTexLevelParameter (target, level, pname, params) :

B{glGetTexLevelParameterfv, glGetTexLevelParameteriv}

return texture parameter values for a specific level of detail

See Also:

[U{opengl.org/developers/documentation/man_pages/hardcopy/GL/html/gl/gettexlevelparameter.html}](https://opengl.org/developers/documentation/man_pages/hardcopy/GL/html/gl/gettexlevelparameter.html)

Parameters

- **target** (*Enumerated constant*) – Specifies the symbolic name of the target texture.
- **level** (*int*) – Specifies the level-of-detail number of the desired image. Level 0 is the base image level. Level n is the nth mipmap reduction image.
- **pname** (*Enumerated constant*) – Specifies the symbolic name of a texture parameter.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the requested data.

glGetTexParameter (target, pname, params) :

B{glGetTexParameterfv, glGetTexParameteriv}

Return texture parameter values

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the symbolic name of the target texture.
- **pname** (*Enumerated constant*) – Specifies the symbolic name the target texture.
- **params** (*Buffer object*. Depends on function prototype.) – Returns the texture parameters.

glHint (target, mode) :

Specify implementation-specific hints

See Also:[OpenGL Docs](#)**Parameters**

- **target** (*Enumerated constant*) – Specifies a symbolic constant indicating the behavior to be controlled.
- **mode** (*Enumerated constant*) – Specifies a symbolic constant indicating the desired behavior.

glIndex (c) :

B{glIndexd, glIndexf, glIndexi, glIndexes, glIndexdv, glIndexfv, glIndexiv, glIndexsv}

Set the current color index

See Also:[OpenGL Docs](#)**Parameters** **c** (*Buffer object*. Depends on function prototype.) – Specifies a pointer to a one element array that contains the new value for the current color index.**glInitNames () :**

Initialize the name stack

See Also:[OpenGL Docs](#)**glIsEnabled (cap) :**

Test whether a capability is enabled

See Also:[OpenGL Docs](#)**Parameters** **cap** (*Enumerated constant*) – Specifies a constant representing a GL capability.**glIsList (list) :**

Determine if a name corresponds to a display-list

See Also:[OpenGL Docs](#)**Parameters** **list** (*unsigned int*) – Specifies a potential display-list name.**glIsTexture (texture) :**

Determine if a name corresponds to a texture

See Also:

[OpenGL Docs](#)

Parameters **texture** (*unsigned int*) – Specifies a value that may be the name of a texture.

glLight (light, pname, param) :
B{glLightf, glLighti, glLightfv, glLightiv}

Set the light source parameters

See Also:

[OpenGL Docs](#)

Parameters

- **light** (*Enumerated constant*) – Specifies a light. The number of lights depends on the implementation, but at least eight lights are supported. They are identified by symbolic names of the form GL_LIGHT*i* where 0 < i < GL_MAX_LIGHTS.
- **pname** (*Enumerated constant*) – Specifies a single-valued light source parameter for light.
- **param** (*Depends on function prototype.*) – Specifies the value that parameter pname of light source light will be set to. If function prototype ends in ‘v’ specifies a pointer to the value or values that parameter pname of light source light will be set to.

glLightModel (pname, param) :
B{glLightModelf, glLightModeli, glLightModelfv, glLightModeliv}

Set the lighting model parameters

See Also:

[OpenGL Docs](#)

Parameters

- **pname** (*Enumerated constant*) – Specifies a single-value light model parameter.
- **param** (*Depends on function prototype.*) – Specifies the value that param will be set to. If function prototype ends in ‘v’ specifies a pointer to the value or values that param will be set to.

glLineStipple (factor, pattern) :
Specify the line stipple pattern

See Also:

[OpenGL Docs](#)

Parameters

- **factor** (*int*) – Specifies a multiplier for each bit in the line stipple pattern. If factor is 3, for example, each bit in the pattern is used three times before the next bit in the pattern is used. factor is clamped to the range [1, 256] and defaults to 1.
- **pattern** (*unsigned short int*) – Specifies a 16-bit integer whose bit pattern determines which fragments of a line will be drawn when the line is rasterized. Bit zero is used first; the default pattern is all 1’s.

glLineWidth (width) :
Specify the width of rasterized lines.

See Also:

[OpenGL Docs](#)

Parameters **width** (*float*) – Specifies the width of rasterized lines. The initial value is 1.

glListBase (base) :

Set the display-list base for glCallLists

See Also:

[OpenGL Docs](#)

Parameters **base** (*unsigned int*) – Specifies an integer offset that will be added to glCallLists offsets to generate display-list names. The initial value is 0.

glLoadIdentity () :

Replace the current matrix with the identity matrix

See Also:

[OpenGL Docs](#)

glLoadMatrix (m) :

B{glLoadMatrixd, glLoadMatixf}

Replace the current matrix with the specified matrix

See Also:

[OpenGL Docs](#)

Parameters **m** (Buffer object. Depends on function prototype.) – Specifies a pointer to 16 consecutive values, which are used as the elements of a 4x4 column-major matrix.

glLoadName (name) :

Load a name onto the name stack.

See Also:

[OpenGL Docs](#)

Parameters **name** (*unsigned int*) – Specifies a name that will replace the top value on the name stack.

glLogicOp (opcode) :

Specify a logical pixel operation for color index rendering

See Also:

[OpenGL Docs](#)

Parameters **opcode** (*Enumerated constant*) – Specifies a symbolic constant that selects a logical operation.

glMap1 (target, u1, u2, stride, order, points) :

B{glMap1d, glMap1f}

Define a one-dimensional evaluator

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the kind of values that are generated by the evaluator.
- **u1,u2** – Specify a linear mapping of u, as presented to glEvalCoord1, to ^, the variable that is evaluated by the equations specified by this command.
- **stride** (*int*) – Specifies the number of floats or float (double)s between the beginning of one control point and the beginning of the next one in the data structure referenced in points. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations.
- **order** (*int*) – Specifies the number of control points. Must be positive.
- **points** (*Buffer object*. Depends on function prototype.) – Specifies a pointer to the array of control points.

glMap2 (**target**, **u1**, **u2**, **ustride**, **uorder**, **v1**, **v2**, **vstride**, **vorder**, **points**):
B{glMap2d, glMap2f}

Define a two-dimensional evaluator

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the kind of values that are generated by the evaluator.
- **u1,u2** – Specify a linear mapping of u, as presented to glEvalCoord2, to ^, the variable that is evaluated by the equations specified by this command. Initially u1 is 0 and u2 is 1.
- **ustride** (*int*) – Specifies the number of floats or float (double)s between the beginning of control point R and the beginning of control point R ij, where i and j are the u and v control point indices, respectively. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations. The initial value of ustride is 0.
- **uorder** (*int*) – Specifies the dimension of the control point array in the u axis. Must be positive. The initial value is 1.
- **v2** (*v1*) – Specify a linear mapping of v, as presented to glEvalCoord2, to ^, one of the two variables that are evaluated by the equations specified by this command. Initially, v1 is 0 and v2 is 1.
- **vstride** (*int*) – Specifies the number of floats or float (double)s between the beginning of control point R and the beginning of control point R ij, where i and j are the u and v control point(indices, respectively. This allows control points to be embedded in arbitrary data structures. The only constraint is that the values for a particular control point must occupy contiguous memory locations. The initial value of vstride is 0.
- **vorder** (*int*) – Specifies the dimension of the control point array in the v axis. Must be positive. The initial value is 1.
- **points** (*Buffer object*. Depends on function prototype.) – Specifies a pointer to the array of control points.

glMapGrid (**un**, **u1,u2**, **vn**, **v1**, **v2**):
B{glMapGrid1d, glMapGrid1f, glMapGrid2d, glMapGrid2f}

Define a one- or two-dimensional mesh

See Also:

[OpenGL Docs](#)

Parameters

- **un** (*int*) – Specifies the number of partitions in the grid range interval [u1, u2]. Must be positive.
- **u2** (*u1*,) – Specify the mappings for integer grid domain values i=0 and i=un.
- **vn** (*int*) – Specifies the number of partitions in the grid range interval [v1, v2] (glMapGrid2 only).
- **v2** (*v1*,) – Specify the mappings for integer grid domain values j=0 and j=vn (glMapGrid2 only).

glMaterial (face, pname, params) :

Specify material parameters for the lighting model.

See Also:

[OpenGL Docs](#)

Parameters

- **face** (*Enumerated constant*) – Specifies which face or faces are being updated. Must be one of:
- **pname** (*Enumerated constant*) – Specifies the single-valued material parameter of the face or faces that is being updated. Must be GL_SHININESS.
- **params** (*int*) – Specifies the value that parameter GL_SHININESS will be set to. If function prototype ends in ‘v’ specifies a pointer to the value or values that pname will be set to.

glMatrixMode (mode) :

Specify which matrix is the current matrix.

See Also:

[OpenGL Docs](#)

Parameters mode (*Enumerated constant*) – Specifies which matrix stack is the target for subsequent matrix operations.

glMultMatrix (m) :

B{glMultMatrixd, glMultMatrixf}

Multiply the current matrix with the specified matrix

See Also:

[OpenGL Docs](#)

Parameters m (*Buffer object*. Depends on function prototype.) – Points to 16 consecutive values that are used as the elements of a 4x4 column major matrix.

glNewList (list, mode) :

Create or replace a display list

See Also:

[OpenGL Docs](#)

Parameters

- **list** (*unsigned int*) – Specifies the display list name
- **mode** (*Enumerated constant*) – Specifies the compilation mode.

glNormal3 (nx, ny, nz, v) :

B{Normal3b, Normal3bv, Normal3d, Normal3dv, Normal3f, Normal3fv, Normal3i, Normal3iv, Normal3s, Normal3sv}

Set the current normal vector

See Also:

[OpenGL Docs](#)

Parameters

- **ny, nz (nx,)** – Specify the x, y, and z coordinates of the new current normal. The initial value of the current normal is the unit vector, (0, 0, 1).
- **v** (Buffer object. Depends on function prototype. ('v' prototypes)) – Specifies a pointer to an array of three elements: the x, y, and z coordinates of the new current normal.

glOrtho(left, right, bottom, top, zNear, zFar) :

Multiply the current matrix with an orthographic matrix

See Also:

[OpenGL Docs](#)

Parameters

- **right (left,)** – Specify the coordinates for the left and right vertical clipping planes.
- **top (bottom,)** – Specify the coordinates for the bottom and top horizontal clipping planes.
- **zFar (zNear,)** – Specify the distances to the nearer and farther depth clipping planes. These values are negative if the plane is to be behind the viewer.

glPassThrough (token) :

Place a marker in the feedback buffer

See Also:

[OpenGL Docs](#)

Parameters token (float) – Specifies a marker value to be placed in the feedback buffer following a GL_PASS_THROUGH_TOKEN.

glPixelMap (map, mapsize, values) :

B{glPixelMapfv, glPixelMapuiv, glPixelMapusv}

Set up pixel transfer maps

See Also:

[OpenGL Docs](#)

Parameters

- **map** (*Enumerated constant*) – Specifies a symbolic map name.
- **mapsize (int)** – Specifies the size of the map being defined.

- **values** (`Buffer` object. Depends on function prototype.) – Specifies an array of mapsize values.

glPixelStore (pname, param) :
B{`glPixelStoref`, `glPixelStorei`}

Set pixel storage modes

See Also:

[OpenGL Docs](#)

Parameters

- **pname** (*Enumerated constant*) – Specifies the symbolic name of the parameter to be set. Six values affect the packing of pixel data into memory. Six more affect the unpacking of pixel data from memory.
- **param** (*Depends on function prototype.*) – Specifies the value that `pname` is set to.

glPixelTransfer (pname, param) :
B{`glPixelTransferf`, `glPixelTransferi`}

Set pixel transfer modes

See Also:

[OpenGL Docs](#)

Parameters

- **pname** (*Enumerated constant*) – Specifies the symbolic name of the pixel transfer parameter to be set.
- **param** (*Depends on function prototype.*) – Specifies the value that `pname` is set to.

glPixelZoom(xfactor, yfactor) :
Specify the pixel zoom factors

See Also:

[OpenGL Docs](#)

Parameters `yfactor` (*xfactor*) – Specify the x and y zoom factors for pixel write operations.

glPointSize(size) :
Specify the diameter of rasterized points

See Also:

[OpenGL Docs](#)

Parameters `size` (*float*) – Specifies the diameter of rasterized points. The initial value is 1.

glPolygonMode(face, mode) :
Select a polygon rasterization mode

See Also:

[OpenGL Docs](#)

Parameters

- **face** (*Enumerated constant*) – Specifies the polygons that mode applies to. Must be GL_FRONT for front-facing polygons, GL_BACK for back-facing polygons, or GL_FRONT_AND_BACK for front- and back-facing polygons.
- **mode** (*Enumerated constant*) – Specifies how polygons will be rasterized. The initial value is GL_FILL for both front- and back-facing polygons.

glPolygonOffset (factor, units) :

Set the scale and units used to calculate depth values

See Also:

[OpenGL Docs](#)

Parameters

- **factor** (*float*) – Specifies a scale factor that is used to create a variable depth offset for each polygon. The initial value is 0.
- **units** (*float*) – Is multiplied by an implementation-specific value to create a constant depth offset. The initial value is 0.

glPolygonStipple (mask) :

Set the polygon stippling pattern

See Also:

[OpenGL Docs](#)

Parameters **mask** (*Buffer object* I{type GL_BYTE}) – Specifies a pointer to a 32x32 stipple pattern that will be unpacked from memory in the same way that glDrawPixels unpacks pixels.

glPopAttrib () :

Pop the server attribute stack

See Also:

[OpenGL Docs](#)

glPopClientAttrib () :

Pop the client attribute stack

See Also:

[OpenGL Docs](#)

glPopMatrix () :

Pop the current matrix stack

See Also:

[OpenGL Docs](#)

glPopName () :

Pop the name stack

See Also:

[OpenGL Docs](#)

glPrioritizeTextures (n, textures, priorities) :

Set texture residence priority

See Also:

[OpenGL Docs](#)

Parameters

- **n** (*int*) – Specifies the number of textures to be prioritized.
- **textures** (*Buffer I{type GL_INT}*) – Specifies an array containing the names of the textures to be prioritized.
- **priorities** (*Buffer I{type GL_FLOAT}*) – Specifies an array containing the texture priorities. A priority given in an element of priorities applies to the texture named by the corresponding element of textures.

glPushAttrib(mask**) :**

Push the server attribute stack

See Also:

[OpenGL Docs](#)

Parameters **mask** (*Enumerated constant(s)*) – Specifies a mask that indicates which attributes to save.

glPushClientAttrib(mask**) :**

Push the client attribute stack

See Also:

[OpenGL Docs](#)

Parameters **mask** (*Enumerated constant(s)*) – Specifies a mask that indicates which attributes to save.

glPushMatrix() :

Push the current matrix stack

See Also:

[OpenGL Docs](#)

glPushName(name**) :**

Push the name stack

See Also:

[OpenGL Docs](#)

Parameters **name** (*unsigned int*) – Specifies a name that will be pushed onto the name stack.

glRasterPos (x, y, z, w**) :**

B{glRasterPos2d, glRasterPos2f, glRasterPos2i, glRasterPos2s, glRasterPos3d, glRasterPos3f, glRasterPos3i, glRasterPos3s, glRasterPos4d, glRasterPos4f, glRasterPos4i, glRasterPos4s, glRasterPos2dv, glRasterPos2fv, glRasterPos2iv, glRasterPos2sv, glRasterPos3dv, glRasterPos3fv, glRasterPos3iv, glRasterPos3sv, glRasterPos4dv, glRasterPos4fv, glRasterPos4iv, glRasterPos4sv}

Specify the raster position for pixel operations

See Also:

[OpenGL Docs](#)

Parameters **y, z, w** (*x,*) – Specify the x,y,z, and w object coordinates (if present) for the raster position. If function prototype ends in ‘v’ specifies a pointer to an array of two, three, or four elements, specifying x, y, z, and w coordinates, respectively.

Note: If you are drawing to the 3d view with a Scriptlink of a space handler the zoom level of the panels will scale the glRasterPos by the view matrix. so a X of 10 will not always offset 10 pixels as you would expect.

To work around this get the scale value of the view matrix and use it to scale your pixel values.

```
import Blender
from Blender.BGL import *
xval, yval= 100, 40
# Get the scale of the view matrix
viewMatrix = Buffer(GL_FLOAT, 16)
glGetFloatv(GL_MODELVIEW_MATRIX, viewMatrix)
f = 1/viewMatrix[0]
glRasterPos2f(xval*f, yval*f) # Instead of the usual glRasterPos2i(xval, yval)
```

glReadBuffer(mode):

Select a color buffer source for pixels.

See Also:

[OpenGL Docs](#)

Parameters **mode** (*Enumerated constant*) – Specifies a color buffer.

glReadPixels(x, y, width, height, format, type, pixels):

Read a block of pixels from the frame buffer

See Also:

[OpenGL Docs](#)

Parameters

- **y** (x,) – Specify the window coordinates of the first pixel that is read from the frame buffer. This location is the lower left corner of a rectangular block of pixels.
- **height** (width,) – Specify the dimensions of the pixel rectangle. width and height of one correspond to a single pixel.
- **format** (*Enumerated constant*) – Specifies the format of the pixel data.
- **type** (*Enumerated constant*) – Specifies the data type of the pixel data.
- **pixels** (Buffer object) – Returns the pixel data.

glRect (x1,y1,x2,y2,v1,v2):

B{glRectd, glRectf, glRecti, glRects, glRectdv, glRectfv, glRectiv, glRectsv}

Draw a rectangle

See Also:

[OpenGL Docs](#)

Parameters

- **y1** (x1,) – Specify one vertex of a rectangle
- **y2** (x2,) – Specify the opposite vertex of the rectangle
- **v2** (v1,) – Specifies a pointer to one vertex of a rectangle and the pointer to the opposite vertex of the rectangle

glRenderMode (mode) :

Set rasterization mode

See Also:

[OpenGL Docs](#)

Parameters **mode** (*Enumerated constant*) – Specifies the rasterization mode.

glRotate (angle, x, y, z) :

B{glRotated, glRotatef}

Multiply the current matrix by a rotation matrix

See Also:

[OpenGL Docs](#)

Parameters

- **angle** (*Depends on function prototype.*) – Specifies the angle of rotation in degrees.
- **y, z (x,)** – Specify the x, y, and z coordinates of a vector respectively.

glScale (x, y, z) :

B{glScaled, glScalef}

Multiply the current matrix by a general scaling matrix

See Also:

[OpenGL Docs](#)

Parameters **y, z (x,)** – Specify scale factors along the x, y, and z axes, respectively.

glScissor(x, y, width, height) :

Define the scissor box

See Also:

[OpenGL Docs](#)

Parameters

- **y (x,)** – Specify the lower left corner of the scissor box. Initially (0, 0).
- **height (width)** – Specify the width and height of the scissor box. When a GL context is first attached to a window, width and height are set to the dimensions of that window.

glSelectBuffer(size, buffer) :

Establish a buffer for selection mode values

See Also:

[OpenGL Docs](#)

Parameters

- **size (int)** – Specifies the size of buffer
- **buffer (Buffer I{type GL_INT})** – Returns the selection data

glShadeModel (mode) :

Select flat or smooth shading

See Also:

[OpenGL Docs](#)

Parameters mode (*Enumerated constant*) – Specifies a symbolic value representing a shading technique.

glStencilFunc (func, ref, mask) :

Set function and reference value for stencil testing

See Also:

[OpenGL Docs](#)

Parameters

- **func** (*Enumerated constant*) – Specifies the test function.
- **ref** (*int*) – Specifies the reference value for the stencil test. ref is clamped to the range [0,2n-1], where n is the number of bitplanes in the stencil buffer. The initial value is 0.
- **mask** (*unsigned int*) – Specifies a mask that is ANDed with both the reference value and the stored stencil value when the test is done. The initial value is all 1's.

glStencilMask (mask) :

Control the writing of individual bits in the stencil planes

See Also:

[OpenGL Docs](#)

Parameters mask (*unsigned int*) – Specifies a bit mask to enable and disable writing of individual bits in the stencil planes. Initially, the mask is all 1's.

glStencilOp (fail, zfail, zpass) :

Set stencil test actions

See Also:

[OpenGL Docs](#)

Parameters

- **fail** (*Enumerated constant*) – Specifies the action to take when the stencil test fails. The initial value is GL_KEEP.
- **zfail** (*Enumerated constant*) – Specifies the stencil action when the stencil test passes, but the depth test fails. zfail accepts the same symbolic constants as fail. The initial value is GL_KEEP.
- **zpass** (*Enumerated constant*) – Specifies the stencil action when both the stencil test and the depth test pass, or when the stencil test passes and either there is no depth buffer or depth testing is not enabled. zpass accepts the same symbolic constants as fail. The initial value is GL_KEEP.

glTexCoord (s, t, r, q, v) :

B{glTexCoord1d, glTexCoord1f, glTexCoord1i, glTexCoord1s, glTexCoord2d, glTexCoord2f, glTexCoord2i, glTexCoord2s, glTexCoord3d, glTexCoord3f, glTexCoord3i, glTexCoord3s, glTexCoord4d, glTexCoord4f, glTexCoord4i, glTexCoord4s, glTexCoord1dv, glTexCoord1fv, glTexCoord1iv, glTexCoord1sv, glTexCoord2dv,

glTexCoord2fv, glTexCoord2iv, glTexCoord2sv, glTexCoord3dv, glTexCoord3fv, glTexCoord3iv, glTexCoord3sv, glTexCoord4dv, glTexCoord4fv, glTexCoord4iv, glTexCoord4sv}

Set the current texture coordinates

See Also:

[OpenGL Docs](#)

Parameters

- **t, r, q (s,)** – Specify s, t, r, and q texture coordinates. Not all parameters are present in all forms of the command.
- **v (Buffer object)**. Depends on function prototype. (for ‘v’ prototypes only) – Specifies a pointer to an array of one, two, three, or four elements, which in turn specify the s, t, r, and q texture coordinates.

glTexEnv (target, pname, param) :

B{glTextEnvf, glTextEnvi, glTextEnvfv, glTextEnviv}

Set texture environment parameters

See Also:

[OpenGL Docs](#)

Parameters

- **target (Enumerated constant)** – Specifies a texture environment. Must be GL_TEXTURE_ENV.
- **pname (Enumerated constant)** – Specifies the symbolic name of a single-valued texture environment parameter. Must be GL_TEXTURE_ENV_MODE.
- **param (Depends on function prototype.)** – Specifies a single symbolic constant. If function prototype ends in ‘v’ specifies a pointer to a parameter array that contains either a single symbolic constant or an RGBA color

glTexGen (coord, pname, param) :

B{glTexGend, glTexGenf, glTexGeni, glTexGendv, glTexGenfv, glTexGeniv}

Control the generation of texture coordinates

See Also:

[OpenGL Docs](#)

Parameters

- **coord (Enumerated constant)** – Specifies a texture coordinate.
- **pname (Enumerated constant)** – Specifies the symbolic name of the texture- coordinate generation function.
- **param (Depends on function prototype.)** – Specifies a single-valued texture generation parameter. If function prototype ends in ‘v’ specifies a pointer to an array of texture generation parameters. If pname is GL_TEXTURE_GEN_MODE, then the array must contain a single symbolic constant. Otherwise, params holds the coefficients for the texture-coordinate generation function specified by pname.

glTexImage1D(target, level, internalformat, width, border, format, type, pixels) :

Specify a one-dimensional texture image

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the target texture.
- **level** (*int*) – Specifies the level-of-detail number. Level 0 is the base image level. Level n is the nth mipmap reduction image.
- **internalformat** (*int*) – Specifies the number of color components in the texture.
- **width** (*int*) – Specifies the width of the texture image. Must be $2n+2(\text{border})$ for some integer n. All implementations support texture images that are at least 64 texels wide. The height of the 1D texture image is 1.
- **border** (*int*) – Specifies the width of the border. Must be either 0 or 1.
- **format** (*Enumerated constant*) – Specifies the format of the pixel data.
- **type** (*Enumerated constant*) – Specifies the data type of the pixel data.
- **pixels** (*Buffer object*) – Specifies a pointer to the image data in memory.

glTexImage2D(target, level, internalformat, width, height, border, format, type, pixels):
Specify a two-dimensional texture image

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the target texture.
- **level** (*int*) – Specifies the level-of-detail number. Level 0 is the base image level. Level n is the nth mipmap reduction image.
- **internalformat** (*int*) – Specifies the number of color components in the texture.
- **width** (*int*) – Specifies the width of the texture image. Must be $2n+2(\text{border})$ for some integer n. All implementations support texture images that are at least 64 texels wide.
- **height** (*int*) – Specifies the height of the texture image. Must be $2m+2(\text{border})$ for some integer m. All implementations support texture images that are at least 64 texels high.
- **border** (*int*) – Specifies the width of the border. Must be either 0 or 1.
- **format** (*Enumerated constant*) – Specifies the format of the pixel data.
- **type** (*Enumerated constant*) – Specifies the data type of the pixel data.
- **pixels** (*Buffer object*) – Specifies a pointer to the image data in memory.

glTexParameter (target, pname, param):
B{glTexParameterf, glTexParameteri, glTexParameterfv, glTexParameteriv}

Set texture parameters

See Also:

[OpenGL Docs](#)

Parameters

- **target** (*Enumerated constant*) – Specifies the target texture.

- **pname** (*Enumerated constant*) – Specifies the symbolic name of a single-valued texture parameter.
- **param** (*Depends on function prototype.*) – Specifies the value of pname. If function prototype ends in ‘v’ specifies a pointer to an array where the value or values of pname are stored.

glTranslate (x, y, z) :
B{glTranslatef, glTranslated}

Multiply the current matrix by a translation matrix

See Also:

[OpenGL Docs](#)

Parameters **y, z** (x,) – Specify the x, y, and z coordinates of a translation vector.

glVertex (x, y, z, w, v) :

B{glVertex2d, glVertex2f, glVertex2i, glVertex2s, glVertex3d, glVertex3f, glVertex3i, glVertex3s, glVertex4d, glVertex4f, glVertex4i, glVertex4s, glVertex2dv, glVertex2fv, glVertex2iv, glVertex2sv, glVertex3dv, glVertex3fv, glVertex3iv, glVertex3sv, glVertex4dv, glVertex4fv, glVertex4iv, glVertex4sv}

Specify a vertex

See Also:

[OpenGL Docs](#)

Parameters

- **y, z, w** (x,) – Specify x, y, z, and w coordinates of a vertex. Not all parameters are present in all forms of the command.
- **v** (Buffer object. Depends of function prototype (for ‘v’ prototypes only)) – Specifies a pointer to an array of two, three, or four elements. The elements of a two-element array are x and y; of a three-element array, x, y, and z; and of a four-element array, x, y, z, and w.

glViewport (x, y, width, height) :

Set the viewport

See Also:

[OpenGL Docs](#)

Parameters

- **y** (x,) – Specify the lower left corner of the viewport rectangle, in pixels. The initial value is (0,0).
- **height** (width,) – Specify the width and height of the viewport. When a GL context is first attached to a window, width and height are set to the dimensions of that window.

gluPerspective (fovY, aspect, zNear, zFar) :

Set up a perspective projection matrix.

See Also:

[U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}](http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch)

Parameters

- **fovY** (*double*) – Specifies the field of view angle, in degrees, in the y direction.

- **aspect** (*double*) – Specifies the aspect ratio that determines the field of view in the x direction. The aspect ratio is the ratio of x (width) to y (height).
- **zNear** (*double*) – Specifies the distance from the viewer to the near clipping plane (always positive).
- **zFar** (*double*) – Specifies the distance from the viewer to the far clipping plane (always positive).

gluLookAt (*eyex*, *eyey*, *eyez*, *centerx*, *centery*, *centerz*, *upx*, *upy*, *upz*):

Define a viewing transformation.

See Also:

U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}

Parameters

- **eyey**, **eyez** (*eyex*,) – Specifies the position of the eye point.
- **centery**, **centerz** (*centerx*,) – Specifies the position of the reference point.
- **upy**, **upz** (*upx*,) – Specifies the direction of the up vector.

gluOrtho2D (*left*, *right*, *bottom*, *top*):

Define a 2-D orthographic projection matrix.

See Also:

U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}

Parameters

- **right** (*left*,) – Specify the coordinates for the left and right vertical clipping planes.
- **top** (*bottom*,) – Specify the coordinates for the bottom and top horizontal clipping planes.

gluPickMatrix (*x*, *y*, *width*, *height*, *viewport*):

Define a picking region.

See Also:

U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}

Parameters

- **y** (*x*,) – Specify the center of a picking region in window coordinates.
- **height** (*width*,) – Specify the width and height, respectively, of the picking region in window coordinates.
- **viewport** (Buffer object. [int]) – Specifies the current viewport.

gluProject (*objx*, *objy*, *objz*, *modelMatrix*, *projMatrix*, *viewport*, *winx*, *winy*, *winz*):

Map object coordinates to window coordinates.

See Also:

U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}

Parameters

- **objy**, **objz** (*objx*,) – Specify the object coordinates.
- **modelMatrix** (Buffer object. [double]) – Specifies the current modelview matrix (as from a glGetDoublev call).

- **projMatrix** (Buffer object. [double]) – Specifies the current projection matrix (as from a glGetDoublev call).
- **viewport** (Buffer object. [int]) – Specifies the current viewport (as from a glGetIntegerv call).
- **winy, winz** (winx,) – Return the computed window coordinates.

gluUnProject (winx, winy, winz, modelMatrix, projMatrix, viewport, objx, objy, objz) :
Map object coordinates to window coordinates.

See Also:

U{http://biology.ncsa.uiuc.edu/cgi-bin/infosrch.cgi?cmd=getdoc&coll=0650&db=bks&fname=/SGI_Developer/OpenGL_RM/ch}

Parameters

- **winy, winz** (winx,) – Specify the window coordinates to be mapped.
- **modelMatrix** (Buffer object. [double]) – Specifies the current modelview matrix (as from a glGetDoublev call).
- **projMatrix** (Buffer object. [double]) – Specifies the current projection matrix (as from a glGetDoublev call).
- **viewport** (Buffer object. [int]) – Specifies the current viewport (as from a glGetIntegerv call).
- **objy, objz** (objx,) – Return the computed object coordinates.

class Buffer:

The Buffer object is simply a block of memory that is delineated and initialized by the user. Many OpenGL functions return data to a C-style pointer, however, because this is not possible in python the Buffer object can be used to this end. Wherever pointer notation is used in the OpenGL functions the Buffer object can be used in it's BGL wrapper. In some instances the Buffer object will need to be initialized with the template parameter, while in other instances the user will want to create just a blank buffer which will be zeroed by default.

Example with Buffer:: import Blender from Blender import BGL myByteBuffer = BGL.Buffer(BGL.GL_BYTE, [32,32]) BGL.glGetPolygonStipple(myByteBuffer) print myByteBuffer.dimensions print myByteBuffer.list sliceBuffer = myByteBuffer[0:16] print sliceBuffer

bgl.list

The contents of the Buffer.

bgl.dimensions

The size of the Buffer.

__init__(type, dimensions, template = None) :

This will create a new Buffer object for use with other BGL OpenGL commands. Only the type of argument to store in the buffer and the dimensions of the buffer are necessary. Buffers are zeroed by default unless a template is supplied, in which case the buffer is initialized to the template.

Parameters

- **type** (int) – The format to store data in. The type should be one of GL_BYTE, GL_SHORT, GL_INT, or GL_FLOAT.
- **dimensions** (An int or sequence object specifying the dimensions of the buffer.) – If the dimensions are specified as an int a linear array will be created for the buffer. If a sequence is passed for the dimensions, the buffer becomes n-Dimensional, where n is equal to the number of parameters passed in the sequence. Example: [256,2]

is a two-dimensional buffer while [256,256,4] creates a three-dimensional buffer. You can think of each additional dimension as a sub-item of the dimension to the left. i.e. [10,2] is a 10 element array each with 2 sub-items. [(0,0), (0,1), (1,0), (1,1), (2,0), ...] etc.

- **template** (*A python sequence object (optional)*) – A sequence of matching dimensions which will be used to initialize the Buffer. If a template is not passed in all fields will be initialized to 0.

Return type Buffer object

Returns The newly created buffer as a PyObject.

3.4 Font Drawing (blf)

This module provides access to blenders text drawing functions.

`blf.CLIPPING`

constant value 2

`blf.KERNING_DEFAULT`

constant value 8

`blf.ROTATION`

constant value 1

`blf.SHADOW`

constant value 4

`blf.aspect (fontid, aspect)`

Set the aspect for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **aspect** (*float*) – The aspect ratio for text drawing to use.

`blf.blur (fontid, radius)`

Set the blur radius for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **radius** (*int*) – The radius for blurring text (in pixels).

`blf.clipping (fontid, xmin, ymin, xmax, ymax)`

Set the clipping, enable/disable using CLIPPING.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **xmin** (*float*) – Clip the drawing area by these bounds.
- **ymin** (*float*) – Clip the drawing area by these bounds.
- **xmax** (*float*) – Clip the drawing area by these bounds.
- **ymax** (*float*) – Clip the drawing area by these bounds.

`blf.dimensions (fontid, text)`

Return the width and height of the text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **text** (*string*) – the text to draw.

Returns the width and height of the text.

Return type tuple of 2 floats

`blf.disable(fontid, option)`

Disable option.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **option** (*int*) – One of ROTATION, CLIPPING, SHADOW or KERNING_DEFAULT.

`blf.draw(fontid, text)`

Draw text in the current context.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **text** (*string*) – the text to draw.

`blf.enable(fontid, option)`

Enable option.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **option** (*int*) – One of ROTATION, CLIPPING, SHADOW or KERNING_DEFAULT.

`blf.load(filename)`

Load a new font.

Parameters **filename** (*string*) – the filename of the font.

Returns the new font's fontid or -1 if there was an error.

Return type integer

`blf.position(fontid, x, y, z)`

Set the position for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **x** (*float*) – X axis position to draw the text.
- **y** (*float*) – Y axis position to draw the text.
- **z** (*float*) – Z axis position to draw the text.

`blf.rotation(fontid, angle)`

Set the text rotation angle, enable/disable using ROTATION.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **angle** (*float*) – The angle for text drawing to use.

`blf.shadow(fontid, level, r, g, b, a)`
Shadow options, enable/disable using SHADOW .

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **level** (*int*) – The blur level, can be 3, 5 or 0.
- **r** (*float*) – Shadow color (red channel 0.0 - 1.0).
- **g** (*float*) – Shadow color (green channel 0.0 - 1.0).
- **b** (*float*) – Shadow color (blue channel 0.0 - 1.0).
- **a** (*float*) – Shadow color (alpha channel 0.0 - 1.0).

`blf.shadow_offset(fontid, x, y)`
Set the offset for shadow text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **x** (*float*) – Vertical shadow offset value in pixels.
- **y** (*float*) – Horizontal shadow offset value in pixels.

`blf.size(fontid, size, dpi)`
Set the size and dpi for drawing text.

Parameters

- **fontid** (*int*) – The id of the typeface as returned by `blf.load()`, for default font use 0.
- **size** (*int*) – Point size of the font.
- **dpi** (*int*) – dots per inch value to use for drawing.

3.5 Audio System (aud)

This module provides access to the audaspace audio library.

3.5.1 Basic Sound Playback

This script shows how to use the classes: `Device`, `Factory` and `Handle`.

```
import aud

device = aud.device()
# load sound file (it can be a video file with audio)
factory = aud.Factory('music.ogg')

# play the audio, this return a handle to control play/pause
handle = device.play(sound)
# if the audio is not too big and will be used often you can buffer it
factory_buffered = aud.Factory.buffer(sound)
handle_buffered = device.play(buffered)

# stop the sounds (otherwise they play until their ends)
```

```
handle.stop()
handle_buffered.stop()

aud.AUD_DEVICE_JACK
    constant value 3

aud.AUD_DEVICE_NULL
    constant value 0

aud.AUD_DEVICE_OPENGL
    constant value 1

aud.AUD_DEVICE SDL
    constant value 2

aud.AUD_DISTANCE_MODEL_EXPONENT
    constant value 5

aud.AUD_DISTANCE_MODEL_EXPONENT_CLAMPED
    constant value 6

aud.AUD_DISTANCE_MODEL_INVALID
    constant value 0

aud.AUD_DISTANCE_MODEL_INVERSE
    constant value 1

aud.AUD_DISTANCE_MODEL_INVERSE_CLAMPED
    constant value 2

aud.AUD_DISTANCE_MODEL_LINEAR
    constant value 3

aud.AUD_DISTANCE_MODEL_LINEAR_CLAMPED
    constant value 4

aud.AUD_FORMAT_FLOAT32
    constant value 36

aud.AUD_FORMAT_FLOAT64
    constant value 40

aud.AUD_FORMAT_INVALID
    constant value 0

aud.AUD_FORMAT_S16
    constant value 18

aud.AUD_FORMAT_S24
    constant value 19

aud.AUD_FORMAT_S32
    constant value 20

aud.AUD_FORMAT_U8
    constant value 1

aud.AUD_STATUS_INVALID
    constant value 0

aud.AUD_STATUS_PAUSED
    constant value 2
```

aud.AUD_STATUS_PLAYING

constant value 1

device()

Returns the application's [Device](#).

return The application's [Device](#).

rtype [Device](#)

class aud.Device

Device objects represent an audio output backend like OpenAL or SDL, but might also represent a file output or RAM buffer output.

lock()

Locks the device so that it's guaranteed, that no samples are read from the streams until `unlock()` is called. This is useful if you want to do start/stop/pause/resume some sounds at the same time.

Note: The device has to be unlocked as often as locked to be able to continue playback.

Warning: Make sure the time between locking and unlocking is as short as possible to avoid clicks.

play(factory, keep=False)

Plays a factory.

Parameters

- **factory** ([Factory](#)) – The factory to play.
- **keep** (*bool*) – See [Handle.keep](#).

Returns The playback handle with which playback can be controlled with.

Return type [Handle](#)

unlock()

Unlocks the device after a lock call, see `lock()` for details.

channels

The channel count of the device.

distance_model

The distance model of the device.

See Also:

http://connect.creativelabs.com/openal/Documentation/OpenAL%201.1%20Specification.htm#_Toc199835864

doppler_factor

The doppler factor of the device. This factor is a scaling factor for the velocity vectors in doppler calculation. So a value bigger than 1 will exaggerate the effect as it raises the velocity.

format

The native sample format of the device.

listener_location

The listeners's location in 3D space, a 3D tuple of floats.

listener_orientation

The listener's orientation in 3D space as quaternion, a 4 float tuple.

listener_velocity

The listener's velocity in 3D space, a 3D tuple of floats.

rate

The sampling rate of the device in Hz.

speed_of_sound

The speed of sound of the device. The speed of sound in air is typically 343 m/s.

volume

The overall volume of the device.

class aud.Factory

Factory objects are immutable and represent a sound that can be played simultaneously multiple times. They are called factories because they create reader objects internally that are used for playback.

`file(filename)`

Creates a factory object of a sound file.

Parameters `filename (string)` – Path of the file.

Returns The created `Factory` object.

Return type `Factory`

Warning: If the file doesn't exist or can't be read you will not get an exception immediately, but when you try to start playback of that factory.

`sine(frequency, rate=44100)`

Creates a sine factory which plays a sine wave.

Parameters

- `frequency (float)` – The frequency of the sine wave in Hz.
- `rate (int)` – The sampling rate in Hz. It's recommended to set this value to the playback device's samling rate to avoid resampling.

Returns The created `Factory` object.

Return type `Factory`

`buffer()`

Buffers a factory into RAM. This saves CPU usage needed for decoding and file access if the underlying factory reads from a file on the harddisk, but it consumes a lot of memory.

Returns The created `Factory` object.

Return type `Factory`

Note: Only known-length factories can be buffered.

Warning: Raw PCM data needs a lot of space, only buffer short factories.

`delay(time)`

Delays by playing adding silence in front of the other factory's data.

Parameters `time (float)` – How many seconds of silence should be added before the factory.

Returns The created `Factory` object.

Return type `Factory`

`fadein(start, length)`

Fades a factory in by raising the volume linearly in the given time interval.

Parameters

- **start** (*float*) – Time in seconds when the fading should start.
- **length** (*float*) – Time in seconds how long the fading should last.

Returns The created `Factory` object.

Return type `Factory`

Note: Before the fade starts it plays silence.

`fadeout(start, length)`

Fades a factory in by lowering the volume linearly in the given time interval.

Parameters

- **start** (*float*) – Time in seconds when the fading should start.
- **length** (*float*) – Time in seconds how long the fading should last.

Returns The created `Factory` object.

Return type `Factory`

Note: After the fade this factory plays silence, so that the length of the factory is not altered.

`filter(b, a = (1))`

Filters a factory with the supplied IIR filter coefficients. Without the second parameter you'll get a FIR filter. If the first value of the a sequence is 0 it will be set to 1 automatically. If the first value of the a sequence is neither 0 nor 1, all filter coefficients will be scaled by this value so that it is 1 in the end, you don't have to scale yourself.

Parameters

- **b** (*sequence of float*) – The nominator filter coefficients.
- **a** (*sequence of float*) – The denominator filter coefficients.

Returns The created `Factory` object.

Return type `Factory`

`highpass(frequency, Q=0.5)`

Creates a second order highpass filter based on the transfer function $H(s) = s^2 / (s^2 + s/Q + 1)$

Parameters

- **frequency** (*float*) – The cut off frequency of the highpass.
- **Q** (*float*) – Q factor of the lowpass.

Returns The created `Factory` object.

Return type `Factory`

join(factory)

Plays two factories in sequence.

Parameters `factory` (`Factory`) – The factory to play second.

Returns The created `Factory` object.

Return type `Factory`

Note: The two factories have to have the same specifications (channels and samplerate).

limit(start, end)

Limits a factory within a specific start and end time.

Parameters

- `start` (`float`) – Start time in seconds.
- `end` (`float`) – End time in seconds.

Returns The created `Factory` object.

Return type `Factory`

loop(count)

Loops a factory.

Parameters `count` (`integer`) – How often the factory should be looped. Negative values mean endlessly.

Returns The created `Factory` object.

Return type `Factory`

Note: This is a filter function, you might consider using `Handle.loop_count` instead.

lowpass(frequency, Q=0.5)

Creates a second order lowpass filter based on the transfer function $H(s) = 1 / (s^2 + s/Q + 1)$

Parameters

- `frequency` (`float`) – The cut off frequency of the lowpass.
- `Q` (`float`) – Q factor of the lowpass.

Returns The created `Factory` object.

Return type `Factory`

mix(factory)

Mixes two factories.

Parameters `factory` (`Factory`) – The factory to mix over the other.

Returns The created `Factory` object.

Return type `Factory`

Note: The two factories have to have the same specifications (channels and samplerate).

pingpong()

Plays a factory forward and then backward. This is like joining a factory with its reverse.

Returns The created [Factory](#) object.

Return type [Factory](#)

pitch(factor)

Changes the pitch of a factory with a specific factor.

Parameters **factor** (*float*) – The factor to change the pitch with.

Returns The created [Factory](#) object.

Return type [Factory](#)

Note: This is done by changing the sample rate of the underlying factory, which has to be an integer, so the factor value rounded and the factor may not be 100 % accurate.

Note: This is a filter function, you might consider using [Handle.pitch](#) instead.

reverse()

Plays a factory reversed.

Returns The created [Factory](#) object.

Return type [Factory](#)

Note: The factory has to have a finite length and has to be seekable. It's recommended to use this only with factories with fast and accurate seeking, which is not true for encoded audio files, such ones should be buffered using [buffer\(\)](#) before being played reversed.

Warning: If seeking is not accurate in the underlying factory you'll likely hear skips/jumps/cracks.

square(threshold = 0)

Makes a square wave out of an audio wave by setting all samples with a amplitude \geq threshold to 1, all \leq -threshold to -1 and all between to 0.

Parameters **threshold** (*float*) – Threshold value over which an amplitude counts non-zero.

Returns The created [Factory](#) object.

Return type [Factory](#)

volume(volume)

Changes the volume of a factory.

Parameters **volume** (*float*) – The new volume..

Returns The created [Factory](#) object.

Return type [Factory](#)

Note: Should be in the range [0, 1] to avoid clipping.

Note: This is a filter function, you might consider using `Handle.volume` instead.

class aud.Handle

Handle objects are playback handles that can be used to control playback of a sound. If a sound is played back multiple times then there are as many handles.

`pause()`

Pauses playback.

Returns Whether the action succeeded.

Return type bool

`resume()`

Resumes playback.

Returns Whether the action succeeded.

Return type bool

`stop()`

Stops playback.

Returns Whether the action succeeded.

Return type bool

Note: This makes the handle invalid.

attenuation

This factor is used for distance based attenuation of the source.

See Also:

`Device.distance_model`

cone_angle_inner

The opening angle of the inner cone of the source. If the cone values of a source are set there are two (audible) cones with the apex at the `location` of the source and with infinite height, heading in the direction of the source's `orientation`. In the inner cone the volume is normal. Outside the outer cone the volume will be `cone_volume_outer` and in the area between the volume will be interpolated linearly.

cone_angle_outer

The opening angle of the outer cone of the source.

See Also:

`cone_angle_inner`

cone_volume_outer

The volume outside the outer cone of the source.

See Also:

`cone_angle_inner`

distance_maximum

The maximum distance of the source. If the listener is further away the source volume will be 0.

See Also:

`Device.distance_model`

distance_reference

The reference distance of the source. At this distance the volume will be exactly `volume`.

See Also:

`Device.distance_model`

keep

Whether the sound should be kept paused in the device when its end is reached. This can be used to seek the sound to some position and start playback again.

Warning: If this is set to true and you forget stopping this equals a memory leak as the handle exists until the device is destroyed.

location

The source's location in 3D space, a 3D tuple of floats.

loop_count

The (remaining) loop count of the sound. A negative value indicates infinity.

orientation

The source's orientation in 3D space as quaternion, a 4 float tuple.

pitch

The pitch of the sound.

position

The playback position of the sound in seconds.

relative

Whether the source's location, velocity and orientation is relative or absolute to the listener.

status

Whether the sound is playing, paused or stopped (=invalid).

velocity

The source's velocity in 3D space, a 3D tuple of floats.

volume

The volume of the sound.

volume_maximum

The maximum volume of the source.

See Also:

`Device.distance_model`

volume_minimum

The minimum volume of the source.

See Also:

`Device.distance_model`

class aud.error

3.6 Extra Utilities (bpy_extras)

Utility modules assosiated with the bpy module.

3.6.1 bpy_extras submodule (bpy_extras.object_utils)

`bpy_extras.object_utils.add_object_align_init(context, operator)`

Return a matrix using the operator settings and view context.

Parameters

- **context** (Context) – The context to use.
- **operator** (Operator) – The operator, checked for location and rotation properties.

Returns the matrix from the context and settings.

Return type

`bpy_extras.object_utils.object_data_add(context, obdata, operator=None)`

Add an object using the view context and preference to to initialize the location, rotation and layer.

Parameters

- **context** (Context) – The context to use.
- **obdata** (*valid object data type or None*) – the data used for the new object.
- **operator** (Operator) – The operator, checked for location and rotation properties.

Returns the newly created object in the scene.

Return type

3.6.2 bpy_extras submodule (bpy_extras.io_utils)

`bpy_extras.io_utils.axis_conversion(from_forward='Y', from_up='Z', to_forward='Y', to_up='Z')`

Each argument us an axis in ['X', 'Y', 'Z', '-X', '-Y', '-Z'] where the first 2 are a source and the second 2 are the target.

`bpy_extras.io_utils.create_derived_objects(scene, ob)`

`bpy_extras.io_utils.free_derived_objects(ob)`

`bpy_extras.io_utils.unpack_list(list_of_tuples)`

`bpy_extras.io_utils.unpack_face_list(list_of_tuples)`

`bpy_extras.io_utils.path_reference(filepath, base_src, base_dst, mode='AUTO', copy_subdir='', copy_set=None)`

Return a filepath relative to a destination directory, for use with exporters.

Parameters

- **filepath** (*string*) – the file path to return, supporting blenders relative ‘//’ prefix.
- **base_src** (*string*) – the directory the *filepath* is relative too (normally the blend file).
- **base_dst** (*string*) – the directory the *filepath* will be referenced from (normally the export path).

- **mode** (*string*) – the method used get the path in [‘AUTO’, ‘ABSOLUTE’, ‘RELATIVE’, ‘MATCH’, ‘STRIP’, ‘COPY’]
- **copy_subdir** (*string*) – the subdirectory of *base_dst* to use when mode=’COPY’.
- **copy_set** (*set*) – collect from/to pairs when mode=’COPY’, pass to *path_reference_copy* when exportign is done.

Returns the new filepath.

Return type string

`bpy_extras.io_utils.path_reference_copy(copy_set, report=<built-in function print>)`
Execute copying files of path_reference

Parameters

- **copy_set** (*set*) – set of (from, to) pairs to copy.
- **report** (*function*) – function used for reporting warnings, takes a string argument.

`bpy_extras.io_utils.path_reference_mode`

constant value (<built-in function EnumProperty>, {‘default’: ‘AUTO’, ‘items’: ((‘AUTO’, ‘Auto’, ‘Use Relative paths with subdirectories only’), (‘ABSOLUTE’, ‘Absolute’, ‘Always write absolute paths’), (‘RELATIVE’, ‘Relative’, ‘Always write relative patsh (where possible)’), (‘MATCH’, ‘Match’, ‘Match Absolute/Relative setting with input path’), (‘STRIP’, ‘Strip Path’, ‘Filename only’), (‘COPY’, ‘Copy’, ‘copy the file to the destination path (or subdirectory)’)), ‘attr’: ‘path_mode’, ‘description’: ‘Method used to reference paths’, ‘name’: ‘Path Mode’})

`bpy_extras.io_utils.unique_name(key, name, name_dict, name_max=-1, clean_func=None)`
Helper function for storing unique names which may have special characters stripped and restricted to a maximum length.

Parameters

- **key** (any hashable object assosiated with the *name*.) – unique item this name belongs to, *name_dict[key]* will be reused when available. This can be the object, mesh, material, etc instance its self.
- **name** (*string*) – The name used to create a unique value in *name_dict*.
- **name_dict** (*dict*) – This is used to cache namespace to ensure no collisions occur, this should be an empty dict initially and only modified by this function.
- **clean_func** (*function*) – Function to call on *name* before creating a unique value.

`class bpy_extras.io_utils.ExportHelper`

`class bpy_extras.io_utils.ImportHelper`

3.6.3 bpy_extras submodule (bpy_extras.image_utils)

`bpy_extras.image_utils.load_image(imagepath, dirname='', place_holder=False, recursive=False, ncase_cmp=True, convert_callback=None, verbose=False)`

Return an image from the file path with options to search multiple paths and return a placeholder if its not found.

Parameters

- **filepath** (*string*) – The image filename If a path precedes it, this will be searched as well.
- **dirname** (*string*) – is the directory where the image may be located - any file at the end will be ignored.

- **place_holder** (*bool*) – if True a new place holder image will be created. this is usefull so later you can relink the image to its original data.
- **recursive** (*bool*) – If True, directories will be recursively searched. Be carefull with this if you have files in your root directory because it may take a long time.
- **ncase_cmp** (*bool*) – on non windows systems, find the correct case for the file.
- **convert_callback** (*function*) – a function that takes an existing path and returns a new one. Use this when loading image formats blender may not support, the CONVERT_CALLBACK can take the path for a GIF (for example), convert it to a PNG and return the PNG's path. For formats blender can read, simply return the path that is given.

Returns an image or None

Return type Image

3.6.4 bpy_extras submodule (bpy_extras.mesh_utils)

bpy_extras.mesh_utils.**mesh_linked_faces** (*mesh*)

Splits the mesh into connected faces, use this for separating cubes from other mesh elements within 1 mesh datablock.

Parameters **mesh** (Mesh) – the mesh used to group with.

Returns lists of lists containing faces.

Return type list

bpy_extras.mesh_utils.**edge_face_count_dict** (*mesh*)

Returns dict of edge keys with their value set to the number of faces using each edge.

Return type dict

bpy_extras.mesh_utils.**edge_face_count** (*mesh*)

Returns list face users for each item in mesh.edges.

Return type list

bpy_extras.mesh_utils.**edge_loops_from_faces** (*mesh, faces=None, seams=()*)

Edge loops defined by faces

Takes me.faces or a list of faces and returns the edge loops These edge loops are the edges that sit between quads, so they don't touch 1 quad, note: not connected will make 2 edge loops, both only containing 2 edges.

return a list of edge key lists [[(0, 1), (4, 8), (3, 8)], ...]

Parameters

- **mesh** (Mesh) – the mesh used to get edge loops from.
- **faces** (MeshFaces, sequence or NoneType) – optional face list to only use some of the meshes faces.

Returns return a list of edge vertex index lists.

Return type list

bpy_extras.mesh_utils.**edge_loops_from_edges** (*mesh, edges=None*)

Edge loops defined by edges

Takes me.edges or a list of edges and returns the edge loops

return a list of vertex indices. [[1, 6, 7, 2], ...]

closed loops have matching start and end values.

`bpy_extras.mesh_utils.ngon_tessellate(from_data, indices, fix_loops=True)`

Takes a polyline of indices (fgon) and returns a list of face indicie lists. Designed to be used for importers that need indices for an fgon to create from existing verts.

`from_data`: either a mesh, or a list/tuple of vectors. `indices`: a list of indices to use this list is the ordered closed polyline to fill, and can be a subset of the data given. `fix_loops`: If this is enabled polylines that use loops to make multiple polylines are delt with correctly.

3.6.5 bpy_extras submodule (`bpy_extras.view3d_utils`)

`bpy_extras.view3d_utils.region_2d_to_vector_3d(region, rv3d, coord)`

Return a direction vector from the viewport at the spesific 2d region coordinate.

Parameters

- `region` (Region) – region of the 3D viewport, typically `bpy.context.region`.
- `rv3d` (RegionView3D) – 3D region data, typically `bpy.context.space_data.region_3d`.
- `coord` (2d vector) – 2d coordinates relative to the region: (`event.mouse_region_x`, `event.mouse_region_y`) for example.

Returns normalized 3d vector.

Return type Vector

`bpy_extras.view3d_utils.region_2d_to_location_3d(region, rv3d, coord, depth_location)`

Return a 3d location from the region relative 2d coords, aligned with `depth_location`.

Parameters

- `region` (Region) – region of the 3D viewport, typically `bpy.context.region`.
- `rv3d` (RegionView3D) – 3D region data, typically `bpy.context.space_data.region_3d`.
- `coord` (2d vector) – 2d coordinates relative to the region; (`event.mouse_region_x`, `event.mouse_region_y`) for example.
- `depth_location` (3d vector) – the returned vectors depth is aligned with this since there is no defined depth with a 2d region input.

Returns normalized 3d vector.

Return type Vector

`bpy_extras.view3d_utils.location_3d_to_region_2d(region, rv3d, coord)`

Return the `region` relative 2d location of a 3d position.

Parameters

- `region` (Region) – region of the 3D viewport, typically `bpy.context.region`.
- `rv3d` (RegionView3D) – 3D region data, typically `bpy.context.space_data.region_3d`.
- `coord` (3d vector) – 3d worldspace location.

Returns 2d location

Return type Vector

GAME ENGINE MODULES

4.1 Game Engine bge.types Module

class `bge.types.PyObjectPlus`

PyObjectPlus base class of most other types in the Game Engine.

invalid

Test if the object has been freed by the game engine and is no longer valid.

Normally this is not a problem but when storing game engine data in the GameLogic module, KX_Scenes or other KX_GameObjects its possible to hold a reference to invalid data. Calling an attribute or method on an invalid object will raise a SystemError.

The invalid attribute allows testing for this case without exception handling.

Type boolean

class `bge.types.CValue (PyObjectPlus)`

This class is a basis for other classes.

name

The name of this CValue derived object (read-only).

Type string

class `bge.types.CPropertyValue (CValue)`

This class has no python functions

class `bge.types.SCA_ILogicBrick (CValue)`

Base class for all logic bricks.

executePriority

This determines the order controllers are evaluated, and actuators are activated (lower priority is executed first).

Type executePriority: int

owner

The game object this logic brick is attached to (read-only).

Type `KX_GameObject` or None in exceptional cases.

name

The name of this logic brick (read-only).

Type string

class `bge.types.SCA_PythonKeyboard` (*PyObjectPlus*)

The current keyboard.

events

A dictionary containing the status of each keyboard event or key. (read-only).

Type dictionary {*keycode*:*status*, ...}

class `bge.types.SCA_PythonMouse` (*PyObjectPlus*)

The current mouse.

events

a dictionary containing the status of each mouse event. (read-only).

Type dictionary {*keycode*:*status*, ...}

position

The normalized x and y position of the mouse cursor.

Type list [x, y]

visible

The visibility of the mouse cursor.

Type boolean

class `bge.types.SCA_IObject` (*CValue*)

This class has no python functions

class `bge.types.SCA_ISensor` (*SCAILogicBrick*)

Base class for all sensor logic bricks.

usePosPulseMode

Flag to turn positive pulse mode on and off.

Type boolean

useNegPulseMode

Flag to turn negative pulse mode on and off.

Type boolean

frequency

The frequency for pulse mode sensors.

Type integer

level

level Option whether to detect level or edge transition when entering a state. It makes a difference only in case of logic state transition (state actuator). A level detector will immediately generate a pulse, negative or positive depending on the sensor condition, as soon as the state is activated. A edge detector will wait for a state change before generating a pulse. note: mutually exclusive with `tap`, enabling will disable `tap`.

Type boolean

tap

When enabled only sensors that are just activated will send a positive event, after this they will be detected as negative by the controllers. This will make a key that's held act as if it's only tapped for an instant. note: mutually exclusive with `level`, enabling will disable `level`.

Type boolean

invert

Flag to set if this sensor activates on positive or negative events.

Type boolean

triggered

True if this sensor brick is in a positive state. (read-only).

Type boolean

positive

True if this sensor brick is in a positive state. (read-only).

Type boolean

status

The status of the sensor (read-only): can be one of *these constants*.

Type int

Note: This convenient attribute combines the values of triggered and positive attributes.

reset()

Reset sensor internal state, effect depends on the type of sensor and settings.

The sensor is put in its initial state as if it was just activated.

class bge.types.SCA_IController(SCAILogicBrick)

Base class for all controller logic bricks.

state

The controllers state bitmask. This can be used with the GameObject's state to test if the controller is active.

Type int bitmask

sensors

A list of sensors linked to this controller.

Type sequence supporting index/string lookups and iteration.

Note: The sensors are not necessarily owned by the same object.

Note: When objects are instanced in dupligrroups links may be lost from objects outside the dupligrroup.

actuators

A list of actuators linked to this controller.

Type sequence supporting index/string lookups and iteration.

Note: The sensors are not necessarily owned by the same object.

Note: When objects are instanced in dupligrroups links may be lost from objects outside the dupligrroup.

useHighPriority

When set the controller executes always before all other controllers that dont have this set.

Type boolen

Note: Order of execution between high priority controllers is not guaranteed.

class bge.types.**SCA_IActuator** (*SCAILogicBrick*)

Base class for all actuator logic bricks.

class bge.types.**BL_ActionActuator** (*SCA_IActuator*)

Action Actuators apply an action to an actor.

action

The name of the action to set as the current action.

Type string

channelNames

A list of channel names that may be used with `setChannel` and `getChannel`.

Type list of strings

frameStart

Specifies the starting frame of the animation.

Type float

frameEnd

Specifies the ending frame of the animation.

Type float

blendIn

Specifies the number of frames of animation to generate when making transitions between actions.

Type float

priority

Sets the priority of this actuator. Actuators will lower priority numbers will override actuators with higher numbers.

Type integer

frame

Sets the current frame for the animation.

Type float

propName

Sets the property to be used in FromProp playback mode.

Type string

blendTime

Sets the internal frame timer. This property must be in the range from 0.0 to blendIn.

Type float

mode

The operation mode of the actuator. Can be one of *these constants*.

Type integer

useContinue

The actions continue option, True or False. When True, the action will always play from where last left off, otherwise negative events to this actuator will reset it to its start frame.

Type boolean

framePropName

The name of the property that is set to the current frame number.

Type string

setChannel (channel, matrix)

Alternative to the 2 arguments, 4 arguments (channel, matrix, loc, size, quat) are also supported.

Parameters

- **channel (string)** – A string specifying the name of the bone channel, error raised if not in [channelNames](#).
- **matrix** – A 4x4 matrix specifying the overriding transformation as an offset from the bone's rest position.
- **matrix** – list [[float]]

Note: These values are relative to the bones rest position, currently the api has no way to get this info (which is annoying), but can be worked around by using bones with a rest pose that has no translation.

getChannel (channel)

Parameters **channel (string)** – A string specifying the name of the bone channel. error raised if not in [channelNames](#).

Returns (loc, size, quat)

Return type tuple

class bge.types.**BL_Shader** (*PyObjectPlus*)
BL_Shader GLSL shaders.

TODO - Description

setUniformfv (name, fList)

Set a uniform with a list of float values

Parameters

- **name (string)** – the uniform name
- **fList (list[float])** – a list (2, 3 or 4 elements) of float values

delSource ()

Clear the shader. Use this method before the source is changed with [setSource](#).

getFragmentProg ()

Returns the fragment program.

Returns The fragment program.

Return type string

getVertexProg ()

Get the vertex program.

Returns The vertex program.

Return type string

isValid ()

Check if the shader is valid.

Returns True if the shader is valid

Return type boolean

setAttrib (*enum*)

Set attribute location. (The parameter is ignored a.t.m. and the value of “tangent” is always used.)

Parameters **enum** (*integer*) – attribute location value

setNumberOfPasses (*max_pass*)

Set the maximum number of passes. Not used a.t.m.

Parameters **max_pass** (*integer*) – the maximum number of passes

setSampler (*name, index*)

Set uniform texture sample index.

Parameters

- **name** (*string*) – Uniform name
- **index** (*integer*) – Texture sample index.

setSource (*vertexProgram, fragmentProgram*)

Set the vertex and fragment programs

Parameters

- **vertexProgram** (*string*) – Vertex program
- **fragmentProgram** (*string*) – Fragment program

setUniform1f (*name, fx*)

Set a uniform with 1 float value.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – Uniform value

setUniform1i (*name, ix*)

Set a uniform with an integer value.

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – the uniform value

setUniform2f (*name, fx, fy*)

Set a uniform with 2 float values

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- (*float*) – second float value

setUniform2i (*name, ix, iy*)

Set a uniform with 2 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value

setUniform3f (*name, fx, fy, fz*)

Set a uniform with 3 float values.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- (*float*) – second float value
- **fz** (*float*) – third float value

setUniform3i (*name, ix, iy, iz*)

Set a uniform with 3 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value
- **iz** (*integer*) – third integer value

setUniform4f (*name, fx, fy, fz, fw*)

Set a uniform with 4 float values.

Parameters

- **name** (*string*) – the uniform name
- **fx** (*float*) – first float value
- **fy** (*float*) – second float value
- **fz** (*float*) – third float value
- **fw** (*float*) – fourth float value

setUniform4i (*name, ix, iy, iz, iw*)

Set a uniform with 4 integer values

Parameters

- **name** (*string*) – the uniform name
- **ix** (*integer*) – first integer value
- **iy** (*integer*) – second integer value
- **iz** (*integer*) – third integer value
- **iw** (*integer*) – fourth integer value

setUniformDef (*name, type*)

Define a new uniform

Parameters

- **name** (*string*) – the uniform name
- **type** (*UNI_NONE, UNI_INT, UNI_FLOAT, UNI_INT2, UNI_FLOAT2, UNI_INT3, UNI_FLOAT3, UNI_INT4, UNI_FLOAT4, UNI_MAT3, UNI_MAT4, UNI_MAX*) – uniform type

setUniformMatrix3 (*name, mat, transpose*)

Set a uniform with a 3x3 matrix value

Parameters

- **name** (*string*) – the uniform name
- **mat** (*3x3 matrix*) – A 3x3 matrix [[f, f, f], [f, f, f], [f, f, f]]
- **transpose** (*boolean*) – set to True to transpose the matrix

setUniformMatrix4 (*name, mat, transpose*)

Set a uniform with a 4x4 matrix value

Parameters

- **name** (*string*) – the uniform name
- **mat** (*4x4 matrix*) – A 4x4 matrix [[f, f, f, f], [f, f, f, f], [f, f, f, f], [f, f, f, f]]
- **transpose** (*boolean*) – set to True to transpose the matrix

setUniformiv (*name, iList*)

Set a uniform with a list of integer values

Parameters

- **name** (*string*) – the uniform name
- **iList** (*list[integer]*) – a list (2, 3 or 4 elements) of integer values

validate()

Validate the shader object.

class bge.types.BL_ShapeActionActuator (*SCA_IActuator*)

ShapeAction Actuators apply an shape action to an mesh object.

action

The name of the action to set as the current shape action.

Type string**frameStart**

Specifies the starting frame of the shape animation.

Type float**frameEnd**

Specifies the ending frame of the shape animation.

Type float**blendIn**

Specifies the number of frames of animation to generate when making transitions between actions.

Type float**priority**

Sets the priority of this actuator. Actuators will lower priority numbers will override actuators with higher numbers.

Type integer**frame**

Sets the current frame for the animation.

Type float**propName**

Sets the property to be used in FromProp playback mode.

Type string

blendTime
Sets the internal frame timer. This property must be in the range from 0.0 to blendin.

Type float

mode
The operation mode of the actuator. Can be one of *these constants*.

Type integer

framePropName
The name of the property that is set to the current frame number.

Type string

class bge.types.CListValue (*CPropertyValue*)
This is a list like object used in the game engine internally that behaves similar to a python list in most ways.
As well as the normal index lookup (`val= clist[i]`), CListValue supports string lookups (`val= scene.objects["Cube"]`)
Other operations such as `len(clist)`, `list(clist)`, `cplist[0:10]` are also supported.

append (*val*)
Add an item to the list (like pythons append)

Warning: Appending values to the list can cause crashes when the list is used internally by the game engine.

count (*val*)
Count the number of instances of a value in the list.

Returns number of instances

Return type integer

index (*val*)
Return the index of a value in the list.

Returns The index of the value in the list.

Return type integer

reverse ()
Reverse the order of the list.

get (*key, default=None*)
Return the value matching key, or the default value if its not found.

Returns The key value or a default.

from_id (*id*)
This is a function especially for the game engine to return a value with a specific id.
Since object names are not always unique, the id of an object can be used to get an object from the CValueList.
Example:
`myObID=id(gameObject)
ob= scene.objects.from_id(myObID)`

Where myObjID is an int or long from the id function.

This has the advantage that you can store the id in places you could not store a gameObject.

Warning: The id is derived from a memory location and will be different each time the game engine starts.

```
class bge.types.KX_BlenderMaterial (PyObjectPlus)
    KX_BlenderMaterial
```

getShader()

Returns the material's shader.

Returns the material's shader

Return type [BL_Shader](#)

setBlending(src, dest)

Set the pixel color arithmetic functions.

Parameters

- **src** – Specifies how the red, green, blue, and alpha source blending factors are computed.
- **dest** – Specifies how the red, green, blue, and alpha destination blending factors are computed.

getMaterialIndex()

Returns the material's index.

Returns the material's index

Return type integer

```
class bge.types.KX_CameraActuator (SCA_IActuator)
```

Applies changes to a camera.

damping

strength of of the camera following movement.

Type float

min

minimum distance to the target object maintained by the actuator.

Type float

max

maximum distance to stay from the target object.

Type float

height

height to stay above the target object.

Type float

useXY

axis this actuator is tracking, True=X, False=Y.

Type boolean

object

the object this actuator tracks.

Type [KX_GameObject](#) or None

```
class bge.types.KX_ConstraintActuator (SCA_IActuator)
    A constraint actuator limits the position, rotation, distance or orientation of an object.

damp
    Time constant of the constraint expressed in frame (not use by Force field constraint).
        Type integer

rotDamp
    Time constant for the rotation expressed in frame (only for the distance constraint), 0 = use damp for
    rotation as well.
        Type integer

direction
    The reference direction in world coordinate for the orientation constraint.
        Type 3-tuple of float: (x, y, z)

option
    Binary combination of these constants
        Type integer

time
    activation time of the actuator. The actuator disables itself after this many frame. If set to 0, the actuator is
    not limited in time.
        Type integer

propName
    the name of the property or material for the ray detection of the distance constraint.
        Type string

min
    The lower bound of the constraint. For the rotation and orientation constraint, it represents radiant.
        Type float

distance
    the target distance of the distance constraint.
        Type float

max
    the upper bound of the constraint. For rotation and orientation constraints, it represents radiant.
        Type float

rayLength
    the length of the ray of the distance constraint.
        Type float

limit
    type of constraint. Use one of the these constants
        Type integer.

class bge.types.KX_ConstraintWrapper (PyObjectPlus)
    KX_ConstraintWrapper

getConstraintId (val)
    Returns the constraint's ID
```

Returns the constraint's ID

Return type integer

class bge.types.KX_GameActuator (SCA_IActuator)

The game actuator loads a new .blend file, restarts the current .blend file or quits the game.

fileName

the new .blend file to load.

Type string

mode

The mode of this actuator. Can be one of *these constants*

Type Int

class bge.types.KX_GameObject (SCA_IObject)

All game objects are derived from this class.

Properties assigned to game objects are accessible as attributes of this class.

Note: Calling ANY method or attribute on an object that has been removed from a scene will raise a SystemError, if an object may have been removed since last accessing it use the invalid attribute to check.

name

The object's name. (read-only).

Type string

mass

The object's mass

Type float

Note: The object must have a physics controller for the mass to be applied, otherwise the mass value will be returned as 0.0.

linVelocityMin

Enforces the object keeps moving at a minimum velocity.

Type float

Note: Applies to dynamic and rigid body objects only.

Note: A value of 0.0 disables this option.

Note: While objects are stationary the minimum velocity will not be applied.

linVelocityMax

Clamp the maximum linear velocity to prevent objects moving beyond a set speed.

Type float

Note: Applies to dynamic and rigid body objects only.

Note: A value of 0.0 disables this option (rather than setting it stationary).

localInertia

the object's inertia vector in local coordinates. Read only.

Type list [ix, iy, iz]

parent

The object's parent object. (read-only).

Type [KX_GameObject](#) or None

visible

visibility flag.

Type boolean

Note: Game logic will still run for invisible objects.

color

The object color of the object. [r, g, b, a]

Type [mathutils.Vector](#)

occlusion

occlusion capability flag.

Type boolean

position

The object's position. [x, y, z] On write: local position, on read: world position Deprecated since version use: [localPosition](#) and [worldPosition](#).

Type [mathutils.Vector](#)

orientation

The object's orientation. 3x3 Matrix. You can also write a Quaternion or Euler vector. On write: local orientation, on read: world orientation Deprecated since version use: [localOrientation](#) and [worldOrientation](#).

Type [mathutils.Matrix](#)

scaling

The object's scaling factor. [sx, sy, sz] On write: local scaling, on read: world scaling Deprecated since version use: [localScale](#) and [worldScale](#).

Type [mathutils.Vector](#)

localOrientation

The object's local orientation. 3x3 Matrix. You can also write a Quaternion or Euler vector.

Type [mathutils.Matrix](#)

worldOrientation

The object's world orientation. 3x3 Matrix.

Type [mathutils.Matrix](#)

localScale

The object's local scaling factor. [sx, sy, sz]

Type [mathutils.Vector](#)

worldScale

The object's world scaling factor. Read-only. [sx, sy, sz]

Type `mathutils.Vector`

localPosition

The object's local position. [x, y, z]

Type `mathutils.Vector`

worldPosition

The object's world position. [x, y, z]

Type `mathutils.Vector`

localLinearVelocity

The object's local linear velocity. [x, y, z]

Type `mathutils.Vector`

worldLinearVelocity

The object's world linear velocity. [x, y, z]

type `mathutils.Vector`

localAngularVelocity

The object's local angular velocity. [x, y, z]

type `mathutils.Vector`

worldAngularVelocity

The object's world angular velocity. [x, y, z]

type `mathutils.Vector`

timeOffset

adjust the slowparent delay at runtime.

Type float

state

the game object's state bitmask, using the first 30 bits, one bit must always be set.

Type int

meshes

a list meshes for this object.

Type list of `KX_MeshProxy`

Note: Most objects use only 1 mesh.

Note: Changes to this list will not update the `KX_GameObject`.

sensors

a sequence of `SCA_ISensor` objects with string/index lookups and iterator support.

Type list

Note: This attribute is experimental and may be removed (but probably won't be).

Note: Changes to this list will not update the KX_GameObject.

controllers

a sequence of [SCA_IController](#) objects with string/index lookups and iterator support.

Type list of [SCA_ISensor](#)

Note: This attribute is experimental and may be removed (but probably won't be).

Note: Changes to this list will not update the KX_GameObject.

actuators

a list of [SCA_IActuator](#) with string/index lookups and iterator support.

Type list

Note: This attribute is experimental and may be removed (but probably won't be).

Note: Changes to this list will not update the KX_GameObject.

attrDict

get the object's internal python attribute dictionary for direct (faster) access.

Type dict

children

direct children of this object, (read-only).

Type CListValue of [KX_GameObject](#)'s

childrenRecursive

all children of this object including children's children, (read-only).

Type CListValue of [KX_GameObject](#)'s

endObject()

Delete this object, can be used in place of the EndObject Actuator.

The actual removal of the object from the scene is delayed.

replaceMesh (mesh, useDisplayMesh=True, usePhysicsMesh=False)

Replace the mesh of this object with a new mesh. This works the same way as the actuator.

Parameters

- **mesh** (MeshProxy or string) – mesh to replace or the mesh's name.
- **useDisplayMesh** (boolean) – when enabled the display mesh will be replaced (optional argument).
- **usePhysicsMesh** (boolean) – when enabled the physics mesh will be replaced (optional argument).

setVisible (visible, recursive)

Sets the game object's visible flag.

Parameters

- **visible** (boolean) – the visible state to set.

- **recursive** (*boolean*) – optional argument to set all childrens visibility flag too.

setOcclusion (*occlusion, recursive*)

Sets the game object's occlusion capability.

Parameters

- **occlusion** (*boolean*) – the state to set the occlusion to.
- **recursive** (*boolean*) – optional argument to set all childrens occlusion flag too.

alignAxisToVect (*vect, axis=2, factor=1.0*)

Aligns any of the game object's axis along the given vector.

Parameters

- **vect** (*3D vector*) – a vector to align the axis.
- **axis** (*integer*) – The axis you want to align
 - 0: X axis
 - 1: Y axis
 - 2: Z axis
- **factor** (*float*) – Only rotate a feaction of the distance to the target vector (0.0 - 1.0)

getAxisVect (*vect*)

Returns the axis vector rotates by the objects worldspace orientation. This is the equivalent of multiplying the vector by the orientation matrix.

Parameters **vect** (*3D Vector*) – a vector to align the axis.

Returns The vector in relation to the objects rotation.

Return type 3d vector.

applyMovement (*movement, local=False*)

Sets the game object's movement.

Parameters

- **movement** (*3D Vector*) – movement vector.
- **local** –
 - False: you get the “global” movement ie: relative to world orientation.
 - True: you get the “local” movement ie: relative to object orientation.
- **local** – boolean

applyRotation (*rotation, local=False*)

Sets the game object's rotation.

Parameters

- **rotation** (*3D Vector*) – rotation vector.
- **local** –
 - False: you get the “global” rotation ie: relative to world orientation.
 - True: you get the “local” rotation ie: relative to object orientation.
- **local** – boolean

applyForce (*force, local=False*)

Sets the game object's force.

This requires a dynamic object.

Parameters

- **force** (*3D Vector*) – force vector.
- **local** (*boolean*) –
 - False: you get the “global” force ie: relative to world orientation.
 - True: you get the “local” force ie: relative to object orientation.

applyTorque (*torque, local=False*)

Sets the game object's torque.

This requires a dynamic object.

Parameters

- **torque** (*3D Vector*) – torque vector.
- **local** (*boolean*) –
 - False: you get the “global” torque ie: relative to world orientation.
 - True: you get the “local” torque ie: relative to object orientation.

getLinearVelocity (*local=False*)

Gets the game object's linear velocity.

This method returns the game object's velocity through it's centre of mass, ie no angular velocity component.

Parameters **local** (*boolean*) –

- False: you get the “global” velocity ie: relative to world orientation.
- True: you get the “local” velocity ie: relative to object orientation.

Returns the object's linear velocity.

Return type list [vx, vy, vz]

setLinearVelocity (*velocity, local=False*)

Sets the game object's linear velocity.

This method sets game object's velocity through it's centre of mass, ie no angular velocity component.

This requires a dynamic object.

Parameters

- **velocity** (*3D Vector*) – linear velocity vector.
- **local** (*boolean*) –
 - False: you get the “global” velocity ie: relative to world orientation.
 - True: you get the “local” velocity ie: relative to object orientation.

getAngularVelocity (*local=False*)

Gets the game object's angular velocity.

Parameters **local** (*boolean*) –

- False: you get the “global” velocity ie: relative to world orientation.

- True: you get the “local” velocity ie: relative to object orientation.

Returns the object’s angular velocity.

Return type list [vx, vy, vz]

setAngularVelocity (*velocity, local=False*)

Sets the game object’s angular velocity.

This requires a dynamic object.

Parameters

- **velocity** (*boolean*) – angular velocity vector.
- **local** –
 - False: you get the “global” velocity ie: relative to world orientation.
 - True: you get the “local” velocity ie: relative to object orientation.

getVelocity (*point=(0, 0, 0)*)

Gets the game object’s velocity at the specified point.

Gets the game object’s velocity at the specified point, including angular components.

Parameters **point** (*3D Vector*) – optional point to return the velocity for, in local coordinates.

Returns the velocity at the specified point.

Return type list [vx, vy, vz]

getReactionForce ()

Gets the game object’s reaction force.

The reaction force is the force applied to this object over the last simulation timestep. This also includes impulses, eg from collisions.

Returns the reaction force of this object.

Return type list [fx, fy, fz]

Note: This is not implemented at the moment.

applyImpulse (*point, impulse*)

Applies an impulse to the game object.

This will apply the specified impulse to the game object at the specified point. If point != position, apply-Impulse will also change the object’s angular momentum. Otherwise, only linear momentum will change.

Parameters **point** (*the point to apply the impulse to (in world coordinates)*) – the point to apply the impulse to (in world coordinates)

suspendDynamics ()

Suspends physics for this object.

restoreDynamics ()

Resumes physics for this object.

Note: The objects linear velocity will be applied from when the dynamics were suspended.

enableRigidBody ()

Enables rigid body physics for this object.

Rigid body physics allows the object to roll on collisions.

Note: This is not working with bullet physics yet.

disableRigidBody ()

Disables rigid body physics for this object.

Note: This is not working with bullet physics yet. The angular is removed but rigid body physics can still rotate it later.

setParent (*parent, compound=True, ghost=True*)

Sets this object's parent. Control the shape status with the optional compound and ghost parameters:

In that case you can control if it should be ghost or not:

Parameters

- **parent** ([KX_GameObject](#)) – new parent object.
- **compound** (*boolean*) – whether the shape should be added to the parent compound shape.
 - True: the object shape should be added to the parent compound shape.
 - False: the object should keep its individual shape.
- **ghost** (*boolean*) – whether the object should be ghost while parented.
 - True: if the object should be made ghost while parented.
 - False: if the object should be solid while parented.

Note: If the object type is sensor, it stays ghost regardless of ghost parameter

removeParent ()

Removes this objects parent.

getPhysicsId ()

Returns the user data object associated with this game object's physics controller.

getPropertyNames ()

Gets a list of all property names.

Returns All property names for this object.

Return type list

getDistanceTo (*other*)

Parameters *other* ([KX_GameObject](#) or list [x, y, z]) – a point or another [KX_GameObject](#) to measure the distance to.

Returns distance to another object or point.

Return type float

getVectTo (*other*)

Returns the vector and the distance to another object or point. The vector is normalized unless the distance is 0, in which a zero length vector is returned.

Parameters *other* ([KX_GameObject](#) or list [x, y, z]) – a point or another [KX_GameObject](#) to get the vector and distance to.

Returns (distance, globalVector(3), localVector(3))

Return type 3-tuple (float, 3-tuple (x, y, z), 3-tuple (x, y, z))

rayCastTo (*other, dist, prop*)

Look towards another point/object and find first object hit within dist that matches prop.

The ray is always casted from the center of the object, ignoring the object itself. The ray is casted towards the center of another object or an explicit [x, y, z] point. Use rayCast() if you need to retrieve the hit point

Parameters

- **other** ([KX_GameObject](#) or 3-tuple) – [x, y, z] or object towards which the ray is casted
- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to other
- **prop** (*string*) – property name that object must have; can be omitted => detect any object

Returns the first object hit or None if no object or object does not match prop

Return type [KX_GameObject](#)

rayCast (*objto, objfrom, dist, prop, face, xray, poly*)

Look from a point/object to another point/object and find first object hit within dist that matches prop. if poly is 0, returns a 3-tuple with object reference, hit point and hit normal or (None, None, None) if no hit. if poly is 1, returns a 4-tuple with in addition a [KX_PolyProxy](#) as 4th element. if poly is 2, returns a 5-tuple with in addition a 2D vector with the UV mapping of the hit point as 5th element.

```
# shoot along the axis gun-gunAim (gunAim should be collision-free)
obj, point, normal = gun.rayCast(gunAim, None, 50)
if obj:
    # do something
    pass
```

The face parameter determines the orientation of the normal.

- 0 => hit normal is always oriented towards the ray origin (as if you casted the ray from outside)
- 1 => hit normal is the real face normal (only for mesh object, otherwise face has no effect)

The ray has X-Ray capability if xray parameter is 1, otherwise the first object hit (other than self object) stops the ray. The prop and xray parameters interact as follow.

- prop off, xray off: return closest hit or no hit if there is no object on the full extend of the ray.
- prop off, xray on : idem.
- prop on, xray off: return closest hit if it matches prop, no hit otherwise.
- prop on, xray on : return closest hit matching prop or no hit if there is no object matching prop on the full extend of the ray.

The [KX_PolyProxy](#) 4th element of the return tuple when poly=1 allows to retrieve information on the polygon hit by the ray. If there is no hit or the hit object is not a static mesh, None is returned as 4th element.

The ray ignores collision-free objects and faces that dont have the collision flag enabled, you can however use ghost objects.

Parameters

- **objto** ([KX_GameObject](#) or 3-tuple) – [x, y, z] or object to which the ray is casted
- **objfrom** ([KX_GameObject](#) or 3-tuple or None) – [x, y, z] or object from which the ray is casted; None or omitted => use self object center

- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to to
- **prop** (*string*) – property name that object must have; can be omitted or “” => detect any object
- **face** (*integer*) – normal option: 1=>return face normal; 0 or omitted => normal is oriented towards origin
- **xray** (*integer*) – X-ray option: 1=>skip objects that don’t match prop; 0 or omitted => stop on first object
- **poly** (*integer*) – polygon option: 0, 1 or 2 to return a 3-, 4- or 5-tuple with information on the face hit.
 - 0 or omitted: return value is a 3-tuple (object, hitpoint, hitnormal) or (None, None, None) if no hit
 - 1: return value is a 4-tuple and the 4th element is a `KX_PolyProxy` or None if no hit or the object doesn’t use a mesh collision shape.
 - 2: return value is a 5-tuple and the 5th element is a 2-tuple (u, v) with the UV mapping of the hit point or None if no hit, or the object doesn’t use a mesh collision shape, or doesn’t have a UV mapping.

Returns

(object, hitpoint, hitnormal) or (object, hitpoint, hitnormal, polygon) or (object, hitpoint, hitnormal, polygon, hituv).

- object, hitpoint and hitnormal are None if no hit.
- polygon is valid only if the object is valid and is a static object, a dynamic object using mesh collision shape or a soft body object, otherwise it is None
- hituv is valid only if polygon is valid and the object has a UV mapping, otherwise it is None

Return type

- 3-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz))
- or 4-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz), `PolyProxy`)
- or 5-tuple (`KX_GameObject`, 3-tuple (x, y, z), 3-tuple (nx, ny, nz), `PolyProxy`, 2-tuple (u, v))

Note: The ray ignores the object on which the method is called. It is casted from/to object center or explicit [x, y, z] points.

`setCollisionMargin (margin)`

Set the objects collision margin.

Parameters **margin** (*float*) – the collision margin distance in blender units.

Note: If this object has no physics controller (a physics ID of zero), this function will raise RuntimeError.

`sendMessage (subject, body=““, to=““)`

Sends a message.

Parameters

- **subject** (*string*) – The subject of the message
- **body** (*string*) – The body of the message (optional)
- **to** (*string*) – The name of the object to send the message to (optional)

reinstancePhysicsMesh (*gameObject*, *meshObject*)

Updates the physics system with the changed mesh.

If no arguments are given the physics mesh will be re-created from the first mesh assigned to the game object.

Parameters

- **gameObject** (*string*, [KX_GameObject](#) or *None*) – optional argument, set the physics shape from this gameObjs mesh.
- **meshObject** (*string*, [MeshProxy](#) or *None*) – optional argument, set the physics shape from this mesh.

Returns True if reinstance succeeded, False if it failed.

Return type boolean

Note: If this object has instances the other instances will be updated too.

Note: The gameObject argument has an advantage that it can convert from a mesh with modifiers applied (such as subsurf).

Warning: Only triangle mesh type objects are supported currently (not convex hull)

Warning: If the object is a part of a combound object it will fail (parent or child)

Warning: Rebuilding the physics mesh can be slow, running many times per second will give a performance hit.

get (*key*, *default=None*)

Return the value matching key, or the default value if its not found. :return: The key value or a default.

class bge.types.KX_IpoActuator (*SCA_IActuator*)

IPO actuator activates an animation.

frameStart

Start frame.

Type float

frameEnd

End frame.

Type float

propName

Use this property to define the Ipo position.

Type string

framePropName

Assign this property this action current frame number.

Type string

mode
Play mode for the ipo. Can be one of *these constants*

Type integer

useIpoAsForce
Apply Ipo as a global or local force depending on the local option (dynamic objects only).

Type boolean

useIpoAdd
Ipo is added to the current loc/rot/scale in global or local coordinate according to Local flag.

Type boolean

useIpoLocal
Let the ipo acts in local coordinates, used in Force and Add mode.

Type boolean

useChildren
Update IPO on all children Objects as well.

Type boolean

class bge.types.KX_LightObject (KX_GameObject)
A Light object.

```
# Turn on a red alert light.
import bge

co = bge.logic.getCurrentController()
light = co.owner

light.energy = 1.0
light.colour = [1.0, 0.0, 0.0]
```

SPOT
A spot light source. See attribute `type`

SUN
A point light source with no attenuation. See attribute `type`

NORMAL
A point light source. See attribute `type`

type
The type of light - must be SPOT, SUN or NORMAL

layer
The layer mask that this light affects objects on.

Type bitfield

energy
The brightness of this light.

Type float

distance
The maximum distance this light can illuminate. (SPOT and NORMAL lights only).

Type float

colour

The colour of this light. Black = [0.0, 0.0, 0.0], White = [1.0, 1.0, 1.0].

Type list [r, g, b]

color

Synonym for colour.

lin_attenuation

The linear component of this light's attenuation. (SPOT and NORMAL lights only).

Type float

quad_attenuation

The quadratic component of this light's attenuation (SPOT and NORMAL lights only).

Type float

spotsize

The cone angle of the spot light, in degrees (SPOT lights only).

Type float in [0 - 180].

spotblend

Specifies the intensity distribution of the spot light (SPOT lights only).

Type float in [0 - 1]

Note: Higher values result in a more focused light source.

class bge.types.KX_MeshProxy (SCA_IObject)

A mesh object.

You can only change the vertex properties of a mesh object, not the mesh topology.

To use mesh objects effectively, you should know a bit about how the game engine handles them.

1.Mesh Objects are converted from Blender at scene load.

2.The Converter groups polygons by Material. This means they can be sent to the renderer efficiently. A material holds:

- (a)The texture.
- (b)The Blender material.
- (c)The Tile properties
- (d)The face properties - (From the “Texture Face” panel)
- (e)Transparency & z sorting
- (f)Light layer
- (g)Polygon shape (triangle/quad)
- (h)Game Object

3.Verticies will be split by face if necessary. Verticies can only be shared between faces if:

- (a)They are at the same position
- (b)UV coordinates are the same
- (c)Their normals are the same (both polygons are “Set Smooth”)
- (d)They are the same colour, for example: a cube has 24 verticies: 6 faces with 4 verticies per face.

The correct method of iterating over every `KX_VertexProxy` in a game object

```
import GameLogic

co = GameLogic.getCurrentController()
obj = co.owner

m_i = 0
mesh = obj.getMesh(m_i) # There can be more than one mesh...
while mesh != None:
    for mat in range(mesh.getNumMaterials()):
        for v_index in range(mesh.getVertexArrayLength(mat)):
            vertex = mesh.getVertex(mat, v_index)
            # Do something with vertex here...
            # ... eg: colour the vertex red.
            vertex.colour = [1.0, 0.0, 0.0, 1.0]
    m_i += 1
    mesh = obj.getMesh(m_i)
```

materials

Type list of `KX_BlenderMaterial` or `KX_PolygonMaterial` types

numPolygons

Type integer

numMaterials

Type integer

getNumMaterials()

Returns number of materials associated with this object

Return type integer

getMaterialName (matid)

Gets the name of the specified material.

Parameters `matid` (integer) – the specified material.

Returns the attached material name.

Return type string

getTextureName (matid)

Gets the name of the specified material's texture.

Parameters `matid` (integer) – the specified material

Returns the attached material's texture name.

Return type string

getVertexArrayLength (matid)

Gets the length of the vertex array associated with the specified material.

There is one vertex array for each material.

Parameters `matid` (integer) – the specified material

Returns the number of vertices in the vertex array.

Return type integer

getVertex (matid, index)

Gets the specified vertex from the mesh object.

Parameters

- **matid** (*integer*) – the specified material
- **index** (*integer*) – the index into the vertex array.

Returns a vertex object.

Return type [KX_VertexProxy](#)

getNumPolygons ()

Returns The number of polygon in the mesh.

Return type integer

getPolygon (index)

Gets the specified polygon from the mesh.

Parameters **index** (*integer*) – polygon number

Returns a polygon object.

Return type PolyProxy

class bge.types.SCA_MouseSensor (SCA_ISensor)

Mouse Sensor logic brick.

position

current [x, y] coordinates of the mouse, in frame coordinates (pixels).

Type [integer, interger]

mode

sensor mode.

Type integer

- KX_MOUSESENSORMODE_LEFTBUTTON(1)
- KX_MOUSESENSORMODE_MIDDLEBUTTON(2)
- KX_MOUSESENSORMODE_RIGHTBUTTON(3)
- KX_MOUSESENSORMODE_WHEELUP(4)
- KX_MOUSESENSORMODE_WHEELEDOWN(5)
- KX_MOUSESENSORMODE_MOVEMENT(6)

getButtonStatus (button)

Get the mouse button status.

Parameters **button** (*int*) – The code that represents the key you want to get the state of, use one of [these constants](#)

Returns The state of the given key, can be one of [these constants](#)

Return type int

class bge.types.KX_MouseFocusSensor (SCA_MouseSensor)

The mouse focus sensor detects when the mouse is over the current game object.

The mouse focus sensor works by transforming the mouse coordinates from 2d device space to 3d space then raycasting away from the camera.

raySource

The worldspace source of the ray (the view position).

Type list (vector of 3 floats)

rayTarget

The worldspace target of the ray.

Type list (vector of 3 floats)

rayDirection

The `rayTarget` - `raySource` normalized.

Type list (normalized vector of 3 floats)

hitObject

the last object the mouse was over.

Type `KX_GameObject` or None

hitPosition

The worldspace position of the ray intersecton.

Type list (vector of 3 floats)

hitNormal

the worldspace normal from the face at point of intersection.

Type list (normalized vector of 3 floats)

hitUV

the UV coordinates at the point of intersection.

Type list (vector of 2 floats)

If the object has no UV mapping, it returns [0, 0].

The UV coordinates are not normalized, they can be < 0 or > 1 depending on the UV mapping.

usePulseFocus

When enabled, moving the mouse over a different object generates a pulse. (only used when the ‘Mouse Over Any’ sensor option is set).

Type boolean

class bge.types.KX_TouchSensor (SCA_ISensor)

Touch sensor detects collisions between objects.

propName

The property or material to collide with.

Type string

useMaterial

Determines if the sensor is looking for a property or material. KX_True = Find material; KX_False = Find property.

Type boolean

usePulseCollision

When enabled, changes to the set of colliding objects generate a pulse.

Type boolean

hitObject

The last collided object. (read-only).

Type `KX_GameObject` or None

hitObjectList

A list of colliding objects. (read-only).

Type `CListValue` of `KX_GameObject`

class bge.types.KX_NearSensor (KX_TouchSensor)

A near sensor is a specialised form of touch sensor.

distance

The near sensor activates when an object is within this distance.

Type float

resetDistance

The near sensor deactivates when the object exceeds this distance.

Type float

class bge.types.KX_NetworkMessageActuator (SCA_IActuator)

Message Actuator

propName

Messages will only be sent to objects with the given property name.

Type string

subject

The subject field of the message.

Type string

body

The body of the message.

Type string

usePropBody

Send a property instead of a regular body message.

Type boolean

class bge.types.KX_NetworkMessageSensor (SCA_ISensor)

The Message Sensor logic brick.

Currently only loopback (local) networks are supported.

subject

The subject the sensor is looking for.

Type string

frameMessageCount

The number of messages received since the last frame. (read-only).

Type integer

subjects

The list of message subjects received. (read-only).

Type list of strings

bodies

The list of message bodies received. (read-only).

Type list of strings

class bge.types.KX_ObjectActuator (SCA_IActuator)

The object actuator (“Motion Actuator”) applies force, torque, displacement, angular displacement, velocity, or angular velocity to an object. Servo control allows to regulate force to achieve a certain speed target.

force

The force applied by the actuator.

Type list [x, y, z]

useLocalForce

A flag specifying if the force is local.

Type boolean

torque

The torque applied by the actuator.

Type list [x, y, z]

useLocalTorque

A flag specifying if the torque is local.

Type boolean

dLoc

The displacement vector applied by the actuator.

Type list [x, y, z]

useLocalDLoc

A flag specifying if the dLoc is local.

Type boolean

dRot

The angular displacement vector applied by the actuator

Type list [x, y, z]

Note: Since the displacement is applied every frame, you must adjust the displacement based on the frame rate, or your game experience will depend on the player’s computer speed.

useLocalDRot

A flag specifying if the dRot is local.

Type boolean

linV

The linear velocity applied by the actuator.

Type list [x, y, z]

useLocalLinV

A flag specifying if the linear velocity is local.

Type boolean

Note: This is the target speed for servo controllers.

angV

The angular velocity applied by the actuator.

Type list [x, y, z]

useLocalAngV

A flag specifying if the angular velocity is local.

Type boolean

damping

The damping parameter of the servo controller.

Type short

forceLimitX

The min/max force limit along the X axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

forceLimitY

The min/max force limit along the Y axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

forceLimitZ

The min/max force limit along the Z axis and activates or deactivates the limits in the servo controller.

Type list [min(float), max(float), bool]

pid

The PID coefficients of the servo controller.

Type list of floats [proportional, integral, derivate]

reference

The object that is used as reference to compute the velocity for the servo controller.

Type [KX_GameObject](#) or None

class bge.types.KX_ParentActuator (SCA_IActuator)

The parent actuator can set or remove an objects parent object.

object

the object this actuator sets the parent too.

Type [KX_GameObject](#) or None

mode

The mode of this actuator.

Type integer from 0 to 1.

compound

Whether the object shape should be added to the parent compound shape when parenting.

Effective only if the parent is already a compound shape.

Type boolean

ghost

Whether the object should be made ghost when parenting Effective only if the shape is not added to the parent compound shape.

Type boolean

class bge.types.KX_PhysicsObjectWrapper (PyObjectPlus)

KX_PhysicsObjectWrapper

setActive (active)

Set the object to be active.

Parameters **active** (*boolean*) – set to True to be active

setAngularVelocity (*x, y, z, local*)

Set the angular velocity of the object.

Parameters

- **x** (*float*) – angular velocity for the x-axis
- **y** (*float*) – angular velocity for the y-axis
- **z** (*float*) – angular velocity for the z-axis
- **local** (*boolean*) – set to True for local axis

setLinearVelocity (*x, y, z, local*)

Set the linear velocity of the object.

Parameters

- **x** (*float*) – linear velocity for the x-axis
- **y** (*float*) – linear velocity for the y-axis
- **z** (*float*) – linear velocity for the z-axis
- **local** (*boolean*) – set to True for local axis

class `bge.types.KX_PolyProxy (SCA_IObject)`

A polygon holds the index of the vertex forming the polygon.

Note: The polygon attributes are read-only, you need to retrieve the vertex proxy if you want to change the vertex settings.

matname

The name of polygon material, empty if no material.

Type string

material

The material of the polygon.

Type `KX_PolygonMaterial` or `KX_BlenderMaterial`

texture

The texture name of the polygon.

Type string

matid

The material index of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v1

vertex index of the first vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v2

vertex index of the second vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v3

vertex index of the third vertex of the polygon, use this to retrieve vertex proxy from mesh proxy.

Type integer

v4

Vertex index of the fourth vertex of the polygon, 0 if polygon has only 3 vertex Use this to retrieve vertex proxy from mesh proxy.

Type integer

visible

visible state of the polygon: 1=visible, 0=invisible.

Type integer

collide

collide state of the polygon: 1=receives collision, 0=collision free.

Type integer

getMaterialName()

Returns the polygon material name with MA prefix

Returns material name

Return type string

getMaterial()

Returns The polygon material

Return type KX_PolygonMaterial or KX_BlenderMaterial

getTextureName()

Returns The texture name

Return type string

getMaterialIndex()

Returns the material bucket index of the polygon. This index and the ones returned by getVertexIndex() are needed to retrieve the vertex proxy from MeshProxy.

Returns the material index in the mesh

Return type integer

getNumVertex()

Returns the number of vertex of the polygon.

Returns number of vertex, 3 or 4.

Return type integer

isVisible()

Returns whether the polygon is visible or not

Returns 0=invisible, 1=visible

Return type boolean

isCollider()

Returns whether the polygon is receives collision or not

Returns 0=collision free, 1=receives collision

Return type integer

getVertexIndex(vertex)

Returns the mesh vertex index of a polygon vertex This index and the one returned by getMaterialIndex() are needed to retrieve the vertex proxy from MeshProxy.

Parameters

- **vertex** – index of the vertex in the polygon: 0->3
- **vertex** – integer

Returns mesh vertex index**Return type** integer**getMesh()**

Returns a mesh proxy

Returns mesh proxy**Return type** MeshProxy**class bge.types.KX_PolygonMaterial (PyObjectPlus)**

This is the interface to materials in the game engine.

Materials define the render state to be applied to mesh objects.

Warning: Some of the methods/variables are CObjects. If you mix these up, you will crash blender.

This example requires PyOpenGL and GLEWPy

```
import GameLogic
import OpenGL
from OpenGL.GL import *
from OpenGL.GLU import *
import glew
from glew import *

glewInit()

vertex_shader = """
void main(void)
{
    gl_Position = ftransform();
}
"""

fragment_shader ="""

void main(void)
{
    gl_FragColor = vec4(1.0, 0.0, 0.0, 1.0);
}
"""

class MyMaterial:
    def __init__(self):
        self.pass_no = 0
        # Create a shader
        self.m_program = glCreateProgramObjectARB()
        # Compile the vertex shader
        self.shader(GL_VERTEX_SHADER_ARB, (vertex_shader))
        # Compile the fragment shader
        self.shader(GL_FRAGMENT_SHADER_ARB, (fragment_shader))
        # Link the shaders together
```

```
        self.link()

def PrintInfoLog(self, tag, object):
    """
    PrintInfoLog prints the GLSL compiler log
    """
    print "Tag:    def PrintGLError(self, tag = ""):

def PrintGLError(self, tag = ""):
    """
    Prints the current GL error status
    """
    if len(tag):
        print tag
    err = glGetError()
    if err != GL_NO_ERROR:
        print "GL Error: %s\n%(gluErrorString(err))

def shader(self, type, shaders):
    """
    shader compiles a GLSL shader and attaches it to the current
    program.

    type should be either GL_VERTEX_SHADER_ARB or GL_FRAGMENT_SHADER_ARB
    shaders should be a sequence of shader source to compile.
    """
    # Create a shader object
    shader_object = glCreateShaderObjectARB(type)

    # Add the source code
    glShaderSourceARB(shader_object, len(shaders), shaders)

    # Compile the shader
    glCompileShaderARB(shader_object)

    # Print the compiler log
    self.PrintInfoLog("vertex shader", shader_object)

    # Check if compiled, and attach if it did
    compiled = glGetObjectParameterivARB(shader_object, GL_OBJECT_COMPILE_STATUS_ARB)
    if compiled:
        glAttachObjectARB(self.m_program, shader_object)

    # Delete the object (glAttachObjectARB makes a copy)
    glDeleteObjectARB(shader_object)

    # print the gl error log
    self.PrintGLError()

def link(self):
    """
    Links the shaders together.
    """
    # clear error indicator
    glGetError()

    glLinkProgramARB(self.m_program)
```

```
    self.PrintInfoLog("link", self.m_program)

linked = glGetObjectParameterivARB(self.m_program, GL_OBJECT_LINK_STATUS_ARB)
if not linked:
    print "Shader failed to link"
    return

glValidateProgramARB(self.m_program)
valid = glGetObjectParameterivARB(self.m_program, GL_OBJECT_VALIDATE_STATUS_ARB)
if not valid:
    print "Shader failed to validate"
    return

def activate(self, rasty, cachingInfo, mat):
    self.pass_no+=1
    if (self.pass_no == 1):
        glDisable(GL_COLOR_MATERIAL)
        glUseProgramObjectARB(self.m_program)
    return True

    glEnable(GL_COLOR_MATERIAL)
    glUseProgramObjectARB(0)
    self.pass_no = 0
    return False

obj = GameLogic.getCurrentController().owner

mesh = obj.meshes[0]

for mat in mesh.materials:
    mat.setCustomMaterial(MyMaterial())
    print mat.texture

texture
    Texture name.

    Type string (read-only)

gl_texture
    OpenGL texture handle (eg for glBindTexture(GL_TEXTURE_2D, gl_texture).

    Type integer (read-only)

material
    Material name.

    Type string (read-only)

tface
    Texture face properties.

    Type CObject (read-only)

tile
    Texture is tiling.

    Type boolean

tilexrep
    Number of tile repetitions in x direction.

    Type integer
```

tileyrep

Number of tile repetitions in y direction.

Type integer

drawingmode

Drawing mode for the material. - 2 (drawingmode & 4) Textured - 4 (drawingmode & 16) Light - 14 (drawingmode & 16384) 3d Polygon Text.

Type bitfield

transparent

This material is transparent. All meshes with this material will be rendered after non transparent meshes from back to front.

Type boolean

zsort

Transparent polygons in meshes with this material will be sorted back to front before rendering. Non-Transparent polygons will be sorted front to back before rendering.

Type boolean

lightlayer

Light layers this material affects.

Type bitfield.

triangle

Mesh data with this material is triangles. It's probably not safe to change this.

Type boolean

diffuse

The diffuse colour of the material. black = [0.0, 0.0, 0.0] white = [1.0, 1.0, 1.0].

Type list [r, g, b]

specular

The specular colour of the material. black = [0.0, 0.0, 0.0] white = [1.0, 1.0, 1.0].

Type list [r, g, b]

shininess

The shininess (specular exponent) of the material. 0.0 <= shininess <= 128.0.

Type float

specularity

The amount of specular of the material. 0.0 <= specularity <= 1.0.

Type float

updateTexture (tface, rasty)

Updates a realtime animation.

Parameters

- **tface** (*CObject*) – Texture face (eg mat.tface)
- **rasty** (*CObject*) – Rasterizer

setTexture (tface)

Sets texture render state.

Parameters **tface** (*CObject*) – Texture face

```
mat.setTexture(mat.tface)
```

activate (*rasty, cachingInfo*)

Sets material parameters for this object for rendering.

Material Parameters set:

- 1.Texture
- 2.Backface culling
- 3.Line drawing
- 4.Specular Colour
- 5.Shininess
- 6.Diffuse Colour
- 7.Polygon Offset.

Parameters

- **rasty** (*CObject*) – Rasterizer instance.
- **cachingInfo** (*CObject*) – Material cache instance.

setCustomMaterial (*material*)

Sets the material state setup object.

Using this method, you can extend or completely replace the gameengine material to do your own advanced multipass effects.

Use this method to register your material class. Instead of the normal material, your class's activate method will be called just before rendering the mesh. This should setup the texture, material, and any other state you would like. It should return True to render the mesh, or False if you are finished. You should clean up any state Blender does not set before returning False.

Activate Method Definition:

```
def activate(self, rasty, cachingInfo, material):
```

Parameters **material** (*instance*) – The material object.

```
class PyMaterial:  
    def __init__(self):  
        self.pass_no = -1  
  
    def activate(self, rasty, cachingInfo, material):  
        # Activate the material here.  
        #  
        # The activate method will be called until it returns False.  
        # Every time the activate method returns True the mesh will  
        # be rendered.  
        #  
        # rasty is a CObject for passing to material.updateTexture()  
        # and material.activate()  
        # cachingInfo is a CObject for passing to material.activate()  
        # material is the KX_PolygonMaterial instance this material  
        # was added to
```

```
# default material properties:  
self.pass_no += 1  
if self.pass_no == 0:  
    material.activate(rasty, cachingInfo)  
    # Return True to do this pass  
    return True  
  
# clean up and return False to finish.  
self.pass_no = -1  
return False  
  
# Create a new Python Material and pass it to the renderer.  
mat.setCustomMaterial(PyMaterial())  
  
class bge.types.KX_RadarSensor (KX_NearSensor)  
    Radar sensor is a near sensor with a conical sensor object.  
  
    coneOrigin  
        The origin of the cone with which to test. The origin is in the middle of the cone. (read-only).  
        Type list of floats [x, y, z]  
  
    coneTarget  
        The center of the bottom face of the cone with which to test. (read-only).  
        Type list of floats [x, y, z]  
  
    distance  
        The height of the cone with which to test.  
        Type float  
  
    angle  
        The angle of the cone (in degrees) with which to test.  
        Type float from 0 to 360  
  
    axis  
        The axis on which the radar cone is cast.  
        Type integer from 0 to 5  
        KX_RADAR_AXIS_POS_X, KX_RADAR_AXIS_POS_Y, KX_RADAR_AXIS_POS_Z,  
        KX_RADAR_AXIS_NEG_X, KX_RADAR_AXIS_NEG_Y, KX_RADAR_AXIS_NEG_Z  
  
    getConeHeight ()  
        Returns The height of the cone with which to test.  
        Return type float  
  
class bge.types.KX_RaySensor (SCA_ISensor)  
    A ray sensor detects the first object in a given direction.  
  
    propName  
        The property the ray is looking for.  
        Type string  
  
    range  
        The distance of the ray.  
        Type float
```

useMaterial

Whether or not to look for a material (false = property).

Type boolean

useXRay

Whether or not to use XRay.

Type boolean

hitObject

The game object that was hit by the ray. (read-only).

Type KX_GameObject

hitPosition

The position (in worldcoordinates) where the object was hit by the ray. (read-only).

Type list [x, y, z]

hitNormal

The normal (in worldcoordinates) of the object at the location where the object was hit by the ray. (read-only).

Type list [x, y, z]

rayDirection

The direction from the ray (in worldcoordinates). (read-only).

Type list [x, y, z]

axis

The axis the ray is pointing on.

Type integer from 0 to 5

- KX_RAY_AXIS_POS_X
- KX_RAY_AXIS_POS_Y
- KX_RAY_AXIS_POS_Z
- KX_RAY_AXIS_NEG_X
- KX_RAY_AXIS_NEG_Y
- KX_RAY_AXIS_NEG_Z

class bge.types.KX_SCA_AddObjectActuator (SCA_IActuator)

Edit Object Actuator (in Add Object Mode)

Warning: An Add Object actuator will be ignored if at game start, the linked object doesn't exist (or is empty) or the linked object is in an active layer.

Error: GameObject 'Name' has a AddObjectActuator 'ActuatorName' without object (in 'nonactive'

object

the object this actuator adds.

Type KX_GameObject or None

objectLastCreated

the last added object from this actuator (read-only).

Type `KX_GameObject` or None

time

the lifetime of added objects, in frames. Set to 0 to disable automatic deletion.

Type integer

linearVelocity

the initial linear velocity of added objects.

Type list [vx, vy, vz]

angularVelocity

the initial angular velocity of added objects.

Type list [vx, vy, vz]

instantAddObject()

adds the object without needing to calling `SCA_PythonController.activate()`

Note: Use `objectLastCreated` to get the newly created object.

class `bge.types.KX_SCA_DynamicActuator (SCA_IActuator)`

Dynamic Actuator.

mode

Type integer

the type of operation of the actuator, 0-4

- `KX_DYN_RESTORE_DYNAMICS(0)`
- `KX_DYN_DISABLE_DYNAMICS(1)`
- `KX_DYN_ENABLE_RIGID_BODY(2)`
- `KX_DYN_DISABLE_RIGID_BODY(3)`
- `KX_DYN_SET_MASS(4)`

mass

the mass value for the `KX_DYN_SET_MASS` operation.

Type float

class `bge.types.KX_SCA_EndObjectActuator (SCA_IActuator)`

Edit Object Actuator (in End Object mode)

This actuator has no python methods.

class `bge.types.KX_SCA_ReplaceMeshActuator (SCA_IActuator)`

Edit Object actuator, in Replace Mesh mode.

Warning: Replace mesh actuators will be ignored if at game start, the named mesh doesn't exist.

This will generate a warning in the console

Error: GameObject 'Name' ReplaceMeshActuator 'ActuatorName' without object

```
# Level-of-detail
# Switch a game object's mesh based on its depth in the camera view.
# +-----+ +-----+ +-----+
# | Always | Python | Edit Object (Replace Mesh) LOD.Mesh |
```

```

# +-----+ +-----+ +-----+
import GameLogic

# List detail meshes here
# Mesh (name, near, far)
# Meshes overlap so that they don't 'pop' when on the edge of the distance.
meshes = ((".Hi", 0.0, -20.0),
           ("Med", -15.0, -50.0),
           ("Lo", -40.0, -100.0)
       )

co = GameLogic.getCurrentController()
obj = co.owner
act = co.actuators["LOD." + obj.name]
cam = GameLogic.getCurrentScene().active_camera

def Depth(pos, plane):
    return pos[0]*plane[0] + pos[1]*plane[1] + pos[2]*plane[2] + plane[3]

# Depth is negative and decreasing further from the camera
depth = Depth(obj.position, cam.world_to_camera[2])

newmesh = None
curmesh = None
# Find the lowest detail mesh for depth
for mesh in meshes:
    if depth < mesh[1] and depth > mesh[2]:
        newmesh = mesh
    if "ME" + obj.name + mesh[0] == act.getMesh():
        curmesh = mesh

if newmesh != None and "ME" + obj.name + newmesh[0] != act.getMesh():
    # The mesh is a different mesh - switch it.
    # Check the current mesh is not a better fit.
    if curmesh == None or curmesh[1] < depth or curmesh[2] > depth:
        act.mesh = obj.getName() + newmesh[0]
        GameLogic.addActiveActuator(act, True)

mesh
    MeshProxy or the name of the mesh that will replace the current one.

    Set to None to disable actuator.

    Type MeshProxy or None if no mesh is set

useDisplayMesh
    when true the displayed mesh is replaced.

    Type boolean

usePhysicsMesh
    when true the physics mesh is replaced.

    Type boolean

instantReplaceMesh()
    Immediately replace mesh without delay.

class bge.types.KX_Scene (PyObjectPlus)
    An active scene that gives access to objects, cameras, lights and scene attributes.

```

The activity culling stuff is supposed to disable logic bricks when their owner gets too far from the active camera. It was taken from some code lurking at the back of KX_Scene - who knows what it does!

```
import GameLogic

# get the scene
scene = GameLogic.getCurrentScene()

# print all the objects in the scene
for obj in scene.objects:
    print obj.name

# get an object named 'Cube'
obj = scene.objects["Cube"]

# get the first object in the scene.
obj = scene.objects[0]

# Get the depth of an object in the camera view.
import GameLogic

obj = GameLogic.getCurrentController().owner
cam = GameLogic.getCurrentScene().active_camera

# Depth is negative and decreasing further from the camera
depth = obj.position[0]*cam.world_to_camera[2][0] + obj.position[1]*cam.world_to_camera[2][1] +
```

@bug: All attributes are read only at the moment.

name

The scene's name, (read-only).

Type string

objects

A list of objects in the scene, (read-only).

Type CListValue of KX_GameObject

objectsInactive

A list of objects on background layers (used for the addObject actuator), (read-only).

Type CListValue of KX_GameObject

lights

A list of lights in the scene, (read-only).

Type CListValue of KX_LightObject

cameras

A list of cameras in the scene, (read-only).

Type CListValue of KX_Camera

active_camera

The current active camera.

Type KX_Camera

Note: This can be set directly from python to avoid using the KX_SceneActuator.

suspended

True if the scene is suspended, (read-only).

Type boolean

activity_culling

True if the scene is activity culling.

Type boolean

activity_culling_radius

The distance outside which to do activity culling. Measured in manhattan distance.

Type float

dbvt_culling

True when Dynamic Bounding box Volume Tree is set (read-only).

Type boolean

pre_draw

A list of callables to be run before the render step.

Type list

post_draw

A list of callables to be run after the render step.

Type list

addObject (object, other, time=0)

Adds an object to the scene like the Add Object Actuator would.

Parameters

- **object** ([KX_GameObject](#) or string) – The object to add
- **other** ([KX_GameObject](#) or string) – The object's center to use when adding the object
- **time** (*integer*) – The lifetime of the added object, in frames. A time of 0 means the object will last forever.

Returns The newly added object.

Return type [KX_GameObject](#)

end()

Removes the scene from the game.

restart()

Restarts the scene.

replace (scene)

Replaces this scene with another one.

Parameters **scene** (*string*) – The name of the scene to replace this scene with.

suspend()

Suspends this scene.

resume()

Resume this scene.

get (key, default=None)

Return the value matching key, or the default value if its not found. :return: The key value or a default.

class bge.types.KX_SceneActuator (SCA_IActuator)
Scene Actuator logic brick.

Warning: Scene actuators that use a scene name will be ignored if at game start, the named scene doesn't exist or is empty

This will generate a warning in the console:

```
Error: GameObject 'Name' has a SceneActuator 'ActuatorName' (SetScene) without scene
```

scene

the name of the scene to change to/overlay/underlay/remove/suspend/resume.

Type string

camera

the camera to change to.

Type KX_Camera on read, string or KX_Camera on write

Note: When setting the attribute, you can use either a KX_Camera or the name of the camera.

useRestart

Set flag to True to restart the scene.

Type boolean

mode

The mode of the actuator.

Type integer from 0 to 5.

class bge.types.KX_SoundActuator (SCA_IActuator)
Sound Actuator.

The startSound, pauseSound and stopSound do not require the actuator to be activated - they act instantly provided that the actuator has been activated once at least.

fileName

The filename of the sound this actuator plays.

Type string

volume

The volume (gain) of the sound.

Type float

pitch

The pitch of the sound.

Type float

rollOffFactor

The roll off factor. Rolloff defines the rate of attenuation as the sound gets further away.

Type float

looping

The loop mode of the actuator.

Type integer

position

The position of the sound as a list: [x, y, z].

Type float array

velocity

The velocity of the emitter as a list: [x, y, z]. The relative velocity to the observer determines the pitch.
List of 3 floats: [x, y, z].

Type float array

orientation

The orientation of the sound. When setting the orientation you can also use quaternion [float, float, float, float] or euler angles [float, float, float].

Type 3x3 matrix [[float]]

mode

The operation mode of the actuator. Can be one of *these constants*

Type integer

class bge.types.KX_StateActuator (SCA_IActuator)

State actuator changes the state mask of parent object.

operation

Type of bit operation to be applied on object state mask.

You can use one of *these constants*

Type integer

mask

Value that defines the bits that will be modified by the operation.

The bits that are 1 in the mask will be updated in the object state.

The bits that are 0 are will be left unmodified expect for the Copy operation which copies the mask to the object state.

Type integer

class bge.types.KX_TrackToActuator (SCA_IActuator)

Edit Object actuator in Track To mode.

Warning: Track To Actuators will be ignored if at game start, the object to track is invalid.
This will generate a warning in the console:

```
GameObject 'Name' no object in EditObjectActuator 'ActuatorName'
```

object

the object this actuator tracks.

Type KX_GameObject or None

time

the time in frames with which to delay the tracking motion.

Type integer

use3D

the tracking motion to use 3D.

Type boolean

```
class bge.types.KX_VehicleWrapper (PyObjectPlus)
KX_VehicleWrapper

TODO - description

addWheel (wheel, attachPos, attachDir, axleDir, suspensionRestLength, wheelRadius, hasSteering)
Add a wheel to the vehicle

Parameters

- wheel (KX\_GameObject or a KX_GameObject name) – The object to use as a wheel.
- attachPos (vector of 3 floats) – The position that this wheel will attach to.
- attachDir (vector of 3 floats) – The direction this wheel points.
- axleDir (vector of 3 floats) – The direction of this wheels axle.
- suspensionRestLength (float) – TODO - Description
- wheelRadius (float) – The size of the wheel.

applyBraking (force, wheelIndex)
Apply a braking force to the specified wheel

Parameters

- force (float) – the brake force
- wheelIndex (integer) – index of the wheel where the force needs to be applied

applyEngineForce (force, wheelIndex)
Apply an engine force to the specified wheel

Parameters

- force (float) – the engine force
- wheelIndex (integer) – index of the wheel where the force needs to be applied

getConstraintId ()
Get the constraint ID

Returns the constraint id

Return type integer

getConstraintType ()
Returns the constraint type.

Returns constraint type

Return type integer

getNumWheels ()
Returns the number of wheels.

Returns the number of wheels for this vehicle

Return type integer

getWheelOrientationQuaternion (wheelIndex)
Returns the wheel orientation as a quaternion.

Parameters wheelIndex (integer) – the wheel index

Returns TODO Description
```

Return type TODO - type should be quat as per method name but from the code it looks like a matrix

getWheelPosition (*wheelIndex*)

Returns the position of the specified wheel

Parameters **wheelIndex** (*integer*) – the wheel index

Returns position vector

Return type list[x, y, z]

getWheelRotation (*wheelIndex*)

Returns the rotation of the specified wheel

Parameters **wheelIndex** (*integer*) – the wheel index

Returns the wheel rotation

Return type float

setRollInfluence (*rollInfluence*, *wheelIndex*)

Set the specified wheel's roll influence. The higher the roll influence the more the vehicle will tend to roll over in corners.

Parameters

- **rollInfluence** (*float*) – the wheel roll influence
- **wheelIndex** (*integer*) – the wheel index

setSteeringValue (*steering*, *wheelIndex*)

Set the specified wheel's steering

Parameters

- **steering** (*float*) – the wheel steering
- **wheelIndex** (*integer*) – the wheel index

setSuspensionCompression (*compression*, *wheelIndex*)

Set the specified wheel's compression

Parameters

- **compression** (*float*) – the wheel compression
- **wheelIndex** (*integer*) – the wheel index

setSuspensionDamping (*damping*, *wheelIndex*)

Set the specified wheel's damping

Parameters

- **damping** (*float*) – the wheel damping
- **wheelIndex** (*integer*) – the wheel index

setSuspensionStiffness (*stiffness*, *wheelIndex*)

Set the specified wheel's stiffness

Parameters

- **stiffness** (*float*) – the wheel stiffness
- **wheelIndex** (*integer*) – the wheel index

setTyreFriction (*friction, wheelIndex*)

Set the specified wheel's tyre friction

Parameters

- **friction** (*float*) – the tyre friction
- **wheelIndex** (*integer*) – the wheel index

class bge.types.KX_VertexProxy (SCA_IObject)

A vertex holds position, UV, colour and normal information.

Note: The physics simulation is NOT currently updated - physics will not respond to changes in the vertex position.

XYZ

The position of the vertex.

Type list [x, y, z]

UV

The texture coordinates of the vertex.

Type list [u, v]

normal

The normal of the vertex.

Type list [nx, ny, nz]

colour

The colour of the vertex.

Type list [r, g, b, a]

Black = [0.0, 0.0, 0.0, 1.0], White = [1.0, 1.0, 1.0, 1.0]

color

Synonym for colour.

x

The x coordinate of the vertex.

Type float

y

The y coordinate of the vertex.

Type float

z

The z coordinate of the vertex.

Type float

u

The u texture coordinate of the vertex.

Type float

v

The v texture coordinate of the vertex.

Type float

u2

The second u texture coordinate of the vertex.

Type float

v2

The second v texture coordinate of the vertex.

Type float

r

The red component of the vertex colour. $0.0 \leq r \leq 1.0$.

Type float

g

The green component of the vertex colour. $0.0 \leq g \leq 1.0$.

Type float

b

The blue component of the vertex colour. $0.0 \leq b \leq 1.0$.

Type float

a

The alpha component of the vertex colour. $0.0 \leq a \leq 1.0$.

Type float

getXYZ()

Gets the position of this vertex.

Returns this vertexes position in local coordinates.

Return type list [x, y, z]

setXYZ(pos)

Sets the position of this vertex.

Type list [x, y, z]

Parameters pos – the new position for this vertex in local coordinates.

getUV()

Gets the UV (texture) coordinates of this vertex.

Returns this vertexes UV (texture) coordinates.

Return type list [u, v]

setUV(uv)

Sets the UV (texture) coordinates of this vertex.

Type list [u, v]

getUV2()

Gets the 2nd UV (texture) coordinates of this vertex.

Returns this vertexes UV (texture) coordinates.

Return type list [u, v]

setUV2(uv, unit)

Sets the 2nd UV (texture) coordinates of this vertex.

Type list [u, v]

Parameters

- **unit** – optional argument, FLAT==1, SECOND_UV==2, defaults to SECOND_UV

- **unit** – integer

getRGBA()

Gets the colour of this vertex.

The colour is represented as four bytes packed into an integer value. The colour is packed as RGBA.

Since Python offers no way to get each byte without shifting, you must use the struct module to access colour in a machine independent way.

Because of this, it is suggested you use the r, g, b and a attributes or the colour attribute instead.

```
import struct;
col = struct.unpack('4B', struct.pack('I', v.getRGBA()))
# col = (r, g, b, a)
# black = (0, 0, 0, 255)
# white = (255, 255, 255, 255)
```

Returns packed colour. 4 byte integer with one byte per colour channel in RGBA format.

Return type integer

setRGBA(col)

Sets the colour of this vertex.

See getRGBA() for the format of col, and its relevant problems. Use the r, g, b and a attributes or the colour attribute instead.

setRGBA() also accepts a four component list as argument col. The list represents the colour as [r, g, b, a] with black = [0.0, 0.0, 0.0, 1.0] and white = [1.0, 1.0, 1.0, 1.0]

```
v.setRGBA(0xff0000ff) # Red
v.setRGBA(0xff00ff00) # Green on little endian, transparent purple on big endian
v.setRGBA([1.0, 0.0, 0.0, 1.0]) # Red
v.setRGBA([0.0, 1.0, 0.0, 1.0]) # Green on all platforms.
```

Parameters **col** (integer or list [r, g, b, a]) – the new colour of this vertex in packed RGBA format.

getNormal()

Gets the normal vector of this vertex.

Returns normalised normal vector.

Return type list [nx, ny, nz]

setNormal(normal)

Sets the normal vector of this vertex.

Type sequence of floats [r, g, b]

Parameters **normal** – the new normal of this vertex.

```
class bge.types.KX_VisibilityActuator(SCA_IActuator)
Visibility Actuator.
```

visibility

whether the actuator makes its parent object visible or invisible.

Type boolean

useOcclusion

whether the actuator makes its parent object an occluder or not.

Type boolean

useRecursion

whether the visibility/occlusion should be propagated to all children of the object.

Type boolean

class bge.types.SCA_2DFilterActuator (SCA_IActuator)

Create, enable and disable 2D filters

The following properties don't have an immediate effect. You must active the actuator to get the result. The actuator is not persistent: it automatically stops itself after setting up the filter but the filter remains active. To stop a filter you must activate the actuator with 'type' set to [RAS_2DFILTER_DISABLED](#) or [RAS_2DFILTER_NOFILTER](#).

shaderText

shader source code for custom shader.

Type string

disableMotionBlur

action on motion blur: 0=enable, 1=disable.

Type integer

mode

Type of 2D filter, use one of [these constants](#)

Type integer

passNumber

order number of filter in the stack of 2D filters. Filters are executed in increasing order of passNb.

Only be one filter can be defined per passNb.

Type integer (0-100)

value

argument for motion blur filter.

Type float (0.0-100.0)

class bge.types.SCA_ANDController (SCA_IController)

An AND controller activates only when all linked sensors are activated.

There are no special python methods for this controller.

class bge.types.SCA_ActuatorSensor (SCA_ISensor)

Actuator sensor detect change in actuator state of the parent object. It generates a positive pulse if the corresponding actuator is activated and a negative pulse if the actuator is deactivated.

actuator

the name of the actuator that the sensor is monitoring.

Type string

class bge.types.SCA_AlwaysSensor (SCA_ISensor)

This sensor is always activated.

class bge.types.SCA_DelaySensor (SCA_ISensor)

The Delay sensor generates positive and negative triggers at precise time, expressed in number of frames. The delay parameter defines the length of the initial OFF period. A positive trigger is generated at the end of this period.

The duration parameter defines the length of the ON period following the OFF period. There is a negative trigger at the end of the ON period. If duration is 0, the sensor stays ON and there is no negative trigger.

The sensor runs the OFF-ON cycle once unless the repeat option is set: the OFF-ON cycle repeats indefinitely (or the OFF cycle if duration is 0).

Use `SCA_ISensor.reset` at any time to restart sensor.

delay

length of the initial OFF period as number of frame, 0 for immediate trigger.

Type integer

duration

length of the ON period in number of frame after the initial OFF period.

If duration is greater than 0, a negative trigger is sent at the end of the ON pulse.

Type integer

repeat

1 if the OFF-ON cycle should be repeated indefinitely, 0 if it should run once.

Type integer

class bge.types.SCA_JoystickSensor (SCA_ISensor)

This sensor detects player joystick events.

axisValues

The state of the joysticks axis as a list of values `numAxis` long. (read-only).

Type list of ints

Each specifies the value of an axis between -32767 and 32767 depending on how far the axis is pushed, 0 for nothing. The first 2 values are used by most joysticks and gamepads for directional control. 3rd and 4th values are only on some joysticks and can be used for arbitrary controls.

- left:[-32767, 0, ...]
- right:[32767, 0, ...]
- up:[0, -32767, ...]
- down:[0, 32767, ...]

axisSingle

like `axisValues` but returns a single axis value that is set by the sensor. (read-only).

Type integer

Note: Only use this for “Single Axis” type sensors otherwise it will raise an error.

hatValues

The state of the joysticks hats as a list of values `numHats` long. (read-only).

Type list of ints

Each specifies the direction of the hat from 1 to 12, 0 when inactive.

Hat directions are as follows...

- 0:None
- 1:Up
- 2:Right

- 4:Down
- 8:Left
- 3:Up - Right
- 6:Down - Right
- 12:Down - Left
- 9:Up - Left

hatSingle

Like `hatValues` but returns a single hat direction value that is set by the sensor. (read-only).

Type integer

numAxis

The number of axes for the joystick at this index. (read-only).

Type integer

numButtons

The number of buttons for the joystick at this index. (read-only).

Type integer

numHats

The number of hats for the joystick at this index. (read-only).

Type integer

connected

True if a joystick is connected at this joysticks index. (read-only).

Type boolean

index

The joystick index to use (from 0 to 7). The first joystick is always 0.

Type integer

threshold

Axis threshold. Joystick axis motion below this threshold wont trigger an event. Use values between (0 and 32767), lower values are more sensitive.

Type integer

button

The button index the sensor reacts to (first button = 0). When the “All Events” toggle is set, this option has no effect.

Type integer

axis

The axis this sensor reacts to, as a list of two values [axisIndex, axisDirection]

- axisIndex: the axis index to use when detecting axis movement, 1=primary directional control, 2=secondary directional control.
- axisDirection: 0=right, 1=up, 2=left, 3=down.

Type [integer, integer]

hat

The hat the sensor reacts to, as a list of two values: [hatIndex, hatDirection]

- hatIndex: the hat index to use when detecting hat movement, 1=primary hat, 2=secondary hat (4 max).
- hatDirection: 1-12.

Type [integer, integer]

getButtonActiveList ()

Returns A list containing the indices of the currently pressed buttons.

Return type list

getButtonStatus (buttonIndex)

Parameters **buttonIndex** (integer) – the button index, 0=first button

Returns The current pressed state of the specified button.

Return type boolean

class bge.types.SCA_KeyboardSensor (SCA_ISensor)

A keyboard sensor detects player key presses.

See module `bge.keys` for keycode values.

key

The key code this sensor is looking for.

Type keycode from `bge.keys` module

hold1

The key code for the first modifier this sensor is looking for.

Type keycode from `bge.keys` module

hold2

The key code for the second modifier this sensor is looking for.

Type keycode from `bge.keys` module

toggleProperty

The name of the property that indicates whether or not to log keystrokes as a string.

Type string

targetProperty

The name of the property that receives keystrokes in case in case a string is logged.

Type string

useAllKeys

Flag to determine whether or not to accept all keys.

Type boolean

events

a list of pressed keys that have either been pressed, or just released, or are active this frame. (read-only).

Type list [[`keycode`, `status`], ...]

getKeyStatus (keycode)

Get the status of a key.

Parameters **keycode** (integer) – The code that represents the key you want to get the state of,
use one of [these constants](#)

Returns The state of the given key, can be one of [these constants](#)

Return type int

class bge.types.**SCA_NANDController** (*SCA_IController*)
An NAND controller activates when all linked sensors are not active.

There are no special python methods for this controller.

class bge.types.**SCA_NORController** (*SCA_IController*)
An NOR controller activates only when all linked sensors are de-activated.

There are no special python methods for this controller.

class bge.types.**SCA_ORController** (*SCA_IController*)
An OR controller activates when any connected sensor activates.

There are no special python methods for this controller.

class bge.types.**SCA_PropertyActuator** (*SCA_IActuator*)
Property Actuator

propName

the property on which to operate.

Type string

value

the value with which the actuator operates.

Type string

mode

TODO - add constants to game logic dict!.

Type integer

class bge.types.**SCA_PropertySensor** (*SCA_ISensor*)

Activates when the game object property matches.

mode

Type of check on the property. Can be one of *these constants*

Type integer.

propName

the property the sensor operates.

Type string

value

the value with which the sensor compares to the value of the property.

Type string

min

the minimum value of the range used to evaluate the property when in interval mode.

Type string

max

the maximum value of the range used to evaluate the property when in interval mode.

Type string

class bge.types.**SCA_PythonController** (*SCA_IController*)

A Python controller uses a Python script to activate it's actuators, based on it's sensors.

script

The value of this variable depends on the execution methid.

- When ‘Script’ execution mode is set this value contains the entire python script as a single string (not the script name as you might expect) which can be modified to run different scripts.
- When ‘Module’ execution mode is set this value will contain a single line string - module name and function “module.func” or “package.module.func” where the module names are python textblocks or external scripts.

Type string

Note: Once this is set the script name given for warnings will remain unchanged.

mode

the execution mode for this controller (read-only).

- Script: 0, Execite the `script` as a python code.
- Module: 1, Execite the `script` as a module and function.

Type integer

activate (*actuator*)

Activates an actuator attached to this controller.

Parameters **actuator** (*actuator or the actuator name as a string*) – The actuator to operate on.

deactivate (*actuator*)

Deactivates an actuator attached to this controller.

Parameters **actuator** (*actuator or the actuator name as a string*) – The actuator to operate on.

class `bge.types.SCA_RandomActuator` (`SCA_IActuator`)
Random Actuator

seed

Seed of the random number generator.

Type integer.

Equal seeds produce equal series. If the seed is 0, the generator will produce the same value on every call.

para1

the first parameter of the active distribution.

Type float, read-only.

Refer to the documentation of the generator types for the meaning of this value.

para2

the second parameter of the active distribution.

Type float, read-only

Refer to the documentation of the generator types for the meaning of this value.

distribution

Distribution type. (read-only). Can be one of *these constants*

Type integer

propName

the name of the property to set with the random value.

Type string

If the generator and property types do not match, the assignment is ignored.

setBoolConst (value)

Sets this generator to produce a constant boolean value.

Parameters **value** (*boolean*) – The value to return.

setBoolUniform ()

Sets this generator to produce a uniform boolean distribution.

The generator will generate True or False with 50% chance.

setBoolBernouilli (value)

Sets this generator to produce a Bernouilli distribution.

Parameters **value** (*float*) – Specifies the proportion of False values to produce.

- 0.0: Always generate True
- 1.0: Always generate False

setIntConst (value)

Sets this generator to always produce the given value.

Parameters **value** (*integer*) – the value this generator produces.

setIntUniform (lower_bound, upper_bound)

Sets this generator to produce a random value between the given lower and upper bounds (inclusive).

setIntPoisson (value)

Generate a Poisson-distributed number.

This performs a series of Bernouilli tests with parameter value. It returns the number of tries needed to achieve success.

setFloatConst (value)

Always generate the given value.

setFloatUniform (lower_bound, upper_bound)

Generates a random float between lower_bound and upper_bound with a uniform distribution.

setFloatNormal (mean, standard_deviation)

Generates a random float from the given normal distribution.

Parameters

- **mean** (*float*) – The mean (average) value of the generated numbers
- **standard_deviation** (*float*) – The standard deviation of the generated numbers.

setFloatNegativeExponential (half_life)

Generate negative-exponentially distributed numbers.

The half-life ‘time’ is characterized by half_life.

class bge.types.**SCA_RandomSensor** (*SCA_ISensor*)
This sensor activates randomly.

lastDraw

The seed of the random number generator.

Type integer

seed

The seed of the random number generator.

Type integer

setSeed (*seed*)

Sets the seed of the random number generator.

If the seed is 0, the generator will produce the same value on every call.

getSeed()

Returns The initial seed of the generator. Equal seeds produce equal random series.

Return type integer

getLastDraw()

Returns The last random number generated.

Return type integer

class bge.types.**SCA_XNORController** (*SCA_IController*)

An XNOR controller activates when all linked sensors are the same (activated or inactive).

There are no special python methods for this controller.

class bge.types.**SCA_XORController** (*SCA_IController*)

An XOR controller activates when there is the input is mixed, but not when all are on or off.

There are no special python methods for this controller.

class bge.types.**KX_Camera** (*KX_GameObject*)

A Camera object.

INSIDE

See [sphereInsideFrustum](#) and [boxInsideFrustum](#)

INTERSECT

See [sphereInsideFrustum](#) and [boxInsideFrustum](#)

OUTSIDE

See [sphereInsideFrustum](#) and [boxInsideFrustum](#)

lens

The camera's lens value.

Type float

ortho_scale

The camera's view scale when in orthographic mode.

Type float

near

The camera's near clip distance.

Type float

far

The camera's far clip distance.

Type float

perspective

True if this camera has a perspective transform, False for an orthographic projection.

Type boolean

frustum_culling

True if this camera is frustum culling.

Type boolean

projection_matrix

This camera's 4x4 projection matrix.

Type 4x4 Matrix [[float]]

modelview_matrix

This camera's 4x4 model view matrix. (read-only).

Type 4x4 Matrix [[float]]

Note: This matrix is regenerated every frame from the camera's position and orientation.

camera_to_world

This camera's camera to world transform. (read-only).

Type 4x4 Matrix [[float]]

Note: This matrix is regenerated every frame from the camera's position and orientation.

world_to_camera

This camera's world to camera transform. (read-only).

Type 4x4 Matrix [[float]]

Note: Regenerated every frame from the camera's position and orientation.

Note: This is camera_to_world inverted.

useViewport

True when the camera is used as a viewport, set True to enable a viewport for this camera.

Type boolean

sphereInsideFrustum(*centre*, *radius*)

Tests the given sphere against the view frustum.

Parameters

- **centre** (*list* [*x*, *y*, *z*]) – The centre of the sphere (in world coordinates.)

- **radius** (*float*) – the radius of the sphere

Returns `INSIDE`, `OUTSIDE` or `INTERSECT`

Return type integer

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# A sphere of radius 4.0 located at [x, y, z] = [1.0, 1.0, 1.0]
if (cam.sphereInsideFrustum([1.0, 1.0, 1.0], 4) != cam.OUTSIDE):
    # Sphere is inside frustum !
    # Do something useful !
else:
    # Sphere is outside frustum
```

boxInsideFrustum(*box*)

Tests the given box against the view frustum.

Parameters `box` (*list of lists*) – Eight (8) corner points of the box (in world coordinates.)

Returns `INSIDE`, `OUTSIDE` or `INTERSECT`

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# Box to test...
box = []
box.append([-1.0, -1.0, -1.0])
box.append([-1.0, -1.0, 1.0])
box.append([-1.0, 1.0, -1.0])
box.append([-1.0, 1.0, 1.0])
box.append([1.0, -1.0, -1.0])
box.append([1.0, -1.0, 1.0])
box.append([1.0, 1.0, -1.0])
box.append([1.0, 1.0, 1.0])
```

```
if (cam.boxInsideFrustum(box) != cam.OUTSIDE):
    # Box is inside/intersects frustum !
    # Do something useful !
else:
    # Box is outside the frustum !
```

pointInsideFrustum(*point*)

Tests the given point against the view frustum.

Parameters `point` (*3D Vector*) – The point to test (in world coordinates.)

Returns True if the given point is inside this camera's viewing frustum.

Return type boolean

Note: When the camera is first initialized the result will be invalid because the projection matrix has not been set.

```
import GameLogic
co = GameLogic.getCurrentController()
cam = co.owner

# Test point [0.0, 0.0, 0.0]
if (cam.pointInsideFrustum([0.0, 0.0, 0.0])):
    # Point is inside frustum !
    # Do something useful !
else:
    # Box is outside the frustum !
```

getCameraToWorld()

Returns the camera-to-world transform.

Returns the camera-to-world transform matrix.

Return type matrix (4x4 list)

getWorldToCamera()

Returns the world-to-camera transform.

This returns the inverse matrix of getCameraToWorld().

Returns the world-to-camera transform matrix.

Return type matrix (4x4 list)

setOnTop()

Set this cameras viewport ontop of all other viewport.

setViewport (left, bottom, right, top)

Sets the region of this viewport on the screen in pixels.

Use `bge.render.getWindowHeight` and `bge.render.getWindowWidth` to calculate values relative to the entire display.

Parameters

- **left** (*integer*) – left pixel coordinate of this viewport
- **bottom** (*integer*) – bottom pixel coordinate of this viewport
- **right** (*integer*) – right pixel coordinate of this viewport
- **top** (*integer*) – top pixel coordinate of this viewport

getScreenPosition (object)

Gets the position of an object projected on screen space.

```
# For an object in the middle of the screen, coord = [0.5, 0.5]
coord = camera.getScreenPosition(object)
```

Parameters **object** (`KX_GameObject` or 3D Vector) – object name or list [x, y, z]

Returns the object's position in screen coordinates.

Return type list [x, y]

getScreenVect (*x, y*)

Gets the vector from the camera position in the screen coordinate direction.

Parameters

- **x** (*float*) – X Axis
- **y** (*float*) – Y Axis

Return type 3D Vector

Returns The vector from screen coordinate.

```
# Gets the vector of the camera front direction:  
m_vect = camera.getScreenVect(0.5, 0.5)
```

getScreenRay (*x, y, dist=inf, property=None*)

Look towards a screen coordinate (*x, y*) and find first object hit within *dist* that matches prop. The ray is similar to KX_GameObject->rayCastTo.

Parameters

- **x** (*float*) – X Axis
- **y** (*float*) – Y Axis
- **dist** (*float*) – max distance to look (can be negative => look behind); 0 or omitted => detect up to other
- **property** (*string*) – property name that object must have; can be omitted => detect any object

Return type KX_GameObject

Returns the first object hit or None if no object or object does not match prop

```
# Gets an object with a property "wall" in front of the camera within a distance of 100:  
target = camera.getScreenRay(0.5, 0.5, 100, "wall")
```

class bge.types.BL_ArmatureObject (KX_GameObject)

An armature object.

constraints

The list of armature constraint defined on this armature. Elements of the list can be accessed by index or string. The key format for string access is ‘<bone_name>:<constraint_name>’.

Type list of BL_ArmatureConstraint

channels

The list of armature channels. Elements of the list can be accessed by index or name the bone.

Type list of BL_ArmatureChannel

update ()

Ensures that the armature will be updated on next graphic frame.

This action is unnecessary if a KX_ArmatureActuator with mode run is active or if an action is playing. Use this function in other cases. It must be called on each frame to ensure that the armature is updated continuously.

class bge.types.BL_ArmatureActuator (SCA_IActuator)

Armature Actuators change constraint condition on armatures. Constants related to **type**

KX_ACT_ARMATURE_RUN

Just make sure the armature will be updated on the next graphic frame. This is the only persistent mode of the actuator: it executes automatically once per frame until stopped by a controller

Value 0

KX_ACT_ARMATURE_ENABLE

Enable the constraint.

Value 1

KX_ACT_ARMATURE_DISABLE

Disable the constraint (runtime constraint values are not updated).

Value 2

KX_ACT_ARMATURE_SETTARGET

Change target and subtarget of constraint.

Value 3

KX_ACT_ARMATURE_SETWEIGHT

Change weight of (only for IK constraint).

Value 4

type

The type of action that the actuator executes when it is active.

Can be one of *these constants*

Type integer

constraint

The constraint object this actuator is controlling.

Type [BL_ArmatureConstraint](#)

target

The object that this actuator will set as primary target to the constraint it controls.

Type [KX_GameObject](#)

subtarget

The object that this actuator will set as secondary target to the constraint it controls.

Type [KX_GameObject](#).

Note: Currently, the only secondary target is the pole target for IK constraint.

weight

The weight this actuator will set on the constraint it controls.

Type float.

Note: Currently only the IK constraint has a weight. It must be a value between 0 and 1.

Note: A weight of 0 disables a constraint while still updating constraint runtime values (see [BL_ArmatureConstraint](#))

class bge.types.KX_ArmatureSensor (SCA_ISensor)

Armature sensor detect conditions on armatures. Constants related to `type`

KX_ARMSENSOR_STATE_CHANGED

Detect that the constraint is changing state (active/inactive)

Value 0

KX_ARMSENSOR_LIN_ERROR_BELOW

Detect that the constraint linear error is above a threshold

Value 1

KX_ARMSENSOR_LIN_ERROR ABOVE

Detect that the constraint linear error is below a threshold

Value 2

KX_ARMSENSOR_ROT_ERROR_BELOW

Detect that the constraint rotation error is above a threshold

Value 3

KX_ARMSENSOR_ROT_ERROR ABOVE

Detect that the constraint rotation error is below a threshold

Value 4

type

The type of measurement that the sensor make when it is active.

Can be one of *these constants*

Type integer.

constraint

The constraint object this sensor is watching.

Type `BL_ArmatureConstraint`

value

The threshold used in the comparison with the constraint error. The linear error is only updated on Copy-Pose/Distance IK constraint with iTaSC solver. The rotation error is only updated on CopyPose+rotation IK constraint with iTaSC solver. The linear error on CopyPose is always ≥ 0 : it is the norm of the distance between the target and the bone. The rotation error on CopyPose is always ≥ 0 : it is the norm of the equivalent rotation vector between the bone and the target orientations. The linear error on Distance can be positive if the distance between the bone and the target is greater than the desired distance, and negative if the distance is smaller.

Type float

class bge.types.BL_ArmatureConstraint (PyObjectPlus)

Proxy to Armature Constraint. Allows to change constraint on the fly. Obtained through `BL_ArmatureObject.constraints`.

Note: Not all armature constraints are supported in the GE.

Constants related to `type`

CONSTRAINT_TYPE_TRACKTO

CONSTRAINT_TYPE_KINEMATIC

CONSTRAINT_TYPE_ROTLIKE

CONSTRAINT_TYPE_LOCLIKE

CONSTRAINT_TYPE_MINMAX

CONSTRAINT_TYPE_SIZELIKE

CONSTRAINT_TYPE_LOCKTRACK

CONSTRAINT_TYPE_STRETCHTO

CONSTRAINT_TYPE_CLAMPTO

CONSTRAINT_TYPE_TRANSFORM

CONSTRAINT_TYPE_DISTLIMIT

Constants related to [ik_type](#)

CONSTRAINT_IK_COPYPOSE

constraint is trying to match the position and eventually the rotation of the target.

Value 0

CONSTRAINT_IK_DISTANCE

Constraint is maintaining a certain distance to target subject to ik_mode

Value 1

Constants related to [ik_flag](#)

CONSTRAINT_IK_FLAG_TIP

Set when the constraint operates on the head of the bone and not the tail

Value 1

CONSTRAINT_IK_FLAG_ROT

Set when the constraint tries to match the orientation of the target

Value 2

CONSTRAINT_IK_FLAG_STRETCH

Set when the armature is allowed to stretch (only the bones with stretch factor > 0.0)

Value 16

CONSTRAINT_IK_FLAG_POS

Set when the constraint tries to match the position of the target.

Value 32

Constants related to [ik_mode](#)

CONSTRAINT_IK_MODE_INSIDE

The constraint tries to keep the bone within ik_dist of target

Value 0

CONSTRAINT_IK_MODE_OUTSIDE

The constraint tries to keep the bone outside ik_dist of the target

Value 1

CONSTRAINT_IK_MODE_ONSURFACE

The constraint tries to keep the bone exactly at ik_dist of the target.

Value 2

type

Type of constraint, (read-only).

Use one of *these constants*.

Type integer, one of CONSTRAINT_TYPE_* constants

name

Name of constraint constructed as <bone_name>:<constraint_name>. constraints list.

Type string

This name is also the key subscript on [BL_ArmatureObject](#).

enforce

fraction of constraint effect that is enforced. Between 0 and 1.

Type float

headtail

Position of target between head and tail of the target bone: 0=head, 1=tail.

Type float.

Note: Only used if the target is a bone (i.e target object is an armature).

lin_error

runtime linear error (in Blender units) on constraint at the current frame.

This is a runtime value updated on each frame by the IK solver. Only available on IK constraint and iTaSC solver.

Type float

rot_error

Runtime rotation error (in radiant) on constraint at the current frame.

Type float.

This is a runtime value updated on each frame by the IK solver. Only available on IK constraint and iTaSC solver.

It is only set if the constraint has a rotation part, for example, a CopyPose+Rotation IK constraint.

target

Primary target object for the constraint. The position of this object in the GE will be used as target for the constraint.

Type [KX_GameObject](#).

subtarget

Secondary target object for the constraint. The position of this object in the GE will be used as secondary target for the constraint.

Type [KX_GameObject](#).

Currently this is only used for pole target on IK constraint.

active

True if the constraint is active.

Type boolean

Note: An inactive constraint does not update lin_error and rot_error.

ik_weight

Weight of the IK constraint between 0 and 1.

Only defined for IK constraint.

Type float

ik_type

Type of IK constraint, (read-only).

Use one of *these constants*.

Type integer

ik_flag

Combination of IK constraint option flags, read-only.

Use one of *these constants*.

Type integer

ik_dist

Distance the constraint is trying to maintain with target, only used when ik_type=CONSTRAINT_IK_DISTANCE.

Type float

ik_mode

Use one of *these constants*.

Additional mode for IK constraint. Currently only used for Distance constraint:

Type integer

class bge.types.BL_ArmatureChannel (PyObjectPlus)

Proxy to armature pose channel. Allows to read and set armature pose. The attributes are identical to RNA attributes, but mostly in read-only mode.

See [rotation_mode](#)

PCHAN_ROT_QUAT**PCHAN_ROT_XYZ****PCHAN_ROT_XZY****PCHAN_ROT_YXZ****PCHAN_ROT_YZX****PCHAN_ROT_ZXY****PCHAN_ROT_ZYX****name**

channel name (=bone name), read-only.

Type string

bone

return the bone object corresponding to this pose channel, read-only.

Type [BL_ArmatureBone](#)

parent

return the parent channel object, None if root channel, read-only.

Type [BL_ArmatureChannel](#)

has_ik

true if the bone is part of an active IK chain, read-only. This flag is not set when an IK constraint is defined but not enabled (miss target information for example).

Type boolean

ik_dof_x

true if the bone is free to rotation in the X axis, read-only.

Type boolean

ik_dof_y

true if the bone is free to rotation in the Y axis, read-only.

Type boolean

ik_dof_z

true if the bone is free to rotation in the Z axis, read-only.

Type boolean

ik_limit_x

true if a limit is imposed on X rotation, read-only.

Type boolean

ik_limit_y

true if a limit is imposed on Y rotation, read-only.

Type boolean

ik_limit_z

true if a limit is imposed on Z rotation, read-only.

Type boolean

ik_rot_control

true if channel rotation should applied as IK constraint, read-only.

Type boolean

ik_lin_control

true if channel size should applied as IK constraint, read-only.

Type boolean

location

displacement of the bone head in armature local space, read-write.

Type vector [X, Y, Z].

Note: You can only move a bone if it is unconnected to its parent. An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see [BL_ArmatureObject.update](#)).

scale

scale of the bone relative to its parent, read-write.

Type vector [sizeX, sizeY, sizeZ].

Note: An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

rotation_quaternion

rotation of the bone relative to its parent expressed as a quaternion, read-write.

Type vector [qr, qi, qj, qk].

Note: This field is only used if rotation_mode is 0. An action playing on the armature may change the value. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

rotation_euler

rotation of the bone relative to its parent expressed as a set of euler angles, read-write.

Type vector [X, Y, Z].

Note: This field is only used if rotation_mode is > 0. You must always pass the angles in [X, Y, Z] order; the order of applying the angles to the bone depends on rotation_mode. An action playing on the armature may change this field. An IK chain does not update this value, see joint_rotation.

Note: Changing this field has no immediate effect, the pose is updated when the armature is updated during the graphic render (see `BL_ArmatureObject.update`)

rotation_mode

Method of updating the bone rotation, read-write.

Type integer

Use the following constants (euler mode are named as in Blender UI but the actual axis order is reversed).

- PCHAN_ROT_QUAT(0) : use quaternion in rotation attribute to update bone rotation
- PCHAN_ROT_XYZ(1) : use euler_rotation and apply angles on bone's Z, Y, X axis successively
- PCHAN_ROT_XZY(2) : use euler_rotation and apply angles on bone's Y, Z, X axis successively
- PCHAN_ROT_YXZ(3) : use euler_rotation and apply angles on bone's Z, X, Y axis successively
- PCHAN_ROT_YZX(4) : use euler_rotation and apply angles on bone's X, Z, Y axis successively
- PCHAN_ROT_ZXY(5) : use euler_rotation and apply angles on bone's Y, X, Z axis successively
- PCHAN_ROT_ZYX(6) : use euler_rotation and apply angles on bone's X, Y, Z axis successively

channel_matrix

pose matrix in bone space (deformation of the bone due to action, constraint, etc), Read-only. This field is updated after the graphic render, it represents the current pose.

Type matrix [4][4]

pose_matrix

pose matrix in armature space, read-only. This field is updated after the graphic render, it represents the current pose.

Type matrix [4][4]

pose_head

position of bone head in armature space, read-only.

Type vector [x, y, z]

pose_tail

position of bone tail in armature space, read-only.

Type vector [x, y, z]

ik_min_x

minimum value of X rotation in degree (<= 0) when X rotation is limited (see ik_limit_x), read-only.

Type float

ik_max_x

maximum value of X rotation in degree (>= 0) when X rotation is limited (see ik_limit_x), read-only.

Type float

ik_min_y

minimum value of Y rotation in degree (<= 0) when Y rotation is limited (see ik_limit_y), read-only.

Type float

ik_max_y

maximum value of Y rotation in degree (>= 0) when Y rotation is limited (see ik_limit_y), read-only.

Type float

ik_min_z

minimum value of Z rotation in degree (<= 0) when Z rotation is limited (see ik_limit_z), read-only.

Type float

ik_max_z

maximum value of Z rotation in degree (>= 0) when Z rotation is limited (see ik_limit_z), read-only.

Type float

ik_stiffness_x

bone rotation stiffness in X axis, read-only.

Type float between 0 and 1

ik_stiffness_y

bone rotation stiffness in Y axis, read-only.

Type float between 0 and 1

ik_stiffness_z

bone rotation stiffness in Z axis, read-only.

Type float between 0 and 1

ik_stretch

ratio of scale change that is allowed, 0=bone can't change size, read-only.

Type float

ik_rot_weight

weight of rotation constraint when ik_rot_control is set, read-write.

Type float between 0 and 1

ik_lin_weight

weight of size constraint when ik_lin_control is set, read-write.

Type float between 0 and 1

joint_rotation

Control bone rotation in term of joint angle (for robotic applications), read-write.

When writing to this attribute, you pass a [x, y, z] vector and an appropriate set of euler angles or quaternion is calculated according to the rotation_mode.

When you read this attribute, the current pose matrix is converted into a [x, y, z] vector representing the joint angles.

The value and the meaning of the x, y, z depends on the ik_dof_x/ik_dof_y/ik_dof_z attributes:

- 1DoF joint X, Y or Z: the corresponding x, y, or z value is used as a joint angle in radiant
- 2DoF joint X+Y or Z+Y: treated as 2 successive 1DoF joints: first X or Z, then Y. The x or z value is used as a joint angle in radiant along the X or Z axis, followed by a rotation along the new Y axis of y radians.
- 2DoF joint X+Z: treated as a 2DoF joint with rotation axis on the X/Z plane. The x and z values are used as the coordinates of the rotation vector in the X/Z plane.
- 3DoF joint X+Y+Z: treated as a revolute joint. The [x, y, z] vector represents the equivalent rotation vector to bring the joint from the rest pose to the new pose.

Type vector [x, y, z]

Note: The bone must be part of an IK chain if you want to set the ik_dof_x/ik_dof_y/ik_dof_z attributes via the UI, but this will interfere with this attribute since the IK solver will overwrite the pose. You can stay in control of the armature if you create an IK constraint but do not finalize it (e.g. don't set a target) the IK solver will not run but the IK panel will show up on the UI for each bone in the chain.

Note: [0, 0, 0] always corresponds to the rest pose.

Note: You must request the armature pose to update and wait for the next graphic frame to see the effect of setting this attribute (see [BL_ArmatureObject.update](#)).

Note: You can read the result of the calculation in rotation or euler_rotation attributes after setting this attribute.

class bge.types.**BL_ArmatureBone** (*PyObjectPlus*)

Proxy to Blender bone structure. All fields are read-only and comply to RNA names. All space attribute correspond to the rest pose.

name

bone name.

Type string

connected

true when the bone head is struck to the parent's tail.

Type boolean

hinge

true when bone doesn't inherit rotation or scale from parent bone.

Type boolean

inherit_scale

true when bone inherits scaling from parent bone.

Type boolean

bbone_segments

number of B-bone segments.

Type integer

roll

bone rotation around head-tail axis.

Type float

head

location of head end of the bone in parent bone space.

Type vector [x, y, z]

tail

location of head end of the bone in parent bone space.

Type vector [x, y, z]

length

bone length.

Type float

arm_head

location of head end of the bone in armature space.

Type vector [x, y, z]

arm_tail

location of tail end of the bone in armature space.

Type vector [x, y, z]

arm_mat

matrix of the bone head in armature space.

Type matrix [4][4]

Note: This matrix has no scale part.

bone_mat

rotation matrix of the bone in parent bone space.

Type matrix [3][3]

parent

parent bone, or None for root bone.

Type BL_ArmatureBone

children

list of bone's children.

Type list of BL_ArmatureBone

4.2 Game Engine bge.logic Module

4.2.1 Intro

Module to access logic functions, imported automatically into the python controllers namespace.

```
# To get the controller that's running this python script:  
cont = bge.logic.getCurrentController() # bge.logic is automatically imported  
  
# To get the game object this controller is on:  
obj = cont.owner  
  
KX_GameObject and KX_Camera or bge.types.KX_LightObject methods are available depending on  
the type of object  
  
# To get a sensor linked to this controller.  
# "sensorname" is the name of the sensor as defined in the Blender interface.  
# +-----+ +-----+  
# | Sensor "sensorname" ---+ Python +  
# +-----+ +-----+  
sens = cont.sensors["sensorname"]  
  
# To get a sequence of all sensors:  
sensors = co.sensors
```

See the sensor's reference for available methods:

- KX_MouseFocusSensor
- KX_NearSensor
- KX_NetworkMessageSensor
- KX_RadarSensor
- KX_RaySensor
- KX_TouchSensor
- SCA_DelaySensor
- SCA_JoystickSensor
- SCA_KeyboardSensor
- SCA_MouseSensor
- SCA_PropertySensor
- SCA_RandomSensor

You can also access actuators linked to the controller

```
# To get an actuator attached to the controller:  
# +-----+ +-----+  
# + Python ---+ Actuator "actuatorname" /  
# +-----+ +-----+
```

```
actuator = co.actuators["actuatorname"]

# Activate an actuator
controller.activate(actuator)
```

See the actuator's reference for available methods

- [BL_ActionActuator](#)
- [BL_ShapeActionActuator](#)
- [KX_CameraActuator](#)
- [KX_ConstraintActuator](#)
- [KX_GameActuator](#)
- [KX_IpoActuator](#)
- [KX_NetworkMessageActuator](#)
- [KX_ObjectActuator](#)
- [KX_ParentActuator](#)
- [KX_SCA_AddObjectActuator](#)
- [KX_SCA_DynamicActuator](#)
- [KX_SCA_EndObjectActuator](#)
- [KX_SCA_ReplaceMeshActuator](#)
- [KX_SceneActuator](#)
- [KX_SoundActuator](#)
- [KX_StateActuator](#)
- [KX_TrackToActuator](#)
- [KX_VisibilityActuator](#)
- [SCA_2DFilterActuator](#)
- [SCA_PropertyActuator](#)
- [SCA_RandomActuator](#)

Most logic brick's methods are accessors for the properties available in the logic buttons. Consult the logic bricks documentation for more information on how each logic brick works.

There are also methods to access the current `bge.types.KX_Scene`

```
# Get the current scene
scene = bge.logic.getCurrentScene()

# Get the current camera
cam = scene.active_camera
```

Matrices as used by the game engine are **row major** `matrix[row][col] = float`

`bge.types.KX_Camera` has some examples using matrices.

4.2.2 Variables

`bge.logic.globalData`

A dictionary that is saved between loading blend files so you can use it to store inventory and other variables you want to store between scenes and blend files. It can also be written to a file and loaded later on with the game load/save actuators.

Note: only python built in types such as int/string/bool/float/tuples/lists can be saved, GameObjects, Actuators etc will not work as expected.

`bge.logic.keyboard`

The current keyboard wrapped in an `SCA_PythonKeyboard` object.

bge.logic.mouse

The current mouse wrapped in an `SCA_PythonMouse` object.

4.2.3 General functions

bge.logic.getCurrentController()

Gets the Python controller associated with this Python script.

Return type `bge.types.SCA_PythonController`

bge.logic.getCurrentScene()

Gets the current Scene.

Return type `bge.types.KX_Scene`

bge.logic.getSceneList()

Gets a list of the current scenes loaded in the game engine.

Return type list of `bge.types.KX_Scene`

Note: Scenes in your blend file that have not been converted wont be in this list. This list will only contain scenes such as overlays scenes.

bge.logic.loadGlobalDict()

Loads `bge.logic.globalDict` from a file.

bge.logic.saveGlobalDict()

Saves `bge.logic.globalDict` to a file.

bge.logic.startGame(*blend*)

Loads the blend file.

Parameters `blend (string)` – The name of the blend file

bge.logic.endGame()

Ends the current game.

bge.logic.restartGame()

Restarts the current game by reloading the .blend file (the last saved version, not what is currently running).

bge.logic.LibLoad(*blend*, *type*, *data*, *load_actions=False*, *verbose=False*)

Converts the all of the datablocks of the given type from the given blend.

Parameters

- **blend (string)** – The path to the blend file (or the name to use for the library if data is supplied)
- **type (string)** – The datablock type (currently only “Action”, “Mesh” and “Scene” are supported)
- **data (bytes)** – Binary data from a blend file (optional)
- **load_actions (bool)** – Search for and load all actions in a given Scene and not just the “active” actions (Scene type only)
- **verbose (bool)** – Whether or not to print debugging information (e.g., “SceneName: Scene”)

bge.logic.LibNew(*name*, *type*, *data*)

Uses existing datablock data and loads in as a new library.

Parameters

- **name** (*string*) – A unique library name used for removal later
- **type** (*string*) – The datablock type (currently only “Mesh” is supported)
- **data** (*list of strings*) – A list of names of the datablocks to load

`bge.logic.LibFree(name)`

Frees a library, removing all objects and meshes from the currently active scenes.

Parameters **name** (*string*) – The name of the library to free (the name used in LibNew)

`bge.logic.LibList()`

Returns a list of currently loaded libraries.

Return type list [str]

`bge.logic.addScene(name, overlay=1)`

Loads a scene into the game engine.

Parameters

- **name** (*string*) – The name of the scene
- **overlay** (*integer*) – Overlay or underlay (optional)

`bge.logic.sendMessage(subject, body=""", to=""", message_from="")`

Sends a message to sensors in any active scene.

Parameters

- **subject** (*string*) – The subject of the message
- **body** (*string*) – The body of the message (optional)
- **to** (*string*) – The name of the object to send the message to (optional)
- **message_from** (*string*) – The name of the object that the message is coming from (optional)

`bge.logic.setGravity(gravity)`

Sets the world gravity.

`bge.logic.getSpectrum()`

Returns a 512 point list from the sound card. This only works if the fmod sound driver is being used.

Return type list [float], len(getSpectrum()) == 512

`bge.logic.stopDSP()`

Stops the sound driver using DSP effects.

Only the fmod sound driver supports this. DSP can be computationally expensive.

`bge.logic.getMaxLogicFrame()`

Gets the maximum number of logic frames per render frame.

Returns The maximum number of logic frames per render frame

Return type integer

`bge.logic.setMaxLogicFrame(maxlogic)`

Sets the maximum number of logic frames that are executed per render frame. This does not affect the physics system that still runs at full frame rate.

Parameters **maxlogic** (*integer*) – The new maximum number of logic frames per render frame.

Valid values: 1..5

`bge.logic.getMaxPhysicsFrame()`

Gets the maximum number of physics frames per render frame.

Returns The maximum number of physics frames per render frame

Return type integer

`bge.logic.setMaxPhysicsFrame(maxphysics)`

Sets the maximum number of physics timestep that are executed per render frame. Higher value allows physics to keep up with realtime even if graphics slows down the game. Physics timestep is fixed and equal to 1/tickrate (see setLogicTicRate) maxphysics/ticrate is the maximum delay of the renderer that physics can compensate.

Parameters `maxphysics` (integer) – The new maximum number of physics timestep per render frame. Valid values: 1..5.

`bge.logic.getLogicTicRate()`

Gets the logic update frequency.

Returns The logic frequency in Hz

Return type float

`bge.logic.setLogicTicRate(ticrate)`

Sets the logic update frequency.

The logic update frequency is the number of times logic bricks are executed every second. The default is 60 Hz.

Parameters `ticrate` (float) – The new logic update frequency (in Hz).

`bge.logic.getPhysicsTicRate()`

Gets the physics update frequency

Returns The physics update frequency in Hz

Return type float

`bge.logic.setPhysicsTicRate(ticrate)`

Sets the physics update frequency

The physics update frequency is the number of times the physics system is executed every second. The default is 60 Hz.

Parameters `ticrate` (float) – The new update frequency (in Hz).

4.2.4 Utility functions

`bge.logic.expandPath(path)`

Converts a blender internal path into a proper file system path.

Use / as directory separator in path You can use ‘//’ at the start of the string to define a relative path; Blender replaces that string by the directory of the startup .blend or runtime file to make a full path name (doesn’t change during the game, even if you load other .blend). The function also converts the directory separator to the local file system format.

Parameters `path` (string) – The path string to be converted/expanded.

Returns The converted string

Return type string

`bge.logic.getAverageFrameRate()`

Gets the estimated/average framerate for all the active scenes, not only the current scene.

Returns The estimated average framerate in frames per second

Return type float

`bge.logic.getBlendFileList (path = "")`

Returns a list of blend files in the same directory as the open blend file, or from using the option argument.

Parameters `path` (*string*) – Optional directory argument, will be expanded (like expandPath) into the full path.

Returns A list of filenames, with no directory prefix

Return type list

`bge.logic.getRandomFloat ()`

Returns a random floating point value in the range [0 - 1)

`bge.logic.PrintGLInfo ()`

Prints GL Extension Info into the console

4.2.5 Constants

`bge.logic.KX_TRUE`

True value used by some modules.

`bge.logic.KX_FALSE`

False value used by some modules.

Sensors

Sensor Status

`bge.logic.KX_SENSOR_INACTIVE`

`bge.logic.KX_SENSOR_JUST_ACTIVATED`

`bge.logic.KX_SENSOR_ACTIVE`

`bge.logic.KX_SENSOR_JUST_DEACTIVATED`

Property Sensor

`bge.logic.KX_PROPSENSOR_EQUAL`

Activate when the property is equal to the sensor value.

Value 1

`bge.logic.KX_PROPSENSOR_NOTEQUAL`

Activate when the property is not equal to the sensor value.

Value 2

`bge.logic.KX_PROPSENSOR_INTERVAL`

Activate when the property is between the specified limits.

Value 3

`bge.logic.KX_PROPSENSOR_CHANGED`

Activate when the property changes

Value 4

bge.logic.KX_PROPSENSOR_EXPRESSION

Activate when the expression matches

Value 5

Radar Sensor

See [bge.types.KX_RadarSensor](#)

bge.logic.KX_RADAR_AXIS_POS_X

bge.logic.KX_RADAR_AXIS_POS_Y

bge.logic.KX_RADAR_AXIS_POS_Z

bge.logic.KX_RADAR_AXIS_NEG_X

bge.logic.KX_RADAR_AXIS_NEG_Y

bge.logic.KX_RADAR_AXIS_NEG_Z

Ray Sensor

See [bge.types.KX_RaySensor](#)

bge.logic.KX_RAY_AXIS_POS_X

bge.logic.KX_RAY_AXIS_POS_Y

bge.logic.KX_RAY_AXIS_POS_Z

bge.logic.KX_RAY_AXIS_NEG_X

bge.logic.KX_RAY_AXIS_NEG_Y

bge.logic.KX_RAY_AXIS_NEG_Z

Actuators

Action Actuator

See [bge.types.BL_ActionActuator](#)

bge.logic.KX_ACTIONACT_PLAY

bge.logic.KX_ACTIONACT_FLIPPER

bge.logic.KX_ACTIONACT_LOOPSTOP

bge.logic.KX_ACTIONACT_LOOPEND

bge.logic.KX_ACTIONACT_PROPERTY

Constraint Actuator

See [bge.types.KX_ConstraintActuator.option](#)

- Applicable to Distance constraint:

`bge.logic.KX_ACT_CONSTRAINT_NORMAL`
Activate alignment to surface

`bge.logic.KX_ACT_CONSTRAINT_DISTANCE`
Activate distance control

`bge.logic.KX_ACT_CONSTRAINT_LOCAL`
Direction of the ray is along the local axis

- Applicable to Force field constraint:

`bge.logic.KX_ACT_CONSTRAINT_DOROTFH`
Force field act on rotation as well

- Applicable to both:

`bge.logic.KX_ACT_CONSTRAINT_MATERIAL`
Detect material rather than property

`bge.logic.KX_ACT_CONSTRAINT_PERMANENT`
No deactivation if ray does not hit target

See `bge.types.KX_ConstraintActuator.limit`

`bge.logic.KX_CONSTRAINTACT_LOCKX`
Limit X coord.

`bge.logic.KX_CONSTRAINTACT_LOCKY`
Limit Y coord

`bge.logic.KX_CONSTRAINTACT_LOCKZ`
Limit Z coord

`bge.logic.KX_CONSTRAINTACT_ROTX`
Limit X rotation

`bge.logic.KX_CONSTRAINTACT_ROTY`
Limit Y rotation

`bge.logic.KX_CONSTRAINTACT_ROTZ`
Limit Z rotation

`bge.logic.KX_CONSTRAINTACT_DIRNX`
Set distance along negative X axis

`bge.logic.KX_CONSTRAINTACT_DIRNY`
Set distance along negative Y axis

`bge.logic.KX_CONSTRAINTACT_DIRNZ`
Set distance along negative Z axis

`bge.logic.KX_CONSTRAINTACT_DIRPX`
Set distance along positive X axis

`bge.logic.KX_CONSTRAINTACT_DIRPY`
Set distance along positive Y axis

`bge.logic.KX_CONSTRAINTACT_DIRPZ`
Set distance along positive Z axis

`bge.logic.KX_CONSTRAINTACT_ORIX`
Set orientation of X axis

`bge.logic.KX_CONSTRAINTACT_ORIY`
Set orientation of Y axis

bge.logic.**KX_CONSTRAINTACT_ORIZ**
Set orientation of Z axis

bge.logic.**KX_ACT_CONSTRAINT_FHNX**
Set force field along negative X axis

bge.logic.**KX_ACT_CONSTRAINT_FHNY**
Set force field along negative Y axis

bge.logic.**KX_ACT_CONSTRAINT_FHNZ**
Set force field along negative Z axis

bge.logic.**KX_ACT_CONSTRAINT_FHPX**
Set force field along positive X axis

bge.logic.**KX_ACT_CONSTRAINT_FHPY**
Set force field along positive Y axis

bge.logic.**KX_ACT_CONSTRAINT_FHPZ**
Set force field along positive Z axis

Dynamic Actuator

See [bge.types.KX_SCA_DynamicActuator](#)

bge.logic.**KX_DYN_RESTORE_DYNAMICS**

bge.logic.**KX_DYN_DISABLE_DYNAMICS**

bge.logic.**KX_DYN_ENABLE_RIGID_BODY**

bge.logic.**KX_DYN_DISABLE_RIGID_BODY**

bge.logic.**KX_DYN_SET_MASS**

Game Actuator

See [bge.types.KX_GameActuator](#)

bge.logic.**KX_GAME_LOAD**

bge.logic.**KX_GAME_START**

bge.logic.**KX_GAME_RESTART**

bge.logic.**KX_GAME_QUIT**

bge.logic.**KX_GAME_SAVECFG**

bge.logic.**KX_GAME_LOADCFG**

IPO Actuator

See [bge.types.KX_IpoActuator](#)

bge.logic.**KX_IPOACT_PLAY**

bge.logic.**KX_IPOACT_PINGPONG**

bge.logic.**KX_IPOACT_FLIPPER**

bge.logic.**KX_IPOACT_LOOPSTOP**

bge.logic.KX_IPOACT_LOOPEND
bge.logic.KX_IPOACT_FROM_PROP

Parent Actuator

bge.logic.KX_PARENT_REMOVE
bge.logic.KX_PARENT_SET

Random Distributions

See [bge.types.SCA_RandomActuator](#)
bge.logic.KX_RANDOMACT_BOOL_CONST
bge.logic.KX_RANDOMACT_BOOL_UNIFORM
bge.logic.KX_RANDOMACT_BOOL_BERNOULLI
bge.logic.KX_RANDOMACT_INT_CONST
bge.logic.KX_RANDOMACT_INT_UNIFORM
bge.logic.KX_RANDOMACT_INT_POISSON
bge.logic.KX_RANDOMACT_FLOAT_CONST
bge.logic.KX_RANDOMACT_FLOAT_UNIFORM
bge.logic.KX_RANDOMACT_FLOAT_NORMAL
bge.logic.KX_RANDOMACT_FLOAT_NEGATIVE_EXPONENTIAL

Scene Actuator

See [bge.types.KX_SceneActuator](#)
bge.logic.KX_SCENE_RESTART
bge.logic.KX_SCENE_SET_SCENE
bge.logic.KX_SCENE_SET_CAMERA
bge.logic.KX_SCENE_ADD_FRONT_SCENE
bge.logic.KX_SCENE_ADD_BACK_SCENE
bge.logic.KX_SCENE_REMOVE_SCENE
bge.logic.KX_SCENE_SUSPEND
bge.logic.KX_SCENE_RESUME

Shape Action Actuator

See [bge.types.BL_ActionActuator](#)
bge.logic.KX_ACTIONACT_PLAY
bge.logic.KX_ACTIONACT_FLIPPER

bge.logic.KX_ACTIONACT_LOOPSTOP
bge.logic.KX_ACTIONACT_LOOPEND
bge.logic.KX_ACTIONACT_PROPERTY

Sound Actuator

See [bge.types.KX_SoundActuator](#)

bge.logic.KX_SOUNDACT_PLAYSTOP

Value 1

bge.logic.KX_SOUNDACT_PLAYEND

Value 2

bge.logic.KX_SOUNDACT_LOOPSTOP

Value 3

bge.logic.KX_SOUNDACT_LOOPEND

Value 4

bge.logic.KX_SOUNDACT_LOOPBIDIRECTIONAL

Value 5

bge.logic.KX_SOUNDACT_LOOPBIDIRECTIONAL_STOP

Value 6

Various

Input Status

See [bge.types.SCA_PythonKeyboard](#), [bge.types.SCA_PythonMouse](#),
[bge.types.SCA_MouseSensor](#), [bge.types.SCA_KeyboardSensor](#)

bge.logic.KX_INPUT_NONE

bge.logic.KX_INPUT_JUST_ACTIVATED

bge.logic.KX_INPUT_ACTIVE

bge.logic.KX_INPUT_JUST_RELEASED

Mouse Buttons

See [bge.types.SCA_MouseSensor](#)

bge.logic.KX_MOUSE_BUT_LEFT

bge.logic.KX_MOUSE_BUT_MIDDLE

bge.logic.KX_MOUSE_BUT_RIGHT

States

See [bge.types.KX_StateActuator](#)

bge.logic.**KX_STATE1**
bge.logic.**KX_STATE2**
bge.logic.**KX_STATE3**
bge.logic.**KX_STATE4**
bge.logic.**KX_STATE5**
bge.logic.**KX_STATE6**
bge.logic.**KX_STATE7**
bge.logic.**KX_STATE8**
bge.logic.**KX_STATE9**
bge.logic.**KX_STATE10**
bge.logic.**KX_STATE11**
bge.logic.**KX_STATE12**
bge.logic.**KX_STATE13**
bge.logic.**KX_STATE14**
bge.logic.**KX_STATE15**
bge.logic.**KX_STATE16**
bge.logic.**KX_STATE17**
bge.logic.**KX_STATE18**
bge.logic.**KX_STATE19**
bge.logic.**KX_STATE20**
bge.logic.**KX_STATE21**
bge.logic.**KX_STATE22**
bge.logic.**KX_STATE23**
bge.logic.**KX_STATE24**
bge.logic.**KX_STATE25**
bge.logic.**KX_STATE26**
bge.logic.**KX_STATE27**
bge.logic.**KX_STATE28**
bge.logic.**KX_STATE29**
bge.logic.**KX_STATE30**

See [bge.types.KX_StateActuator.operation](#)

bge.logic.**KX_STATE_OP_CLR**
Subtract bits to state mask

Value 0

bge.logic.KX_STATE_OP_CPY

Copy state mask

Value 1

bge.logic.KX_STATE_OP_NEG

Invert bits to state mask

Value 2

bge.logic.KX_STATE_OP_SET

Add bits to state mask

Value 3

2D Filter

bge.logic.RAS_2DFILTER_BLUR

Value 2

bge.logic.RAS_2DFILTER_CUSTOMFILTER

Customer filter, the code code is set via shaderText property.

Value 12

bge.logic.RAS_2DFILTER_DILATION

Value 4

bge.logic.RAS_2DFILTER_DISABLED

Disable the filter that is currently active

Value -1

bge.logic.RAS_2DFILTER_ENABLED

Enable the filter that was previously disabled

Value -2

bge.logic.RAS_2DFILTER_EROSION

Value 5

bge.logic.RAS_2DFILTER_GRAYSCALE

Value 9

bge.logic.RAS_2DFILTER_INVERT

Value 11

bge.logic.RAS_2DFILTER_LAPLACIAN

Value 6

bge.logic.RAS_2DFILTER_MOTIONBLUR

Create and enable preset filters

Value 1

bge.logic.RAS_2DFILTER_NOFILTER

Disable and destroy the filter that is currently active

Value 0

bge.logic.RAS_2DFILTER_PREWITT

Value 8

bge.logic.RAS_2DFILTER_SEPIA

Value 10

bge.logic.RAS_2DFILTER_SHARPEN

Value 3

bge.logic.RAS_2DFILTER_SOBEL

Value 7

Shader

bge.logic.VIEWMATRIX

bge.logic.VIEWMATRIX_INVERSE

bge.logic.VIEWMATRIX_INVERSETRANSPOSE

bge.logic.VIEWMATRIX_TRANSPOSE

bge.logic.MODELMATRIX

bge.logic.MODELMATRIX_INVERSE

bge.logic.MODELMATRIX_INVERSETRANSPOSE

bge.logic.MODELMATRIX_TRANSPOSE

bge.logic.MODELVIEWMATRIX

bge.logic.MODELVIEWMATRIX_INVERSE

bge.logic.MODELVIEWMATRIX_INVERSETRANSPOSE

bge.logic.MODELVIEWMATRIX_TRANSPOSE

bge.logic.CAM_POS

Current camera position

bge.logic.CONSTANT_TIMER

User a timer for the uniform value.

bge.logic.SHD_TANGENT

Blender Material

bge.logic.BL_DST_ALPHA

bge.logic.BL_DST_COLOR

bge.logic.BL_ONE

bge.logic.BL_ONE_MINUS_DST_ALPHA

bge.logic.BL_ONE_MINUS_DST_COLOR

bge.logic.BL_ONE_MINUS_SRC_ALPHA

bge.logic.BL_ONE_MINUS_SRC_COLOR

```
bge.logic.BL_SRC_ALPHA  
bge.logic.BL_SRC_ALPHA_SATURATE  
bge.logic.BL_SRC_COLOR  
bge.logic.BL_ZERO
```

4.3 Game Engine bge.render Module

4.3.1 Intro

```
# Example Uses an L{SCA_MouseSensor}, and two L{KX_ObjectActuator}s to implement MouseLook::  
# To use a mouse movement sensor "Mouse" and a  
# motion actuator to mouse look:  
import bge.render  
import bge.logic  
  
# SCALE sets the speed of motion  
SCALE=[1, 0.5]  
  
co = bge.logic.getCurrentController()  
obj = co.getOwner()  
mouse = co.getSensor("Mouse")  
lmotion = co.getActuator("LMove")  
wmotion = co.getActuator("WMove")  
  
# Transform the mouse coordinates to see how far the mouse has moved.  
def mousePos():  
    x = (bge.render.getWindowWidth() / 2 - mouse.getXPosition()) * SCALE[0]  
    y = (bge.render.getWindowHeight() / 2 - mouse.getYPosition()) * SCALE[1]  
    return (x, y)  
  
pos = mousePos()  
  
# Set the amount of motion: X is applied in world coordinates...  
lmotion.setTorque(0.0, 0.0, pos[0], False)  
# ...Y is applied in local coordinates  
wmotion.setTorque(-pos[1], 0.0, 0.0, True)  
  
# Activate both actuators  
bge.logic.addActiveActuator(lmotion, True)  
bge.logic.addActiveActuator(wmotion, True)  
  
# Centre the mouse  
bge.render.setMousePosition(bge.render.getWindowWidth() / 2, bge.render.getWindowHeight() / 2)
```

4.3.2 Constants

bge.render.KX_TEXFACE_MATERIAL

Materials as defined by the texture face settings.

bge.render.KX_BLENDER_MULTITEX_MATERIAL

Materials approximating blender materials with multitexturing.

bge.render.KX_BLENDER_GLSL_MATERIAL

Materials approximating blender materials with GLSL.

4.3.3 Functions

bge.render.getWindowWidth()

Gets the width of the window (in pixels)

Return type integer

bge.render.getWindowHeight()

Gets the height of the window (in pixels)

Return type integer

bge.render.makeScreenshot (filename)

Writes a screenshot to the given filename.

If filename starts with // the image will be saved relative to the current directory. If the filename contains # it will be replaced with the frame number.

The standalone player saves .png files. It does not support colour space conversion or gamma correction.

When run from Blender, makeScreenshot supports Iris, IrisZ, TGA, Raw TGA, PNG, HamX, and Jpeg. Gamma, Colourspace conversion and Jpeg compression are taken from the Render settings panels.

bge.render.enableVisibility (visible)

Doesn't really do anything...

bge.render.showMouse (visible)

Enables or disables the operating system mouse cursor.

bge.render.setMousePosition (x, y)

Sets the mouse cursor position.

bge.render.setBackgroundColor (rgba)

Sets the window background colour.

bge.render.setMistColor (rgb)

Sets the mist colour.

bge.render.setAmbientColor (rgb)

Sets the color of ambient light.

bge.render.setMistStart (start)

Sets the mist start value. Objects further away than start will have mist applied to them.

bge.render.setMistEnd (end)

Sets the mist end value. Objects further away from this will be coloured solid with the colour set by setMistColor().

bge.render.**disableMist**()
Disables mist.

Note: Set any of the mist properties to enable mist.

bge.render.**setEyeSeparation**(*eyesep*)
Sets the eye separation for stereo mode. Usually Focal Length/30 provides a comfortable value.

Parameters *eyesep* (*float*) – The distance between the left and right eye.

bge.render.**getEyeSeparation**()
Gets the current eye separation for stereo mode.

Return type float

bge.render.**setFocalLength**(*focallength*)
Sets the focal length for stereo mode. It uses the current camera focal length as initial value.

Parameters *focallength* (*float*) – The focal length.

bge.render.**getFocalLength**()
Gets the current focal length for stereo mode.

Return type float

bge.render.**setMaterialMode**(*mode*)
Set the material mode to use for OpenGL rendering.

Note: Changes will only affect newly created scenes.

bge.render.**getMaterialMode**(*mode*)
Get the material mode to use for OpenGL rendering.

Return type KX_TEXFACE_MATERIAL, KX_BLENDER_MULTITEX_MATERIAL,
KX_BLENDER_GLSL_MATERIAL

bge.render.**setGLSLMaterialSetting**(*setting, enable*)
Enables or disables a GLSL material setting.

bge.render.**getGLSLMaterialSetting**(*setting, enable*)
Get the state of a GLSL material setting.

Return type boolean

bge.render.**drawLine**(*fromVec, toVec, color*)
Draw a line in the 3D scene.

Parameters

- **fromVec** (*list [x, y, z]*) – the origin of the line
- **toVec** (*list [x, y, z]*) – the end of the line
- **color** (*list [r, g, b]*) – the color of the line

bge.render.**enableMotionBlur**(*factor*)
Enable the motion blur effect.

Parameters **factor** (*float [0.0 - 1.0]*) – the amount of motion blur to display.

```
bge.render.disableMotionBlur()  
Disable the motion blur effect.
```

4.4 Game Engine bge.events module

4.4.1 Intro

This module holds key constants for the SCA_KeyboardSensor.

```
# Set a connected keyboard sensor to accept F1  
import bge  
  
co = bge.logic.getCurrentController()  
# 'Keyboard' is a keyboard sensor  
sensor = co.sensors["Keyboard"]  
sensor.key = bge.events.F1KEY  
  
# Do the all keys thing  
import bge  
  
co = bge.logic.getCurrentController()  
# 'Keyboard' is a keyboard sensor  
sensor = co.sensors["Keyboard"]  
  
for key,status in sensor.events:  
    # key[0] == bge.events.keycode, key[1] = status  
    if status == bge.logic.KX_INPUT_JUST_ACTIVATED:  
        if key == bge.events.WKEY:  
            # Activate Forward!  
        if key == bge.events.SKEY:  
            # Activate Backward!  
        if key == bge.events.AKEY:  
            # Activate Left!  
        if key == bge.events.DKEY:  
            # Activate Right!  
  
# The all keys thing without a keyboard sensor (but you will  
# need an always sensor with pulse mode on)  
import bge  
  
# Just shortening names here  
keyboard = bge.logic.keyboard  
JUST_ACTIVATED = bge.logic.KX_INPUT_JUST_ACTIVATED  
  
if keyboard.events[bge.events.WKEY] == JUST_ACTIVATED:  
    print("Activate Forward!")  
if keyboard.events[bge.events.SKEY] == JUST_ACTIVATED:  
    print("Activate Backward!")  
if keyboard.events[bge.events.AKEY] == JUST_ACTIVATED:  
    print("Activate Left!")  
if keyboard.events[bge.events.DKEY] == JUST_ACTIVATED:  
    print("Activate Right!")
```

4.4.2 Functions

`bge.events.EventToString(event)`

Return the string name of a key event. Will raise a ValueError error if its invalid.

Parameters `event (int)` – key event from `bge.keys` or the keyboard sensor.

Return type string

`bge.events.EventToCharacter(event, shift)`

Return the string name of a key event. Returns an empty string if the event cant be represented as a character.

Parameters

- `event (int)` – key event from `bge.keys` or the keyboard sensor.

- `shift (bool)` – set to true if shift is held.

Return type string

4.4.3 Keys (Constants)

Mouse Keys

`bge.events.LEFTMOUSE`

`bge.events.MIDDLEMOUSE`

`bge.events.RIGHTMOUSE`

`bge.events.WHEELUPMOUSE`

`bge.events.WHEELEDOWNMOUSE`

`bge.events.MOUSEX`

`bge.events.MOUSEY`

Keyboard Keys

Alphabet keys

`bge.events.AKEY`

`bge.events.BKEY`

`bge.events.CKEY`

`bge.events.DKEY`

`bge.events.EKEY`

`bge.events.FKEY`

`bge.events.GKEY`

`bge.events.HKEY`

`bge.events.IKEY`

`bge.events.JKEY`

`bge.events.KKEY`

```
bge.events.LKEY
bge.events.MKEY
bge.events.NKEY
bge.events.OKEY
bge.events.PKEY
bge.events.QKEY
bge.events.RKEY
bge.events.SKEY
bge.events.TKEY
bge.events.UKEY
bge.events.VKEY
bge.events.WKEY
bge.events.XKEY
bge.events.YKEY
bge.events.ZKEY
```

Number keys

```
bge.events.ZEROKEY
bge.events.ONEKEY
bge.events.TWOKEY
bge.events.THREEKEY
bge.events.FOURKEY
bge.events.FIVEKEY
bge.events.SIXKEY
bge.events.SEVENKEY
bge.events.EIGHTKEY
bge.events.NINEKEY
```

Modifiers Keys

```
bge.events.CAPSLOCKKEY
bge.events.LEFTCTRLKEY
bge.events.LEFTALTKEY
bge.events.RIGHTALTKEY
bge.events.RIGHTCTRLKEY
bge.events.RIGHTSHIFTKEY
bge.events.LEFTSHIFTKEY
```

Arrow Keys

```
bge.events.LEFTARROWKEY  
bge.events.DOWNARROWKEY  
bge.events.RIGHTARROWKEY  
bge.events.UPARROWKEY
```

Numberpad Keys

```
bge.events.PAD0  
bge.events.PAD1  
bge.events.PAD2  
bge.events.PAD3  
bge.events.PAD4  
bge.events.PAD5  
bge.events.PAD6  
bge.events.PAD7  
bge.events.PAD8  
bge.events.PAD9  
bge.events.PADPERIOD  
bge.events.PADSLASHKEY  
bge.events.PADASTERKEY  
bge.events.PADMINUS  
bge.events.PADENTER  
bge.events.PADPLUSKEY
```

Function Keys

```
bge.events.F1KEY  
bge.events.F2KEY  
bge.events.F3KEY  
bge.events.F4KEY  
bge.events.F5KEY  
bge.events.F6KEY  
bge.events.F7KEY  
bge.events.F8KEY  
bge.events.F9KEY  
bge.events.F10KEY
```

```
bge.events.F11KEY
bge.events.F12KEY
bge.events.F13KEY
bge.events.F14KEY
bge.events.F15KEY
bge.events.F16KEY
bge.events.F17KEY
bge.events.F18KEY
bge.events.F19KEY
```

Other Keys

```
bge.events.ACCENTGRAVEKEY
bge.events.BACKSLASHKEY
bge.events.BACKSPACEKEY
bge.events.COMMASEPKEY
bge.events.DELKEY
bge.events.ENDKEY
bge.events.EQUALKEY
bge.events.ESCKEY
bge.events.HOMEKEY
bge.events.INSERTKEY
bge.events.LEFTBRACKETKEY
bge.events.LINEFEEDKEY
bge.events.MINUSKEY
bge.events.PAGEDOWNKEY
bge.events.PAGEUPKEY
bge.events.PAUSEKEY
bge.events.PERIODKEY
bge.events.QUOTEKEY
bge.events.RIGHTBRACKETKEY
bge.events.RETKEY (Deprecated: use bge.events.ENTERKEY)
bge.events.ENTERKEY
bge.events.SEMICOLONKEY
bge.events.SLASHKEY
bge.events.SPACEKEY
bge.events.TABKEY
```

API INFO

5.1 Blender API Change Log

5.1.1 2.56 to 2.57

bpy.types.SplineBezierPoints

Function Arguments

- bpy.types.SplineBezierPoints.friction (count), was (number)

bpy.types.RenderSettings

Added

- bpy.types.RenderSettings.use_stamp_lens

Removed

- use_backbuf

bpy.types.ActionPoseMarkers

Added

- bpy.types.ActionPoseMarkers.active
- bpy.types.ActionPoseMarkers.active_index

bpy.types.SpaceImageEditor

Renamed

- **curves** -> bpy.types.SpaceImageEditor.curve

bpy.types.Scene

Removed

- `network_render`

bpy.types.GameObjectSettings

Added

- `bpy.types.GameObjectSettings.use_material_physics_fh`

Removed

- `use_material_physics`

bpy.types.SplinePoints

Function Arguments

- `bpy.types.SplinePoints.use_material_physics(count), was (number)`

bpy.types.Area

Added

- `bpy.types.Area.height`
- `bpy.types.Area.width`

bpy.types.SolidifyModifier

Added

- `bpy.types.SolidifyModifier.material_offset`
- `bpy.types.SolidifyModifier.material_offset_rim`

Removed

- `use_rim_material`

bpy.types.UserPreferencesEdit

Removed

- `use_keyframe_insert_keyingset`

bpy.types.MaterialTextureSlot**Added**

- bpy.types.MaterialTextureSlot.bump_method
- bpy.types.MaterialTextureSlot.bump_objectspace

Removed

- use_old_bump

bpy.types.ExplodeModifier**Added**

- bpy.types.ExplodeModifier.particle_uv
- bpy.types.ExplodeModifier.use_edge_cut

Removed

- use_edge_split

bpy.types.Node**Added**

- bpy.types.Node.label

bpy.types.RigidBodyJointConstraint**Added**

- bpy.types.RigidBodyJointConstraint.limit_angle_max_x
- bpy.types.RigidBodyJointConstraint.limit_angle_max_y
- bpy.types.RigidBodyJointConstraint.limit_angle_max_z
- bpy.types.RigidBodyJointConstraint.limit_angle_min_x
- bpy.types.RigidBodyJointConstraint.limit_angle_min_y
- bpy.types.RigidBodyJointConstraint.limit_angle_min_z
- bpy.types.RigidBodyJointConstraint.limit_max_x
- bpy.types.RigidBodyJointConstraint.limit_max_y
- bpy.types.RigidBodyJointConstraint.limit_max_z
- bpy.types.RigidBodyJointConstraint.limit_min_x
- bpy.types.RigidBodyJointConstraint.limit_min_y

- bpy.types.RigidBodyJointConstraint.limit_min_z

Removed

- limit_cone_max
- limit_cone_min
- limit_generic_max
- limit_generic_min

bpy.types.KeyMap

Renamed

- items -> bpy.types.KeyMap.keymap_items

bpy.types.SpaceNodeEditor

Added

- bpy.types.SpaceNodeEditor.backdrop_channels
- bpy.types.SpaceNodeEditor.backdrop_x
- bpy.types.SpaceNodeEditor.backdrop_y
- bpy.types.SpaceNodeEditor.backdrop_zoom
- bpy.types.SpaceNodeEditor.use_auto_render

bpy.types.SPHFluidSettings

Added

- bpy.types.SPHFluidSettings.factor_density
- bpy.types.SPHFluidSettings.factor_radius
- bpy.types.SPHFluidSettings.factor_repulsion
- bpy.types.SPHFluidSettings.factor_rest_length
- bpy.types.SPHFluidSettings.factor_stiff_viscosity
- bpy.types.SPHFluidSettings.plasticity
- bpy.types.SPHFluidSettings.repulsion
- bpy.types.SPHFluidSettings.spring_frames
- bpy.types.SPHFluidSettings.stiff_viscosity
- bpy.types.SPHFluidSettings.use_initial_rest_length
- bpy.types.SPHFluidSettings.use_viscoelastic_springs
- bpy.types.SPHFluidSettings.yield_ratio

Removed

- **stiffness_near**
- **viscosity_beta**

Renamed

- **viscosity_omega** -> `bpy.types.SPHFluidSettings.linear_viscosity`

bpy.types.ConstraintActuator**Added**

- `bpy.types.ConstraintActuator.direction_axis_pos`
- `bpy.types.ConstraintActuator.fh_force`

Removed

- **spring**

bpy.typesUILayout**Renamed**

- **operator_enums** -> `bpy.typesUILayout.operator_enum`

bpy.types.SpaceDopeSheetEditor**Added**

- `bpy.types.SpaceDopeSheetEditor.show_pose_markers`

bpy.types.ToolSettings**Added**

- `bpy.types.ToolSettings.edge_path_live_unwrap`
- `bpy.types.ToolSettings.proportional_size`
- `bpy.types.ToolSettings.use_keyframe_insert_keyingset`

bpy.types.EditBone

Added

- bpy.types>EditBone.bbone_x
- bpy.types>EditBone.bbone_z

Function Arguments

- bpy.types>EditBone.bbone_z (self, matrix, scale, roll), was (self, matrix)

bpy.types.ID

Renamed

- **update** -> bpy.types.ID.update_tag

bpy.types.SpaceGraphEditor

Added

- bpy.types.SpaceGraphEditor.use_fancy_drawing

bpy.types.ParticleSystem

Added

- bpy.types.ParticleSystem.child_seed

bpy.types.SpaceTimeline

Removed

- use_play_3d_editors
- use_play_animation_editors
- use_play_image_editors
- use_play_node_editors
- use_play_properties_editors
- use_play_sequence_editors
- use_play_top_left_3d_editor

bpy.types.Mesh

Added

- bpy.types.Mesh.validate

Renamed

- **show_extra_edge_angle** -> bpy.types.Mesh.show_extra_face_angle

Function Arguments

- bpy.types.Mesh.show_extra_face_angle (*self, vertices, edges, faces*), *was (self, verts, edges, faces)*

bpy.types.EnumProperty

Added

- bpy.types.EnumProperty.default_flag

Renamed

- **items** -> bpy.types.EnumProperty.enum_items

bpy.types.Screen

Added

- bpy.types.Screen.use_play_3d_editors
- bpy.types.Screen.use_play_animation_editors
- bpy.types.Screen.use_play_image_editors
- bpy.types.Screen.use_play_node_editors
- bpy.types.Screen.use_play_properties_editors
- bpy.types.Screen.use_play_sequence_editors
- bpy.types.Screen.use_play_top_left_3d_editor

bpy.types.MirrorModifier

Added

- bpy.types.MirrorModifier.use_mirror_merge

bpy.types.Operator

Added

- bpy.types.Operator.cancel

bpy.types.Brush

Added

- bpy.types.Brush.height
- bpy.types.Brush.use_fixed_texture

Renamed

- **imagepaint_tool** -> bpy.types.Brush.image_tool
- **use_paint_texture** -> bpy.types.Brush.use_paint_image
- **vertexpaint_tool** -> bpy.types.Brush.vertex_tool

bpy.types.Key

Renamed

- **keys** -> bpy.types.Key.key_blocks

bpy.types.CompositorNodeBlur

Added

- bpy.types.CompositorNodeBlur.aspect_correction

bpy.types.SpaceTextEditor

Added

- bpy.types.SpaceTextEditor.margin_column
- bpy.types.SpaceTextEditor.show_margin

bpy.types.GPencilLayer

Added

- bpy.types.GPencilLayer.show_x_ray

Removed

- **active**

bpy.types.MarbleTexture**Renamed**

- **noisebasis_2** -> bpy.types.MarbleTexture.noise_basis_2

bpy.types.Particle**Removed**

- **is_hair**

Renamed

- **keys** -> bpy.types.Particle.hair_keys
- **keys** -> bpy.types.Particle.particle_keys

bpy.types.Modifier**Added**

- bpy.types.Modifier.use_apply_on_spline

bpy.types.Property**Added**

- bpy.types.Property.is_enum_flag

bpy.types.SpaceProperties**Added**

- bpy.types.SpaceProperties.texture_context

Removed

- **show_brush_texture**

bpy.types.VertexGroups

Added

- bpy.types.VertexGroups.remove

Removed

- assign

bpy.types.Material

Added

- bpy.types.Material.shadow_only_type

bpy.types.RenderLayer

Function Arguments

- bpy.types.RenderLayer.shadow_only_type (filename, x, y), was (filename)

bpy.types.Object

Added

- bpy.types.Object.is_modified

Renamed

- **create_dupli_list** -> bpy.types.Object.dupli_list_create
- **create_mesh** -> bpy.types.Object.to_mesh
- **free_dupli_list** -> bpy.types.Object.dupli_list_clear

bpy.types.NodeTree

Added

- bpy.types.NodeTree.inputs
- bpy.types.NodeTree.outputs

bpy.types.DopeSheet

Added

- bpy.types.DopeSheet.filter_fcurve_name
- bpy.types.DopeSheet.show_lattices
- bpy.types.DopeSheet.show_only_matching_fcurves

bpy.types.ActionFCurves

Function Arguments

- bpy.types.ActionFCurves.show_only_matching_fcurves (data_path, index, action_group),
was (*data_path*, *array_index*, *action_group*)

bpy.types.ShrinkwrapModifier

Added

- bpy.types.ShrinkwrapModifier.cull_face

Removed

- use_cull_back_faces
- use_cull_front_faces

bpy.types.WindowManager

Added

- bpy.types.WindowManager.addon_filter
- bpy.types.WindowManager.addon_search
- bpy.types.WindowManager.addon_support
- bpy.types.WindowManager.event_timer_add
- bpy.types.WindowManager.event_timer_remove

bpy.types.WoodTexture

Renamed

- noisebasis_2 -> bpy.types.WoodTexture.noise_basis_2

bpy.types.VertexGroup

Added

- bpy.types.VertexGroup.add
- bpy.types.VertexGroup.remove
- bpy.types.VertexGroup.weight

bpy.types.FCurveKeyframePoints

Added

- bpy.types.FCurveKeyframePoints.insert

Function Arguments

- bpy.types.FCurveKeyframePoints.insert (*count*), *was* (*frame*, *value*, *replace*, *needed*, *fast*)

bpy.types.ThemeView3D

Added

- bpy.types.ThemeView3D.outline_width

bpy.types.Image

Added

- bpy.types.Image.pixels

bpy.types.Bone

Added

- bpy.types.Bone.bbone_x
- bpy.types.Bone.bbone_z

bpy.types.InputKeyMapPanel

Removed

- draw_entry
- draw_filtered
- draw_hierarchy

- **draw_keymaps**
- **draw_km**
- **draw_kmi**
- **draw_kmi_properties**
- **indented_layout**

bpy.types.ParticleSettings

Added

- bpy.types.ParticleSettings.active_texture
- bpy.types.ParticleSettings.active_texture_index
- bpy.types.ParticleSettings.child_parting_factor
- bpy.types.ParticleSettings.child_parting_max
- bpy.types.ParticleSettings.child_parting_min
- bpy.types.ParticleSettings.color_maximum
- bpy.types.ParticleSettings.create_long_hair_children
- bpy.types.ParticleSettings.draw_color
- bpy.types.ParticleSettings.effector_amount
- bpy.types.ParticleSettings.grid_random
- bpy.types.ParticleSettings.hair_length
- bpy.types.ParticleSettings.hexagonal_grid
- bpy.types.ParticleSettings.is_fluid
- bpy.types.ParticleSettings.kink_amplitude_clump
- bpy.types.ParticleSettings.kink_flat
- bpy.types.ParticleSettings.texture_slots
- bpy.types.ParticleSettings.timestep
- bpy.types.ParticleSettings.use_advanced_hair

Removed

- **reaction_shape**
- **show_material_color**
- **use_animate_branching**
- **use_branching**
- **use_symmetric_branching**

bpy.types.SceneGameData

Added

- bpy.types.SceneGameData.show_mouse

bpy.types.MaterialPhysics

Renamed

- **damping** -> bpy.types.MaterialPhysics.fh_damping
- **distance** -> bpy.types.MaterialPhysics.fh_distance
- **force** -> bpy.types.MaterialPhysics.fh_force
- **use_normal_align** -> bpy.types.MaterialPhysics.use_fh_normal

5.1.2 2.57 to 2.58

bpy_extras

Added

- bpy_extras
- bpy_extras.view3d_utils

Moved

- io_utils -> bpy_extras.io_utils
- image_utils -> bpy_extras.image_utils
- mesh_utils -> bpy_extras.mesh_utils
- object_utils -> bpy_extras.object_utils

bpy.types.RenderSettings

Added

- bpy.types.RenderSettings.use_bake_lores_mesh
- bpy.types.RenderSettings.use_bake_multires

bpy.types.Camera

Added

- bpy.types.Camera.show_guide

bpy.types.SpaceImageEditor**Added**

- bpy.types.SpaceImageEditor.zoom

bpy.types.SpaceView3D**Added**

- bpy.types.SpaceView3D.lock_camera

bpy.types.RegionView3D**Added**

- bpy.types.RegionView3D.is_perspective

bpy.types.Scene**Added**

- bpy.types.Scene.frame_subframe

bpy.types.Area**Removed**

- active_space

bpy.types.DisplaceModifier**Renamed**

- texture_coordinate_object -> bpy.types.DisplaceModifier.texture_coords_object

bpy.types.UserPreferencesView**Added**

- bpy.types.UserPreferencesView.use_camera_lock_parent

bpy.types.DomainFluidSettings

Added

- bpy.types.DomainFluidSettings.fluid_mesh_vertices
- bpy.types.DomainFluidSettings.surface_noobs

bpy.types.Sculpt

Added

- bpy.types.Sculpt.use_deform_only

bpy.types.ClothCollisionSettings

Added

- bpy.types.ClothCollisionSettings.distance_repel
- bpy.types.ClothCollisionSettings.repel_force

bpy.typesUILayout

Added

- bpy.typesUILayout.template_edit_mode_selection

bpy.types.ToolSettings

Added

- bpy.types.ToolSettings.use_snap_project_self

bpy.types.Mesh

Removed

- edge_face_count
- edge_face_count_dict
- edge_loops_from_edges
- edge_loops_from_faces

bpy.types.PointDensity**Added**

- bpy.types.PointDensity.falloff_curve
- bpy.types.PointDensity.falloff_speed_scale
- bpy.types.PointDensity.use_falloff_curve

bpy.types.SpaceTextEditor**Added**

- bpy.types.SpaceTextEditor.use_match_case

bpy.types.CameraActuator**Added**

- bpy.types.CameraActuator.damping

bpy.types.Property**Added**

- bpy.types.Property.is_skip_save

bpy.types.UserPreferencesSystem**Added**

- bpy.types.UserPreferencesSystem.anisotropic_filter

bpy.types.Object**Added**

- bpy.types.Object.empty_image_offset

bpy.types.Image**Added**

- bpy.types.Image.resolution

bpy.types.SceneGameData

Added

- `bpy.types.SceneGameData.use_gsl_color_management`
-

Note: The Blender Python API has areas which are still in development.

The following areas are subject to change.

- operator behavior, names and arguments
- mesh creation and editing functions

These parts of the API are relatively stable and are unlikely to change significantly

- data API, access to attributes of blender data such as mesh verts, material color, timeline frames and scene objects
 - user interface functions for defining buttons, creation of menus, headers, panels
 - render engine integration
 - modules: bgl, mathutils & game engine.
-

PYTHON MODULE INDEX

a

aud, 1120

b

bge.events, 1222

bge.logic, 1205

bge.render, 1219

bge.types, 1133

bgl, 1088

blf, 1118

bpy, 9

bpy.app, 1047

bpy.context, 5

bpy.ops.action, 10

bpy.ops.anim, 13

bpy.ops.armature, 16

bpy.ops.boid, 19

bpy.ops.brush, 19

bpy.ops.buttons, 20

bpy.ops.cloth, 21

bpy.ops.console, 21

bpy.ops.constraint, 23

bpy.ops.curve, 24

bpy.ops.ed, 28

bpy.ops.export_anim, 28

bpy.ops.export_mesh, 29

bpy.ops.export_scene, 29

bpy.ops.file, 32

bpy.ops.fluid, 34

bpy.ops.font, 34

bpy.ops.gpencil, 37

bpy.ops.graph, 37

bpy.ops.group, 41

bpy.ops.help, 42

bpy.ops.image, 42

bpy.ops.import_anim, 46

bpy.ops.import_curve, 46

bpy.ops.import_mesh, 46

bpy.ops.import_scene, 47

bpy.ops.info, 48

bpy.ops.lamp, 49

bpy.ops.lattice, 49

bpy.ops.logic, 49

bpy.ops.marker, 51

bpy.ops.material, 52

bpy.ops.mball, 52

bpy.ops.mesh, 52

bpy.ops.nla, 65

bpy.ops.node, 67

bpy.ops.object, 71

bpy.ops.outliner, 87

bpy.ops.paint, 88

bpy.ops.particle, 90

bpy.ops.pose, 92

bpy.ops.poselib, 96

bpy.ops.ptcache, 96

bpy.ops.render, 97

bpy.ops.scene, 97

bpy.ops.screen, 98

bpy.ops.script, 101

bpy.ops.sculpt, 101

bpy.ops.sequencer, 101

bpy.ops.sketch, 108

bpy.ops.sound, 108

bpy.ops.surface, 109

bpy.ops.text, 111

bpy.ops.texture, 115

bpy.ops.time, 116

bpy.ops.transform, 116

bpy.ops.ui, 125

bpy.ops.uv, 125

bpy.ops.view2d, 130

bpy.ops.view3d, 132

bpy.ops.wm, 136

bpy.ops.world, 146

bpy.path, 1046

bpy.props, 1048

bpy.types, 1040

bpy.utils, 1044

bpy_extras, 1129

bpy_extras.image_utils, 1130

bpy_extras.io_utils, 1129

`bpy_extras.mesh_utils`, 1131
`bpy_extras.object_utils`, 1129
`bpy_extras.view3d_utils`, 1132

m

`mathutils`, 1055
`mathutils.geometry`, 1084

INDEX

A

a (bge.types.KX_VertexProxy attribute), 1181
absorption (bpy.types.CollisionSettings attribute), 263
abspath() (in module bpy.path), 1046
ACCENTGRAVEKEY (in module bge.events), 1226
accuracy (bpy.types.BoidSettings attribute), 224
accuracy (bpy.types.Scopes attribute), 760
act_spline (bpy.types.ThemeView3D attribute), 939
action (bge.types.BL_ActionActuator attribute), 1136
action (bge.types.BL_ShapeActionActuator attribute), 1140
action (bpy.types.ActionActuator attribute), 148
action (bpy.types.ActionConstraint attribute), 149
action (bpy.types.AnimData attribute), 163
action (bpy.types.NlaStrip attribute), 597
action (bpy.types.ShapeActionActuator attribute), 797
action (bpy.types.SpaceDopeSheetEditor attribute), 825
Action (class in bpy.types), 146
Action.fcurves (in module bpy.types), 147
Action.frame_range (in module bpy.types), 147
Action.groups (in module bpy.types), 147
Action.pose_markers (in module bpy.types), 147
action_blend_type (bpy.types.AnimData attribute), 163
action_extrapolation (bpy.types.AnimData attribute), 163
action_frame_end (bpy.types.NlaStrip attribute), 597
action_frame_start (bpy.types.NlaStrip attribute), 597
action_influence (bpy.types.AnimData attribute), 163
action_sanitise() (in module bpy.ops.poselib), 96
action_sync_length() (in module bpy.ops.nla), 65
ActionActuator (class in bpy.types), 148
actionclip_add() (in module bpy.ops.nla), 65
ActionConstraint (class in bpy.types), 149
ActionFCurves (class in bpy.types), 151
ActionGroup (class in bpy.types), 152
ActionGroup.channels (in module bpy.types), 152
ActionGroups (class in bpy.types), 153
ActionPoseMarkers (class in bpy.types), 154
actionzone() (in module bpy.ops.screen), 98
activate() (bge.types.KX_PolygonMaterial method), 1169
activate() (bge.types.SCA_PythonController method), 1188

active (bge.types.BL_ArmatureConstraint attribute), 1198
active (bpy.types.ActionPoseMarkers attribute), 154
active (bpy.types.ArmatureBones attribute), 178
active (bpy.types.ArmatureEditBones attribute), 179
active (bpy.types.BoneGroups attribute), 233
active (bpy.types.Constraint attribute), 328
active (bpy.types.CurveSplines attribute), 351
active (bpy.types.FCurveModifiers attribute), 393
active (bpy.types.FModifier attribute), 394
active (bpy.types.GreasePencilLayers attribute), 439
active (bpy.types.KeyConfigurations attribute), 472
active (bpy.types.KeyingSetPaths attribute), 490
active (bpy.types.KeyingSets attribute), 492
active (bpy.types.KeyingSetsAll attribute), 493
active (bpy.types.KeyMapItem attribute), 475
active (bpy.types.MeshColorLayer attribute), 554
active (bpy.types.MeshFaces attribute), 560
active (bpy.types.MeshTextureFaceLayer attribute), 568
active (bpy.types.NlaTracks attribute), 601
active (bpy.types.ObjectConstraints attribute), 625
active (bpy.types.PoseBoneConstraints attribute), 700
active (bpy.types.RenderLayers attribute), 726
active (bpy.types.SceneBases attribute), 748
active (bpy.types.SceneObjects attribute), 753
active (bpy.types.ThemeBoneColorSet attribute), 908
active (bpy.typesUILayout attribute), 959
active (bpy.types.UVTextures attribute), 984
active (bpy.types.VertexColors attribute), 1006
active() (bpy.types.KeyMap method), 474
active_base (in module bpy.context), 6, 7
active_boid_rule_index (bpy.types.BoidState attribute), 227
active_boid_state_index (bpy.types.BoidSettings attribute), 225
active_bone (in module bpy.context), 6
active_camera (bge.types.KX_Scene attribute), 1174
active_channels_group (bpy.types.ThemeDopeSheet attribute), 911
active_channels_group (bpy.types.ThemeGraphEditor attribute), 916

active_clone (bpy.types.MeshTextureFaceLayer attribute), 568
active_dupliclimate_index (bpy.types.ParticleSettings attribute), 657
active_file (bpy.types.ThemeFileBrowser attribute), 913
active_file_text (bpy.types.ThemeFileBrowser attribute), 913
active_frame_delete() (in module bpy.ops.gpencil), 37
active_index (bpy.types.ActionPoseMarkers attribute), 154
active_index (bpy.types.BoneGroups attribute), 233
active_index (bpy.types.KeyingSetPaths attribute), 490
active_index (bpy.types.KeyingSets attribute), 492
active_index (bpy.types.KeyingSetsAll attribute), 493
active_index (bpy.types.ParticleSystems attribute), 679
active_index (bpy.types.PointCaches attribute), 687
active_index (bpy.types.RenderLayers attribute), 726
active_index (bpy.types.UVTextures attribute), 984
active_index (bpy.types.VertexColors attribute), 1006
active_index (bpy.types.VertexGroups attribute), 1009
active_index_set() (in module bpy.ops.brush), 19
active_keyconfig (bpy.types.UserPreferencesInput attribute), 994
active_material (bpy.types.Object attribute), 611
active_material_index (bpy.types.Object attribute), 611
active_node_material (bpy.types.Material attribute), 521
active_object (in module bpy.context), 6, 7
active_particle_target_index (bpy.types.ParticleSystem attribute), 674
active_pose_bone (in module bpy.context), 6
active_render (bpy.types.MeshColorLayer attribute), 554
active_render (bpy.types.MeshTextureFaceLayer attribute), 569
active_section (bpy.types.UserPreferences attribute), 987
active_shape_key_index (bpy.types.Object attribute), 611
active_strip (bpy.types.SequenceEditor attribute), 773
active_textbox (bpy.types.TextCurve attribute), 877
active_texture (bpy.types.Lamp attribute), 496
active_texture (bpy.types.Material attribute), 521
active_texture (bpy.types.ParticleSettings attribute), 657
active_texture (bpy.types.World attribute), 1028
active_texture_index (bpy.types.Lamp attribute), 496
active_texture_index (bpy.types.Material attribute), 521
active_texture_index (bpy.types.ParticleSettings attribute), 657
active_texture_index (bpy.types.World attribute), 1028
activity_culling (bge.types.KX_Scene attribute), 1175
activity_culling_box_radius (bpy.types.SceneGameData attribute), 749
activity_culling_radius (bge.types.KX_Scene attribute), 1175
actuator (bge.types.SCA_ActuatorSensor attribute), 1183
actuator (bpy.types.ActuatorSensor attribute), 156
Actuator (class in bpy.types), 155
actuator_add() (in module bpy.ops.logic), 49
actuator_move() (in module bpy.ops.logic), 49
actuator_remove() (in module bpy.ops.logic), 49
actuators (bge.types.KX_GameObject attribute), 1147
actuators (bge.types.SCA_IController attribute), 1135
ActuatorSensor (class in bpy.types), 156
adapt_to_speed (bpy.types.WorldLighting attribute), 1030
adaptation (bpy.types.CompositorNodeTonemap attribute), 319
adaptive_angle (bpy.types.ParticleSettings attribute), 657
adaptive_pixel (bpy.types.ParticleSettings attribute), 657
add (bpy.types.MaterialHalo attribute), 528
add() (bpy.types.FCurveKeyframePoints method), 392
add() (bpy.types.KeyingSetPaths method), 490
add() (bpy.types.LampTextureSlots class method), 501
add() (bpy.types.MaterialTextureSlots class method), 543
add() (bpy.types.MeshEdges method), 558
add() (bpy.types.MeshFaces method), 560
add() (bpy.types.MeshVertices method), 571
add() (bpy.types.ParticleSettingsTextureSlots class method), 673
add() (bpy.types.SplineBezierPoints method), 853
add() (bpy.types.SplinePoints method), 856
add() (bpy.types.VertexGroup method), 1007
add() (bpy.types.WorldTextureSlots class method), 1036
add() (in module bpy.ops.brush), 19
add() (in module bpy.ops.marker), 51
add() (in module bpy.ops.object), 71
add() (in module bpy.ops.ptcache), 96
add_file() (in module bpy.ops.node), 67
add_named() (in module bpy.ops.object), 71
add_named_cursor() (in module bpy.ops.object), 71
add_object_align_init() (in module bpy_extras.object_utils), 1129
addObject() (bge.types.KX_Scene method), 1175
Addon (class in bpy.types), 157
addon_disable() (in module bpy.ops.wm), 136
addon_enable() (in module bpy.ops.wm), 136
addon_expand() (in module bpy.ops.wm), 136
addon_filter (bpy.types.WindowManager attribute), 1022
addon_install() (in module bpy.ops.wm), 136
addon_remove() (in module bpy.ops.wm), 136
addon_search (bpy.types.WindowManager attribute), 1022
addon_support (bpy.types.WindowManager attribute), 1022
Addons (class in bpy.types), 158
addScene() (in module bge.logic), 1208
addWheel() (bge.types.KX_VehicleWrapper method), 1178
AdjustmentSequence (class in bpy.types), 159
AdjustmentSequence.color_balance (in module bpy.types), 159

AdjustmentSequence.crop (in module bpy.types), 159
 AdjustmentSequence.proxy (in module bpy.types), 159
 AdjustmentSequence.transform (in module bpy.types), 159
 aero (bpy.types.SoftBodySettings attribute), 813
 aerodynamics_type (bpy.types.SoftBodySettings attribute), 813
 aggression (bpy.types.BoidSettings attribute), 225
 air_acc_max (bpy.types.BoidSettings attribute), 225
 air_ave_max (bpy.types.BoidSettings attribute), 225
 air_damping (bpy.types.ClothSettings attribute), 255
 air_personal_space (bpy.types.BoidSettings attribute), 225
 air_speed_max (bpy.types.BoidSettings attribute), 225
 air_speed_min (bpy.types.BoidSettings attribute), 225
 AKEY (in module bge.events), 1223
 alert (bpy.typesUILayout attribute), 959
 align (bpy.types.SpaceProperties attribute), 837
 align (bpy.types.TextCurve attribute), 877
 align() (in module bpy.ops.armature), 16
 align() (in module bpy.ops.object), 71
 align() (in module bpy.ops.uv), 125
 align_orientation() (bpy.types>EditBone method), 371
 align_roll() (bpy.types>EditBone method), 371
 alignAxisToVect() (bge.types.KX_GameObject method), 1148
 alignment (bpy.typesUILayout attribute), 959
 alive_state (bpy.types.Particle attribute), 647
 all (bpy.types.EffectorWeights attribute), 376
 alliance (bpy.types.ParticleTarget attribute), 680
 alpha (bpy.types.CompositorNodeMapUV attribute), 302
 alpha (bpy.types.GPencilLayer attribute), 422
 alpha (bpy.types.Material attribute), 521
 alpha (bpy.types.SmokeDomainSettings attribute), 806
 alpha_factor (bpy.types.MaterialTextureSlot attribute), 538
 alpha_influence (bpy.types.ParticleFluidSettings attribute), 652
 alpha_mode (bpy.types.RenderSettings attribute), 729
 alt (bpy.types.KeyMapItem attribute), 475
 AlwaysSensor (class in bpy.types), 161
 ambient (bpy.types.Material attribute), 521
 ambient_color (bpy.types.World attribute), 1028
 ambient_factor (bpy.types.MaterialTextureSlot attribute), 538
 amplify (bpy.types.SmokeDomainSettings attribute), 807
 amplitude (bpy.types.FModifierFunctionGenerator attribute), 399
 AndController (class in bpy.types), 162
 angle (bge.types.KX_RadarSensor attribute), 1170
 angle (bpy.types.BrushTextureSlot attribute), 242
 angle (bpy.types.Camera attribute), 244
 angle (bpy.types.CompositorNodeDBlur attribute), 286
 angle (bpy.types.CompositorNodeDefocus attribute), 287
 angle (bpy.types.RadarSensor attribute), 711
 angle (bpy.types.ScrewModifier attribute), 763
 angle (bpy.types.WipeSequence attribute), 1025
 angle (mathutils.Quaternion attribute), 1063
 angle_limit (bpy.types.BevelModifier attribute), 186
 angle_max (bpy.types.ConstraintActuator attribute), 330
 angle_min (bpy.types.ConstraintActuator attribute), 330
 angle_offset (bpy.types.CompositorNodeGlare attribute), 294
 angular_velocity (bpy.types>EditObjectActuator attribute), 372
 angular_velocity (bpy.types.ObjectActuator attribute), 621
 angular_velocity (bpy.types.Particle attribute), 647
 angular_velocity (bpy.types.ParticleKey attribute), 656
 angular_velocity_factor (bpy.types.ParticleSettings attribute), 658
 angular_velocity_mode (bpy.types.ParticleSettings attribute), 658
 angularVelocity (bge.types.KX_SCA_AddObjectActuator attribute), 1172
 angV (bge.types.KX_ObjectActuator attribute), 1161
 animation_cancel() (in module bpy.ops.screen), 98
 animation_data_clear() (bpy.types.ID method), 449
 animation_data_create() (bpy.types.ID method), 449
 animation_offset_end (bpy.types.AdjustmentSequence attribute), 159
 animation_offset_end (bpy.types.ImageSequence attribute), 457
 animation_offset_end (bpy.types.MetaSequence attribute), 578
 animation_offset_end (bpy.types.MovieSequence attribute), 586
 animation_offset_end (bpy.types.MulticamSequence attribute), 589
 animation_offset_end (bpy.types.SceneSequence attribute), 757
 animation_offset_end (bpy.types.SoundSequence attribute), 821
 animation_offset_start (bpy.types.AdjustmentSequence attribute), 159
 animation_offset_start (bpy.types.ImageSequence attribute), 457
 animation_offset_start (bpy.types.MetaSequence attribute), 578
 animation_offset_start (bpy.types.MovieSequence attribute), 586
 animation_offset_start (bpy.types.MulticamSequence attribute), 589
 animation_offset_start (bpy.types.SceneSequence attribute), 757
 animation_offset_start (bpy.types.SoundSequence attribute), 821
 animation_play() (in module bpy.ops.screen), 98

animation_player (bpy.types.UserPreferencesFilePaths attribute), 991
animation_player_preset (bpy.types.UserPreferencesFilePaths attribute), 992
animation_step() (in module bpy.ops.screen), 98
AnimData (class in bpy.types), 163
AnimData.drivers (in module bpy.types), 163
AnimData.nla_tracks (in module bpy.types), 163
AnimDataDrivers (class in bpy.types), 164
AnimViz (class in bpy.types), 165
AnimViz.motion_path (in module bpy.types), 165
AnimViz.onion_skin_frames (in module bpy.types), 165
AnimVizMotionPaths (class in bpy.types), 166
AnimVizOnionSkinning (class in bpy.types), 168
anisotropic_filter (bpy.types.UserPreferencesSystem attribute), 996
antialiasing_samples (bpy.types.RenderSettings attribute), 729
any (bpy.types.KeyMapItem attribute), 475
AnyType (class in bpy.types), 169
ao_blend_type (bpy.types.WorldLighting attribute), 1030
ao_factor (bpy.types.WorldLighting attribute), 1030
appconfig_activate() (in module bpy.ops.wm), 136
appconfig_default() (in module bpy.ops.wm), 136
append() (bge.types.CListValue method), 1141
append() (bpy.types.Header class method), 444
append() (bpy.types.IDMaterials method), 450
append() (bpy.types.Menu class method), 548
append() (bpy.types.Panel class method), 645
apply_effector_to_children (bpy.types.ParticleSettings attribute), 658
apply_guide_to_children (bpy.types.ParticleSettings attribute), 658
apply_pose() (in module bpy.ops.poselib), 96
apply_scale() (in module bpy.ops.nla), 65
apply_to_children (bpy.types.FCurveActuator attribute), 390
apply_to_children (bpy.types.VisibilityActuator attribute), 1011
apply_to_hair_growing (bpy.types.EffectorWeights attribute), 376
apply_to_location (bpy.types.FieldSettings attribute), 405
apply_to_rotation (bpy.types.FieldSettings attribute), 405
applyBraking() (bge.types.KX_VehicleWrapper method), 1178
applyEngineForce() (bge.types.KX_VehicleWrapper method), 1178
applyForce() (bge.types.KX_GameObject method), 1148
applyImpulse() (bge.types.KX_GameObject method), 1150
applyMovement() (bge.types.KX_GameObject method), 1148
applyRotation() (bge.types.KX_GameObject method), 1148
applyTorque() (bge.types.KX_GameObject method), 1149
Area (class in bpy.types), 170
Area.height (in module bpy.types), 170
Area.regions (in module bpy.types), 170
Area.spaces (in module bpy.types), 170
Area.width (in module bpy.types), 170
area_dupli() (in module bpy.ops.screen), 98
area_join() (in module bpy.ops.screen), 98
area_move() (in module bpy.ops.screen), 98
area_options() (in module bpy.ops.screen), 98
area_split() (in module bpy.ops.screen), 99
area_swap() (in module bpy.ops.screen), 99
area_tri() (in module mathutils.geometry), 1084
AreaLamp (class in bpy.types), 171
AreaSpaces (class in bpy.types), 174
AreaSpaces.active (in module bpy.types), 174
arm_head (bge.types.BL_ArmatureBone attribute), 1204
arm_mat (bge.types.BL_ArmatureBone attribute), 1204
arm_tail (bge.types.BL_ArmatureBone attribute), 1204
armature (bpy.types.MaskModifier attribute), 519
Armature (class in bpy.types), 174
armature (in module bpy.context), 7
Armature.animation_data (in module bpy.types), 174
Armature.bones (in module bpy.types), 174
Armature.edit_bones (in module bpy.types), 175
armature_add() (in module bpy.ops.object), 71
armature_apply() (in module bpy.ops.pose), 92
armature_layers() (in module bpy.ops.armature), 16
armature_layers() (in module bpy.ops.pose), 92
ArmatureActuator (class in bpy.types), 177
ArmatureBones (class in bpy.types), 178
ArmatureEditBones (class in bpy.types), 179
ArmatureModifier (class in bpy.types), 180
ArmatureSensor (class in bpy.types), 181
array_index (bpy.types.FCurve attribute), 388
array_index (bpy.types.KeyingSetPath attribute), 489
ArrayModifier (class in bpy.types), 182
as_keywords() (bpy.types.Operator method), 634
as_pointer() (bpy.types.bpy_struct method), 1041
as_string() (bpy.types.Text static method), 874
aspect() (in module blf), 1118
aspect_correction (bpy.types.CompositorNodeBlur attribute), 272
aspect_x (bpy.types.UVProjectModifier attribute), 982
aspect_y (bpy.types.UVProjectModifier attribute), 982
asymmetry (bpy.types.MaterialVolume attribute), 544
atmosphere_distance_factor (bpy.types.LampSkySettings attribute), 498
atmosphere_extinction (bpy.types.LampSkySettings attribute), 498
atmosphere_inscattering (bpy.types.LampSkySettings attribute), 498

atmosphere_turbidity (bpy.types.LampSkySettings attribute), 498
attenuation (aud.Handle attribute), 1127
attenuation (bpy.types.SoundSequence attribute), 821
attraction_radius (bpy.types.ControlFluidSettings attribute), 335
attraction_strength (bpy.types.ControlFluidSettings attribute), 335
attrDict (bge.types.KX_GameObject attribute), 1147
aud (module), 1120
AUD_DEVICE_JACK (in module aud), 1121
AUD_DEVICE_NULL (in module aud), 1121
AUD_DEVICE_OPENGL (in module aud), 1121
AUD_DEVICE SDL (in module aud), 1121
AUD_DISTANCE_MODEL_EXPONENT (in module aud), 1121
AUD_DISTANCE_MODEL_EXPONENT_CLAMPED (in module aud), 1121
AUD_DISTANCE_MODEL_INVALID (in module aud), 1121
AUD_DISTANCE_MODEL_INVERSE (in module aud), 1121
AUD_DISTANCE_MODEL_INVERSE_CLAMPED (in module aud), 1121
AUD_DISTANCE_MODEL_LINEAR (in module aud), 1121
AUD_DISTANCE_MODEL_LINEAR_CLAMPED (in module aud), 1121
AUD_FORMAT_FLOAT32 (in module aud), 1121
AUD_FORMAT_FLOAT64 (in module aud), 1121
AUD_FORMAT_INVALID (in module aud), 1121
AUD_FORMAT_S16 (in module aud), 1121
AUD_FORMAT_S24 (in module aud), 1121
AUD_FORMAT_S32 (in module aud), 1121
AUD_FORMAT_U8 (in module aud), 1121
AUD_STATUS_INVALID (in module aud), 1121
AUD_STATUS_PAUSED (in module aud), 1121
AUD_STATUS_PLAYING (in module aud), 1121
audio_channels (bpy.types.UserPreferencesSystem attribute), 996
audio_device (bpy.types.UserPreferencesSystem attribute), 996
audio_distance_model (bpy.types.Scene attribute), 743
audio_doppler_factor (bpy.types.Scene attribute), 743
audio_doppler_speed (bpy.types.Scene attribute), 743
audio_mixing_buffer (bpy.types.UserPreferencesSystem attribute), 996
audio_sample_format (bpy.types.UserPreferencesSystem attribute), 996
audio_sample_rate (bpy.types.UserPreferencesSystem attribute), 996
audio_strip (bpy.types.ThemeSequenceEditor attribute), 930
author (bpy.types.UserPreferencesSystem attribute), 996
auto_keying_mode (bpy.types.ToolSettings attribute), 948
auto_keying_mode (bpy.types.UserPreferencesEdit attribute), 988
auto_save_time (bpy.types.UserPreferencesFilePaths attribute), 992
auto_smooth_angle (bpy.types.Mesh attribute), 549
auto_smooth_factor (bpy.types.Brush attribute), 236
auto_snap (bpy.types.SpaceDopeSheetEditor attribute), 825
auto_snap (bpy.types.SpaceGraphEditor attribute), 827
auto_snap (bpy.types.SpaceNLA attribute), 833
autocomplete() (in module bpy.ops.console), 21
autodesk_3ds() (in module bpy.ops.export_scene), 29
autodesk_3ds() (in module bpy.ops.import_scene), 47
autoside_names() (in module bpy.ops.armature), 16
autoside_names() (in module bpy.ops.pose), 92
auxiliary_target (bpy.types.ShrinkwrapModifier attribute), 803
average_islands_scale() (in module bpy.ops.uv), 125
average_separation (bpy.types.WorldStarsSettings attribute), 1034
axis (bge.types.KX_RadarSensor attribute), 1170
axis (bge.types.KX_RaySensor attribute), 1171
axis (bge.types.SCA_JoystickSensor attribute), 1185
axis (bpy.types.CameraActuator attribute), 246
axis (bpy.types.CompositorNodeFlip attribute), 292
axis (bpy.types.CompositorNodeSplitViewer attribute), 316
axis (bpy.types.ParticleInstanceModifier attribute), 654
axis (bpy.types.RadarSensor attribute), 711
axis (bpy.types.RaySensor attribute), 715
axis (bpy.types.ScrewModifier attribute), 763
axis (mathutils.Quaternion attribute), 1063
axis_conversion() (in module bpy_extras.io_utils), 1129
axis_direction (bpy.types.JoystickSensor attribute), 468
axis_number (bpy.types.JoystickSensor attribute), 468
axis_threshold (bpy.types.JoystickSensor attribute), 469
axis_x (bpy.types.RigidBodyJointConstraint attribute), 738
axis_y (bpy.types.RigidBodyJointConstraint attribute), 738
axis_z (bpy.types.RigidBodyJointConstraint attribute), 738
axisSingle (bge.types.SCA_JoystickSensor attribute), 1184
axisValues (bge.types.SCA_JoystickSensor attribute), 1184

B

b (bge.types.KX_VertexProxy attribute), 1181
b (mathutils.Color attribute), 1055
back (bpy.types.MaterialSubsurfaceScattering attribute), 536

back (bpy.types.ThemeAudioWindow attribute), 907
back (bpy.types.ThemeConsole attribute), 909
back (bpy.types.ThemeDopeSheet attribute), 911
back (bpy.types.ThemeFileBrowser attribute), 913
back (bpy.types.ThemeGraphEditor attribute), 916
back (bpy.types.ThemeImageEditor attribute), 919
back (bpy.types.ThemeInfo attribute), 921
back (bpy.types.ThemeLogicEditor attribute), 922
back (bpy.types.ThemeNLAEditor attribute), 923
back (bpy.types.ThemeNodeEditor attribute), 925
back (bpy.types.ThemeOutliner attribute), 927
back (bpy.types.ThemeProperties attribute), 928
back (bpy.types.ThemeSequenceEditor attribute), 930
back (bpy.types.ThemeTextEditor attribute), 933
back (bpy.types.ThemeTimeline attribute), 934
back (bpy.types.ThemeUserPreferences attribute), 938
back (bpy.types.ThemeView3D attribute), 939
back_to_previous() (in module bpy.ops.screen), 99
backdrop_channels (bpy.types.SpaceNodeEditor attribute), 834
backdrop_x (bpy.types.SpaceNodeEditor attribute), 834
backdrop_y (bpy.types.SpaceNodeEditor attribute), 834
backdrop_zoom (bpy.types.SpaceNodeEditor attribute), 834
background (in module bpy.app), 1047
background_image_add() (in module bpy.ops.view3d), 132
background_image_remove() (in module bpy.ops.view3d), 132
background_set (bpy.types.Scene attribute), 743
BackgroundImage (class in bpy.types), 184
BackgroundImage.image_user (in module bpy.types), 184
backimage_move() (in module bpy.ops.node), 68
backimage_sample() (in module bpy.ops.node), 68
backimage_zoom() (in module bpy.ops.node), 68
backscattered_light (bpy.types.LampSkySettings attribute), 498
BACKSLASHKEY (in module bge.events), 1226
BACKSPACEKEY (in module bge.events), 1226
bake() (in module bpy.ops.fluid), 34
bake() (in module bpy.ops.graph), 37
bake() (in module bpy.ops.nla), 65
bake() (in module bpy.ops.ptcache), 96
bake_aa_mode (bpy.types.RenderSettings attribute), 729
bake_all() (in module bpy.ops.ptcache), 96
bake_bias (bpy.types.RenderSettings attribute), 729
bake_distance (bpy.types.RenderSettings attribute), 729
bake_from_cache() (in module bpy.ops.ptcache), 96
bake_image() (in module bpy.ops.object), 72
bake_location (bpy.types.AnimVizMotionPaths attribute), 166
bake_margin (bpy.types.RenderSettings attribute), 729
bake_normal_space (bpy.types.RenderSettings attribute), 729
bake_quad_split (bpy.types.RenderSettings attribute), 729
bake_type (bpy.types.RenderSettings attribute), 729
ball_damp (bpy.types.SoftBodySettings attribute), 813
ball_size (bpy.types.SoftBodySettings attribute), 813
ball_stiff (bpy.types.SoftBodySettings attribute), 813
bank (bpy.types.BoidSettings attribute), 225
banner() (in module bpy.ops.console), 22
bars (bpy.types.ThemeNLAEditor attribute), 923
bars_selected (bpy.types.ThemeNLAEditor attribute), 923
barycentric_transform() (in module mathutils.geometry), 1085
bbone_in (bpy.types.Bone attribute), 228
bbone_in (bpy.types.EditBone attribute), 368
bbone_out (bpy.types.Bone attribute), 228
bbone_out (bpy.types.EditBone attribute), 368
bbone_segments (bge.types.BL_ArmatureBone attribute), 1204
bbone_segments (bpy.types.Bone attribute), 228
bbone_segments (bpy.types.EditBone attribute), 368
bbone_x (bpy.types.Bone attribute), 228
bbone_x (bpy.types.EditBone attribute), 368
bbone_z (bpy.types.Bone attribute), 228
bbone_z (bpy.types.EditBone attribute), 368
beautify_fill() (in module bpy.ops.mesh), 52
begin_result() (bpy.types.RenderEngine method), 720
bend (bpy.types.SoftBodySettings attribute), 813
bending_stiffness (bpy.types.ClothSettings attribute), 255
bending_stiffness_max (bpy.types.ClothSettings attribute), 256
beta (bpy.types.SmokeDomainSettings attribute), 807
bevel_depth (bpy.types.Curve attribute), 343
bevel_object (bpy.types.Curve attribute), 343
bevel_resolution (bpy.types.Curve attribute), 343
bevel_weight (bpy.types.MeshEdge attribute), 556
bevel_weight (bpy.types.MeshVertex attribute), 570
BevelModifier (class in bpy.types), 185
BezierSplinePoint (class in bpy.types), 187
bge.events (module), 1222
bge.logic (module), 1205
bge.render (module), 1219
bge.types (module), 1133
bgl (module), 1088
bias (bpy.types.WorldLighting attribute), 1030
billboard_align (bpy.types.ParticleSettings attribute), 658
billboard_animation (bpy.types.ParticleSettings attribute), 658
billboard_normal_uv (bpy.types.ParticleSystem attribute), 674
billboard_object (bpy.types.ParticleSettings attribute), 658

billboard_offset (bpy.types.ParticleSettings attribute), 658
 billboard_offset_split (bpy.types.ParticleSettings attribute), 658
 billboard_size (bpy.types.ParticleSettings attribute), 658
 billboard_split_uv (bpy.types.ParticleSystem attribute), 674
 billboard_tilt (bpy.types.ParticleSettings attribute), 658
 billboard_tilt_random (bpy.types.ParticleSettings attribute), 658
 billboard_time_index_uv (bpy.types.ParticleSystem attribute), 674
 billboard_uv_split (bpy.types.ParticleSettings attribute), 658
 billboard_velocity_head (bpy.types.ParticleSettings attribute), 659
 billboard_velocity_tail (bpy.types.ParticleSettings attribute), 659
 binary_path (in module bpy.app), 1047
 birth_time (bpy.types.Particle attribute), 647
 BKEY (in module bge.events), 1223
 BL_ActionActuator (class in bge.types), 1136
 BL_ArmatureActuator (class in bge.types), 1194
 BL_ArmatureActuator.KX_ACT_ARMATURE_DISABLE (in module bge.types), 1195
 BL_ArmatureActuator.KX_ACT_ARMATURE_ENABLE (in module bge.types), 1195
 BL_ArmatureActuator.KX_ACT_ARMATURE_RUN (in module bge.types), 1194
 BL_ArmatureActuator.KX_ACT_ARMATURE_SETTARGET (in module bge.types), 1195
 BL_ArmatureActuator.KX_ACT_ARMATURE_SETWEIGHT (in module bge.types), 1195
 BL_ArmatureBone (class in bge.types), 1203
 BL_ArmatureChannel (class in bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_QUAT (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_XYZ (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_XZY (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_YXZ (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_YZX (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_ZXY (in module bge.types), 1199
 BL_ArmatureChannel.PCHAN_ROT_ZYX (in module bge.types), 1199
 BL_ArmatureConstraint (class in bge.types), 1196
 BL_ArmatureConstraint.CONSTRAINT_IK_COPYPOSE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_DISTANCE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_POS (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_ROT (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_STRETCH (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_FLAG_TIP (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_MODE_INSIDE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_MODE_ONSURFACE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_IK_MODE_OUTSIDE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_CLAMPTO (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_DISTLIMIT (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_KINEMATIC (in module bge.types), 1196
 BL_ArmatureConstraint.CONSTRAINT_TYPE_LOCKTRACK (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_LOCLIKE (in module bge.types), 1196
 BL_ArmatureConstraint.CONSTRAINT_TYPE_MINMAX (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_ROTLIKE (in module bge.types), 1196
 BL_ArmatureConstraint.CONSTRAINT_TYPE_SIZELIKE (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_STRETCHTO (in module bge.types), 1197
 BL_ArmatureConstraint.CONSTRAINT_TYPE_TRACKTO (in module bge.types), 1196
 BL_ArmatureConstraint.CONSTRAINT_TYPE_TRANSFORM (in module bge.types), 1197
 BL_ArmatureObject (class in bge.types), 1194
 bl_context (bpy.types.Panel attribute), 644
 bl_description (bpy.types.Macro attribute), 514
 bl_description (bpy.types.Operator attribute), 633
 BL_DST_ALPHA (in module bge.logic), 1218
 BL_DST_COLOR (in module bge.logic), 1218
 bl_idname (bpy.types.Header attribute), 444
 bl_idname (bpy.types.KeyingSetInfo attribute), 488
 bl_idname (bpy.types.Macro attribute), 514
 bl_idname (bpy.types.Menu attribute), 547
 bl_idname (bpy.types.Operator attribute), 633
 bl_idname (bpy.types.Panel attribute), 644
 bl_idname (bpy.types.RenderEngine attribute), 720
 bl_label (bpy.types.KeyingSetInfo attribute), 488
 bl_label (bpy.types.Macro attribute), 514
 bl_label (bpy.types.Menu attribute), 548
 bl_label (bpy.types.Operator attribute), 633
 bl_label (bpy.types.Panel attribute), 644

bl_label (bpy.types.RenderEngine attribute), 720
BL_ONE (in module bge.logic), 1218
BL_ONE_MINUS_DST_ALPHA (in module bge.logic), 1218
BL_ONE_MINUS_DST_COLOR (in module bge.logic), 1218
BL_ONE_MINUS_SRC_ALPHA (in module bge.logic), 1218
BL_ONE_MINUS_SRC_COLOR (in module bge.logic), 1218
bl_options (bpy.types.KeyingSet attribute), 487
bl_options (bpy.types.KeyingSetInfo attribute), 488
bl_options (bpy.types.KeyingSetPath attribute), 489
bl_options (bpy.types.Macro attribute), 514
bl_options (bpy.types.Operator attribute), 633
bl_options (bpy.types.Panel attribute), 644
bl_region_type (bpy.types.Panel attribute), 644
BL_Shader (class in bge.types), 1137
BL_ShapeActionActuator (class in bge.types), 1140
bl_space_type (bpy.types.Header attribute), 444
bl_space_type (bpy.types.Panel attribute), 644
BL_SRC_ALPHA (in module bge.logic), 1218
BL_SRC_ALPHA_SATURATE (in module bge.logic), 1219
BL_SRC_COLOR (in module bge.logic), 1219
bl_use_postprocess (bpy.types.RenderEngine attribute), 720
bl_use_preview (bpy.types.RenderEngine attribute), 720
BL_ZERO (in module bge.logic), 1219
black_level (bpy.types.CurveMapping attribute), 348
blend (bpy.types.Brush attribute), 236
blend (bpy.types.ThemeWidgetStateColors attribute), 944
blend_alpha (bpy.types.Sequence attribute), 768
blend_distance (bpy.types.MaterialStrand attribute), 535
blend_factor (bpy.types.WorldTextureSlot attribute), 1035
blend_from_shape() (in module bpy.ops.mesh), 52
blend_in (bpy.types.NlaStrip attribute), 597
blend_out (bpy.types.NlaStrip attribute), 597
blend_paths() (in module bpy.utils), 1044
blend_type (bpy.types.CompositorNodeMixRGB attribute), 305
blend_type (bpy.types.FModifierNoise attribute), 402
blend_type (bpy.types.MeshTextureFace attribute), 566
blend_type (bpy.types.NlaStrip attribute), 597
blend_type (bpy.types.Sequence attribute), 768
blend_type (bpy.types.ShaderNodeMixRGB attribute), 785
blend_type (bpy.types.TextureNodeMixRGB attribute), 894
blend_type (bpy.types.TextureSlot attribute), 903
BlendData (class in bpy.types), 188
BlendData.actions (in module bpy.types), 188
BlendData.armatures (in module bpy.types), 188
BlendData.brushes (in module bpy.types), 188
BlendData.cameras (in module bpy.types), 188
BlendData.curves (in module bpy.types), 188
BlendData.filepath (in module bpy.types), 189
BlendData.fonts (in module bpy.types), 189
BlendData.grease_pencil (in module bpy.types), 189
BlendData.groups (in module bpy.types), 189
BlendData.images (in module bpy.types), 189
BlendData.is_dirty (in module bpy.types), 189
BlendData.is_saved (in module bpy.types), 189
BlendData.lamps (in module bpy.types), 189
BlendData.lattices (in module bpy.types), 189
BlendData.libraries (in module bpy.types), 189
BlendData.materials (in module bpy.types), 189
BlendData.meshes (in module bpy.types), 189
BlendData.metaballs (in module bpy.types), 189
BlendData.node_groups (in module bpy.types), 189
BlendData.objects (in module bpy.types), 190
BlendData.particles (in module bpy.types), 190
BlendData.scenes (in module bpy.types), 190
BlendData.screens (in module bpy.types), 190
BlendData.scripts (in module bpy.types), 190
BlendData.shape_keys (in module bpy.types), 190
BlendData.sounds (in module bpy.types), 190
BlendData.texts (in module bpy.types), 190
BlendData.textures (in module bpy.types), 190
BlendData.window_managers (in module bpy.types), 190
BlendData.worlds (in module bpy.types), 190
BlendDataActions (class in bpy.types), 191
BlendDataArmatures (class in bpy.types), 192
BlendDataBrushes (class in bpy.types), 193
BlendDataCameras (class in bpy.types), 194
BlendDataCurves (class in bpy.types), 195
BlendDataFonts (class in bpy.types), 196
BlendDataGreasePencils (class in bpy.types), 197
BlendDataGroups (class in bpy.types), 198
BlendDataImages (class in bpy.types), 199
BlendDataLamps (class in bpy.types), 200
BlendDataLattices (class in bpy.types), 201
BlendDataLibraries (class in bpy.types), 202
BlendDataMaterials (class in bpy.types), 204
BlendDataMeshes (class in bpy.types), 205
BlendDataMetaBalls (class in bpy.types), 206
BlendDataNodeTrees (class in bpy.types), 207
BlendDataObjects (class in bpy.types), 208
BlendDataParticles (class in bpy.types), 209
BlendDataScenes (class in bpy.types), 210
BlendDataScreens (class in bpy.types), 211
BlendDataSounds (class in bpy.types), 211
BlendDataTexts (class in bpy.types), 212
BlendDataTextures (class in bpy.types), 213
BlendDataWindowManagers (class in bpy.types), 214
BlendDataWorlds (class in bpy.types), 215
BlenderRNA (class in bpy.types), 217

BlenderRNA.structs (in module bpy.types), 217
blendIn (bge.types.BL_ActionActuator attribute), 1136
blendIn (bge.types.BL_ShapeActionActuator attribute), 1140
BlendTexture (class in bpy.types), 216
BlendTexture.users_material (in module bpy.types), 216
BlendTexture.users_object_modifier (in module bpy.types), 216
blendTime (bge.types.BL_ActionActuator attribute), 1136
blendTime (bge.types.BL_ShapeActionActuator attribute), 1141
blf (module), 1118
blur() (in module blf), 1118
blur_max (bpy.types.CompositorNodeDefocus attribute), 287
blur_radius (bpy.types.GlowSequence attribute), 436
blur_width (bpy.types.WipeSequence attribute), 1025
bodies (bge.types.KX_NetworkMessageSensor attribute), 1160
body (bge.types.KX_NetworkMessageActuator attribute), 1160
body (bpy.types.ConsoleLine attribute), 327
body (bpy.types.TextCurve attribute), 877
body (bpy.types.TextLine attribute), 880
body_message (bpy.types.MessageActuator attribute), 571
body_property (bpy.types.MessageActuator attribute), 572
body_type (bpy.types.MessageActuator attribute), 572
boid (bpy.types.EffectorWeights attribute), 376
BoidRule (class in bpy.types), 218
BoidRule.type (in module bpy.types), 218
BoidRuleAverageSpeed (class in bpy.types), 219
BoidRuleAvoid (class in bpy.types), 220
BoidRuleAvoidCollision (class in bpy.types), 221
BoidRuleFight (class in bpy.types), 222
BoidRuleFollowLeader (class in bpy.types), 223
BoidRuleGoal (class in bpy.types), 224
BoidSettings (class in bpy.types), 224
BoidSettings.active_boid_state (in module bpy.types), 224
BoidSettings.states (in module bpy.types), 226
BoidState (class in bpy.types), 227
BoidState.active_boid_rule (in module bpy.types), 227
BoidState.rules (in module bpy.types), 227
bokeh (bpy.types.CompositorNodeDefocus attribute), 287
bone (bge.types.BL_ArmatureChannel attribute), 1199
bone (bpy.types.ArmatureActuator attribute), 177
bone (bpy.types.ArmatureSensor attribute), 181
Bone (class in bpy.types), 228
bone (in module bpy.context), 8
Bone.basename (in module bpy.types), 231
Bone.center (in module bpy.types), 231
Bone.children (in module bpy.types), 229, 231
Bone.children_recursive (in module bpy.types), 231
Bone.children_recursive_basename (in module bpy.types), 231
Bone.parent (in module bpy.types), 229
Bone.parent_recursive (in module bpy.types), 231
Bone.use_connect (in module bpy.types), 230
Bone.vector (in module bpy.types), 231
Bone.x_axis (in module bpy.types), 231
Bone.y_axis (in module bpy.types), 231
Bone.z_axis (in module bpy.types), 231
bone_group (bpy.types.PoseBone attribute), 695
bone_group_index (bpy.types.PoseBone attribute), 695
bone_layers() (in module bpy.ops.armature), 17
bone_layers() (in module bpy.ops.pose), 92
bone_mat (bge.types.BL_ArmatureBone attribute), 1204
bone_pose (bpy.types.ThemeView3D attribute), 939
bone_primitive_add() (in module bpy.ops.armature), 17
bone_solid (bpy.types.ThemeView3D attribute), 939
bone_target (bpy.types.DriverTarget attribute), 364
BoneGroup (class in bpy.types), 232
BoneGroup.colors (in module bpy.types), 232
BoneGroups (class in bpy.types), 233
bookmark_add() (in module bpy.ops.file), 32
bookmark_toggle() (in module bpy.ops.file), 32
BooleanModifier (class in bpy.types), 234
BooleanProperty (class in bpy.types), 235
BooleanProperty.array_length (in module bpy.types), 235
BooleanProperty.default (in module bpy.types), 235
BooleanProperty.default_array (in module bpy.types), 235
BoolProperty() (in module bpy.props), 1050
BoolVectorProperty() (in module bpy.props), 1050
boost_factor (bpy.types.GlowSequence attribute), 436
border_max_x (bpy.types.RenderSettings attribute), 729
border_max_y (bpy.types.RenderSettings attribute), 729
border_min_x (bpy.types.RenderSettings attribute), 729
border_min_y (bpy.types.RenderSettings attribute), 730
box() (bpy.typesUILayout method), 960
box_pack_2d() (in module mathutils.geometry), 1085
boxInsideFrustum() (bge.types.KX_Camera method), 1192
bpy (module), 9
bpy.app (module), 1047
bpy.context (module), 5
bpy.ops.action (module), 10
bpy.ops.anim (module), 13
bpy.ops.armature (module), 16
bpy.ops.boid (module), 19
bpy.ops.brush (module), 19
bpy.ops.buttons (module), 20
bpy.ops.cloth (module), 21
bpy.ops.console (module), 21

bpy.ops.constraint (module), 23
bpy.ops.curve (module), 24
bpy.ops.ed (module), 28
bpy.ops.export_anim (module), 28
bpy.ops.export_mesh (module), 29
bpy.ops.export_scene (module), 29
bpy.ops.file (module), 32
bpy.ops.fluid (module), 34
bpy.ops.font (module), 34
bpy.ops.gpencil (module), 37
bpy.ops.graph (module), 37
bpy.ops.group (module), 41
bpy.ops.help (module), 42
bpy.ops.image (module), 42
bpy.ops.import_anim (module), 46
bpy.ops.import_curve (module), 46
bpy.ops.import_mesh (module), 46
bpy.ops.import_scene (module), 47
bpy.ops.info (module), 48
bpy.ops.lamp (module), 49
bpy.ops.lattice (module), 49
bpy.ops.logic (module), 49
bpy.ops.marker (module), 51
bpy.ops.material (module), 52
bpy.ops.mball (module), 52
bpy.ops.mesh (module), 52
bpy.ops.nla (module), 65
bpy.ops.node (module), 67
bpy.ops.object (module), 71
bpy.ops.outliner (module), 87
bpy.ops.paint (module), 88
bpy.ops.particle (module), 90
bpy.ops.pose (module), 92
bpy.ops.poselib (module), 96
bpy.ops.ptcache (module), 96
bpy.ops.render (module), 97
bpy.ops.scene (module), 97
bpy.ops.screen (module), 98
bpy.ops.script (module), 101
bpy.ops.sculpt (module), 101
bpy.ops.sequencer (module), 101
bpy.ops.sketch (module), 108
bpy.ops.sound (module), 108
bpy.ops.surface (module), 109
bpy.ops.text (module), 111
bpy.ops.texture (module), 115
bpy.ops.time (module), 116
bpy.ops.transform (module), 116
bpy.ops.ui (module), 125
bpy.ops.uv (module), 125
bpy.ops.view2d (module), 130
bpy.ops.view3d (module), 132
bpy.ops.wm (module), 136
bpy.ops.world (module), 146

bpy.path (module), 1046
bpy.props (module), 1048
bpy.types (module), 146, 148, 149, 151–159, 161–166, 168–171, 174, 177–182, 184, 185, 187, 188, 191–202, 204–224, 227, 228, 232–236, 241, 242, 244, 246, 247, 249, 251–255, 258, 260–262, 264–267, 269–328, 330, 333, 335, 336, 338, 339, 341–343, 346–348, 350–356, 358, 360, 363–368, 372, 374, 376, 378–380, 382, 384, 386–388, 390–394, 396–398, 400–405, 409, 411, 412, 414–418, 420–428, 432–436, 438–448, 450–452, 455, 457, 460, 463–465, 467, 468, 470–473, 475, 478, 481, 483, 485, 487–490, 492, 493, 496, 498, 500–502, 504–508, 510, 511, 513–515, 517–520, 528, 530, 531, 533–536, 538, 543, 544, 546, 549, 553–556, 558–566, 568, 569, 571–573, 575–577, 580, 582–586, 589, 591, 593, 595, 596, 599–607, 609–611, 621, 624–628, 635–642, 646–650, 652–654, 656, 657, 670, 673, 674, 678–682, 684, 685, 687, 690, 691, 693–695, 700, 701, 703, 704, 706–712, 714–717, 719, 722, 726–729, 738, 741, 743, 747–749, 753, 754, 757, 760, 761, 763, 764, 766, 767, 770, 771, 773–795, 797–804, 806, 809–813, 817–819, 821, 823–827, 829, 831–835, 837–839, 841, 842, 844, 845, 848, 850, 853, 855–857, 860–862, 864, 865, 867–869, 871–873, 875–877, 880, 882, 884–903, 905, 907–909, 911, 913, 915, 916, 919, 921–923, 925, 927, 928, 930, 932–934, 936, 938, 939, 943–948, 952–954, 957, 959, 982–988, 991, 994, 996, 999, 1002–1012, 1014, 1015, 1017, 1018, 1021, 1022, 1024, 1026, 1028, 1030, 1032, 1034–1040
bpy.utils (module), 1044
bpy_extras (module), 1129
bpy_extras.image_utils (module), 1130
bpy_extras.io_utils (module), 1129
bpy_extras.mesh_utils (module), 1131
bpy_extras.object_utils (module), 1129
bpy_extras.view3d_utils (module), 1132
bpy_prop_collection (class in bpy.types), 1039
bpy_struct (class in bpy.types), 1041
branch_threshold (bpy.types.ParticleSettings attribute), 659
breakdown() (in module bpy.ops.pose), 92
brownian_factor (bpy.types.ParticleSettings attribute), 659
browse_interactive() (in module bpy.ops.poselib), 96
brush (bpy.types.Paint attribute), 641
Brush (class in bpy.types), 236
brush (in module bpy.context), 8
Brush.curve (in module bpy.types), 237
Brush.texture_slot (in module bpy.types), 238

brush_edit() (in module bpy.ops.particle), 90
brush_stroke() (in module bpy.ops.sculpt), 101
BrushTextureSlot (class in bpy.types), 241
buffer_paste() (in module bpy.ops.font), 34
build_cflags (in module bpy.app), 1047
build_cxxflags (in module bpy.app), 1047
build_date (in module bpy.app), 1047
build_linkflags (in module bpy.app), 1047
build_platform (in module bpy.app), 1047
build_revision (in module bpy.app), 1047
build_system (in module bpy.app), 1047
build_time (in module bpy.app), 1047
build_type (in module bpy.app), 1048
BuildModifier (class in bpy.types), 242
bulge (bpy.types.StretchToConstraint attribute), 861
bump_method (bpy.types.MaterialTextureSlot attribute), 538
bump_objectspace (bpy.types.MaterialTextureSlot attribute), 538
buoyancy (bpy.types.SPHFluidSettings attribute), 741
button (bge.types.SCA_JoystickSensor attribute), 1185
button (bpy.types.ThemeAudioWindow attribute), 907
button (bpy.types.ThemeConsole attribute), 909
button (bpy.types.ThemeDopeSheet attribute), 911
button (bpy.types.ThemeFileBrowser attribute), 913
button (bpy.types.ThemeGraphEditor attribute), 916
button (bpy.types.ThemeImageEditor attribute), 919
button (bpy.types.ThemeInfo attribute), 921
button (bpy.types.ThemeLogicEditor attribute), 922
button (bpy.types.ThemeNLAEditor attribute), 923
button (bpy.types.ThemeNodeEditor attribute), 925
button (bpy.types.ThemeOutliner attribute), 927
button (bpy.types.ThemeProperties attribute), 929
button (bpy.types.ThemeSequenceEditor attribute), 930
button (bpy.types.ThemeTextEditor attribute), 933
button (bpy.types.ThemeTimeline attribute), 935
button (bpy.types.ThemeUserPreferences attribute), 938
button (bpy.types.ThemeView3D attribute), 939
button_number (bpy.types.JoystickSensor attribute), 469
button_text (bpy.types.ThemeAudioWindow attribute), 907
button_text (bpy.types.ThemeConsole attribute), 909
button_text (bpy.types.ThemeDopeSheet attribute), 911
button_text (bpy.types.ThemeFileBrowser attribute), 913
button_text (bpy.types.ThemeGraphEditor attribute), 916
button_text (bpy.types.ThemeImageEditor attribute), 919
button_text (bpy.types.ThemeInfo attribute), 921
button_text (bpy.types.ThemeLogicEditor attribute), 922
button_text (bpy.types.ThemeNLAEditor attribute), 923
button_text (bpy.types.ThemeNodeEditor attribute), 925
button_text (bpy.types.ThemeOutliner attribute), 927
button_text (bpy.types.ThemeProperties attribute), 929
button_text (bpy.types.ThemeSequenceEditor attribute), 930
button_text (bpy.types.ThemeTextEditor attribute), 933
button_text (bpy.types.ThemeTimeline attribute), 935
button_text (bpy.types.ThemeUserPreferences attribute), 938
button_text (bpy.types.ThemeView3D attribute), 939
bvh() (in module bpy.ops.export_anim), 28
button_text (bpy.types.ThemeTextEditor attribute), 933
button_text (bpy.types.ThemeTimeline attribute), 935
button_text (bpy.types.ThemeUserPreferences attribute), 938
button_text (bpy.types.ThemeView3D attribute), 939
button_text_hi (bpy.types.ThemeAudioWindow attribute), 907
button_text_hi (bpy.types.ThemeConsole attribute), 909
button_text_hi (bpy.types.ThemeDopeSheet attribute), 911
button_text_hi (bpy.types.ThemeFileBrowser attribute), 913
button_text_hi (bpy.types.ThemeGraphEditor attribute), 916
button_text_hi (bpy.types.ThemeImageEditor attribute), 919
button_text_hi (bpy.types.ThemeInfo attribute), 921
button_text_hi (bpy.types.ThemeLogicEditor attribute), 922
button_text_hi (bpy.types.ThemeNLAEditor attribute), 924
button_text_hi (bpy.types.ThemeNodeEditor attribute), 925
button_text_hi (bpy.types.ThemeOutliner attribute), 927
button_text_hi (bpy.types.ThemeProperties attribute), 929
button_text_hi (bpy.types.ThemeSequenceEditor attribute), 930
button_text_hi (bpy.types.ThemeTextEditor attribute), 933
button_text_hi (bpy.types.ThemeTimeline attribute), 935
button_text_hi (bpy.types.ThemeUserPreferences attribute), 938
button_text_hi (bpy.types.ThemeView3D attribute), 939
button_title (bpy.types.ThemeAudioWindow attribute), 907
button_title (bpy.types.ThemeConsole attribute), 909
button_title (bpy.types.ThemeDopeSheet attribute), 911
button_title (bpy.types.ThemeFileBrowser attribute), 913
button_title (bpy.types.ThemeGraphEditor attribute), 916
button_title (bpy.types.ThemeImageEditor attribute), 919
button_title (bpy.types.ThemeInfo attribute), 921
button_title (bpy.types.ThemeLogicEditor attribute), 922
button_title (bpy.types.ThemeNLAEditor attribute), 924
button_title (bpy.types.ThemeNodeEditor attribute), 925
button_title (bpy.types.ThemeOutliner attribute), 927
button_title (bpy.types.ThemeProperties attribute), 929
button_title (bpy.types.ThemeSequenceEditor attribute), 930
button_title (bpy.types.ThemeTextEditor attribute), 933
button_title (bpy.types.ThemeTimeline attribute), 935
button_title (bpy.types.ThemeUserPreferences attribute), 938
button_title (bpy.types.ThemeView3D attribute), 939

bvh() (in module bpy.ops.import_anim), 46

C

cache_cloth (bpy.types.SpaceTimeline attribute), 841
cache_particles (bpy.types.SpaceTimeline attribute), 841
cache_resolution (bpy.types.MaterialVolume attribute), 544
cache_smoke (bpy.types.SpaceTimeline attribute), 841
cache_softbody (bpy.types.SpaceTimeline attribute), 841
calc_normals() (bpy.types.Mesh method), 552
calculate_roll() (in module bpy.ops.armature), 17
call_menu() (in module bpy.ops.wm), 136
CAM_POS (in module bge.logic), 1218
camera (bge.types.KX_SceneActuator attribute), 1176
camera (bpy.types.Scene attribute), 743
camera (bpy.types.SceneActuator attribute), 747
camera (bpy.types.SpaceView3D attribute), 845
camera (bpy.types.TimelineMarker attribute), 945
Camera (class in bpy.types), 244
camera (in module bpy.context), 8
Camera.animation_data (in module bpy.types), 244
camera_add() (in module bpy.ops.object), 72
camera_bind() (in module bpy.ops.marker), 51
camera_to_view() (in module bpy.ops.view3d), 132
camera_to_world (bge.types.KX_Camera attribute), 1191
CameraActuator (class in bpy.types), 246
cameras (bge.types.KX_Scene attribute), 1174
cancel() (bpy.types.Operator method), 634
cancel() (in module bpy.ops.file), 32
cancel_stroke() (in module bpy.ops.sketch), 108
CAPSLOCKKEY (in module bge.events), 1224
case_set() (in module bpy.ops.font), 34
case_toggle() (in module bpy.ops.font), 34
cast_type (bpy.types.CastModifier attribute), 247
CastModifier (class in bpy.types), 247
center_x (bpy.types.CompositorNodeDBlur attribute), 286
center_y (bpy.types.CompositorNodeDBlur attribute), 286
chain_count (bpy.types.KinematicConstraint attribute), 493
chain_count (bpy.types.SplineIKConstraint attribute), 853
chance (bpy.types.RandomActuator attribute), 712
change_character() (in module bpy.ops.font), 34
change_frame() (in module bpy.ops.anim), 13
change_spacing() (in module bpy.ops.font), 35
channel (bpy.types.CompositorNodeColorSpill attribute), 278
channel (bpy.types.CompositorNodeLevels attribute), 301
channel (bpy.types.Sequence attribute), 768
channel_group (bpy.types.ThemeDopeSheet attribute), 911

channel_group (bpy.types.ThemeGraphEditor attribute), 916
channel_matrix (bge.types.BL_ArmatureChannel attribute), 1201
ChannelDriverVariables (class in bpy.types), 249
channelNames (bge.types.BL_ActionActuator attribute), 1136
channels (aud.Device attribute), 1122
channels (bge.types.BL_ArmatureObject attribute), 1194
channels (bpy.types.ThemeDopeSheet attribute), 911
channels_click() (in module bpy.ops.anim), 13
channels_click() (in module bpy.ops.nla), 65
channelsCollapse() (in module bpy.ops.anim), 13
channels_delete() (in module bpy.ops.anim), 13
channels_editable_toggle() (in module bpy.ops.anim), 13
channels_expand() (in module bpy.ops.anim), 13
channels_fcurves_enable() (in module bpy.ops.anim), 13
channels_move() (in module bpy.ops.anim), 13
channels_region (bpy.types.ThemeGraphEditor attribute), 916
channels_select_all_toggle() (in module bpy.ops.anim), 14
channels_select_border() (in module bpy.ops.anim), 14
channels_selected (bpy.types.ThemeDopeSheet attribute), 911
channels_setting_disable() (in module bpy.ops.anim), 14
channels_setting_enable() (in module bpy.ops.anim), 14
channels_setting_toggle() (in module bpy.ops.anim), 14
channels_visibility_set() (in module bpy.ops.anim), 14
channels_visibility_toggle() (in module bpy.ops.anim), 14
charge (bpy.types.EffectorWeights attribute), 376
check() (bpy.types.Operator method), 634
checker_distance (bpy.types.ImageTexture attribute), 460
child (bpy.types.RigidBodyJointConstraint attribute), 738
child_length (bpy.types.ParticleSettings attribute), 659
child_length_threshold (bpy.types.ParticleSettings attribute), 659
child_nbr (bpy.types.ParticleSettings attribute), 659
child_parting_factor (bpy.types.ParticleSettings attribute), 659
child_parting_max (bpy.types.ParticleSettings attribute), 659
child_parting_min (bpy.types.ParticleSettings attribute), 659
child_radius (bpy.types.ParticleSettings attribute), 659
child_roundness (bpy.types.ParticleSettings attribute), 659
child_seed (bpy.types.ParticleSystem attribute), 674
child_size (bpy.types.ParticleSettings attribute), 660
child_size_random (bpy.types.ParticleSettings attribute), 660
child_type (bpy.types.ParticleSettings attribute), 660

childof_clear_inverse() (in module bpy.ops.constraint), 23
childof_set_inverse() (in module bpy.ops.constraint), 23
ChildOfConstraint (class in bpy.types), 249
ChildParticle (class in bpy.types), 251
children (bge.types.BL_ArmatureBone attribute), 1205
children (bge.types.KX_GameObject attribute), 1147
childrenRecursive (bge.types.KX_GameObject attribute), 1147
choke (bpy.types.SoftBodySettings attribute), 813
cineon_black (bpy.types.RenderSettings attribute), 730
cineon_gamma (bpy.types.RenderSettings attribute), 730
cineon_white (bpy.types.RenderSettings attribute), 730
circle_select() (in module bpy.ops.uv), 125
CKEY (in module bge.events), 1223
clamp (bpy.types.GlowSequence attribute), 436
ClampToConstraint (class in bpy.types), 252
clean() (in module bpy.ops.action), 10
clean() (in module bpy.ops.graph), 37
clean_name() (in module bpy.path), 1046
clear() (bpy.types.KeyingSetPaths method), 491
clear() (bpy.types.LampTextureSlots class method), 501
clear() (bpy.types.MaterialTextureSlots class method), 543
clear() (bpy.types.ParticleSettingsTextureSlots class method), 673
clear() (bpy.types.Text method), 874
clear() (bpy.types.WorldTextureSlots class method), 1037
clear() (in module bpy.ops.console), 22
clear_scale() (in module bpy.ops.nla), 65
click_extrude() (in module bpy.ops.armature), 17
click_insert() (in module bpy.ops.graph), 38
click_select() (in module bpy.ops.nla), 65
clickselect() (in module bpy.ops.action), 10
clickselect() (in module bpy.ops.graph), 38
clip_border() (in module bpy.ops.view3d), 132
clip_end (bpy.types.Camera attribute), 244
clip_end (bpy.types.EnvironmentMap attribute), 380
clip_end (bpy.types.SpaceView3D attribute), 845
clip_max_x (bpy.types.CurveMapping attribute), 348
clip_max_y (bpy.types.CurveMapping attribute), 348
clip_min_x (bpy.types.CurveMapping attribute), 348
clip_min_y (bpy.types.CurveMapping attribute), 348
clip_start (bpy.types.Camera attribute), 244
clip_start (bpy.types.EnvironmentMap attribute), 380
clip_start (bpy.types.SpaceView3D attribute), 845
clipboard (bpy.types.WindowManager attribute), 1022
CLIPPING (in module blf), 1118
clipping() (in module blf), 1118
CListValue (class in bge.types), 1141
clone_alpha (bpy.types.Brush attribute), 236
clone_cursor_set() (in module bpy.ops.paint), 88
clone_image (bpy.types.Brush attribute), 236
clone_offset (bpy.types.Brush attribute), 236
cloth (in module bpy.context), 8
ClothCollisionSettings (class in bpy.types), 253
ClothModifier (class in bpy.types), 254
ClothModifier.collision_settings (in module bpy.types), 254
ClothModifier.point_cache (in module bpy.types), 254
ClothModifier.settings (in module bpy.types), 255
ClothSettings (class in bpy.types), 255
ClothSettings.effector_weights (in module bpy.types), 256
cloud_type (bpy.types.CloudsTexture attribute), 258
CloudsTexture (class in bpy.types), 258
CloudsTexture.users_material (in module bpy.types), 258
CloudsTexture.users_object_modifier (in module bpy.types), 258
clump_factor (bpy.types.ParticleSettings attribute), 660
clump_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
clump_shape (bpy.types.ParticleSettings attribute), 660
cluster_iterations (bpy.types.GameSoftBodySettings attribute), 433
co (bpy.types.BezierSplinePoint attribute), 187
co (bpy.types.FCurveSample attribute), 394
co (bpy.types.GPencilStrokePoint attribute), 424
co (bpy.types.Keyframe attribute), 485
co (bpy.types.MeshSticky attribute), 564
co (bpy.types.MeshVertex attribute), 570
co (bpy.types.MetaElement attribute), 576
co (bpy.types.MotionPathVert attribute), 584
co (bpy.types.ParticleHairKey attribute), 653
co (bpy.types.ShapeKeyBezierPoint attribute), 800
co (bpy.types.ShapeKeyCurvePoint attribute), 800
co (bpy.types.ShapeKeyPoint attribute), 801
co (bpy.types.SplinePoint attribute), 855
co_deform (bpy.types.LatticePoint attribute), 505
co_hair_space (bpy.types.ParticleHairKey attribute), 653
coefficients (bpy.types.FModifierGenerator attribute), 400
col_size (mathutils.Matrix attribute), 1061
CollectionProperty (class in bpy.types), 260
CollectionProperty() (in module bpy.props), 1051
CollectionProperty.fixed_type (in module bpy.types), 260
collide (bge.types.KX_PolyProxy attribute), 1164
collider_friction (bpy.types.ClothSettings attribute), 256
collision (in module bpy.context), 8
collision_bounds_type (bpy.types.GameObjectSettings attribute), 428
collision_extents (bpy.types.SmokeDomainSettings attribute), 807
collision_group (bpy.types.SmokeDomainSettings attribute), 807
collision_margin (bpy.types.GameObjectSettings attribute), 428
collision_margin (bpy.types.GameSoftBodySettings attribute), 433

collision_quality (bpy.types.ClothCollisionSettings attribute), 253
collision_type (bpy.types.SoftBodySettings attribute), 813
CollisionModifier (class in bpy.types), 261
CollisionModifier.settings (in module bpy.types), 261
CollisionSensor (class in bpy.types), 261
CollisionSettings (class in bpy.types), 262
color (bge.types.KX_GameObject attribute), 1145
color (bge.types.KX_LightObject attribute), 1156
color (bge.types.KX_VertexProxy attribute), 1180
color (bpy.types.Brush attribute), 236
color (bpy.types.ColorRampElement attribute), 265
color (bpy.types.ColorSequence attribute), 267
color (bpy.types.FCurve attribute), 388
color (bpy.types.GPencilLayer attribute), 422
color (bpy.types.Lamp attribute), 496
color (bpy.types.MaterialSubsurfaceScattering attribute), 536
color (bpy.types.Object attribute), 611
color (bpy.types.TextMarker attribute), 881
color (bpy.types.TextureSlot attribute), 903
Color (class in mathutils), 1055
Color.copy() (in module mathutils), 1055
color1 (bpy.types.MeshColor attribute), 553
color2 (bpy.types.MeshColor attribute), 553
color3 (bpy.types.MeshColor attribute), 553
color4 (bpy.types.MeshColor attribute), 553
color_factor (bpy.types.LampTextureSlot attribute), 500
color_factor (bpy.types.MaterialSubsurfaceScattering attribute), 537
color_hue (bpy.types.CompositorNodeColorMatte attribute), 277
color_hue (bpy.types.CompositorNodeHueSat attribute), 296
color_layer (bpy.types.ShaderNodeGeometry attribute), 780
color_maximum (bpy.types.ParticleSettings attribute), 660
color_mode (bpy.types.FCurve attribute), 388
color_mode (bpy.types.RenderSettings attribute), 730
color_mode (bpy.types.VoronoiTexture attribute), 1012
color_modulation (bpy.types.CompositorNodeGlare attribute), 294
color_multiply (bpy.types.AdjustmentSequence attribute), 159
color_multiply (bpy.types.EffectSequence attribute), 374
color_multiply (bpy.types.ImageSequence attribute), 457
color_multiply (bpy.types.MetaSequence attribute), 578
color_multiply (bpy.types.MovieSequence attribute), 586
color_multiply (bpy.types.MulticamSequence attribute), 589
color_multiply (bpy.types.SceneSequence attribute), 758
color_picker_type (bpy.types.UserPreferencesSystem attribute), 996
color_random (bpy.types.WorldStarsSettings attribute), 1034
color_range (bpy.types.World attribute), 1028
color_saturation (bpy.types.AdjustmentSequence attribute), 159
color_saturation (bpy.types.CompositorNodeColorMatte attribute), 277
color_saturation (bpy.types.CompositorNodeHueSat attribute), 296
color_saturation (bpy.types.EffectSequence attribute), 374
color_saturation (bpy.types.ImageSequence attribute), 457
color_saturation (bpy.types.MetaSequence attribute), 578
color_saturation (bpy.types.MovieSequence attribute), 586
color_saturation (bpy.types.MulticamSequence attribute), 589
color_saturation (bpy.types.SceneSequence attribute), 758
color_set (bpy.types.BoneGroup attribute), 232
color_source (bpy.types.PointDensity attribute), 688
color_space (bpy.types.CompositorNodeChannelMatte attribute), 274
color_value (bpy.types.CompositorNodeColorMatte attribute), 277
color_value (bpy.types.CompositorNodeHueSat attribute), 296
ColorRamp (class in bpy.types), 264
ColorRamp.elements (in module bpy.types), 264
ColorRampElement (class in bpy.types), 265
ColorRampElements (class in bpy.types), 266
colors_mirror() (in module bpy.ops.mesh), 53
colors_rotate() (in module bpy.ops.mesh), 53
ColorSequence (class in bpy.types), 267
colour (bge.types.KX_LightObject attribute), 1156
colour (bge.types.KX_VertexProxy attribute), 1180
column() (bpy.typesUILayout method), 960
column_flow() (bpy.typesUILayout method), 960
COMMAKEY (in module bge.events), 1226
comment() (in module bpy.ops.text), 111
compare() (bpy.types.KeyMapItem method), 477
CompositorNode (class in bpy.types), 269
CompositorNode.type (in module bpy.types), 269
CompositorNodeAlphaOver (class in bpy.types), 270
CompositorNodeBilateralblur (class in bpy.types), 271
CompositorNodeBlur (class in bpy.types), 272
CompositorNodeBrightContrast (class in bpy.types), 273
CompositorNodeChannelMatte (class in bpy.types), 274
CompositorNodeChromaMatte (class in bpy.types), 275
CompositorNodeColorBalance (class in bpy.types), 276
CompositorNodeColorMatte (class in bpy.types), 277

CompositorNodeColorSpill (class in bpy.types), 278
 CompositorNodeCombHSVA (class in bpy.types), 279
 CompositorNodeCombRGBA (class in bpy.types), 280
 CompositorNodeCombYCCA (class in bpy.types), 281
 CompositorNodeCombYUVA (class in bpy.types), 281
 CompositorNodeComposite (class in bpy.types), 282
 CompositorNodeCrop (class in bpy.types), 283
 CompositorNodeCurveRGB (class in bpy.types), 284
 CompositorNodeCurveRGB.mapping (in module bpy.types), 284
 CompositorNodeCurveVec (class in bpy.types), 285
 CompositorNodeCurveVec.mapping (in module bpy.types), 285
 CompositorNodeDBlur (class in bpy.types), 286
 CompositorNodeDefocus (class in bpy.types), 287
 CompositorNodeDiffMatte (class in bpy.types), 288
 CompositorNodeDilateErode (class in bpy.types), 289
 CompositorNodeDisplace (class in bpy.types), 290
 CompositorNodeDistanceMatte (class in bpy.types), 291
 CompositorNodeFilter (class in bpy.types), 291
 CompositorNodeFlip (class in bpy.types), 292
 CompositorNodeGamma (class in bpy.types), 293
 CompositorNodeGlare (class in bpy.types), 294
 CompositorNodeHueCorrect (class in bpy.types), 295
 CompositorNodeHueCorrect.mapping (in module bpy.types), 295
 CompositorNodeHueSat (class in bpy.types), 296
 CompositorNodeIDMask (class in bpy.types), 297
 CompositorNodeImage (class in bpy.types), 298
 CompositorNodeInvert (class in bpy.types), 299
 CompositorNodeLensdist (class in bpy.types), 300
 CompositorNodeLevels (class in bpy.types), 301
 CompositorNodeLumaMatte (class in bpy.types), 301
 CompositorNodeMapUV (class in bpy.types), 302
 CompositorNodeMapView (class in bpy.types), 303
 CompositorNodeMath (class in bpy.types), 304
 CompositorNodeMixRGB (class in bpy.types), 305
 CompositorNodeNormal (class in bpy.types), 306
 CompositorNodeNormalize (class in bpy.types), 306
 CompositorNodeOutputFile (class in bpy.types), 307
 CompositorNodePremulKey (class in bpy.types), 308
 CompositorNodeRGB (class in bpy.types), 309
 CompositorNodeRGBToBW (class in bpy.types), 310
 CompositorNodeRLayers (class in bpy.types), 310
 CompositorNodeRotate (class in bpy.types), 311
 CompositorNodes (class in bpy.types), 326
 CompositorNodeScale (class in bpy.types), 312
 CompositorNodeSepHSVA (class in bpy.types), 313
 CompositorNodeSepRGBA (class in bpy.types), 313
 CompositorNodeSepYCCA (class in bpy.types), 314
 CompositorNodeSepYUVA (class in bpy.types), 315
 CompositorNodeSetAlpha (class in bpy.types), 316
 CompositorNodeSplitViewer (class in bpy.types), 316
 CompositorNodeTexture (class in bpy.types), 317
 CompositorNodeTime (class in bpy.types), 318
 CompositorNodeTime.curve (in module bpy.types), 318
 CompositorNodeTonemap (class in bpy.types), 319
 CompositorNodeTranslate (class in bpy.types), 320
 CompositorNodeTree (class in bpy.types), 321
 CompositorNodeTree.nodes (in module bpy.types), 321
 CompositorNodeValToRGB (class in bpy.types), 322
 CompositorNodeValToRGB.color_ramp (in module bpy.types), 322
 CompositorNodeValue (class in bpy.types), 323
 CompositorNodeVecBlur (class in bpy.types), 323
 CompositorNodeViewer (class in bpy.types), 324
 CompositorNodeZcombine (class in bpy.types), 325
 compound (bge.types.KX_ParentActuator attribute), 1162
 compressibility (bpy.types.DomainFluidSettings attribute), 358
 compression (bpy.types.PointCache attribute), 685
 compression_threshold (bpy.types.SpotLamp attribute), 857
 cone_angle_inner (aud.Handle attribute), 1127
 cone_angle_outer (aud.Handle attribute), 1127
 cone_inner_angle_3d (bpy.types.SoundActuator attribute), 820
 cone_outer_angle_3d (bpy.types.SoundActuator attribute), 820
 cone_outer_gain_3d (bpy.types.SoundActuator attribute), 820
 cone_volume_outer (aud.Handle attribute), 1127
 coneOrigin (bge.types.KX_RadarSensor attribute), 1170
 coneTarget (bge.types.KX_RadarSensor attribute), 1170
 connect_hair() (in module bpy.ops.particle), 90
 connected (bge.types.BL_ArmatureBone attribute), 1204
 connected (bge.types.SCA_JoystickSensor attribute), 1185
 ConsoleLine (class in bpy.types), 327
 constant_offset_displace (bpy.types.ArrayModifier attribute), 182
 CONSTANT_TIMER (in module bge.logic), 1218
 constraint (bge.types.BL_ArmatureActuator attribute), 1195
 constraint (bge.types.KX_ArmatureSensor attribute), 1196
 constraint (bpy.types.ArmatureActuator attribute), 177
 constraint (bpy.types.ArmatureSensor attribute), 181
 Constraint (class in bpy.types), 328
 Constraint.error_location (in module bpy.types), 328
 Constraint.error_rotation (in module bpy.types), 328
 Constraint.is_valid (in module bpy.types), 328
 Constraint.type (in module bpy.types), 329
 constraint_add() (in module bpy.ops.object), 72
 constraint_add() (in module bpy.ops.pose), 93
 constraint_add_with_targets() (in module bpy.ops.object), 72

constraint_add_with_targets() (in module bpy.ops.pose), 93
ConstraintActuator (class in bpy.types), 330
constraints (bge.types.BL_ArmatureObject attribute), 1194
constraints_clear() (in module bpy.ops.object), 73
constraints_clear() (in module bpy.ops.pose), 93
constraints_copy() (in module bpy.ops.object), 73
constraints_copy() (in module bpy.ops.pose), 93
ConstraintTarget (class in bpy.types), 333
context (bpy.types.SpaceProperties attribute), 837
Context (class in bpy.types), 333
Context.area (in module bpy.types), 333
Context.blend_data (in module bpy.types), 333
Context.mode (in module bpy.types), 334
Context.region (in module bpy.types), 334
Context.region_data (in module bpy.types), 334
Context.scene (in module bpy.types), 334
Context.screen (in module bpy.types), 334
Context.space_data (in module bpy.types), 334
Context.tool_settings (in module bpy.types), 334
Context.user_preferences (in module bpy.types), 334
Context.window (in module bpy.types), 334
Context.window_manager (in module bpy.types), 334
context_collection_boolean_set() (in module bpy.ops.wm), 137
context_cycle_array() (in module bpy.ops.wm), 137
context_cycle_enum() (in module bpy.ops.wm), 137
context_cycle_int() (in module bpy.ops.wm), 137
context_menu_enum() (in module bpy.ops.wm), 137
context_modal_mouse() (in module bpy.ops.wm), 137
context_pointer_set() (bpy.typesUILayout method), 978
context_scale_int() (in module bpy.ops.wm), 138
context_set_boolean() (in module bpy.ops.wm), 138
context_set_enum() (in module bpy.ops.wm), 138
context_set_float() (in module bpy.ops.wm), 138
context_set_id() (in module bpy.ops.wm), 138
context_set_int() (in module bpy.ops.wm), 139
context_set_string() (in module bpy.ops.wm), 139
context_set_value() (in module bpy.ops.wm), 139
context_toggle() (in module bpy.ops.wm), 139
context_toggle_enum() (in module bpy.ops.wm), 139
contrast (bpy.types.CompositorNodeTonemap attribute), 319
contrast (bpy.types.Texture attribute), 882
ControlFluidSettings (class in bpy.types), 335
Controller (class in bpy.types), 336
controller_add() (in module bpy.ops.logic), 49
controller_move() (in module bpy.ops.logic), 50
controller_remove() (in module bpy.ops.logic), 50
controllers (bge.types.KX_GameObject attribute), 1147
convert() (in module bpy.ops.gpencil), 37
convert() (in module bpy.ops.object), 73
convert() (in module bpy.ops.sketch), 108
convert_whitespace() (in module bpy.ops.text), 111
converter_node (bpy.types.ThemeNodeEditor attribute), 925
copy() (bpy.types.Context static method), 334
copy() (bpy.types.ID method), 449
copy() (in module bpy.ops.action), 11
copy() (in module bpy.ops.console), 22
copy() (in module bpy.ops.graph), 38
copy() (in module bpy.ops.material), 52
copy() (in module bpy.ops.pose), 93
copy() (in module bpy.ops.sequencer), 101
copy() (in module bpy.ops.text), 111
copy() (mathutils.Matrix method), 1058
copy_data_path_button() (in module bpy.ops.ui), 125
copy_driver_button() (in module bpy.ops.anim), 14
copy_prev_settings() (in module bpy.ops.wm), 139
copy_to_selected_button() (in module bpy.ops.ui), 125
copy_to_user() (bpy.types.KeyMap method), 474
CopyLocationConstraint (class in bpy.types), 338
CopyRotationConstraint (class in bpy.types), 339
CopyScaleConstraint (class in bpy.types), 341
CopyTransformsConstraint (class in bpy.types), 342
correction (bpy.types.CompositorNodeTonemap attribute), 319
correction (bpy.types.WorldLighting attribute), 1030
correction_method (bpy.types.CompositorNodeColorBalance attribute), 276
count (bpy.types.ArrayModifier attribute), 182
count (bpy.types.ParticleBrush attribute), 648
count (bpy.types.ParticleDupliWeight attribute), 649
count (bpy.types.ParticleSettings attribute), 660
count() (bge.types.CListValue method), 1141
CPropValue (class in bge.types), 1133
crease (bpy.types.MeshEdge attribute), 556
crease_pinch_factor (bpy.types.Brush attribute), 236
create() (bpy.types.LampTextureSlots class method), 501
create() (bpy.types.MaterialTextureSlots class method), 543
create() (bpy.types.ParticleSettingsTextureSlots class method), 673
create() (bpy.types.WorldTextureSlots class method), 1036
create() (in module bpy.ops.group), 41
create_derived_objects() (in module bpy_extras.io_utils), 1129
create_long_hair_children (bpy.types.ParticleSettings attribute), 660
create_orientation() (in module bpy.ops.transform), 116
crop_max_x (bpy.types.ImageTexture attribute), 460
crop_max_y (bpy.types.ImageTexture attribute), 460
crop_min_x (bpy.types.ImageTexture attribute), 460
crop_min_y (bpy.types.ImageTexture attribute), 460
cross() (mathutils.Quaternion method), 1062
cross() (mathutils.Vector method), 1065

crossfade_sounds() (in module bpy.ops.sequencer), 101
 ctrl (bpy.types.KeyMapItem attribute), 475
 cube_project() (in module bpy.ops.uv), 125
 cull_face (bpy.types.ShrinkwrapModifier attribute), 803
 current_character (bpy.types.ConsoleLine attribute), 327
 cursor (bpy.types.ThemeConsole attribute), 909
 cursor (bpy.types.ThemeTextEditor attribute), 933
 cursor3d() (in module bpy.ops.view3d), 132
 cursor_color_add (bpy.types.Brush attribute), 236
 cursor_color_subtract (bpy.types.Brush attribute), 236
 cursor_location (bpy.types.Scene attribute), 743
 cursor_location (bpy.types.SpaceUVEditor attribute), 842
 cursor_location (bpy.types.SpaceView3D attribute), 845
 cursor_position_y (bpy.types.SpaceGraphEditor attribute), 827
 cursor_set() (in module bpy.ops.graph), 38
 cursor_set() (in module bpy.ops.text), 112
 cursor_set() (in module bpy.ops.uv), 125
 curve (bpy.types.ArrayModifier attribute), 182
 Curve (class in bpy.types), 343
 curve (in module bpy.context), 7
 Curve.animation_data (in module bpy.types), 343
 Curve.materials (in module bpy.types), 344
 Curve.shape_keys (in module bpy.types), 344
 Curve.splines (in module bpy.types), 344
 curve_guide (bpy.types.EffectorWeights attribute), 377
 curve_preset() (in module bpy.ops.brush), 19
 CurveMap (class in bpy.types), 346
 CurveMap.extend (in module bpy.types), 347
 CurveMap.points (in module bpy.types), 347
 CurveMapping (class in bpy.types), 348
 CurveMapping.curves (in module bpy.types), 349
 CurveMapPoint (class in bpy.types), 347
 CurveMapPoint.handle_type (in module bpy.types), 347
 CurveMapPoint.location (in module bpy.types), 347
 CurveModifier (class in bpy.types), 350
 curves_point_set() (in module bpy.ops.image), 42
 CurveSplines (class in bpy.types), 351
 custom_color (bpy.types.ActionGroup attribute), 152
 custom_shape (bpy.types.PoseBone attribute), 696
 custom_shape_transform (bpy.types.PoseBone attribute), 696
 cut() (in module bpy.ops.sequencer), 101
 cut() (in module bpy.ops.text), 112
 cut_multicam() (in module bpy.ops.sequencer), 102
 CValue (class in bge.types), 1133
 cycle_render_slot() (in module bpy.ops.image), 42
 cycles_after (bpy.types.FModifierCycles attribute), 396
 cycles_before (bpy.types.FModifierCycles attribute), 396
 cyclic_toggle() (in module bpy.ops.curve), 24
 cylinder_project() (in module bpy.ops.uv), 126

D

damp (bge.types.KX_ConstraintActuator attribute), 1143
 damp_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
 DampedTrackConstraint (class in bpy.types), 352
 damping (bge.types.KX_CameraActuator attribute), 1142
 damping (bge.types.KX_ObjectActuator attribute), 1162
 damping (bpy.types.CameraActuator attribute), 246
 damping (bpy.types.CollisionSettings attribute), 263
 damping (bpy.types.ConstraintActuator attribute), 330
 damping (bpy.types.GameObjectSettings attribute), 429
 damping (bpy.types.ObjectActuator attribute), 621
 damping (bpy.types.ParticleSettings attribute), 660
 damping (bpy.types.SoftBodySettings attribute), 813
 damping_epsilon (bpy.types.Itasc attribute), 467
 damping_factor (bpy.types.CollisionSettings attribute), 263
 damping_max (bpy.types.Itasc attribute), 467
 damping_random (bpy.types.CollisionSettings attribute), 263
 damping_rotation (bpy.types.ConstraintActuator attribute), 330
 damping_time (bpy.types.WaveModifier attribute), 1019
 darkness (bpy.types.Material attribute), 521
 data (bpy.types.Object attribute), 611
 data (in module bpy), 9
 data_add() (in module bpy.ops.gpencil), 37
 data_operation() (in module bpy.ops.outliner), 87
 data_path (bpy.types.DriverTarget attribute), 364
 data_path (bpy.types.FCurve attribute), 388
 data_path (bpy.types.KeyingSetPath attribute), 489
 data_unlink() (in module bpy.ops.gpencil), 37
 dbvt_culling (bge.types.KX_Scene attribute), 1175
 de_select_first() (in module bpy.ops.curve), 24
 de_select_last() (in module bpy.ops.curve), 24
 deactivate() (bge.types.SCA_PythonController method), 1188
 debug (in module bpy.app), 1047
 debug_menu() (in module bpy.ops.wm), 139
 debug_value (in module bpy.app), 1047
 DecimateModifier (class in bpy.types), 353
 DecimateModifier.face_count (in module bpy.types), 353
 decompose() (mathutils.Matrix method), 1059
 default_key_count (bpy.types.ParticleEdit attribute), 650
 default_max (bpy.types.FModifierEnvelope attribute), 397
 default_min (bpy.types.FModifierEnvelope attribute), 397
 default_value (bpy.types.RGBANodeSocket attribute), 710
 default_value (bpy.types.TextureSlot attribute), 904
 default_value (bpy.types.ValueNodeSocket attribute), 1004
 default_value (bpy.types.VectorNodeSocket attribute), 1005
 define() (bpy.types.Macro method), 515
 deform_axis (bpy.types.CurveModifier attribute), 350

deform_method (bpy.types.SimpleDeformModifier attribute), 804
deinterlace_selected_movies() (in module bpy.ops.sequencer), 102
delay (bge.types.SCA_DelaySensor attribute), 1184
delay (bpy.types.DelaySensor attribute), 354
DelaySensor (class in bpy.types), 354
delete() (in module bpy.ops.action), 11
delete() (in module bpy.ops.armature), 17
delete() (in module bpy.ops.console), 22
delete() (in module bpy.ops.constraint), 23
delete() (in module bpy.ops.curve), 24
delete() (in module bpy.ops.file), 32
delete() (in module bpy.ops.font), 35
delete() (in module bpy.ops.graph), 38
delete() (in module bpy.ops.marker), 51
delete() (in module bpy.ops.mesh), 53
delete() (in module bpy.ops.nla), 65
delete() (in module bpy.ops.node), 68
delete() (in module bpy.ops.object), 73
delete() (in module bpy.ops.particle), 90
delete() (in module bpy.ops.scene), 97
delete() (in module bpy.ops.screen), 99
delete() (in module bpy.ops.sequencer), 102
delete() (in module bpy.ops.sketch), 108
delete() (in module bpy.ops.text), 112
delete_bookmark() (in module bpy.ops.file), 32
delete_edgeloop() (in module bpy.ops.mesh), 53
delete_metelems() (in module bpy.ops.mball), 52
delete_orientation() (in module bpy.ops.transform), 116
delete_tracks() (in module bpy.ops.nla), 65
DELKEY (in module bge.events), 1226
delSource() (bge.types.BL_Shader method), 1137
delta_location (bpy.types.Object attribute), 612
delta_rotation_euler (bpy.types.Object attribute), 612
delta_rotation_quaternion (bpy.types.Object attribute), 612
delta_scale (bpy.types.Object attribute), 612
density (bpy.types.MaterialVolume attribute), 544
density (bpy.types.SmokeFlowSettings attribute), 809
density_factor (bpy.types.MaterialTextureSlot attribute), 538
density_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
density_scale (bpy.types.MaterialVolume attribute), 544
depth (bpy.types.EnvironmentMap attribute), 380
depth (bpy.types.FModifierNoise attribute), 402
depth (bpy.types.MaterialRaytraceMirror attribute), 531
depth (bpy.types.MaterialRaytraceTransparency attribute), 533
depth (bpy.types.SceneGameData attribute), 749
depth (bpy.types.WorldMistSettings attribute), 1032
depth_max (bpy.types.MaterialRaytraceTransparency attribute), 533
depth_threshold (bpy.types.MaterialVolume attribute), 544
derivate_coefficient (bpy.types.ObjectActuator attribute), 622
determinant() (mathutils.Matrix method), 1059
Device (class in aud), 1122
die_time (bpy.types.Particle attribute), 647
diffuse (bge.types.KX_PolygonMaterial attribute), 1168
diffuse_color (bpy.types.Material attribute), 521
diffuse_color (bpy.types.UserSolidLight attribute), 1003
diffuse_color_factor (bpy.types.MaterialTextureSlot attribute), 538
diffuse_factor (bpy.types.MaterialTextureSlot attribute), 538
diffuse_fresnel (bpy.types.Material attribute), 521
diffuse_fresnel_factor (bpy.types.Material attribute), 521
diffuse_intensity (bpy.types.Material attribute), 521
diffuse_ramp_blend (bpy.types.Material attribute), 521
diffuse_ramp_factor (bpy.types.Material attribute), 522
diffuse_ramp_input (bpy.types.Material attribute), 522
diffuse_shader (bpy.types.Material attribute), 522
diffuse_toon_size (bpy.types.Material attribute), 522
diffuse_toon_smooth (bpy.types.Material attribute), 522
dimension_max (bpy.types.MusgraveTexture attribute), 593
dimensions (bpy.types.Curve attribute), 343
dimensions (bpy.types.Object attribute), 612
dimensions (in module bgl), 1117
dimensions() (in module blf), 1118
direction (bge.types.KX_ConstraintActuator attribute), 1143
direction (bpy.types.Brush attribute), 237
direction (bpy.types.ConstraintActuator attribute), 330
direction (bpy.types.DisplaceModifier attribute), 355
direction (bpy.types.UserSolidLight attribute), 1003
direction (bpy.types.WipeSequence attribute), 1025
direction_axis (bpy.types.ConstraintActuator attribute), 330
direction_axis_pos (bpy.types.ConstraintActuator attribute), 330
directory (bpy.types.FileSelectParams attribute), 409
directory (bpy.types.ImageSequence attribute), 457
directory (bpy.types.SequenceProxy attribute), 775
directory() (in module bpy.ops.file), 32
directory_browse() (in module bpy.ops.buttons), 20
directory_new() (in module bpy.ops.file), 32
disable() (in module blf), 1119
disableMist() (in module bge.render), 1221
disableMotionBlur (bge.types.SCA_2DFilterActuator attribute), 1183
disableMotionBlur() (in module bge.render), 1222
disableRigidBody() (bge.types.KX_GameObject method), 1151
disconnect_hair() (in module bpy.ops.particle), 90

displacement_factor (bpy.types.MaterialTextureSlot attribute), 538
DisplaceModifier (class in bpy.types), 355
 display_aspect (bpy.types.Image attribute), 452
 display_channel (bpy.types.SpaceSequenceEditor attribute), 838
 display_mode (bpy.types.RenderSettings attribute), 730
 display_mode (bpy.types.SpaceOutliner attribute), 836
 display_mode (bpy.types.SpaceSequenceEditor attribute), 838
 display_name() (in module bpy.path), 1046
 display_name_from_filepath() (in module bpy.path), 1046
 display_type (bpy.types.FileSelectParams attribute), 409
 dissolve_speed (bpy.types.SmokeDomainSettings attribute), 807
 distance (bge.types.KX_ConstraintActuator attribute), 1143
 distance (bge.types.KX_LightObject attribute), 1155
 distance (bge.types.KX_NearSensor attribute), 1160
 distance (bge.types.KX_RadarSensor attribute), 1170
 distance (bpy.types.BoidRuleFight attribute), 222
 distance (bpy.types.BoidRuleFollowLeader attribute), 223
 distance (bpy.types.CompositorNodeDBlur attribute), 286
 distance (bpy.types.CompositorNodeDilateErode attribute), 289
 distance (bpy.types.ConstraintActuator attribute), 330
 distance (bpy.types.KinematicConstraint attribute), 494
 distance (bpy.types.Lamp attribute), 496
 distance (bpy.types.LimitDistanceConstraint attribute), 507
 distance (bpy.types.MaterialRaytraceMirror attribute), 531
 distance (bpy.types.NearSensor attribute), 595
 distance (bpy.types.RadarSensor attribute), 711
 distance (bpy.types.ShrinkwrapConstraint attribute), 802
 distance (bpy.types.WorldLighting attribute), 1030
 distance_3d_max (bpy.types.SoundActuator attribute), 820
 distance_3d_reference (bpy.types.SoundActuator attribute), 820
 distance_max (bpy.types.FieldSettings attribute), 405
 distance_maximum (aud.Handle attribute), 1127
 distance_metric (bpy.types.VoronoiTexture attribute), 1012
 distance_min (bpy.types.ClothCollisionSettings attribute), 253
 distance_min (bpy.types.FieldSettings attribute), 405
 distance_min (bpy.types.WorldStarsSettings attribute), 1034
 distance_model (aud.Device attribute), 1122
 distance_reference (aud.Handle attribute), 1128
 distance_repel (bpy.types.ClothCollisionSettings attribute), 253
 DistortedNoiseTexture (class in bpy.types), 356
 DistortedNoiseTexture.users_material (in module bpy.types), 356
 DistortedNoiseTexture.users_object_modifier (in module bpy.types), 356
 distortion (bpy.types.DistortedNoiseTexture attribute), 356
 distribution (bge.types.SCA_RandomActuator attribute), 1188
 distribution (bpy.types.ParticleSettings attribute), 660
 distribution (bpy.types.RandomActuator attribute), 712
 dither_intensity (bpy.types.RenderSettings attribute), 730
 DKEY (in module bge.events), 1223
 dLoc (bge.types.KX_ObjectActuator attribute), 1161
 doc_edit() (in module bpy.ops.wm), 139
 doc_view() (in module bpy.ops.wm), 140
 dof_distance (bpy.types.Camera attribute), 244
 dof_object (bpy.types.Camera attribute), 244
 dolly() (in module bpy.ops.view3d), 132
 domain_object (bpy.types.VoxelData attribute), 1014
 DomainFluidSettings (class in bpy.types), 358
 DomainFluidSettings.fluid_mesh_vertices (in module bpy.types), 358
 DomainFluidSettings.memory_estimate (in module bpy.types), 358
 dome_angle (bpy.types.SceneGameData attribute), 749
 dome_buffer_resolution (bpy.types.SceneGameData attribute), 749
 dome_mode (bpy.types.SceneGameData attribute), 749
 dome_tesselation (bpy.types.SceneGameData attribute), 749
 dome_text (bpy.types.SceneGameData attribute), 749
 dome_tilt (bpy.types.SceneGameData attribute), 749
 DopeSheet (class in bpy.types), 360
 DopeSheet.source (in module bpy.types), 362
 dopesheet_channel (bpy.types.ThemeDopeSheet attribute), 911
 dopesheet_channel (bpy.types.ThemeGraphEditor attribute), 916
 dopesheet_subchannel (bpy.types.ThemeDopeSheet attribute), 911
 dopesheet_subchannel (bpy.types.ThemeGraphEditor attribute), 916
 doppler_factor (aud.Device attribute), 1122
 dot() (mathutils.Quaternion method), 1062
 dot() (mathutils.Vector method), 1066
 double (bpy.types.PropertyGroupItem attribute), 706
 double_array (bpy.types.PropertyGroupItem attribute), 706
 DOWNARROWKEY (in module bge.events), 1225
 dpi (bpy.types.UserPreferencesSystem attribute), 997
 drag (bpy.types.EffectorWeights attribute), 377

drag_factor (bpy.types.ParticleSettings attribute), 660
drag_threshold (bpy.types.UserPreferencesInput attribute), 994
draw() (bpy.types.Header method), 444
draw() (bpy.types.Macro method), 515
draw() (bpy.types.Menu method), 548
draw() (bpy.types.Operator method), 634
draw() (bpy.types.Panel method), 645
draw() (in module blf), 1119
draw() (in module bpy.ops.gpencil), 37
draw_action (bpy.types.ThemeSequenceEditor attribute), 930
draw_bounds_type (bpy.types.Object attribute), 612
draw_channels (bpy.types.SpaceImageEditor attribute), 829
draw_color (bpy.types.ParticleSettings attribute), 660
draw_header() (bpy.types.Panel method), 645
draw_method (bpy.types.ParticleSettings attribute), 660
draw_mode (bpy.types.GreasePencil attribute), 438
draw_overexposed (bpy.types.SpaceSequenceEditor attribute), 838
draw_percentage (bpy.types.ParticleSettings attribute), 660
draw_preset() (bpy.types.Menu method), 548
draw_preview() (in module bpy.ops.sketch), 108
draw_size (bpy.types.Camera attribute), 244
draw_size (bpy.types.ParticleSettings attribute), 661
draw_step (bpy.types.ParticleEdit attribute), 650
draw_step (bpy.types.ParticleSettings attribute), 661
draw_stretch_type (bpy.types.SpaceUVEditor attribute), 842
draw_stroke() (in module bpy.ops.sketch), 108
draw_type (bpy.types.Armature attribute), 174
draw_type (bpy.types.Object attribute), 612
drawingmode (bge.types.KX_PolygonMaterial attribute), 1168
drawLine() (in module bge.render), 1221
Driver (class in bpy.types), 363
Driver.variables (in module bpy.types), 363
driver_add() (bpy.types.bpy_struct method), 1041
driver_button_add() (in module bpy.ops.anim), 14
driver_button_remove() (in module bpy.ops.anim), 14
driver_namespace (in module bpy.app), 1047
driver_remove() (bpy.types.bpy_struct method), 1041
drivers_add_selected() (in module bpy.ops.outliner), 87
drivers_delete_selected() (in module bpy.ops.outliner), 87
DriverTarget (class in bpy.types), 364
DriverVariable (class in bpy.types), 365
DriverVariable.targets (in module bpy.types), 365
drop_named_image() (in module bpy.ops.mesh), 53
drop_named_material() (in module bpy.ops.object), 73
dRot (bge.types.KX_ObjectActuator attribute), 1161
dupli_extrude_cursor() (in module bpy.ops.mesh), 53
dupli_faces_scale (bpy.types.Object attribute), 612
dupli_frames_end (bpy.types.Object attribute), 612
dupli_frames_off (bpy.types.Object attribute), 612
dupli_frames_on (bpy.types.Object attribute), 612
dupli_frames_start (bpy.types.Object attribute), 612
dupli_group (bpy.types.Object attribute), 612
dupli_group (bpy.types.ParticleSettings attribute), 661
dupli_list_clear() (bpy.types.Object method), 618
dupli_list_create() (bpy.types.Object method), 618
dupli_object (bpy.types.ParticleSettings attribute), 661
dupli_offset (bpy.types.Group attribute), 440
dupli_type (bpy.types.Object attribute), 613
duplicate() (in module bpy.ops.action), 11
duplicate() (in module bpy.ops.armature), 17
duplicate() (in module bpy.ops.curve), 24
duplicate() (in module bpy.ops.graph), 38
duplicate() (in module bpy.ops.marker), 51
duplicate() (in module bpy.ops.mesh), 53
duplicate() (in module bpy.ops.nla), 65
duplicate() (in module bpy.ops.node), 68
duplicate() (in module bpy.ops.object), 73
duplicate() (in module bpy.ops.sequencer), 102
duplicate_metealems() (in module bpy.ops.mball), 52
duplicate_move() (in module bpy.ops.action), 11
duplicate_move() (in module bpy.ops.armature), 17
duplicate_move() (in module bpy.ops.graph), 38
duplicate_move() (in module bpy.ops.mesh), 53
duplicate_move() (in module bpy.ops.node), 68
duplicate_move() (in module bpy.ops.object), 73
duplicate_move_linked() (in module bpy.ops.object), 73
duplicates_make_real() (in module bpy.ops.object), 73
dupliob_copy() (in module bpy.ops.particle), 90
dupliob_move_down() (in module bpy.ops.particle), 90
dupliob_move_up() (in module bpy.ops.particle), 91
dupliob_remove() (in module bpy.ops.particle), 91
DupliObject (class in bpy.types), 366
DupliObject.object (in module bpy.types), 366
duration (bge.types.SCA_DelaySensor attribute), 1184
duration (bpy.types.DelaySensor attribute), 354
duration (bpy.types.ParticleTarget attribute), 680
dynamic_friction (bpy.types.GameSoftBodySettings attribute), 433
dynamic_operation (bpy.types.EditObjectActuator attribute), 372

E

edge_color (bpy.types.RenderSettings attribute), 730
edge_creature (bpy.types.ThemeView3D attribute), 939
edge_creature() (in module bpy.ops.transform), 116
edge_creature_inner (bpy.types.SolidifyModifier attribute), 817
edge_creature_outer (bpy.types.SolidifyModifier attribute), 817
edge_creature_rim (bpy.types.SolidifyModifier attribute), 817

edge_draw_type (bpy.types.SpaceUVEditor attribute), 842
 edge_face_add() (in module bpy.ops.mesh), 54
 edge_face_count() (in module bpy_extras.mesh_utils), 1131
 edge_face_count_dict() (in module bpy_extras.mesh_utils), 1131
 edge_facesel (bpy.types.ThemeView3D attribute), 939
 edge_flip() (in module bpy.ops.mesh), 54
 edge_loops_from_edges() (in module bpy_extras.mesh_utils), 1131
 edge_loops_from_faces() (in module bpy_extras.mesh_utils), 1131
 edge_path_live_unwrap (bpy.types.ToolSettings attribute), 948
 edge_path_mode (bpy.types.ToolSettings attribute), 948
 edge_rotate() (in module bpy.ops.mesh), 54
 edge_seam (bpy.types.ThemeView3D attribute), 939
 edge_select (bpy.types.ThemeView3D attribute), 940
 edge_sharp (bpy.types.ThemeView3D attribute), 940
 edge_slide() (in module bpy.ops.transform), 117
 edge_threshold (bpy.types.RenderSettings attribute), 730
 edge_weight_method (bpy.types.BevelModifier attribute), 186
 edgering_select() (in module bpy.ops.mesh), 54
 edges_select_sharp() (in module bpy.ops.mesh), 54
 EdgeSplitModifier (class in bpy.types), 367
 edit_bone (in module bpy.context), 8
 edit_image (in module bpy.context), 9
 edit_mesh_extrude_individual_move() (in module bpy.ops.view3d), 132
 edit_mesh_extrude_move_normal() (in module bpy.ops.view3d), 132
 edit_object (in module bpy.context), 6
 edit_text (in module bpy.context), 9
 editable_bones (in module bpy.context), 5
 EditBone (class in bpy.types), 368
 EditBone.basename (in module bpy.types), 370
 EditBone.center (in module bpy.types), 370
 EditBone.children (in module bpy.types), 370
 EditBone.children_recursive (in module bpy.types), 370
 EditBone.children_recursive_basename (in module bpy.types), 370
 EditBone.matrix (in module bpy.types), 369
 EditBone.parent_recursive (in module bpy.types), 371
 EditBone.vector (in module bpy.types), 371
 EditBone.x_axis (in module bpy.types), 371
 EditBone.y_axis (in module bpy.types), 371
 EditBone.z_axis (in module bpy.types), 371
 edited_clear() (in module bpy.ops.particle), 91
 editmesh_active (bpy.types.ThemeImageEditor attribute), 919
 editmesh_active (bpy.types.ThemeView3D attribute), 940
 editmode_toggle() (in module bpy.ops.object), 74
 EditObjectActuator (class in bpy.types), 372
 effect_fader (bpy.types.Sequence attribute), 768
 effect_hair (bpy.types.ParticleSettings attribute), 661
 effect_strip (bpy.types.ThemeSequenceEditor attribute), 930
 effect_strip_add() (in module bpy.ops.sequencer), 102
 effector_add() (in module bpy.ops.object), 74
 effector_amount (bpy.types.ParticleSettings attribute), 661
 effector_group (bpy.types.SmokeDomainSettings attribute), 807
 EffectorWeights (class in bpy.types), 376
 EffectSequence (class in bpy.types), 374
 EffectSequence.color_balance (in module bpy.types), 374
 EffectSequence.crop (in module bpy.types), 374
 EffectSequence.proxy (in module bpy.types), 374
 EffectSequence.transform (in module bpy.types), 374
 EIGHTKEY (in module bge.events), 1224
 EKEY (in module bge.events), 1223
 elasticity (bpy.types.MaterialPhysics attribute), 530
 emission (bpy.types.MaterialVolume attribute), 544
 emission_color (bpy.types.MaterialVolume attribute), 544
 emission_color_factor (bpy.types.MaterialTextureSlot attribute), 538
 emission_factor (bpy.types.MaterialTextureSlot attribute), 539
 emit (bpy.types.Material attribute), 522
 emit_factor (bpy.types.MaterialTextureSlot attribute), 539
 emit_from (bpy.types.ParticleSettings attribute), 661
 emitter_distance (bpy.types.ParticleEdit attribute), 651
 empty_draw_size (bpy.types.Object attribute), 613
 empty_draw_type (bpy.types.Object attribute), 613
 empty_image_offset (bpy.types.Object attribute), 613
 enable() (in module blf), 1119
 enable_manipulator() (in module bpy.ops.view3d), 132
 enabled (bpy.typesUILayout attribute), 960
 enableMotionBlur() (in module bge.render), 1221
 enableRigidBody() (bge.types.KX_GameObject method), 1150
 enableVisibility() (in module bge.render), 1220
 end() (bge.types.KX_Scene method), 1175
 end_cap (bpy.types.ArrayModifier attribute), 183
 end_frame_set() (in module bpy.ops.time), 116
 end_result() (bpy.types.RenderEngine method), 721
 end_time (bpy.types.ControlFluidSettings attribute), 335
 end_time (bpy.types.DomainFluidSettings attribute), 358
 endGame() (in module bge.logic), 1207
 ENDKEY (in module bge.events), 1226
 endObject() (bge.types.KX_GameObject method), 1147
 energy (bge.types.KX_LightObject attribute), 1155
 energy (bpy.types.Lamp attribute), 496
 enforce (bge.types.BL_ArmatureConstraint attribute), 1198
 engine (bpy.types.RenderSettings attribute), 730

ensure_ext() (in module bpy.path), 1046
ENTERKEY (in module bge.events), 1226
EnumProperty (class in bpy.types), 378
EnumProperty() (in module bpy.props), 1051
EnumProperty.default (in module bpy.types), 378
EnumProperty.default_flag (in module bpy.types), 378
EnumProperty.enum_items (in module bpy.types), 378
EnumPropertyItem (class in bpy.types), 379
EnumPropertyItem.description (in module bpy.types), 379
EnumPropertyItem.identifier (in module bpy.types), 379
EnumPropertyItem.name (in module bpy.types), 379
EnumPropertyItem.value (in module bpy.types), 379
envelope_distance (bpy.types.Bone attribute), 229
envelope_distance (bpy.types.EditBone attribute), 368
envelope_weight (bpy.types.Bone attribute), 229
envelope_weight (bpy.types.EditBone attribute), 368
environment_color (bpy.types.WorldLighting attribute), 1030
environment_energy (bpy.types.WorldLighting attribute), 1031
EnvironmentMap (class in bpy.types), 380
EnvironmentMapTexture (class in bpy.types), 382
EnvironmentMapTexture.environment_map (in module bpy.types), 382
EnvironmentMapTexture.image_user (in module bpy.types), 382
EnvironmentMapTexture.users_material (in module bpy.types), 382
EnvironmentMapTexture.users_object_modifier (in module bpy.types), 382
envmap_clear() (in module bpy.ops.texture), 115
envmap_clear_all() (in module bpy.ops.texture), 115
envmap_save() (in module bpy.ops.texture), 115
EQUALKEY (in module bge.events), 1226
error (class in aud), 1128
error_threshold (bpy.types.MaterialSubsurfaceScattering attribute), 537
error_threshold (bpy.types.SoftBodySettings attribute), 814
error_threshold (bpy.types.WorldLighting attribute), 1031
ESCKEY (in module bge.events), 1226
etch_adaptive_limit (bpy.types.ToolSettings attribute), 948
etch_convert_mode (bpy.types.ToolSettings attribute), 948
etch_length_limit (bpy.types.ToolSettings attribute), 948
etch_number (bpy.types.ToolSettings attribute), 949
etch_roll_mode (bpy.types.ToolSettings attribute), 949
etch_side (bpy.types.ToolSettings attribute), 949
etch_subdivision_number (bpy.types.ToolSettings attribute), 949
etch_template (bpy.types.ToolSettings attribute), 949
Euler (class in mathutils), 1056
Euler.copy() (in module mathutils), 1056
euler_filter() (in module bpy.ops.graph), 38
eval_time (bpy.types.Curve attribute), 343
evaluate() (bpy.types.ColorRamp method), 264
evaluate() (bpy.types.FCurve method), 389
evaluate_envelope() (bpy.types.Bone method), 231
evaluate_envelope() (bpy.types.PoseBone method), 699
evaluation_type (bpy.types.PropertySensor attribute), 707
Event (class in bpy.types), 384
Event.alt (in module bpy.types), 384
Event.ascii (in module bpy.types), 384
Event.ctrl (in module bpy.types), 384
Event.mouse_prev_x (in module bpy.types), 384
Event.mouse_prev_y (in module bpy.types), 384
Event.mouse_region_x (in module bpy.types), 384
Event.mouse_region_y (in module bpy.types), 384
Event.mouse_x (in module bpy.types), 384
Event.mouse_y (in module bpy.types), 384
Event.oskey (in module bpy.types), 384
Event.shift (in module bpy.types), 384
Event.type (in module bpy.types), 384
Event.value (in module bpy.types), 385
event_timer_add() (bpy.types.WindowManager method), 1022
event_timer_remove() (bpy.types.WindowManager method), 1023
event_type (bpy.types.JoystickSensor attribute), 469
events (bge.types.SCA_KeyboardSensor attribute), 1186
events (bge.types.SCA_PythonKeyboard attribute), 1134
events (bge.types.SCA_PythonMouse attribute), 1134
EventToCharacter() (in module bge.events), 1223
EventToString() (in module bge.events), 1223
exclude_ambient_occlusion (bpy.types.SceneRenderLayer attribute), 754
exclude_emit (bpy.types.SceneRenderLayer attribute), 754
exclude_environment (bpy.types.SceneRenderLayer attribute), 754
exclude_indirect (bpy.types.SceneRenderLayer attribute), 754
exclude_reflection (bpy.types.SceneRenderLayer attribute), 754
exclude_refraction (bpy.types.SceneRenderLayer attribute), 754
exclude_shadow (bpy.types.SceneRenderLayer attribute), 754
exclude_specular (bpy.types.SceneRenderLayer attribute), 754
execute() (bpy.types.Operator method), 633
execute() (in module bpy.ops.console), 22
execute() (in module bpy.ops.file), 32
execute_preset() (in module bpy.ops.script), 101

executePriority (bge.types.SCAILogicBrick attribute), 1133
 expanded_toggle() (in module bpy.ops.outliner), 87
 expandPath() (in module bge.logic), 1209
 explode_refresh() (in module bpy.ops.object), 74
 ExplodeModifier (class in bpy.types), 386
 export_layout() (in module bpy.ops.uv), 126
 ExportHelper (class in bpy_extras.io_utils), 1130
 expose() (bpy.types.GroupInputs method), 441
 expose() (bpy.types.GroupOutputs method), 443
 exposure (bpy.types.World attribute), 1028
 expression (bpy.types.Driver attribute), 363
 expression (bpy.types.ExpressionController attribute), 387
 ExpressionController (class in bpy.types), 387
 exr_codec (bpy.types.CompositorNodeOutputFile attribute), 307
 extension (bpy.types.ImageTexture attribute), 460
 extension (bpy.types.VoxelData attribute), 1014
 external_edit() (in module bpy.ops.image), 42
 extra_edge_len (bpy.types.ThemeView3D attribute), 940
 extra_face_angle (bpy.types.ThemeView3D attribute), 940
 extra_face_area (bpy.types.ThemeView3D attribute), 940
 extrapolation (bpy.types.FCurve attribute), 388
 extrapolation (bpy.types.NlaStrip attribute), 597
 extrapolation_type() (in module bpy.ops.action), 11
 extrapolation_type() (in module bpy.ops.graph), 38
 extrude (bpy.types.Curve attribute), 344
 extrude() (in module bpy.ops.armature), 17
 extrude() (in module bpy.ops.curve), 24
 extrude() (in module bpy.ops.mesh), 54
 extrude_edges_move() (in module bpy.ops.mesh), 54
 extrude_faces_move() (in module bpy.ops.mesh), 54
 extrude_forked() (in module bpy.ops.armature), 17
 extrude_move() (in module bpy.ops.armature), 17
 extrude_region_move() (in module bpy.ops.mesh), 54
 extrude_repeat() (in module bpy.ops.mesh), 54
 extrude_vertices_move() (in module bpy.ops.mesh), 55
 eyedropper() (in module bpy.ops.ui), 125

F

F10KEY (in module bge.events), 1225
 F11KEY (in module bge.events), 1225
 F12KEY (in module bge.events), 1226
 F13KEY (in module bge.events), 1226
 F14KEY (in module bge.events), 1226
 F15KEY (in module bge.events), 1226
 F16KEY (in module bge.events), 1226
 F17KEY (in module bge.events), 1226
 F18KEY (in module bge.events), 1226
 F19KEY (in module bge.events), 1226
 F1KEY (in module bge.events), 1225
 F2KEY (in module bge.events), 1225
 F3KEY (in module bge.events), 1225
 F4KEY (in module bge.events), 1225
 F5KEY (in module bge.events), 1225
 F6KEY (in module bge.events), 1225
 F7KEY (in module bge.events), 1225
 F8KEY (in module bge.events), 1225
 F9KEY (in module bge.events), 1225
 f_stop (bpy.types.CompositorNodeDefocus attribute), 287
 face (bpy.types.ThemeImageEditor attribute), 919
 face (bpy.types.ThemeView3D attribute), 940
 face_dot (bpy.types.ThemeImageEditor attribute), 919
 face_dot (bpy.types.ThemeView3D attribute), 940
 face_select (bpy.types.ThemeImageEditor attribute), 919
 face_select (bpy.types.ThemeView3D attribute), 940
 face_select_all() (in module bpy.ops.paint), 88
 face_select_hide() (in module bpy.ops.paint), 88
 face_select_inverse() (in module bpy.ops.paint), 88
 face_select_linked() (in module bpy.ops.paint), 88
 face_select_linked_pick() (in module bpy.ops.paint), 88
 face_select_reveal() (in module bpy.ops.paint), 89
 facedot_size (bpy.types.ThemeImageEditor attribute), 919
 facedot_size (bpy.types.ThemeView3D attribute), 940
 faces_mirror_uv() (in module bpy.ops.mesh), 55
 faces_select_interior() (in module bpy.ops.mesh), 55
 faces_select_linked_flat() (in module bpy.ops.mesh), 55
 faces_shade_flat() (in module bpy.ops.mesh), 55
 faces_shade_smooth() (in module bpy.ops.mesh), 55
 factor (bpy.types.CastModifier attribute), 247
 factor (bpy.types.CompositorNodeBlur attribute), 272
 factor (bpy.types.CompositorNodeSplitViewer attribute), 316
 factor (bpy.types.CompositorNodeVecBlur attribute), 323
 factor (bpy.types.SimpleDeformModifier attribute), 805
 factor (bpy.types.SmoothModifier attribute), 811
 factor_blue (bpy.types.Texture attribute), 882
 factor_density (bpy.types.SPHFluidSettings attribute), 741
 factor_green (bpy.types.Texture attribute), 882
 factor_radius (bpy.types.SPHFluidSettings attribute), 741
 factor_random (bpy.types.ParticleSettings attribute), 661
 factor_red (bpy.types.Texture attribute), 882
 factor_repulsion (bpy.types.SPHFluidSettings attribute), 741
 factor_rest_length (bpy.types.SPHFluidSettings attribute), 741
 factor_stiff_viscosity (bpy.types.SPHFluidSettings attribute), 741
 factor_x (bpy.types.CompositorNodeBlur attribute), 272
 factor_y (bpy.types.CompositorNodeBlur attribute), 272
 Factory (class in aud), 1123
 fade (bpy.types.CompositorNodeGlare attribute), 294
 fade_frames (bpy.types.ParticleEdit attribute), 651

fade_to (bpy.types.MaterialRaytraceMirror attribute), 531
falloff (bpy.types.BoidState attribute), 227
falloff (bpy.types.CompositorNodeDiffMatte attribute), 288
falloff (bpy.types.CompositorNodeDistanceMatte attribute), 291
falloff (bpy.types.HookModifier attribute), 447
falloff (bpy.types.MaterialRaytraceTransparency attribute), 533
falloff (bpy.types.PointDensity attribute), 688
falloff (bpy.types.WorldMistSettings attribute), 1032
falloff_power (bpy.types.FieldSettings attribute), 405
falloff_radius (bpy.types.WarpModifier attribute), 1017
falloff_radius (bpy.types.WaveModifier attribute), 1019
falloff_soft (bpy.types.PointDensity attribute), 688
falloff_speed_scale (bpy.types.PointDensity attribute), 688
falloff_strength (bpy.types.WorldLighting attribute), 1031
falloff_type (bpy.types.FieldSettings attribute), 405
falloff_type (bpy.types.PointLamp attribute), 691
falloff_type (bpy.types.SpotLamp attribute), 857
falloff_type (bpy.types.WarpModifier attribute), 1017
family (bpy.types.TextCurve attribute), 877
far (bge.types.KX_Camera attribute), 1191
fbx() (in module bpy.ops.export_scene), 29
FCurve (class in bpy.types), 388
FCurve.driver (in module bpy.types), 388
FCurve.keyframe_points (in module bpy.types), 389
FCurve.modifiers (in module bpy.types), 389
FCurve.sampled_points (in module bpy.types), 389
FCurveActuator (class in bpy.types), 390
FCurveKeyframePoints (class in bpy.types), 391
FCurveModifiers (class in bpy.types), 392
FCurveSample (class in bpy.types), 393
fear_factor (bpy.types.BoidRuleAvoid attribute), 220
feedback (bpy.types.Itasc attribute), 467
fgon_clear() (in module bpy.ops.mesh), 55
fgon_make() (in module bpy.ops.mesh), 55
fh_damping (bpy.types.ConstraintActuator attribute), 331
fh_damping (bpy.types.MaterialPhysics attribute), 530
fh_distance (bpy.types.MaterialPhysics attribute), 530
fh_force (bpy.types.ConstraintActuator attribute), 331
fh_force (bpy.types.MaterialPhysics attribute), 530
fh_height (bpy.types.ConstraintActuator attribute), 331
field_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
field_order (bpy.types.Image attribute), 452
field_order (bpy.types.RenderSettings attribute), 730
fields_per_frame (bpy.types.ImageUser attribute), 463
FieldSettings (class in bpy.types), 405
file_browse() (in module bpy.ops.buttons), 21
file_format (bpy.types.Image attribute), 452
file_format (bpy.types.RenderSettings attribute), 730
file_format (bpy.types.VoxelData attribute), 1014
file_paste() (in module bpy.ops.font), 35
file_quality (bpy.types.RenderSettings attribute), 731
fileName (bge.types.KX_GameActuator attribute), 1144
fileName (bge.types.KX_SoundActuator attribute), 1176
filename (bpy.types.FileSelectParams attribute), 409
filename (bpy.types.GameActuator attribute), 425
filename (bpy.types.SequenceElement attribute), 774
filenum() (in module bpy.ops.file), 32
filepath (bpy.types.CompositorNodeOutputFile attribute), 307
filepath (bpy.types.DomainFluidSettings attribute), 358
filepath (bpy.types.Image attribute), 452
filepath (bpy.types.Library attribute), 506
filepath (bpy.types.MovieSequence attribute), 586
filepath (bpy.types.MultiresModifier attribute), 591
filepath (bpy.types.ParticleFluidSettings attribute), 652
filepath (bpy.types.PointCache attribute), 685
filepath (bpy.types.RenderSettings attribute), 731
filepath (bpy.types.SequenceProxy attribute), 775
filepath (bpy.types.Sound attribute), 818
filepath (bpy.types.SoundSequence attribute), 821
filepath (bpy.types.Text attribute), 873
filepath (bpy.types.TextureNodeOutput attribute), 895
filepath (bpy.types.VoxelData attribute), 1014
filepath_raw (bpy.types.Image attribute), 452
fileselect_add() (bpy.types.WindowManager class method), 1022
FileSelectParams (class in bpy.types), 409
FileSelectParams.title (in module bpy.types), 409
fill() (in module bpy.ops.armature), 18
fill() (in module bpy.ops.mesh), 55
filter (bpy.types.MaterialRaytraceTransparency attribute), 533
Filter2DActuator (class in bpy.types), 411
filter_eccentricity (bpy.types.EnvironmentMapTexture attribute), 382
filter_eccentricity (bpy.types.ImageTexture attribute), 460
filter_fcurve_name (bpy.types.DopeSheet attribute), 360
filter_glob (bpy.types.FileSelectParams attribute), 409
filter_group (bpy.types.DopeSheet attribute), 360
filter_pass (bpy.types.Filter2DActuator attribute), 411
filter_probes (bpy.types.EnvironmentMapTexture attribute), 382
filter_probes (bpy.types.ImageTexture attribute), 460
filter_size (bpy.types.EnvironmentMapTexture attribute), 382
filter_size (bpy.types.ImageTexture attribute), 460
filter_size (bpy.types.RenderSettings attribute), 731
filter_text (bpy.types.SpaceOutliner attribute), 836
filter_text (bpy.types.SpaceUserPreferences attribute), 844
filter_type (bpy.types.CompositorNodeBlur attribute), 272

filter_type (bpy.types.CompositorNodeFilter attribute), 292
 filter_type (bpy.types.CompositorNodeRotate attribute), 311
 filter_type (bpy.types.EnvironmentMapTexture attribute), 382
 filter_type (bpy.types.ImageTexture attribute), 460
 find() (bpy.types.KeyMaps method), 482
 find() (in module bpy.ops.text), 112
 find_armature() (bpy.types.Object method), 618
 find_missing_files() (in module bpy.ops.file), 33
 find_modal() (bpy.types.KeyMaps method), 482
 find_set_selected() (in module bpy.ops.text), 112
 find_text (bpy.types.SpaceTextEditor attribute), 839
 finish_stroke() (in module bpy.ops.sketch), 108
 fit_length (bpy.types.ArrayModifier attribute), 183
 fit_type (bpy.types.ArrayModifier attribute), 183
 FIVEKEY (in module bge.events), 1224
 FKEY (in module bge.events), 1223
 flare_boost (bpy.types.MaterialHalo attribute), 528
 flare_seed (bpy.types.MaterialHalo attribute), 528
 flare_size (bpy.types.MaterialHalo attribute), 528
 flare_subflare_count (bpy.types.MaterialHalo attribute), 528
 flare_subflare_size (bpy.types.MaterialHalo attribute), 528
 flee_distance (bpy.types.BoidRuleFight attribute), 222
 flip_names() (in module bpy.ops.armature), 18
 flip_names() (in module bpy.ops.pose), 93
 flip_normals() (in module bpy.ops.mesh), 55
 float (bpy.types.PropertyGroupItem attribute), 706
 float_array (bpy.types.PropertyGroupItem attribute), 706
 float_max (bpy.types.RandomActuator attribute), 712
 float_mean (bpy.types.RandomActuator attribute), 713
 float_min (bpy.types.RandomActuator attribute), 713
 float_value (bpy.types.RandomActuator attribute), 713
 FloatProperty (class in bpy.types), 412
 FloatProperty() (in module bpy.props), 1051
 FloatProperty.array_length (in module bpy.types), 412
 FloatProperty.default (in module bpy.types), 412
 FloatProperty.default_array (in module bpy.types), 412
 FloatProperty.hard_max (in module bpy.types), 412
 FloatProperty.hard_min (in module bpy.types), 412
 FloatProperty.precision (in module bpy.types), 412
 FloatProperty.soft_max (in module bpy.types), 412
 FloatProperty.soft_min (in module bpy.types), 413
 FloatProperty.step (in module bpy.types), 413
 FloatVectorProperty() (in module bpy.props), 1052
 floor_location (bpy.types.FloorConstraint attribute), 414
 FloorConstraint (class in bpy.types), 414
 flow (bpy.types.FieldSettings attribute), 405
 fluid (in module bpy.context), 8
 fluid_group (bpy.types.SmokeDomainSettings attribute), 807
 fluid_radius (bpy.types.SPHFluidSettings attribute), 741
 FluidFluidSettings (class in bpy.types), 415
 FluidMeshVertex (class in bpy.types), 416
 FluidMeshVertex.velocity (in module bpy.types), 416
 FluidSettings (class in bpy.types), 417
 FluidSimulationModifier (class in bpy.types), 417
 FluidSimulationModifier.settings (in module bpy.types), 417
 fly() (in module bpy.ops.view3d), 132
 FModifier (class in bpy.types), 394
 FModifier.is_valid (in module bpy.types), 395
 FModifier.type (in module bpy.types), 395
 fmodifier_add() (in module bpy.ops.graph), 39
 fmodifier_add() (in module bpy.ops.nla), 66
 fmodifier_copy() (in module bpy.ops.graph), 39
 fmodifier_copy() (in module bpy.ops.nla), 66
 fmodifier_paste() (in module bpy.ops.graph), 39
 fmodifier_paste() (in module bpy.ops.nla), 66
 FModifierCycles (class in bpy.types), 396
 FModifierEnvelope (class in bpy.types), 397
 FModifierEnvelope.control_points (in module bpy.types), 397
 FModifierEnvelopeControlPoint (class in bpy.types), 398
 FModifierFunctionGenerator (class in bpy.types), 398
 FModifierGenerator (class in bpy.types), 400
 FModifierLimits (class in bpy.types), 401
 FModifierNoise (class in bpy.types), 402
 FModifierPython (class in bpy.types), 403
 FModifierStepped (class in bpy.types), 404
 follow_active_quads() (in module bpy.ops.uv), 126
 follow_curve (bpy.types.TextCurve attribute), 877
 FollowPathConstraint (class in bpy.types), 418
 font (bpy.types.TextCurve attribute), 877
 font_bold (bpy.types.TextCurve attribute), 877
 font_bold_italic (bpy.types.TextCurve attribute), 877
 font_directory (bpy.types.UserPreferencesFilePaths attribute), 992
 font_italic (bpy.types.TextCurve attribute), 877
 font_kerning_style (bpy.types.ThemeFontStyle attribute), 915
 font_size (bpy.types.SpaceConsole attribute), 824
 font_size (bpy.types.SpaceTextEditor attribute), 839
 force (bge.types.KX_ObjectActuator attribute), 1161
 force (bpy.types.EffectorWeights attribute), 377
 force (bpy.types.HookModifier attribute), 447
 force (bpy.types.ObjectActuator attribute), 622
 force_max_x (bpy.types.ObjectActuator attribute), 622
 force_max_y (bpy.types.ObjectActuator attribute), 622
 force_max_z (bpy.types.ObjectActuator attribute), 622
 force_min_x (bpy.types.ObjectActuator attribute), 622
 force_min_y (bpy.types.ObjectActuator attribute), 622
 force_min_z (bpy.types.ObjectActuator attribute), 622
 forcefield_toggle() (in module bpy.ops.object), 74

forceLimitX (bge.types.KX_ObjectActuator attribute), 1162
forceLimitY (bge.types.KX_ObjectActuator attribute), 1162
forceLimitZ (bge.types.KX_ObjectActuator attribute), 1162
foreach_get() (bpy.types.bpy_prop_collection method), 1039
foreach_set() (bpy.types.bpy_prop_collection method), 1039
form_factor (bpy.types.GameObjectSettings attribute), 429
format (aud.Device attribute), 1122
forward_axis (bpy.types.FollowPathConstraint attribute), 418
FOURKEY (in module bge.events), 1224
fps (bpy.types.Image attribute), 452
fps (bpy.types.RenderSettings attribute), 731
fps (bpy.types.SceneGameData attribute), 749
fps_base (bpy.types.RenderSettings attribute), 731
frame (bge.types.BL_ActionActuator attribute), 1136
frame (bge.types.BL_ShapeActionActuator attribute), 1140
frame (bpy.types.FModifierEnvelopeControlPoint attribute), 398
frame (bpy.types.TimelineMarker attribute), 945
frame_after (bpy.types.AnimVizMotionPaths attribute), 166
frame_after (bpy.types.AnimVizOnionSkinning attribute), 168
frame_before (bpy.types.AnimVizMotionPaths attribute), 166
frame_before (bpy.types.AnimVizOnionSkinning attribute), 168
frame_blend_in (bpy.types.ActionActuator attribute), 148
frame_blend_in (bpy.types.ShapeActionActuator attribute), 797
frame_color (bpy.types.SceneGameData attribute), 749
frame_current (bpy.types.Scene attribute), 743
frame_current (bpy.types.ThemeAudioWindow attribute), 907
frame_current (bpy.types.ThemeDopeSheet attribute), 911
frame_current (bpy.types.ThemeGraphEditor attribute), 917
frame_current (bpy.types.ThemeNLAEditor attribute), 924
frame_current (bpy.types.ThemeSequenceEditor attribute), 930
frame_current (bpy.types.ThemeTimeline attribute), 935
frame_current (bpy.types.ThemeView3D attribute), 940
frame_duration (bpy.types.BuildModifier attribute), 243
frame_duration (bpy.types.CompositorNodeImage attribute), 298
frame_duration (bpy.types.ImageUser attribute), 463
frame_end (bpy.types.ActionActuator attribute), 148
frame_end (bpy.types.ActionConstraint attribute), 150
frame_end (bpy.types.AnimVizMotionPaths attribute), 166
frame_end (bpy.types.AnimVizOnionSkinning attribute), 168
frame_end (bpy.types.CompositorNodeOutputFile attribute), 307
frame_end (bpy.types.CompositorNodeTime attribute), 318
frame_end (bpy.types.FCurveActuator attribute), 390
frame_end (bpy.types.FModifierStepped attribute), 404
frame_end (bpy.types.Image attribute), 452
frame_end (bpy.types.NlaStrip attribute), 597
frame_end (bpy.types.ParticleSettings attribute), 661
frame_end (bpy.types.PointCache attribute), 685
frame_end (bpy.types.Scene attribute), 743
frame_end (bpy.types.ShapeActionActuator attribute), 797
frame_end (bpy.types.TextureNodeCurveTime attribute), 889
frame_final_duration (bpy.types.Sequence attribute), 768
frame_final_end (bpy.types.Sequence attribute), 768
frame_final_start (bpy.types.Sequence attribute), 768
frame_jump() (in module bpy.ops.action), 11
frame_jump() (in module bpy.ops.graph), 39
frame_jump() (in module bpy.ops.screen), 99
frame_map_new (bpy.types.RenderSettings attribute), 731
frame_map_old (bpy.types.RenderSettings attribute), 731
frame_number (bpy.types.GPencilFrame attribute), 421
frame_offset (bpy.types.CompositorNodeImage attribute), 298
frame_offset (bpy.types.FModifierStepped attribute), 404
frame_offset (bpy.types.ImageUser attribute), 463
frame_offset() (in module bpy.ops.screen), 99
frame_path() (bpy.types.RenderSettings method), 737
frame_preview_end (bpy.types.Scene attribute), 743
frame_preview_start (bpy.types.Scene attribute), 743
frame_property (bpy.types.ActionActuator attribute), 148
frame_property (bpy.types.FCurveActuator attribute), 390
frame_property (bpy.types.ShapeActionActuator attribute), 797
frame_server_port (bpy.types.UserPreferencesSystem attribute), 997
frame_set() (bpy.types.Scene method), 746
frame_start (bpy.types.ActionActuator attribute), 148
frame_start (bpy.types.ActionConstraint attribute), 150
frame_start (bpy.types.AnimVizMotionPaths attribute), 166
frame_start (bpy.types.AnimVizOnionSkinning attribute), 168

frame_start (bpy.types.BuildModifier attribute), 243
 frame_start (bpy.types.CompositorNodeImage attribute), 298
 frame_start (bpy.types.CompositorNodeOutputFile attribute), 307
 frame_start (bpy.types.CompositorNodeTime attribute), 318
 frame_start (bpy.types.FCurveActuator attribute), 390
 frame_start (bpy.types.FModifierStepped attribute), 404
 frame_start (bpy.types.Image attribute), 452
 frame_start (bpy.types.ImageUser attribute), 463
 frame_start (bpy.types.NlaStrip attribute), 597
 frame_start (bpy.types.ParticleSettings attribute), 662
 frame_start (bpy.types.PointCache attribute), 685
 frame_start (bpy.types.Scene attribute), 744
 frame_start (bpy.types.Sequence attribute), 768
 frame_start (bpy.types.ShapeActionActuator attribute), 797
 frame_start (bpy.types.TextureNodeCurveTime attribute), 889
 frame_step (bpy.types.AnimVizMotionPaths attribute), 166
 frame_step (bpy.types.AnimVizOnionSkinning attribute), 168
 frame_step (bpy.types.FModifierStepped attribute), 404
 frame_step (bpy.types.PointCache attribute), 685
 frame_step (bpy.types.Scene attribute), 744
 frame_type (bpy.types.SceneGameData attribute), 749
 frameEnd (bge.types.BL_ActionActuator attribute), 1136
 frameEnd (bge.types.BL_ShapeActionActuator attribute), 1140
 frameEnd (bge.types.KX_IpoActuator attribute), 1154
 frameMessageCount (bge.types.KX_NetworkMessageSensor attribute), 1160
 framePropName (bge.types.BL_ActionActuator attribute), 1136
 framePropName (bge.types.BL_ShapeActionActuator attribute), 1141
 framePropName (bge.types.KX_IpoActuator attribute), 1154
 frameStart (bge.types.BL_ActionActuator attribute), 1136
 frameStart (bge.types.BL_ShapeActionActuator attribute), 1140
 frameStart (bge.types.KX_IpoActuator attribute), 1154
 free_axis (bpy.types.MaintainVolumeConstraint attribute), 517
 free_bake() (in module bpy.ops.ptcache), 96
 free_bake_all() (in module bpy.ops.ptcache), 97
 free_derived_objects() (in module bpy_extras.io_utils), 1129
 frequency (bge.types.SCA_ISensor attribute), 1134
 frequency (bpy.types.SceneGameData attribute), 750
 frequency (bpy.types.Sensor attribute), 766
 fresnel (bpy.types.MaterialRaytraceMirror attribute), 531
 fresnel (bpy.types.MaterialRaytraceTransparency attribute), 533
 fresnel_factor (bpy.types.MaterialRaytraceMirror attribute), 531
 fresnel_factor (bpy.types.MaterialRaytraceTransparency attribute), 533
 friction (bpy.types.ClothCollisionSettings attribute), 253
 friction (bpy.types.MaterialPhysics attribute), 530
 friction (bpy.types.SoftBodySettings attribute), 814
 friction_coefficients (bpy.types.GameObjectSettings attribute), 429
 friction_factor (bpy.types.CollisionSettings attribute), 263
 friction_random (bpy.types.CollisionSettings attribute), 263
 from_existing() (bpy.types.AnimDataDrivers method), 164
 from_id() (bge.types.CListValue method), 1141
 from_id() (bpy.types.KeyMapItems method), 480
 from_max_x (bpy.types.TransformConstraint attribute), 954
 from_max_y (bpy.types.TransformConstraint attribute), 954
 from_max_z (bpy.types.TransformConstraint attribute), 954
 from_min_x (bpy.types.TransformConstraint attribute), 955
 from_min_y (bpy.types.TransformConstraint attribute), 955
 from_min_z (bpy.types.TransformConstraint attribute), 955
 from_pydata() (bpy.types.Mesh method), 552
 from_string() (bpy.types.Text method), 874
 front (bpy.types.MaterialSubsurfaceScattering attribute), 537
 frustum_culling (bge.types.KX_Camera attribute), 1191
 Function (class in bpy.types), 420
 Function.description (in module bpy.types), 420
 Function.identifier (in module bpy.types), 420
 Function.is_registered (in module bpy.types), 420
 Function.is_registered_optional (in module bpy.types), 420
 Function.parameters (in module bpy.types), 420
 Function.use_self (in module bpy.types), 420
 function_type (bpy.types.FModifierFunctionGenerator attribute), 399
 fuzzy (bpy.types.SoftBodySettings attribute), 814

G

 g (bge.types.KX_VertexProxy attribute), 1181
 g (mathutils.Color attribute), 1055
 gain (bpy.types.CompositorNodeChromaMatte attribute), 275

gain (bpy.types.CompositorNodeColorBalance attribute), 276
gain (bpy.types.MusgraveTexture attribute), 593
gain (bpy.types.SequenceColorBalance attribute), 770
gain_3d_max (bpy.types.SoundActuator attribute), 820
gain_3d_min (bpy.types.SoundActuator attribute), 820
game_property_clear() (in module bpy.ops.object), 74
game_property_copy() (in module bpy.ops.object), 74
game_property_new() (in module bpy.ops.object), 74
game_property_remove() (in module bpy.ops.object), 74
game_start() (in module bpy.ops.view3d), 133
GameActuator (class in bpy.types), 425
GameBooleanProperty (class in bpy.types), 426
GameFloatProperty (class in bpy.types), 427
GameIntProperty (class in bpy.types), 427
GameObjectSettings (class in bpy.types), 428
GameObjectSettings.actuators (in module bpy.types), 428
GameObjectSettings.controllers (in module bpy.types), 428
GameObjectSettings.properties (in module bpy.types), 429
GameObjectSettings.sensors (in module bpy.types), 430
GameObjectSettings.soft_body (in module bpy.types), 430
GameObjectSettings.used_states (in module bpy.types), 431
GameProperty (class in bpy.types), 432
GameSoftBodySettings (class in bpy.types), 433
GameStringProperty (class in bpy.types), 434
GameTimerProperty (class in bpy.types), 435
gamma (bpy.types.AreaLamp attribute), 171
gamma (bpy.types.CompositorNodeColorBalance attribute), 276
gamma (bpy.types.CompositorNodeTonemap attribute), 319
gamma (bpy.types.SequenceColorBalance attribute), 770
gather_method (bpy.types.WorldLighting attribute), 1031
generate() (bpy.types.KeyingSetInfo method), 488
generate_particles (bpy.types.DomainFluidSettings attribute), 358
generated_height (bpy.types.Image attribute), 452
generated_type (bpy.types.Image attribute), 452
generated_width (bpy.types.Image attribute), 453
gesture() (in module bpy.ops.sketch), 108
get() (bge.types.CListValue method), 1141
get() (bge.types.KX_GameObject method), 1154
get() (bge.types.KX_Scene method), 1175
get() (bpy.types.bpy_prop_collection method), 1039
get() (bpy.types.bpy_struct method), 1041
getAngularVelocity() (bge.types.KX_GameObject method), 1149
getAverageFrameRate() (in module bge.logic), 1209
getAxisVect() (bge.types.KX_GameObject method), 1148
getBlendFileList() (in module bge.logic), 1210
getButtonActiveList() (bge.types.SCA_JoystickSensor method), 1186
getButtonStatus() (bge.types.SCA_JoystickSensor method), 1186
getButtonStatus() (bge.types.SCA_MouseSensor method), 1158
getCameraToWorld() (bge.types.KX_Camera method), 1193
getChannel() (bge.types.BL_ActionActuator method), 1137
getConeHeight() (bge.types.KX_RadarSensor method), 1170
getConstraintId() (bge.types.KX_ConstraintWrapper method), 1143
getConstraintId() (bge.types.KX_VehicleWrapper method), 1178
getConstraintType() (bge.types.KX_VehicleWrapper method), 1178
getCurrentController() (in module bge.logic), 1207
getCurrentScene() (in module bge.logic), 1207
getDistanceTo() (bge.types.KX_GameObject method), 1151
getEyeSeparation() (in module bge.render), 1221
getFocalLength() (in module bge.render), 1221
getFragmentProg() (bge.types.BL_Shader method), 1137
getGLSLMaterialSetting() (in module bge.render), 1221
getKeyStatus() (bge.types.SCA_KeyboardSensor method), 1186
getLastDraw() (bge.types.SCA_RandomSensor method), 1190
getLinearVelocity() (bge.types.KX_GameObject method), 1149
getLogicTicRate() (in module bge.logic), 1209
getMaterial() (bge.types.KX_PolyProxy method), 1164
getMaterialIndex() (bge.types.KX_BlanderMaterial method), 1142
getMaterialIndex() (bge.types.KX_PolyProxy method), 1164
getMaterialMode() (in module bge.render), 1221
getMaterialName() (bge.types.KX_MeshProxy method), 1157
getMaterialName() (bge.types.KX_PolyProxy method), 1164
getMaxLogicFrame() (in module bge.logic), 1208
getMaxPhysicsFrame() (in module bge.logic), 1208
getMesh() (bge.types.KX_PolyProxy method), 1165
getNormal() (bge.types.KX_VertexProxy method), 1182
getNumMaterials() (bge.types.KX_MeshProxy method), 1157
getNumPolygons() (bge.types.KX_MeshProxy method), 1158
getNumVertex() (bge.types.KX_PolyProxy method), 1164

getNumWheels() (bge.types.KX_VehicleWrapper method), 1178
 getPhysicsId() (bge.types.KX_GameObject method), 1151
 getPhysicsTicRate() (in module bge.logic), 1209
 getPolygon() (bge.types.KX_MeshProxy method), 1158
 getPropertyNames() (bge.types.KX_GameObject method), 1151
 getRandomFloat() (in module bge.logic), 1210
 getReactionForce() (bge.types.KX_GameObject method), 1150
 getRGBA() (bge.types.KX_VertexProxy method), 1182
 getSceneList() (in module bge.logic), 1207
 getScreenPosition() (bge.types.KX_Camera method), 1193
 getScreenRay() (bge.types.KX_Camera method), 1194
 getScreenVect() (bge.types.KX_Camera method), 1193
 getSeed() (bge.types.SCA_RandomSensor method), 1190
 getShader() (bge.types.KX_BlenderMaterial method), 1142
 getSpectrum() (in module bge.logic), 1208
 getStripElem() (bpy.types.Sequence method), 769
 getTextureName() (bge.types.KX_MeshProxy method), 1157
 getTextureName() (bge.types.KX_PolyProxy method), 1164
 getUV() (bge.types.KX_VertexProxy method), 1181
 getUV2() (bge.types.KX_VertexProxy method), 1181
 getVectTo() (bge.types.KX_GameObject method), 1151
 getVelocity() (bge.types.KX_GameObject method), 1150
 getVertex() (bge.types.KX_MeshProxy method), 1157
 getVertexArrayLength() (bge.types.KX_MeshProxy method), 1157
 getVertexIndex() (bge.types.KX_PolyProxy method), 1164
 getVertexProg() (bge.types.BL_Shader method), 1137
 getWheelOrientationQuaternion() (bge.types.KX_VehicleWrapper method), 1178
 getWheelPosition() (bge.types.KX_VehicleWrapper method), 1179
 getWheelRotation() (bge.types.KX_VehicleWrapper method), 1179
 getWindowHeight() (in module bge.render), 1220
 getWindowWidth() (in module bge.render), 1220
 getWorldToCamera() (bge.types.KX_Camera method), 1193
 getXYZ() (bge.types.KX_VertexProxy method), 1181
 ghost (bge.types.KX_ParentActuator attribute), 1162
 ghost_curves_clear() (in module bpy.ops.graph), 39
 ghost_curves_create() (in module bpy.ops.graph), 39
 ghost_frame_end (bpy.types.Armature attribute), 175
 ghost_frame_start (bpy.types.Armature attribute), 175
 ghost_range_max (bpy.types.GPencilLayer attribute), 422
 ghost_size (bpy.types.Armature attribute), 175
 ghost_step (bpy.types.Armature attribute), 175
 ghost_type (bpy.types.Armature attribute), 175
 GKEY (in module bge.events), 1223
 gl_clip_alpha (bpy.types.UserPreferencesSystem attribute), 997
 gl_free() (bpy.types.Image method), 454
 gl_load() (bpy.types.Image method), 454
 gl_texture (bge.types.KX_PolygonMaterial attribute), 1167
 gl_texture_limit (bpy.types.UserPreferencesSystem attribute), 997
 glare_type (bpy.types.CompositorNodeGlare attribute), 294
 globalDict (in module bge.logic), 1206
 gloss_anisotropic (bpy.types.MaterialRaytraceMirror attribute), 531
 gloss_factor (bpy.types.MaterialRaytraceMirror attribute), 532
 gloss_factor (bpy.types.MaterialRaytraceTransparency attribute), 533
 gloss_samples (bpy.types.MaterialRaytraceMirror attribute), 532
 gloss_samples (bpy.types.MaterialRaytraceTransparency attribute), 533
 gloss_threshold (bpy.types.MaterialRaytraceMirror attribute), 532
 gloss_threshold (bpy.types.MaterialRaytraceTransparency attribute), 533
 GlowSequence (class in bpy.types), 436
 glsl_shader (bpy.types.Filter2DActuator attribute), 411
 goal_default (bpy.types.ClothSettings attribute), 256
 goal_default (bpy.types.SoftBodySettings attribute), 814
 goal_friction (bpy.types.ClothSettings attribute), 256
 goal_friction (bpy.types.SoftBodySettings attribute), 814
 goal_max (bpy.types.ClothSettings attribute), 256
 goal_max (bpy.types.SoftBodySettings attribute), 814
 goal_min (bpy.types.ClothSettings attribute), 256
 goal_min (bpy.types.SoftBodySettings attribute), 814
 goal_spring (bpy.types.ClothSettings attribute), 256
 goal_spring (bpy.types.SoftBodySettings attribute), 814
 GPencilFrame (class in bpy.types), 421
 GPencilFrame.strokes (in module bpy.types), 421
 GPencilLayer (class in bpy.types), 422
 GPencilLayer.active_frame (in module bpy.types), 422
 GPencilLayer.frames (in module bpy.types), 422
 GPencilStroke (class in bpy.types), 423
 GPencilStroke.points (in module bpy.types), 424
 GPencilStrokePoint (class in bpy.types), 424
 grab_clone() (in module bpy.ops.paint), 89
 gravity (bpy.types.ClothSettings attribute), 256
 gravity (bpy.types.DomainFluidSettings attribute), 358

gravity (bpy.types.EffectorWeights attribute), 377
gravity (bpy.types.Scene attribute), 744
gravity (bpy.types.SoftBodySettings attribute), 814
gravity_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
grease_pencil (bpy.types.NodeTree attribute), 607
grease_pencil (bpy.types.Object attribute), 613
grease_pencil (bpy.types.Scene attribute), 744
grease_pencil (bpy.types.SpaceImageEditor attribute), 829
grease_pencil_eraser_radius (bpy.types.UserPreferencesEdit attribute), 988
grease_pencil_euclidean_distance (bpy.types.UserPreferencesEdit attribute), 988
grease_pencil_manhattan_distance (bpy.types.UserPreferencesEdit attribute), 988
GreasePencil (class in bpy.types), 438
GreasePencil.layers (in module bpy.types), 438
GreasePencilLayers (class in bpy.types), 439
grid (bpy.types.ThemeAudioWindow attribute), 907
grid (bpy.types.ThemeDopeSheet attribute), 911
grid (bpy.types.ThemeGraphEditor attribute), 917
grid (bpy.types.ThemeNLAEditor attribute), 924
grid (bpy.types.ThemeSequenceEditor attribute), 930
grid (bpy.types.ThemeTimeline attribute), 935
grid (bpy.types.ThemeView3D attribute), 940
grid_levels (bpy.types.DomainFluidSettings attribute), 358
grid_lines (bpy.types.SpaceView3D attribute), 845
grid_random (bpy.types.ParticleSettings attribute), 662
grid_resolution (bpy.types.ParticleSettings attribute), 662
grid_scale (bpy.types.SpaceView3D attribute), 845
grid_subdivisions (bpy.types.SpaceView3D attribute), 845
group (bpy.types.ClothCollisionSettings attribute), 253
group (bpy.types.EffectorWeights attribute), 377
group (bpy.types.FCurve attribute), 388
group (bpy.types.KeyingSetPath attribute), 489
Group (class in bpy.types), 440
Group.objects (in module bpy.types), 440
Group.users_duplicat_group (in module bpy.types), 440
group_add() (in module bpy.ops.object), 74
group_add() (in module bpy.ops.pose), 93
group_assign() (in module bpy.ops.pose), 93
group_deselect() (in module bpy.ops.pose), 93
group_edit() (in module bpy.ops.node), 68
group_instance_add() (in module bpy.ops.object), 74
group_link() (in module bpy.ops.object), 75
group_make() (in module bpy.ops.node), 68
group_method (bpy.types.KeyingSetPath attribute), 489
group_node (bpy.types.ThemeNodeEditor attribute), 925
group_operation() (in module bpy.ops.outliner), 87
group_remove() (in module bpy.ops.object), 75
group_remove() (in module bpy.ops.pose), 93
group_select() (in module bpy.ops.pose), 93
group_socket_add() (in module bpy.ops.node), 68
group_socket_move_down() (in module bpy.ops.node), 68
group_socket_move_up() (in module bpy.ops.node), 68
group_socket_remove() (in module bpy.ops.node), 68
group_unassign() (in module bpy.ops.pose), 93
group_ungroup() (in module bpy.ops.node), 69
GroupInputs (class in bpy.types), 441
GroupObjects (class in bpy.types), 442
GroupOutputs (class in bpy.types), 443
guide_clump_amount (bpy.types.FieldSettings attribute), 405
guide_clump_shape (bpy.types.FieldSettings attribute), 405
guide_free (bpy.types.FieldSettings attribute), 406
guide_kink_amplitude (bpy.types.FieldSettings attribute), 406
guide_kink_axis (bpy.types.FieldSettings attribute), 406
guide_kink_frequency (bpy.types.FieldSettings attribute), 406
guide_kink_shape (bpy.types.FieldSettings attribute), 406
guide_kink_type (bpy.types.FieldSettings attribute), 406
guide_minimum (bpy.types.FieldSettings attribute), 406

H

h (mathutils.Color attribute), 1056
hair_length (bpy.types.ParticleSettings attribute), 662
hair_step (bpy.types.ParticleSettings attribute), 662
half_life_time (bpy.types.RandomActuator attribute), 713
halo_intensity (bpy.types.SpotLamp attribute), 857
halo_step (bpy.types.SpotLamp attribute), 857
Handle (class in aud), 1127
handle_align (bpy.types.ThemeGraphEditor attribute), 917
handle_align (bpy.types.ThemeView3D attribute), 940
handle_auto (bpy.types.ThemeGraphEditor attribute), 917
handle_auto (bpy.types.ThemeView3D attribute), 940
handle_free (bpy.types.ThemeGraphEditor attribute), 917
handle_free (bpy.types.ThemeView3D attribute), 940
handle_left (bpy.types.BezierSplinePoint attribute), 187
handle_left (bpy.types.Keyframe attribute), 485
handle_left (bpy.types.ShapeKeyBezierPoint attribute), 800
handle_left_type (bpy.types.BezierSplinePoint attribute), 187
handle_left_type (bpy.types.Keyframe attribute), 485
handle_right (bpy.types.BezierSplinePoint attribute), 187
handle_right (bpy.types.Keyframe attribute), 485

handle_right (bpy.types.ShapeKeyBezierPoint attribute), 800
 handle_right_type (bpy.types.BezierSplinePoint attribute), 187
 handle_right_type (bpy.types.Keyframe attribute), 485
 handle_sel_align (bpy.types.ThemeGraphEditor attribute), 917
 handle_sel_align (bpy.types.ThemeView3D attribute), 940
 handle_sel_auto (bpy.types.ThemeGraphEditor attribute), 917
 handle_sel_auto (bpy.types.ThemeView3D attribute), 940
 handle_sel_free (bpy.types.ThemeGraphEditor attribute), 917
 handle_sel_free (bpy.types.ThemeView3D attribute), 940
 handle_sel_vect (bpy.types.ThemeGraphEditor attribute), 917
 handle_sel_vect (bpy.types.ThemeView3D attribute), 940
 handle_type() (in module bpy.ops.action), 11
 handle_type() (in module bpy.ops.graph), 39
 handle_type_set() (in module bpy.ops.curve), 24
 handle_vect (bpy.types.ThemeGraphEditor attribute), 917
 handle_vect (bpy.types.ThemeView3D attribute), 941
 handle_vertex (bpy.types.ThemeGraphEditor attribute), 917
 handle_vertex_select (bpy.types.ThemeGraphEditor attribute), 917
 handle_vertex_size (bpy.types.ThemeGraphEditor attribute), 917
 handlers (in module bpy.app), 1048
 handles_view_toggle() (in module bpy.ops.graph), 39
 hardness (bpy.types.MaterialHalo attribute), 528
 hardness_factor (bpy.types.MaterialTextureSlot attribute), 539
 harmonic (bpy.types.EffectorWeights attribute), 377
 harmonic_damping (bpy.types.FieldSettings attribute), 406
 has_ghost_curves (bpy.types.SpaceGraphEditor attribute), 827
 has_ik (bge.types.BL_ArmatureChannel attribute), 1200
 hat (bge.types.SCA_JoystickSensor attribute), 1185
 hat_direction (bpy.types.JoystickSensor attribute), 469
 hat_number (bpy.types.JoystickSensor attribute), 469
 hatSingle (bge.types.SCA_JoystickSensor attribute), 1185
 hatValues (bge.types.SCA_JoystickSensor attribute), 1184
 head (bge.types.BL_ArmatureBone attribute), 1204
 head (bpy.types.Bone attribute), 229
 head (bpy.types.EditBone attribute), 369
 head_local (bpy.types.Bone attribute), 229
 head_radius (bpy.types.Bone attribute), 229
 head_radius (bpy.types.EditBone attribute), 369
 head_tail (bpy.types.CopyLocationConstraint attribute), 338
 head_tail (bpy.types.CopyTransformsConstraint attribute), 342
 head_tail (bpy.types.PivotConstraint attribute), 681
 head_tail (bpy.types.StretchToConstraint attribute), 861
 head_tail (bpy.types.TrackToConstraint attribute), 953
 header (bpy.types.ThemeAudioWindow attribute), 907
 header (bpy.types.ThemeConsole attribute), 910
 header (bpy.types.ThemeDopeSheet attribute), 911
 header (bpy.types.ThemeFileBrowser attribute), 913
 header (bpy.types.ThemeGraphEditor attribute), 917
 header (bpy.types.ThemeImageEditor attribute), 919
 header (bpy.types.ThemeInfo attribute), 921
 header (bpy.types.ThemeLogicEditor attribute), 922
 header (bpy.types.ThemeNLAEditor attribute), 924
 header (bpy.types.ThemeNodeEditor attribute), 926
 header (bpy.types.ThemeOutliner attribute), 927
 header (bpy.types.ThemeProperties attribute), 929
 header (bpy.types.ThemeSequenceEditor attribute), 930
 header (bpy.types.ThemeTextEditor attribute), 933
 header (bpy.types.ThemeTimeline attribute), 935
 header (bpy.types.ThemeUserPreferences attribute), 938
 header (bpy.types.ThemeView3D attribute), 941
 Header (class in bpy.types), 444
 Header.layout (in module bpy.types), 444
 header_flip() (in module bpy.ops.screen), 99
 header_text (bpy.types.ThemeAudioWindow attribute), 907
 header_text (bpy.types.ThemeConsole attribute), 910
 header_text (bpy.types.ThemeDopeSheet attribute), 912
 header_text (bpy.types.ThemeFileBrowser attribute), 913
 header_text (bpy.types.ThemeGraphEditor attribute), 917
 header_text (bpy.types.ThemeImageEditor attribute), 919
 header_text (bpy.types.ThemeInfo attribute), 921
 header_text (bpy.types.ThemeLogicEditor attribute), 922
 header_text (bpy.types.ThemeNLAEditor attribute), 924
 header_text (bpy.types.ThemeNodeEditor attribute), 926
 header_text (bpy.types.ThemeOutliner attribute), 927
 header_text (bpy.types.ThemeProperties attribute), 929
 header_text (bpy.types.ThemeSequenceEditor attribute), 930
 header_text (bpy.types.ThemeTextEditor attribute), 933
 header_text (bpy.types.ThemeTimeline attribute), 935
 header_text (bpy.types.ThemeUserPreferences attribute), 938
 header_text (bpy.types.ThemeView3D attribute), 941
 header_text_hi (bpy.types.ThemeAudioWindow attribute), 907
 header_text_hi (bpy.types.ThemeConsole attribute), 910
 header_text_hi (bpy.types.ThemeDopeSheet attribute), 912
 header_text_hi (bpy.types.ThemeFileBrowser attribute), 913

header_text_hi (bpy.types.ThemeGraphEditor attribute), 917
header_text_hi (bpy.types.ThemeImageEditor attribute), 920
header_text_hi (bpy.types.ThemeInfo attribute), 921
header_text_hi (bpy.types.ThemeLogicEditor attribute), 922
header_text_hi (bpy.types.ThemeNLAEditor attribute), 924
header_text_hi (bpy.types.ThemeNodeEditor attribute), 926
header_text_hi (bpy.types.ThemeOutliner attribute), 928
header_text_hi (bpy.types.ThemeProperties attribute), 929
header_text_hi (bpy.types.ThemeSequenceEditor attribute), 930
header_text_hi (bpy.types.ThemeTextEditor attribute), 933
header_text_hi (bpy.types.ThemeTimeline attribute), 935
header_text_hi (bpy.types.ThemeUserPreferences attribute), 938
header_text_hi (bpy.types.ThemeView3D attribute), 941
header_text_set() (bpy.types.Area method), 171
header_toolbox() (in module bpy.ops.screen), 99
headtail (bge.types.BL_ArmatureConstraint attribute), 1198
health (bpy.types.BoidSettings attribute), 225
height (bge.types.KX_CameraActuator attribute), 1142
height (bpy.types.BoidSettings attribute), 225
height (bpy.types.Brush attribute), 237
height (bpy.types.CameraActuator attribute), 246
height (bpy.types.TextBox attribute), 875
height (bpy.types.WaveModifier attribute), 1019
height (bpy.types.WorldMistSettings attribute), 1033
HemiLamp (class in bpy.types), 445
hexagonal_grid (bpy.types.ParticleSettings attribute), 662
hide (bpy.types.BezierSplinePoint attribute), 187
hide (bpy.types.Bone attribute), 229
hide (bpy.types.EditBone attribute), 369
hide (bpy.types.FCurve attribute), 388
hide (bpy.types.GPencilLayer attribute), 422
hide (bpy.types.MeshEdge attribute), 557
hide (bpy.types.MeshFace attribute), 559
hide (bpy.types.MeshTextureFace attribute), 566
hide (bpy.types.MeshVertex attribute), 570
hide (bpy.types.MetaElement attribute), 576
hide (bpy.types.Object attribute), 613
hide (bpy.types.Spline attribute), 850
hide (bpy.types.SplinePoint attribute), 855
hide() (in module bpy.ops.armature), 18
hide() (in module bpy.ops.curve), 24
hide() (in module bpy.ops.mesh), 55
hide() (in module bpy.ops.particle), 91
hide() (in module bpy.ops.pose), 93
hide() (in module bpy.ops.uv), 126
hide_metaelems() (in module bpy.ops.mball), 52
hide_recent_locations (bpy.types.UserPreferencesFilePaths attribute), 992
hide_render (bpy.types.Object attribute), 613
hide_render_clear() (in module bpy.ops.object), 75
hide_render_clear_all() (in module bpy.ops.object), 75
hide_render_set() (in module bpy.ops.object), 75
hide_select (bpy.types.Bone attribute), 229
hide_select (bpy.types.EditBone attribute), 369
hide_select (bpy.types.Object attribute), 613
hide_socket_toggle() (in module bpy.ops.node), 69
hide_toggle() (in module bpy.ops.node), 69
hide_view_clear() (in module bpy.ops.object), 75
hide_view_set() (in module bpy.ops.object), 75
hidedot() (in module bpy.ops.file), 33
highlight() (in module bpy.ops.file), 33
hinge (bge.types.BL_ArmatureBone attribute), 1204
Histogram (class in bpy.types), 446
history_append() (in module bpy.ops.console), 22
history_cycle() (in module bpy.ops.console), 22
hitNormal (bge.types.KX_MouseFocusSensor attribute), 1159
hitNormal (bge.types.KX_RaySensor attribute), 1171
hitObject (bge.types.KX_MouseFocusSensor attribute), 1159
hitObject (bge.types.KX_RaySensor attribute), 1171
hitObject (bge.types.KX_TouchSensor attribute), 1159
hitObjectList (bge.types.KX_TouchSensor attribute), 1160
hitPosition (bge.types.KX_MouseFocusSensor attribute), 1159
hitPosition (bge.types.KX_RaySensor attribute), 1171
hitUV (bge.types.KX_MouseFocusSensor attribute), 1159
HKEY (in module bge.events), 1223
hold1 (bge.types.SCA_KeyboardSensor attribute), 1186
hold2 (bge.types.SCA_KeyboardSensor attribute), 1186
HOMEKEY (in module bge.events), 1226
hook_add_newob() (in module bpy.ops.object), 75
hook_add_selob() (in module bpy.ops.object), 75
hook_assign() (in module bpy.ops.object), 75
hook_recenter() (in module bpy.ops.object), 75
hook_remove() (in module bpy.ops.object), 76
hook_reset() (in module bpy.ops.object), 76
hook_select() (in module bpy.ops.object), 76
HookModifier (class in bpy.types), 447
horizon_brightness (bpy.types.LampSkySettings attribute), 498
horizon_color (bpy.types.World attribute), 1028
horizon_factor (bpy.types.WorldTextureSlot attribute), 1035
hsv (mathutils.Color attribute), 1056

|

icon_file (bpy.types.ThemeUserInterface attribute), 936
 icon_filepath (bpy.types.Brush attribute), 237
 id (bpy.types.DriverTarget attribute), 364
 id (bpy.types.KeyingSetPath attribute), 489
 ID (class in bpy.types), 448
 ID.library (in module bpy.types), 448
 ID.users (in module bpy.types), 448
 id_data (bpy.types.bpy_struct attribute), 1044
 id_operation() (in module bpy.ops.outliner), 87
 id_root (bpy.types.Action attribute), 147
 id_type (bpy.types.DriverTarget attribute), 364
 id_type (bpy.types.KeyingSetPath attribute), 489
 identity() (mathutils.Matrix method), 1059
 IDMMaterials (class in bpy.types), 450
 idname (bpy.types.KeyMapItem attribute), 475
 ik_add() (in module bpy.ops.pose), 93
 ik_clear() (in module bpy.ops.pose), 94
 ik_dist (bge.types.BL_ArmatureConstraint attribute), 1199
 ik_dof_x (bge.types.BL_ArmatureChannel attribute), 1200
 ik_dof_y (bge.types.BL_ArmatureChannel attribute), 1200
 ik_dof_z (bge.types.BL_ArmatureChannel attribute), 1200
 ik_flag (bge.types.BL_ArmatureConstraint attribute), 1199
 ik_limit_x (bge.types.BL_ArmatureChannel attribute), 1200
 ik_limit_y (bge.types.BL_ArmatureChannel attribute), 1200
 ik_limit_z (bge.types.BL_ArmatureChannel attribute), 1200
 ik_lin_control (bge.types.BL_ArmatureChannel attribute), 1200
 ik_lin_weight (bge.types.BL_ArmatureChannel attribute), 1203
 ik_linear_weight (bpy.types.PoseBone attribute), 696
 ik_max_x (bge.types.BL_ArmatureChannel attribute), 1202
 ik_max_x (bpy.types.PoseBone attribute), 696
 ik_max_y (bge.types.BL_ArmatureChannel attribute), 1202
 ik_max_z (bge.types.BL_ArmatureChannel attribute), 1202
 ik_max_z (bpy.types.PoseBone attribute), 696
 ik_min_x (bge.types.BL_ArmatureChannel attribute), 1202
 ik_min_x (bpy.types.PoseBone attribute), 696
 ik_min_y (bge.types.BL_ArmatureChannel attribute), 1202
 ik_min_y (bpy.types.PoseBone attribute), 696
 ik_min_z (bge.types.BL_ArmatureChannel attribute), 1202
 ik_min_z (bpy.types.PoseBone attribute), 696
 ik_mode (bge.types.BL_ArmatureConstraint attribute), 1199
 ik_rot_control (bge.types.BL_ArmatureChannel attribute), 1200
 ik_rot_weight (bge.types.BL_ArmatureChannel attribute), 1203
 ik_rotation_weight (bpy.types.PoseBone attribute), 696
 ik_solver (bpy.types.Pose attribute), 694
 ik_stiffness_x (bge.types.BL_ArmatureChannel attribute), 1202
 ik_stiffness_x (bpy.types.PoseBone attribute), 696
 ik_stiffness_y (bge.types.BL_ArmatureChannel attribute), 1202
 ik_stiffness_y (bpy.types.PoseBone attribute), 696
 ik_stiffness_z (bge.types.BL_ArmatureChannel attribute), 1202
 ik_stiffness_z (bpy.types.PoseBone attribute), 696
 ik_stretch (bge.types.BL_ArmatureChannel attribute), 1202
 ik_stretch (bpy.types.PoseBone attribute), 697
 ik_type (bge.types.BL_ArmatureConstraint attribute), 1199
 ik_type (bpy.types.KinematicConstraint attribute), 494
 ik_weight (bge.types.BL_ArmatureConstraint attribute), 1199
 IKEY (in module bge.events), 1223
 IKParam (class in bpy.types), 451
 IKParam.ik_solver (in module bpy.types), 451
 image (bpy.types.BackgroundImage attribute), 184
 image (bpy.types.CompositorNodeImage attribute), 298
 image (bpy.types.EnvironmentMapTexture attribute), 382
 image (bpy.types.ImageTexture attribute), 460
 image (bpy.types.MeshTextureFace attribute), 566
 image (bpy.types.SpaceImageEditor attribute), 829
 image (bpy.types.TextureNodeImage attribute), 892
 image (bpy.types.UVProjectModifier attribute), 982
 image (bpy.types.VoxelDataTexture attribute), 1016
 Image (class in bpy.types), 452
 Image.bindcode (in module bpy.types), 452
 Image.depth (in module bpy.types), 452
 Image.has_data (in module bpy.types), 453
 Image.is_dirty (in module bpy.types), 453
 Image.packed_file (in module bpy.types), 453
 Image.size (in module bpy.types), 453
 Image.type (in module bpy.types), 453
 image_editor (bpy.types.UserPreferencesFilePaths attribute), 992
 image_from_view() (in module bpy.ops.paint), 89
 image_paint() (in module bpy.ops.paint), 89
 image_paint_object (in module bpy.context), 6

image_strip (bpy.types.ThemeSequenceEditor attribute), 931
image_strip_add() (in module bpy.ops.sequencer), 103
image_tool (bpy.types.Brush attribute), 237
image_tool_set() (in module bpy.ops.brush), 20
image_type (bpy.types.CompositorNodeOutputFile attribute), 307
ImagePaint (class in bpy.types), 455
images_separate() (in module bpy.ops.sequencer), 103
ImageSequence (class in bpy.types), 457
ImageSequence.color_balance (in module bpy.types), 457
ImageSequence.crop (in module bpy.types), 457
ImageSequence.elements (in module bpy.types), 457
ImageSequence.proxy (in module bpy.types), 457
ImageSequence.transform (in module bpy.types), 458
ImageTexture (class in bpy.types), 460
ImageTexture.image_user (in module bpy.types), 460
ImageTexture.users_material (in module bpy.types), 462
ImageTexture.users_object_modifier (in module bpy.types), 462
ImageUser (class in bpy.types), 463
ImageUser.multilayer_layer (in module bpy.types), 463
ImageUser.multilayer_pass (in module bpy.types), 463
impact_factor (bpy.types.ObstacleFluidSettings attribute), 627
ImportHelper (class in bpy_extras.io_utils), 1130
in_out_node (bpy.types.ThemeNodeEditor attribute), 926
indent() (in module bpy.ops.text), 112
index (bge.types.SCA_JoystickSensor attribute), 1185
index (bpy.types.CompositorNodeIDMask attribute), 297
index (bpy.types.PointCache attribute), 685
index() (bge.types.CListValue method), 1141
indirect_bounces (bpy.types.WorldLighting attribute), 1031
indirect_factor (bpy.types.WorldLighting attribute), 1031
inflow (bpy.types.FieldSettings attribute), 406
inflow_velocity (bpy.types.InflowFluidSettings attribute), 464
InflowFluidSettings (class in bpy.types), 464
influence (bpy.types.Constraint attribute), 328
influence (bpy.types.NlaStrip attribute), 597
info (bpy.types.GPencilLayer attribute), 422
inherit_scale (bge.types.BL_ArmatureBone attribute), 1204
initial_velocity (bpy.types.FluidFluidSettings attribute), 415
initial_velocity (bpy.types.SmokeFlowSettings attribute), 809
inner (bpy.types.ThemeWidgetColors attribute), 943
inner_anim (bpy.types.ThemeWidgetStateColors attribute), 944
inner_anim_sel (bpy.types.ThemeWidgetStateColors attribute), 944
inner_driven (bpy.types.ThemeWidgetStateColors attribute), 944
inner_driven_sel (bpy.types.ThemeWidgetStateColors attribute), 944
inner_key (bpy.types.ThemeWidgetStateColors attribute), 944
inner_key_sel (bpy.types.ThemeWidgetStateColors attribute), 945
inner_sel (bpy.types.ThemeWidgetColors attribute), 943
insert() (bpy.types.FCurveKeyframePoints method), 391
insert() (in module bpy.ops.console), 22
insert() (in module bpy.ops.text), 112
insert_lorem() (in module bpy.ops.font), 35
INSERTKEY (in module bge.events), 1226
instantAddObject() (bge.types.KX_SCA_AddObjectActuator method), 1172
instantReplaceMesh() (bge.types.KX_SCA_ReplaceMeshActuator method), 1173
int (bpy.types.PropertyGroupItem attribute), 706
int_array (bpy.types.PropertyGroupItem attribute), 706
int_max (bpy.types.RandomActuator attribute), 713
int_mean (bpy.types.RandomActuator attribute), 713
int_min (bpy.types.RandomActuator attribute), 713
int_value (bpy.types.RandomActuator attribute), 713
integral_coefficient (bpy.types.ObjectActuator attribute), 622
integrator (bpy.types.ParticleSettings attribute), 662
intensity (bpy.types.CompositorNodeTonemap attribute), 319
intensity (bpy.types.Texture attribute), 882
intensity (bpy.types.VoxelData attribute), 1014
intensity (bpy.types.WorldMistSettings attribute), 1033
interaction_preset_add() (in module bpy.ops.wm), 140
internal_friction (bpy.types.ClothSettings attribute), 256
interpolate_bezier() (in module mathutils.geometry), 1085
interpolation (bpy.types.ColorRamp attribute), 264
interpolation (bpy.types.Keyframe attribute), 486
interpolation (bpy.types.ShapeKey attribute), 798
interpolation (bpy.types.TransformSequence attribute), 957
interpolation (bpy.types.VoxelData attribute), 1014
interpolation_type() (in module bpy.ops.action), 11
interpolation_type() (in module bpy.ops.graph), 39
interpolation_type_u (bpy.types.Lattice attribute), 502
interpolation_type_v (bpy.types.Lattice attribute), 502
interpolation_type_w (bpy.types.Lattice attribute), 502
intersect_line_line() (in module mathutils.geometry), 1085
intersect_line_line_2d() (in module mathutils.geometry), 1085
intersect_line_plane() (in module mathutils.geometry), 1086

intersect_line_sphere() (in module `mathutils.geometry`), [1086](#)
intersect_line_sphere_2d() (in module `mathutils.geometry`), [1086](#)
intersect_point_line() (in module `mathutils.geometry`), [1087](#)
intersect_point_quad_2d() (in module `mathutils.geometry`), [1087](#)
intersect_point_tri_2d() (in module `mathutils.geometry`), [1087](#)
intersect_ray_tri() (in module `mathutils.geometry`), [1087](#)
IntProperty (class in `bpy.types`), [465](#)
IntProperty() (in module `bpy.props`), [1052](#)
IntProperty.array_length (in module `bpy.types`), [465](#)
IntProperty.default (in module `bpy.types`), [465](#)
IntProperty.default_array (in module `bpy.types`), [465](#)
IntProperty.hard_max (in module `bpy.types`), [465](#)
IntProperty.hard_min (in module `bpy.types`), [466](#)
IntProperty.soft_max (in module `bpy.types`), [466](#)
IntProperty.soft_min (in module `bpy.types`), [466](#)
IntProperty.step (in module `bpy.types`), [466](#)
introspect() (`bpy.typesUILayout` method), [981](#)
IntVectorProperty() (in module `bpy.props`), [1052](#)
invalid (`bge.typesPyObjectPlus` attribute), [1133](#)
invert (`bge.typesSCA_ISensor` attribute), [1134](#)
invert (`bpy.typesSensor` attribute), [766](#)
invert (`bpy.typesTextureSlot` attribute), [904](#)
invert() (in module `bpy.ops.image`), [42](#)
invert() (`mathutils.Matrix` method), [1059](#)
invert_alpha (`bpy.typesCompositorNodeInvert` attribute), [299](#)
invert_alpha (`bpy.typesImageTexture` attribute), [461](#)
invert_gain (`bpy.typesSequenceColorBalance` attribute), [770](#)
invert_gamma (`bpy.typesSequenceColorBalance` attribute), [771](#)
invert_grid (`bpy.typesParticleSettings` attribute), [662](#)
invert_lift (`bpy.typesSequenceColorBalance` attribute), [771](#)
invert_mouse_zoom (`bpy.typesUserPreferencesInput` attribute), [994](#)
invert_normal (`bpy.typesShaderNodeExtendedMaterial` attribute), [779](#)
invert_normal (`bpy.typesShaderNodeMaterial` attribute), [783](#)
invert_rgb (`bpy.typesCompositorNodeInvert` attribute), [299](#)
invert_stencil (`bpy.typesImagePaint` attribute), [455](#)
invert_vertex_group (`bpy.typesArmatureModifier` attribute), [180](#)
invert_vertex_group (`bpy.typesMaskModifier` attribute), [520](#)
invert_vertex_group (`bpy.typesMeshDeformModifier` attribute), [555](#)
invert_vertex_group (`bpy.typesSolidifyModifier` attribute), [817](#)
invert_vertex_group_clump (`bpy.typesParticleSystem` attribute), [674](#)
invert_vertex_group_density (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_field (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_kink (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_length (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_rotation (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_roughness_1 (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_roughness_2 (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_roughness_end (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_size (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_tangent (`bpy.typesParticleSystem` attribute), [675](#)
invert_vertex_group_velocity (`bpy.typesParticleSystem` attribute), [675](#)
invert_x (`bpy.typesCopyLocationConstraint` attribute), [338](#)
invert_x (`bpy.typesCopyRotationConstraint` attribute), [339](#)
invert_y (`bpy.typesCopyLocationConstraint` attribute), [338](#)
invert_y (`bpy.typesCopyRotationConstraint` attribute), [339](#)
invert_z (`bpy.typesCopyLocationConstraint` attribute), [338](#)
invert_z (`bpy.typesCopyRotationConstraint` attribute), [340](#)
invert_z (`bpy.typesMaterial` attribute), [522](#)
invert_zmask (`bpy.typesSceneRenderLayer` attribute), [754](#)
invert_zoom_wheel (`bpy.typesUserPreferencesInput` attribute), [994](#)
inverted() (`mathutils.Matrix` method), [1059](#)
invoke() (`bpy.typesOperator` method), [634](#)
invoke_confirm() (`bpy.types.WindowManager` class method), [1023](#)
invoke_popup() (`bpy.types.WindowManager` class method), [1023](#)
invoke_props_dialog() (`bpy.types.WindowManager` class method), [1023](#)
invoke_props_popup() (`bpy.types.WindowManager` class method), [1023](#)

invoke_search_popup() (bpy.types.WindowManager class method), 1023
ior (bpy.types.MaterialRaytraceTransparency attribute), 533
ior (bpy.types.MaterialSubsurfaceScattering attribute), 537
is_edited (bpy.types.GPencilFrame attribute), 421
is_fgon (bpy.types.MeshEdge attribute), 557
is_loose (bpy.types.MeshEdge attribute), 557
is_modified (bpy.types.MotionPath attribute), 583
is_modified() (bpy.types.Object method), 619
is_negative (mathutils.Matrix attribute), 1061
is_orthogonal (mathutils.Matrix attribute), 1061
is_perspective (bpy.types.RegionView3D attribute), 717
is_property_hidden() (bpy.types.bpy_struct method), 1042
is_property_set() (bpy.types.bpy_struct method), 1042
is_proxy_local (bpy.types.Constraint attribute), 328
is_start (bpy.types.OperatorStrokeElement attribute), 637
is_subdir() (in module bpy.path), 1046
is_user_defined (bpy.types.KeyMap attribute), 473
is_valid (bpy.types.Driver attribute), 363
is_valid (bpy.types.FCurve attribute), 388
is_valid (bpy.types.ParticleTarget attribute), 680
is_visible() (bpy.types.Object method), 618
is_wrapped (mathutils.Color attribute), 1056
is_wrapped (mathutils.Euler attribute), 1057
is_wrapped (mathutils.Matrix attribute), 1061
is_wrapped (mathutils.Quaternion attribute), 1063
is_wrapped (mathutils.Vector attribute), 1068
isCollider() (bge.types.KX_PolyProxy method), 1164
isolate_type_render() (in module bpy.ops.object), 76
isValid() (bge.types.BL_Shader method), 1137
isVisible() (bge.types.KX_PolyProxy method), 1164
Itasc (class in bpy.types), 467
item (bpy.types.ThemeWidgetColors attribute), 943
item_activate() (in module bpy.ops.outliner), 87
item_openclose() (in module bpy.ops.outliner), 87
item_rename() (in module bpy.ops.outliner), 87
items() (bpy.types.bpy_prop_collection method), 1039
items() (bpy.types.bpy_struct method), 1042
iterations (bpy.types.CompositorNodeBilateralblur attribute), 271
iterations (bpy.types.CompositorNodeDBlur attribute), 286
iterations (bpy.types.CompositorNodeGlare attribute), 294
iterations (bpy.types.Itasc attribute), 467
iterations (bpy.types.KinematicConstraint attribute), 494
iterations (bpy.types.ScrewModifier attribute), 763
iterations (bpy.types.SmoothModifier attribute), 811
iterator() (bpy.types.KeyingSetInfo method), 488

J

jitter (bpy.types.Brush attribute), 237
jitter_factor (bpy.types.ParticleSettings attribute), 662
JKEY (in module bge.events), 1223
join() (in module bpy.ops.object), 76
join_shapes() (in module bpy.ops.object), 76
joinUvs() (in module bpy.ops.object), 76
joint_bindings (bpy.types.SplineIKConstraint attribute), 854
joint_rotation (bge.types.BL_ArmatureChannel attribute), 1203
joystick_index (bpy.types.JoystickSensor attribute), 469
JoystickSensor (class in bpy.types), 468
jump() (in module bpy.ops.text), 112

K

keep (aud.Handle attribute), 1128
keep_axis (bpy.types.StretchToConstraint attribute), 861
KERNING_DEFAULT (in module blf), 1118
key (bge.types.SCA_KeyboardSensor attribute), 1186
key (bpy.types.CompositorNodeTonemap attribute), 319
key (bpy.types.KeyboardSensor attribute), 483
Key (class in bpy.types), 470
Key.animation_data (in module bpy.types), 470
Key.key_blocks (in module bpy.types), 470
Key.reference_key (in module bpy.types), 470
Key.user (in module bpy.types), 470
key_modifier (bpy.types.KeyMapItem attribute), 476
keyboard (in module bge.logic), 1206
KeyboardSensor (class in bpy.types), 483
KeyConfig (class in bpy.types), 471
KeyConfig.is_user_defined (in module bpy.types), 471
KeyConfig.keymaps (in module bpy.types), 471
keyconfig_activate() (in module bpy.ops.wm), 140
keyconfig_export() (in module bpy.ops.wm), 140
keyconfig_import() (in module bpy.ops.wm), 140
keyconfig_preset_add() (in module bpy.ops.wm), 140
keyconfig_remove() (in module bpy.ops.wm), 141
keyconfig_set() (in module bpy.utils), 1044
keyconfig_test() (in module bpy.ops.wm), 141
KeyConfigurations (class in bpy.types), 472
KeyConfigurations.default (in module bpy.types), 472
keyed_loops (bpy.types.ParticleSettings attribute), 662
keyframe (bpy.types.ThemeSequenceEditor attribute), 931
Keyframe (class in bpy.types), 485
keyframe_delete() (bpy.types.bpy_struct method), 1042
keyframe_delete() (in module bpy.ops.anim), 14
keyframe_delete_button() (in module bpy.ops.anim), 15
keyframe_delete_v3d() (in module bpy.ops.anim), 15
keyframe_insert() (bpy.types.bpy_struct method), 1042
keyframe_insert() (in module bpy.ops.action), 11
keyframe_insert() (in module bpy.ops.anim), 15
keyframe_insert() (in module bpy.ops.graph), 39

keyframe_insert_button() (in module bpy.ops.anim), 15
 keyframe_insert_menu() (in module bpy.ops.anim), 15
 keyframe_jump() (in module bpy.ops.screen), 99
 keyframe_new_handle_type
 (bpy.types.UserPreferencesEdit attribute), 989
 keyframe_new_interpolation_type
 (bpy.types.UserPreferencesEdit attribute), 989
 keyframe_type() (in module bpy.ops.action), 11
 keying_set_active_set() (in module bpy.ops.anim), 15
 keying_set_add() (in module bpy.ops.anim), 15
 keying_set_export() (in module bpy.ops.anim), 15
 keying_set_path_add() (in module bpy.ops.anim), 16
 keying_set_path_remove() (in module bpy.ops.anim), 16
 keying_set_remove() (in module bpy.ops.anim), 16
 KeyingSet (class in bpy.types), 487
 KeyingSet.is_path_absolute (in module bpy.types), 487
 KeyingSet.paths (in module bpy.types), 487
 KeyingSet.type_info (in module bpy.types), 487
 keyingset_add_selected() (in module bpy.ops.outliner), 87
 keyingset_button_add() (in module bpy.ops.anim), 16
 keyingset_button_remove() (in module bpy.ops.anim), 16
 keyingset_remove_selected() (in module bpy.ops.outliner), 87
 KeyingSetInfo (class in bpy.types), 488
 KeyingSetPath (class in bpy.types), 489
 KeyingSetPaths (class in bpy.types), 490
 KeyingSets (class in bpy.types), 492
 KeyingSetsAll (class in bpy.types), 493
 keyitem_add() (in module bpy.ops.wm), 141
 keyitem_remove() (in module bpy.ops.wm), 141
 keyitem_restore() (in module bpy.ops.wm), 141
 KeyMap (class in bpy.types), 473
 KeyMap.is_modal (in module bpy.types), 473
 KeyMap.keymap_items (in module bpy.types), 473
 KeyMap.name (in module bpy.types), 474
 KeyMap.region_type (in module bpy.types), 474
 KeyMap.space_type (in module bpy.types), 474
 keymap_edit() (in module bpy.ops.wm), 141
 keymap_restore() (in module bpy.ops.wm), 141
 KeyMapItem (class in bpy.types), 475
 KeyMapItem.id (in module bpy.types), 475
 KeyMapItem.is_user_defined (in module bpy.types), 476
 KeyMapItem.name (in module bpy.types), 476
 KeyMapItem.properties (in module bpy.types), 476
 KeyMapItems (class in bpy.types), 478
 KeyMaps (class in bpy.types), 481
 keys() (bpy.types.bpy_prop_collection method), 1039
 keys() (bpy.types.bpy_struct method), 1043
 keys_step (bpy.types.ParticleSettings attribute), 662
 KinematicConstraint (class in bpy.types), 493
 kink (bpy.types.ParticleSettings attribute), 662
 kink_amplitude (bpy.types.ParticleSettings attribute), 662
 kink_amplitude_clump (bpy.types.ParticleSettings attribute), 663
 kink_axis (bpy.types.ParticleSettings attribute), 663
 kink_factor (bpy.types.ParticleSettingsTextureSlot attribute), 670
 kink_flat (bpy.types.ParticleSettings attribute), 663
 kink_frequency (bpy.types.ParticleSettings attribute), 663
 kink_shape (bpy.types.ParticleSettings attribute), 663
 KKEY (in module bge.events), 1223
 knife_cut() (in module bpy.ops.mesh), 55
 KX_ACT_CONSTRAINT_DISTANCE (in module bge.logic), 1212
 KX_ACT_CONSTRAINT_DOROTFH (in module bge.logic), 1212
 KX_ACT_CONSTRAINT_FHNX (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_FHNY (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_FHNZ (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_FHPX (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_FHPY (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_FHPZ (in module bge.logic), 1213
 KX_ACT_CONSTRAINT_LOCAL (in module bge.logic), 1212
 KX_ACT_CONSTRAINT_MATERIAL (in module bge.logic), 1212
 KX_ACT_CONSTRAINT_NORMAL (in module bge.logic), 1211
 KX_ACT_CONSTRAINT_PERMANENT (in module bge.logic), 1212
 KX_ACTIONACT_FLIPPER (in module bge.logic), 1211, 1214
 KX_ACTIONACT_LOOPEND (in module bge.logic), 1211, 1215
 KX_ACTIONACT_LOOPSTOP (in module bge.logic), 1211, 1214
 KX_ACTIONACT_PLAY (in module bge.logic), 1211, 1214
 KX_ACTIONACT_PROPERTY (in module bge.logic), 1211, 1215
 KX_ArmatureSensor (class in bge.types), 1195
 KX_ArmatureSensor.KX_ARMSENSOR_LIN_ERROR ABOVE
 (in module bge.types), 1196
 KX_ArmatureSensor.KX_ARMSENSOR_LIN_ERROR BELOW
 (in module bge.types), 1196
 KX_ArmatureSensor.KX_ARMSENSOR_ROT_ERROR ABOVE
 (in module bge.types), 1196
 KX_ArmatureSensor.KX_ARMSENSOR_ROT_ERROR BELOW
 (in module bge.types), 1196

KX_ArmatureSensor.KX_ARMSENSOR_STATE_CHANGED (in module bge.types), 1196
KX_BLENDER_GLSL_MATERIAL (in module bge.render), 1219
KX_BLENDER_MULTITEX_MATERIAL (in module bge.render), 1219
KX_BlenderMaterial (class in bge.types), 1142
KX_Camera (class in bge.types), 1190
KX_Camera.INSIDE (in module bge.types), 1190
KX_Camera.INTERSECT (in module bge.types), 1190
KX_Camera.OUTSIDE (in module bge.types), 1190
KX_CameraActuator (class in bge.types), 1142
KX_CONSTRAINTACT_DIRNX (in module bge.logic), 1212
KX_CONSTRAINTACT_DIRNY (in module bge.logic), 1212
KX_CONSTRAINTACT_DIRNZ (in module bge.logic), 1212
KX_CONSTRAINTACT_DIRPX (in module bge.logic), 1212
KX_CONSTRAINTACT_DIRPY (in module bge.logic), 1212
KX_CONSTRAINTACT_DIRPZ (in module bge.logic), 1212
KX_CONSTRAINTACT_LOCX (in module bge.logic), 1212
KX_CONSTRAINTACT_LOCY (in module bge.logic), 1212
KX_CONSTRAINTACT_LOCZ (in module bge.logic), 1212
KX_CONSTRAINTACT_ORIX (in module bge.logic), 1212
KX_CONSTRAINTACT_ORIY (in module bge.logic), 1212
KX_CONSTRAINTACT_ORIZ (in module bge.logic), 1212
KX_CONSTRAINTACT_ROTX (in module bge.logic), 1212
KX_CONSTRAINTACT_ROTY (in module bge.logic), 1212
KX_CONSTRAINTACT_ROTZ (in module bge.logic), 1212
KX_ConstraintActuator (class in bge.types), 1142
KX_ConstraintWrapper (class in bge.types), 1143
KX_DYN_DISABLE_DYNAMICS (in module bge.logic), 1213
KX_DYN_DISABLE_RIGID_BODY (in module bge.logic), 1213
KX_DYN_ENABLE_RIGID_BODY (in module bge.logic), 1213
KX_DYN_RESTORE_DYNAMICS (in module bge.logic), 1213
KX_DYN_SET_MASS (in module bge.logic), 1213
KX_FALSE (in module bge.logic), 1210
KX_GAME_LOAD (in module bge.logic), 1213
KX_GAME_LOADCFG (in module bge.logic), 1213
KX_GAME_QUIT (in module bge.logic), 1213
KX_GAME_RESTART (in module bge.logic), 1213
KX_GAME_SAVECFG (in module bge.logic), 1213
KX_GAME_START (in module bge.logic), 1213
KX_GameActuator (class in bge.types), 1144
KX_GameObject (class in bge.types), 1144
KX_INPUT_ACTIVE (in module bge.logic), 1215
KX_INPUT JUST_ACTIVATED (in module bge.logic), 1215
KX_INPUT JUST_RELEASED (in module bge.logic), 1215
KX_INPUT_NONE (in module bge.logic), 1215
KX_IPOACT_FLIPPER (in module bge.logic), 1213
KX_IPOACT_FROM_PROP (in module bge.logic), 1214
KX_IPOACT_LOOPEND (in module bge.logic), 1213
KX_IPOACT_LOOPSTOP (in module bge.logic), 1213
KX_IPOACT_PINGPONG (in module bge.logic), 1213
KX_IPOACT_PLAY (in module bge.logic), 1213
KX_IpoActuator (class in bge.types), 1154
KX_LightObject (class in bge.types), 1155
KX_LightObject.NORMAL (in module bge.types), 1155
KX_LightObject.SPOT (in module bge.types), 1155
KX_LightObject.SUN (in module bge.types), 1155
KX_MeshProxy (class in bge.types), 1156
KX_MOUSE_BUT_LEFT (in module bge.logic), 1215
KX_MOUSE_BUT_MIDDLE (in module bge.logic), 1215
KX_MOUSE_BUT_RIGHT (in module bge.logic), 1215
KX_MouseFocusSensor (class in bge.types), 1158
KX_NearSensor (class in bge.types), 1160
KX_NetworkMessageActuator (class in bge.types), 1160
KX_NetworkMessageSensor (class in bge.types), 1160
KX_ObjectActuator (class in bge.types), 1160
KX_PARENT_REMOVE (in module bge.logic), 1214
KX_PARENT_SET (in module bge.logic), 1214
KX_ParentActuator (class in bge.types), 1162
KX_PhysicsObjectWrapper (class in bge.types), 1162
KX_PolygonMaterial (class in bge.types), 1165
KX_PolyProxy (class in bge.types), 1163
KX_PROPSENSOR_CHANGED (in module bge.logic), 1210
KX_PROPSENSOR_EQUAL (in module bge.logic), 1210
KX_PROPSENSOR_EXPRESSION (in module bge.logic), 1210
KX_PROPSENSOR_INTERVAL (in module bge.logic), 1210
KX_PROPSENSOR_NOTEQUAL (in module bge.logic), 1210
KX_RADAR_AXIS_NEG_X (in module bge.logic), 1211

KX_RADAR_AXIS_NEG_Y (in module bge.logic),	KX_SENSOR_ACTIVE (in module bge.logic),
1211	1210
KX_RADAR_AXIS_NEG_Z (in module bge.logic),	KX_SENSOR_INACTIVE (in module bge.logic),
1211	1210
KX_RADAR_AXIS_POS_X (in module bge.logic),	KX_SENSOR JUST_ACTIVATED (in module
1211	bge.logic),
KX_RADAR_AXIS_POS_Y (in module bge.logic),	KX_SENSOR JUST_DEACTIVATED (in module
1211	bge.logic),
KX_RADAR_AXIS_POS_Z (in module bge.logic),	KX_SOUNDACT_LOOPBIDIRECTIONAL (in module
1211	bge.logic),
KX_RadarSensor (class in bge.types),	KX_SOUNDACT_LOOPBIDIRECTIONAL_STOP (in
1170	module bge.logic),
KX_RANDOMACT_BOOL_BERNOULLI (in module	KX_SOUNDACT_LOOPEND (in module bge.logic),
bge.logic),	1215
1214	KX_SOUNDACT_LOOPSTOP (in module bge.logic),
KX_RANDOMACT_BOOL_CONST (in module	1215
bge.logic),	KX_SOUNDACT_PLAYEND (in module bge.logic),
1214	1215
KX_RANDOMACT_BOOL_UNIFORM (in module	KX_SOUNDACT_PLAYSTOP (in module bge.logic),
bge.logic),	1215
1214	KX_SoundActuator (class in bge.types),
KX_RANDOMACT_FLOAT_CONST (in module	1176
bge.logic),	KX_STATE1 (in module bge.logic),
1214	1216
KX_RANDOMACT_FLOAT_UNIFORM (in module	KX_STATE10 (in module bge.logic),
bge.logic),	1216
1214	KX_STATE11 (in module bge.logic),
KX_RANDOMACT_INT_CONST (in module	1216
bge.logic),	KX_STATE12 (in module bge.logic),
1214	1216
KX_RANDOMACT_INT_POISSON (in module	KX_STATE13 (in module bge.logic),
bge.logic),	1216
1214	KX_STATE14 (in module bge.logic),
KX_RANDOMACT_INT_UNIFORM (in module	1216
bge.logic),	KX_STATE15 (in module bge.logic),
1214	1216
KX_RAY_AXIS_NEG_X (in module bge.logic),	KX_STATE16 (in module bge.logic),
1211	1216
KX_RAY_AXIS_NEG_Y (in module bge.logic),	KX_STATE17 (in module bge.logic),
1211	1216
KX_RAY_AXIS_NEG_Z (in module bge.logic),	KX_STATE18 (in module bge.logic),
1211	1216
KX_RAY_AXIS_POS_X (in module bge.logic),	KX_STATE19 (in module bge.logic),
1211	1216
KX_RAY_AXIS_POS_Y (in module bge.logic),	KX_STATE2 (in module bge.logic),
1211	1216
KX_RAY_AXIS_POS_Z (in module bge.logic),	KX_STATE20 (in module bge.logic),
1211	1216
KX_RaySensor (class in bge.types),	KX_STATE21 (in module bge.logic),
1170	1216
KX_SCA_AddObjectActuator (class in bge.types),	KX_STATE22 (in module bge.logic),
1171	1216
KX_SCA_DynamicActuator (class in bge.types),	KX_STATE23 (in module bge.logic),
1172	1216
KX_SCA_EndObjectActuator (class in bge.types),	KX_STATE24 (in module bge.logic),
1172	1216
KX_SCA_ReplaceMeshActuator (class in bge.types),	KX_STATE25 (in module bge.logic),
1172	1216
KX_Scene (class in bge.types),	KX_STATE26 (in module bge.logic),
1173	1216
KX_SCENE_ADD_BACK_SCENE (in module	KX_STATE27 (in module bge.logic),
bge.logic),	1216
1214	KX_STATE28 (in module bge.logic),
KX_SCENE_ADD_FRONT_SCENE (in module	1216
bge.logic),	KX_STATE29 (in module bge.logic),
1214	1216
KX_SCENE_REMOVE_SCENE (in module bge.logic),	KX_STATE3 (in module bge.logic),
1214	1216
KX_SCENE_RESTART (in module bge.logic),	KX_STATE30 (in module bge.logic),
1214	1216
KX_SCENE_RESUME (in module bge.logic),	KX_STATE4 (in module bge.logic),
1214	1216
KX_SCENE_SET_CAMERA (in module bge.logic),	KX_STATE5 (in module bge.logic),
1214	1216
KX_SCENE_SET_SCENE (in module bge.logic),	KX_STATE6 (in module bge.logic),
1214	1216
KX_SCENE_SUSPEND (in module bge.logic),	KX_STATE7 (in module bge.logic),
1214	1216
KX_SceneActuator (class in bge.types),	KX_STATE8 (in module bge.logic),
1175	1216
	KX_STATE9 (in module bge.logic),
	1216
	KX_STATE_OP_CLR (in module bge.logic),
	1216
	KX_STATE_OP_CPY (in module bge.logic),
	1216
	KX_STATE_OP_NEG (in module bge.logic),
	1217
	KX_STATE_OP_SET (in module bge.logic),
	1217
	KX_StateActuator (class in bge.types),
	1177

KX_TEXFACE_MATERIAL (in module bge.render), [1219](#)
KX_TouchSensor (class in bge.types), [1159](#)
KX_TrackToActuator (class in bge.types), [1177](#)
KX_TRUE (in module bge.logic), [1210](#)
KX_VehicleWrapper (class in bge.types), [1177](#)
KX_VertexProxy (class in bge.types), [1180](#)
KX_VisibilityActuator (class in bge.types), [1182](#)

L

label (bpy.types.Node attribute), [602](#)
label() (bpy.typesUILayout method), [974](#)
lacunarity (bpy.types.MusgraveTexture attribute), [593](#)
lamp (bpy.types.ThemeView3D attribute), [941](#)
Lamp (class in bpy.types), [496](#)
lamp (in module bpy.context), [8](#)
Lamp.animation_data (in module bpy.types), [496](#)
Lamp.texture_slots (in module bpy.types), [497](#)
lamp_add() (in module bpy.ops.object), [76](#)
LampSkySettings (class in bpy.types), [498](#)
LampTextureSlot (class in bpy.types), [500](#)
LampTextureSlots (class in bpy.types), [501](#)
land_acc_max (bpy.types.BoidSettings attribute), [225](#)
land_ave_max (bpy.types.BoidSettings attribute), [225](#)
land_jump_speed (bpy.types.BoidSettings attribute), [225](#)
land_personal_space (bpy.types.BoidSettings attribute), [225](#)
land_smooth (bpy.types.BoidSettings attribute), [226](#)
land_speed_max (bpy.types.BoidSettings attribute), [226](#)
land_stick_force (bpy.types.BoidSettings attribute), [226](#)
language (bpy.types.SpaceConsole attribute), [824](#)
language (bpy.types.UserPreferencesSystem attribute), [997](#)
language() (in module bpy.ops.console), [22](#)
lastDraw (bge.types.SCA_RandomSensor attribute), [1190](#)
lastsel_point (bpy.types.ThemeGraphEditor attribute), [917](#)
lastsel_point (bpy.types.ThemeView3D attribute), [941](#)
Lattice (class in bpy.types), [502](#)
lattice (in module bpy.context), [7](#)
Lattice.animation_data (in module bpy.types), [502](#)
Lattice.points (in module bpy.types), [502](#)
Lattice.shape_keys (in module bpy.types), [503](#)
LatticeModifier (class in bpy.types), [504](#)
LatticePoint (class in bpy.types), [505](#)
LatticePoint.co (in module bpy.types), [505](#)
LatticePoint.groups (in module bpy.types), [505](#)
layer (bge.types.KX_LightObject attribute), [1155](#)
layer (bpy.types.CompositorNodeImage attribute), [298](#)
layer (bpy.types.CompositorNodeRLayers attribute), [310](#)
layer_add() (in module bpy.ops.gpencil), [37](#)
layers (bpy.types.Armature attribute), [175](#)
layers (bpy.types.Bone attribute), [229](#)

layers (bpy.types.EditBone attribute), [369](#)
layers (bpy.types.Group attribute), [440](#)
layers (bpy.types.Object attribute), [613](#)
layers (bpy.types.ObjectBase attribute), [624](#)
layers (bpy.types.Scene attribute), [744](#)
layers (bpy.types.SceneRenderLayer attribute), [754](#)
layers (bpy.types.SpaceView3D attribute), [846](#)
layers() (in module bpy.ops.view3d), [133](#)
layers_from_view() (bpy.types.ObjectBase method), [624](#)
layers_ignore (bpy.types.EnvironmentMap attribute), [380](#)
layers_protected (bpy.types.Armature attribute), [175](#)
layers_show_all() (in module bpy.ops.armature), [18](#)
layers_zmask (bpy.types.SceneRenderLayer attribute), [754](#)

LEFTALTKEY (in module bge.events), [1224](#)
LEFTARROWKEY (in module bge.events), [1225](#)
LEFTBRACKETKEY (in module bge.events), [1226](#)
LEFTCTRLKEY (in module bge.events), [1224](#)
LEFTMOUSE (in module bge.events), [1223](#)
LEFTSHIFTKEY (in module bge.events), [1224](#)
length (bge.types.BL_ArmatureBone attribute), [1204](#)
length (bpy.types.Bone attribute), [231](#)
length (bpy.types.EditBone attribute), [371](#)
length (bpy.types.PoseBone attribute), [699](#)
length (mathutils.Vector attribute), [1068](#)
length_factor (bpy.types.ParticleSettingsTextureSlot attribute), [670](#)
length_mode (bpy.types.ParticleBrush attribute), [648](#)
length_random (bpy.types.ParticleSettings attribute), [663](#)
lennardjones (bpy.types.EffectorWeights attribute), [377](#)
lens (bge.types.KX_Camera attribute), [1190](#)
lens (bpy.types.Camera attribute), [244](#)
lens (bpy.types.SpaceView3D attribute), [846](#)
lens_unit (bpy.types.Camera attribute), [244](#)
level (bge.types.SCA_ISensor attribute), [1134](#)
level (bpy.types.BoidRuleAverageSpeed attribute), [219](#)
levels (bpy.types.MultiresModifier attribute), [592](#)
levels (bpy.types.SubsurfModifier attribute), [867](#)
LibFree() (in module bge.logic), [1208](#)
LibList() (in module bge.logic), [1208](#)
LibLoad() (in module bge.logic), [1207](#)
LibNew() (in module bge.logic), [1207](#)
Library (class in bpy.types), [506](#)
Library.parent (in module bpy.types), [506](#)
Library.users_id (in module bpy.types), [506](#)
life_factor (bpy.types.ParticleSettingsTextureSlot attribute), [670](#)
lifetime (bpy.types.Particle attribute), [647](#)
lifetime (bpy.types.ParticleSettings attribute), [663](#)
lifetime (bpy.types.WaveModifier attribute), [1019](#)
lifetime_random (bpy.types.ParticleSettings attribute), [663](#)
lift (bpy.types.CompositorNodeChromaMatte attribute), [275](#)

lift (bpy.types.CompositorNodeColorBalance attribute), 276
 lift (bpy.types.SequenceColorBalance attribute), 771
 light_group (bpy.types.Material attribute), 522
 light_method (bpy.types.MaterialVolume attribute), 544
 light_override (bpy.types.SceneRenderLayer attribute), 755
 lightlayer (bge.types.KX_PolygonMaterial attribute), 1168
 lightmap_pack() (in module bpy.ops.uv), 126
 lights (bge.types.KX_Scene attribute), 1174
 limit (bge.types.KX_ConstraintActuator attribute), 1143
 limit (bpy.types.ConstraintActuator attribute), 331
 limit_angle_max_x (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_angle_max_y (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_angle_max_z (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_angle_min_x (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_angle_min_y (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_angle_min_z (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_channel (bpy.types.CompositorNodeChannelMatte attribute), 274
 limit_channel (bpy.types.CompositorNodeColorSpill attribute), 278
 limit_max (bpy.types.CompositorNodeChannelMatte attribute), 274
 limit_max (bpy.types.CompositorNodeLumaMatte attribute), 301
 limit_max (bpy.types.ConstraintActuator attribute), 331
 limit_max_x (bpy.types.RigidBodyJointConstraint attribute), 738
 limit_max_y (bpy.types.RigidBodyJointConstraint attribute), 739
 limit_max_z (bpy.types.RigidBodyJointConstraint attribute), 739
 limit_method (bpy.types.BevelModifier attribute), 186
 limit_method (bpy.types.CompositorNodeChannelMatte attribute), 274
 limit_method (bpy.types.CompositorNodeColorSpill attribute), 278
 limit_min (bpy.types.CompositorNodeChannelMatte attribute), 274
 limit_min (bpy.types.CompositorNodeLumaMatte attribute), 301
 limit_min (bpy.types.ConstraintActuator attribute), 331
 limit_min_x (bpy.types.RigidBodyJointConstraint attribute), 739
 limit_min_y (bpy.types.RigidBodyJointConstraint attribute), 739
 limit_min_z (bpy.types.RigidBodyJointConstraint attribute), 739
 limit_mode (bpy.types.KinematicConstraint attribute), 494
 limit_mode (bpy.types.LimitDistanceConstraint attribute), 507
 limitdistance_reset() (in module bpy.ops.constraint), 23
 LimitDistanceConstraint (class in bpy.types), 507
 LimitLocationConstraint (class in bpy.types), 508
 LimitRotationConstraint (class in bpy.types), 510
 limits (bpy.types.SimpleDeformModifier attribute), 805
 LimitScaleConstraint (class in bpy.types), 511
 lin_attenuation (bge.types.KX_LightObject attribute), 1156
 lin_error (bge.types.BL_ArmatureConstraint attribute), 1198
 line_break() (in module bpy.ops.font), 35
 line_break() (in module bpy.ops.text), 112
 line_count (bpy.types.MaterialHalo attribute), 528
 line_error (bpy.types.ThemeConsole attribute), 910
 line_info (bpy.types.ThemeConsole attribute), 910
 line_input (bpy.types.ThemeConsole attribute), 910
 line_length_head (bpy.types.ParticleSettings attribute), 663
 line_length_tail (bpy.types.ParticleSettings attribute), 663
 line_number() (in module bpy.ops.text), 112
 line_numbers_background (bpy.types.ThemeTextEditor attribute), 933
 line_output (bpy.types.ThemeConsole attribute), 910
 line_width (bpy.types.GPencilLayer attribute), 422
 linear_attenuation (bpy.types.PointLamp attribute), 691
 linear_attenuation (bpy.types.SpotLamp attribute), 857
 linear_drag (bpy.types.FieldSettings attribute), 406
 linear_stiffness (bpy.types.GameSoftBodySettings attribute), 433
 linear_velocity (bpy.types.EditObjectActuator attribute), 372
 linear_velocity (bpy.types.ObjectActuator attribute), 622
 linear_viscosity (bpy.types.SPHFluidSettings attribute), 741
 linearVelocity (bge.types.KX_SCA_AddObjectActuator attribute), 1172
 LINEFEEDKEY (in module bge.events), 1226
 link (bpy.types.MaterialSlot attribute), 534
 link() (bpy.types.Actuator method), 155
 link() (bpy.types.Controller method), 337
 link() (bpy.types.GroupObjects method), 442
 link() (bpy.types.SceneObjects method), 753
 link() (bpy.types.Sensor method), 767
 link() (in module bpy.ops.node), 69
 link_append() (in module bpy.ops.wm), 141
 link_make() (in module bpy.ops.node), 69
 link_viewer() (in module bpy.ops.node), 69
 links_cut() (in module bpy.ops.logic), 50

links_cut() (in module bpy.ops.node), 69
linV (bge.types.KX_ObjectActuator attribute), 1161
linVelocityMax (bge.types.KX_GameObject attribute), 1144
linVelocityMin (bge.types.KX_GameObject attribute), 1144
list (bpy.types.ThemeDopeSheet attribute), 912
list (bpy.types.ThemeFileBrowser attribute), 914
list (bpy.types.ThemeGraphEditor attribute), 917
list (bpy.types.ThemeNLAEditor attribute), 924
list (bpy.types.ThemeNodeEditor attribute), 926
list (in module bgl), 1117
list_text (bpy.types.ThemeDopeSheet attribute), 912
list_text (bpy.types.ThemeFileBrowser attribute), 914
list_text (bpy.types.ThemeGraphEditor attribute), 918
list_text (bpy.types.ThemeNLAEditor attribute), 924
list_text (bpy.types.ThemeNodeEditor attribute), 926
list_text_hi (bpy.types.ThemeDopeSheet attribute), 912
list_text_hi (bpy.types.ThemeFileBrowser attribute), 914
list_text_hi (bpy.types.ThemeGraphEditor attribute), 918
list_text_hi (bpy.types.ThemeNLAEditor attribute), 924
list_text_hi (bpy.types.ThemeNodeEditor attribute), 926
list_title (bpy.types.ThemeDopeSheet attribute), 912
list_title (bpy.types.ThemeFileBrowser attribute), 914
list_title (bpy.types.ThemeGraphEditor attribute), 918
list_title (bpy.types.ThemeNLAEditor attribute), 924
list_title (bpy.types.ThemeNodeEditor attribute), 926
listener_location (aud.Device attribute), 1122
listener_orientation (aud.Device attribute), 1122
listener_velocity (aud.Device attribute), 1122
LKEY (in module bge.events), 1223
load() (bpy.typesBlendDataFonts method), 196
load() (bpy.typesBlendDataImages method), 199
load() (bpy.typesBlendDataLibraries method), 202
load() (bpy.typesBlendDataTexts method), 212
load() (in module blf), 1119
load_from_file() (bpy.types.RenderLayer method), 725
load_from_file() (bpy.types.RenderResult method), 728
load_image() (in module bpy_extras.image_utils), 1130
load_scripts() (in module bpy.utils), 1044
loadGlobalDict() (in module bge.logic), 1207
loc (bpy.types.OperatorMousePath attribute), 636
loc_clear() (in module bpy.ops.pose), 94
localAngularVelocity (bge.types.KX_GameObject attribute), 1146
localInertia (bge.types.KX_GameObject attribute), 1145
localLinearVelocity (bge.types.KX_GameObject attribute), 1146
localOrientation (bge.types.KX_GameObject attribute), 1145
localPosition (bge.types.KX_GameObject attribute), 1146
localScale (bge.types.KX_GameObject attribute), 1145
localview() (in module bpy.ops.view3d), 133
location (aud.Handle attribute), 1128
location (bge.types.BL_ArmatureChannel attribute), 1200
location (bpy.types.Node attribute), 602
location (bpy.types.Object attribute), 613
location (bpy.types.OperatorStrokeElement attribute), 637
location (bpy.types.Particle attribute), 647
location (bpy.types.ParticleKey attribute), 656
location (bpy.types.PoseBone attribute), 697
location (bpy.types.ShaderNodeMapping attribute), 782
location (bpy.types.TexMapping attribute), 872
location_3d_to_region_2d() (in module bpy_extras.view3d_utils), 1132
location_clear() (in module bpy.ops.object), 76
location_iterations (bpy.types.GameSoftBodySettings attribute), 433
location_mass_center (bpy.types.SoftBodySettings attribute), 814
lock (bpy.types.ActionGroup attribute), 152
lock (bpy.types.EditBone attribute), 369
lock (bpy.types.FCurve attribute), 389
lock (bpy.types.GPencilLayer attribute), 422
lock (bpy.types.NlaTrack attribute), 600
lock (bpy.types.Sequence attribute), 769
lock() (in module bpy.ops.sequencer), 104
lock_axis (bpy.types.LockedTrackConstraint attribute), 513
lock_billboard (bpy.types.ParticleSettings attribute), 663
lock_boids_to_surface (bpy.types.ParticleSettings attribute), 663
lock_bone (bpy.types.SpaceView3D attribute), 846
lock_bounds (bpy.types.SpaceUVEditor attribute), 843
lock_camera (bpy.types.SpaceView3D attribute), 846
lock_camera_and_layers (bpy.types.SpaceView3D attribute), 846
lock_cursor (bpy.types.SpaceView3D attribute), 846
lock_frame (bpy.types.GPencilLayer attribute), 422
lock_ik_x (bpy.types.PoseBone attribute), 697
lock_ik_y (bpy.types.PoseBone attribute), 697
lock_ik_z (bpy.types.PoseBone attribute), 697
lock_location (bpy.types.Object attribute), 614
lock_location (bpy.types.PoseBone attribute), 697
lock_location_x (bpy.types.GameObjectSettings attribute), 429
lock_location_x (bpy.types.KinematicConstraint attribute), 494
lock_location_y (bpy.types.GameObjectSettings attribute), 429
lock_location_y (bpy.types.KinematicConstraint attribute), 494
lock_location_z (bpy.types.GameObjectSettings attribute), 429

lock_location_z (bpy.types.KinematicConstraint attribute), 494	at-	MagicTexture.users_object_modifier (in module bpy.types), 516
lock_object (bpy.types.SpaceView3D attribute), 846		magnetic (bpy.types.EffectorWeights attribute), 377
lock_rotation (bpy.types.Object attribute), 614		magnitude (mathutils.Quaternion attribute), 1063
lock_rotation (bpy.types.PoseBone attribute), 697		magnitude (mathutils.Vector attribute), 1068
lock_rotation (bpy.types.RegionView3D attribute), 717		main_axis (bpy.types.ClampToConstraint attribute), 252
lock_rotation_w (bpy.types.Object attribute), 614		MaintainVolumeConstraint (class in bpy.types), 517
lock_rotation_w (bpy.types.PoseBone attribute), 697		make_compatible() (mathutils.Euler method), 1056
lock_rotation_x (bpy.types.GameObjectSettings attribute), 429	at-	make_dupli_face() (in module bpy.ops.object), 76
lock_rotation_x (bpy.types.KinematicConstraint attribute), 494	at-	make_internal() (in module bpy.ops.text), 112
lock_rotation_y (bpy.types.GameObjectSettings attribute), 429	at-	make_links_data() (in module bpy.ops.object), 76
lock_rotation_y (bpy.types.KinematicConstraint attribute), 494	at-	make_links_scene() (in module bpy.ops.marker), 51
lock_rotation_z (bpy.types.GameObjectSettings attribute), 429	at-	make_links_scene() (in module bpy.ops.object), 77
lock_rotation_z (bpy.types.KinematicConstraint attribute), 494	at-	make_local() (in module bpy.ops.object), 77
lock_rotations_4d (bpy.types.Object attribute), 614		make_paths_absolute() (in module bpy.ops.file), 33
lock_rotations_4d (bpy.types.PoseBone attribute), 697		make_paths_relative() (in module bpy.ops.file), 33
lock_scale (bpy.types.Object attribute), 614		make_regular() (in module bpy.ops.lattice), 49
lock_scale (bpy.types.PoseBone attribute), 697		make_segment() (in module bpy.ops.curve), 24
lock_x (bpy.types.Sculpt attribute), 764		make_single_user() (in module bpy.ops.object), 77
lock_x (bpy.types.SimpleDeformModifier attribute), 805		makeScreenshot() (in module bge.render), 1220
lock_y (bpy.types.Sculpt attribute), 764		manipulator() (in module bpy.ops.view3d), 133
lock_y (bpy.types.SimpleDeformModifier attribute), 805		manipulator_handle_size (bpy.types.UserPreferencesView attribute), 999
lock_z (bpy.types.Sculpt attribute), 764		manipulator_hotspot (bpy.types.UserPreferencesView attribute), 999
LockedTrackConstraint (class in bpy.types), 513		manipulator_size (bpy.types.UserPreferencesView attribute), 1000
log (bpy.types.KeyboardSensor attribute), 483		map_from (bpy.types.TransformConstraint attribute), 955
logic_bricks_copy() (in module bpy.ops.object), 76		map_mode (bpy.types.BrushTextureSlot attribute), 242
logic_step_max (bpy.types.SceneGameData attribute), 750		map_to (bpy.types.TransformConstraint attribute), 955
long_key (bpy.types.ThemeDopeSheet attribute), 912		map_to_x_from (bpy.types.TransformConstraint attribute), 955
long_key_selected (bpy.types.ThemeDopeSheet attribute), 912	at-	map_to_y_from (bpy.types.TransformConstraint attribute), 955
look_ahead (bpy.types.BoidRuleAvoidCollision attribute), 221	at-	map_to_z_from (bpy.types.TransformConstraint attribute), 955
loop_count (aud.Handle attribute), 1128		map_type (bpy.types.KeyMapItem attribute), 476
loop_multi_select() (in module bpy.ops.mesh), 56		mapping (bpy.types.CompositorNodePremulKey attribute), 308
loop_select() (in module bpy.ops.mesh), 56		mapping (bpy.types.EnvironmentMap attribute), 381
loop_to_region() (in module bpy.ops.mesh), 56		mapping (bpy.types.Image attribute), 453
loopcut() (in module bpy.ops.mesh), 56		mapping (bpy.types.MaterialTextureSlot attribute), 539
loopcut_slide() (in module bpy.ops.mesh), 56		mapping (bpy.types.ParticleSettingsTextureSlot attribute), 670
looping (bge.types.KX_SoundActuator attribute), 1176		mapping_x (bpy.types.MaterialTextureSlot attribute), 539
M		mapping_x (bpy.types.ParticleSettingsTextureSlot attribute), 670
Macro (class in bpy.types), 514		mapping_y (bpy.types.MaterialTextureSlot attribute), 539
Macro.name (in module bpy.types), 514		mapping_y (bpy.types.ParticleSettingsTextureSlot attribute), 670
Macro.properties (in module bpy.types), 514		mapping_z (bpy.types.MaterialTextureSlot attribute), 539
MagicTexture (class in bpy.types), 515		mapping_z (bpy.types.ParticleSettingsTextureSlot attribute), 670
MagicTexture.users_material (in module bpy.types), 516		

marble_type (bpy.types.MarbleTexture attribute), 518
MarbleTexture (class in bpy.types), 518
MarbleTexture.users_material (in module bpy.types), 518
MarbleTexture.users_object_modifier (in module bpy.types), 518
margin_column (bpy.types.SpaceTextEditor attribute), 840
mark_all() (in module bpy.ops.text), 112
mark_seam() (in module bpy.ops.mesh), 56
mark_sharp() (in module bpy.ops.mesh), 56
markers_clear() (in module bpy.ops.text), 112
markers_make_local() (in module bpy.ops.action), 11
mask (bge.types.KX_StateActuator attribute), 1177
MaskModifier (class in bpy.types), 519
mass (bge.types.KX_GameObject attribute), 1144
mass (bge.types.KX_SCA_DynamicActuator attribute), 1172
mass (bpy.types.ClothSettings attribute), 256
mass (bpy.types.EditObjectActuator attribute), 372
mass (bpy.types.GameObjectSettings attribute), 429
mass (bpy.types.ParticleSettings attribute), 663
mass (bpy.types.SoftBodySettings attribute), 814
material (bge.types.KX_PolygonMaterial attribute), 1167
material (bge.types.KX_PolyProxy attribute), 1163
material (bpy.types.CollisionSensor attribute), 261
material (bpy.types.ConstraintActuator attribute), 331
material (bpy.types.MaterialSlot attribute), 534
material (bpy.types.ParticleSettings attribute), 664
material (bpy.types.RaySensor attribute), 715
material (bpy.types.ShaderNodeExtendedMaterial attribute), 779
material (bpy.types.ShaderNodeMaterial attribute), 783
material (bpy.types.TouchSensor attribute), 952
Material (class in bpy.types), 520
material (in module bpy.context), 8
Material.animation_data (in module bpy.types), 521
Material.diffuse_ramp (in module bpy.types), 521
Material.halo (in module bpy.types), 522
Material.node_tree (in module bpy.types), 522
Material.physics (in module bpy.types), 522
Material.raytrace_mirror (in module bpy.types), 523
Material.raytrace_transparency (in module bpy.types), 523
Material.specular_ramp (in module bpy.types), 524
Material.strand (in module bpy.types), 524
Material.subsurface_scattering (in module bpy.types), 524
Material.texture_slots (in module bpy.types), 524
Material.volume (in module bpy.types), 526
material_index (bpy.types.MeshFace attribute), 559
material_index (bpy.types.Spline attribute), 851
material_link (bpy.types.UserPreferencesEdit attribute), 989
material_mode (bpy.types.SceneGameData attribute), 750
material_offset (bpy.types.SolidifyModifier attribute), 817
material_offset_rim (bpy.types.SolidifyModifier attribute), 817
material_override (bpy.types.SceneRenderLayer attribute), 755
material_slot (in module bpy.context), 8
material_slot_add() (in module bpy.ops.object), 77
material_slot_assign() (in module bpy.ops.object), 77
material_slot_copy() (in module bpy.ops.object), 77
material_slot_deselect() (in module bpy.ops.object), 77
material_slot_remove() (in module bpy.ops.object), 77
material_slot_select() (in module bpy.ops.object), 77
MaterialHalo (class in bpy.types), 528
MaterialPhysics (class in bpy.types), 530
MaterialRaytraceMirror (class in bpy.types), 531
MaterialRaytraceTransparency (class in bpy.types), 533
materials (bge.types.KX_MeshProxy attribute), 1157
MaterialSlot (class in bpy.types), 534
MaterialSlot.name (in module bpy.types), 534
MaterialStrand (class in bpy.types), 535
MaterialStrand.use_surface_diffuse (in module bpy.types), 535
MaterialSubsurfaceScattering (class in bpy.types), 536
MaterialTextureSlot (class in bpy.types), 538
MaterialTextureSlots (class in bpy.types), 543
MaterialVolume (class in bpy.types), 544
mathutils (module), 1055
mathutils.geometry (module), 1084
matid (bge.types.KX_PolyProxy attribute), 1163
matname (bge.types.KX_PolyProxy attribute), 1163
matrix (bpy.types.Bone attribute), 229
matrix (bpy.types.DupliObject attribute), 366
matrix (bpy.types.TransformOrientation attribute), 957
Matrix (class in mathutils), 1057
Matrix.lerp() (in module mathutils), 1059
matrix_basis (bpy.types.Object attribute), 614
matrix_basis (bpy.types.PoseBone attribute), 697
matrix_local (bpy.types.Bone attribute), 229
matrix_local (bpy.types.Object attribute), 614
matrix_original (bpy.types.DupliObject attribute), 366
matrix_world (bpy.types.Object attribute), 614
matte_channel (bpy.types.CompositorNodeChannelMatte attribute), 274
max (bge.types.KX_CameraActuator attribute), 1142
max (bge.types.KX_ConstraintActuator attribute), 1143
max (bge.types.SCA_PropertySensor attribute), 1187
max (bpy.types.ActionConstraint attribute), 150
max (bpy.types.CameraActuator attribute), 246
max (bpy.types.CompositorNodeMapValue attribute), 303

max (bpy.types.FModifierEnvelopeControlPoint attribute), 398
 max (bpy.types.ShaderNodeMapping attribute), 782
 max (bpy.types.TexMapping attribute), 872
 max_x (bpy.types.CompositorNodeCrop attribute), 283
 max_x (bpy.types.FModifierLimits attribute), 401
 max_x (bpy.types.LimitLocationConstraint attribute), 508
 max_x (bpy.types.LimitRotationConstraint attribute), 510
 max_x (bpy.types.LimitScaleConstraint attribute), 511
 max_x (bpy.types.SequenceCrop attribute), 772
 max_y (bpy.types.CompositorNodeCrop attribute), 283
 max_y (bpy.types.FModifierLimits attribute), 401
 max_y (bpy.types.LimitLocationConstraint attribute), 508
 max_y (bpy.types.LimitRotationConstraint attribute), 510
 max_y (bpy.types.LimitScaleConstraint attribute), 511
 max_y (bpy.types.SequenceCrop attribute), 772
 max_z (bpy.types.LimitLocationConstraint attribute), 508
 max_z (bpy.types.LimitRotationConstraint attribute), 510
 max_z (bpy.types.LimitScaleConstraint attribute), 511
 median_scale (mathutils.Matrix attribute), 1061
 memory_cache_limit (bpy.types.UserPreferencesSystem attribute), 997
 memory_statistics() (in module bpy.ops.wm), 142
 Menu (class in bpy.types), 547
 menu() (bpy.typesUILayout method), 976
 Menu.layout (in module bpy.types), 548
 merge() (in module bpy.ops.armature), 18
 merge() (in module bpy.ops.mesh), 56
 merge_threshold (bpy.types.ArrayModifier attribute), 183
 merge_threshold (bpy.types.MirrorModifier attribute), 580
 mesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1173
 mesh (bpy.types.EditObjectActuator attribute), 372
 Mesh (class in bpy.types), 549
 mesh (in module bpy.context), 7
 Mesh.animation_data (in module bpy.types), 549
 Mesh.edge_keys (in module bpy.types), 552
 Mesh.edges (in module bpy.types), 549
 Mesh.faces (in module bpy.types), 549
 Mesh.layers_float (in module bpy.types), 549
 Mesh.layers_int (in module bpy.types), 549
 Mesh.layers_string (in module bpy.types), 549
 Mesh.materials (in module bpy.types), 549
 Mesh.shape_keys (in module bpy.types), 549
 Mesh.sticky (in module bpy.types), 550
 Mesh.total_edge_sel (in module bpy.types), 551
 Mesh.total_face_sel (in module bpy.types), 551
 Mesh.total_vert_sel (in module bpy.types), 551
 Mesh.uv_textures (in module bpy.types), 552
 Mesh.vertex_colors (in module bpy.types), 552
 Mesh.vertices (in module bpy.types), 552
 at-
 mesh_linked_faces() (in module bpy_extras.mesh_utils), 1131
 mesh_select_mode (bpy.types.ToolSettings attribute), 949
 MeshColor (class in bpy.types), 553
 MeshColorLayer (class in bpy.types), 554
 MeshColorLayer.data (in module bpy.types), 554
 meshdeform_bind() (in module bpy.ops.object), 77
 MeshDeformModifier (class in bpy.types), 555
 MeshDeformModifier.is_bound (in module bpy.types), 555
 MeshEdge (class in bpy.types), 556
 MeshEdge.index (in module bpy.types), 557
 MeshEdge.key (in module bpy.types), 557
 MeshEdges (class in bpy.types), 558
 meshes (bge.types.KX_GameObject attribute), 1146
 MeshFace (class in bpy.types), 559
 MeshFace.area (in module bpy.types), 559
 MeshFace.center (in module bpy.types), 559
 MeshFace.edge_keys (in module bpy.types), 559
 MeshFace.index (in module bpy.types), 559
 MeshFace.normal (in module bpy.types), 559
 MeshFaces (class in bpy.types), 560
 MeshFaces.active_tface (in module bpy.types), 560
 MeshFloatProperty (class in bpy.types), 561
 MeshFloatPropertyLayer (class in bpy.types), 562
 MeshFloatPropertyLayer.data (in module bpy.types), 562
 MeshIntProperty (class in bpy.types), 562
 MeshIntPropertyLayer (class in bpy.types), 563
 MeshIntPropertyLayer.data (in module bpy.types), 563
 MeshSticky (class in bpy.types), 564
 MeshStringProperty (class in bpy.types), 565
 MeshStringPropertyLayer (class in bpy.types), 565
 MeshStringPropertyLayer.data (in module bpy.types), 565
 MeshTextureFace (class in bpy.types), 566
 MeshTextureFaceLayer (class in bpy.types), 568
 MeshTextureFaceLayer.data (in module bpy.types), 569
 MeshVertex (class in bpy.types), 569
 MeshVertex.groups (in module bpy.types), 570
 MeshVertex.index (in module bpy.types), 570
 MeshVertices (class in bpy.types), 571
 MessageActuator (class in bpy.types), 571
 MessageSensor (class in bpy.types), 572
 meta_add() (in module bpy.ops.nla), 66
 meta_ball (in module bpy.context), 8
 meta_make() (in module bpy.ops.sequencer), 104
 meta_remove() (in module bpy.ops.nla), 66
 meta_separate() (in module bpy.ops.sequencer), 104
 meta_strip (bpy.types.ThemeSequenceEditor attribute), 931
 meta_toggle() (in module bpy.ops.sequencer), 104
 MetaBall (class in bpy.types), 573
 MetaBall.animation_data (in module bpy.types), 573

MetaBall.elements (in module bpy.types), 573
MetaBall.materials (in module bpy.types), 574
metaball_add() (in module bpy.ops.object), 77
MetaBallElements (class in bpy.types), 575
MetaBallElements.active (in module bpy.types), 575
MetaElement (class in bpy.types), 576
MetaSequence (class in bpy.types), 577
MetaSequence.color_balance (in module bpy.types), 578
MetaSequence.crop (in module bpy.types), 578
MetaSequence.proxy (in module bpy.types), 578
MetaSequence.sequences (in module bpy.types), 578
MetaSequence.transform (in module bpy.types), 578
mid_level (bpy.types.DisplaceModifier attribute), 355
MIDDLEMOUSE (in module bge.events), 1223
min (bge.types.KX_CameraActuator attribute), 1142
min (bge.types.KX_ConstraintActuator attribute), 1143
min (bge.types.SCA_PropertySensor attribute), 1187
min (bpy.types.ActionConstraint attribute), 150
min (bpy.types.CameraActuator attribute), 246
min (bpy.types.CompositorNodeMapView attribute), 303
min (bpy.types.FModifierEnvelopeControlPoint attribute), 398
min (bpy.types.ShaderNodeMapping attribute), 782
min (bpy.types.TexMapping attribute), 872
min_x (bpy.types.CompositorNodeCrop attribute), 283
min_x (bpy.types.FModifierLimits attribute), 401
min_x (bpy.types.LimitLocationConstraint attribute), 508
min_x (bpy.types.LimitRotationConstraint attribute), 510
min_x (bpy.types.LimitScaleConstraint attribute), 511
min_x (bpy.types.SequenceCrop attribute), 772
min_y (bpy.types.CompositorNodeCrop attribute), 283
min_y (bpy.types.FModifierLimits attribute), 401
min_y (bpy.types.LimitLocationConstraint attribute), 508
min_y (bpy.types.LimitRotationConstraint attribute), 510
min_y (bpy.types.LimitScaleConstraint attribute), 511
min_y (bpy.types.SequenceCrop attribute), 772
min_z (bpy.types.LimitLocationConstraint attribute), 508
min_z (bpy.types.LimitRotationConstraint attribute), 510
min_z (bpy.types.LimitScaleConstraint attribute), 512
mini_axis_brightness (bpy.types.UserPreferencesView attribute), 1000
mini_axis_size (bpy.types.UserPreferencesView attribute), 1000
minimize_stretch() (in module bpy.ops.uv), 127
minkovsky_exponent (bpy.types.VoronoiTexture attribute), 1012
MINUSKEY (in module bge.events), 1226
mirror() (in module bpy.ops.action), 12
mirror() (in module bpy.ops.graph), 39
mirror() (in module bpy.ops.particle), 91
mirror() (in module bpy.ops.transform), 117
mirror_color (bpy.types.Material attribute), 522
mirror_factor (bpy.types.MaterialTextureSlot attribute), 539
mirror_object (bpy.types.MirrorModifier attribute), 580
MirrorModifier (class in bpy.types), 580
mix (bpy.types.CompositorNodeGlare attribute), 294
MKEY (in module bge.events), 1224
modal() (bpy.types.Operator method), 634
modal_handler_add() (bpy.types.WindowManager class method), 1022
mode (bge.types.BL_ActionActuator attribute), 1136
mode (bge.types.BL_ShapeActionActuator attribute), 1141
mode (bge.types.KX_GameActuator attribute), 1144
mode (bge.types.KX_IpoActuator attribute), 1155
mode (bge.types.KX_ParentActuator attribute), 1162
mode (bge.types.KX_SCA_DynamicActuator attribute), 1172
mode (bge.types.KX_SceneActuator attribute), 1176
mode (bge.types.KX_SoundActuator attribute), 1177
mode (bge.types.SCA_2DFilterActuator attribute), 1183
mode (bge.types.SCA_MouseSensor attribute), 1158
mode (bge.types.SCA_PropertyActuator attribute), 1187
mode (bge.types.SCA_PropertySensor attribute), 1187
mode (bge.types.SCA_PythonController attribute), 1188
mode (bpy.types.ArmatureActuator attribute), 177
mode (bpy.types.CompositorNodeCombYCCA attribute), 281
mode (bpy.types.CompositorNodeSepYCCA attribute), 314
mode (bpy.types.ConstraintActuator attribute), 331
mode (bpy.types.EditObjectActuator attribute), 372
mode (bpy.types.Filter2DActuator attribute), 411
mode (bpy.types.FModifierGenerator attribute), 400
mode (bpy.types.GameActuator attribute), 425
mode (bpy.types.Histogram attribute), 446
mode (bpy.types.Itasc attribute), 467
mode (bpy.types.MaskModifier attribute), 520
mode (bpy.types.ObjectActuator attribute), 622
mode (bpy.types.ParentActuator attribute), 646
mode (bpy.types.PropertyActuator attribute), 703
mode (bpy.types.PythonController attribute), 709
mode (bpy.types.SceneActuator attribute), 747
mode (bpy.types.ShapeActionActuator attribute), 797
mode (bpy.types.SoundActuator attribute), 820
mode (bpy.types.SpaceDopeSheetEditor attribute), 825
mode (bpy.types.SpaceGraphEditor attribute), 827
mode_after (bpy.types.FModifierCycles attribute), 396
mode_before (bpy.types.FModifierCycles attribute), 396
mode_set() (in module bpy.ops.object), 78
MODELMATRIX (in module bge.logic), 1218
MODELMATRIX_INVERSE (in module bge.logic), 1218
MODELMATRIX_INVERSETRANSPOSE (in module bge.logic), 1218
MODELMATRIX_TRANSPOSE (in module bge.logic), 1218

modelview_matrix (bge.types.KX_Camera attribute), 1191
MODELVIEWMATRIX (in module bge.logic), 1218
MODELVIEWMATRIX_INVERSE (in module bge.logic), 1218
MODELVIEWMATRIX_INVERSETRANSPOSE (in module bge.logic), 1218
MODELVIEWMATRIX_TRANSPOSE (in module bge.logic), 1218
Modifier (class in bpy.types), 582
Modifier.type (in module bpy.types), 582
modifier_add() (in module bpy.ops.object), 78
modifier_apply() (in module bpy.ops.object), 78
modifier_convert() (in module bpy.ops.object), 78
modifier_copy() (in module bpy.ops.object), 78
modifier_key_1 (bpy.types.KeyboardSensor attribute), 483
modifier_key_2 (bpy.types.KeyboardSensor attribute), 484
modifier_move_down() (in module bpy.ops.object), 78
modifier_move_up() (in module bpy.ops.object), 78
modifier_remove() (in module bpy.ops.object), 78
module (bpy.types.Addon attribute), 157
module (bpy.types.PythonController attribute), 709
module_names() (in module bpy.path), 1046
modules_from_path() (in module bpy.utils), 1044
motion_blur_factor (bpy.types.Filter2DActuator attribute), 411
motion_blur_samples (bpy.types.RenderSettings attribute), 731
motion_blur_shutter (bpy.types.RenderSettings attribute), 731
MotionPath (class in bpy.types), 583
MotionPath.frame_end (in module bpy.types), 583
MotionPath.frame_start (in module bpy.types), 583
MotionPath.length (in module bpy.types), 583
MotionPath.points (in module bpy.types), 584
MotionPath.use_bone_head (in module bpy.types), 584
MotionPathVert (class in bpy.types), 584
mouse (bpy.types.OperatorStrokeElement attribute), 637
mouse (in module bge.logic), 1207
mouse_double_click_time (bpy.types.UserPreferencesInput attribute), 994
mouse_event (bpy.types.MouseSensor attribute), 585
MouseSensor (class in bpy.types), 585
MOUSEX (in module bge.events), 1223
MOUSEY (in module bge.events), 1223
move() (in module bpy.ops.console), 22
move() (in module bpy.ops.font), 35
move() (in module bpy.ops.marker), 51
move() (in module bpy.ops.text), 112
move() (in module bpy.ops.view3d), 133
move_down() (in module bpy.ops.constraint), 23
move_select() (in module bpy.ops.nla), 66
move_select() (in module bpy.ops.font), 36
move_to_layer() (in module bpy.ops.object), 79
move_up() (in module bpy.ops.constraint), 23
move_up() (in module bpy.ops.nla), 66
movie_strip (bpy.types.ThemeSequenceEditor attribute), 931
movie_strip_add() (in module bpy.ops.sequencer), 104
MovieSequence (class in bpy.types), 586
MovieSequence.color_balance (in module bpy.types), 586
MovieSequence.crop (in module bpy.types), 586
MovieSequence.elements (in module bpy.types), 586
MovieSequence.proxy (in module bpy.types), 587
MovieSequence.transform (in module bpy.types), 587
mpeg_preseek (bpy.types.MovieSequence attribute), 587
ms_diffusion (bpy.types.MaterialVolume attribute), 544
ms_intensity (bpy.types.MaterialVolume attribute), 545
ms_spread (bpy.types.MaterialVolume attribute), 545
multicam_source (bpy.types.MulticamSequence attribute), 589
MulticamSequence (class in bpy.types), 589
MulticamSequence.color_balance (in module bpy.types), 589
MulticamSequence.crop (in module bpy.types), 589
MulticamSequence.proxy (in module bpy.types), 589
MulticamSequence.transform (in module bpy.types), 589
multiply_speed (bpy.types.SpeedControlSequence attribute), 849
multires_base_apply() (in module bpy.ops.object), 79
multires_external_pack() (in module bpy.ops.object), 79
multires_external_save() (in module bpy.ops.object), 79
multires_higher_levels_delete() (in module bpy.ops.object), 79
multires_reshape() (in module bpy.ops.object), 79
multires_subdivide() (in module bpy.ops.object), 80
MultiresModifier (class in bpy.types), 591
MultiresModifier.is_external (in module bpy.types), 592
MultiresModifier.total_levels (in module bpy.types), 592
musgrave_type (bpy.types.MusgraveTexture attribute), 593
MusgraveTexture (class in bpy.types), 593
MusgraveTexture.users_material (in module bpy.types), 594
MusgraveTexture.users_object_modifier (in module bpy.types), 594
mute (bpy.types.Constraint attribute), 328
mute (bpy.types.FCurve attribute), 389
mute (bpy.types.FModifier attribute), 395
mute (bpy.types.NlaStrip attribute), 597
mute (bpy.types.NlaTrack attribute), 600
mute (bpy.types.Sequence attribute), 769
mute (bpy.types.ShapeKey attribute), 798

mute() (in module bpy.ops.sequencer), 104
mute_toggle() (in module bpy.ops.nla), 66
mute_toggle() (in module bpy.ops.node), 69

N

nabla (bpy.types.CloudsTexture attribute), 258
nabla (bpy.types.DistortedNoiseTexture attribute), 356
nabla (bpy.types.MarbleTexture attribute), 518
nabla (bpy.types.MusgraveTexture attribute), 593
nabla (bpy.types.VoronoiTexture attribute), 1012
nabla (bpy.types.WoodTexture attribute), 1026
name (bge.types.BL_ArmatureBone attribute), 1203
name (bge.types.BL_ArmatureChannel attribute), 1199
name (bge.types.BL_ArmatureConstraint attribute), 1198
name (bge.types.CValue attribute), 1133
name (bge.types.KX_GameObject attribute), 1144
name (bge.types.KX_Scene attribute), 1174
name (bge.types.SCAILogicBrick attribute), 1133
name (bpy.types.ActionGroup attribute), 152
name (bpy.types.Actuator attribute), 155
name (bpy.types.BoidRule attribute), 218
name (bpy.types.BoidState attribute), 227
name (bpy.types.Bone attribute), 229
name (bpy.types.BoneGroup attribute), 232
name (bpy.types.Constraint attribute), 328
name (bpy.types.Controller attribute), 336
name (bpy.types.DriverVariable attribute), 365
name (bpy.types.EditBone attribute), 369
name (bpy.types.GameProperty attribute), 432
name (bpy.types.ID attribute), 448
name (bpy.types.KeyConfig attribute), 471
name (bpy.types.KeyingSet attribute), 487
name (bpy.types.MeshColorLayer attribute), 554
name (bpy.types.MeshFloatPropertyLayer attribute), 562
name (bpy.types.MeshIntPropertyLayer attribute), 563
name (bpy.types.MeshStringPropertyLayer attribute), 565
name (bpy.types.MeshTextureFaceLayer attribute), 569
name (bpy.types.Modifier attribute), 582
name (bpy.types.NlaStrip attribute), 597
name (bpy.types.NlaTrack attribute), 600
name (bpy.types.Node attribute), 603
name (bpy.types.NodeSocket attribute), 606
name (bpy.types.OperatorFileListElement attribute), 635
name (bpy.types.ParticleSystem attribute), 676
name (bpy.types.PointCache attribute), 686
name (bpy.types.PoseBone attribute), 698
name (bpy.types.PropertyGroup attribute), 705
name (bpy.types.SceneRenderLayer attribute), 755
name (bpy.types.Sensor attribute), 766
name (bpy.types.Sequence attribute), 769
name (bpy.types.ShapeKey attribute), 798
name (bpy.types.Theme attribute), 905
name (bpy.types.TimelineMarker attribute), 945
name (bpy.types.TransformOrientation attribute), 957

name (bpy.types.VertexGroup attribute), 1007
NandController (class in bpy.types), 595
narrowness (bpy.types.WaveModifier attribute), 1019
ndof_pan_speed (bpy.types.UserPreferencesInput attribute), 994
ndof_rotate_speed (bpy.types.UserPreferencesInput attribute), 994
near (bge.types.KX_Camera attribute), 1190
NearSensor (class in bpy.types), 595
negate() (mathutils.Vector method), 1066
new() (bpy.types.ActionFCurves method), 151
new() (bpy.types.ActionGroups method), 153
new() (bpy.types.ActionPoseMarkers method), 154
new() (bpy.types.Addons class method), 158
new() (bpy.types.ArmatureEditBones method), 179
new() (bpy.types.BlendDataActions method), 191
new() (bpy.types.BlendDataArmatures method), 192
new() (bpy.types.BlendDataBrushes method), 193
new() (bpy.types.BlendDataCameras method), 194
new() (bpy.types.BlendDataCurves method), 195
new() (bpy.types.BlendDataGroups method), 198
new() (bpy.types.BlendDataImages method), 199
new() (bpy.types.BlendDataLamps method), 200
new() (bpy.types.BlendDataLattices method), 201
new() (bpy.types.BlendDataMaterials method), 204
new() (bpy.types.BlendDataMeshes method), 205
new() (bpy.types.BlendDataMetaBalls method), 206
new() (bpy.types.BlendDataNodeTrees method), 207
new() (bpy.types.BlendDataObjects method), 208
new() (bpy.types.BlendDataParticles method), 209
new() (bpy.types.BlendDataScenes method), 210
new() (bpy.types.BlendDataTexts method), 212
new() (bpy.types.BlendDataTextures method), 213
new() (bpy.types.BlendDataWorlds method), 215
new() (bpy.types.ChannelDriverVariables method), 249
new() (bpy.types.ColorRampElements method), 266
new() (bpy.types.CompositorNodes method), 326
new() (bpy.types.CurveSplines method), 351
new() (bpy.types.FCurveModifiers method), 393
new() (bpy.types.GroupInputs method), 441
new() (bpy.types.GroupOutputs method), 443
new() (bpy.types.KeyConfigurations method), 472
new() (bpy.types.KeyingSets method), 492
new() (bpy.types.KeyMapItems method), 478
new() (bpy.types.KeyMaps method), 481
new() (bpy.types.MetaBallElements method), 575
new() (bpy.types.NlaStrips method), 599
new() (bpy.types.NlaTracks method), 601
new() (bpy.types.NodeLinks method), 605
new() (bpy.types.ObjectConstraints method), 625
new() (bpy.types.ObjectModifiers method), 626
new() (bpy.types.PoseBoneConstraints method), 700
new() (bpy.types.ShaderNodes method), 796
new() (bpy.types.TextureNodes method), 902

new() (bpy.types.TimelineMarkers method), 946
new() (bpy.types.UVTextures method), 984
new() (bpy.types.VertexColors method), 1006
new() (bpy.types.VertexGroups method), 1009
new() (in module bpy.ops.action), 12
new() (in module bpy.ops.image), 42
new() (in module bpy.ops.material), 52
new() (in module bpy.ops.particle), 91
new() (in module bpy.ops.poselib), 96
new() (in module bpy.ops.scene), 97
new() (in module bpy.ops.screen), 99
new() (in module bpy.ops.text), 113
new() (in module bpy.ops.texture), 116
new() (in module bpy.ops.world), 146
new_modal() (bpy.types.KeyMapItems method), 479
new_target() (in module bpy.ops.particle), 91
next() (in module bpy.ops.file), 33
next_edit() (in module bpy.ops.sequencer), 104
next_marker() (in module bpy.ops.text), 113
ngon_tesselate() (in module bpy_extras.mesh_utils), 1132
NINEKEY (in module bge.events), 1224
NKEY (in module bge.events), 1224
NlaStrip (class in bpy.types), 596
NlaStrip.active (in module bpy.types), 597
NlaStrip.fcurves (in module bpy.types), 597
NlaStrip.modifiers (in module bpy.types), 597
NlaStrip.strips (in module bpy.types), 598
NlaStrip.type (in module bpy.types), 598
NlaStrips (class in bpy.types), 599
NlaTrack (class in bpy.types), 600
NlaTrack.active (in module bpy.types), 600
NlaTrack.is_solo (in module bpy.types), 600
NlaTrack.strips (in module bpy.types), 601
NlaTracks (class in bpy.types), 601
Node (class in bpy.types), 602
Node.inputs (in module bpy.types), 602
Node.outputs (in module bpy.types), 603
node_backdrop (bpy.types.ThemeNodeEditor attribute), 926
node_output (bpy.types.CompositorNodeTexture attribute), 317
node_output (bpy.types.ShaderNodeTexture attribute), 791
node_output (bpy.types.TextureNodeTexture attribute), 898
node_tree (bpy.types.NodeGroup attribute), 604
NodeGroup (class in bpy.types), 603
NodeLink (class in bpy.types), 604
NodeLink.from_node (in module bpy.types), 604
NodeLink.from_socket (in module bpy.types), 604
NodeLink.to_node (in module bpy.types), 604
NodeLink.to_socket (in module bpy.types), 604
NodeLinks (class in bpy.types), 605
NodeSocket (class in bpy.types), 606
NodeSocket.type (in module bpy.types), 606
NodeTree (class in bpy.types), 607
NodeTree.animation_data (in module bpy.types), 607
NodeTree.inputs (in module bpy.types), 607
NodeTree.links (in module bpy.types), 608
NodeTree.outputs (in module bpy.types), 608
NodeTree.type (in module bpy.types), 608
noise (bpy.types.FieldSettings attribute), 406
noise() (in module bpy.ops.mesh), 56
noise_basis (bpy.types.CloudsTexture attribute), 258
noise_basis (bpy.types.DistortedNoiseTexture attribute), 356
noise_basis (bpy.types.MarbleTexture attribute), 518
noise_basis (bpy.types.MusgraveTexture attribute), 593
noise_basis (bpy.types.PointDensity attribute), 688
noise_basis (bpy.types.StucciTexture attribute), 865
noise_basis (bpy.types.WoodTexture attribute), 1026
noise_basis_2 (bpy.types.MarbleTexture attribute), 518
noise_basis_2 (bpy.types.WoodTexture attribute), 1026
noise_depth (bpy.types.CloudsTexture attribute), 258
noise_depth (bpy.types.MagicTexture attribute), 515
noise_depth (bpy.types.MarbleTexture attribute), 518
noise_distortion (bpy.types.DistortedNoiseTexture attribute), 356
noise_intensity (bpy.types.MusgraveTexture attribute), 593
noise_intensity (bpy.types.VoronoiTexture attribute), 1012
noise_scale (bpy.types.CloudsTexture attribute), 258
noise_scale (bpy.types.DistortedNoiseTexture attribute), 356
noise_scale (bpy.types.MarbleTexture attribute), 518
noise_scale (bpy.types.MusgraveTexture attribute), 593
noise_scale (bpy.types.StucciTexture attribute), 865
noise_scale (bpy.types.VoronoiTexture attribute), 1012
noise_scale (bpy.types.WoodTexture attribute), 1027
noise_type (bpy.types.CloudsTexture attribute), 258
noise_type (bpy.types.MarbleTexture attribute), 518
noise_type (bpy.types.SmokeDomainSettings attribute), 807
noise_type (bpy.types.StucciTexture attribute), 865
noise_type (bpy.types.WoodTexture attribute), 1027
NoiseTexture (class in bpy.types), 609
NoiseTexture.users_material (in module bpy.types), 609
NoiseTexture.users_object_modifier (in module bpy.types), 609
NorController (class in bpy.types), 610
normal (bge.types.KX_VertexProxy attribute), 1180
normal (bpy.types.MeshVertex attribute), 570
normal (bpy.types.ThemeBoneColorSet attribute), 908
normal (bpy.types.ThemeView3D attribute), 941
normal() (in module mathutils.geometry), 1088
normal_angle (bpy.types.ImagePaint attribute), 456

normal_factor (bpy.types.MaterialTextureSlot attribute), 539
normal_factor (bpy.types.ParticleSettings attribute), 664
normal_map_space (bpy.types.MaterialTextureSlot attribute), 539
normal_size (bpy.types.ToolSettings attribute), 949
normal_weight (bpy.types.Brush attribute), 237
normalize() (mathutils.Vector method), 1066
normalized() (mathutils.Vector method), 1066
normals_make_consistent() (in module bpy.ops.mesh), 56
numAxis (bge.types.SCA_JoystickSensor attribute), 1185
numButtons (bge.types.SCA_JoystickSensor attribute), 1185
numHats (bge.types.SCA_JoystickSensor attribute), 1185
numMaterials (bge.types.KX_MeshProxy attribute), 1157
numPolygons (bge.types.KX_MeshProxy attribute), 1157
nurb_sel_uiline (bpy.types.ThemeView3D attribute), 941
nurb_sel_vline (bpy.types.ThemeView3D attribute), 941
nurb_uiline (bpy.types.ThemeView3D attribute), 941
nurb_vline (bpy.types.ThemeView3D attribute), 941

O

obj() (in module bpy.ops.export_scene), 30
obj() (in module bpy.ops.import_scene), 47
object (bge.types.KX_CameraActuator attribute), 1142
object (bge.types.KX_ParentActuator attribute), 1162
object (bge.types.KX_SCA_AddObjectActuator attribute), 1171
object (bge.types.KX_TrackToActuator attribute), 1177
object (bpy.types.ArmatureModifier attribute), 180
object (bpy.types.BoidRuleAvoid attribute), 220
object (bpy.types.BoidRuleFollowLeader attribute), 223
object (bpy.types.BoidRuleGoal attribute), 224
object (bpy.types.BooleanModifier attribute), 234
object (bpy.types.CameraActuator attribute), 246
object (bpy.types.CastModifier attribute), 247
object (bpy.types.CurveModifier attribute), 350
object (bpy.types.EditObjectActuator attribute), 372
object (bpy.types.HookModifier attribute), 447
object (bpy.types.LampTextureSlot attribute), 500
object (bpy.types.LatticeModifier attribute), 504
object (bpy.types.MaterialTextureSlot attribute), 539
object (bpy.types.MeshDeformModifier attribute), 555
object (bpy.types.ParentActuator attribute), 646
object (bpy.types.ParticleInstanceModifier attribute), 654
object (bpy.types.ParticleSettingsTextureSlot attribute), 670
object (bpy.types.ParticleTarget attribute), 680
object (bpy.types.PointDensity attribute), 688
object (bpy.types.PropertyActuator attribute), 703
object (bpy.types.ScrewModifier attribute), 763
object (bpy.types.UVProjector attribute), 984
object (bpy.types.WorldTextureSlot attribute), 1035
Object (class in bpy.types), 611
object (in module bpy.context), 6, 7
Object.active_shape_key (in module bpy.types), 611
Object.animation_data (in module bpy.types), 611
Object.animation_visualisation (in module bpy.types), 611
Object.bound_box (in module bpy.types), 611
Object.children (in module bpy.types), 617
Object.collision (in module bpy.types), 611
Object.constraints (in module bpy.types), 611
Object.duplicl_list (in module bpy.types), 612
Object.field (in module bpy.types), 613
Object.game (in module bpy.types), 613
Object.is_duplicator (in module bpy.types), 613
Object.material_slots (in module bpy.types), 614
Object.mode (in module bpy.types), 614
Object.modifiers (in module bpy.types), 614
Object.motion_path (in module bpy.types), 614
Object.particle_systems (in module bpy.types), 615
Object.pose (in module bpy.types), 615
Object.proxy (in module bpy.types), 615
Object.proxy_group (in module bpy.types), 615
Object.soft_body (in module bpy.types), 616
Object.type (in module bpy.types), 617
Object.users_group (in module bpy.types), 618
Object.users_scene (in module bpy.types), 618
Object.vertex_groups (in module bpy.types), 617
object_active (bpy.types.ThemeView3D attribute), 941
object_align (bpy.types.UserPreferencesEdit attribute), 989
object_align_factor (bpy.types.ParticleSettings attribute), 664
object_as_camera() (in module bpy.ops.view3d), 133
object_data_add() (in module bpy_extras.object_utils), 1129
object_factor (bpy.types.ParticleSettings attribute), 664
object_from (bpy.types.WarpModifier attribute), 1017
object_grouped (bpy.types.ThemeView3D attribute), 941
object_grouped_active (bpy.types.ThemeView3D attribute), 941
object_operation() (in module bpy.ops.outliner), 87
object_origin_size (bpy.types.UserPreferencesView attribute), 1000
object_property (bpy.types.PropertyActuator attribute), 703
object_selected (bpy.types.ThemeView3D attribute), 941
object_to (bpy.types.WarpModifier attribute), 1017
ObjectActuator (class in bpy.types), 621
ObjectBase (class in bpy.types), 624
ObjectBase.object (in module bpy.types), 624
ObjectConstraints (class in bpy.types), 625
objectLastCreated (bge.types.KX_SCA_AddObjectActuator attribute), 1171
ObjectModifiers (class in bpy.types), 626
objects (bge.types.KX_Scene attribute), 1174

objects_add_active() (in module bpy.ops.group), 41
objects_remove() (in module bpy.ops.group), 42
objects_remove_active() (in module bpy.ops.group), 42
objectsInactive (bge.types.KX_Scene attribute), 1174
ObstacleFluidSettings (class in bpy.types), 627
occlusion (bge.types.KX_GameObject attribute), 1145
occlusion_culling_resolution (bpy.types.SceneGameData attribute), 750
octaves (bpy.types.MusgraveTexture attribute), 593
octree_resolution (bpy.types.RenderSettings attribute), 731
offset (bpy.types.CompositorNodeColorBalance attribute), 276
offset (bpy.types.CompositorNodeMapValue attribute), 303
offset (bpy.types.CompositorNodeTonemap attribute), 319
offset (bpy.types.Curve attribute), 344
offset (bpy.types.FloorConstraint attribute), 414
offset (bpy.types.FollowPathConstraint attribute), 418
offset (bpy.types.MusgraveTexture attribute), 593
offset (bpy.types.PivotConstraint attribute), 681
offset (bpy.types.ShrinkwrapModifier attribute), 803
offset (bpy.types.SolidifyModifier attribute), 817
offset (bpy.types.TextureNodeBricks attribute), 885
offset (bpy.types.TextureSlot attribute), 904
offset_factor (bpy.types.FollowPathConstraint attribute), 418
offset_frequency (bpy.types.TextureNodeBricks attribute), 885
offset_location (bpy.types.ObjectActuator attribute), 622
offset_object (bpy.types.ArrayModifier attribute), 183
offset_rotation (bpy.types.ObjectActuator attribute), 622
offset_x (bpy.types.BackgroundImage attribute), 184
offset_x (bpy.types.SequenceTransform attribute), 776
offset_x (bpy.types.SpaceSequenceEditor attribute), 838
offset_x (bpy.types.TextCurve attribute), 877
offset_y (bpy.types.BackgroundImage attribute), 184
offset_y (bpy.types.SequenceTransform attribute), 776
offset_y (bpy.types.SpaceSequenceEditor attribute), 838
offset_y (bpy.types.TextCurve attribute), 878
offset_z (bpy.types.Material attribute), 522
OKEY (in module bge.events), 1224
ONEKEY (in module bge.events), 1224
opacity (bpy.types.BackgroundImage attribute), 185
open() (in module bpy.ops.font), 36
open() (in module bpy.ops.image), 43
open() (in module bpy.ops.sound), 108
open() (in module bpy.ops.text), 113
open_left_mouse_delay (bpy.types.UserPreferencesView attribute), 1000
open_mainfile() (in module bpy.ops.wm), 142
open_right_mouse_delay (bpy.types.UserPreferencesView attribute), 1000
open_sublevel_delay (bpy.types.UserPreferencesView attribute), 1000
open_toplevel_delay (bpy.types.UserPreferencesView attribute), 1000
opengl() (in module bpy.ops.render), 97
operation (bge.types.KX_StateActuator attribute), 1177
operation (bpy.types.BooleanModifier attribute), 234
operation (bpy.types.CompositorNodeMath attribute), 304
operation (bpy.types.ShaderNodeMath attribute), 784
operation (bpy.types.ShaderNodeVectorMath attribute), 795
operation (bpy.types.StateActuator attribute), 860
operation (bpy.types.TextureNodeMath attribute), 893
operation() (in module bpy.ops.outliner), 88
Operator (class in bpy.types), 633
operator() (bpy.typesUILayout method), 969
Operator.has_reports (in module bpy.types), 633
Operator.layout (in module bpy.types), 633
Operator.name (in module bpy.types), 633
Operator.properties (in module bpy.types), 633
operator_cheat_sheet() (in module bpy.ops.help), 42
operator_context (bpy.typesUILayout attribute), 960
operator_enum() (bpy.typesUILayout method), 971
operator_menu_enum() (bpy.typesUILayout method), 972
operator_node (bpy.types.ThemeNodeEditor attribute), 926
operator_preset_add() (in module bpy.ops.wm), 143
OperatorFileListElement (class in bpy.types), 635
OperatorMousePath (class in bpy.types), 636
OperatorProperties (class in bpy.types), 636
OperatorStrokeElement (class in bpy.types), 637
OperatorTypeMacro (class in bpy.types), 638
OperatorTypeMacro.properties (in module bpy.types), 638
option (bge.types.KX_ConstraintActuator attribute), 1143
OrController (class in bpy.types), 639
order (mathutils.Euler attribute), 1057
order_u (bpy.types.Spline attribute), 851
order_v (bpy.types.Spline attribute), 851
orient_weight (bpy.types.KinematicConstraint attribute), 494
orientation (aud.Handle attribute), 1128
orientation (bge.types.KX_GameObject attribute), 1145
orientation (bge.types.KX_SoundActuator attribute), 1177
origin (bpy.types.SimpleDeformModifier attribute), 805
origin_clear() (in module bpy.ops.object), 80
origin_set() (in module bpy.ops.object), 80
ortho_scale (bge.types.KX_Camera attribute), 1190
ortho_scale (bpy.types.Camera attribute), 244

OrthoProjection() (mathutils.Matrix class method), 1057
oskey (bpy.types.KeyMapItem attribute), 476
OutflowFluidSettings (class in bpy.types), 640
outline (bpy.types.ThemeWidgetColors attribute), 943
outline_width (bpy.types.ThemeView3D attribute), 941
output_node (bpy.types.TextureSlot attribute), 904
overlay_frame (bpy.types.SequenceEditor attribute), 773
overlay_lock (bpy.types.SequenceEditor attribute), 773
overwrite_toggle() (in module bpy.ops.text), 113
owner (bge.types.SCAILogicBrick attribute), 1133
owner (mathutils.Color attribute), 1056
owner (mathutils.Euler attribute), 1057
owner (mathutils.Matrix attribute), 1061
owner (mathutils.Quaternion attribute), 1064
owner (mathutils.Vector attribute), 1068
owner_space (bpy.types.Constraint attribute), 329

P

pack() (in module bpy.ops.image), 43
pack() (in module bpy.ops.sound), 109
pack_all() (in module bpy.ops.file), 33
pack_islands() (in module bpy.ops.uv), 127
PackedFile (class in bpy.types), 640
PackedFile.size (in module bpy.types), 640
PAD0 (in module bge.events), 1225
PAD1 (in module bge.events), 1225
PAD2 (in module bge.events), 1225
PAD3 (in module bge.events), 1225
PAD4 (in module bge.events), 1225
PAD5 (in module bge.events), 1225
PAD6 (in module bge.events), 1225
PAD7 (in module bge.events), 1225
PAD8 (in module bge.events), 1225
PAD9 (in module bge.events), 1225
PADASTERKEY (in module bge.events), 1225
PADEENTER (in module bge.events), 1225
PADMINUS (in module bge.events), 1225
PADPERIOD (in module bge.events), 1225
PADPLUSKEY (in module bge.events), 1225
PADSLASHKEY (in module bge.events), 1225
PAGEDOWNKEY (in module bge.events), 1226
PAGEUPKEY (in module bge.events), 1226
Paint (class in bpy.types), 641
pan() (in module bpy.ops.view2d), 130
panel (bpy.types.ThemeGraphEditor attribute), 918
panel (bpy.types.ThemeLogicEditor attribute), 922
panel (bpy.types.ThemeProperties attribute), 929
panel (bpy.types.ThemeView3D attribute), 941
Panel (class in bpy.types), 644
Panel.layout (in module bpy.types), 645
para1 (bge.types.SCA_RandomActuator attribute), 1188
para2 (bge.types.SCA_RandomActuator attribute), 1188
parent (bge.types.BL_ArmatureBone attribute), 1205
parent (bge.types.BL_ArmatureChannel attribute), 1199

parent (bge.types.KX_GameObject attribute), 1145
parent (bpy.types.EditBone attribute), 369
parent (bpy.types.Object attribute), 615
parent (bpy.types.ParticleSystem attribute), 676
parent() (in module bpy.ops.file), 33
parent_bone (bpy.types.Object attribute), 615
parent_clear() (in module bpy.ops.armature), 18
parent_clear() (in module bpy.ops.object), 80
parent_index() (bpy.types.Bone method), 231
parent_index() (bpy.types.EditBone method), 371
parent_index() (bpy.types.PoseBone method), 699
parent_no_inverse_set() (in module bpy.ops.object), 80
parent_set() (in module bpy.ops.armature), 18
parent_set() (in module bpy.ops.object), 80
parent_type (bpy.types.Object attribute), 615
parent_vertices (bpy.types.Object attribute), 615
ParentActuator (class in bpy.types), 646
partial_slip_factor (bpy.types.DomainFluidSettings attribute), 358
partial_slip_factor (bpy.types.ObstacleFluidSettings attribute), 627
Particle (class in bpy.types), 647
Particle.hair_keys (in module bpy.types), 647
Particle.is_exist (in module bpy.types), 647
Particle.is_visible (in module bpy.types), 647
Particle.particle_keys (in module bpy.types), 647
particle_cache_space (bpy.types.PointDensity attribute), 688
particle_edit_object (in module bpy.context), 6
particle_edit_toggle() (in module bpy.ops.particle), 91
particle_factor (bpy.types.ParticleSettings attribute), 664
particle_influence (bpy.types.ParticleFluidSettings attribute), 653
particle_size (bpy.types.ParticleSettings attribute), 664
particle_system (bpy.types.PointDensity attribute), 688
particle_system (bpy.types.SmokeFlowSettings attribute), 809
particle_system (in module bpy.context), 8
particle_system_add() (in module bpy.ops.object), 80
particle_system_editable (in module bpy.context), 8
particle_system_index (bpy.types.ParticleInstanceModifier attribute), 655
particle_system_remove() (in module bpy.ops.object), 80
particle_uv (bpy.types.ExplodeModifier attribute), 386
ParticleBrush (class in bpy.types), 648
ParticleBrush.curve (in module bpy.types), 648
ParticleDupliWeight (class in bpy.types), 649
ParticleDupliWeight.name (in module bpy.types), 650
ParticleEdit (class in bpy.types), 650
ParticleEdit.brush (in module bpy.types), 650
ParticleEdit.is_editable (in module bpy.types), 651
ParticleEdit.is_hair (in module bpy.types), 651
ParticleEdit.object (in module bpy.types), 651
ParticleFluidSettings (class in bpy.types), 652

ParticleHairKey (class in bpy.types), 653
 ParticleInstanceModifier (class in bpy.types), 654
 ParticleKey (class in bpy.types), 656
 ParticleSettings (class in bpy.types), 657
 ParticleSettings.active_dupliweight (in module bpy.types), 657
 ParticleSettings.animation_data (in module bpy.types), 658
 ParticleSettings.boids (in module bpy.types), 659
 ParticleSettings.dupli_weights (in module bpy.types), 661
 ParticleSettings.effector_weights (in module bpy.types), 661
 ParticleSettings.fluid (in module bpy.types), 661
 ParticleSettings.force_field_1 (in module bpy.types), 661
 ParticleSettings.force_field_2 (in module bpy.types), 661
 ParticleSettings.is_fluid (in module bpy.types), 662
 ParticleSettings.texture_slots (in module bpy.types), 666
 ParticleSettingsTextureSlot (class in bpy.types), 670
 ParticleSettingsTextureSlots (class in bpy.types), 673
 ParticleSystem (class in bpy.types), 674
 ParticleSystem.active_particle_target (in module bpy.types), 674
 ParticleSystem.child_particles (in module bpy.types), 674
 ParticleSystem.cloth (in module bpy.types), 674
 ParticleSystem.has_multiple_caches (in module bpy.types), 674
 ParticleSystem.is_editable (in module bpy.types), 675
 ParticleSystem.is_edited (in module bpy.types), 675
 ParticleSystem.is_global_hair (in module bpy.types), 675
 ParticleSystem.particles (in module bpy.types), 676
 ParticleSystem.point_cache (in module bpy.types), 676
 ParticleSystem.targets (in module bpy.types), 676
 ParticleSystemModifier (class in bpy.types), 678
 ParticleSystemModifier.particle_system (in module bpy.types), 678
 ParticleSystems (class in bpy.types), 679
 ParticleSystems.active (in module bpy.types), 679
 ParticleTarget (class in bpy.types), 680
 ParticleTarget.name (in module bpy.types), 680
 parts_x (bpy.types.RenderSettings attribute), 731
 parts_y (bpy.types.RenderSettings attribute), 732
 pass_index (bpy.types.Object attribute), 615
 passepertout_alpha (bpy.types.Camera attribute), 244
 passes (bpy.types.WorldLighting attribute), 1031
 passNumber (bge.types.SCA_2DFilterActuator attribute), 1183
 paste() (in module bpy.ops.action), 12
 paste() (in module bpy.ops.console), 22
 paste() (in module bpy.ops.graph), 39
 paste() (in module bpy.ops.material), 52
 paste() (in module bpy.ops.pose), 94
 paste() (in module bpy.ops.sequencer), 105
 paste() (in module bpy.ops.text), 113
 paste_driver_button() (in module bpy.ops.anim), 16
 path_duration (bpy.types.Curve attribute), 344
 path_end (bpy.types.ParticleSettings attribute), 664
 path_from_id() (bpy.types.bpy_struct method), 1043
 path_menu() (bpy.types.Menu method), 548
 path_open() (in module bpy.ops.wm), 143
 path_reference() (in module bpy_extras.io_utils), 1129
 path_reference_copy() (in module bpy_extras.io_utils), 1130
 path_reference_mode (in module bpy_extras.io_utils), 1130
 path_resolve() (bpy.types.bpy_struct method), 1044
 path_start (bpy.types.ParticleSettings attribute), 664
 paths_calculate() (in module bpy.ops.object), 80
 paths_calculate() (in module bpy.ops.pose), 94
 paths_clear() (in module bpy.ops.object), 80
 paths_clear() (in module bpy.ops.pose), 94
 PAUSEKEY (in module bge.events), 1226
 pen_flip (bpy.types.OperatorStrokeElement attribute), 637
 PERIODKEY (in module bge.events), 1226
 permeability (bpy.types.CollisionSettings attribute), 263
 perspective (bge.types.KX_Camera attribute), 1191
 phase (bpy.types.FModifierNoise attribute), 402
 phase_factor (bpy.types.ParticleSettings attribute), 664
 phase_factor_random (bpy.types.ParticleSettings attribute), 664
 phase_multiplier (bpy.types.FModifierFunctionGenerator attribute), 399
 phase_offset (bpy.types.FModifierFunctionGenerator attribute), 399
 physics_engine (bpy.types.SceneGameData attribute), 750
 physics_gravity (bpy.types.SceneGameData attribute), 750
 physics_step_max (bpy.types.SceneGameData attribute), 750
 physics_step_sub (bpy.types.SceneGameData attribute), 750
 physics_type (bpy.types.GameObjectSettings attribute), 429
 physics_type (bpy.types.ParticleSettings attribute), 664
 pid (bge.types.KX_ObjectActuator attribute), 1162
 pin (bpy.types.Actuator attribute), 155
 pin (bpy.types.Sensor attribute), 766
 pin() (in module bpy.ops.uv), 127
 pin_id (bpy.types.SpaceProperties attribute), 837
 pin_stiffness (bpy.types.ClothSettings attribute), 256
 pin_uv (bpy.types.MeshTextureFace attribute), 566
 pitch (aud.Handle attribute), 1128
 pitch (bge.types.KX_SoundActuator attribute), 1176
 pitch (bpy.types.BoidSettings attribute), 226
 pitch (bpy.types.SoundActuator attribute), 820
 pivot_point (bpy.types.SpaceGraphEditor attribute), 827
 pivot_point (bpy.types.SpaceUVEditor attribute), 843

pivot_point (bpy.types.SpaceView3D attribute), 846
pivot_type (bpy.types.RigidBodyJointConstraint attribute), 739
pivot_x (bpy.types.RigidBodyJointConstraint attribute), 739
pivot_y (bpy.types.RigidBodyJointConstraint attribute), 739
pivot_z (bpy.types.RigidBodyJointConstraint attribute), 739
PivotConstraint (class in bpy.types), 681
pixel_aspect_x (bpy.types.RenderSettings attribute), 732
pixel_aspect_y (bpy.types.RenderSettings attribute), 732
pixel_filter_type (bpy.types.RenderSettings attribute), 732
pixels (bpy.types.Image attribute), 453
PKEY (in module bge.events), 1224
plane_offset (bpy.types.Brush attribute), 237
plane_trim (bpy.types.Brush attribute), 237
plastic (bpy.types.SoftBodySettings attribute), 814
plasticity (bpy.types.SPHFluidSettings attribute), 741
play_mode (bpy.types.ActionActuator attribute), 148
play_rendered_anim() (in module bpy.ops.render), 97
play_type (bpy.types.FCurveActuator attribute), 390
plugin_strip (bpy.types.ThemeSequenceEditor attribute), 931
PluginSequence (class in bpy.types), 682
PluginSequence.filename (in module bpy.types), 682
PluginTexture (class in bpy.types), 684
PluginTexture.users_material (in module bpy.types), 684
PluginTexture.users_object_modifier (in module bpy.types), 684
ply() (in module bpy.ops.export_mesh), 29
ply() (in module bpy.ops.import_mesh), 46
point_cache_compress_type (bpy.types.SmokeDomainSettings attribute), 807
point_source (bpy.types.PointDensity attribute), 688
PointCache (class in bpy.types), 685
PointCache.frames_skipped (in module bpy.types), 685
PointCache.info (in module bpy.types), 685
PointCache.is_baked (in module bpy.types), 685
PointCache.is_baking (in module bpy.types), 685
PointCache.is_outdated (in module bpy.types), 686
PointCache.point_caches (in module bpy.types), 686
PointCaches (class in bpy.types), 687
PointDensity (class in bpy.types), 687
PointDensity.color_ramp (in module bpy.types), 688
PointDensity.falloff_curve (in module bpy.types), 688
PointDensityTexture (class in bpy.types), 690
PointDensityTexture.point_density (in module bpy.types), 690
PointDensityTexture.users_material (in module bpy.types), 690
PointDensityTexture.users_object_modifier (in module bpy.types), 690
PointDensityTexture.users_material (in module bpy.types), 690
PointDensityTexture.users_object_modifier (in module bpy.types), 690
PointerProperty (class in bpy.types), 693
PointerProperty() (in module bpy.props), 1053
PointerProperty.fixed_type (in module bpy.types), 693
pointInsideFrustum() (bge.types.KX_Camera method), 1192
PointLamp (class in bpy.types), 691
PointLamp.falloff_curve (in module bpy.types), 691
points (bpy.types.ThemeFontStyle attribute), 915
points_u (bpy.types.Lattice attribute), 503
points_v (bpy.types.Lattice attribute), 503
points_w (bpy.types.Lattice attribute), 503
pole_angle (bpy.types.KinematicConstraint attribute), 494
pole_subtarget (bpy.types.KinematicConstraint attribute), 494
pole_target (bpy.types.KinematicConstraint attribute), 494
poll() (bpy.types.KeyingSetInfo method), 488
poll() (bpy.types.Macro class method), 515
poll() (bpy.types.Menu class method), 548
poll() (bpy.types.Operator class method), 633
poll() (bpy.types.Panel class method), 645
poly_order (bpy.types.FModifierGenerator attribute), 400
pop() (bpy.types.IDMaterials method), 450
Pose (class in bpy.types), 694
Pose.animation_visualisation (in module bpy.types), 694
Pose.bone_groups (in module bpy.types), 694
Pose.bones (in module bpy.types), 694
Pose.ik_param (in module bpy.types), 694
pose_add() (in module bpy.ops.poselib), 96
pose_bone (in module bpy.context), 8
pose_head (bge.types.BL_ArmatureChannel attribute), 1202
pose_library (bpy.types.Object attribute), 615
pose_matrix (bge.types.BL_ArmatureChannel attribute), 1202
pose_position (bpy.types.Armature attribute), 175
pose_remove() (in module bpy.ops.poselib), 96
pose_rename() (in module bpy.ops.poselib), 96
pose_tail (bge.types.BL_ArmatureChannel attribute), 1202
PoseBone (class in bpy.types), 695
PoseBone.basename (in module bpy.types), 699
PoseBone.bone (in module bpy.types), 695
PoseBone.center (in module bpy.types), 699
PoseBone.child (in module bpy.types), 695
PoseBone.children (in module bpy.types), 699
PoseBone.children_recursive (in module bpy.types), 699
PoseBone.children_recursive_basename (in module bpy.types), 699
PoseBone.constraints (in module bpy.types), 695
PoseBone.head (in module bpy.types), 696

PoseBone.is_in_ik_chain (in module bpy.types), 697
 PoseBone.matrix (in module bpy.types), 697
 PoseBone.matrix_channel (in module bpy.types), 698
 PoseBone.motion_path (in module bpy.types), 698
 PoseBone.parent (in module bpy.types), 698
 PoseBone.parent_recursive (in module bpy.types), 699
 PoseBone.tail (in module bpy.types), 698
 PoseBone.vector (in module bpy.types), 699
 PoseBone.x_axis (in module bpy.types), 699
 PoseBone.y_axis (in module bpy.types), 699
 PoseBone.z_axis (in module bpy.types), 699
 PoseBoneConstraints (class in bpy.types), 700
 posemode_toggle() (in module bpy.ops.object), 80
 position (aud.Handle attribute), 1128
 position (bge.types.KX_GameObject attribute), 1145
 position (bge.types.KX_SoundActuator attribute), 1176
 position (bge.types.SCA_MouseSensor attribute), 1158
 position (bge.types.SCA_PythonMouse attribute), 1134
 position (bpy.types.ColorRampElement attribute), 265
 position (bpy.types.ParticleInstanceModifier attribute), 655
 position() (in module blf), 1119
 positive (bge.types.SCA_ISensor attribute), 1135
 post_draw (bge.types.KX_Scene attribute), 1175
 power (bpy.types.CompositorNodeColorBalance attribute), 276
 pre_draw (bge.types.KX_Scene attribute), 1175
 pre_roll (bpy.types.ClothSettings attribute), 256
 precision (bpy.types.Itasc attribute), 467
 precision (bpy.types.MeshDeformModifier attribute), 555
 prefetch_frames (bpy.types.UserPreferencesSystem attribute), 997
 premul (bpy.types.CompositorNodeAlphaOver attribute), 270
 prepend() (bpy.types.Header class method), 445
 prepend() (bpy.types.Menu class method), 548
 prepend() (bpy.types.Panel class method), 645
 preset_add() (in module bpy.ops.cloth), 21
 preset_add() (in module bpy.ops.render), 97
 preset_find() (in module bpy.utils), 1045
 preset_paths() (in module bpy.utils), 1045
 pressure (bpy.types.GPencilStrokePoint attribute), 424
 pressure (bpy.types.OperatorStrokeElement attribute), 637
 prev_angular_velocity (bpy.types.Particle attribute), 647
 prev_location (bpy.types.Particle attribute), 647
 prev_rotation (bpy.types.Particle attribute), 647
 prev_velocity (bpy.types.Particle attribute), 647
 preview_render_type (bpy.types.Material attribute), 523
 preview_resolution (bpy.types.DomainFluidSettings attribute), 358
 preview_toggle() (in module bpy.ops.node), 69
 previewrange_clear() (in module bpy.ops.anim), 16
 previewrange_set() (in module bpy.ops.action), 12
 previewrange_set() (in module bpy.ops.anim), 16
 previewrange_set() (in module bpy.ops.graph), 39
 previous() (in module bpy.ops.file), 33
 previous_edit() (in module bpy.ops.sequencer), 105
 previous_marker() (in module bpy.ops.text), 113
 primitive_bezier_circle_add() (in module bpy.ops.curve), 24
 primitive_bezier_curve_add() (in module bpy.ops.curve), 25
 primitive_circle_add() (in module bpy.ops.mesh), 57
 primitive_cone_add() (in module bpy.ops.mesh), 57
 primitive_cube_add() (in module bpy.ops.mesh), 57
 primitive_cylinder_add() (in module bpy.ops.mesh), 58
 primitive_grid_add() (in module bpy.ops.mesh), 58
 primitive_ico_sphere_add() (in module bpy.ops.mesh), 59
 primitive_monkey_add() (in module bpy.ops.mesh), 59
 primitive_nurbs_circle_add() (in module bpy.ops.curve), 25
 primitive_nurbs_curve_add() (in module bpy.ops.curve), 26
 primitive_nurbs_path_add() (in module bpy.ops.curve), 26
 primitive_nurbs_surface_circle_add() (in module bpy.ops.surface), 109
 primitive_nurbs_surface_curve_add() (in module bpy.ops.surface), 109
 primitive_nurbs_surface_cylinder_add() (in module bpy.ops.surface), 110
 primitive_nurbs_surface_sphere_add() (in module bpy.ops.surface), 110
 primitive_nurbs_surface_surface_add() (in module bpy.ops.surface), 110
 primitive_nurbs_surface_torus_add() (in module bpy.ops.surface), 111
 primitive_plane_add() (in module bpy.ops.mesh), 59
 primitive_torus_add() (in module bpy.ops.mesh), 60
 primitive_uv_sphere_add() (in module bpy.ops.mesh), 60
 PrintGLInfo() (in module bge.logic), 1210
 priority (bge.types.BL_ActionActuator attribute), 1136
 priority (bge.types.BL_ShapeActionActuator attribute), 1140
 priority (bpy.types.ActionActuator attribute), 148
 priority (bpy.types.ShapeActionActuator attribute), 797
 progression (bpy.types.BlendTexture attribute), 216
 project_apply() (in module bpy.ops.image), 43
 project_edit() (in module bpy.ops.image), 43
 project_from_view() (in module bpy.ops.uv), 127
 project_image() (in module bpy.ops.paint), 89
 projection_matrix (bge.types.KX_Camera attribute), 1191
 projector_count (bpy.types.UVProjectModifier attribute), 982
 prompt (bpy.types.SpaceConsole attribute), 824
 prop() (bpy.typesUILayout method), 961

prop_enum() (bpy.typesUILayout method), 965
prop_menu_enum() (bpy.typesUILayout method), 963
prop_search() (bpy.typesUILayout method), 967
propagate() (in module bpy.ops.pose), 94
properties() (in module bpy.ops.graph), 39
properties() (in module bpy.ops.image), 43
properties() (in module bpy.ops.logic), 50
properties() (in module bpy.ops.nla), 66
properties() (in module bpy.ops.node), 69
properties() (in module bpy.ops.sequencer), 105
properties() (in module bpy.ops.text), 113
properties() (in module bpy.ops.view3d), 133
properties_add() (in module bpy.ops.wm), 143
properties_context_change() (in module bpy.ops.wm), 143
properties_edit() (in module bpy.ops.wm), 143
properties_remove() (in module bpy.ops.wm), 143
property (bpy.types.ActionActuator attribute), 149
property (bpy.types.CollisionSensor attribute), 261
property (bpy.types.ConstraintActuator attribute), 331
property (bpy.types.FCurveActuator attribute), 390
property (bpy.types.NearSensor attribute), 596
property (bpy.types.PropertyActuator attribute), 703
property (bpy.types.PropertySensor attribute), 707
property (bpy.types.RadarSensor attribute), 711
property (bpy.types.RandomActuator attribute), 713
property (bpy.types.RaySensor attribute), 715
property (bpy.types.ShapeActionActuator attribute), 797
Property (class in bpy.types), 701
Property.description (in module bpy.types), 701
Property.identifier (in module bpy.types), 701
Property.is_enum_flag (in module bpy.types), 701
Property.is_hidden (in module bpy.types), 701
Property.is_never_none (in module bpy.types), 701
Property.is_output (in module bpy.types), 702
Property.is_READONLY (in module bpy.types), 702
Property.is_registered (in module bpy.types), 702
Property.is_registered_optional (in module bpy.types), 702
Property.is_REQUIRED (in module bpy.types), 702
Property.is_RUNTIME (in module bpy.types), 702
Property.is_SKIP_SAVE (in module bpy.types), 702
Property.name (in module bpy.types), 702
Property.srna (in module bpy.types), 702
Property.subtype (in module bpy.types), 702
Property.type (in module bpy.types), 702
Property.unit (in module bpy.types), 702
PropertyActuator (class in bpy.types), 703
PropertyGroup (class in bpy.types), 705
PropertyGroupItem (class in bpy.types), 706
PropertyGroupItem.collection (in module bpy.types), 706
PropertyGroupItem.group (in module bpy.types), 706
PropertyGroupItem.idp_array (in module bpy.types), 706
PropertySensor (class in bpy.types), 707
propName (bge.types.BL_ActionActuator attribute), 1136
propName (bge.types.BL_ShapeActionActuator attribute), 1140
propName (bge.types.KX_ConstraintActuator attribute), 1143
propName (bge.types.KX_IpoActuator attribute), 1154
propName (bge.types.KX_NetworkMessageActuator attribute), 1160
propName (bge.types.KX_RaySensor attribute), 1170
propName (bge.types.KX_TouchSensor attribute), 1159
propName (bge.types.SCA_PropertyActuator attribute), 1187
propName (bge.types.SCA_PropertySensor attribute), 1187
propName (bge.types.SCA_RandomActuator attribute), 1188
proportional_coefficient (bpy.types.ObjectActuator attribute), 622
proportional_edit (bpy.types.ToolSettings attribute), 949
proportional_edit_falloff (bpy.types.ToolSettings attribute), 949
proportional_size (bpy.types.ToolSettings attribute), 949
props_enum() (bpy.typesUILayout method), 963
propvalue (bpy.types.KeyMapItem attribute), 476
protect (bpy.types.ExplodeModifier attribute), 386
proxy_make() (in module bpy.ops.object), 80
proxy_render_size (bpy.types.SpaceSequenceEditor attribute), 838
puff_mode (bpy.types.ParticleBrush attribute), 648
pull (bpy.types.SoftBodySettings attribute), 815
push (bpy.types.SoftBodySettings attribute), 815
push() (in module bpy.ops.pose), 94
push_pull() (in module bpy.ops.transform), 117
PyObjectPlus (class in bge.types), 1133
python_file_run() (in module bpy.ops.script), 101
PythonConstraint (class in bpy.types), 708
PythonConstraint.has_script_error (in module bpy.types), 708
PythonConstraint.targets (in module bpy.types), 708
PythonController (class in bpy.types), 709

Q

QKEY (in module bge.events), 1224
quad_attenuation (bge.types.KX_LightObject attribute), 1156
quadratic_attenuation (bpy.types.PointLamp attribute), 691
quadratic_attenuation (bpy.types.SpotLamp attribute), 857
quadratic_drag (bpy.types.FieldSettings attribute), 406
quads_convert_to_tris() (in module bpy.ops.mesh), 61
quality (bpy.types.ClothSettings attribute), 256
quality (bpy.types.CompositorNodeGlare attribute), 294

quality (bpy.types.CompositorNodeOutputFile attribute), 307
 quality (bpy.types.ControlFluidSettings attribute), 335
 quality (bpy.types.GlowSequence attribute), 436
 Quaternion (class in mathutils), 1061
 Quaternion.conjugate() (in module mathutils), 1061
 Quaternion.conjugated() (in module mathutils), 1061
 Quaternion.copy() (in module mathutils), 1062
 Quaternion.difference() (in module mathutils), 1063
 Quaternion.identity() (in module mathutils), 1062
 Quaternion.invert() (in module mathutils), 1062
 Quaternion.inverted() (in module mathutils), 1062
 Quaternion.negate() (in module mathutils), 1062
 Quaternion.normalize() (in module mathutils), 1062
 Quaternion.normalized() (in module mathutils), 1062
 Quaternion.slerp() (in module mathutils), 1063
 quaternions_flip() (in module bpy.ops.pose), 94
 queue_count (bpy.types.BoidRuleFollowLeader attribute), 223
 quick_explode() (in module bpy.ops.object), 80
 quick_fluid() (in module bpy.ops.object), 81
 quick_fur() (in module bpy.ops.object), 81
 quick_smoke() (in module bpy.ops.object), 81
 quit_blender() (in module bpy.ops.wm), 143
 QUOTEKEY (in module bge.events), 1226

R

r (bge.types.KX_VertexProxy attribute), 1181
 r (mathutils.Color attribute), 1056
 RadarSensor (class in bpy.types), 711
 radial_control() (in module bpy.ops.wm), 143
 radial_falloff (bpy.types.FieldSettings attribute), 406
 radial_max (bpy.types.FieldSettings attribute), 406
 radial_min (bpy.types.FieldSettings attribute), 407
 radial_symmetry (bpy.types.Sculpt attribute), 765
 radius (bpy.types.BezierSplinePoint attribute), 187
 radius (bpy.types.CastModifier attribute), 247
 radius (bpy.types.GameObjectSettings attribute), 429
 radius (bpy.types.MaterialSubsurfaceScattering attribute), 537
 radius (bpy.types.MetaElement attribute), 576
 radius (bpy.types.PointDensity attribute), 688
 radius (bpy.types.SplinePoint attribute), 855
 radius_interpolation (bpy.types.Spline attribute), 851
 radius_set() (in module bpy.ops.curve), 26
 random_position (bpy.types.ParticleInstanceModifier attribute), 655
 RandomActuator (class in bpy.types), 712
 randomize_transform() (in module bpy.ops.object), 81
 RandomSensor (class in bpy.types), 714
 range (bge.types.KX_RaySensor attribute), 1170
 range (bpy.types.BoidSettings attribute), 226
 range (bpy.types.ConstraintActuator attribute), 331
 range (bpy.types.RaySensor attribute), 715

range() (bpy.types.FCurve method), 389
 RAS_2DFILTER_BLUR (in module bge.logic), 1217
 RAS_2DFILTER_CUSTOMFILTER (in module bge.logic), 1217
 RAS_2DFILTER_DILATION (in module bge.logic), 1217
 RAS_2DFILTER_DISABLED (in module bge.logic), 1217
 RAS_2DFILTER_ENABLED (in module bge.logic), 1217
 RAS_2DFILTER_EROSION (in module bge.logic), 1217
 RAS_2DFILTER_GRAYSCALE (in module bge.logic), 1217
 RAS_2DFILTER_INVERT (in module bge.logic), 1217
 RAS_2DFILTER_LAPLACIAN (in module bge.logic), 1217
 RAS_2DFILTER_MOTIONBLUR (in module bge.logic), 1217
 RAS_2DFILTER_NOFILTER (in module bge.logic), 1217
 RAS_2DFILTER_PREWITT (in module bge.logic), 1217
 RAS_2DFILTER_SEPIA (in module bge.logic), 1218
 RAS_2DFILTER_SHARPEN (in module bge.logic), 1218
 RAS_2DFILTER_SOBEL (in module bge.logic), 1218
 rate (aud.Device attribute), 1123
 rate (bpy.types.Brush attribute), 237
 ratio (bpy.types.CompositorNodeColorSpill attribute), 278
 ratio (bpy.types.DecimateModifier attribute), 353
 ray_cast() (bpy.types.Object method), 618
 ray_type (bpy.types.RaySensor attribute), 715
 rayCast() (bge.types.KX_GameObject method), 1152
 rayCastTo() (bge.types.KX_GameObject method), 1152
 rayDirection (bge.types.KX_MouseFocusSensor attribute), 1159
 rayDirection (bge.types.KX_RaySensor attribute), 1171
 rayLength (bge.types.KX_ConstraintActuator attribute), 1143
 raymir_factor (bpy.types.MaterialTextureSlot attribute), 539
 RaySensor (class in bpy.types), 715
 raySource (bge.types.KX_MouseFocusSensor attribute), 1158
 rayTarget (bge.types.KX_MouseFocusSensor attribute), 1159
 raytrace_method (bpy.types.RenderSettings attribute), 732
 react_event (bpy.types.ParticleSettings attribute), 664
 reactor_factor (bpy.types.ParticleSettings attribute), 664
 reactor_target_object (bpy.types.ParticleSystem attribute), 676
 reactor_target_particle_system (bpy.types.ParticleSystem attribute), 676

read_factory_settings() (in module bpy.ops.wm), 144
read_fullsamplelayers() (in module bpy.ops.node), 69
read_homefile() (in module bpy.ops.wm), 144
read_renderlayers() (in module bpy.ops.node), 69
reassign_inputs() (in module bpy.ops.sequencer), 105
recent_files (bpy.types.UserPreferencesFilePaths attribute), 992
record_composite() (in module bpy.ops.image), 43
recover_auto_save() (in module bpy.ops.wm), 144
recover_last_session() (in module bpy.ops.wm), 144
rect (bpy.types.RenderLayer attribute), 723
rect (bpy.types.RenderPass attribute), 727
redo() (in module bpy.ops.ed), 28
redo_last() (in module bpy.ops.screen), 99
redraw_timer() (in module bpy.ops.wm), 144
reference (bge.types.KX_ObjectActuator attribute), 1162
reference_axis (bpy.types.KinematicConstraint attribute), 495
reference_object (bpy.types.ObjectActuator attribute), 623
reference_value (bpy.types.FModifierEnvelope attribute), 397
reflect() (mathutils.Vector method), 1066
reflect_factor (bpy.types.MaterialRaytraceMirror attribute), 532
reflection (bpy.types.MaterialVolume attribute), 545
reflection_color (bpy.types.MaterialVolume attribute), 545
reflection_color_factor (bpy.types.MaterialTextureSlot attribute), 539
reflection_factor (bpy.types.MaterialTextureSlot attribute), 539
refresh() (in module bpy.ops.file), 33
refresh_all() (in module bpy.ops.sequencer), 105
refresh_pyconstraints() (in module bpy.ops.text), 113
refresh_script_paths() (in module bpy.utils), 1045
Region (class in bpy.types), 716
Region.height (in module bpy.types), 716
Region.id (in module bpy.types), 716
Region.type (in module bpy.types), 717
Region.width (in module bpy.types), 717
region_2d_to_location_3d() (in module bpy_extras.view3d_utils), 1132
region_2d_to_vector_3d() (in module bpy_extras.view3d_utils), 1132
region_flip() (in module bpy.ops.screen), 99
region_quadview() (in module bpy.ops.screen), 99
region_scale() (in module bpy.ops.screen), 99
region_to_loop() (in module bpy.ops.mesh), 61
RegionView3D (class in bpy.types), 717
RegionView3D.perspective_matrix (in module bpy.types), 718
register_class() (in module bpy.utils), 1045
register_module() (in module bpy.utils), 1045
regrow_hair (bpy.types.ParticleSettings attribute), 664
reinstancePhysicsMesh() (bge.types.KX_GameObject method), 1154
reiteration_method (bpy.types.Itasc attribute), 467
rekey() (in module bpy.ops.particle), 91
rel_max_x (bpy.types.CompositorNodeCrop attribute), 283
rel_max_y (bpy.types.CompositorNodeCrop attribute), 283
rel_min_x (bpy.types.CompositorNodeCrop attribute), 283
rel_min_y (bpy.types.CompositorNodeCrop attribute), 283
relative (aud.Handle attribute), 1128
relative (bpy.types.CompositorNodeCrop attribute), 283
relative_key (bpy.types.ShapeKey attribute), 798
relative_offset_displace (bpy.types.ArrayModifier attribute), 183
relax() (in module bpy.ops.pose), 94
reload() (bpy.types.Image method), 454
reload() (in module bpy.ops.image), 43
reload() (in module bpy.ops.script), 101
reload() (in module bpy.ops.sequencer), 105
reload() (in module bpy.ops.text), 113
relpath() (in module bpy.path), 1047
remove() (bpy.types.ActionFCurves method), 151
remove() (bpy.types.ActionGroups method), 153
remove() (bpy.types.ActionPoseMarkers method), 154
remove() (bpy.types.Addons class method), 158
remove() (bpy.types.ArmatureEditBones method), 179
remove() (bpy.types.BlendDataActions method), 191
remove() (bpy.types.BlendDataArmatures method), 192
remove() (bpy.types.BlendDataBrushes method), 193
remove() (bpy.types.BlendDataCameras method), 194
remove() (bpy.types.BlendDataCurves method), 195
remove() (bpy.types.BlendDataFonts method), 196
remove() (bpy.types.BlendDataGroups method), 198
remove() (bpy.types.BlendDataImages method), 199
remove() (bpy.types.BlendDataLamps method), 200
remove() (bpy.types.BlendDataLattices method), 201
remove() (bpy.types.BlendDataMaterials method), 204
remove() (bpy.types.BlendDataMeshes method), 205
remove() (bpy.types.BlendDataMetaBalls method), 206
remove() (bpy.types.BlendDataNodeTrees method), 207
remove() (bpy.types.BlendDataObjects method), 208
remove() (bpy.types.BlendDataParticles method), 209
remove() (bpy.types.BlendDataScenes method), 210
remove() (bpy.types.BlendDataTexts method), 212
remove() (bpy.types.BlendDataTextures method), 213
remove() (bpy.types.BlendDataWorlds method), 215
remove() (bpy.types.ChannelDriverVariables method), 249
remove() (bpy.types.ColorRampElements method), 266
remove() (bpy.types.CompositorNodes method), 326

remove() (bpy.types.CurveSplines method), 351
remove() (bpy.types.FCurveKeyframePoints method), 392
remove() (bpy.types.FCurveModifiers method), 393
remove() (bpy.types.Header class method), 445
remove() (bpy.types.KeyConfigurations method), 473
remove() (bpy.types.KeyingSetPaths method), 491
remove() (bpy.types.KeyMapItems method), 480
remove() (bpy.types.Menu class method), 548
remove() (bpy.types.MetaBallElements method), 575
remove() (bpy.types.NlaStrips method), 599
remove() (bpy.types.NlaTracks method), 602
remove() (bpy.types.NodeLinks method), 605
remove() (bpy.types.ObjectConstraints method), 625
remove() (bpy.types.ObjectModifiers method), 627
remove() (bpy.types.Panel class method), 645
remove() (bpy.types.PoseBoneConstraints method), 700
remove() (bpy.types.ShaderNodes method), 796
remove() (bpy.types.TextureNodes method), 903
remove() (bpy.types.TimelineMarkers method), 946
remove() (bpy.types.VertexGroup method), 1007
remove() (bpy.types.VertexGroups method), 1009
remove() (in module bpy.ops.ptcache), 97
remove_doubles() (in module bpy.ops.mesh), 61
remove_doubles() (in module bpy.ops.particle), 91
removeParent() (bge.types.KX_GameObject method), 1151
RemoveProperty() (in module bpy.props), 1053
rename() (in module bpy.ops.file), 33
rename() (in module bpy.ops.marker), 51
render() (bpy.types.RenderEngine method), 720
render() (in module bpy.ops.render), 97
render_border() (in module bpy.ops.view3d), 133
render_changed() (in module bpy.ops.node), 69
render_display_mode (bpy.types.DomainFluidSettings attribute), 358
render_layer_add() (in module bpy.ops.scene), 98
render_layer_remove() (in module bpy.ops.scene), 98
render_levels (bpy.types.MultiresModifier attribute), 592
render_levels (bpy.types.SubsurfModifier attribute), 867
render_output_directory (bpy.types.UserPreferencesFilePath attribute), 992
render_resolution (bpy.types.MetaBall attribute), 574
render_resolution_u (bpy.types.Curve attribute), 344
render_resolution_v (bpy.types.Curve attribute), 344
render_step (bpy.types.ParticleSettings attribute), 665
render_steps (bpy.types.ScrewModifier attribute), 763
render_type (bpy.types.ParticleSettings attribute), 665
renderability_toggle() (in module bpy.ops.outliner), 88
rendered_child_count (bpy.types.ParticleSettings attribute), 665
RenderEngine (class in bpy.types), 720
RenderLayer (class in bpy.types), 722
RenderLayer.exclude_ambient_occlusion (in module bpy.types), 722
RenderLayer.exclude_emit (in module bpy.types), 722
RenderLayer.exclude_environment (in module bpy.types), 722
RenderLayer.exclude_indirect (in module bpy.types), 722
RenderLayer.exclude_reflection (in module bpy.types), 722
RenderLayer.exclude_refraction (in module bpy.types), 722
RenderLayer.exclude_shadow (in module bpy.types), 722
RenderLayer.exclude_specular (in module bpy.types), 722
RenderLayer.invert_zmask (in module bpy.types), 722
RenderLayer.layers (in module bpy.types), 722
RenderLayer.layers_zmask (in module bpy.types), 723
RenderLayer.light_override (in module bpy.types), 723
RenderLayer.material_override (in module bpy.types), 723
RenderLayer.name (in module bpy.types), 723
RenderLayer.passes (in module bpy.types), 723
RenderLayer.use (in module bpy.types), 723
RenderLayer.use_all_z (in module bpy.types), 723
RenderLayer.use_edge_enhance (in module bpy.types), 723
RenderLayer.use_halo (in module bpy.types), 723
RenderLayer.use_pass_ambient_occlusion (in module bpy.types), 723
RenderLayer.use_pass_color (in module bpy.types), 723
RenderLayer.use_pass_combined (in module bpy.types), 723
RenderLayer.use_pass_diffuse (in module bpy.types), 723
RenderLayer.use_pass_emit (in module bpy.types), 724
RenderLayer.use_pass_environment (in module bpy.types), 724
RenderLayer.use_pass_indirect (in module bpy.types), 724
RenderLayer.use_pass_mist (in module bpy.types), 724
RenderLayer.use_pass_normal (in module bpy.types), 724
RenderLayer.use_pass_object_index (in module bpy.types), 724
RenderLayer.use_pass_reflection (in module bpy.types), 724
RenderLayer.use_pass_refraction (in module bpy.types), 724
RenderLayer.use_pass_shadow (in module bpy.types), 724
RenderLayer.use_pass_specular (in module bpy.types), 724
RenderLayer.use_pass_uv (in module bpy.types), 724
RenderLayer.use_pass_vector (in module bpy.types), 724
RenderLayer.use_pass_z (in module bpy.types), 724
RenderLayer.use_sky (in module bpy.types), 724

RenderLayer.use_solid (in module bpy.types), 725
RenderLayer.use_strand (in module bpy.types), 725
RenderLayer.use_zmask (in module bpy.types), 725
RenderLayer.use_ztransp (in module bpy.types), 725
RenderLayers (class in bpy.types), 726
RenderPass (class in bpy.types), 727
RenderPass.channel_id (in module bpy.types), 727
RenderPass.channels (in module bpy.types), 727
RenderPass.name (in module bpy.types), 727
RenderPass.type (in module bpy.types), 727
RenderResult (class in bpy.types), 728
RenderResult.layers (in module bpy.types), 728
RenderResult.resolution_x (in module bpy.types), 728
RenderResult.resolution_y (in module bpy.types), 728
RenderSettings (class in bpy.types), 729
RenderSettings.file_extension (in module bpy.types), 730
RenderSettings.has_multiple_engines (in module bpy.types), 731
RenderSettings.is_movie_format (in module bpy.types), 731
RenderSettings.layers (in module bpy.types), 731
RenderSettings.use_game_engine (in module bpy.types), 735
rendersize() (in module bpy.ops.sequencer), 105
repeat (bge.types.SCA_DelaySensor attribute), 1184
repeat (bpy.types.NlaStrip attribute), 598
repeat_history() (in module bpy.ops.screen), 99
repeat_last() (in module bpy.ops.screen), 99
repeat_x (bpy.types.ImageTexture attribute), 461
repeat_y (bpy.types.ImageTexture attribute), 461
repel_force (bpy.types.ClothCollisionSettings attribute), 253
replace() (bge.types.KX_Scene method), 1175
replace() (in module bpy.ops.image), 43
replace() (in module bpy.ops.text), 113
replace_set_selected() (in module bpy.ops.text), 114
replace_text (bpy.types.SpaceTextEditor attribute), 840
replaceMesh() (bge.types.KX_GameObject method), 1147
report() (bpy.types.Macro method), 514
report() (bpy.types.Operator method), 633
report() (bpy.types.RenderEngine method), 721
report_copy() (in module bpy.ops.info), 48
report_delete() (in module bpy.ops.info), 48
report_missing_files() (in module bpy.ops.file), 34
report_replay() (in module bpy.ops.info), 48
reports_display_update() (in module bpy.ops.info), 48
reports_to_textblock() (in module bpy.ops.ui), 125
repulsion (bpy.types.SPHFluidSettings attribute), 741
reset() (bge.types.SCA_ISensor method), 1135
reset() (in module bpy.ops.brush), 20
reset() (in module bpy.ops.uv), 128
reset() (in module bpy.ops.view2d), 130
reset_default_button() (in module bpy.ops.ui), 125
reset_default_theme() (in module bpy.ops.ui), 125
reset_distance (bpy.types.NearSensor attribute), 596
resetDistance (bge.types.KX_NearSensor attribute), 1160
resize() (in module bpy.ops.node), 69
resize() (in module bpy.ops.transform), 118
resize_2d() (mathutils.Vector method), 1066
resize_3d() (mathutils.Vector method), 1067
resize_4d() (mathutils.Vector method), 1067
resize_4x4() (mathutils.Matrix method), 1059
resolution (bpy.types.DomainFluidSettings attribute), 358
resolution (bpy.types.EnvironmentMap attribute), 381
resolution (bpy.types.Image attribute), 453
resolution (bpy.types.MetaBall attribute), 574
resolution (bpy.types.VoxelData attribute), 1015
resolution_max (bpy.types.SmokeDomainSettings attribute), 807
resolution_percentage (bpy.types.RenderSettings attribute), 732
resolution_u (bpy.types.Curve attribute), 344
resolution_u (bpy.types.Spline attribute), 851
resolution_v (bpy.types.Curve attribute), 344
resolution_v (bpy.types.Spline attribute), 851
resolution_x (bpy.types.RenderSettings attribute), 732
resolution_x (bpy.types.SceneGameData attribute), 750
resolution_y (bpy.types.RenderSettings attribute), 732
resolution_y (bpy.types.SceneGameData attribute), 750
resolve_conflict() (in module bpy.ops.text), 114
resolve_ncase() (in module bpy.path), 1047
resource_path() (in module bpy.utils), 1045
rest_density (bpy.types.SPHFluidSettings attribute), 741
rest_length (bpy.types.FieldSettings attribute), 407
rest_length (bpy.types.SPHFluidSettings attribute), 741
rest_length (bpy.types.StretchToConstraint attribute), 861
rest_shape_key (bpy.types.ClothSettings attribute), 257
restart() (bge.types.KX_Scene method), 1175
restartGame() (in module bge.logic), 1207
restore_item_to_default() (bpy.types.KeyMap method), 474
restore_to_default() (bpy.types.KeyMap method), 474
restoreDynamics() (bge.types.KX_GameObject method), 1150
resume() (bge.types.KX_Scene method), 1175
RETKEY (in module bge.events), 1226
reveal() (in module bpy.ops.armature), 18
reveal() (in module bpy.ops.curve), 26
reveal() (in module bpy.ops.mesh), 61
reveal() (in module bpy.ops.particle), 91
reveal() (in module bpy.ops.pose), 95
reveal() (in module bpy.ops.uv), 128
reveal_metealems() (in module bpy.ops.mball), 52
reverse() (bge.types.CListValue method), 1141
RGBANodeSocket (class in bpy.types), 710
RIGHTALTKEY (in module bge.events), 1224
RIGHTARROWKEY (in module bge.events), 1225

RIGHTBRACKETKEY (in module bge.events), 1226
 RIGHTCTRLKEY (in module bge.events), 1224
 RIGHTMOUSE (in module bge.events), 1223
 RIGHTSHIFTKEY (in module bge.events), 1224
 RigidBodyJointConstraint (class in bpy.types), 738
 ring_count (bpy.types.MaterialHalo attribute), 528
 rip() (in module bpy.ops.mesh), 61
 rip_move() (in module bpy.ops.mesh), 61
 RKEY (in module bge.events), 1224
 roll (bge.types.BL_ArmatureBone attribute), 1204
 roll (bpy.types.EditBone attribute), 369
 rolloff_factor_3d (bpy.types.SoundActuator attribute), 820
 rollOffFactor (bge.types.KX_SoundActuator attribute), 1176
 root_size (bpy.types.MaterialStrand attribute), 535
 rot_clear() (in module bpy.ops.pose), 95
 rot_error (bge.types.BL_ArmatureConstraint attribute), 1198
 rotate() (in module bpy.ops.transform), 119
 rotate() (in module bpy.ops.view3d), 133
 rotate() (mathutils.Euler method), 1056
 rotate() (mathutils.Matrix method), 1060
 rotate() (mathutils.Quaternion method), 1063
 rotate_axis() (mathutils.Euler method), 1056
 rotation (bpy.types.MetaElement attribute), 576
 rotation (bpy.types.Particle attribute), 647
 rotation (bpy.types.ParticleKey attribute), 656
 rotation (bpy.types.ShaderNodeMapping attribute), 782
 rotation (bpy.types.TexMapping attribute), 872
 ROTATION (in module blf), 1118
 rotation() (in module blf), 1119
 Rotation() (mathutils.Matrix class method), 1058
 rotation_angle (bpy.types.UserPreferencesView attribute), 1000
 rotation_axis_angle (bpy.types.Object attribute), 615
 rotation_axis_angle (bpy.types.PoseBone attribute), 698
 rotation_clear() (in module bpy.ops.object), 82
 rotation_damping (bpy.types.GameObjectSettings attribute), 429
 rotation_estimate (bpy.types.SoftBodySettings attribute), 815
 rotation_euler (bge.types.BL_ArmatureChannel attribute), 1201
 rotation_euler (bpy.types.Object attribute), 615
 rotation_euler (bpy.types.PoseBone attribute), 698
 rotation_factor_random (bpy.types.ParticleSettings attribute), 665
 rotation_max (bpy.types.ConstraintActuator attribute), 331
 rotation_mode (bge.types.BL_ArmatureChannel attribute), 1201
 rotation_mode (bpy.types.Object attribute), 615
 rotation_mode (bpy.types.ParticleSettings attribute), 665
 rotation_mode (bpy.types.PoseBone attribute), 698
 rotation_quaternion (bge.types.BL_ArmatureChannel attribute), 1201
 rotation_quaternion (bpy.types.Object attribute), 616
 rotation_quaternion (bpy.types.PoseBone attribute), 698
 rotation_range (bpy.types.PivotConstraint attribute), 681
 rotation_start (bpy.types.TransformSequence attribute), 957
 rotDamp (bge.types.KX_ConstraintActuator attribute), 1143
 rough_factor (bpy.types.ParticleSettingsTextureSlot attribute), 671
 roughness (bpy.types.Material attribute), 523
 roughness_1 (bpy.types.ParticleSettings attribute), 665
 roughness_1_size (bpy.types.ParticleSettings attribute), 665
 roughness_2 (bpy.types.ParticleSettings attribute), 665
 roughness_2_size (bpy.types.ParticleSettings attribute), 665
 roughness_2_threshold (bpy.types.ParticleSettings attribute), 665
 roughness_end_shape (bpy.types.ParticleSettings attribute), 665
 roughness_endpoint (bpy.types.ParticleSettings attribute), 665
 row() (bpy.typesUILayout method), 960
 row_size (mathutils.Matrix attribute), 1061
 rule_add() (in module bpy.ops.boid), 19
 rule_del() (in module bpy.ops.boid), 19
 rule_fuzzy (bpy.types.BoidState attribute), 227
 rule_move_down() (in module bpy.ops.boid), 19
 rule_move_up() (in module bpy.ops.boid), 19
 ruleset_type (bpy.types.BoidState attribute), 227
 run_script() (in module bpy.ops.text), 114

S

s (mathutils.Color attribute), 1056
 sample() (in module bpy.ops.action), 12
 sample() (in module bpy.ops.graph), 40
 sample() (in module bpy.ops.image), 44
 sample_color() (in module bpy.ops.paint), 89
 sample_line() (in module bpy.ops.image), 44
 sample_method (bpy.types.WorldLighting attribute), 1031
 samples (bpy.types.CompositorNodeDefocus attribute), 287
 samples (bpy.types.CompositorNodeVecBlur attribute), 323
 samples (bpy.types.WorldLighting attribute), 1031
 saturation (bpy.types.Texture attribute), 882
 save() (bpy.types.Image method), 454
 save() (in module bpy.ops.image), 44
 save() (in module bpy.ops.text), 114
 save_as() (in module bpy.ops.image), 44

save_as() (in module bpy.ops.text), 114
save_as_mainfile() (in module bpy.ops.wm), 145
save_dirty() (in module bpy.ops.image), 45
save_homefile() (in module bpy.ops.wm), 145
save_mainfile() (in module bpy.ops.wm), 145
save_render() (bpy.types.Image method), 454
save_sequence() (in module bpy.ops.image), 45
save_version (bpy.types.UserPreferencesFilePaths attribute), 992
saveGlobalDict() (in module bge.logic), 1207
SCA_2DFilterActuator (class in bge.types), 1183
SCA_ActuatorSensor (class in bge.types), 1183
SCA_AlwaysSensor (class in bge.types), 1183
SCA_ANDController (class in bge.types), 1183
SCA_DelaySensor (class in bge.types), 1183
SCA_IActuator (class in bge.types), 1136
SCA_IController (class in bge.types), 1135
SCAILogicBrick (class in bge.types), 1133
SCA_IObject (class in bge.types), 1134
SCA_ISensor (class in bge.types), 1134
SCA_JoystickSensor (class in bge.types), 1184
SCA_KeyboardSensor (class in bge.types), 1186
SCA_MouseSensor (class in bge.types), 1158
SCA_NANDController (class in bge.types), 1187
SCA_NORController (class in bge.types), 1187
SCA_ORController (class in bge.types), 1187
SCA_PropertyActuator (class in bge.types), 1187
SCA_PropertySensor (class in bge.types), 1187
SCA_PythonController (class in bge.types), 1187
SCA_PythonKeyboard (class in bge.types), 1133
SCA_PythonMouse (class in bge.types), 1134
SCA_RandomActuator (class in bge.types), 1188
SCA_RandomSensor (class in bge.types), 1190
SCA_XNORController (class in bge.types), 1190
SCA_XORController (class in bge.types), 1190
scale (bge.types.BL_ArmatureChannel attribute), 1200
scale (bpy.types.FModifierNoise attribute), 402
scale (bpy.types.MaterialSubsurfaceScattering attribute), 537
scale (bpy.types.NlaStrip attribute), 598
scale (bpy.types.Object attribute), 616
scale (bpy.types.PoseBone attribute), 698
scale (bpy.types.ShaderNodeMapping attribute), 782
scale (bpy.types.TexMapping attribute), 872
scale (bpy.types.TextureSlot attribute), 904
Scale() (mathutils.Matrix class method), 1058
scale_clear() (in module bpy.ops.object), 82
scale_clear() (in module bpy.ops.pose), 95
scale_estimate (bpy.types.SoftBodySettings attribute), 815
scale_length (bpy.types.UnitSettings attribute), 985
scale_size() (in module bpy.ops.brush), 20
scale_start_x (bpy.types.TransformSequence attribute), 958
scale_start_y (bpy.types.TransformSequence attribute), 958
scale_to_length (bpy.types.SpeedControlSequence attribute), 849
scale_x (bpy.typesUILayout attribute), 960
scale_x (bpy.types.UVProjectModifier attribute), 983
scale_y (bpy.typesUILayout attribute), 960
scale_y (bpy.types.UVProjectModifier attribute), 983
scaling (bge.types.KX_GameObject attribute), 1145
scattering (bpy.types.MaterialVolume attribute), 545
scattering_factor (bpy.types.MaterialTextureSlot attribute), 540
scene (bge.types.KX_SceneActuator attribute), 1176
scene (bpy.types.CompositorNodeRLayers attribute), 310
scene (bpy.types.SceneActuator attribute), 747
scene (bpy.types.SceneSequence attribute), 758
scene (bpy.types.Screen attribute), 761
Scene (class in bpy.types), 743
scene (in module bpy.context), 5
Scene.animation_data (in module bpy.types), 743
Scene.frame_subframe (in module bpy.types), 744
Scene.game_settings (in module bpy.types), 744
Scene.is_nla_tweakmode (in module bpy.types), 744
Scene.keying_sets (in module bpy.types), 744
Scene.keying_sets_all (in module bpy.types), 744
Scene.node_tree (in module bpy.types), 744
Scene.object_bases (in module bpy.types), 744
Scene.objects (in module bpy.types), 744
Scene.orientations (in module bpy.types), 744
Scene.render (in module bpy.types), 744
Scene.sequence_editor (in module bpy.types), 745
Scene.timeline_markers (in module bpy.types), 745
Scene.tool_settings (in module bpy.types), 745
Scene.unit_settings (in module bpy.types), 745
scene_camera (bpy.types.SceneSequence attribute), 758
scene_strip (bpy.types.ThemeSequenceEditor attribute), 931
scene_strip_add() (in module bpy.ops.sequencer), 105
SceneActuator (class in bpy.types), 747
SceneBases (class in bpy.types), 748
SceneGameData (class in bpy.types), 749
SceneObjects (class in bpy.types), 753
SceneRenderLayer (class in bpy.types), 754
SceneSequence (class in bpy.types), 757
SceneSequence.color_balance (in module bpy.types), 758
SceneSequence.crop (in module bpy.types), 758
SceneSequence.proxy (in module bpy.types), 758
SceneSequence.transform (in module bpy.types), 758
scope_back (bpy.types.ThemeImageEditor attribute), 920
Scopes (class in bpy.types), 760
scopes() (in module bpy.ops.image), 45
Scopes.histogram (in module bpy.types), 760
screen (bpy.types.Window attribute), 1021
Screen (class in bpy.types), 761

Screen.areas (in module bpy.types), 761
Screen.is_animation_playing (in module bpy.types), 761
Screen.show_fullscreen (in module bpy.types), 761
screen_full_area() (in module bpy.ops.screen), 100
screen_grab_size (bpy.types.ImagePaint attribute), 456
screen_set() (in module bpy.ops.screen), 100
screencast() (in module bpy.ops.screen), 100
screencast_fps (bpy.types.UserPreferencesSystem attribute), 997
screencast_wait_time (bpy.types.UserPreferencesSystem attribute), 997
screenshot() (in module bpy.ops.screen), 100
screw() (in module bpy.ops.mesh), 61
screw_offset (bpy.types.ScrewModifier attribute), 763
ScrewModifier (class in bpy.types), 763
script (bge.types.SCA_PythonController attribute), 1187
script_directory (bpy.types.UserPreferencesFilePaths attribute), 992
script_paths() (in module bpy.utils), 1045
scroll() (in module bpy.ops.text), 114
scroll_bar (bpy.types.ThemeTextEditor attribute), 933
scroll_bar() (in module bpy.ops.text), 114
scroll_down() (in module bpy.ops.view2d), 130
scroll_handle (bpy.types.ThemeFileBrowser attribute), 914
scroll_left() (in module bpy.ops.view2d), 130
scroll_page() (in module bpy.ops.outliner), 88
scroll_right() (in module bpy.ops.view2d), 130
scroll_up() (in module bpy.ops.view2d), 131
scrollback (bpy.types.UserPreferencesSystem attribute), 997
scrollback_append() (in module bpy.ops.console), 23
scrollbar (bpy.types.ThemeFileBrowser attribute), 914
scroller_activate() (in module bpy.ops.view2d), 131
Sculpt (class in bpy.types), 764
sculpt_levels (bpy.types.MultiresModifier attribute), 592
sculpt_object (in module bpy.context), 6
sculpt_paint_overlay_color (bpy.types.UserPreferencesEdit attribute), 989
sculpt_paint_use_unified_size (bpy.types.ToolSettings attribute), 949
sculpt_paint_use_unified_strength (bpy.types.ToolSettings attribute), 950
sculpt_plane (bpy.types.Brush attribute), 237
sculpt_tool (bpy.types.Brush attribute), 237
sculpt_tool_set() (in module bpy.ops.brush), 20
sculptmode_toggle() (in module bpy.ops.sculpt), 101
seam_bleed (bpy.types.ImagePaint attribute), 456
search_menu() (in module bpy.ops.wm), 146
secondary_target (bpy.types.ArmatureActuator attribute), 177
seed (bge.types.SCA_RandomActuator attribute), 1188
seed (bge.types.SCA_RandomSensor attribute), 1190
seed (bpy.types.BuildModifier attribute), 243
seed (bpy.types.FieldSettings attribute), 407
seed (bpy.types.MaterialHalo attribute), 528
seed (bpy.types.ParticleSystem attribute), 676
seed (bpy.types.RandomActuator attribute), 713
seed (bpy.types.RandomSensor attribute), 714
select (bpy.types.ActionGroup attribute), 152
select (bpy.types.Bone attribute), 230
select (bpy.types.CurveMapPoint attribute), 347
select (bpy.types.EditBone attribute), 369
select (bpy.types.FCurve attribute), 389
select (bpy.types.FCurveSample attribute), 394
select (bpy.types.GPencilFrame attribute), 421
select (bpy.types.GPencilLayer attribute), 423
select (bpy.types.MeshEdge attribute), 557
select (bpy.types.MeshFace attribute), 559
select (bpy.types.MeshVertex attribute), 570
select (bpy.types.MotionPathVert attribute), 584
select (bpy.types.NlaStrip attribute), 598
select (bpy.types.NlaTrack attribute), 600
select (bpy.types.Object attribute), 616
select (bpy.types.ObjectBase attribute), 624
select (bpy.types.Sequence attribute), 769
select (bpy.types.SplinePoint attribute), 855
select (bpy.types.ThemeBoneColorSet attribute), 908
select (bpy.types.TimelineMarker attribute), 945
select() (in module bpy.ops.file), 34
select() (in module bpy.ops.marker), 51
select() (in module bpy.ops.node), 69
select() (in module bpy.ops.sequencer), 105
select() (in module bpy.ops.sketch), 108
select() (in module bpy.ops.uv), 128
select() (in module bpy.ops.view3d), 133
select_active_side() (in module bpy.ops.sequencer), 105
select_all() (in module bpy.ops.armature), 18
select_all() (in module bpy.ops.curve), 26
select_all() (in module bpy.ops.lattice), 49
select_all() (in module bpy.ops.marker), 51
select_all() (in module bpy.ops.mball), 52
select_all() (in module bpy.ops.mesh), 62
select_all() (in module bpy.ops.node), 69
select_all() (in module bpy.ops.object), 82
select_all() (in module bpy.ops.particle), 91
select_all() (in module bpy.ops.pose), 95
select_all() (in module bpy.ops.text), 114
select_all() (in module bpy.ops.uv), 128
select_all_toggle() (in module bpy.ops.action), 12
select_all_toggle() (in module bpy.ops.file), 34
select_all_toggle() (in module bpy.ops.graph), 40
select_all_toggle() (in module bpy.ops.info), 48
select_all_toggle() (in module bpy.ops.nla), 66
select_all_toggle() (in module bpy.ops.sequencer), 105
select_axis() (in module bpy.ops.mesh), 62
select_bookmark() (in module bpy.ops.file), 34

select_border() (in module bpy.ops.action), 12
select_border() (in module bpy.ops.file), 34
select_border() (in module bpy.ops.graph), 40
select_border() (in module bpy.ops.info), 48
select_border() (in module bpy.ops.marker), 51
select_border() (in module bpy.ops.nla), 66
select_border() (in module bpy.ops.node), 70
select_border() (in module bpy.ops.sequencer), 105
select_border() (in module bpy.ops.uv), 128
select_border() (in module bpy.ops.view3d), 134
select_by_layer() (in module bpy.ops.object), 82
select_by_number_vertices() (in module bpy.ops.mesh), 62
select_by_type() (in module bpy.ops.object), 82
select_camera() (in module bpy.ops.object), 82
select_circle() (in module bpy.ops.view3d), 134
select_column() (in module bpy.ops.action), 12
select_column() (in module bpy.ops.graph), 40
select_constraint_target() (in module bpy.ops.pose), 95
select_control_point (bpy.types.BezierSplinePoint attribute), 187
select_control_point (bpy.types.Keyframe attribute), 486
select_end (bpy.types.SpaceConsole attribute), 824
select_flip_active() (in module bpy.ops.pose), 95
select_grouped() (in module bpy.ops.object), 82
select_grouped() (in module bpy.ops.pose), 95
select_handles() (in module bpy.ops.sequencer), 106
select_head (bpy.types.Bone attribute), 230
select_head (bpy.types.EditBone attribute), 369
select_hierarchy() (in module bpy.ops.armature), 18
select_hierarchy() (in module bpy.ops.object), 83
select_hierarchy() (in module bpy.ops.pose), 95
select_inverse() (in module bpy.ops.armature), 18
select_inverse() (in module bpy.ops.curve), 26
select_inverse() (in module bpy.ops.mesh), 62
select_inverse() (in module bpy.ops.object), 83
select_inverse() (in module bpy.ops.particle), 91
select_inverse() (in module bpy.ops.pose), 95
select_inverse() (in module bpy.ops.sequencer), 106
select_inverse_metalems() (in module bpy.ops.mball), 52
select_lasso() (in module bpy.ops.view3d), 134
select_left_handle (bpy.types.BezierSplinePoint attribute), 187
select_left_handle (bpy.types.Keyframe attribute), 486
select_left_handle (bpy.types.Sequence attribute), 769
select_leftright() (in module bpy.ops.action), 12
select_leftright() (in module bpy.ops.graph), 40
select_leftright() (in module bpy.ops.nla), 66
select_less() (in module bpy.ops.action), 12
select_less() (in module bpy.ops.curve), 26
select_less() (in module bpy.ops.graph), 40
select_less() (in module bpy.ops.mesh), 62
select_less() (in module bpy.ops.particle), 91
select_less() (in module bpy.ops.sequencer), 106
select_line() (in module bpy.ops.text), 114
select_link_viewer() (in module bpy.ops.node), 70
select_linked() (in module bpy.ops.action), 13
select_linked() (in module bpy.ops.armature), 18
select_linked() (in module bpy.ops.curve), 26
select_linked() (in module bpy.ops.graph), 40
select_linked() (in module bpy.ops.mesh), 62
select_linked() (in module bpy.ops.object), 83
select_linked() (in module bpy.ops.particle), 91
select_linked() (in module bpy.ops.pose), 95
select_linked() (in module bpy.ops.sequencer), 106
select_linked() (in module bpy.ops.uv), 128
select_linked_from() (in module bpy.ops.node), 70
select_linked_pick() (in module bpy.ops.curve), 27
select_linked_pick() (in module bpy.ops.mesh), 62
select_linked_pick() (in module bpy.ops.sequencer), 106
select_linked_pick() (in module bpy.ops.uv), 128
select_linked_to() (in module bpy.ops.node), 70
select_loop() (in module bpy.ops.uv), 128
select_mirror() (in module bpy.ops.mesh), 62
select_mirror() (in module bpy.ops.object), 83
select_mode (bpy.types.ParticleEdit attribute), 651
select_more() (in module bpy.ops.action), 13
select_more() (in module bpy.ops.curve), 27
select_more() (in module bpy.ops.graph), 40
select_more() (in module bpy.ops.mesh), 62
select_more() (in module bpy.ops.particle), 91
select_more() (in module bpy.ops.sequencer), 106
select_mouse (bpy.types.UserPreferencesInput attribute), 994
select_name() (in module bpy.ops.object), 83
select_next() (in module bpy.ops.curve), 27
select_non_manifold() (in module bpy.ops.mesh), 62
select_nth() (in module bpy.ops.curve), 27
select_nth() (in module bpy.ops.mesh), 62
select_orientation() (in module bpy.ops.transform), 119
select_parent() (in module bpy.ops.pose), 95
select_pattern() (in module bpy.ops.object), 83
select_pick() (in module bpy.ops.info), 48
select_pinned() (in module bpy.ops.uv), 129
select_previous() (in module bpy.ops.curve), 27
select_random() (in module bpy.ops.curve), 27
select_random() (in module bpy.ops.mesh), 63
select_random() (in module bpy.ops.object), 83
select_random_metalems() (in module bpy.ops.mball), 52
select_right_handle (bpy.types.BezierSplinePoint attribute), 187
select_right_handle (bpy.types.Keyframe attribute), 486
select_right_handle (bpy.types.Sequence attribute), 769
select_roots() (in module bpy.ops.particle), 92
select_row() (in module bpy.ops.curve), 27
select_same_group() (in module bpy.ops.object), 84

select_same_type() (in module bpy.ops.node), 70
select_same_type_next() (in module bpy.ops.node), 70
select_same_type_prev() (in module bpy.ops.node), 70
select_set() (in module bpy.ops.console), 23
select_shortest_path() (in module bpy.ops.mesh), 63
select_similar() (in module bpy.ops.mesh), 63
select_start (bpy.types.SpaceConsole attribute), 824
select_tail (bpy.types.Bone attribute), 230
select_tail (bpy.types.EditBone attribute), 369
select_tips() (in module bpy.ops.particle), 92
select_uv (bpy.types.MeshTextureFace attribute), 566
select_vertex_path() (in module bpy.ops.mesh), 63
select_word() (in module bpy.ops.text), 115
selectability_toggle() (in module bpy.ops.outliner), 88
selectable_bases (in module bpy.context), 5, 7
selectable_objects (in module bpy.context), 5, 7
selected_bases (in module bpy.context), 5, 7
selected_bones (in module bpy.context), 6
selected_editable_bases (in module bpy.context), 5, 7
selected_editable_bones (in module bpy.context), 6
selected_editable_objects (in module bpy.context), 5, 7
selected_editable_sequences (in module bpy.context), 6
selected_file (bpy.types.ThemeFileBrowser attribute), 914
selected_nodes (in module bpy.context), 9
selected_objects (in module bpy.context), 5, 7
selected_pose_bones (in module bpy.context), 6
selected_sequences (in module bpy.context), 6
selected_text (bpy.types.ThemeNodeEditor attribute), 926
selected_text (bpy.types.ThemeTextEditor attribute), 933
selected_toggle() (in module bpy.ops.outliner), 88
selection_set() (in module bpy.ops.text), 115
self_collision_quality (bpy.types.ClothCollisionSettings attribute), 253
self_distance_min (bpy.types.ClothCollisionSettings attribute), 253
self_friction (bpy.types.ClothCollisionSettings attribute), 253
SEMICOLONKEY (in module bge.events), 1226
sendMessage() (bge.types.KX_GameObject method), 1153
sendMessage() (in module bge.logic), 1208
Sensor (class in bpy.types), 766
sensor_add() (in module bpy.ops.logic), 50
sensor_move() (in module bpy.ops.logic), 50
sensor_remove() (in module bpy.ops.logic), 50
sensors (bge.types.KX_GameObject attribute), 1146
sensors (bge.types.SCA_IController attribute), 1135
separate() (in module bpy.ops.armature), 19
separate() (in module bpy.ops.curve), 27
separate() (in module bpy.ops.mesh), 63
separator() (bpy.typesUILayout method), 978
seq_slide() (in module bpy.ops.transform), 119
Sequence (class in bpy.types), 767
Sequence.frame_duration (in module bpy.types), 768
Sequence.frame_offset_end (in module bpy.types), 768
Sequence.frame_offset_start (in module bpy.types), 768
Sequence.frame_still_end (in module bpy.types), 768
Sequence.frame_still_start (in module bpy.types), 768
Sequence.input_1 (in module bpy.types), 768
Sequence.input_2 (in module bpy.types), 768
Sequence.input_3 (in module bpy.types), 769
Sequence.input_count (in module bpy.types), 769
Sequence.type (in module bpy.types), 769
sequence_plugin_directory
 (bpy.types.UserPreferencesFilePaths attribute), 992
SequenceColorBalance (class in bpy.types), 770
SequenceCrop (class in bpy.types), 771
SequenceEditor (class in bpy.types), 773
SequenceEditor.meta_stack (in module bpy.types), 773
SequenceEditor.sequences (in module bpy.types), 773
SequenceEditor.sequences_all (in module bpy.types), 773
SequenceElement (class in bpy.types), 774
SequenceElement.orig_height (in module bpy.types), 774
SequenceElement.orig_width (in module bpy.types), 774
SequenceProxy (class in bpy.types), 775
sequencer_gl_preview (bpy.types.RenderSettings attribute), 732
sequencer_gl_render (bpy.types.RenderSettings attribute), 732
sequences (in module bpy.context), 6
SequenceTransform (class in bpy.types), 775
set_persistent_base() (in module bpy.ops.sculpt), 101
setActive()
 (bge.types.KX_PhysicsObjectWrapper method), 1162
setAmbientColor() (in module bge.render), 1220
setAngularVelocity()
 (bge.types.KX_GameObject method), 1150
setAngularVelocity() (bge.types.KX_PhysicsObjectWrapper method), 1163
setAttrib() (bge.types.BL_Shader method), 1138
setBackgroundColor() (in module bge.render), 1220
setBlending() (bge.types.KX_BlenderMaterial method), 1142
setBoolBernouilli()
 (bge.types.SCA_RandomActuator method), 1189
setBoolConst()
 (bge.types.SCA_RandomActuator method), 1189
setBoolUniform()
 (bge.types.SCA_RandomActuator method), 1189
setChannel() (bge.types.BL_ActionActuator method), 1137
setCollisionMargin()
 (bge.types.KX_GameObject method), 1153
setCustomMaterial()
 (bge.types.KX_PolygonMaterial method), 1169

setEyeSeparation() (in module bge.render), 1221
setFloatConst() (bge.types.SCA_RandomActuator method), 1189
setFloatNegativeExponential() (bge.types.SCA_RandomActuator method), 1189
setFloatNormal() (bge.types.SCA_RandomActuator method), 1189
setFloatUniform() (bge.types.SCA_RandomActuator method), 1189
setFocalLength() (in module bge.render), 1221
setGLSLMaterialSetting() (in module bge.render), 1221
setGravity() (in module bge.logic), 1208
setIntConst() (bge.types.SCA_RandomActuator method), 1189
setIntPoisson() (bge.types.SCA_RandomActuator method), 1189
setIntUniform() (bge.types.SCA_RandomActuator method), 1189
setLinearVelocity() (bge.types.KX_GameObject method), 1149
setLinearVelocity() (bge.types.KX_PhysicsObjectWrapper method), 1163
setLogicTicRate() (in module bge.logic), 1209
setMaterialMode() (in module bge.render), 1221
setMaxLogicFrame() (in module bge.logic), 1208
setMaxPhysicsFrame() (in module bge.logic), 1209
setMistColor() (in module bge.render), 1220
setMistEnd() (in module bge.render), 1220
setMistStart() (in module bge.render), 1220
setMousePosition() (in module bge.render), 1220
setNormal() (bge.types.KX_VertexProxy method), 1182
setNumberOfPasses() (bge.types.BL_Shader method), 1138
setOcclusion() (bge.types.KX_GameObject method), 1148
setOnTop() (bge.types.KX_Camera method), 1193
setParent() (bge.types.KX_GameObject method), 1151
setPhysicsTicRate() (in module bge.logic), 1209
setRGBA() (bge.types.KX_VertexProxy method), 1182
setRollInfluence() (bge.types.KX_VehicleWrapper method), 1179
setSampler() (bge.types.BL_Shader method), 1138
setSeed() (bge.types.SCA_RandomSensor method), 1190
setSource() (bge.types.BL_Shader method), 1138
setSteeringValue() (bge.types.KX_VehicleWrapper method), 1179
setSuspensionCompression() (bge.types.KX_VehicleWrapper method), 1179
setSuspensionDamping() (bge.types.KX_VehicleWrapper method), 1179
setSuspensionStiffness() (bge.types.KX_VehicleWrapper method), 1179
setTexture() (bge.types.KX_PolygonMaterial method), 1168
settings (bpy.types.ParticleSystem attribute), 676
setTyreFriction() (bge.types.KX_VehicleWrapper method), 1179
setUniform1f() (bge.types.BL_Shader method), 1138
setUniform1i() (bge.types.BL_Shader method), 1138
setUniform2f() (bge.types.BL_Shader method), 1138
setUniform2i() (bge.types.BL_Shader method), 1138
setUniform3f() (bge.types.BL_Shader method), 1138
setUniform3i() (bge.types.BL_Shader method), 1139
setUniform4f() (bge.types.BL_Shader method), 1139
setUniform4i() (bge.types.BL_Shader method), 1139
setUniformDef() (bge.types.BL_Shader method), 1139
setUniformfv() (bge.types.BL_Shader method), 1137
setUniformiv() (bge.types.BL_Shader method), 1140
setUniformMatrix3() (bge.types.BL_Shader method), 1139
setUniformMatrix4() (bge.types.BL_Shader method), 1140
setUV() (bge.types.KX_VertexProxy method), 1181
setUV2() (bge.types.KX_VertexProxy method), 1181
setViewport() (bge.types.KX_Camera method), 1193
setVisible() (bge.types.KX_GameObject method), 1147
setXYZ() (bge.types.KX_VertexProxy method), 1181
SEVENKEY (in module bge.events), 1224
shade_flat() (in module bpy.ops.curve), 27
shade_flat() (in module bpy.ops.object), 84
shade_smooth() (in module bpy.ops.curve), 27
shade_smooth() (in module bpy.ops.object), 84
shadedown (bpy.types.ThemeWidgetColors attribute), 943
ShaderNode (class in bpy.types), 777
ShaderNode.type (in module bpy.types), 777
ShaderNodeCameraData (class in bpy.types), 777
ShaderNodeCombineRGB (class in bpy.types), 778
ShaderNodeExtendedMaterial (class in bpy.types), 779
ShaderNodeGeometry (class in bpy.types), 780
ShaderNodeHueSaturation (class in bpy.types), 781
ShaderNodeInvert (class in bpy.types), 781
ShaderNodeMapping (class in bpy.types), 782
ShaderNodeMaterial (class in bpy.types), 783
ShaderNodeMath (class in bpy.types), 784
ShaderNodeMixRGB (class in bpy.types), 785
ShaderNodeNormal (class in bpy.types), 786
ShaderNodeOutput (class in bpy.types), 786
ShaderNodeRGB (class in bpy.types), 787
ShaderNodeRGBCurve (class in bpy.types), 788
ShaderNodeRGBCurve.mapping (in module bpy.types), 788
ShaderNodeRGBToBW (class in bpy.types), 789
ShaderNodes (class in bpy.types), 795

ShaderNodeSeparateRGB (class in bpy.types), 789
 ShaderNodeSqueeze (class in bpy.types), 790
 ShaderNodeTexture (class in bpy.types), 791
 ShaderNodeTree (class in bpy.types), 792
 ShaderNodeTree.nodes (in module bpy.types), 792
 ShaderNodeValToRGB (class in bpy.types), 792
 ShaderNodeValToRGB.color_ramp (in module bpy.types), 793
 ShaderNodeValue (class in bpy.types), 793
 ShaderNodeVectorCurve (class in bpy.types), 794
 ShaderNodeVectorCurve.mapping (in module bpy.types), 794
 ShaderNodeVectorMath (class in bpy.types), 795
 shaderText (bge.types.SCA_2DFilterActuator attribute), 1183
 shadetop (bpy.types.ThemeWidgetColors attribute), 943
 shadow (bpy.types.ThemeFontStyle attribute), 915
 SHADOW (in module blf), 1118
 shadow() (in module blf), 1119
 shadow_adaptive_threshold (bpy.types.AreaLamp attribute), 171
 shadow_adaptive_threshold (bpy.types.PointLamp attribute), 691
 shadow_adaptive_threshold (bpy.types.SpotLamp attribute), 857
 shadow_adaptive_threshold (bpy.types.SunLamp attribute), 868
 shadow_adjust (bpy.types.CompositorNodeChromaMatte attribute), 275
 shadow_buffer_bias (bpy.types.Material attribute), 523
 shadow_buffer_bias (bpy.types.SpotLamp attribute), 857
 shadow_buffer_clip_end (bpy.types.SpotLamp attribute), 858
 shadow_buffer_clip_start (bpy.types.SpotLamp attribute), 858
 shadow_buffer_samples (bpy.types.SpotLamp attribute), 858
 shadow_buffer_size (bpy.types.SpotLamp attribute), 858
 shadow_buffer_soft (bpy.types.SpotLamp attribute), 858
 shadow_buffer_type (bpy.types.SpotLamp attribute), 858
 shadow_cast_alpha (bpy.types.Material attribute), 523
 shadow_color (bpy.types.AreaLamp attribute), 171
 shadow_color (bpy.types.PointLamp attribute), 691
 shadow_color (bpy.types.SpotLamp attribute), 858
 shadow_color (bpy.types.SunLamp attribute), 868
 shadow_factor (bpy.types.LampTextureSlot attribute), 500
 shadow_filter_type (bpy.types.SpotLamp attribute), 858
 shadow_method (bpy.types.AreaLamp attribute), 172
 shadow_method (bpy.types.PointLamp attribute), 692
 shadow_method (bpy.types.SpotLamp attribute), 858
 shadow_method (bpy.types.SunLamp attribute), 868
 shadow_offset() (in module blf), 1120
 shadow_offset_x (bpy.types.ThemeFontStyle attribute), 915
 shadow_offset_y (bpy.types.ThemeFontStyle attribute), 915
 shadow_only_type (bpy.types.Material attribute), 523
 shadow_ray_bias (bpy.types.Material attribute), 523
 shadow_ray_sample_method (bpy.types.AreaLamp attribute), 172
 shadow_ray_sample_method (bpy.types.PointLamp attribute), 692
 shadow_ray_sample_method (bpy.types.SpotLamp attribute), 858
 shadow_ray_sample_method (bpy.types.SunLamp attribute), 868
 shadow_ray_samples (bpy.types.PointLamp attribute), 692
 shadow_ray_samples (bpy.types.SpotLamp attribute), 858
 shadow_ray_samples (bpy.types.SunLamp attribute), 868
 shadow_ray_samples_x (bpy.types.AreaLamp attribute), 172
 shadow_ray_samples_y (bpy.types.AreaLamp attribute), 172
 shadow_sample_buffers (bpy.types.SpotLamp attribute), 858
 shadow_soft_size (bpy.types.AreaLamp attribute), 172
 shadow_soft_size (bpy.types.PointLamp attribute), 692
 shadow_soft_size (bpy.types.SpotLamp attribute), 858
 shadow_soft_size (bpy.types.SunLamp attribute), 868
 shadowalpha (bpy.types.ThemeFontStyle attribute), 915
 shadowcolor (bpy.types.ThemeFontStyle attribute), 915
 shape (bpy.types.AreaLamp attribute), 172
 shape (bpy.types.FieldSettings attribute), 407
 shape (bpy.types.MaterialStrand attribute), 535
 shape_key_add() (bpy.types.Object method), 618
 shape_key_add() (in module bpy.ops.object), 84
 shape_key_clear() (in module bpy.ops.object), 84
 shape_key_mirror() (in module bpy.ops.object), 84
 shape_key_move() (in module bpy.ops.object), 84
 shape_key_remove() (in module bpy.ops.object), 84
 shape_key_transfer() (in module bpy.ops.object), 84
 shape_propagate_to_all() (in module bpy.ops.mesh), 63
 shape_threshold (bpy.types.GameSoftBodySettings attribute), 433
 ShapeActionActuator (class in bpy.types), 797
 ShapeKey (class in bpy.types), 798
 ShapeKey.data (in module bpy.types), 798
 ShapeKey.frame (in module bpy.types), 798
 ShapeKeyBezierPoint (class in bpy.types), 799
 ShapeKeyCurvePoint (class in bpy.types), 800
 ShapeKeyPoint (class in bpy.types), 801
 SHD_TANGENT (in module bge.logic), 1218
 shear (bpy.types.SoftBodySettings attribute), 815
 shear (bpy.types.TextCurve attribute), 878

shear() (in module bpy.ops.transform), 120
Shear() (mathutils.Matrix class method), 1058
shift (bpy.types.KeyMapItem attribute), 476
shift_x (bpy.types.Camera attribute), 244
shift_y (bpy.types.Camera attribute), 244
shininess (bge.types.KX_PolygonMaterial attribute), 1168
show_active() (in module bpy.ops.outliner), 88
show_actuators (bpy.types.GameObjectSettings attribute), 430
show_actuators_active_object (bpy.types.SpaceLogicEditor attribute), 832
show_actuators_active_states (bpy.types.SpaceLogicEditor attribute), 832
show_actuators_linked_controller (bpy.types.SpaceLogicEditor attribute), 832
show_actuators_selected_objects (bpy.types.SpaceLogicEditor attribute), 832
show_alive (bpy.types.ExplodeModifier attribute), 386
show_alive (bpy.types.ParticleInstanceModifier attribute), 655
show_all_edges (bpy.types.Mesh attribute), 549
show_all_objects_origin (bpy.types.SpaceView3D attribute), 846
show_armatures (bpy.types.DopeSheet attribute), 360
show_axes (bpy.types.Armature attribute), 175
show_axis (bpy.types.Object attribute), 616
show_axis_x (bpy.types.SpaceView3D attribute), 847
show_axis_y (bpy.types.SpaceView3D attribute), 847
show_axis_z (bpy.types.SpaceView3D attribute), 847
showBackdrop (bpy.types.SpaceNodeEditor attribute), 835
showBackground_images (bpy.types.SpaceView3D attribute), 847
showBone_custom_shapes (bpy.types.Armature attribute), 175
showBounds (bpy.types.Object attribute), 616
showBrush (bpy.types.Paint attribute), 641
showBrush_on_surface (bpy.types.Paint attribute), 641
showCache (bpy.types.SpaceTimeline attribute), 841
showCameras (bpy.types.DopeSheet attribute), 360
showColored_constraints (bpy.types.ThemeBoneColorSet attribute), 908
showColumn_layout (bpy.types.UserPreferencesView attribute), 1000
showCone (bpy.types.SpotLamp attribute), 858
showControllers (bpy.types.GameObjectSettings attribute), 430
showControllers_active_object (bpy.types.SpaceLogicEditor attribute), 832
showControllers_linked_controller (bpy.types.SpaceLogicEditor attribute), 832
showControllersSelected_objects (bpy.types.SpaceLogicEditor attribute), 832
showCursor (bpy.types.SpaceGraphEditor attribute), 827
showCurves (bpy.types.DopeSheet attribute), 360
showCyclic_dependencies() (in module bpy.ops.node), 70
showDead (bpy.types.ExplodeModifier attribute), 386
showDead (bpy.types.ParticleInstanceModifier attribute), 655
showDebug (bpy.types.GameProperty attribute), 432
showDebug_info (bpy.types.Driver attribute), 363
showDebug_properties (bpy.types.SceneGameData attribute), 750
showDebug_state (bpy.types.GameObjectSettings attribute), 430
showDouble_sided (bpy.types.Mesh attribute), 549
showEdge_bevel_weight (bpy.types.Mesh attribute), 549
showEdge_creature (bpy.types.Mesh attribute), 550
showEdge_seams (bpy.types.Mesh attribute), 550
showEdge_sharp (bpy.types.Mesh attribute), 550
showEdges (bpy.types.Mesh attribute), 550
showExpanded (bpy.types.ActionGroup attribute), 152
showExpanded (bpy.types.Actuator attribute), 155
showExpanded (bpy.types.BackgroundImage attribute), 185
showExpanded (bpy.types.Constraint attribute), 329
showExpanded (bpy.types.Controller attribute), 337
showExpanded (bpy.types.FModifier attribute), 395
showExpanded (bpy.types.KeyMapItem attribute), 477
showExpanded (bpy.types.Modifier attribute), 582
showExpanded (bpy.types.Sensor attribute), 766
showExpanded_children (bpy.types.KeyMap attribute), 474
showExpanded_items (bpy.types.KeyMap attribute), 474
showExpanded_summary (bpy.types.DopeSheet attribute), 360
showExtra_edge_length (bpy.types.Mesh attribute), 550
showExtra_face_angle (bpy.types.Mesh attribute), 550
showExtra_face_area (bpy.types.Mesh attribute), 550
showFaces (bpy.types.Mesh attribute), 550
showFaces (bpy.types.SpaceUVEditor attribute), 843
showFloor (bpy.types.SpaceView3D attribute), 847
showFrame_indicator (bpy.types.SpaceDopeSheetEditor attribute), 825
showFrame_indicator (bpy.types.SpaceGraphEditor attribute), 828
showFrame_indicator (bpy.types.SpaceNLA attribute), 833
showFrame_indicator (bpy.types.SpaceSequenceEditor attribute), 838
showFrame_indicator (bpy.types.SpaceTimeline attribute), 842
showFrame_numbers (bpy.types.AnimVizMotionPaths attribute), 167

show_framerate_profile (bpy.types.SceneGameData attribute), 750
 show_frames (bpy.types.SpaceSequenceEditor attribute), 838
 show_fullscreen (bpy.types.SceneGameData attribute), 751
 show_group_colors (bpy.types.Armature attribute), 175
 show_guide (bpy.types.Camera attribute), 245
 show_handles (bpy.types.Curve attribute), 344
 show_handles (bpy.types.SpaceGraphEditor attribute), 828
 show_health (bpy.types.ParticleSettings attribute), 665
 show_hidden (bpy.types.DopeSheet attribute), 361
 show_hidden (bpy.types.FileSelectParams attribute), 409
 show_hidden_files_datablocks (bpy.types.UserPreferencesFilePaths attribute), 992
 show_hierarchy() (in module bpy.ops.outliner), 88
 show_high_resolution (bpy.types.SmokeDomainSettings attribute), 807
 show_in_editmode (bpy.types.Modifier attribute), 582
 show_keyframe_action_all (bpy.types.AnimVizMotionPaths attribute), 167
 show_keyframe_highlight (bpy.types.AnimVizMotionPaths attribute), 167
 show_keyframe_numbers (bpy.types.AnimVizMotionPaths attribute), 167
 show_lamps (bpy.types.DopeSheet attribute), 361
 show_large_cursors (bpy.types.UserPreferencesView attribute), 1000
 show_lattices (bpy.types.DopeSheet attribute), 361
 show_limits (bpy.types.Camera attribute), 245
 show_line_highlight (bpy.types.SpaceTextEditor attribute), 840
 show_line_numbers (bpy.types.SpaceTextEditor attribute), 840
 show_low_resolution (bpy.types.Paint attribute), 641
 show_manipulator (bpy.types.SpaceView3D attribute), 847
 show_manipulator (bpy.types.UserPreferencesView attribute), 1000
 show_margin (bpy.types.SpaceTextEditor attribute), 840
 show_materials (bpy.types.DopeSheet attribute), 361
 show_menus (bpy.types.Area attribute), 170
 show_meshes (bpy.types.DopeSheet attribute), 361
 show_metaballs (bpy.types.DopeSheet attribute), 361
 show_mini_axis (bpy.types.UserPreferencesView attribute), 1000
 show_missing_nla (bpy.types.DopeSheet attribute), 361
 show_mist (bpy.types.Camera attribute), 245
 show_modified_edges (bpy.types.SpaceUVEditor attribute), 843
 show_mouse (bpy.types.SceneGameData attribute), 751
 show_name (bpy.types.Camera attribute), 245
 show_name (bpy.types.Object attribute), 616
 show_names (bpy.types.Armature attribute), 176
 show_nodes (bpy.types.DopeSheet attribute), 361
 show_normal_face (bpy.types.Curve attribute), 344
 show_normal_face (bpy.types.Mesh attribute), 550
 show_normal_vertex (bpy.types.Mesh attribute), 550
 show_normalized_coords (bpy.types.SpaceUVEditor attribute), 843
 show_number (bpy.types.ParticleSettings attribute), 666
 show_object_info (bpy.types.UserPreferencesView attribute), 1001
 show_on_cage (bpy.types.Modifier attribute), 582
 show_one_level() (in module bpy.ops.outliner), 88
 show_only_control_edges (bpy.types.MultiresModifier attribute), 592
 show_only_control_edges (bpy.types.SubsurfModifier attribute), 867
 show_only_ghost_selected (bpy.types.Armature attribute), 176
 show_only_group_objects (bpy.types.DopeSheet attribute), 361
 show_only_matching_fcurves (bpy.types.DopeSheet attribute), 361
 show_only_render (bpy.types.SpaceView3D attribute), 847
 show_only_selected (bpy.types.AnimVizOnionSkinning attribute), 168
 show_only_selected (bpy.types.DopeSheet attribute), 361
 show_only_selected (bpy.types.SpaceTimeline attribute), 842
 show_only_shape_key (bpy.types.Object attribute), 616
 show_other_objects (bpy.types.SpaceUVEditor attribute), 843
 show_outline_selected (bpy.types.SpaceView3D attribute), 847
 show_overlay (bpy.types.SequenceEditor attribute), 773
 show_particles (bpy.types.DopeSheet attribute), 361
 show_particles (bpy.types.ParticleEdit attribute), 651
 show_passepartout (bpy.types.Camera attribute), 245
 show_physics_visualization (bpy.types.SceneGameData attribute), 751
 show_pivot (bpy.types.RigidBodyJointConstraint attribute), 739
 show_playback_fps (bpy.types.UserPreferencesView attribute), 1001
 show_points (bpy.types.GPencilLayer attribute), 423
 show_pose_markers (bpy.types.SpaceDopeSheetEditor attribute), 825
 show_relationship_lines (bpy.types.SpaceView3D attribute), 847

show_render (bpy.types.Modifier attribute), 582
show_repeat (bpy.types.SpaceImageEditor attribute), 829
show_report_debug (bpy.types.SpaceInfo attribute), 831
show_report_error (bpy.types.SpaceInfo attribute), 831
show_report_info (bpy.types.SpaceInfo attribute), 831
show_report_operator (bpy.types.SpaceInfo attribute),
 831
show_report_warning (bpy.types.SpaceInfo attribute),
 831
show_restrict_columns (bpy.types.SpaceOutliner attribute), 836
show_safe_margin (bpy.types.SpaceSequenceEditor attribute), 838
show_scenes (bpy.types.DopeSheet attribute), 361
show_sensors (bpy.types.GameObjectSettings attribute),
 430
show_sensors_active_object
 (bpy.types.SpaceLogicEditor attribute), 832
show_sensors_active_states (bpy.types.SpaceLogicEditor attribute), 832
show_sensors_linked_controller
 (bpy.types.SpaceLogicEditor attribute), 832
show_sensors_selected_objects
 (bpy.types.SpaceLogicEditor attribute), 832
show_separate_color (bpy.types.SpaceSequenceEditor attribute), 838
show_shaded (bpy.types.ThemeWidgetColors attribute),
 943
show_shapekeys (bpy.types.DopeSheet attribute), 362
show_size (bpy.types.ParticleSettings attribute), 666
show_sliders (bpy.types.SpaceDopeSheetEditor attribute), 825
show_sliders (bpy.types.SpaceGraphEditor attribute), 828
show_smooth_edges (bpy.types.SpaceUVEditor attribute), 843
show_splash (bpy.types.UserPreferencesView attribute),
 1001
show_state_panel (bpy.types.GameObjectSettings attribute), 430
show_stretch (bpy.types.SpaceUVEditor attribute), 843
show_strip_curves (bpy.types.SpaceNLA attribute), 833
show_summary (bpy.types.DopeSheet attribute), 362
show_sync_view (bpy.types.RegionView3D attribute),
 718
show_syntax_highlight (bpy.types.SpaceTextEditor attribute), 840
show_texture_space (bpy.types.Object attribute), 616
show_textured_solid (bpy.types.SpaceView3D attribute),
 847
show_textures (bpy.types.DopeSheet attribute), 362
show_thumbnails (bpy.types.UserPreferencesFilePaths attribute), 992
show_title_safe (bpy.types.Camera attribute), 245
show_tooltips (bpy.types.UserPreferencesView attribute),
 1001
show_tooltips_python (bpy.types.UserPreferencesView attribute), 1001
show_tracer (bpy.types.ParticleFluidSettings attribute),
 653
show_transforms (bpy.types.DopeSheet attribute), 362
show_transparent (bpy.types.Object attribute), 616
show_unborn (bpy.types.ExplodeModifier attribute), 386
show_unborn (bpy.types.ParticleInstanceModifier attribute), 655
show_unborn (bpy.types.ParticleSettings attribute), 666
show_uv_local_view (bpy.types.ToolSettings attribute),
 950
show_velocity (bpy.types.ParticleSettings attribute), 666
show_view_name (bpy.types.UserPreferencesView attribute), 1001
show_viewport (bpy.types.Modifier attribute), 582
show_wire (bpy.types.Bone attribute), 230
show_wire (bpy.types.EditBone attribute), 370
show_wire (bpy.types.Object attribute), 616
show_word_wrap (bpy.types.SpaceTextEditor attribute),
 840
show_worlds (bpy.types.DopeSheet attribute), 362
show_x_ray (bpy.types.GPencilLayer attribute), 423
show_x_ray (bpy.types.Object attribute), 616
showMouse() (in module bge.render), 1220
shrink_fatten() (in module bpy.ops.transform), 120
shrinkwrap_type (bpy.types.ShrinkwrapConstraint attribute), 802
ShrinkwrapConstraint (class in bpy.types), 802
ShrinkwrapModifier (class in bpy.types), 803
sigma_color (bpy.types.CompositorNodeBilateralblur attribute), 271
sigma_space (bpy.types.CompositorNodeBilateralblur attribute), 271
SimpleDeformModifier (class in bpy.types), 804
simplify_ao_sss (bpy.types.RenderSettings attribute), 732
simplify_child_particles (bpy.types.RenderSettings attribute), 732
simplify_rate (bpy.types.ParticleSettings attribute), 666
simplify_resize (bpy.types.ParticleSettings attribute),
 666
simplify_shadow_samples (bpy.types.RenderSettings attribute), 733
simplify_subdivision (bpy.types.RenderSettings attribute), 733
simplify_transition (bpy.types.ParticleSettings attribute),
 666
simplify_viewport (bpy.types.ParticleSettings attribute),
 666
simulation_scale (bpy.types.DomainFluidSettings attribute), 358

single_axis_number (bpy.types.JoystickSensor attribute), 469
 SIXKEY (in module bge.events), 1224
 size (bpy.types.AreaLamp attribute), 172
 size (bpy.types.BackgroundImage attribute), 185
 size (bpy.types.Brush attribute), 237
 size (bpy.types.CastModifier attribute), 247
 size (bpy.types.CompositorNodeGlare attribute), 294
 size (bpy.types.CompositorNodeMapView attribute), 303
 size (bpy.types.FieldSettings attribute), 407
 size (bpy.types.MaterialHalo attribute), 528
 size (bpy.types.Particle attribute), 647
 size (bpy.types.ParticleBrush attribute), 648
 size (bpy.types.TextCurve attribute), 878
 size (bpy.types.WorldStarsSettings attribute), 1034
 size() (in module blf), 1120
 size_factor (bpy.types.ParticleSettingsTextureSlot attribute), 671
 size_min (bpy.types.MaterialStrand attribute), 535
 size_random (bpy.types.ParticleSettings attribute), 666
 size_x (bpy.types.CompositorNodeBlur attribute), 272
 size_x (bpy.types.MetaElement attribute), 576
 size_y (bpy.types.AreaLamp attribute), 172
 size_y (bpy.types.CompositorNodeBlur attribute), 272
 size_y (bpy.types.MetaElement attribute), 576
 size_z (bpy.types.MetaElement attribute), 576
 SKEY (in module bge.events), 1224
 sky_blend (bpy.types.LampSkySettings attribute), 498
 sky_blend_type (bpy.types.LampSkySettings attribute), 498
 sky_color_space (bpy.types.LampSkySettings attribute), 499
 sky_exposure (bpy.types.LampSkySettings attribute), 499
 SLASHKEY (in module bge.events), 1226
 slider_max (bpy.types.ShapeKey attribute), 798
 slider_min (bpy.types.ShapeKey attribute), 799
 slip_type (bpy.types.DomainFluidSettings attribute), 359
 slip_type (bpy.types.ObstacleFluidSettings attribute), 627
 slope (bpy.types.CompositorNodeColorBalance attribute), 276
 slot_copy() (in module bpy.ops.texture), 116
 slot_move() (in module bpy.ops.texture), 116
 slot_paste() (in module bpy.ops.texture), 116
 slow_parent_clear() (in module bpy.ops.object), 84
 slow_parent_set() (in module bpy.ops.object), 84
 slurph (bpy.types.Key attribute), 470
 small_caps_scale (bpy.types.TextCurve attribute), 878
 smart_project() (in module bpy.ops.uv), 129
 smoke (in module bpy.context), 8
 smoke_data_type (bpy.types.VoxelData attribute), 1015
 smoke_type (bpy.types.SMOKEModifier attribute), 810
 SmokeCollSettings (class in bpy.types), 806
 SmokeDomainSettings (class in bpy.types), 806
 SmokeDomainSettings.effector_weights (in module bpy.types), 807
 SmokeDomainSettings.point_cache (in module bpy.types), 807
 SmokeFlowSettings (class in bpy.types), 809
 SmokeModifier (class in bpy.types), 810
 SmokeModifier.coll_settings (in module bpy.types), 810
 SmokeModifier.domain_settings (in module bpy.types), 810
 SmokeModifier.flow_settings (in module bpy.types), 810
 smooth() (in module bpy.ops.curve), 27
 smooth() (in module bpy.ops.graph), 40
 smooth_emitter (bpy.types.SmokeDomainSettings attribute), 808
 smooth_radius() (in module bpy.ops.curve), 27
 smooth_stroke_factor (bpy.types.Brush attribute), 237
 smooth_stroke_radius (bpy.types.Brush attribute), 237
 smooth_view (bpy.types.UserPreferencesView attribute), 1001
 SmoothModifier (class in bpy.types), 811
 smoothscroll() (in module bpy.ops.file), 34
 smoothview() (in module bpy.ops.view3d), 134
 smpte_from_frame() (in module bpy.utils), 1045
 smpte_from_seconds() (in module bpy.utils), 1045
 snap() (in module bpy.ops.action), 13
 snap() (in module bpy.ops.graph), 40
 snap() (in module bpy.ops.nla), 67
 snap() (in module bpy.ops.sequencer), 106
 snap_cursor() (in module bpy.ops.uv), 129
 snap_cursor_to_active() (in module bpy.ops.view3d), 134
 snap_cursor_to_center() (in module bpy.ops.view3d), 134
 snap_cursor_to_grid() (in module bpy.ops.view3d), 134
 snap_cursor_to_selected() (in module bpy.ops.view3d), 134
 snap_element (bpy.types.ToolSettings attribute), 950
 snap_selected() (in module bpy.ops.uv), 129
 snap_selected_to_cursor() (in module bpy.ops.view3d), 134
 snap_selected_to_grid() (in module bpy.ops.view3d), 134
 snap_target (bpy.types.ToolSettings attribute), 950
 snap_type() (in module bpy.ops.transform), 121
 soft_body (in module bpy.context), 8
 SoftBodyModifier (class in bpy.types), 812
 SoftBodyModifier.point_cache (in module bpy.types), 812
 SoftBodyModifier.settings (in module bpy.types), 812
 SoftBodySettings (class in bpy.types), 813
 SoftBodySettings.effector_weights (in module bpy.types), 814
 solidify() (in module bpy.ops.mesh), 63
 SolidifyModifier (class in bpy.types), 817
 solver (bpy.types.Itasc attribute), 467
 sort_faces() (in module bpy.ops.mesh), 63
 sort_method (bpy.types.FileSelectParams attribute), 409

sound (bpy.types.SoundActuator attribute), 820
Sound (class in bpy.types), 818
Sound.packed_file (in module bpy.types), 818
sound_bake() (in module bpy.ops.graph), 40
sound_directory (bpy.types.UserPreferencesFilePaths attribute), 992
sound_strip_add() (in module bpy.ops.sequencer), 106
SoundActuator (class in bpy.types), 819
SoundSequence (class in bpy.types), 821
SoundSequence.sound (in module bpy.types), 821
source (bpy.types.EnvironmentMap attribute), 381
source (bpy.types.Image attribute), 453
space (bpy.types.CompositorNodeScale attribute), 312
Space (class in bpy.types), 823
Space.type (in module bpy.types), 823
space_character (bpy.types.TextCurve attribute), 878
space_line (bpy.types.TextCurve attribute), 878
space_word (bpy.types.TextCurve attribute), 878
SpaceConsole (class in bpy.types), 824
SpaceConsole.history (in module bpy.types), 824
SpaceConsole.scrollback (in module bpy.types), 824
spacedata_cleanup() (in module bpy.ops.screen), 100
SpaceDopeSheetEditor (class in bpy.types), 825
SpaceDopeSheetEditor.dopesheet (in module bpy.types), 825
SpaceDopeSheetEditor.show_seconds (in module bpy.types), 825
SpaceFileBrowser (class in bpy.types), 826
SpaceFileBrowser.operator (in module bpy.types), 826
SpaceFileBrowser.params (in module bpy.types), 826
SpaceGraphEditor (class in bpy.types), 827
SpaceGraphEditor.dopesheet (in module bpy.types), 827
SpaceGraphEditor.show_seconds (in module bpy.types), 828
SpaceImageEditor (class in bpy.types), 829
SpaceImageEditor.curve (in module bpy.types), 829
SpaceImageEditor.image_user (in module bpy.types), 829
SpaceImageEditor.sample_histogram (in module bpy.types), 829
SpaceImageEditor.scopes (in module bpy.types), 829
SpaceImageEditor.show_paint (in module bpy.types), 829
SpaceImageEditor.show_render (in module bpy.types), 829
SpaceImageEditor.show_uvedit (in module bpy.types), 830
SpaceImageEditor.uv_editor (in module bpy.types), 830
SpaceImageEditor.zoom (in module bpy.types), 830
SpaceInfo (class in bpy.types), 831
SPACEKEY (in module bge.events), 1226
SpaceLogicEditor (class in bpy.types), 832
SpaceNLA (class in bpy.types), 833
SpaceNLA.dopesheet (in module bpy.types), 833
SpaceNLA.show_seconds (in module bpy.types), 833
SpaceNodeEditor (class in bpy.types), 834
SpaceNodeEditor.id (in module bpy.types), 834
SpaceNodeEditor.id_from (in module bpy.types), 834
SpaceNodeEditor.node_tree (in module bpy.types), 835
SpaceOutliner (class in bpy.types), 835
SpaceProperties (class in bpy.types), 837
SpaceSequenceEditor (class in bpy.types), 838
SpaceSequenceEditor.grease_pencil (in module bpy.types), 838
SpaceTextEditor (class in bpy.types), 839
SpaceTimeline (class in bpy.types), 841
SpaceUserPreferences (class in bpy.types), 844
SpaceUVEditor (class in bpy.types), 842
SpaceView3D (class in bpy.types), 845
SpaceView3D.background_images (in module bpy.types), 845
SpaceView3D.current_orientation (in module bpy.types), 845
SpaceView3D.layers_used (in module bpy.types), 846
SpaceView3D.local_view (in module bpy.types), 846
SpaceView3D.region_3d (in module bpy.types), 846
SpaceView3D.region_quadview (in module bpy.types), 846
spacing (bpy.types.Brush attribute), 238
specular (bge.types.KX_PolygonMaterial attribute), 1168
specular_alpha (bpy.types.Material attribute), 523
specular_color (bpy.types.Material attribute), 523
specular_color (bpy.types.UserSolidLight attribute), 1003
specular_color_factor (bpy.types.MaterialTextureSlot attribute), 540
specular_factor (bpy.types.MaterialTextureSlot attribute), 540
specular_hardness (bpy.types.Material attribute), 523
specular_intensity (bpy.types.Material attribute), 523
specular_ior (bpy.types.Material attribute), 523
specular_ramp_blend (bpy.types.Material attribute), 524
specular_ramp_factor (bpy.types.Material attribute), 524
specular_ramp_input (bpy.types.Material attribute), 524
specular_shader (bpy.types.Material attribute), 524
specular_slope (bpy.types.Material attribute), 524
specular_toon_size (bpy.types.Material attribute), 524
specular_toon_smooth (bpy.types.Material attribute), 524
specularity (bge.types.KX_PolygonMaterial attribute), 1168
speed (bpy.types.BoidRuleAverageSpeed attribute), 219
speed (bpy.types.SoftBodySettings attribute), 815
speed (bpy.types.WaveModifier attribute), 1019
speed_factor (bpy.types.Sequence attribute), 769
speed_max (bpy.types.CompositorNodeVecBlur attribute), 323
speed_min (bpy.types.CompositorNodeVecBlur attribute), 323
speed_of_sound (aud.Device attribute), 1123
speed_scale (bpy.types.PointDensity attribute), 688
SpeedControlSequence (class in bpy.types), 848

sphere_project() (in module bpy.ops.uv), 129
 sphereInsideFrustum() (bge.types.KX_Camera method), 1191
 SPHFluidSettings (class in bpy.types), 741
 spin (bpy.types.CompositorNodeDBlur attribute), 286
 spin() (in module bpy.ops.curve), 27
 spin() (in module bpy.ops.mesh), 63
 splash() (in module bpy.ops.wm), 146
 Spline (class in bpy.types), 850
 Spline.bezier_points (in module bpy.types), 850
 Spline.character_index (in module bpy.types), 850
 Spline.point_count_u (in module bpy.types), 851
 Spline.point_count_v (in module bpy.types), 851
 Spline.points (in module bpy.types), 851
 spline_type_set() (in module bpy.ops.curve), 27
 spline_weight_set() (in module bpy.ops.curve), 27
 SplineBezierPoints (class in bpy.types), 853
 SplineIKConstraint (class in bpy.types), 853
 SplinePoint (class in bpy.types), 855
 SplinePoints (class in bpy.types), 856
 split() (bpy.typesUILayout method), 960
 split() (in module bpy.ops.mesh), 63
 split() (in module bpy.ops.nla), 67
 split_angle (bpy.types.EdgeSplitModifier attribute), 367
 spot_blend (bpy.types.SpotLamp attribute), 859
 spot_size (bpy.types.SpotLamp attribute), 859
 spotblend (bge.types.KX_LightObject attribute), 1156
 SpotLamp (class in bpy.types), 857
 SpotLamp.falloff_curve (in module bpy.types), 857
 spotsize (bge.types.KX_LightObject attribute), 1156
 spread (bpy.types.LampSkySettings attribute), 499
 spring_damping (bpy.types.ClothSettings attribute), 257
 spring_force (bpy.types.SPHFluidSettings attribute), 741
 spring_frames (bpy.types.SPHFluidSettings attribute), 742
 spring_length (bpy.types.SoftBodySettings attribute), 815
 squash (bpy.types.TextureNodeBricks attribute), 885
 squash_frequency (bpy.types.TextureNodeBricks attribute), 885
 sss_preset_add() (in module bpy.ops.material), 52
 stamp_background (bpy.types.RenderSettings attribute), 733
 stamp_font_size (bpy.types.RenderSettings attribute), 733
 stamp_foreground (bpy.types.RenderSettings attribute), 733
 stamp_note_text (bpy.types.RenderSettings attribute), 733
 standard_derivation (bpy.types.RandomActuator attribute), 713
 star_tip_count (bpy.types.MaterialHalo attribute), 529
 start (bpy.types.WorldMistSettings attribute), 1033
 start_cap (bpy.types.ArrayModifier attribute), 183
 start_frame_set() (in module bpy.ops.time), 116
 start_position_object (bpy.types.WaveModifier attribute), 1019
 start_position_x (bpy.types.WaveModifier attribute), 1019
 start_position_y (bpy.types.WaveModifier attribute), 1019
 start_time (bpy.types.ControlFluidSettings attribute), 335
 start_time (bpy.types.DomainFluidSettings attribute), 359
 startGame() (in module bge.logic), 1207
 state (bge.types.KX_GameObject attribute), 1146
 state (bge.types.SCA_IController attribute), 1135
 state_add() (in module bpy.ops.boid), 19
 state_del() (in module bpy.ops.boid), 19
 state_move_down() (in module bpy.ops.boid), 19
 state_move_up() (in module bpy.ops.boid), 19
 StateActuator (class in bpy.types), 860
 states (bpy.types.Controller attribute), 337
 states (bpy.types.StateActuator attribute), 860
 states_initial (bpy.types.GameObjectSettings attribute), 430
 states_visible (bpy.types.GameObjectSettings attribute), 430
 statistics() (bpy.types.Scene method), 746
 status (aud.Handle attribute), 1128
 status (bge.types.SCA_ISensor attribute), 1135
 step_count (bpy.types.Itasc attribute), 467
 step_max (bpy.types.Itasc attribute), 467
 step_max (bpy.types.SoftBodySettings attribute), 815
 step_method (bpy.types.MaterialVolume attribute), 545
 step_min (bpy.types.Itasc attribute), 468
 step_min (bpy.types.SoftBodySettings attribute), 815
 step_size (bpy.types.MaterialVolume attribute), 545
 steps (bpy.types.ParticleBrush attribute), 649
 steps (bpy.types.ScrewModifier attribute), 763
 stereo (bpy.types.SceneGameData attribute), 751
 stereo_eye_separation (bpy.types.SceneGameData attribute), 751
 stereo_mode (bpy.types.SceneGameData attribute), 751
 stickiness (bpy.types.CollisionSettings attribute), 263
 sticky_add() (in module bpy.ops.mesh), 64
 sticky_remove() (in module bpy.ops.mesh), 64
 sticky_select_mode (bpy.types.SpaceUVEditor attribute), 843
 stiff_viscosity (bpy.types.SPHFluidSettings attribute), 742
 stiffness (bpy.types.MetaElement attribute), 577
 stiffness (bpy.types.SPHFluidSettings attribute), 742
 still_frame (bpy.types.VoxelData attribute), 1015
 stitch() (in module bpy.ops.uv), 129
 stl() (in module bpy.ops.export_mesh), 29
 stl() (in module bpy.ops.import_mesh), 47
 stopDSP() (in module bge.logic), 1208
 streaks (bpy.types.CompositorNodeGlare attribute), 294
 strength (bpy.types.BoidSettings attribute), 226

strength (bpy.types.Brush attribute), 238
strength (bpy.types.DisplaceModifier attribute), 355
strength (bpy.types.FieldSettings attribute), 407
strength (bpy.types.FModifierNoise attribute), 402
strength (bpy.types.ParticleBrush attribute), 649
strength (bpy.types.SmokeDomainSettings attribute), 808
strength (bpy.types.WarpModifier attribute), 1017
stretchto_reset() (in module bpy.ops.constraint), 23
StretchToConstraint (class in bpy.types), 861
string (bpy.types.PropertyGroupItem attribute), 706
StringProperty (class in bpy.types), 862
StringProperty() (in module bpy.props), 1053
StringProperty.default (in module bpy.types), 862
StringProperty.length_max (in module bpy.types), 863
strip_time (bpy.types.NlaStrip attribute), 598
strips (bpy.types.ThemeNLAEditor attribute), 924
strips_selected (bpy.types.ThemeNLAEditor attribute), 924
strobe (bpy.types.AdjustmentSequence attribute), 159
strobe (bpy.types.EffectSequence attribute), 374
strobe (bpy.types.ImageSequence attribute), 458
strobe (bpy.types.MetaSequence attribute), 578
strobe (bpy.types.MovieSequence attribute), 587
strobe (bpy.types.MulticamSequence attribute), 589
strobe (bpy.types.SceneSequence attribute), 758
stroke_method (bpy.types.Brush attribute), 238
Struct (class in bpy.types), 864
Struct.base (in module bpy.types), 864
Struct.description (in module bpy.types), 864
Struct.functions (in module bpy.types), 864
Struct.identifier (in module bpy.types), 864
Struct.name (in module bpy.types), 864
Struct.name_property (in module bpy.types), 864
Struct.nested (in module bpy.types), 864
Struct.properties (in module bpy.types), 864
structural_stiffness (bpy.types.ClothSettings attribute), 257
structural_stiffness_max (bpy.types.ClothSettings attribute), 257
stucci_type (bpy.types.StucciTexture attribute), 865
StucciTexture (class in bpy.types), 865
StucciTexture.users_material (in module bpy.types), 865
StucciTexture.users_object_modifier (in module bpy.types), 865
style_set() (in module bpy.ops.font), 36
style_toggle() (in module bpy.ops.font), 36
subdivide() (in module bpy.ops.armature), 19
subdivide() (in module bpy.ops.curve), 28
subdivide() (in module bpy.ops.mesh), 64
subdivide() (in module bpy.ops.particle), 92
subdivision_set() (in module bpy.ops.object), 84
subdivision_type (bpy.types.MultiresModifier attribute), 592
subdivision_type (bpy.types.SubsurfModifier attribute), 867
subframes (bpy.types.ParticleSettings attribute), 666
subject (bge.types.KX_NetworkMessageActuator attribute), 1160
subject (bge.types.KX_NetworkMessageSensor attribute), 1160
subject (bpy.types.MessageActuator attribute), 572
subject (bpy.types.MessageSensor attribute), 573
subjects (bge.types.KX_NetworkMessageSensor attribute), 1160
subsurf_levels (bpy.types.ShrinkwrapModifier attribute), 803
SubsurfModifier (class in bpy.types), 867
subtarget (bge.types.BL_ArmatureActuator attribute), 1195
subtarget (bge.types.BL_ArmatureConstraint attribute), 1198
subtarget (bpy.types.ActionConstraint attribute), 150
subtarget (bpy.types.ChildOfConstraint attribute), 250
subtarget (bpy.types.ConstraintTarget attribute), 333
subtarget (bpy.types.CopyLocationConstraint attribute), 338
subtarget (bpy.types.CopyRotationConstraint attribute), 340
subtarget (bpy.types.CopyScaleConstraint attribute), 341
subtarget (bpy.types.CopyTransformsConstraint attribute), 342
subtarget (bpy.types.DampedTrackConstraint attribute), 352
subtarget (bpy.types.FloorConstraint attribute), 414
subtarget (bpy.types.HookModifier attribute), 447
subtarget (bpy.types.KinematicConstraint attribute), 495
subtarget (bpy.types.LimitDistanceConstraint attribute), 507
subtarget (bpy.types.LockedTrackConstraint attribute), 513
subtarget (bpy.types.PivotConstraint attribute), 681
subtarget (bpy.types.StretchToConstraint attribute), 861
subtarget (bpy.types.TrackToConstraint attribute), 953
subtarget (bpy.types.TransformConstraint attribute), 955
sun_brightness (bpy.types.LampSkySettings attribute), 499
sun_intensity (bpy.types.LampSkySettings attribute), 499
sun_size (bpy.types.LampSkySettings attribute), 499
SunLamp (class in bpy.types), 868
SunLamp.sky (in module bpy.types), 868
sunsky_preset_add() (in module bpy.ops.lamp), 49
surface_noobs (bpy.types.DomainFluidSettings attribute), 359
surface_smooth (bpy.types.DomainFluidSettings attribute), 359
surface_subdivisions (bpy.types.DomainFluidSettings attribute), 359

- SurfaceCurve (class in bpy.types), 869
 SurfaceModifier (class in bpy.types), 871
 suspend() (bge.types.KX_Scene method), 1175
 suspendDynamics() (bge.types.KX_GameObject method), 1150
 suspended (bge.types.KX_Scene attribute), 1174
 svg() (in module bpy.ops.import_curve), 46
 swap() (bpy.types.Sequence method), 769
 swap() (in module bpy.ops.nla), 67
 swap() (in module bpy.ops.sequencer), 107
 swap_data() (in module bpy.ops.sequencer), 107
 swap_inputs() (in module bpy.ops.sequencer), 107
 switch_direction() (in module bpy.ops.armature), 19
 switch_direction() (in module bpy.ops.curve), 28
 sync_mode (bpy.types.Scene attribute), 745
 syntax_builtin (bpy.types.ThemeTextEditor attribute), 933
 syntax_comment (bpy.types.ThemeTextEditor attribute), 933
 syntax_numbers (bpy.types.ThemeTextEditor attribute), 933
 syntax_special (bpy.types.ThemeTextEditor attribute), 934
 syntax_string (bpy.types.ThemeTextEditor attribute), 934
 sysinfo() (in module bpy.ops.wm), 146
 system (bpy.types.ParticleTarget attribute), 680
 system (bpy.types.UnitSettings attribute), 985
 system_rotation (bpy.types.UnitSettings attribute), 985
- T**
- tab_width (bpy.types.SpaceTextEditor attribute), 840
 TABKEY (in module bge.events), 1226
 tag (bpy.types.ID attribute), 448
 tag() (bpy.typesBlendDataActions method), 191
 tag() (bpy.typesBlendDataArmatures method), 192
 tag() (bpy.typesBlendDataBrushes method), 193
 tag() (bpy.typesBlendDataCameras method), 194
 tag() (bpy.typesBlendDataCurves method), 195
 tag() (bpy.typesBlendDataFonts method), 196
 tag() (bpy.typesBlendDataGreasePencils method), 197
 tag() (bpy.typesBlendDataGroups method), 198
 tag() (bpy.typesBlendDataImages method), 199
 tag() (bpy.typesBlendDataLamps method), 200
 tag() (bpy.typesBlendDataLattices method), 201
 tag() (bpy.typesBlendDataLibraries method), 202
 tag() (bpy.typesBlendDataMaterials method), 204
 tag() (bpy.typesBlendDataMeshes method), 205
 tag() (bpy.typesBlendDataMetaBalls method), 206
 tag() (bpy.typesBlendDataNodeTrees method), 207
 tag() (bpy.typesBlendDataObjects method), 208
 tag() (bpy.typesBlendDataParticles method), 209
 tag() (bpy.typesBlendDataScreens method), 211
 tag() (bpy.typesBlendDataSounds method), 211
 tag() (bpy.typesBlendDataTexts method), 212
- tag() (bpy.typesBlendDataTextures method), 214
 tag() (bpy.typesBlendDataWindowManagers method), 214
 tag() (bpy.typesBlendDataWorlds method), 215
 tag_redraw() (bpy.typesArea method), 170
 tag_redraw() (bpy.typesRegion method), 717
 tail (bge.typesBL_ArmatureBone attribute), 1204
 tail (bpy.typesBone attribute), 230
 tail (bpy.typesEditBone attribute), 370
 tail_local (bpy.typesBone attribute), 230
 tail_radius (bpy.typesBone attribute), 230
 tail_radius (bpy.typesEditBone attribute), 370
 tangent_factor (bpy.typesParticleSettings attribute), 666
 tangent_phase (bpy.typesParticleSettings attribute), 666
 tap (bge.typesSCA_ISensor attribute), 1134
 taper_object (bpy.typesCurve attribute), 344
 target (bge.typesBL_ArmatureActuator attribute), 1195
 target (bge.typesBL_ArmatureConstraint attribute), 1198
 target (bpy.typesActionConstraint attribute), 150
 target (bpy.typesArmatureActuator attribute), 177
 target (bpy.typesChildOfConstraint attribute), 250
 target (bpy.typesClampToConstraint attribute), 252
 target (bpy.typesConstraintTarget attribute), 333
 target (bpy.typesCopyLocationConstraint attribute), 338
 target (bpy.typesCopyRotationConstraint attribute), 340
 target (bpy.typesCopyScaleConstraint attribute), 341
 target (bpy.typesCopyTransformsConstraint attribute), 342
 target (bpy.typesDampedTrackConstraint attribute), 352
 target (bpy.typesFloorConstraint attribute), 414
 target (bpy.typesFollowPathConstraint attribute), 418
 target (bpy.typesKeyboardSensor attribute), 484
 target (bpy.typesKinematicConstraint attribute), 495
 target (bpy.typesLimitDistanceConstraint attribute), 507
 target (bpy.typesLockedTrackConstraint attribute), 513
 target (bpy.typesPivotConstraint attribute), 681
 target (bpy.typesRigidBodyJointConstraint attribute), 739
 target (bpy.typesShrinkwrapConstraint attribute), 802
 target (bpy.typesShrinkwrapModifier attribute), 803
 target (bpy.typesSplineIKConstraint attribute), 854
 target (bpy.typesStretchToConstraint attribute), 861
 target (bpy.typesTrackToConstraint attribute), 953
 target (bpy.typesTransformConstraint attribute), 955
 target_count (bpy.typesPythonConstraint attribute), 708
 target_move_down() (in module bpy.ops.particle), 92
 target_move_up() (in module bpy.ops.particle), 92
 target_remove() (in module bpy.ops.particle), 92
 target_space (bpy.typesConstraint attribute), 329
 targetProperty (bge.typesSCA_KeyboardSensor attribute), 1186
 tempdir (in module bpy.app), 1047
 temperature (bpy.typesSmokeFlowSettings attribute), 809

template_any_ID() (bpy.typesUILayout method), 978
template_color_ramp() (bpy.typesUILayout method), 979
template_color_wheel() (bpy.typesUILayout method), 980
template_constraint() (bpy.typesUILayout method), 979
template_curve_mapping() (bpy.typesUILayout method), 979
template_edit_mode_selection() (bpy.typesUILayout method), 981
template_header() (bpy.typesUILayout method), 978
template_header_3D() (bpy.typesUILayout method), 981
template_histogram() (bpy.typesUILayout method), 980
template_ID() (bpy.typesUILayout method), 978
template_ID_preview() (bpy.typesUILayout method), 978
template_image() (bpy.typesUILayout method), 981
template_image_layers() (bpy.typesUILayout method), 981
template_layers() (bpy.typesUILayout method), 980
template_list() (bpy.typesUILayout method), 981
template_modifier() (bpy.typesUILayout method), 979
template_operator_search() (bpy.typesUILayout method), 981
template_path_builder() (bpy.typesUILayout method), 979
template_preview() (bpy.typesUILayout method), 979
template_reports_banner() (bpy.typesUILayout method), 981
template_running_jobs() (bpy.typesUILayout method), 981
template_vectorscope() (bpy.typesUILayout method), 980
template_waveform() (bpy.typesUILayout method), 980
temporary_directory (bpy.types.UserPreferencesFilePaths attribute), 993
tessellate_polygon() (in module mathutils.geometry), 1088
test_break() (bpy.types.RenderEngine method), 721
test_type (bpy.types.ArmatureSensor attribute), 181
texco_mesh (bpy.types.Mesh attribute), 550
TexMapping (class in bpy.types), 872
texspace_location (bpy.types.Curve attribute), 345
texspace_location (bpy.types.Mesh attribute), 550
texspace_location (bpy.types.MetaBall attribute), 574
texspace_size (bpy.types.Curve attribute), 345
texspace_size (bpy.types.Mesh attribute), 551
texspace_size (bpy.types.MetaBall attribute), 574
text (bpy.types.Panel attribute), 645
text (bpy.types.PythonConstraint attribute), 708
text (bpy.types.PythonController attribute), 710
text (bpy.types.SpaceTextEditor attribute), 840
text (bpy.types.ThemeAudioWindow attribute), 907
text (bpy.types.ThemeConsole attribute), 910
text (bpy.types.ThemeDopeSheet attribute), 912
text (bpy.types.ThemeFileBrowser attribute), 914
text (bpy.types.ThemeGraphEditor attribute), 918
text (bpy.types.ThemeImageEditor attribute), 920
text (bpy.types.ThemeInfo attribute), 921
text (bpy.types.ThemeLogicEditor attribute), 922
text (bpy.types.ThemeNLAEditor attribute), 924
text (bpy.types.ThemeNodeEditor attribute), 926
text (bpy.types.ThemeOutliner attribute), 928
text (bpy.types.ThemeProperties attribute), 929
text (bpy.types.ThemeSequenceEditor attribute), 931
text (bpy.types.ThemeTextEditor attribute), 934
text (bpy.types.ThemeTimeline attribute), 935
text (bpy.types.ThemeUserPreferences attribute), 938
text (bpy.types.ThemeView3D attribute), 941
text (bpy.types.ThemeWidgetColors attribute), 943
Text (class in bpy.types), 873
Text.current_character (in module bpy.types), 873
Text.current_line (in module bpy.types), 873
Text.is_dirty (in module bpy.types), 873
Text.is_in_memory (in module bpy.types), 873
Text.is_modified (in module bpy.types), 873
Text.lines (in module bpy.types), 873
Text.markers (in module bpy.types), 873
Text.select_end_character (in module bpy.types), 873
Text.select_end_line (in module bpy.types), 873
Text.users_logic (in module bpy.types), 874
text_add() (in module bpy.ops.object), 85
text_copy() (in module bpy.ops.font), 36
text_cut() (in module bpy.ops.font), 36
text_hi (bpy.types.ThemeAudioWindow attribute), 907
text_hi (bpy.types.ThemeConsole attribute), 910
text_hi (bpy.types.ThemeDopeSheet attribute), 912
text_hi (bpy.types.ThemeFileBrowser attribute), 914
text_hi (bpy.types.ThemeGraphEditor attribute), 918
text_hi (bpy.types.ThemeImageEditor attribute), 920
text_hi (bpy.types.ThemeInfo attribute), 921
text_hi (bpy.types.ThemeLogicEditor attribute), 922
text_hi (bpy.types.ThemeNLAEditor attribute), 924
text_hi (bpy.types.ThemeNodeEditor attribute), 926
text_hi (bpy.types.ThemeOutliner attribute), 928
text_hi (bpy.types.ThemeProperties attribute), 929
text_hi (bpy.types.ThemeSequenceEditor attribute), 931
text_hi (bpy.types.ThemeTextEditor attribute), 934
text_hi (bpy.types.ThemeTimeline attribute), 935
text_hi (bpy.types.ThemeUserPreferences attribute), 938
text_hi (bpy.types.ThemeView3D attribute), 942
text_insert() (in module bpy.ops.font), 37
text_paste() (in module bpy.ops.font), 37
text_sel (bpy.types.ThemeWidgetColors attribute), 943
TextBox (class in bpy.types), 875
textbox_add() (in module bpy.ops.font), 37
textbox_remove() (in module bpy.ops.font), 37
TextCharacterFormat (class in bpy.types), 876

TextCurve (class in bpy.types), 877
 TextCurve.body_format (in module bpy.types), 877
 TextCurve.edit_format (in module bpy.types), 877
 TextCurve.text_boxes (in module bpy.types), 878
 TextLine (class in bpy.types), 880
 TextMarker (class in bpy.types), 880
 TextMarker.character_index_end (in module bpy.types), 880
 TextMarker.character_index_start (in module bpy.types), 881
 TextMarker.group (in module bpy.types), 881
 TextMarker.is_temporary (in module bpy.types), 881
 TextMarker.line (in module bpy.types), 881
 TextMarker.use_edit_all (in module bpy.types), 881
 texture (bge.types.KX_PolygonMaterial attribute), 1167
 texture (bge.types.KX_PolyProxy attribute), 1163
 texture (bpy.types.Brush attribute), 238
 texture (bpy.types.CompositorNodeTexture attribute), 317
 texture (bpy.types.DisplaceModifier attribute), 355
 texture (bpy.types.EffectorWeights attribute), 377
 texture (bpy.types.FieldSettings attribute), 407
 texture (bpy.types.ShaderNodeTexture attribute), 791
 texture (bpy.types.TextureNodeTexture attribute), 898
 texture (bpy.types.TextureSlot attribute), 904
 texture (bpy.types.WarpModifier attribute), 1017
 texture (bpy.types.WaveModifier attribute), 1019
 Texture (class in bpy.types), 882
 texture (in module bpy.context), 8
 Texture.animation_data (in module bpy.types), 882
 Texture.color_ramp (in module bpy.types), 882
 Texture.node_tree (in module bpy.types), 882
 Texture.users_material (in module bpy.types), 883
 Texture.users_object_modifier (in module bpy.types), 883
 texture_angle_source_no_random (bpy.types.Brush attribute), 238
 texture_angle_source_random (bpy.types.Brush attribute), 238
 texture_collection_rate (bpy.types.UserPreferencesSystem attribute), 997
 texture_context (bpy.types.SpaceProperties attribute), 837
 texture_coords (bpy.types.DisplaceModifier attribute), 355
 texture_coords (bpy.types.LampTextureSlot attribute), 500
 texture_coords (bpy.types.MaterialTextureSlot attribute), 540
 texture_coords (bpy.types.ParticleSettingsTextureSlot attribute), 671
 texture_coords (bpy.types.WarpModifier attribute), 1017
 texture_coords (bpy.types.WaveModifier attribute), 1019
 texture_coords (bpy.types.WorldTextureSlot attribute), 1035
 texture_coords_object (bpy.types.DisplaceModifier attribute), 355
 texture_coords_object (bpy.types.WarpModifier attribute), 1017
 texture_coords_object (bpy.types.WaveModifier attribute), 1019
 texture_directory (bpy.types.UserPreferencesFilePaths attribute), 993
 texture_factor (bpy.types.MaterialSubsurfaceScattering attribute), 537
 texture_mesh (bpy.types.Mesh attribute), 551
 texture_mode (bpy.types.FieldSettings attribute), 407
 texture_nabla (bpy.types.FieldSettings attribute), 407
 texture_overlay_alpha (bpy.types.Brush attribute), 238
 texture_paint_toggle() (in module bpy.ops.paint), 89
 texture_plugin_directory (bpy.types.UserPreferencesFilePaths attribute), 993
 texture_sample_bias (bpy.types.Brush attribute), 238
 texture_slot (in module bpy.context), 8
 texture_time_out (bpy.types.UserPreferencesSystem attribute), 998
 texture_type (bpy.types.SpaceNodeEditor attribute), 835
 TextureNode (class in bpy.types), 884
 TextureNode.type (in module bpy.types), 884
 TextureNodeBricks (class in bpy.types), 885
 TextureNodeChecker (class in bpy.types), 886
 TextureNodeCompose (class in bpy.types), 887
 TextureNodeCoordinates (class in bpy.types), 887
 TextureNodeCurveRGB (class in bpy.types), 888
 TextureNodeCurveRGB.mapping (in module bpy.types), 888
 TextureNodeCurveTime (class in bpy.types), 889
 TextureNodeCurveTime.curve (in module bpy.types), 889
 TextureNodeDecompose (class in bpy.types), 890
 TextureNodeDistance (class in bpy.types), 890
 TextureNodeHueSaturation (class in bpy.types), 891
 TextureNodeImage (class in bpy.types), 892
 TextureNodeInvert (class in bpy.types), 892
 TextureNodeMath (class in bpy.types), 893
 TextureNodeMixRGB (class in bpy.types), 894
 TextureNodeOutput (class in bpy.types), 895
 TextureNodeRGBToBW (class in bpy.types), 896
 TextureNodeRotate (class in bpy.types), 896
 TextureNodes (class in bpy.types), 902
 TextureNodeScale (class in bpy.types), 897
 TextureNodeTexture (class in bpy.types), 898
 TextureNodeTranslate (class in bpy.types), 898
 TextureNodeTree (class in bpy.types), 899
 TextureNodeTree.nodes (in module bpy.types), 899
 TextureNodeValToNor (class in bpy.types), 900
 TextureNodeValToRGB (class in bpy.types), 901
 TextureNodeValToRGB.color_ramp (in module bpy.types), 901
 TextureNodeViewer (class in bpy.types), 902

TextureSlot (class in bpy.types), 903
TextureSlot.name (in module bpy.types), 904
tface (bge.types.KX_PolygonMaterial attribute), 1167
Theme (class in bpy.types), 905
Theme.bone_color_sets (in module bpy.types), 905
Theme.console (in module bpy.types), 905
Theme.dopesheet_editor (in module bpy.types), 905
Theme.file_browser (in module bpy.types), 905
Theme.graph_editor (in module bpy.types), 905
Theme.image_editor (in module bpy.types), 905
Theme.info (in module bpy.types), 905
Theme.logic_editor (in module bpy.types), 905
Theme.nla_editor (in module bpy.types), 905
Theme.node_editor (in module bpy.types), 905
Theme.outliner (in module bpy.types), 906
Theme.properties (in module bpy.types), 906
Theme.sequence_editor (in module bpy.types), 906
Theme.text_editor (in module bpy.types), 906
Theme.timeline (in module bpy.types), 906
Theme.user_interface (in module bpy.types), 906
Theme.user_preferences (in module bpy.types), 906
Theme.view_3d (in module bpy.types), 906
theme_area (bpy.types.Theme attribute), 906
ThemeAudioWindow (class in bpy.types), 907
ThemeBoneColorSet (class in bpy.types), 908
ThemeConsole (class in bpy.types), 909
ThemeDopeSheet (class in bpy.types), 911
ThemeFileBrowser (class in bpy.types), 913
ThemeFontStyle (class in bpy.types), 915
ThemeGraphEditor (class in bpy.types), 916
ThemeImageEditor (class in bpy.types), 919
ThemeInfo (class in bpy.types), 921
ThemeLogicEditor (class in bpy.types), 922
ThemeNLAEditor (class in bpy.types), 923
ThemeNodeEditor (class in bpy.types), 925
ThemeOutliner (class in bpy.types), 927
ThemeProperties (class in bpy.types), 928
ThemeSequenceEditor (class in bpy.types), 930
ThemeStyle (class in bpy.types), 932
ThemeStyle.panel_title (in module bpy.types), 932
ThemeStyle.widget (in module bpy.types), 932
ThemeStyle.widget_label (in module bpy.types), 932
ThemeTextEditor (class in bpy.types), 933
ThemeTimeline (class in bpy.types), 934
ThemeUserInterface (class in bpy.types), 936
ThemeUserInterface.wcol_box (in module bpy.types), 936
ThemeUserInterface.wcol_list_item (in module bpy.types), 936
ThemeUserInterface.wcol_menu (in module bpy.types), 936
ThemeUserInterface.wcol_menu_back (in module bpy.types), 936
ThemeUserInterface.wcol_menu_item (in module bpy.types), 936
ThemeUserInterface.wcol_num (in module bpy.types), 936
ThemeUserInterface.wcol_numslider (in module bpy.types), 936
ThemeUserInterface.wcol_option (in module bpy.types), 936
ThemeUserInterface.wcol_progress (in module bpy.types), 936
ThemeUserInterface.wcol_pulldown (in module bpy.types), 936
ThemeUserInterface.wcol_radio (in module bpy.types), 937
ThemeUserInterface.wcol_regular (in module bpy.types), 937
ThemeUserInterface.wcol_scroll (in module bpy.types), 937
ThemeUserInterface.wcol_state (in module bpy.types), 937
ThemeUserInterface.wcol_text (in module bpy.types), 937
ThemeUserInterface.wcol_toggle (in module bpy.types), 937
ThemeUserInterface.wcol_tool (in module bpy.types), 937
ThemeUserPreferences (class in bpy.types), 938
ThemeView3D (class in bpy.types), 939
ThemeWidgetColors (class in bpy.types), 943
ThemeWidgetStateColors (class in bpy.types), 944
thickness (bpy.types.SolidifyModifier attribute), 817
thickness_inner (bpy.types.CollisionSettings attribute), 263
thickness_outer (bpy.types.CollisionSettings attribute), 263
threads (bpy.types.RenderSettings attribute), 733
threads_mode (bpy.types.RenderSettings attribute), 733
THREEKEY (in module bge.events), 1224
threshold (bge.types.SCA_JoystickSensor attribute), 1185
threshold (bpy.types.CompositorNodeChromaMatte attribute), 275
threshold (bpy.types.CompositorNodeDefocus attribute), 287
threshold (bpy.types.CompositorNodeGlare attribute), 294
threshold (bpy.types.GlowSequence attribute), 436
threshold (bpy.types.MetaBall attribute), 574
threshold (bpy.types.WorldLighting attribute), 1031
tile (bge.types.KX_PolygonMaterial attribute), 1167
tile_set() (in module bpy.ops.uv), 130
tiles (bpy.types.ThemeFileBrowser attribute), 914
tiles_x (bpy.types.Image attribute), 453
tiles_y (bpy.types.Image attribute), 453

tilexrep (bge.types.KX_PolygonMaterial attribute), 1167
 tileyrep (bge.types.KX_PolygonMaterial attribute), 1167
 tilt (bpy.types.BezierSplinePoint attribute), 187
 tilt (bpy.types.ShapeKeyCurvePoint attribute), 800
 tilt (bpy.types.SplinePoint attribute), 855
 tilt() (in module bpy.ops.transform), 121
 tilt_clear() (in module bpy.ops.curve), 28
 tilt_interpolation (bpy.types.Spline attribute), 851
 time (bge.types.KX_ConstraintActuator attribute), 1143
 time (bge.types.KX_SCA_AddObjectActuator attribute), 1172
 time (bge.types.KX_TrackToActuator attribute), 1177
 time (bpy.types.ConstraintActuator attribute), 331
 time (bpy.types.EditObjectActuator attribute), 373
 time (bpy.types.OperatorMousePath attribute), 636
 time (bpy.types.OperatorStrokeElement attribute), 638
 time (bpy.types.ParticleHairKey attribute), 654
 time (bpy.types.ParticleKey attribute), 656
 time (bpy.types.ParticleTarget attribute), 680
 time_factor (bpy.types.ParticleSettingsTextureSlot attribute), 671
 time_offset (bpy.types.Object attribute), 616
 time_offset (bpy.types.WaveModifier attribute), 1019
 time_scale (bpy.types.SmokeDomainSettings attribute), 808
 time_toggle() (in module bpy.ops.anim), 16
 time_tweak (bpy.types.ParticleSettings attribute), 667
 timecode_style (bpy.types.UserPreferencesView attribute), 1001
 TimelineMarker (class in bpy.types), 945
 TimelineMarkers (class in bpy.types), 946
 timeOffset (bge.types.KX_GameObject attribute), 1146
 Timer (class in bpy.types), 947
 Timer.time_delta (in module bpy.types), 947
 Timer.time_duration (in module bpy.types), 947
 Timer.time_step (in module bpy.types), 947
 timestep (bpy.types.ParticleSettings attribute), 667
 tip_size (bpy.types.MaterialStrand attribute), 535
 title (bpy.types.ThemeAudioWindow attribute), 907
 title (bpy.types.ThemeConsole attribute), 910
 title (bpy.types.ThemeDopeSheet attribute), 912
 title (bpy.types.ThemeFileBrowser attribute), 914
 title (bpy.types.ThemeGraphEditor attribute), 918
 title (bpy.types.ThemeImageEditor attribute), 920
 title (bpy.types.ThemeInfo attribute), 921
 title (bpy.types.ThemeLogicEditor attribute), 923
 title (bpy.types.ThemeNLAEditor attribute), 924
 title (bpy.types.ThemeNodeEditor attribute), 926
 title (bpy.types.ThemeOutliner attribute), 928
 title (bpy.types.ThemeProperties attribute), 929
 title (bpy.types.ThemeSequenceEditor attribute), 931
 title (bpy.types.ThemeTextEditor attribute), 934
 title (bpy.types.ThemeTimeline attribute), 935
 title (bpy.types.ThemeUserPreferences attribute), 938
 title (bpy.types.ThemeView3D attribute), 942
 TKEY (in module bge.events), 1224
 to_2d() (mathutils.Vector method), 1067
 to_3d() (mathutils.Vector method), 1067
 to_3d_object() (in module bpy.ops.text), 115
 to_3x3() (mathutils.Matrix method), 1060
 to_4d() (mathutils.Vector method), 1067
 to_4x4() (mathutils.Matrix method), 1060
 to_euler() (mathutils.Matrix method), 1060
 to_euler() (mathutils.Quaternion method), 1063
 to_matrix() (mathutils.Euler method), 1057
 to_matrix() (mathutils.Quaternion method), 1063
 to_max_x (bpy.types.TransformConstraint attribute), 955
 to_max_y (bpy.types.TransformConstraint attribute), 955
 to_max_z (bpy.types.TransformConstraint attribute), 955
 to_mesh() (bpy.types.Object method), 618
 to_min_x (bpy.types.TransformConstraint attribute), 955
 to_min_y (bpy.types.TransformConstraint attribute), 956
 to_min_z (bpy.types.TransformConstraint attribute), 956
 to_property (bpy.types.MessageActuator attribute), 572
 to_quaternion() (mathutils.Euler method), 1057
 to_quaternion() (mathutils.Matrix method), 1060
 to_scale() (mathutils.Matrix method), 1060
 to_track_quat() (mathutils.Vector method), 1067
 to_translation() (mathutils.Matrix method), 1060
 to_tuple() (mathutils.Vector method), 1068
 toggleProperty (bge.types.SCA_KeyboardSensor attribute), 1186
 tolerance (bpy.types.CompositorNodeChromaMatte attribute), 275
 tolerance (bpy.types.CompositorNodeDiffMatte attribute), 288
 tolerance (bpy.types.CompositorNodeDistanceMatte attribute), 291
 tonemap_type (bpy.types.CompositorNodeTonemap attribute), 319
 tool (bpy.types.ParticleEdit attribute), 651
 toolbox() (in module bpy.ops.buttons), 21
 ToolSettings (class in bpy.types), 948
 ToolSettings.image_paint (in module bpy.types), 949
 ToolSettings.particle_edit (in module bpy.types), 949
 ToolSettings.sculpt (in module bpy.types), 949
 ToolSettings.vertex_paint (in module bpy.types), 951
 ToolSettings.weight_paint (in module bpy.types), 951
 toolshelf() (in module bpy.ops.view3d), 135
 torque (bge.types.KX_ObjectActuator attribute), 1161
 torque (bpy.types.ObjectActuator attribute), 623
 tosphere() (in module bpy.ops.transform), 121
 TouchSensor (class in bpy.types), 952
 tracer_particles (bpy.types.DomainFluidSettings attribute), 359
 track_axis (bpy.types.DampedTrackConstraint attribute), 352

track_axis (bpy.types.LockedTrackConstraint attribute), 513
track_axis (bpy.types.Object attribute), 616
track_axis (bpy.types.TrackToConstraint attribute), 953
track_clear() (in module bpy.ops.object), 85
track_object (bpy.types.EditObjectActuator attribute), 373
track_set() (in module bpy.ops.object), 85
trackball() (in module bpy.ops.transform), 122
tracks_add() (in module bpy.ops.nla), 67
TrackToConstraint (class in bpy.types), 953
trail_count (bpy.types.ParticleSettings attribute), 667
transform (bpy.types.ThemeView3D attribute), 942
transform() (bpy.types.EditBone method), 371
transform() (bpy.types.Mesh method), 552
transform() (in module bpy.ops.transform), 122
transform_apply() (in module bpy.ops.object), 85
transform_channel (bpy.types.ActionConstraint attribute), 150
transform_orientation (bpy.types.SpaceView3D attribute), 847
transform_type (bpy.types.DriverTarget attribute), 364
TransformConstraint (class in bpy.types), 954
TransformOrientation (class in bpy.types), 957
transforms_clear() (in module bpy.ops.pose), 95
TransformSequence (class in bpy.types), 957
transition_add() (in module bpy.ops.nla), 67
transition_strip (bpy.types.ThemeSequenceEditor attribute), 931
transition_type (bpy.types.WipeSequence attribute), 1025
translate() (bpy.types.Bone method), 231
translate() (bpy.types.EditBone method), 371
translate() (bpy.types.PoseBone method), 699
translate() (in module bpy.ops.transform), 123
translate_start_x (bpy.types.TransformSequence attribute), 958
translate_start_y (bpy.types.TransformSequence attribute), 958
Translation() (mathutils.Matrix class method), 1058
translation_unit (bpy.types.TransformSequence attribute), 958
translucency (bpy.types.Material attribute), 524
translucency_factor (bpy.types.MaterialTextureSlot attribute), 540
transmission_color (bpy.types.MaterialVolume attribute), 545
transmission_color_factor (bpy.types.MaterialTextureSlot attribute), 540
transparency_method (bpy.types.Material attribute), 524
transparent (bge.types.KX_PolygonMaterial attribute), 1168
transpose() (mathutils.Matrix method), 1061
transposed() (mathutils.Matrix method), 1061
tree_type (bpy.types.SpaceNodeEditor attribute), 835
triangle (bge.types.KX_PolygonMaterial attribute), 1168
triggered (bge.types.SCA_ISensor attribute), 1135
tris_convert_to_quads() (in module bpy.ops.mesh), 64
turbulence (bpy.types.EffectorWeights attribute), 377
turbulence (bpy.types.MagicTexture attribute), 515
turbulence (bpy.types.MarbleTexture attribute), 518
turbulence (bpy.types.StucciTexture attribute), 865
turbulence (bpy.types.WoodTexture attribute), 1027
turbulence_depth (bpy.types.PointDensity attribute), 689
turbulence_influence (bpy.types.PointDensity attribute), 689
turbulence_scale (bpy.types.PointDensity attribute), 689
turbulence_strength (bpy.types.PointDensity attribute), 689
tweakmode_enter() (in module bpy.ops.nla), 67
tweakmode_exit() (in module bpy.ops.nla), 67
twist_mode (bpy.types.Curve attribute), 345
twist_smooth (bpy.types.Curve attribute), 345
TWOKEY (in module bge.events), 1224
type (bge.types.BL_ArmatureActuator attribute), 1195
type (bge.types.BL_ArmatureConstraint attribute), 1197
type (bge.types.KX_ArmatureSensor attribute), 1196
type (bge.types.KX_LightObject attribute), 1155
type (bpy.types.Actuator attribute), 155
type (bpy.types.AnimVizMotionPaths attribute), 167
type (bpy.types.AnimVizOnionSkinning attribute), 168
type (bpy.types.Area attribute), 170
type (bpy.types.Camera attribute), 245
type (bpy.types.Controller attribute), 337
type (bpy.types.Driver attribute), 363
type (bpy.types.DriverVariable attribute), 365
type (bpy.types.FieldSettings attribute), 407
type (bpy.types.FluidSettings attribute), 417
type (bpy.types.GameProperty attribute), 432
type (bpy.types.Keyframe attribute), 486
type (bpy.types.KeyMapItem attribute), 477
type (bpy.types.Lamp attribute), 497
type (bpy.types.Material attribute), 525
type (bpy.types.MetaElement attribute), 577
type (bpy.types.ParticleEdit attribute), 651
type (bpy.types.ParticleSettings attribute), 667
type (bpy.types.Sensor attribute), 766
type (bpy.types.Spline attribute), 851
type (bpy.types.Texture attribute), 882
type_recast() (bpy.types.bpy_struct method), 1044

U

u (bge.types.KX_VertexProxy attribute), 1180
u2 (bge.types.KX_VertexProxy attribute), 1180
UILayout (class in bpy.types), 959
UKEY (in module bge.events), 1224
uncomment() (in module bpy.ops.text), 115
underline_height (bpy.types.TextCurve attribute), 878

underline_position (bpy.types.TextCurve attribute), 878
 undo() (in module bpy.ops.ed), 28
 undo_history() (in module bpy.ops.ed), 28
 undo_memory_limit (bpy.types.UserPreferencesEdit attribute), 989
 undo_push() (in module bpy.ops.ed), 28
 undo_steps (bpy.types.UserPreferencesEdit attribute), 989
 unindent() (in module bpy.ops.text), 115
 unique_name() (in module bpy_extras.io_utils), 1130
 UnitSettings (class in bpy.types), 985
 UnknownType (class in bpy.types), 986
 unlink() (bpy.types.Actuator method), 155
 unlink() (bpy.types.Controller method), 337
 unlink() (bpy.types.GroupObjects method), 442
 unlink() (bpy.types.SceneObjects method), 753
 unlink() (bpy.types.Sensor method), 767
 unlink() (in module bpy.ops.font), 37
 unlink() (in module bpy.ops.poselib), 96
 unlink() (in module bpy.ops.text), 115
 unlink_selected() (in module bpy.ops.uv), 130
 unlock() (in module bpy.ops.sequencer), 107
 unmute() (in module bpy.ops.sequencer), 107
 unpack() (in module bpy.ops.image), 45
 unpack() (in module bpy.ops.sound), 109
 unpack_all() (in module bpy.ops.file), 34
 unpack_face_list() (in module bpy_extras.io_utils), 1129
 unpack_list() (in module bpy_extras.io_utils), 1129
 unprojected_radius (bpy.types.Brush attribute), 238
 unregister_class() (in module bpy.utils), 1046
 unregister_module() (in module bpy.utils), 1046
 unspill_blue (bpy.types.CompositorNodeColorSpill attribute), 278
 unspill_green (bpy.types.CompositorNodeColorSpill attribute), 278
 unspill_red (bpy.types.CompositorNodeColorSpill attribute), 279
 unwrap() (in module bpy.ops.uv), 130
 up_axis (bpy.types.FollowPathConstraint attribute), 419
 up_axis (bpy.types.Object attribute), 617
 up_axis (bpy.types.TrackToConstraint attribute), 953
 UPARROWKEY (in module bge.events), 1225
 update() (bge.types.BL_ArmatureObject method), 1194
 update() (bpy.types.Image method), 454
 update() (bpy.types.Mesh method), 552
 update() (bpy.types.Scene method), 746
 update_data_paths() (in module bpy.ops.anim), 16
 update_method (bpy.types.MetaBall attribute), 574
 update_result() (bpy.types.RenderEngine method), 721
 update_stats() (bpy.types.RenderEngine method), 721
 update_tag() (bpy.types.ID method), 449
 updateTexture() (bge.types.KX_PolygonMaterial method), 1168
 url_open() (in module bpy.ops.wm), 146
 use (bpy.types.CollisionSettings attribute), 263
 use (bpy.types.ControlFluidSettings attribute), 336
 use (bpy.types.FluidFluidSettings attribute), 415
 use (bpy.types.InflowFluidSettings attribute), 464
 use (bpy.types.MaterialRaytraceMirror attribute), 532
 use (bpy.types.MaterialSubsurfaceScattering attribute), 537
 use (bpy.types.MaterialTextureSlot attribute), 540
 use (bpy.types.ObstacleFluidSettings attribute), 628
 use (bpy.types.OutflowFluidSettings attribute), 640
 use (bpy.types.SceneRenderLayer attribute), 755
 use (bpy.types.UserSolidLight attribute), 1003
 use3D (bge.types.KX_TrackToActuator attribute), 1177
 use_2d_force (bpy.types.FieldSettings attribute), 407
 use_3d_tracking (bpy.types.EditObjectActuator attribute), 373
 use_absolute (bpy.types.SmokeFlowSettings attribute), 809
 use_absolute_path_time (bpy.types.ParticleSettings attribute), 667
 use_absorption (bpy.types.FieldSettings attribute), 407
 use_accumulate (bpy.types.Brush attribute), 238
 use_activity_culling (bpy.types.GameObjectSettings attribute), 430
 use_activity_culling (bpy.types.SceneGameData attribute), 751
 use_actor (bpy.types.GameObjectSettings attribute), 430
 use_adaptive_space (bpy.types.Brush attribute), 238
 use_add_linear_velocity (bpy.types.ObjectActuator attribute), 623
 use_additive (bpy.types.FCurveActuator attribute), 390
 use_additive (bpy.types.FModifierFunctionGenerator attribute), 399
 use_additive (bpy.types.FModifierGenerator attribute), 400
 use_advanced_hair (bpy.types.ParticleSettings attribute), 667
 use_airbrush (bpy.types.Brush attribute), 238
 use_all_events (bpy.types.JoystickSensor attribute), 469
 use_all_faces (bpy.types.VertexPaint attribute), 1010
 use_all_keys (bpy.types.KeyboardSensor attribute), 484
 use_all_states (bpy.types.GameObjectSettings attribute), 430
 use_all_z (bpy.types.SceneRenderLayer attribute), 755
 use_alpha (bpy.types.Brush attribute), 238
 use_alpha (bpy.types.CompositorNodeMixRGB attribute), 305
 use_alpha (bpy.types.CompositorNodeZcombine attribute), 325
 use_alpha (bpy.types.ImageTexture attribute), 461
 use_alpha (bpy.types.ShaderNodeMixRGB attribute), 785
 use_alpha (bpy.types.TextureNodeMixRGB attribute), 894

use_alpha_sort (bpy.types.MeshTextureFace attribute), 567
use_always_true (bpy.types.RandomActuator attribute), 713
use_ambient_occlusion (bpy.types.WorldLighting attribute), 1031
use_anchor (bpy.types.Brush attribute), 239
use-angular_limit_x (bpy.types.RigidBodyJointConstraint attribute), 739
use-angular_limit_y (bpy.types.RigidBodyJointConstraint attribute), 739
use-angular_limit_z (bpy.types.RigidBodyJointConstraint attribute), 739
use_animated_influence (bpy.types.NlaStrip attribute), 598
use_animated_mesh (bpy.types.FluidFluidSettings attribute), 415
use_animated_mesh (bpy.types.InflowFluidSettings attribute), 464
use_animated_mesh (bpy.types.ObstacleFluidSettings attribute), 628
use_animated_mesh (bpy.types.OutflowFluidSettings attribute), 640
use_animated_time (bpy.types.NlaStrip attribute), 598
use_animated_time_cyclic (bpy.types.NlaStrip attribute), 598
use_animation (bpy.types.Image attribute), 453
use_animation_record (bpy.types.SceneGameData attribute), 751
use_anisotropic_friction (bpy.types.GameObjectSettings attribute), 431
use_antialiasing (bpy.types.RenderSettings attribute), 733
use_antialiasing (bpy.types.UserPreferencesSystem attribute), 998
use_apply_on_spline (bpy.types.Modifier attribute), 582
use_as_speed (bpy.types.SpeedControlSequence attribute), 849
use_atmosphere (bpy.types.LampSkySettings attribute), 499
use_audio (bpy.types.Scene attribute), 745
use_audio_scrub (bpy.types.Scene attribute), 745
use_audio_sync (bpy.types.Scene attribute), 745
use_auto_blend (bpy.types.NlaStrip attribute), 598
use_auto_clip_end (bpy.types.SpotLamp attribute), 859
use_auto_clip_start (bpy.types.SpotLamp attribute), 859
use_auto_handle_clamp (bpy.types.FCurve attribute), 389
use_auto_ik (bpy.types.Armature attribute), 176
use_auto_keying (bpy.types.UserPreferencesEdit attribute), 989
use_auto_merge_keyframes (bpy.types.SpaceDopeSheetEditor attribute), 825
use_auto_merge_keyframes (bpy.types.SpaceGraphEditor attribute), 828
use_auto_normalize (bpy.types.ToolSettings attribute), 950
use_auto_perspective (bpy.types.UserPreferencesView attribute), 1001
use_auto_refresh (bpy.types.CompositorNodeImage attribute), 298
use_auto_refresh (bpy.types.ImageUser attribute), 463
use_auto_render (bpy.types.SpaceNodeEditor attribute), 835
use_auto_save_temporary_files (bpy.types.UserPreferencesFilePaths attribute), 993
use_auto_smooth (bpy.types.Mesh attribute), 551
use_auto_start (bpy.types.SceneGameData attribute), 751
use_auto_step (bpy.types.Itasc attribute), 468
use_auto_step (bpy.types.SoftBodySettings attribute), 815
use_auto_txspace (bpy.types.Curve attribute), 345
use_auto_txspace (bpy.types.Mesh attribute), 551
use_auto_txspace (bpy.types.MetaBall attribute), 574
use_auto_velocity (bpy.types.ParticleEdit attribute), 651
use_avoid (bpy.types.BoidRuleAvoidCollision attribute), 221
use_avoid_collision (bpy.types.BoidRuleAvoidCollision attribute), 221
use_backface_culling (bpy.types.ImagePaint attribute), 456
use_bake_antialiasing (bpy.types.RenderSettings attribute), 733
use_bake_clear (bpy.types.RenderSettings attribute), 733
use_bake_lores_mesh (bpy.types.RenderSettings attribute), 733
use_bake_multires (bpy.types.RenderSettings attribute), 733
use_bake_normalize (bpy.types.RenderSettings attribute), 733
use_bake_selected_to_active (bpy.types.RenderSettings attribute), 734
use_bending_constraints (bpy.types.GameSoftBodySettings attribute), 433
use_bezier_u (bpy.types.Spline attribute), 851
use_bezier_v (bpy.types.Spline attribute), 851
use_billboard (bpy.types.MeshTextureFace attribute), 567
use_bitmap_text (bpy.types.MeshTextureFace attribute), 567
use_blend_shared (bpy.types.MeshTextureFace attribute), 567
use_blender_units (bpy.types.MaterialStrand attribute), 535
use_bokeh (bpy.types.CompositorNodeBlur attribute), 272
use_bold (bpy.types.TextCharacterFormat attribute), 876

use_bone_envelopes (bpy.types.ArmatureModifier attribute), 180
 use_bone_sketching (bpy.types.ToolSettings attribute), 950
 use_border (bpy.types.RenderSettings attribute), 734
 use_box_clip (bpy.types.RegionView3D attribute), 718
 use_cache (bpy.types.WorldLighting attribute), 1031
 use_calculate_alpha (bpy.types.ImageTexture attribute), 461
 use_camera_lock_parent (bpy.types.UserPreferencesView attribute), 1001
 use_cast_approximate (bpy.types.Material attribute), 525
 use_cast_buffer_shadows (bpy.types.Material attribute), 525
 use_cast_shadows_only (bpy.types.Material attribute), 525
 use_chain_offset (bpy.types.SplineIKConstraint attribute), 854
 use_checker_even (bpy.types.ImageTexture attribute), 461
 use_checker_odd (bpy.types.ImageTexture attribute), 461
 use_children (bpy.types.ParticleInstanceModifier attribute), 655
 use_cineon_log (bpy.types.RenderSettings attribute), 734
 use_clamp_x (bpy.types.Image attribute), 453
 use_clamp_y (bpy.types.Image attribute), 454
 use_climb (bpy.types.BoidSettings attribute), 226
 use_clip (bpy.types.CurveMapping attribute), 349
 use_clip (bpy.types.MirrorModifier attribute), 580
 use_clone_layer (bpy.types.ImagePaint attribute), 456
 use_cluster_rigid_to_softbody (bpy.types.GameSoftBodySettings attribute), 433
 use_cluster_soft_to_softbody (bpy.types.GameSoftBodySettings attribute), 434
 use_collision (bpy.types.ClothCollisionSettings attribute), 254
 use_collision (bpy.types.MeshTextureFace attribute), 567
 use_collision_bounds (bpy.types.GameObjectSettings attribute), 431
 use_collision_compound (bpy.types.GameObjectSettings attribute), 431
 use_color_balance (bpy.types.AdjustmentSequence attribute), 159
 use_color_balance (bpy.types.EffectSequence attribute), 374
 use_color_balance (bpy.types.ImageSequence attribute), 458
 use_color_balance (bpy.types.MetaSequence attribute), 578
 use_color_balance (bpy.types.MovieSequence attribute), 587
 use_color_balance (bpy.types.MulticamSequence attribute), 589
 use_color_balance (bpy.types.SceneSequence attribute), 758
 use_color_management (bpy.types.RenderSettings attribute), 734
 use_color_ramp (bpy.types.Texture attribute), 882
 use_compositing (bpy.types.RenderSettings attribute), 734
 use_compound (bpy.types.ParentActuator attribute), 646
 use_connect (bpy.types.EditBone attribute), 370
 use_constant_offset (bpy.types.ArrayModifier attribute), 183
 use_continue_last_frame (bpy.types.ActionActuator attribute), 149
 use_continue_last_frame (bpy.types.ShapeActionActuator attribute), 797
 use_crop (bpy.types.AdjustmentSequence attribute), 159
 use_crop (bpy.types.EffectSequence attribute), 374
 use_crop (bpy.types.ImageSequence attribute), 458
 use_crop (bpy.types.MetaSequence attribute), 578
 use_crop (bpy.types.MovieSequence attribute), 587
 use_crop (bpy.types.MulticamSequence attribute), 590
 use_crop (bpy.types.SceneSequence attribute), 758
 use_crop_size (bpy.types.CompositorNodeCrop attribute), 283
 use_crop_to_border (bpy.types.RenderSettings attribute), 734
 use_cubic (bpy.types.Material attribute), 525
 use_curve_follow (bpy.types.FollowPathConstraint attribute), 419
 use_curve_radius (bpy.types.FollowPathConstraint attribute), 419
 use_curve_radius (bpy.types.SplineIKConstraint attribute), 854
 use_curved (bpy.types.CompositorNodeVecBlur attribute), 324
 use_custom_icon (bpy.types.Brush attribute), 239
 use_cyclic (bpy.types.ClampToConstraint attribute), 252
 use_cyclic (bpy.types.CompositorNodeImage attribute), 298
 use_cyclic (bpy.types.ImageUser attribute), 463
 use_cyclic (bpy.types.WaveModifier attribute), 1019
 use_cyclic_offset (bpy.types.Bone attribute), 230
 use_cyclic_offset (bpy.types.EditBone attribute), 370
 use_cyclic_u (bpy.types.Spline attribute), 852
 use_cyclic_v (bpy.types.Spline attribute), 852
 use_dead (bpy.types.ParticleSettings attribute), 667
 use_debug (bpy.types.PythonController attribute), 710
 use_default_fade (bpy.types.Sequence attribute), 769
 use_default_interpolate (bpy.types.ParticleEdit attribute), 651
 use_deform (bpy.types.Bone attribute), 230

use_deform (bpy.types.EditBone attribute), 370
use_deform_bounds (bpy.types.Curve attribute), 345
use_deform_delay (bpy.types.Armature attribute), 176
use_deform_envelopes (bpy.types.Armature attribute), 176
use_deform_only (bpy.types.Sculpt attribute), 765
use_deform_preserve_volume (bpy.types.Armature attribute), 176
use_deform_preserve_volume (bpy.types.ArmatureModifier attribute), 180
use_deform_vertex_groups (bpy.types.Armature attribute), 176
use_deinterlace (bpy.types.AdjustmentSequence attribute), 159
use_deinterlace (bpy.types.EffectSequence attribute), 374
use_deinterlace (bpy.types.ImageSequence attribute), 458
use_deinterlace (bpy.types.MetaSequence attribute), 578
use_deinterlace (bpy.types.MovieSequence attribute), 587
use_deinterlace (bpy.types.MulticamSequence attribute), 590
use_deinterlace (bpy.types.SceneSequence attribute), 758
use_deprecation_warnings (bpy.types.SceneGameData attribute), 751
use_diagnose (bpy.types.SoftBodySettings attribute), 815
use_die_on_collision (bpy.types.ParticleSettings attribute), 667
use_diffuse (bpy.types.Lamp attribute), 497
use_diffuse (bpy.types.ShaderNodeExtendedMaterial attribute), 779
use_diffuse (bpy.types.ShaderNodeMaterial attribute), 783
use_diffuse_ramp (bpy.types.Material attribute), 525
use_directional_menus (bpy.types.UserPreferencesView attribute), 1001
use_disk_cache (bpy.types.PointCache attribute), 686
use_display_lists (bpy.types.SceneGameData attribute), 751
use_dissolve_smoke (bpy.types.SmokeDomainSettings attribute), 808
use_dissolve_smoke_log (bpy.types.SmokeDomainSettings attribute), 808
use_dither (bpy.types.AreaLamp attribute), 172
use_drag_immediately (bpy.types.UserPreferencesEdit attribute), 989
use_drops (bpy.types.ParticleFluidSettings attribute), 653
use_dupli_faces_scale (bpy.types.Object attribute), 617
use_dupli_frames_speed (bpy.types.Object attribute), 617
use_dupli_vertices_rotation (bpy.types.Object attribute), 617
use_duplicate_action (bpy.types.UserPreferencesEdit attribute), 989
use_duplicate_armature (bpy.types.UserPreferencesEdit attribute), 989
use_duplicate_curve (bpy.types.UserPreferencesEdit attribute), 989
use_duplicate_fcurve (bpy.types.UserPreferencesEdit attribute), 989
use_duplicate_lamp (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_material (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_mesh (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_metaball (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_particle (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_surface (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_text (bpy.types.UserPreferencesEdit attribute), 990
use_duplicate_texture (bpy.types.UserPreferencesEdit attribute), 990
use_dynamic_bind (bpy.types.MeshDeformModifier attribute), 555
use_dynamic_rotation (bpy.types.ParticleSettings attribute), 667
use_edge_angle (bpy.types.EdgeSplitModifier attribute), 367
use_edge_collision (bpy.types.SoftBodySettings attribute), 815
use_edge_cut (bpy.types.ExplodeModifier attribute), 386
use_edge_enhance (bpy.types.RenderSettings attribute), 734
use_edge_enhance (bpy.types.SceneRenderLayer attribute), 755
use_edge_sharp (bpy.types.EdgeSplitModifier attribute), 367
use_edge_sharp (bpy.types.MeshEdge attribute), 557
use_edge_to_edge (bpy.types.Brush attribute), 239
use_edges (bpy.types.SoftBodySettings attribute), 815
use_emit_random (bpy.types.ParticleSettings attribute), 667
use_emitter_deflect (bpy.types.ParticleEdit attribute), 651
use_emulate_numpad (bpy.types.UserPreferencesInput attribute), 995
use_endpoint_u (bpy.types.Spline attribute), 852
use_endpoint_v (bpy.types.Spline attribute), 852
use_enter_edit_mode (bpy.types.UserPreferencesEdit attribute), 990
use_entire_array (bpy.types.KeyingSetPath attribute), 490
use_envelope_multiply (bpy.types.Bone attribute), 230
use_envelope_multiply (bpy.types.EditBone attribute), 370

use_environment_light (bpy.types.WorldLighting attribute), 1031
 use_envmaps (bpy.types.RenderSettings attribute), 734
 use_estimate_matrix (bpy.types.SoftBodySettings attribute), 815
 use_etch_autoname (bpy.types.ToolSettings attribute), 950
 use_etch_overdraw (bpy.types.ToolSettings attribute), 950
 use_etch_quick (bpy.types.ToolSettings attribute), 950
 use_even_distribution (bpy.types.ParticleSettings attribute), 667
 use_even_divisions (bpy.types.SplineIKConstraint attribute), 854
 use_even_offset (bpy.types.SolidifyModifier attribute), 817
 use_exr_half (bpy.types.CompositorNodeOutputFile attribute), 307
 use_external (bpy.types.PointCache attribute), 686
 use_external_shadows (bpy.types.MaterialVolume attribute), 545
 use_extreme_alpha (bpy.types.MaterialHalo attribute), 529
 use_face_collision (bpy.types.SoftBodySettings attribute), 816
 use_face_texture (bpy.types.Material attribute), 525
 use_face_texture_alpha (bpy.types.Material attribute), 525
 use_fade_time (bpy.types.ParticleEdit attribute), 651
 use_fake_user (bpy.types.ID attribute), 448
 use_falloff (bpy.types.WorldLighting attribute), 1032
 use_falloff_curve (bpy.types.PointDensity attribute), 689
 use_fancy_drawing (bpy.types.SpaceGraphEditor attribute), 828
 use_fast_edit (bpy.types.TextCurve attribute), 878
 use_fh_normal (bpy.types.ConstraintActuator attribute), 331
 use_fh_normal (bpy.types.MaterialPhysics attribute), 530
 use_fh_parallel_axis (bpy.types.ConstraintActuator attribute), 331
 use_fields (bpy.types.Image attribute), 454
 use_fields (bpy.types.RenderSettings attribute), 734
 use_fields_still (bpy.types.RenderSettings attribute), 734
 use_file_compression (bpy.types.UserPreferencesFilePaths attribute), 993
 use_file_extension (bpy.types.RenderSettings attribute), 734
 use_fill_back (bpy.types.Curve attribute), 345
 use_fill_deform (bpy.types.Curve attribute), 345
 use_fill_front (bpy.types.Curve attribute), 345
 use_filter (bpy.types.FileSelectParams attribute), 410
 use_filter_blender (bpy.types.FileSelectParams attribute), 410
 use_filter_case_sensitive (bpy.types.SpaceOutliner attribute), 836
 use_filter_complete (bpy.types.SpaceOutliner attribute), 836
 use_filter_files (bpy.types.UserPreferencesFilePaths attribute), 993
 use_filter_folder (bpy.types.FileSelectParams attribute), 410
 use_filter_font (bpy.types.FileSelectParams attribute), 410
 use_filter_image (bpy.types.FileSelectParams attribute), 410
 use_filter_movie (bpy.types.FileSelectParams attribute), 410
 use_filter_script (bpy.types.FileSelectParams attribute), 410
 use_filter_size_min (bpy.types.EnvironmentMapTexture attribute), 382
 use_filter_size_min (bpy.types.ImageTexture attribute), 461
 use_filter_sound (bpy.types.FileSelectParams attribute), 410
 use_filter_text (bpy.types.FileSelectParams attribute), 410
 use_find_all (bpy.types.SpaceTextEditor attribute), 840
 use_find_wrap (bpy.types.SpaceTextEditor attribute), 840
 use_fit (bpy.types.CompositorNodeLensdist attribute), 300
 use_fixed_location (bpy.types.FollowPathConstraint attribute), 419
 use_fixed_texture (bpy.types.Brush attribute), 239
 use_flare_mode (bpy.types.MaterialHalo attribute), 529
 use_flight (bpy.types.BoidSettings attribute), 226
 use_flip_axis (bpy.types.BlendTexture attribute), 216
 use_flip_axis (bpy.types.ImageTexture attribute), 461
 use_flip_x (bpy.types.AdjustmentSequence attribute), 160
 use_flip_x (bpy.types.EffectSequence attribute), 374
 use_flip_x (bpy.types.ImageSequence attribute), 458
 use_flip_x (bpy.types.MetaSequence attribute), 578
 use_flip_x (bpy.types.MovieSequence attribute), 587
 use_flip_x (bpy.types.MulticamSequence attribute), 590
 use_flip_x (bpy.types.SceneSequence attribute), 758
 use_flip_y (bpy.types.AdjustmentSequence attribute), 160
 use_flip_y (bpy.types.EffectSequence attribute), 374
 use_flip_y (bpy.types.ImageSequence attribute), 458
 use_flip_y (bpy.types.MetaSequence attribute), 578
 use_flip_y (bpy.types.MovieSequence attribute), 587
 use_flip_y (bpy.types.MulticamSequence attribute), 590
 use_flip_y (bpy.types.SceneSequence attribute), 758
 use_float (bpy.types.AdjustmentSequence attribute), 160
 use_float (bpy.types.EffectSequence attribute), 375
 use_float (bpy.types.ImageSequence attribute), 458
 use_float (bpy.types.MetaSequence attribute), 579

use_float (bpy.types.MovieSequence attribute), 587
use_float (bpy.types.MulticamSequence attribute), 590
use_float (bpy.types.SceneSequence attribute), 758
use_floats (bpy.types.ParticleFluidSettings attribute), 653
use_force (bpy.types.FCurveActuator attribute), 391
use_force_distance (bpy.types.ConstraintActuator attribute), 331
use_frame_blend (bpy.types.SpeedControlSequence attribute), 849
use_frame_drop (bpy.types.Scene attribute), 745
use_frame_end (bpy.types.FModifierStepped attribute), 404
use_frame_rate (bpy.types.SceneGameData attribute), 751
use_frame_start (bpy.types.FModifierStepped attribute), 404
use_free_image_textures (bpy.types.RenderSettings attribute), 734
use_free_unused_nodes (bpy.types.RenderSettings attribute), 734
use_from_dupli (bpy.types.MaterialTextureSlot attribute), 540
use_from_original (bpy.types.MaterialTextureSlot attribute), 540
use_frontface (bpy.types.Brush attribute), 239
use_full_oversampling (bpy.types.Material attribute), 525
use_full_resolution (bpy.types.Scopes attribute), 760
use_full_sample (bpy.types.RenderSettings attribute), 735
use_gamma_correction (bpy.types.CompositorNodeBlur attribute), 272
use_gamma_correction (bpy.types.CompositorNodeDefocus attribute), 287
use_ghost (bpy.types.GameObjectSettings attribute), 431
use_ghost (bpy.types.ParentActuator attribute), 646
use_global_coords (bpy.types.FieldSettings attribute), 407
use_global_dupli (bpy.types.ParticleSettings attribute), 667
use_global_pivot (bpy.types.UserPreferencesView attribute), 1001
use_global_scene (bpy.types.UserPreferencesView attribute), 1001
use_global_undo (bpy.types.UserPreferencesEdit attribute), 990
use_glsl_color_management (bpy.types.SceneGameData attribute), 751
use_glsl_extra_textures (bpy.types.SceneGameData attribute), 751
use_glsl_lights (bpy.types.SceneGameData attribute), 752
use_glsl_nodes (bpy.types.SceneGameData attribute), 752
use_glsl_ramps (bpy.types.SceneGameData attribute), 752
use_glsl_shaders (bpy.types.SceneGameData attribute), 752
use_glsl_shadows (bpy.types.SceneGameData attribute), 752
use_goal (bpy.types.SoftBodySettings attribute), 816
use_gravity (bpy.types.Scene attribute), 745
use_grease_pencil (bpy.types.SpaceImageEditor attribute), 830
use_grease_pencil (bpy.types.SpaceSequenceEditor attribute), 838
use_grease_pencil_sessions (bpy.types.ToolSettings attribute), 950
use_grease_pencil_simplify_stroke (bpy.types.UserPreferencesEdit attribute), 990
use_grease_pencil_smooth_stroke (bpy.types.UserPreferencesEdit attribute), 990
use_group_count (bpy.types.ParticleSettings attribute), 667
use_group_pick_random (bpy.types.ParticleSettings attribute), 667
use_guide_path_add (bpy.types.FieldSettings attribute), 408
use_guide_path_weight (bpy.types.FieldSettings attribute), 408
use_hair_bspline (bpy.types.ParticleSettings attribute), 668
use_hair_dynamics (bpy.types.ParticleSystem attribute), 676
use_halo (bpy.types.MeshTextureFace attribute), 567
use_halo (bpy.types.SceneRenderLayer attribute), 755
use_halo (bpy.types.SpotLamp attribute), 859
use_high_resolution (bpy.types.SmokeDomainSettings attribute), 808
use_ik_limit_x (bpy.types.PoseBone attribute), 698
use_ik_limit_y (bpy.types.PoseBone attribute), 698
use_ik_limit_z (bpy.types.PoseBone attribute), 698
use_ik_linear_control (bpy.types.PoseBone attribute), 698
use_ik_rotation_control (bpy.types.PoseBone attribute), 699
use_image (bpy.types.MeshTextureFace attribute), 567
use_image_override (bpy.types.UVProjectModifier attribute), 983
use_image_paint (bpy.types.SpaceImageEditor attribute), 830
use_image_pin (bpy.types.SpaceImageEditor attribute), 830
use_in_air (bpy.types.BoidRule attribute), 218
use_indirect_light (bpy.types.WorldLighting attribute), 1032

use_inherit_rotation (bpy.types.Bone attribute), 230
 use_inherit_rotation (bpy.types.EditBone attribute), 370
 use_inherit_scale (bpy.types.Bone attribute), 230
 use_inherit_scale (bpy.types.EditBone attribute), 370
 use_initial_rest_length (bpy.types.SPHFluidSettings attribute), 742
 use_insertkey_xyz_to_rgb (bpy.types.UserPreferencesEdit attribute), 990
 use_instances (bpy.types.RenderSettings attribute), 735
 use_international_fonts (bpy.types.UserPreferencesSystem attribute), 998
 use_interpolation (bpy.types.ImageTexture attribute), 461
 use_inverse_smooth_pressure (bpy.types.Brush attribute), 239
 use_italic (bpy.types.TextCharacterFormat attribute), 876
 use_jitter (bpy.types.AreaLamp attribute), 172
 use_jitter (bpy.types.CompositorNodeLensdist attribute), 300
 use_keep_above_surface (bpy.types.ShrinkwrapModifier attribute), 803
 use_keyed_timing (bpy.types.ParticleSystem attribute), 676
 use_keyframe_insert_auto (bpy.types.ToolSettings attribute), 950
 use_keyframe_insert_available (bpy.types.UserPreferencesEdit attribute), 990
 use_keyframe_insert_keyingset (bpy.types.ToolSettings attribute), 950
 use_keyframe_insert_needed (bpy.types.UserPreferencesEdit attribute), 991
 use_land (bpy.types.BoidSettings attribute), 226
 use_level (bpy.types.Sensor attribute), 766
 use_library_path (bpy.types.PointCache attribute), 686
 use_light (bpy.types.MeshTextureFace attribute), 567
 use_light_cache (bpy.types.MaterialVolume attribute), 545
 use_light_group_exclusive (bpy.types.Material attribute), 525
 use_limit_x (bpy.types.LimitRotationConstraint attribute), 510
 use_limit_x (bpy.types.RigidBodyJointConstraint attribute), 739
 use_limit_y (bpy.types.LimitRotationConstraint attribute), 510
 use_limit_y (bpy.types.RigidBodyJointConstraint attribute), 740
 use_limit_z (bpy.types.LimitRotationConstraint attribute), 510
 use_limit_z (bpy.types.RigidBodyJointConstraint attribute), 740
 use_line (bpy.types.BoidRuleFollowLeader attribute), 223
 use_lines (bpy.types.MaterialHalo attribute), 529
 use_linked_collision (bpy.types.RigidBodyJointConstraint attribute), 740
 use_live_edit (bpy.types.SpaceTextEditor attribute), 840
 use_live_unwrap (bpy.types.SpaceUVEditor attribute), 843
 use_load_ui (bpy.types.UserPreferencesFilePaths attribute), 993
 use_local (bpy.types.ConstraintActuator attribute), 332
 use_local (bpy.types.FCurveActuator attribute), 391
 use_local_angular_velocity (bpy.types>EditObjectActuator attribute), 373
 use_local_angular_velocity (bpy.types.ObjectActuator attribute), 623
 use_local_coords (bpy.types.InflowFluidSettings attribute), 465
 use_local_coords (bpy.types.RenderSettings attribute), 735
 use_local_force (bpy.types.ObjectActuator attribute), 623
 use_local_linear_velocity (bpy.types>EditObjectActuator attribute), 373
 use_local_linear_velocity (bpy.types.ObjectActuator attribute), 623
 use_local_location (bpy.types.Bone attribute), 230
 use_local_location (bpy.types>EditBone attribute), 370
 use_local_location (bpy.types.ObjectActuator attribute), 623
 use_local_rotation (bpy.types.ObjectActuator attribute), 623
 use_local_space_transform (bpy.types.DriverTarget attribute), 364
 use_local_torque (bpy.types.ObjectActuator attribute), 623
 use_location (bpy.types.KinematicConstraint attribute), 495
 use_location_x (bpy.types.ChildOfConstraint attribute), 250
 use_location_y (bpy.types.ChildOfConstraint attribute), 250
 use_location_z (bpy.types.ChildOfConstraint attribute), 250
 use_locked_size (bpy.types.Brush attribute), 239
 use_manipulator_rotate (bpy.types.SpaceView3D attribute), 847
 use_manipulator_scale (bpy.types.SpaceView3D attribute), 847
 use_manipulator_translate (bpy.types.SpaceView3D attribute), 847
 use_map_alpha (bpy.types.MaterialTextureSlot attribute), 540

use_map_ambient (bpy.types.MaterialTextureSlot attribute), [540](#)
use_map_blend (bpy.types.WorldTextureSlot attribute), [1035](#)
use_map_clump (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_color (bpy.types.LampTextureSlot attribute), [500](#)
use_map_color_diffuse (bpy.types.MaterialTextureSlot attribute), [540](#)
use_map_color_emission (bpy.types.MaterialTextureSlot attribute), [540](#)
use_map_color_reflection (bpy.types.MaterialTextureSlot attribute), [540](#)
use_map_color_spec (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_color_transmission (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_damp (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_density (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_density (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_diffuse (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_displacement (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_emission (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_emit (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_field (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_gravity (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_hardness (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_horizon (bpy.types.WorldTextureSlot attribute), [1035](#)
use_map_kink (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_length (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_life (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_mirror (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_normal (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_raymir (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_reflect (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_rough (bpy.types.ParticleSettingsTextureSlot attribute), [671](#)
use_map_scatter (bpy.types.MaterialTextureSlot attribute), [541](#)
use_map_shadow (bpy.types.LampTextureSlot attribute), [500](#)
use_map_size (bpy.types.ParticleSettingsTextureSlot attribute), [672](#)
use_map_specular (bpy.types.MaterialTextureSlot attribute), [542](#)
use_map_time (bpy.types.ParticleSettingsTextureSlot attribute), [672](#)
use_map_translucency (bpy.types.MaterialTextureSlot attribute), [542](#)
use_map_velocity (bpy.types.ParticleSettingsTextureSlot attribute), [672](#)
use_map_warp (bpy.types.MaterialTextureSlot attribute), [542](#)
use_map_zenith_down (bpy.types.WorldTextureSlot attribute), [1035](#)
use_map_zenith_up (bpy.types.WorldTextureSlot attribute), [1035](#)
use_marker_sync (bpy.types.SpaceDopeSheetEditor attribute), [825](#)
use_marker_sync (bpy.types.SpaceSequenceEditor attribute), [839](#)
use_match_case (bpy.types.SpaceTextEditor attribute), [840](#)
use_material (bpy.types.CollisionSensor attribute), [262](#)
use_material_detect (bpy.types.ConstraintActuator attribute), [332](#)
use_material_physics_fh (bpy.types.GameObjectSettings attribute), [431](#)
use_max (bpy.types.CompositorNodeMapValue attribute), [303](#)
use_max (bpy.types.ShaderNodeMapping attribute), [782](#)
use_max (bpy.types.TexMapping attribute), [872](#)
use_max_distance (bpy.types.FieldSettings attribute), [408](#)
use_max_x (bpy.types.FModifierLimits attribute), [401](#)
use_max_x (bpy.types.LimitLocationConstraint attribute), [508](#)
use_max_x (bpy.types.LimitScaleConstraint attribute), [512](#)
use_max_y (bpy.types.FModifierLimits attribute), [401](#)
use_max_y (bpy.types.LimitLocationConstraint attribute), [508](#)
use_max_y (bpy.types.LimitScaleConstraint attribute), [512](#)
use_max_z (bpy.types.LimitLocationConstraint attribute), [508](#)
use_max_z (bpy.types.LimitScaleConstraint attribute), [512](#)

use_memory_cache (bpy.types.Sound attribute), 819
 use_merge_vertices (bpy.types.ArrayModifier attribute), 183
 use_merge_vertices_cap (bpy.types.ArrayModifier attribute), 183
 use_mesh_automerge (bpy.types.ToolSettings attribute), 950
 use_min (bpy.types.CompositorNodeMapValue attribute), 303
 use_min (bpy.types.ShaderNodeMapping attribute), 782
 use_min (bpy.types.TexMapping attribute), 872
 use_min_distance (bpy.types.FieldSettings attribute), 408
 use_min_x (bpy.types.FModifierLimits attribute), 401
 use_min_x (bpy.types.LimitLocationConstraint attribute), 509
 use_min_x (bpy.types.LimitScaleConstraint attribute), 512
 use_min_y (bpy.types.FModifierLimits attribute), 401
 use_min_y (bpy.types.LimitLocationConstraint attribute), 509
 use_min_y (bpy.types.LimitScaleConstraint attribute), 512
 use_min_z (bpy.types.LimitLocationConstraint attribute), 509
 use_min_z (bpy.types.LimitScaleConstraint attribute), 512
 use_mipmap (bpy.types.EnvironmentMapTexture attribute), 382
 use_mipmap (bpy.types.ImageTexture attribute), 461
 use_mipmap_gauss (bpy.types.EnvironmentMapTexture attribute), 382
 use_mipmap_gauss (bpy.types.ImageTexture attribute), 461
 use_mipmaps (bpy.types.UserPreferencesSystem attribute), 998
 use_mirror_merge (bpy.types.MirrorModifier attribute), 580
 use_mirror_topology (bpy.types.Mesh attribute), 551
 use_mirror_u (bpy.types.MirrorModifier attribute), 580
 use_mirror_v (bpy.types.MirrorModifier attribute), 581
 use_mirror_vertex_groups (bpy.types.MirrorModifier attribute), 581
 use_mirror_x (bpy.types.Armature attribute), 176
 use_mirror_x (bpy.types.ImageTexture attribute), 461
 use_mirror_x (bpy.types.Mesh attribute), 551
 use_mirror_y (bpy.types.ImageTexture attribute), 462
 use_mist (bpy.types.Material attribute), 525
 use_mist (bpy.types.WorldMistSettings attribute), 1033
 use_module (bpy.types.Text attribute), 873
 use_motion_blur (bpy.types.Filter2DActuator attribute), 411
 use_motion_blur (bpy.types.RenderSettings attribute), 735
 use_motion_extrapolate (bpy.types.TransformConstraint attribute), 956
 use_mouse_auto_depth (bpy.types.UserPreferencesView attribute), 1001
 use_mouse_continuous (bpy.types.UserPreferencesInput attribute), 995
 use_mouse_emulate_3_button (bpy.types.UserPreferencesInput attribute), 995
 use_mouse_mmb_paste (bpy.types.UserPreferencesInput attribute), 995
 use_mouse_over_open (bpy.types.UserPreferencesView attribute), 1002
 use_multi_modifier (bpy.types.ArmatureModifier attribute), 180
 use_multiple_springs (bpy.types.FieldSettings attribute), 408
 use_multiply_size_mass (bpy.types.ParticleSettings attribute), 668
 use_negative (bpy.types.Lamp attribute), 497
 use_negative (bpy.types.MetaElement attribute), 577
 use_negative_direction (bpy.types.ShrinkwrapModifier attribute), 803
 use_negative_frames (bpy.types.UserPreferencesEdit attribute), 991
 use_nla (bpy.types.AnimData attribute), 163
 use_nodes (bpy.types.Material attribute), 525
 use_nodes (bpy.types.Scene attribute), 745
 use_nodes (bpy.types.Texture attribute), 883
 use_normal (bpy.types.ConstraintActuator attribute), 332
 use_normal (bpy.types.ParticleInstanceModifier attribute), 655
 use_normal (bpy.types.VertexPaint attribute), 1010
 use_normal (bpy.types.WaveModifier attribute), 1020
 use_normal_calculate (bpy.types.ScrewModifier attribute), 763
 use_normal_falloff (bpy.types.ImagePaint attribute), 456
 use_normal_flip (bpy.types.ScrewModifier attribute), 763
 use_normal_map (bpy.types.ImageTexture attribute), 462
 use_normal_x (bpy.types.WaveModifier attribute), 1020
 use_normal_y (bpy.types.WaveModifier attribute), 1020
 use_normal_z (bpy.types.WaveModifier attribute), 1020
 use_object_color (bpy.types.Material attribute), 525
 use_object_color (bpy.types.MeshTextureFace attribute), 567
 use_object_coords (bpy.types.FieldSettings attribute), 408
 use_object_offset (bpy.types.ArrayModifier attribute), 183
 use_object_screw_offset (bpy.types.ScrewModifier attribute), 763
 use_occlude (bpy.types.ImagePaint attribute), 456
 use_occlude_geometry (bpy.types.SpaceView3D attribute), 848

use_occlusion (bpy.types.VisibilityActuator attribute), 1011
use_occlusion_culling (bpy.types.SceneGameData attribute), 752
use_offset (bpy.types.CopyLocationConstraint attribute), 338
use_offset (bpy.types.CopyRotationConstraint attribute), 340
use_offset (bpy.types.CopyScaleConstraint attribute), 341
use_offset_pressure (bpy.types.Brush attribute), 239
use_on_land (bpy.types.BoidRule attribute), 218
use_onion_skinning (bpy.types.GPencilLayer attribute), 423
use_only_boost (bpy.types.GlowSequence attribute), 436
use_only_selected_curves_handles (bpy.types.SpaceGraphEditor attribute), 828
use_only_selected_keyframe_handles (bpy.types.SpaceGraphEditor attribute), 828
use_only_shadow (bpy.types.AreaLamp attribute), 172
use_only_shadow (bpy.types.Material attribute), 526
use_only_shadow (bpy.types.PointLamp attribute), 692
use_only_shadow (bpy.types.SpotLamp attribute), 859
use_only_shadow (bpy.types.SunLamp attribute), 868
use_only_vertices (bpy.types.BevelModifier attribute), 186
use_original_normal (bpy.types.Brush attribute), 239
use_outflow (bpy.types.SmokeFlowSettings attribute), 809
use_outside (bpy.types.Lattice attribute), 503
use_overwrite (bpy.types.RenderSettings attribute), 735
use_overwrite (bpy.types.SpaceTextEditor attribute), 840
use_own_layer (bpy.types.Lamp attribute), 497
use_paint_image (bpy.types.Brush attribute), 239
use_paint_mask (bpy.types.Mesh attribute), 551
use_paint_sculpt (bpy.types.Brush attribute), 239
use_paint_vertex (bpy.types.Brush attribute), 239
use_paint_weight (bpy.types.Brush attribute), 239
use_panorama (bpy.types.Camera attribute), 245
use_parent_particles (bpy.types.ParticleSettings attribute), 668
use_particle_kill (bpy.types.CollisionSettings attribute), 263
use_pass_ambient_occlusion (bpy.types.SceneRenderLayer attribute), 755
use_pass_color (bpy.types.SceneRenderLayer attribute), 755
use_pass_combined (bpy.types.SceneRenderLayer attribute), 755
use_pass_diffuse (bpy.types.SceneRenderLayer attribute), 755
use_pass_emit (bpy.types.SceneRenderLayer attribute), 755
use_pass_environment (bpy.types.SceneRenderLayer attribute), 755
use_pass_indirect (bpy.types.SceneRenderLayer attribute), 755
use_pass_mist (bpy.types.SceneRenderLayer attribute), 756
use_pass_normal (bpy.types.SceneRenderLayer attribute), 756
use_pass_object_index (bpy.types.SceneRenderLayer attribute), 756
use_pass_reflection (bpy.types.SceneRenderLayer attribute), 756
use_pass_refraction (bpy.types.SceneRenderLayer attribute), 756
use_pass_shadow (bpy.types.SceneRenderLayer attribute), 756
use_pass_specular (bpy.types.SceneRenderLayer attribute), 756
use_pass_uv (bpy.types.SceneRenderLayer attribute), 756
use_pass_vector (bpy.types.SceneRenderLayer attribute), 756
use_pass_z (bpy.types.SceneRenderLayer attribute), 756
use_path (bpy.types.Curve attribute), 345
use_path (bpy.types.ParticleInstanceModifier attribute), 655
use_path_follow (bpy.types.Curve attribute), 345
use_persistent (bpy.types.Brush attribute), 239
use_persistent (bpy.types.ConstraintActuator attribute), 332
use_pin_cloth (bpy.types.ClothSettings attribute), 257
use_pin_id (bpy.types.SpaceProperties attribute), 837
use_pivot_point_align (bpy.types.SpaceView3D attribute), 848
use_placeholder (bpy.types.RenderSettings attribute), 735
use_plane_trim (bpy.types.Brush attribute), 240
use_play_3d_editors (bpy.types.Screen attribute), 762
use_play_animation_editors (bpy.types.Screen attribute), 762
use_play_image_editors (bpy.types.Screen attribute), 762
use_play_node_editors (bpy.types.Screen attribute), 762
use_play_properties_editors (bpy.types.Screen attribute), 762
use_play_sequence_editors (bpy.types.Screen attribute), 762
use_play_top_left_3d_editor (bpy.types.Screen attribute), 762
use_positive_direction (bpy.types.ShrinkwrapModifier attribute), 803
use_predict (bpy.types.BoidRuleAvoid attribute), 220
use_predict (bpy.types.BoidRuleGoal attribute), 224
use_premultiply (bpy.types.AdjustmentSequence attribute), 160

use_premultiply (bpy.types.CompositorNodeAlphaOver attribute), 270
 use_premultiply (bpy.types.EffectSequence attribute), 375
 use_premultiply (bpy.types.Image attribute), 454
 use_premultiply (bpy.types.ImageSequence attribute), 458
 use_premultiply (bpy.types.MetaSequence attribute), 579
 use_premultiply (bpy.types.MovieSequence attribute), 587
 use_premultiply (bpy.types.MulticamSequence attribute), 590
 use_premultiply (bpy.types.SceneSequence attribute), 759
 use_preserve_length (bpy.types.ParticleEdit attribute), 652
 use_preserve_root (bpy.types.ParticleEdit attribute), 652
 use_preserve_shape (bpy.types.ParticleInstanceModifier attribute), 655
 use_pressure_jitter (bpy.types.Brush attribute), 240
 use_pressure_size (bpy.types.Brush attribute), 240
 use_pressure_spacing (bpy.types.Brush attribute), 240
 use_pressure_strength (bpy.types.Brush attribute), 240
 use_preview (bpy.types.CompositorNodeDefocus attribute), 287
 use_preview_alpha (bpy.types.Texture attribute), 883
 use_preview_images (bpy.types.UserPreferencesSystem attribute), 998
 use_preview_range (bpy.types.Scene attribute), 745
 use_priority (bpy.types.Controller attribute), 337
 use_project_x (bpy.types.ShrinkwrapModifier attribute), 803
 use_project_y (bpy.types.ShrinkwrapModifier attribute), 804
 use_project_z (bpy.types.ShrinkwrapModifier attribute), 804
 use_projection (bpy.types.ImagePaint attribute), 456
 use_projector (bpy.types.CompositorNodeLensdist attribute), 300
 use_proportional_edit_objects (bpy.types.ToolSettings attribute), 951
 use_proxy (bpy.types.AdjustmentSequence attribute), 160
 use_proxy (bpy.types.EffectSequence attribute), 375
 use_proxy (bpy.types.ImageSequence attribute), 458
 use_proxy (bpy.types.MetaSequence attribute), 579
 use_proxy (bpy.types.MovieSequence attribute), 587
 use_proxy (bpy.types.MulticamSequence attribute), 590
 use_proxy (bpy.types.SceneSequence attribute), 759
 use_proxy_custom_directory (bpy.types.AdjustmentSequence attribute), 160
 use_proxy_custom_directory (bpy.types.EffectSequence attribute), 375
 use_proxy_custom_directory (bpy.types.ImageSequence attribute), 458
 use_proxy_custom_directory (bpy.types.MetaSequence attribute), 579
 use_proxy_custom_directory (bpy.types.MovieSequence attribute), 587
 use_proxy_custom_directory (bpy.types.MulticamSequence attribute), 590
 use_proxy_custom_directory (bpy.types.SceneSequence attribute), 759
 use_proxy_custom_file (bpy.types.AdjustmentSequence attribute), 160
 use_proxy_custom_file (bpy.types.EffectSequence attribute), 375
 use_proxy_custom_file (bpy.types.ImageSequence attribute), 458
 use_proxy_custom_file (bpy.types.MetaSequence attribute), 579
 use_proxy_custom_file (bpy.types.MovieSequence attribute), 587
 use_proxy_custom_file (bpy.types.MulticamSequence attribute), 590
 use_proxy_custom_file (bpy.types.SceneSequence attribute), 759
 use_puff_volume (bpy.types.ParticleBrush attribute), 649
 use_pulse (bpy.types.CollisionSensor attribute), 262
 use_pulse_false_level (bpy.types.Sensor attribute), 766
 use_pulse_true_level (bpy.types.Sensor attribute), 766
 use_quality_normals (bpy.types.SolidifyModifier attribute), 817
 use_quick_cache (bpy.types.PointCache attribute), 686
 use_radial_max (bpy.types.FieldSettings attribute), 408
 use_radial_min (bpy.types.FieldSettings attribute), 408
 use_radiosity (bpy.types.RenderSettings attribute), 735
 use_radius (bpy.types.Curve attribute), 345
 use_radius_as_size (bpy.types.CastModifier attribute), 248
 use_rake (bpy.types.Brush attribute), 240
 use_random_order (bpy.types.BuildModifier attribute), 243
 use_random_rotation (bpy.types.Brush attribute), 240
 use_ray_shadow_bias (bpy.types.Material attribute), 526
 use_raytrace (bpy.types.Material attribute), 526
 use_raytrace (bpy.types.RenderSettings attribute), 735
 use_react_multiple (bpy.types.ParticleSettings attribute), 668
 use_react_start_end (bpy.types.ParticleSettings attribute), 668
 use_realtime_update (bpy.types.SpaceDopeSheetEditor attribute), 826
 use_realtime_update (bpy.types.SpaceGraphEditor attribute), 828

use_realtime_update (bpy.types.SpaceImageEditor attribute), 830
use_realtime_update (bpy.types.SpaceNLA attribute), 833
use_record_with_nla (bpy.types.ToolSettings attribute), 951
use_relative (bpy.types.CompositorNodeBlur attribute), 272
use_relative (bpy.types.Key attribute), 470
use_relative (bpy.types.SimpleDeformModifier attribute), 805
use_relative_location (bpy.types.PivotConstraint attribute), 681
use_relative_offset (bpy.types.ArrayModifier attribute), 183
use_relative_paths (bpy.types.UserPreferencesFilePaths attribute), 993
use_render_adaptive (bpy.types.ParticleSettings attribute), 668
use_render_emitter (bpy.types.ParticleSettings attribute), 668
use_repeat (bpy.types.DelaySensor attribute), 354
use_replace_display_mesh (bpy.types.EditObjectActuator attribute), 373
use_replace_physics_mesh (bpy.types.EditObjectActuator attribute), 373
use_restore_mesh (bpy.types.Brush attribute), 240
use_reverse (bpy.types.NlaStrip attribute), 598
use_reverse_frames (bpy.types.AdjustmentSequence attribute), 160
use_reverse_frames (bpy.types.ControlFluidSettings attribute), 336
use_reverse_frames (bpy.types.DomainFluidSettings attribute), 359
use_reverse_frames (bpy.types.EffectSequence attribute), 375
use_reverse_frames (bpy.types.ImageSequence attribute), 458
use_reverse_frames (bpy.types.MetaSequence attribute), 579
use_reverse_frames (bpy.types.MovieSequence attribute), 588
use_reverse_frames (bpy.types.MulticamSequence attribute), 590
use_reverse_frames (bpy.types.SceneSequence attribute), 759
use_rgb_to_intensity (bpy.types.TextureSlot attribute), 904
use_rim (bpy.types.SolidifyModifier attribute), 818
use_ring (bpy.types.MaterialHalo attribute), 529
use_root_coords (bpy.types.FieldSettings attribute), 408
use_rotate_45 (bpy.types.CompositorNodeGlare attribute), 294
use_rotate_around_active (bpy.types.UserPreferencesView attribute), 1002
use_rotate_from_normal (bpy.types.GameObjectSettings attribute), 431
use_rotation (bpy.types.FloorConstraint attribute), 414
use_rotation (bpy.types.KinematicConstraint attribute), 495
use_rotation_x (bpy.types.ChildOfConstraint attribute), 250
use_rotation_y (bpy.types.ChildOfConstraint attribute), 250
use_rotation_z (bpy.types.ChildOfConstraint attribute), 250
use_save_buffers (bpy.types.RenderSettings attribute), 735
use_save_preview_images (bpy.types.UserPreferencesFilePaths attribute), 993
use_scale_x (bpy.types.ChildOfConstraint attribute), 250
use_scale_y (bpy.types.ChildOfConstraint attribute), 250
use_scale_z (bpy.types.ChildOfConstraint attribute), 250
use_scripts_auto_execute (bpy.types.UserPreferencesSystem attribute), 998
use_seam (bpy.types.MeshEdge attribute), 557
use_self_collision (bpy.types.ClothCollisionSettings attribute), 254
use_self_collision (bpy.types.SoftBodySettings attribute), 816
use_self_effect (bpy.types.ParticleSettings attribute), 668
use_separate (bpy.types.UnitSettings attribute), 985
use_sequencer (bpy.types.RenderSettings attribute), 735
use_sequencer_gl_preview (bpy.types.RenderSettings attribute), 735
use_sequencer_gl_render (bpy.types.RenderSettings attribute), 736
use_servo_limit_x (bpy.types.ObjectActuator attribute), 623
use_servo_limit_y (bpy.types.ObjectActuator attribute), 623
use_servo_limit_z (bpy.types.ObjectActuator attribute), 623
use_shaded (bpy.types.MaterialHalo attribute), 529
use_shadeless (bpy.types.Material attribute), 526
use_shadow_cast (bpy.types.MeshTextureFace attribute), 567
use_shadow_layer (bpy.types.AreaLamp attribute), 172
use_shadow_layer (bpy.types.PointLamp attribute), 692
use_shadow_layer (bpy.types.SpotLamp attribute), 859
use_shadow_layer (bpy.types.SunLamp attribute), 868
use_shadows (bpy.types.Material attribute), 526

use_shadows (bpy.types.RenderSettings attribute), 736
 use_shape_key_edit_mode (bpy.types.Object attribute), 617
 use_shape_match (bpy.types.GameSoftBodySettings attribute), 434
 use_simplify (bpy.types.ParticleSettings attribute), 668
 use_simplify (bpy.types.RenderSettings attribute), 736
 use_simplify_triangulate (bpy.types.RenderSettings attribute), 736
 use_simplify_viewport (bpy.types.ParticleSettings attribute), 668
 use_single_layer (bpy.types.RenderSettings attribute), 736
 use_size (bpy.types.ExplodeModifier attribute), 386
 use_size (bpy.types.ParticleInstanceModifier attribute), 655
 use_size_deflect (bpy.types.ParticleSettings attribute), 668
 use_sky (bpy.types.LampSkySettings attribute), 499
 use_sky (bpy.types.Material attribute), 526
 use_sky (bpy.types.SceneRenderLayer attribute), 756
 use_sky_blend (bpy.types.World attribute), 1029
 use_sky_paper (bpy.types.World attribute), 1029
 use_sky_real (bpy.types.World attribute), 1029
 use_sleep (bpy.types.GameObjectSettings attribute), 431
 use_slow_parent (bpy.types.Object attribute), 617
 use_small_caps (bpy.types.TextCharacterFormat attribute), 876
 use_smooth (bpy.types.MeshFace attribute), 559
 use_smooth (bpy.types.Spline attribute), 852
 use_smooth_stroke (bpy.types.Brush attribute), 240
 use_snap (bpy.types.ToolSettings attribute), 951
 use_snap_align_rotation (bpy.types.ToolSettings attribute), 951
 use_snap_peel_object (bpy.types.ToolSettings attribute), 951
 use_snap_project (bpy.types.ToolSettings attribute), 951
 use_snap_project_self (bpy.types.ToolSettings attribute), 951
 use_snap_to_pixels (bpy.types.SpaceUVEditor attribute), 843
 use_soft (bpy.types.MaterialHalo attribute), 529
 use_solid (bpy.types.SceneRenderLayer attribute), 756
 use_sound_3d (bpy.types.SoundActuator attribute), 820
 use_space (bpy.types.Brush attribute), 240
 use_space_atten (bpy.types.Brush attribute), 240
 use_specular (bpy.types.Lamp attribute), 497
 use_specular (bpy.types.ShaderNodeExtendedMaterial attribute), 779
 use_specular (bpy.types.ShaderNodeMaterial attribute), 783
 use_specular_ramp (bpy.types.Material attribute), 526
 use_speed_vectors (bpy.types.DomainFluidSettings attribute), 359
 use_sphere (bpy.types.PointLamp attribute), 692
 use_sphere (bpy.types.SpotLamp attribute), 859
 use_spray (bpy.types.VertexPaint attribute), 1010
 use_square (bpy.types.SpotLamp attribute), 859
 use_sss (bpy.types.RenderSettings attribute), 736
 use_stamp (bpy.types.RenderSettings attribute), 736
 use_stamp_camera (bpy.types.RenderSettings attribute), 736
 use_stamp_date (bpy.types.RenderSettings attribute), 736
 use_stamp_filename (bpy.types.RenderSettings attribute), 736
 use_stamp_frame (bpy.types.RenderSettings attribute), 736
 use_stamp_lens (bpy.types.RenderSettings attribute), 736
 use_stamp_marker (bpy.types.RenderSettings attribute), 736
 use_stamp_note (bpy.types.RenderSettings attribute), 736
 use_stamp_note (bpy.types.Scene attribute), 745
 use_stamp_render_time (bpy.types.RenderSettings attribute), 737
 use_stamp_scene (bpy.types.RenderSettings attribute), 737
 use_stamp_sequencer_strip (bpy.types.RenderSettings attribute), 737
 use_stamp_time (bpy.types.RenderSettings attribute), 737
 use_star (bpy.types.MaterialHalo attribute), 529
 use_stars (bpy.types.WorldStarsSettings attribute), 1034
 use_stencil (bpy.types.TextureSlot attribute), 904
 use_stencil_layer (bpy.types.ImagePaint attribute), 456
 use_sticky (bpy.types.FloorConstraint attribute), 414
 use_stiff_quads (bpy.types.SoftBodySettings attribute), 816
 use_stiffness_scale (bpy.types.ClothSettings attribute), 257
 use_still_frame (bpy.types.VoxelData attribute), 1015
 use_strand (bpy.types.SceneRenderLayer attribute), 756
 use_strand_primitive (bpy.types.ParticleSettings attribute), 668
 use_stretch (bpy.types.Curve attribute), 345
 use_stretch (bpy.types.KinematicConstraint attribute), 495
 use_stroke_endpoints (bpy.types.GreasePencil attribute), 438
 use_subsurf_uv (bpy.types.SubsurfModifier attribute), 867
 use_symmetry_feather (bpy.types.Sculpt attribute), 765
 use_symmetry_x (bpy.types.Sculpt attribute), 765
 use_symmetry_y (bpy.types.Sculpt attribute), 765
 use_symmetry_z (bpy.types.Sculpt attribute), 765
 use_tabs_as_spaces (bpy.types.Text attribute), 873
 use_tabs_as_spaces (bpy.types.UserPreferencesSystem attribute), 998
 use_tail (bpy.types.KinematicConstraint attribute), 495
 use_tangent_shading (bpy.types.Material attribute), 526

use_tangent_shading (bpy.types.MaterialStrand attribute), 536
use_tap (bpy.types.Sensor attribute), 767
use_target (bpy.types.KinematicConstraint attribute), 495
use_target_z (bpy.types.TrackToConstraint attribute), 953
use_targets (bpy.types.PythonConstraint attribute), 708
use_text_antialiasing (bpy.types.UserPreferencesSystem attribute), 998
use_texture (bpy.types.MaterialHalo attribute), 529
use_texture_overlay (bpy.types.Brush attribute), 240
use_textured_fonts (bpy.types.UserPreferencesSystem attribute), 998
use_textures (bpy.types.Material attribute), 526
use_textures (bpy.types.RenderSettings attribute), 737
use_threaded (bpy.types.Sculpt attribute), 765
use_tiff_16bit (bpy.types.RenderSettings attribute), 737
use_tiles (bpy.types.Image attribute), 454
use_time_offset (bpy.types.Curve attribute), 345
use_time_offset_add_parent (bpy.types.Object attribute), 617
use_time_offset_edit (bpy.types.Object attribute), 617
use_time_offset_parent (bpy.types.Object attribute), 617
use_time_offset_particle (bpy.types.Object attribute), 617
use_time_override (bpy.types.DomainFluidSettings attribute), 359
use_transform (bpy.types.CastModifier attribute), 248
use_transform_limit (bpy.types.LimitLocationConstraint attribute), 509
use_transform_limit (bpy.types.LimitRotationConstraint attribute), 510
use_transform_limit (bpy.types.LimitScaleConstraint attribute), 512
use_translate_buttons (bpy.types.UserPreferencesSystem attribute), 998
use_translate_toolbox (bpy.types.UserPreferencesSystem attribute), 998
use_translate_tooltips (bpy.types.UserPreferencesSystem attribute), 998
use_translation (bpy.types.AdjustmentSequence attribute), 160
use_translation (bpy.types.EffectSequence attribute), 375
use_translation (bpy.types.ImageSequence attribute), 458
use_translation (bpy.types.MetaSequence attribute), 579
use_translation (bpy.types.MovieSequence attribute), 588
use_translation (bpy.types.MulticamSequence attribute), 590
use_translation (bpy.types.SceneSequence attribute), 759
use_transparency (bpy.types.Material attribute), 526
use_transparent_shadows (bpy.types.Material attribute), 526
use_turbulence (bpy.types.PointDensity attribute), 689
use_twoside (bpy.types.MeshTextureFace attribute), 567
use_umbra (bpy.types.AreaLamp attribute), 172
use_underline (bpy.types.TextCharacterFormat attribute), 876
use_uniform_scale (bpy.types.TransformSequence attribute), 958
use_unspill (bpy.types.CompositorNodeColorSpill attribute), 279
use_uv_as_generated (bpy.types.Curve attribute), 346
use_uv_as_generated (bpy.types.SurfaceCurve attribute), 869
use_uv_as_generated (bpy.types.TextCurve attribute), 878
use_uv_select_sync (bpy.types.ToolSettings attribute), 951
use_velocity_length (bpy.types.ParticleSettings attribute), 668
use_vertex_buffer_objects (bpy.types.UserPreferencesSystem attribute), 998
use_vertex_color_light (bpy.types.Material attribute), 526
use_vertex_color_paint (bpy.types.Material attribute), 526
use_vertex_groups (bpy.types.ArmatureModifier attribute), 180
use_vertex_normal (bpy.types.MaterialHalo attribute), 529
use_viscoelastic_springs (bpy.types.SPHFluidSettings attribute), 742
use_visible (bpy.types.VisibilityActuator attribute), 1011
use_visual_keying (bpy.types.UserPreferencesEdit attribute), 991
use_volume_preserve (bpy.types.WarpModifier attribute), 1018
use_weight_color_range (bpy.types.UserPreferencesSystem attribute), 998
use_whole_group (bpy.types.ParticleSettings attribute), 669
use_wrap (bpy.types.Brush attribute), 240
use_wrap (bpy.types.CompositorNodeDBlur attribute), 286
use_x (bpy.types.CastModifier attribute), 248
use_x (bpy.types.CopyLocationConstraint attribute), 338
use_x (bpy.types.CopyRotationConstraint attribute), 340
use_x (bpy.types.CopyScaleConstraint attribute), 341
use_x (bpy.types.MirrorModifier attribute), 581
use_x (bpy.types.ShrinkwrapConstraint attribute), 802
use_x (bpy.types.SmoothModifier attribute), 811
use_x (bpy.types.WaveModifier attribute), 1020
use_x_ray (bpy.types.RaySensor attribute), 715
use_y (bpy.types.CastModifier attribute), 248
use_y (bpy.types.CopyLocationConstraint attribute), 338
use_y (bpy.types.CopyRotationConstraint attribute), 340
use_y (bpy.types.CopyScaleConstraint attribute), 341
use_y (bpy.types.MirrorModifier attribute), 581
use_y (bpy.types.ShrinkwrapConstraint attribute), 802

use_y (bpy.types.SmoothModifier attribute), 811
 use_y (bpy.types.WaveModifier attribute), 1020
 use_y_stretch (bpy.types.SplineIKConstraint attribute), 854
 use_z (bpy.types.CastModifier attribute), 248
 use_z (bpy.types.CopyLocationConstraint attribute), 338
 use_z (bpy.types.CopyRotationConstraint attribute), 340
 use_z (bpy.types.CopyScaleConstraint attribute), 341
 use_z (bpy.types.MirrorModifier attribute), 581
 use_z (bpy.types.ShrinkwrapConstraint attribute), 802
 use_z (bpy.types.SmoothModifier attribute), 811
 use_zbuffer (bpy.types.CompositorNodeDefocus attribute), 287
 use_zmask (bpy.types.SceneRenderLayer attribute), 757
 use_zoom_to_mouse (bpy.types.UserPreferencesView attribute), 1002
 use_ztransp (bpy.types.SceneRenderLayer attribute), 757
 useAllKeys (bge.types.SCA_KeyboardSensor attribute), 1186
 useChildren (bge.types.KX_IpoActuator attribute), 1155
 useContinue (bge.types.BL_ActionActuator attribute), 1136
 useDisplayMesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1173
 useHighPriority (bge.types.SCA_IController attribute), 1135
 useIpoAdd (bge.types.KX_IpoActuator attribute), 1155
 useIpoAsForce (bge.types.KX_IpoActuator attribute), 1155
 useIpoLocal (bge.types.KX_IpoActuator attribute), 1155
 useLocalAngV (bge.types.KX_ObjectActuator attribute), 1162
 useLocalDLoc (bge.types.KX_ObjectActuator attribute), 1161
 useLocalDRot (bge.types.KX_ObjectActuator attribute), 1161
 useLocalForce (bge.types.KX_ObjectActuator attribute), 1161
 useLocalLinV (bge.types.KX_ObjectActuator attribute), 1161
 useLocalTorque (bge.types.KX_ObjectActuator attribute), 1161
 useMaterial (bge.types.KX_RaySensor attribute), 1170
 useMaterial (bge.types.KX_TouchSensor attribute), 1159
 useNegPulseMode (bge.types.SCA_ISensor attribute), 1134
 useOcclusion (bge.types.KX_VisibilityActuator attribute), 1182
 usePhysicsMesh (bge.types.KX_SCA_ReplaceMeshActuator attribute), 1173
 usePosPulseMode (bge.types.SCA_ISensor attribute), 1134
 usePropBody (bge.types.KX_NetworkMessageActuator attribute), 1160
 usePulseCollision (bge.types.KX_TouchSensor attribute), 1159
 usePulseFocus (bge.types.KX_MouseFocusSensor attribute), 1159
 user_clear() (bpy.types.ID method), 449
 user_resource() (in module bpy.utils), 1046
 user_script_path() (in module bpy.utils), 1046
 useRecursion (bge.types.KX_VisibilityActuator attribute), 1183
 useRestart (bge.types.KX_SceneActuator attribute), 1176
 userjit (bpy.types.ParticleSettings attribute), 669
 userpref_show() (in module bpy.ops.screen), 100
 UserPreferences (class in bpy.types), 987
 UserPreferences.addons (in module bpy.types), 987
 UserPreferences.edit (in module bpy.types), 987
 UserPreferences.filepaths (in module bpy.types), 987
 UserPreferences.inputs (in module bpy.types), 987
 UserPreferences.system (in module bpy.types), 987
 UserPreferences.themes (in module bpy.types), 987
 UserPreferences.ui_styles (in module bpy.types), 987
 UserPreferences.view (in module bpy.types), 988
 UserPreferencesEdit (class in bpy.types), 988
 UserPreferencesFilePaths (class in bpy.types), 991
 UserPreferencesInput (class in bpy.types), 994
 UserPreferencesInput.edited_keymaps (in module bpy.types), 994
 UserPreferencesSystem (class in bpy.types), 996
 UserPreferencesSystem.solid_lights (in module bpy.types), 997
 UserPreferencesSystem.weight_color_range (in module bpy.types), 999
 UserPreferencesView (class in bpy.types), 999
 UserSolidLight (class in bpy.types), 1002
 useViewport (bge.types.KX_Camera attribute), 1191
 useXRay (bge.types.KX_RaySensor attribute), 1171
 useXY (bge.types.KX_CameraActuator attribute), 1142
 UV (bge.types.KX_VertexProxy attribute), 1180
 uv (bpy.types.MeshTextureFace attribute), 567
 uv1 (bpy.types.MeshTextureFace attribute), 567
 uv2 (bpy.types.MeshTextureFace attribute), 567
 uv3 (bpy.types.MeshTextureFace attribute), 568
 uv4 (bpy.types.MeshTextureFace attribute), 568
 uv_layer (bpy.types.DisplaceModifier attribute), 355
 uv_layer (bpy.types.MaterialStrand attribute), 536
 uv_layer (bpy.types.MaterialTextureSlot attribute), 542
 uv_layer (bpy.types.ParticleSettingsTextureSlot attribute), 672
 uv_layer (bpy.types.ShaderNodeGeometry attribute), 780
 uv_layer (bpy.types.UVProjectModifier attribute), 983
 uv_layer (bpy.types.WarpModifier attribute), 1018
 uv_layer (bpy.types.WaveModifier attribute), 1020
 uv_raw (bpy.types.MeshTextureFace attribute), 568
 uv_select_mode (bpy.types.ToolSettings attribute), 951
 uv_texture_add() (in module bpy.ops.mesh), 64

uv_texture_clone (bpy.types.Mesh attribute), 551
uv_texture_clone_index (bpy.types.Mesh attribute), 551
uv_texture_remove() (in module bpy.ops.mesh), 64
uv_texture_stencil (bpy.types.Mesh attribute), 551
uv_texture_stencil_index (bpy.types.Mesh attribute), 551
UVProjectModifier (class in bpy.types), 982
UVProjectModifier.projectors (in module bpy.types), 982
UVProjector (class in bpy.types), 983
uvs_mirror() (in module bpy.ops.mesh), 64
uvs_rotate() (in module bpy.ops.mesh), 64
UVTextures (class in bpy.types), 984

V

v (bge.types.KX_VertexProxy attribute), 1180
v (mathutils.Color attribute), 1056
v1 (bge.types.KX_PolyProxy attribute), 1163
v2 (bge.types.KX_PolyProxy attribute), 1163
v2 (bge.types.KX_VertexProxy attribute), 1181
v3 (bge.types.KX_PolyProxy attribute), 1163
v4 (bge.types.KX_PolyProxy attribute), 1163
validate() (bge.types.BL_Shader method), 1140
validate() (bpy.types.Mesh method), 552
value (bge.types.KX_ArmatureSensor attribute), 1196
value (bge.types.SCA_2DFilterActuator attribute), 1183
value (bge.types.SCA_PropertyActuator attribute), 1187
value (bge.types.SCA_PropertySensor attribute), 1187
value (bpy.types.ArmatureSensor attribute), 181
value (bpy.types.GameBooleanProperty attribute), 426
value (bpy.types.GameFloatProperty attribute), 427
value (bpy.types.GameIntProperty attribute), 427
value (bpy.types.GameStringProperty attribute), 434
value (bpy.types.GameTimerProperty attribute), 435
value (bpy.types.KeyMapItem attribute), 477
value (bpy.types.MeshFloatProperty attribute), 561
value (bpy.types.MeshIntProperty attribute), 562
value (bpy.types.MeshStringProperty attribute), 565
value (bpy.types.PropertyActuator attribute), 704
value (bpy.types.PropertySensor attribute), 707
value (bpy.types.ShapeKey attribute), 799
value_max (bpy.types.PropertySensor attribute), 707
value_min (bpy.types.PropertySensor attribute), 707
value_offset (bpy.types.FModifierFunctionGenerator attribute), 399
value_sliders (bpy.types.ThemeDopeSheet attribute), 912
ValueNodeSocket (class in bpy.types), 1003
values() (bpy.types.bpy_prop_collection method), 1040
values() (bpy.types.bpy_struct method), 1044
Vector (class in mathutils), 1064
Vector.angle() (in module mathutils), 1065
Vector.copy() (in module mathutils), 1065
Vector.difference() (in module mathutils), 1067
Vector.lerp() (in module mathutils), 1066
Vector.project() (in module mathutils), 1066
Vector.rotate() (in module mathutils), 1067

VectorFont (class in bpy.types), 1004
VectorFont.filepath (in module bpy.types), 1004
VectorFont.packed_file (in module bpy.types), 1004
VectorNodeSocket (class in bpy.types), 1005
vectorscope_alpha (bpy.types.Scopes attribute), 760
velocity (aud.Handle attribute), 1128
velocity (bge.types.KX_SoundActuator attribute), 1177
velocity (bpy.types.Particle attribute), 647
velocity (bpy.types.ParticleKey attribute), 656
velocity_factor (bpy.types.ParticleSettingsTextureSlot attribute), 672
velocity_factor (bpy.types.SmokeFlowSettings attribute), 809
velocity_max (bpy.types.GameObjectSettings attribute), 431
velocity_max (bpy.types.Itasc attribute), 468
velocity_min (bpy.types.GameObjectSettings attribute), 431
velocity_radius (bpy.types.ControlFluidSettings attribute), 336
velocity_strength (bpy.types.ControlFluidSettings attribute), 336
version (in module bpy.app), 1048
version_char (in module bpy.app), 1048
version_cycle (in module bpy.app), 1048
version_string (in module bpy.app), 1048
vertex (bpy.types.ThemeGraphEditor attribute), 918
vertex (bpy.types.ThemeImageEditor attribute), 920
vertex (bpy.types.ThemeView3D attribute), 942
vertex_add() (in module bpy.ops.curve), 28
vertex_cache_space (bpy.types.PointDensity attribute), 689
vertex_color_add() (in module bpy.ops.mesh), 64
vertex_color_dirt() (in module bpy.ops.paint), 89
vertex_color_remove() (in module bpy.ops.mesh), 64
vertex_color_set() (in module bpy.ops.paint), 89
vertex_group (bpy.types.ArmatureModifier attribute), 180
vertex_group (bpy.types.CastModifier attribute), 248
vertex_group (bpy.types.CurveModifier attribute), 350
vertex_group (bpy.types.DisplaceModifier attribute), 355
vertex_group (bpy.types.ExplodeModifier attribute), 386
vertex_group (bpy.types.HookModifier attribute), 447
vertex_group (bpy.types.Lattice attribute), 503
vertex_group (bpy.types.LatticeModifier attribute), 504
vertex_group (bpy.types.MaskModifier attribute), 520
vertex_group (bpy.types.MeshDeformModifier attribute), 556
vertex_group (bpy.types.ShapeKey attribute), 799
vertex_group (bpy.types.ShrinkwrapModifier attribute), 804
vertex_group (bpy.types.SimpleDeformModifier attribute), 805
vertex_group (bpy.types.SmoothModifier attribute), 811
vertex_group (bpy.types.SolidifyModifier attribute), 818

vertex_group (`bpy.types.WarpModifier` attribute), 1018
vertex_group (`bpy.types.WaveModifier` attribute), 1020
vertex_group_add() (in module `bpy.ops.object`), 85
vertex_group_assign() (in module `bpy.ops.object`), 85
vertex_group_bending (`bpy.types.ClothSettings` attribute), 257
vertex_group_blend() (in module `bpy.ops.object`), 85
vertex_group_clean() (in module `bpy.ops.object`), 85
vertex_group_clump (`bpy.types.ParticleSystem` attribute), 676
vertex_group_copy() (in module `bpy.ops.object`), 85
vertex_group_copy_to_linked() (in module `bpy.ops.object`), 86
vertex_group_copy_to_selected() (in module `bpy.ops.object`), 86
vertex_group_density (`bpy.types.ParticleSystem` attribute), 676
vertex_group_deselect() (in module `bpy.ops.object`), 86
vertex_group_field (`bpy.types.ParticleSystem` attribute), 677
vertex_group_goal (`bpy.types.SoftBodySettings` attribute), 816
vertex_group_invert() (in module `bpy.ops.object`), 86
vertex_group_kink (`bpy.types.ParticleSystem` attribute), 677
vertex_group_length (`bpy.types.ParticleSystem` attribute), 677
vertex_group_levels() (in module `bpy.ops.object`), 86
vertex_group_mass (`bpy.types.ClothSettings` attribute), 257
vertex_group_mass (`bpy.types.SoftBodySettings` attribute), 816
vertex_group_mirror() (in module `bpy.ops.object`), 86
vertex_group_move() (in module `bpy.ops.object`), 86
vertex_group_normalize() (in module `bpy.ops.object`), 86
vertex_group_normalize_all() (in module `bpy.ops.object`), 86
vertex_group_remove() (in module `bpy.ops.object`), 86
vertex_group_remove_from() (in module `bpy.ops.object`), 86
vertex_group_rotation (`bpy.types.ParticleSystem` attribute), 677
vertex_group_roughness_1 (`bpy.types.ParticleSystem` attribute), 677
vertex_group_roughness_2 (`bpy.types.ParticleSystem` attribute), 677
vertex_group_roughness_end (`bpy.types.ParticleSystem` attribute), 677
vertex_group_select() (in module `bpy.ops.object`), 86
vertex_group_set_active() (in module `bpy.ops.object`), 87
vertex_group_size (`bpy.types.ParticleSystem` attribute), 677
vertex_group_sort() (in module `bpy.ops.object`), 87
vertex_group_spring (`bpy.types.SoftBodySettings` attribute), 816
vertex_group_structural_stiffness (`bpy.types.ClothSettings` attribute), 257
vertex_group_tangent (`bpy.types.ParticleSystem` attribute), 677
vertex_group_velocity (`bpy.types.ParticleSystem` attribute), 677
vertex_group_weight (`bpy.types.ToolSettings` attribute), 951
vertex_normal (`bpy.types.ThemeView3D` attribute), 942
vertex_paint() (in module `bpy.ops.paint`), 89
vertex_paint_object (in module `bpy.context`), 6
vertex_paint_toggle() (in module `bpy.ops.paint`), 90
vertex_parent_set() (in module `bpy.ops.object`), 87
vertex_select (`bpy.types.ThemeGraphEditor` attribute), 918
vertex_select (`bpy.types.ThemeImageEditor` attribute), 920
vertex_select (`bpy.types.ThemeView3D` attribute), 942
vertex_size (`bpy.types.ThemeGraphEditor` attribute), 918
vertex_size (`bpy.types.ThemeImageEditor` attribute), 920
vertex_size (`bpy.types.ThemeView3D` attribute), 942
vertex_tool (`bpy.types.Brush` attribute), 241
vertex_tool_set() (in module `bpy.ops.brush`), 20
VertexColors (class in `bpy.types`), 1006
VertexGroup (class in `bpy.types`), 1007
VertexGroup.index (in module `bpy.types`), 1007
VertexGroupElement (class in `bpy.types`), 1008
VertexGroupElement.group (in module `bpy.types`), 1008
VertexGroups (class in `bpy.types`), 1009
VertexGroups.active (in module `bpy.types`), 1009
VertexPaint (class in `bpy.types`), 1010
vertices (`bpy.types.MeshEdge` attribute), 557
vertices (`bpy.types.MeshFace` attribute), 559
vertices_randomize() (in module `bpy.ops.mesh`), 64
vertices_raw (`bpy.types.MeshFace` attribute), 559
vertices_smooth() (in module `bpy.ops.mesh`), 64
vertices_sort() (in module `bpy.ops.mesh`), 64
view2d_grid_spacing_min (`bpy.types.UserPreferencesView` attribute), 1002
view_all() (in module `bpy.ops.action`), 13
view_all() (in module `bpy.ops.graph`), 41
view_all() (in module `bpy.ops.image`), 45
view_all() (in module `bpy.ops.node`), 70
view_all() (in module `bpy.ops.sequencer`), 107
view_all() (in module `bpy.ops.time`), 116
view_all() (in module `bpy.ops.view3d`), 135
view_all_preview() (in module `bpy.ops.sequencer`), 107
view_axis (`bpy.types.BackgroundImage` attribute), 185
view_cancel() (in module `bpy.ops.render`), 97
view_center_camera() (in module `bpy.ops.view3d`), 135
view_center_cursor() (in module `bpy.ops.view3d`), 135

view_distance (bpy.types.RegionView3D attribute), 718
view_ghost_border() (in module bpy.ops.sequencer), 107
view_location (bpy.types.RegionView3D attribute), 718
view_matrix (bpy.types.RegionView3D attribute), 718
view_orbit() (in module bpy.ops.view3d), 135
view_pan() (in module bpy.ops.image), 45
view_pan() (in module bpy.ops.view3d), 135
view_perspective (bpy.types.RegionView3D attribute), 718
view_persportho() (in module bpy.ops.view3d), 135
view_rotate_method (bpy.types.UserPreferencesInput attribute), 995
view_rotation (bpy.types.RegionView3D attribute), 718
view_selected() (in module bpy.ops.action), 13
view_selected() (in module bpy.ops.graph), 41
view_selected() (in module bpy.ops.image), 45
view_selected() (in module bpy.ops.sequencer), 107
view_selected() (in module bpy.ops.view3d), 135
view_show() (in module bpy.ops.render), 97
view_sliders (bpy.types.ThemeDopeSheet attribute), 912
view_sliders (bpy.types.ThemeNLAEditor attribute), 924
view_toggle() (in module bpy.ops.sequencer), 107
view_type (bpy.types.SpaceSequenceEditor attribute), 839
view_zoom() (in module bpy.ops.image), 45
view_zoom_axis (bpy.types.UserPreferencesInput attribute), 995
view_zoom_in() (in module bpy.ops.image), 46
view_zoom_method (bpy.types.UserPreferencesInput attribute), 995
view_zoom_out() (in module bpy.ops.image), 46
view_zoom_ratio() (in module bpy.ops.image), 46
view_zoom_ratio() (in module bpy.ops.sequencer), 107
VIEWMATRIX (in module bge.logic), 1218
VIEWMATRIX_INVERSE (in module bge.logic), 1218
VIEWMATRIX_INVERSETRANSPOSE (in module bge.logic), 1218
VIEWMATRIX_TRANSPOSE (in module bge.logic), 1218
viewnumpad() (in module bpy.ops.view3d), 135
viewpoint_object (bpy.types.EnvironmentMap attribute), 381
viewport_display_mode (bpy.types.DomainFluidSettings attribute), 359
viewport_shade (bpy.types.SpaceView3D attribute), 848
virtual_parents (bpy.types.ParticleSettings attribute), 669
viscosity_base (bpy.types.DomainFluidSettings attribute), 359
viscosity_exponent (bpy.types.DomainFluidSettings attribute), 359
viscosity_preset (bpy.types.DomainFluidSettings attribute), 359
visibility (bge.types.KX_VisibilityActuator attribute), 1182
visibility_toggle() (in module bpy.ops.node), 70
visibility_toggle() (in module bpy.ops.outliner), 88
VisibilityActuator (class in bpy.types), 1011
visible (bge.types.KX_GameObject attribute), 1145
visible (bge.types.KX_PolyProxy attribute), 1164
visible (bge.types.SCA_PythonMouse attribute), 1134
visible_bases (in module bpy.context), 5, 7
visible_bones (in module bpy.context), 5
visible_objects (in module bpy.context), 5, 7
visible_pose_bones (in module bpy.context), 6
visual_transform_apply() (in module bpy.ops.object), 87
visual_transform_apply() (in module bpy.ops.pose), 95
VKEY (in module bge.events), 1224
volume (aud.Device attribute), 1123
volume (aud.Handle attribute), 1128
volume (bge.types.KX_SoundActuator attribute), 1176
volume (bpy.types.BoidState attribute), 227
volume (bpy.types.MaintainVolumeConstraint attribute), 517
volume (bpy.types.SoundActuator attribute), 820
volume (bpy.types.SoundSequence attribute), 822
volume (bpy.types.StretchToConstraint attribute), 862
volume_initialization (bpy.types.FluidFluidSettings attribute), 415
volume_initialization (bpy.types.InflowFluidSettings attribute), 465
volume_initialization (bpy.types.ObstacleFluidSettings attribute), 628
volume_initialization (bpy.types.OutflowFluidSettings attribute), 640
volume_maximum (aud.Handle attribute), 1128
volume_minimum (aud.Handle attribute), 1128
VoronoiTexture (class in bpy.types), 1012
VoronoiTexture.users_material (in module bpy.types), 1013
VoronoiTexture.users_object_modifier (in module bpy.types), 1013
vortex (bpy.types.EffectorWeights attribute), 377
vorticity (bpy.types.SmokeDomainSettings attribute), 808
VoxelData (class in bpy.types), 1014
VoxelDataTexture (class in bpy.types), 1015
VoxelDataTexture.image_user (in module bpy.types), 1016
VoxelDataTexture.users_material (in module bpy.types), 1016
VoxelDataTexture.users_object_modifier (in module bpy.types), 1016
VoxelDataTexture.voxel_data (in module bpy.types), 1016

W

w (mathutils.Quaternion attribute), 1064
w (mathutils.Vector attribute), 1068
wander (bpy.types.BoidRuleAverageSpeed attribute), 219

warp() (in module bpy.ops.transform), 124
warp_factor (bpy.types.MaterialTextureSlot attribute), 542
WarpModifier (class in bpy.types), 1017
WarpModifier.falloff_curve (in module bpy.types), 1017
waveform_alpha (bpy.types.Scopes attribute), 760
waveform_mode (bpy.types.Scopes attribute), 760
WaveModifier (class in bpy.types), 1018
weight (bge.types.BL_ArmatureActuator attribute), 1195
weight (bpy.types.ArmatureActuator attribute), 177
weight (bpy.types.BezierSplinePoint attribute), 187
weight (bpy.types.KinematicConstraint attribute), 495
weight (bpy.types.ParticleHairKey attribute), 654
weight (bpy.types.SplinePoint attribute), 855
weight (bpy.types.VertexGroupElement attribute), 1008
weight() (bpy.types.VertexGroup method), 1007
weight_1 (bpy.types.VoronoiTexture attribute), 1013
weight_2 (bpy.types.VoronoiTexture attribute), 1013
weight_3 (bpy.types.VoronoiTexture attribute), 1013
weight_4 (bpy.types.VoronoiTexture attribute), 1013
weight_from_bones() (in module bpy.ops.paint), 90
weight_paint() (in module bpy.ops.paint), 90
weight_paint_object (in module bpy.context), 6
weight_paint_toggle() (in module bpy.ops.paint), 90
weight_sample() (in module bpy.ops.paint), 90
weight_sample_group() (in module bpy.ops.paint), 90
weight_set() (in module bpy.ops.paint), 90
weight_set() (in module bpy.ops.particle), 92
weight_softbody (bpy.types.SplinePoint attribute), 855
weight_tool_set() (in module bpy.ops.brush), 20
weld() (in module bpy.ops.uv), 130
weld_threshold (bpy.types.GameSoftBodySettings attribute), 434
wheel_scroll_lines (bpy.types.UserPreferencesInput attribute), 995
WHEELDOWNMOUSE (in module bge.events), 1223
WHEELUPMOUSE (in module bge.events), 1223
white_level (bpy.types.CurveMapping attribute), 349
width (bpy.types.BevelModifier attribute), 186
width (bpy.types.TextBox attribute), 875
width (bpy.types.WaveModifier attribute), 1020
width_fade (bpy.types.MaterialStrand attribute), 536
wind (bpy.types.EffectorWeights attribute), 377
Window (class in bpy.types), 1021
window_draw_method (bpy.types.UserPreferencesSystem attribute), 999
window_duplicate() (in module bpy.ops.wm), 146
window_fullscreen_toggle() (in module bpy.ops.wm), 146
window_sliders (bpy.types.ThemeAudioWindow attribute), 908
window_sliders (bpy.types.ThemeGraphEditor attribute), 918
window_sliders (bpy.types.ThemeSequenceEditor attribute), 931
WindowManager (class in bpy.types), 1022
WindowManager.keyconfigs (in module bpy.types), 1022
WindowManager.operators (in module bpy.types), 1022
WindowManager.windows (in module bpy.types), 1022
WipeSequence (class in bpy.types), 1024
wire (bpy.types.ThemeNodeEditor attribute), 926
wire (bpy.types.ThemeView3D attribute), 942
wire_select (bpy.types.ThemeNodeEditor attribute), 926
WKEY (in module bge.events), 1224
wood_type (bpy.types.WoodTexture attribute), 1027
WoodTexture (class in bpy.types), 1026
WoodTexture.users_material (in module bpy.types), 1027
WoodTexture.users_object_modifier (in module bpy.types), 1027
world (bpy.types.Scene attribute), 745
World (class in bpy.types), 1028
world (in module bpy.context), 7
World.animation_data (in module bpy.types), 1028
World.light_settings (in module bpy.types), 1029
World.mist_settings (in module bpy.types), 1029
World.star_settings (in module bpy.types), 1029
World.texture_slots (in module bpy.types), 1029
world_to_camera (bge.types.KX_Camera attribute), 1191
worldAngularVelocity (bge.types.KX_GameObject attribute), 1146
WorldLighting (class in bpy.types), 1030
worldLinearVelocity (bge.types.KX_GameObject attribute), 1146
WorldMistSettings (class in bpy.types), 1032
worldOrientation (bge.types.KX_GameObject attribute), 1145
worldPosition (bge.types.KX_GameObject attribute), 1146
worldScale (bge.types.KX_GameObject attribute), 1146
WorldStarsSettings (class in bpy.types), 1034
WorldTextureSlot (class in bpy.types), 1035
WorldTextureSlots (class in bpy.types), 1036
wrap_method (bpy.types.ShrinkwrapModifier attribute), 804
write() (bpy.types.Text method), 874
ww (mathutils.Vector attribute), 1068
www (mathutils.Vector attribute), 1068
wwww (mathutils.Vector attribute), 1068
wwwx (mathutils.Vector attribute), 1068
wwwy (mathutils.Vector attribute), 1068
wwwz (mathutils.Vector attribute), 1068
wwx (mathutils.Vector attribute), 1068
wwxw (mathutils.Vector attribute), 1068
wwxx (mathutils.Vector attribute), 1068
wwxy (mathutils.Vector attribute), 1069
wwxz (mathutils.Vector attribute), 1069
wwy (mathutils.Vector attribute), 1069

`wwyw` (`mathutils.Vector` attribute), 1069
`wwyx` (`mathutils.Vector` attribute), 1069
`wwyy` (`mathutils.Vector` attribute), 1069
`wwyz` (`mathutils.Vector` attribute), 1069
`wwz` (`mathutils.Vector` attribute), 1069
`wwzw` (`mathutils.Vector` attribute), 1069
`wwzx` (`mathutils.Vector` attribute), 1069
`wwzy` (`mathutils.Vector` attribute), 1069
`wwzz` (`mathutils.Vector` attribute), 1069
`wx` (`mathutils.Vector` attribute), 1069
`wxw` (`mathutils.Vector` attribute), 1069
`wxww` (`mathutils.Vector` attribute), 1069
`wxxw` (`mathutils.Vector` attribute), 1069
`wxy` (`mathutils.Vector` attribute), 1069
`wxwz` (`mathutils.Vector` attribute), 1069
`wxx` (`mathutils.Vector` attribute), 1069
`wxxw` (`mathutils.Vector` attribute), 1069
`wxxx` (`mathutils.Vector` attribute), 1069
`wxxy` (`mathutils.Vector` attribute), 1070
`wxxz` (`mathutils.Vector` attribute), 1070
`wxy` (`mathutils.Vector` attribute), 1070
`wxyw` (`mathutils.Vector` attribute), 1070
`wxyx` (`mathutils.Vector` attribute), 1070
`wxyy` (`mathutils.Vector` attribute), 1070
`wxyz` (`mathutils.Vector` attribute), 1070
`wxz` (`mathutils.Vector` attribute), 1070
`wxzw` (`mathutils.Vector` attribute), 1070
`wxzx` (`mathutils.Vector` attribute), 1070
`wxzy` (`mathutils.Vector` attribute), 1070
`wxzz` (`mathutils.Vector` attribute), 1070
`wy` (`mathutils.Vector` attribute), 1070
`wyw` (`mathutils.Vector` attribute), 1070
`wyww` (`mathutils.Vector` attribute), 1070
`wyx` (`mathutils.Vector` attribute), 1070
`wywy` (`mathutils.Vector` attribute), 1070
`wywz` (`mathutils.Vector` attribute), 1070
`wyx` (`mathutils.Vector` attribute), 1070
`wyxw` (`mathutils.Vector` attribute), 1070
`wyxx` (`mathutils.Vector` attribute), 1070
`wyxy` (`mathutils.Vector` attribute), 1071
`wyxz` (`mathutils.Vector` attribute), 1071
`wyy` (`mathutils.Vector` attribute), 1071
`wyyw` (`mathutils.Vector` attribute), 1071
`wyyx` (`mathutils.Vector` attribute), 1071
`wyyy` (`mathutils.Vector` attribute), 1071
`wyyz` (`mathutils.Vector` attribute), 1071
`wyz` (`mathutils.Vector` attribute), 1071
`wyzw` (`mathutils.Vector` attribute), 1071
`wyzx` (`mathutils.Vector` attribute), 1071
`wyzy` (`mathutils.Vector` attribute), 1071
`wyzz` (`mathutils.Vector` attribute), 1071
`wz` (`mathutils.Vector` attribute), 1071
`wzw` (`mathutils.Vector` attribute), 1071
`wzww` (`mathutils.Vector` attribute), 1071

wzwx (mathutils.Vector attribute), 1071
wzwy (mathutils.Vector attribute), 1071
wzwz (mathutils.Vector attribute), 1071
wzx (mathutils.Vector attribute), 1071
wzxw (mathutils.Vector attribute), 1071
wzxx (mathutils.Vector attribute), 1071
wzxy (mathutils.Vector attribute), 1072
wzxz (mathutils.Vector attribute), 1072
wzy (mathutils.Vector attribute), 1072
wzyw (mathutils.Vector attribute), 1072
wzyx (mathutils.Vector attribute), 1072
wzyy (mathutils.Vector attribute), 1072
wzyz (mathutils.Vector attribute), 1072
wzz (mathutils.Vector attribute), 1072
wzzw (mathutils.Vector attribute), 1072
wzxz (mathutils.Vector attribute), 1072
wzzy (mathutils.Vector attribute), 1072
wzzz (mathutils.Vector attribute), 1072

X

x (bge.types.KX_VertexProxy attribute), 1180
x (bpy.types.TextBox attribute), 875
x (mathutils.Euler attribute), 1057
x (mathutils.Quaternion attribute), 1064
x (mathutils.Vector attribute), 1072
x3d() (in module bpy.ops.export_scene), 31
x3d() (in module bpy.ops.import_scene), 48
XKEY (in module bge.events), 1224
XnorController (class in bpy.types), 1037
XorController (class in bpy.types), 1038
xw (mathutils.Vector attribute), 1072
xww (mathutils.Vector attribute), 1072
xwww (mathutils.Vector attribute), 1072
xwx (mathutils.Vector attribute), 1072
xwy (mathutils.Vector attribute), 1072
xwz (mathutils.Vector attribute), 1072
xwxw (mathutils.Vector attribute), 1072
xwxx (mathutils.Vector attribute), 1073
xwxy (mathutils.Vector attribute), 1073
xwxz (mathutils.Vector attribute), 1073
xwy (mathutils.Vector attribute), 1073
xwyw (mathutils.Vector attribute), 1073
xwyx (mathutils.Vector attribute), 1073
xwyy (mathutils.Vector attribute), 1073
xwyz (mathutils.Vector attribute), 1073
xwz (mathutils.Vector attribute), 1073
xwzw (mathutils.Vector attribute), 1073
xwzx (mathutils.Vector attribute), 1073
xwzy (mathutils.Vector attribute), 1073
xwzz (mathutils.Vector attribute), 1073
xx (mathutils.Vector attribute), 1073
xxw (mathutils.Vector attribute), 1073
xxww (mathutils.Vector attribute), 1073

xxwx (mathutils.Vector attribute), 1073
xxwy (mathutils.Vector attribute), 1073
xxwz (mathutils.Vector attribute), 1073
xxx (mathutils.Vector attribute), 1073
xxxw (mathutils.Vector attribute), 1073
xxxx (mathutils.Vector attribute), 1074
xxxxy (mathutils.Vector attribute), 1074
xxxxz (mathutils.Vector attribute), 1074
xxxy (mathutils.Vector attribute), 1074
xxyy (mathutils.Vector attribute), 1074
xxyz (mathutils.Vector attribute), 1074
xxz (mathutils.Vector attribute), 1074
xxzw (mathutils.Vector attribute), 1074
xxzx (mathutils.Vector attribute), 1074
xxzy (mathutils.Vector attribute), 1074
xxzz (mathutils.Vector attribute), 1074
xy (mathutils.Vector attribute), 1074
xyw (mathutils.Vector attribute), 1074
xyww (mathutils.Vector attribute), 1074
xywx (mathutils.Vector attribute), 1074
xywy (mathutils.Vector attribute), 1074
xywz (mathutils.Vector attribute), 1074
xyx (mathutils.Vector attribute), 1074
xyxw (mathutils.Vector attribute), 1074
xyxx (mathutils.Vector attribute), 1075
xyxy (mathutils.Vector attribute), 1075
xyxz (mathutils.Vector attribute), 1075
xyy (mathutils.Vector attribute), 1075
xyyw (mathutils.Vector attribute), 1075
xyyx (mathutils.Vector attribute), 1075
xyyy (mathutils.Vector attribute), 1075
xyyz (mathutils.Vector attribute), 1075
XYZ (bge.types.KX_VertexProxy attribute), 1180
xyz (mathutils.Vector attribute), 1075
xyzw (mathutils.Vector attribute), 1075
xyzx (mathutils.Vector attribute), 1075
xyzy (mathutils.Vector attribute), 1075
xyzz (mathutils.Vector attribute), 1075
xz (mathutils.Vector attribute), 1075
xz_scale_mode (bpy.types.SplineIKConstraint attribute),
854
xzw (mathutils.Vector attribute), 1075
xzww (mathutils.Vector attribute), 1075
xzwx (mathutils.Vector attribute), 1075
xzyw (mathutils.Vector attribute), 1075
xzwz (mathutils.Vector attribute), 1075
xzx (mathutils.Vector attribute), 1075
xzxw (mathutils.Vector attribute), 1075
xzxx (mathutils.Vector attribute), 1076
xzxy (mathutils.Vector attribute), 1076
xzxz (mathutils.Vector attribute), 1076
xzy (mathutils.Vector attribute), 1076

xzyw (mathutils.Vector attribute), 1076
xzyx (mathutils.Vector attribute), 1076
xzyy (mathutils.Vector attribute), 1076
xzyz (mathutils.Vector attribute), 1076
xzz (mathutils.Vector attribute), 1076
xzzw (mathutils.Vector attribute), 1076
xzzx (mathutils.Vector attribute), 1076
xzzy (mathutils.Vector attribute), 1076
xzzz (mathutils.Vector attribute), 1076

Y

y (bge.types.KX_VertexProxy attribute), 1180
y (bpy.types.TextBox attribute), 875
y (mathutils.Euler attribute), 1057
y (mathutils.Quaternion attribute), 1064
y (mathutils.Vector attribute), 1076
yield_ratio (bpy.types.SPHFluidSettings attribute), 742
YKEY (in module bge.events), 1224
yw (mathutils.Vector attribute), 1076
yww (mathutils.Vector attribute), 1076
ywww (mathutils.Vector attribute), 1076
ywwx (mathutils.Vector attribute), 1076
ywwy (mathutils.Vector attribute), 1076
ywwz (mathutils.Vector attribute), 1076
ywx (mathutils.Vector attribute), 1076
ywxw (mathutils.Vector attribute), 1077
ywxx (mathutils.Vector attribute), 1077
ywxy (mathutils.Vector attribute), 1077
ywzx (mathutils.Vector attribute), 1077
wy (mathutils.Vector attribute), 1077
wyw (mathutils.Vector attribute), 1077
wyw (mathutils.Vector attribute), 1077
wyx (mathutils.Vector attribute), 1077
wyyy (mathutils.Vector attribute), 1077
ywyz (mathutils.Vector attribute), 1077
ywz (mathutils.Vector attribute), 1077
ywzw (mathutils.Vector attribute), 1077
ywzx (mathutils.Vector attribute), 1077
ywzy (mathutils.Vector attribute), 1077
ywzz (mathutils.Vector attribute), 1077
yx (mathutils.Vector attribute), 1077
yxw (mathutils.Vector attribute), 1077
yxww (mathutils.Vector attribute), 1077
yxwx (mathutils.Vector attribute), 1077
yxwy (mathutils.Vector attribute), 1077
yxwz (mathutils.Vector attribute), 1077
yxx (mathutils.Vector attribute), 1077
yxxw (mathutils.Vector attribute), 1078
xxxx (mathutils.Vector attribute), 1078
yxxx (mathutils.Vector attribute), 1078
yxxz (mathutils.Vector attribute), 1078
xy (mathutils.Vector attribute), 1078
xyw (mathutils.Vector attribute), 1078
xyx (mathutils.Vector attribute), 1078
xyy (mathutils.Vector attribute), 1078

yxyz (mathutils.Vector attribute), 1078
yxz (mathutils.Vector attribute), 1078
yxzw (mathutils.Vector attribute), 1078
yxzx (mathutils.Vector attribute), 1078
yxzy (mathutils.Vector attribute), 1078
yxzz (mathutils.Vector attribute), 1078
yy (mathutils.Vector attribute), 1078
yyw (mathutils.Vector attribute), 1078
yyww (mathutils.Vector attribute), 1078
yywx (mathutils.Vector attribute), 1078
yywy (mathutils.Vector attribute), 1078
yywz (mathutils.Vector attribute), 1078
yyx (mathutils.Vector attribute), 1078
yyxw (mathutils.Vector attribute), 1079
yyxx (mathutils.Vector attribute), 1079
yyxy (mathutils.Vector attribute), 1079
yyxz (mathutils.Vector attribute), 1079
yyy (mathutils.Vector attribute), 1079
yyyw (mathutils.Vector attribute), 1079
yyyy (mathutils.Vector attribute), 1079
yyyyz (mathutils.Vector attribute), 1079
yyz (mathutils.Vector attribute), 1079
yyzw (mathutils.Vector attribute), 1079
yyzx (mathutils.Vector attribute), 1079
yyzy (mathutils.Vector attribute), 1079
yyzz (mathutils.Vector attribute), 1079
yz (mathutils.Vector attribute), 1079
yzw (mathutils.Vector attribute), 1079
yzww (mathutils.Vector attribute), 1079
yzwx (mathutils.Vector attribute), 1079
yzwy (mathutils.Vector attribute), 1079
yzwz (mathutils.Vector attribute), 1079
yzx (mathutils.Vector attribute), 1079
yzxw (mathutils.Vector attribute), 1080
yzxx (mathutils.Vector attribute), 1080
yzxy (mathutils.Vector attribute), 1080
yzxz (mathutils.Vector attribute), 1080
yzy (mathutils.Vector attribute), 1080
yzyw (mathutils.Vector attribute), 1080
yzyx (mathutils.Vector attribute), 1080
yzyy (mathutils.Vector attribute), 1080
yzyz (mathutils.Vector attribute), 1080
yzz (mathutils.Vector attribute), 1080
yzzw (mathutils.Vector attribute), 1080
yzzx (mathutils.Vector attribute), 1080
yzyz (mathutils.Vector attribute), 1080
yzzz (mathutils.Vector attribute), 1080

Z

z (bge.types.KX_VertexProxy attribute), 1180
z (mathutils.Euler attribute), 1057
z (mathutils.Quaternion attribute), 1064
z (mathutils.Vector attribute), 1080

z_direction (bpy.types.FieldSettings attribute), 408
z_scale (bpy.types.CompositorNodeDefocus attribute), 288
zenith_color (bpy.types.World attribute), 1029
zenith_down_factor (bpy.types.WorldTextureSlot attribute), 1035
zenith_up_factor (bpy.types.WorldTextureSlot attribute), 1035
zero() (mathutils.Euler method), 1057
zero() (mathutils.Matrix method), 1061
zero() (mathutils.Vector method), 1068
ZEROKEY (in module bge.events), 1224
ZKEY (in module bge.events), 1224
zoom (bpy.types.CompositorNodeDBlur attribute), 286
zoom (bpy.types.EnvironmentMap attribute), 381
zoom (bpy.types.SpaceSequenceEditor attribute), 839
zoom() (in module bpy.ops.view2d), 131
zoom() (in module bpy.ops.view3d), 135
zoom_border() (in module bpy.ops.view2d), 131
zoom_border() (in module bpy.ops.view3d), 135
zoom_camera_1_to_1() (in module bpy.ops.view3d), 136
zoom_in() (in module bpy.ops.view2d), 131
zoom_out() (in module bpy.ops.view2d), 131
zsort (bge.types.KX_PolygonMaterial attribute), 1168
zw (mathutils.Vector attribute), 1080
zww (mathutils.Vector attribute), 1080
zwww (mathutils.Vector attribute), 1080
zwwx (mathutils.Vector attribute), 1080
zwwy (mathutils.Vector attribute), 1080
zwwz (mathutils.Vector attribute), 1080
zwx (mathutils.Vector attribute), 1081
zwxw (mathutils.Vector attribute), 1081
zwxx (mathutils.Vector attribute), 1081
zwxy (mathutils.Vector attribute), 1081
zwxz (mathutils.Vector attribute), 1081
zwy (mathutils.Vector attribute), 1081
zwyw (mathutils.Vector attribute), 1081
zwyx (mathutils.Vector attribute), 1081
zwyy (mathutils.Vector attribute), 1081
zwyz (mathutils.Vector attribute), 1081
zwz (mathutils.Vector attribute), 1081
zwzw (mathutils.Vector attribute), 1081
zwzx (mathutils.Vector attribute), 1081
zwzy (mathutils.Vector attribute), 1081
zwzz (mathutils.Vector attribute), 1081
zx (mathutils.Vector attribute), 1081
zxw (mathutils.Vector attribute), 1081
zxww (mathutils.Vector attribute), 1081
zxwx (mathutils.Vector attribute), 1081
zxwy (mathutils.Vector attribute), 1081
zxwz (mathutils.Vector attribute), 1081
xxx (mathutils.Vector attribute), 1082
xxxw (mathutils.Vector attribute), 1082
xxxx (mathutils.Vector attribute), 1082

zxx (mathutils.Vector attribute), 1082
zxxz (mathutils.Vector attribute), 1082
zxy (mathutils.Vector attribute), 1082
zxyw (mathutils.Vector attribute), 1082
zxyx (mathutils.Vector attribute), 1082
zxyy (mathutils.Vector attribute), 1082
zxyz (mathutils.Vector attribute), 1082
zxz (mathutils.Vector attribute), 1082
zxzw (mathutils.Vector attribute), 1082
zxzx (mathutils.Vector attribute), 1082
zxzy (mathutils.Vector attribute), 1082
zxzz (mathutils.Vector attribute), 1082
zy (mathutils.Vector attribute), 1082
zyw (mathutils.Vector attribute), 1082
zyww (mathutils.Vector attribute), 1082
zywx (mathutils.Vector attribute), 1082
zywy (mathutils.Vector attribute), 1082
zywz (mathutils.Vector attribute), 1082
zyx (mathutils.Vector attribute), 1083
zyxw (mathutils.Vector attribute), 1083
zyxx (mathutils.Vector attribute), 1083
zyxy (mathutils.Vector attribute), 1083
zyxz (mathutils.Vector attribute), 1083
zyy (mathutils.Vector attribute), 1083
zyyw (mathutils.Vector attribute), 1083
zyyx (mathutils.Vector attribute), 1083
zyyy (mathutils.Vector attribute), 1083
zyyz (mathutils.Vector attribute), 1083
zyz (mathutils.Vector attribute), 1083
zyzw (mathutils.Vector attribute), 1083
zyzx (mathutils.Vector attribute), 1083
zyzy (mathutils.Vector attribute), 1083
zyzz (mathutils.Vector attribute), 1083
zz (mathutils.Vector attribute), 1083
zzw (mathutils.Vector attribute), 1083
zzww (mathutils.Vector attribute), 1083
zzwx (mathutils.Vector attribute), 1083
zzwy (mathutils.Vector attribute), 1083
zzwz (mathutils.Vector attribute), 1083
zzx (mathutils.Vector attribute), 1084
zzxw (mathutils.Vector attribute), 1084
zzxx (mathutils.Vector attribute), 1084
zzxy (mathutils.Vector attribute), 1084
zzxz (mathutils.Vector attribute), 1084
zzy (mathutils.Vector attribute), 1084
zzyw (mathutils.Vector attribute), 1084
zzyx (mathutils.Vector attribute), 1084
zzyy (mathutils.Vector attribute), 1084
zzyz (mathutils.Vector attribute), 1084
zzz (mathutils.Vector attribute), 1084
zzzw (mathutils.Vector attribute), 1084
zzzx (mathutils.Vector attribute), 1084
zzzy (mathutils.Vector attribute), 1084
zzzz (mathutils.Vector attribute), 1084